

Vesync (US) Corporation

TEST REPORT

SCOPE OF WORK

FCC TESTING—LPF-R382S-AUS, LPF-R382S-WCA, LPF-R382S-KUS, LPF-R382S-WUS, LPF-R382S-KCA, LPF-R382S-ACA, LPF-R382S—may be followed by up to four characters.

REPORT NUMBER

260203018SZN-003

ISSUE DATE

[REVISED DATE]

05 March 2026[-----]

PAGES

42

DOCUMENT CONTROL NUMBER

FCC ID 247_b

© 2017 INTERTEK



Intertek Report No.: 260203018SZN-003

Vesync (US) CorporationApplication
For
Certification**FCC ID: 2AB22-LPFR382S****CoreBreeze Smart Pedestal Fan****Model: LPF-R382S-AUS,
LPF-R382S-WCA, LPF-R382S-KUS, LPF-R382S-WUS, LPF-R382S-KCA, LPF-R382S-
ACA, LPF-R382S-may be followed by up to four characters.
2.4GHz Wi-Fi Transceiver**

Report No.: 260203018SZN-003

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-24]

Prepared and Checked by:**Approved by:****Tenet Cao
Assistant Engineer**

**Johnny Wang
Project Engineer
Date: 05 March 2026**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China.

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

MEASUREMENT/TECHNICAL REPORT

This report concerns (check one) Original Grant ☒ Class II Change ☐

Equipment Type: DTS - Part 15 Digital Transmission Systems (Wi-Fi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-24] Edition] provision.

Report prepared by:

Tenet Cao

Intertek Testing Services Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue,
Zhangkengjing Community, GuanHu Subdistrict, LongHua
District, Shenzhen, P.R. China.

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6661

Table of Contents

1.0	<u>Summary of Test Results</u>	4
2.0	<u>General Description</u>	5
2.1	Product Description	5
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	6
3.0	<u>System Test Configuration</u>	7
3.1	Justification	7
3.2	EUT Exercising Software	7
3.3	Special Accessories	7
3.4	Measurement Uncertainty	8
3.5	Equipment Modification	8
3.6	Support Equipment List and Description	8
4.0	<u>Measurement Results</u>	9
4.1	Maximum Conducted Output Power at Antenna Terminals	9
4.2	Minimum 6 dB RF Bandwidth	11
4.3	Maximum Power Density Reading	12
4.4	Out of Band Conducted Emissions	13
4.5	Out of Band Radiated Emissions	14
4.6	Transmitter Radiated Emissions in Restricted Bands	15
4.7	Field Strength Calculation	16
4.8	Radiated Spurious Emission	17
4.9	Conducted Emission	34
4.10	Radiated Emissions from Digital Section of Transceiver	39
4.11	Transmitter Duty Cycle Calculation and Measurements	40
5.0	<u>Equipment Photographs</u>	41
6.0	<u>Product Labelling</u>	41
7.0	<u>Technical Specifications</u>	41
8.0	<u>Instruction Manual</u>	41
9.0	<u>Confidentiality Request</u>	41
10.0	<u>Discussion of Pulse Desensitization</u>	41
11.0	<u>Test Equipment List</u>	42

1.0 Summary of Test Results

Applicant: Vesync (US) Corporation

Applicant Address: 1775 FLIGHT WAY, SUITE 150 TUSTIN, CA 92782,USA

Manufacturer: Vesync (US) Corporation

Manufacturer Address: 1775 FLIGHT WAY, SUITE 150 TUSTIN, CA 92782,USA

Model: LPF-R382S-AUS

FCC ID: 2AB22-LPFR382S

TEST ITEM	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is a Evaporative Humidifier, LPF-R382S-AUS with Wi-Fi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing and 2422-2452MHz for 802.11n-HT40, 7 channels with 5MHz channel spacing. The EUT is powered by Adapter with AC100-240V. For more detailed features description, please refer to the user's manual.

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM for OFDM; CCK, DQPSK, DBPSK for DSSS.

Antenna Type: Integral antenna

Antenna Gain: 1.2dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

Sample ID: Z260203018-001

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

The Model: LPF-R382S-WCA, LPF-R382S-KUS, LPF-R382S-WUS, LPF-R382S-KCA, LPF-R382S-ACA, LPF-R382S-may be followed by up to four characters. are the same as the Model: LPF-R382S-AUS in hardware aspect. The difference in model number serves as marketing strategy.

This Tower Fan is equipped with two motors. The Model one is from Green-Intelligence Electrical Equipment Co.,Ltd. The Model two is from Guangdong Huilipu Intelligent Technology Co.,Ltd. After evaluating both combinations, the motors were tested. Only the worst data was reflected in the report.

This Tower Fan is equipped with two remote controls. The Model one is from Shenzhen jiechuang shinco electronics Co., Ltd. The Model two is from ShenZhen C&D Electronics CO.Ltd. After evaluating both combinations, the remote controls were tested. Only the worst data was reflected in the report.

2.2 Related Submittal(s) Grants

This is an application for certification of transceiver for the Evaporative Humidifier which has WIFI function. Other digital functions were reported in the verification report: 251211005SZN-002.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2020) and KDB 558074 D01 v05r02. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

2.4 Test Facility

The Semi-anechoic chamber and shielded room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by AC120V during the test.

On 802.11b/g/n-HT20/ n-HT40 mode, only one antenna is used, and all data rate were tested and only the worst case data is shown in the report.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.1m. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

The EUT and transmitting antenna was centered on the turntable.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

Test software: EspRFTTestTool_v3.6

3.3 Special Accessories

N/A.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Measurement Uncertainty	Uncertainty
Conducted Emission Test	$\pm 2.80\text{dB}$
RF power, conducted, PSD	$\pm 0.16\text{dB}$
Spurious emissions, conducted	$\pm 0.21\text{dB}$
All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
All emissions, radiated(>6GHz)	$\pm 2.52\text{dB}$
Temperature	$\pm 0.5^{\circ}\text{C}$
All emissions, radiated(9KHz~30MHz)	$\pm 6\text{dB}$
Occupied bandwidth	$\pm 4.7\text{dB}$

3.5 Equipment Modification

Any modifications installed previous to testing by Vesync (US) Corporation will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

3.6 Support Equipment List and Description

Description	Manufacturer	Model No.
Laptop (Provided by Intertek)	DELL	Latitude 3480
AC ADAPTER (Provided by applicant)	KEERDA	Model: DZ024EHL240100U Input:100-240V~ 50/60Hz 0.8A Max Output: 24V=1A, 24.0W

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter has a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (Antenna Gain = 1.2dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	19.1	81.28
Middle Channel: 2437	19.2	83.18
High Channel: 2462	18.8	75.86

IEEE 802.11g (Antenna Gain = 1.2dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	23.0	199.53
Middle Channel: 2437	23.1	204.17
High Channel: 2462	22.9	194.98

IEEE 802.11n-HT20 (Antenna Gain = 1.2dBi) (64QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	21.6	144.54
Middle Channel: 2437	21.5	141.25
High Channel: 2462	21.3	134.90

IEEE 802.11n-HT40 (Antenna Gain = 1.2dBi) (64QAM, 13.5Mbps)		
Frequency (MHz)	Output in dBm (Average Reading)	Output in mWatt
Low Channel: 2422	21.1	128.82
Middle Channel: 2437	21.0	125.89
High Channel: 2452	21.0	125.89

Cable loss: 0.5 dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 23.1dBm

EUT max. E.I.R.P = 23.1dBm + 1.2dBi = 24.3dBm = 269.15mW

For RF Exposure, the information is saved with filename: RF exposure.pdf.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v05r02. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

Test Result: Please refer the Appendix of 260203018SZN-003 Appendix A.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v05r02.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/3 kHz.

Test Result: Please refer the Appendix of 260203018SZN-003 Appendix D.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v05r02.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b and 6Mbps for 802.11g and 6Mbps for 802.11n-HT20 and 13.5Mbps for 802.11n-HT40.

The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

The test plots are attached as below.

Test Result: Please refer the Appendix of 260203018SZN-003 Appendix E and Appendix F.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

☒ Not required, since all emissions are more than 20dB below fundamental

☐ See attached data sheet

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b) (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB/m
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB/m and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB/m}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission
at 4874.000MHz
is passed by 3.1dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026


Worst Case Operating Mode:

Model: LPF-R382S-AUS(Model one motor)

2.4G WIFI Link

ANT Polarity: Horizontal

FCC Part 15



Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
56.545667	22.3	1000.0	120.000	H	13.2	17.7	40.0
257.723667	24.1	1000.0	120.000	H	19.7	21.9	46.0
638.157667	35.4	1000.0	120.000	H	29.5	10.6	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026


Worst Case Operating Mode:

Model: LPF-R382S-AUS(Model one motor)

2.4G WIFI Link

ANT Polarity: Vertical

FCC Part 15



Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
54.347000	19.6	1000.0	120.000	V	13.1	20.4	40.0
96.186333	23.0	1000.0	120.000	V	14.3	20.5	43.5
144.266000	21.1	1000.0	120.000	V	15.5	22.4	43.5

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026


Worst Case Operating Mode:

Model: LPF-R382S-AUS(Model two motor)

2.4G WIFI Link

ANT Polarity: Horizontal

FCC Part 15



Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
257.691333	21.0	1000.0	120.000	H	20.0	25.0	46.0
371.828000	24.1	1000.0	120.000	H	23.0	21.9	46.0
662.698667	33.6	1000.0	120.000	H	30.0	12.4	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026


Worst Case Operating Mode:

Model: LPF-R382S-AUS(Model two motor)

2.4G WIFI Link

ANT Polarity: Vertical

FCC Part 15



Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
96.154000	22.7	1000.0	120.000	V	14.0	20.8	43.5
184.262333	19.0	1000.0	120.000	V	17.0	24.5	43.5
697.036667	32.3	1000.0	120.000	V	32.0	13.7	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Worst Case Operating Mode:

Model: LPF-R382S-AUS

Transmitting (802.11b-Channel 01)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2390.000	66.5	33.1	27.4	60.8	74.0	-13.2
Horizontal	*4824.000	54.1	30.6	32.7	56.2	74.0	-17.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2390.000	54.5	33.1	27.4	48.8	54.0	-5.2
Horizontal	*4824.000	43.4	30.6	32.7	45.5	54.0	-8.5

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Worst Case Operating Mode:

Model: LPF-R382S-AUS

Transmitting (802.11b-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	64.3	33.1	27.8	59.0	74.0	-15.0
Horizontal	*7311.000	56.1	30.5	32.9	58.5	74.0	-15.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	53.0	33.1	27.8	47.7	54.0	-6.3
Horizontal	*7311.000	42.4	30.5	32.9	44.8	54.0	-9.2

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Worst Case Operating Mode:

Model: LPF-R382S-AUS

Transmitting (802.11b-Channel 11)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2483.500	65.1	33.1	27.8	59.8	74.0	-14.2
Horizontal	*4924.000	65.3	36.5	29.3	58.1	74.0	-15.9
Horizontal	*7386.000	47.7	30.9	37.3	54.1	74.0	-19.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2483.500	53.2	33.1	27.8	47.9	54.0	-6.1
Horizontal	*4924.000	54.4	36.5	29.3	47.2	54.0	-6.8
Horizontal	*7386.000	35.0	30.9	37.3	41.4	54.0	-12.6

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Worst Case Operating Mode:

Model: LPF-R382S-AUS

Transmitting (802.11g-Channel 01)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2390.000	67.4	33.1	27.4	61.7	74.0	-12.3
Horizontal	*4824.000	50.5	30.6	32.7	52.6	74.0	-21.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2390.000	55.4	33.1	27.4	49.7	54.0	-4.3
Horizontal	*4824.000	41.8	30.6	32.7	43.9	54.0	-10.1

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Worst Case Operating Mode:

Model: LPF-R382S-AUS

Transmitting (802.11g-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	62.3	33.1	27.8	57.0	74.0	-17.0
Horizontal	*7311.000	51.9	30.5	32.9	54.3	74.0	-19.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	48.6	33.1	27.8	43.3	54.0	-10.7
Horizontal	*7311.000	39.2	30.5	32.9	41.6	54.0	-12.4

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Worst Case Operating Mode:

Model: LPF-R382S-AUS

Transmitting (802.11g-Channel 11)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2483.500	70.7	33.1	27.8	65.4	74.0	-8.6
Horizontal	*4924.000	61.9	36.5	29.3	54.7	74.0	-19.3
Horizontal	*7386.000	47.5	30.9	37.3	53.9	74.0	-20.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2483.500	55.0	33.1	27.8	49.7	54.0	-4.3
Horizontal	*4924.000	52.1	36.5	29.3	44.9	54.0	-9.1
Horizontal	*7386.000	34.8	30.9	37.3	41.2	54.0	-12.8

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Worst Case Operating Mode:

Model: LPF-R382S-AUS

Transmitting (802.11n20-Channel 01)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2390.000	67.3	33.1	27.4	61.6	74.0	-12.4
Horizontal	*4824.000	47.3	30.6	32.7	49.4	74.0	-24.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2390.000	54.9	33.1	27.4	49.2	54.0	-4.8
Horizontal	*4824.000	39.6	30.6	32.7	41.7	54.0	-12.3

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Worst Case Operating Mode:

Model: LPF-R382S-AUS

Transmitting (802.11n20-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	54.5	33.1	27.8	49.2	74.0	-24.8
Horizontal	*7311.000	52.2	30.5	32.9	54.6	74.0	-19.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	48.8	33.1	27.8	43.5	54.0	-10.5
Horizontal	*7311.000	39.1	30.5	32.9	41.5	54.0	-12.5

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Worst Case Operating Mode:

Model: LPF-R382S-AUS

Transmitting (802.11n20-Channel 11)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2483.500	69.5	33.1	27.8	64.2	74.0	-9.8
Horizontal	*4924.000	56.5	36.5	29.3	49.3	74.0	-24.7
Horizontal	*7386.000	48.3	30.9	37.3	54.7	74.0	-19.3

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2483.500	54.7	33.1	27.8	49.4	54.0	-4.6
Horizontal	*4924.000	50.1	36.5	29.3	42.9	54.0	-11.1
Horizontal	*7386.000	35.3	30.9	37.3	41.7	54.0	-12.3

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Worst Case Operating Mode:

Model: LPF-R382S-AUS

Transmitting (802.11n40-Channel 03)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2390.000	67.0	33.1	27.8	61.7	74.0	-12.3
Horizontal	*4844.000	59.7	36.5	29.3	52.5	74.0	-21.5
Horizontal	*7266.000	46.9	30.9	37.3	53.3	74.0	-20.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2390.000	55.3	33.1	27.8	50.0	54.0	-4.0
Horizontal	*4844.000	47.3	36.5	29.3	40.1	54.0	-13.9
Horizontal	*7266.000	34.5	30.9	37.3	40.9	54.0	-13.1

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.

Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

Worst Case Operating Mode:

Transmitting (802.11n40-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	67.2	33.1	27.8	61.9	74.0	-12.1
Horizontal	*7311.000	52.2	30.5	32.9	54.6	74.0	-19.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	56.2	33.1	27.8	50.9	54.0	-3.1
Horizontal	*7311.000	38.7	30.5	32.9	41.1	54.0	-12.9

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.

Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

Worst Case Operating Mode:

Transmitting (802.11n40-Channel 09)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2483.500	63.9	33.1	27.8	58.6	74.0	-15.4
Horizontal	*4904.000	61.5	36.5	29.3	54.3	74.0	-19.7
Horizontal	*7386.000	50.4	30.9	37.3	56.8	74.0	-17.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2483.500	52.5	33.1	27.8	47.2	54.0	-6.8
Horizontal	*4904.000	48.6	36.5	29.3	41.4	54.0	-12.6
Horizontal	*7386.000	37.5	30.9	37.3	43.9	54.0	-10.1

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.

Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

4.9 Conducted Emission

Worst Case Conducted Emission
at 0.170000MHz
is passed by 11.5dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: conducted photos.pdf.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026


Model: LPF-R382S-AUS

Worst Case Operating Mode: WIFI Link(Model one motor)

Phase: Live

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.170000	53.5	9.000	L1	9.6	11.5	65.0
0.178000	52.4	9.000	L1	9.6	12.2	64.6
0.222000	47.9	9.000	L1	9.6	14.8	62.7
0.278000	46.4	9.000	L1	9.6	14.5	60.9
0.290000	44.5	9.000	L1	9.6	16.0	60.5
0.390000	40.0	9.000	L1	9.6	18.1	58.1

Limit and Margin AV

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.170000	39.0	9.000	L1	9.6	16.0	55.0
0.178000	38.4	9.000	L1	9.6	16.2	54.6
0.222000	31.5	9.000	L1	9.6	21.2	52.7
0.278000	32.3	9.000	L1	9.6	18.6	50.9
0.290000	31.3	9.000	L1	9.6	19.2	50.5
0.390000	26.7	9.000	L1	9.6	21.4	48.1

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Limit (dBμV) – Level (dBμV)

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026


Model: LPF-R382S-AUS

Worst Case Operating Mode: WIFI Link(Model one motor)

Phase: Neutral

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.166000	49.3	9.000	N	9.8	15.9	65.2
0.178000	48.8	9.000	N	9.8	15.8	64.6
0.234000	43.8	9.000	N	9.8	18.5	62.3
0.286000	40.6	9.000	N	9.7	20.0	60.6
0.338000	37.2	9.000	N	9.6	22.1	59.3
0.398000	34.2	9.000	N	9.6	23.7	57.9

Limit and Margin AV

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.166000	33.1	9.000	N	9.8	22.1	55.2
0.178000	34.0	9.000	N	9.8	20.6	54.6
0.234000	27.3	9.000	N	9.8	25.0	52.3
0.286000	28.4	9.000	N	9.7	22.2	50.6
0.338000	24.6	9.000	N	9.6	24.7	49.3
0.398000	24.1	9.000	N	9.6	23.8	47.9

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)

2. Margin (dB) = Limit (dBμV) – Level (dBμV)

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026


Model: LPF-R382S-AUS

Worst Case Operating Mode: WIFI Link(Model two motor)

Phase: Live

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.174000	41.8	9.000	L1	9.6	23.0	64.8
0.274000	39.3	9.000	L1	9.6	21.7	61.0
0.382000	38.5	9.000	L1	9.6	19.7	58.2
0.470000	38.5	9.000	L1	9.6	18.0	56.5
0.554000	34.6	9.000	L1	9.6	21.4	56.0
0.718000	33.5	9.000	L1	9.5	22.5	56.0

Limit and Margin AV

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.174000	38.7	9.000	L1	9.6	16.1	54.8
0.274000	37.2	9.000	L1	9.6	13.8	51.0
0.382000	27.4	9.000	L1	9.6	20.8	48.2
0.470000	28.5	9.000	L1	9.6	18.0	46.5
0.554000	24.5	9.000	L1	9.6	21.5	46.0
0.718000	22.1	9.000	L1	9.5	23.9	46.0

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Limit (dBμV) – Level (dBμV)

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026


Model: LPF-R382S-AUS

Worst Case Operating Mode: WIFI Link(Model two motor)

Phase: Neutral

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.162000	46.2	9.000	N	9.8	19.2	65.4
0.218000	44.3	9.000	N	9.8	18.6	62.9
0.274000	44.1	9.000	N	9.7	16.9	61.0
0.390000	36.4	9.000	N	9.6	21.7	58.1
0.446000	35.2	9.000	N	9.6	21.7	56.9
0.546000	35.1	9.000	N	9.5	20.9	56.0

Limit and Margin AV

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.162000	32.2	9.000	N	9.8	23.2	55.4
0.218000	31.5	9.000	N	9.8	21.4	52.9
0.274000	33.4	9.000	N	9.7	17.6	51.0
0.390000	23.0	9.000	N	9.6	25.1	48.1
0.446000	24.5	9.000	N	9.6	22.4	46.9
0.546000	23.4	9.000	N	9.5	22.6	46.0

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Limit (dBμV) – Level (dBμV)

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

- ☐ Not required - No digital part
- ☐ Test results are attached
- ☒ Included in the separated report.

Applicant: Vesync (US) Corporation

Date of Test: 03 February 2026

Model: LPF-R382S-AUS

4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	2025-04-21	2026-04-21
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	2025-04-21	2026-04-21
SZ061-13	BiConiLog Antenna	ETS	3142E	00217919	2025-05-29	2028-05-29
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2024-05-05	2027-05-05
SZ185-03	EMI Receiver	R&S	ESR7	101975	2025-04-13	2026-04-13
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	2025-09-11	2028-09-11
SZ061-08	Double - Ridged Waveguide Horn Antenna	ETS	3115	00092346	2024-09-13	2027-09-13
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	2025-12-01	2026-12-01
SZ181-08	Microwave System Amplifier	keysight	83017A	MY57280108	2025-07-20	2026-07-30
SZ188-05	Anechoic Chamber	ETS	FACT 3-2.0	CT001880-Q13914102	2025-06-18	2028-06-18
SZ062-02	RF Cable	RADIAL	RG 213U	--	2025-04-30	2026-04-30
SZ062-05	RF Cable	RADIAL	0.04-26.5GHz	0833254	2025-04-30	2026-04-30
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	083387	2025-04-30	2026-04-30
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	2025-06-30	2026-06-30
SZ187-01	Two-Line V-Network	R&S	ENV216	100073	2025-10-27	2026-10-27
SZ188-03	Shielding Room	ETS	RFD-100	4100	2022-12-20	2027-12-20
SZ062-16	RF Cable	HUBER+SUHNER	CBL2-BN-1m	110127-2231000	2025-06-30	2026-06-30

***** End of Report*****