

Test Report

Report No. : MTi251216001-1101E1
Date of issue : 2026-01-30
Applicant : LEEDARSON LIGHTING CO., LTD.
Product : LED lamp
Model(s) : 15aSA-A1600ST-Q1QM-01,
15aSy-A1600ST-Q1QM-xx, 15A21100D6CCTxx,
14A21100D6CCTxx
FCC ID : 2AB2Q-15A1600STQ1QM

Shenzhen Microtest Co., Ltd.

TEST REPORT



Report No.: MTi251216001-1101E1

Table of contents

1	General Description	4
1.1	Description of the EUT	4
1.2	Description of test modes	4
1.3	Environmental Conditions	6
1.4	Description of support units	6
1.5	Measurement uncertainty	6
2	Summary of Test Result	7
3	Test Facilities and accreditations	8
3.1	Test laboratory	8
4	List of test equipment	9
5	Evaluation Results (Evaluation)	11
5.1	Antenna requirement	11
6	Radio Spectrum Matter Test Results (RF)	11
6.1	Conducted Emission at AC power line	11
6.2	Occupied Bandwidth	14
6.3	Field strength of fundamental	18
6.4	Band edge emissions (Radiated)	22
6.5	Emissions in frequency bands (below 1GHz)	26
6.6	Emissions in frequency bands (above 1GHz)	30
	Photographs of the test setup	35
	Photographs of the EUT	36

TEST REPORT

Report No.: MTi251216001-1101E1

Test Result Certification		
Applicant	LEEDARSON LIGHTING CO., LTD.	
Applicant Address	Xingda Road, Xingtai Industrial Zone, Changtai County, Zhangzhou, Fujian, China	
Manufacturer	LEEDARSON LIGHTING CO., LTD.	
Manufacturer Address	Xingda Road, Xingtai Industrial Zone, Changtai County, Zhangzhou, Fujian, China	
Product description		
Product name	LED lamp	
Trademark	N/A	
Model name	15aSA-A1600ST-Q1QM-01	
Series Model(s)	15aSy-A1600ST-Q1QM-xx, 15A21100D6CCTxx, 14A21100D6CCTxx	
Model difference:	All the models are the same circuit and module, except the model name, color, appearance and package(Where "y" may be "A" to "Z", which designates there is a difference in the surface striations at the junction between the metal lamp cap and the plastic part; "xx" may be "00" to "99", which designates for different beam angle, color of eyelet contact, different package of style.).	
Standards	47 CFR Part 15.249	
Test Method	ANSI C63.10-2020+COR 1-2023	
Testing Information		
Date of test	2025-12-25 to 2026-01-28	
Test result	Pass	
Prepared by:	James Qin	
Reviewed by:	David Lee	
Approved by:	Lewis Lian	

TEST REPORT

Report No.: MTi251216001-1101E1

1 General Description

1.1 Description of the EUT

Product name:	LED lamp
Model name:	15aSA-A1600ST-Q1QM-01
Series Model(s):	15aSy-A1600ST-Q1QM-xx, 15A21100D6CCTxx, 14A21100D6CCTxx
Model difference:	All the models are the same circuit and module, except the model name, color, appearance and package(Where "y" may be "A" to "Z", which designates there is a difference in the surface striations at the junction between the metal lamp cap and the plastic part; "xx" may be "00" to "99", which designates for different beam angle, color of eyelet contact, different package of style.).
Electrical rating:	Input: AC 120V/ 60Hz
Accessories:	N/A
Hardware version:	EDC18H-VA
Software version:	0xA49C
Test sample(s) number:	MTi251216001-11-R001 (TX Freq.: 5730MHz, for Radiated and AC Conducted test) MTi251216001-11-R002 (TX Freq.: 5775MHz, for Radiated and AC Conducted test) MTi251216001-11-R003 (TX Freq.: 5820MHz, for Radiated and AC Conducted test) MTi251216001-11-R004 (TX Freq.: 5730MHz, for RF Conducted test) MTi251216001-11-R005 (TX Freq.: 5775MHz, for RF Conducted test) MTi251216001-11-R006 (TX Freq.: 5820MHz, for RF Conducted test)
RF specification	
Operating frequency range:	5730-5820MHz
Channel number:	91
Modulation type:	FSK
Antenna(s) type:	Built-in microstrip patch antenna
Antenna(s) gain:	3.0dBi

1.2 Description of test modes

No.	Emission test modes
Mode1	TX

TEST REPORT

Report No.: MTi251216001-1101E1

1.2.1 Operation channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5730	2	5731	3	5732
...	...	...	...	...	...
45	5774	46	5775	47	5776
...	...	...	...	...	...
91	5820	/			
Note: Channel separation is 1MHz					

Test Channel List

Operation Band: 5730 MHz to 5820 MHz

Lowest Channel (LCH) (MHz)	Middle Channel (MCH) (MHz)	Highest Channel (HCH) (MHz)
5730	5775	5820

Test Software:

For power setting, refer to below table.

Test Software		N/A	
Mode	5730MHz	5775MHz	5820MHz
TX	DEF	DEF	DEF

There is no test software. The test software has been burned, and high, medium and low channels samples have been provided.

TEST REPORT

Report No.: MTi251216001-1101E1

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

1.4 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list

Description	Model	Serial No.	Manufacturer
/	/	/	/

Support cable list

Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Measurement	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	±3.1dB
Occupied channel bandwidth	±3 %
Radiated spurious emissions (above 1GHz)	±5.3dB
Radiated spurious emissions (9kHz~30MHz)	±4.3dB
Radiated spurious emissions (30MHz~1GHz)	±4.7dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

TEST REPORT

Report No.: MTi251216001-1101E1

2 Summary of Test Result

No.	Item	Standard	Requirement	Result
1	Antenna requirement	47 CFR Part 15.249	47 CFR Part 15.203	Pass
2	Conducted Emission at AC power line	47 CFR Part 15.249	47 CFR 15.207(a)	Pass
3	Occupied Bandwidth	47 CFR Part 15.249	47 CFR 15.215(c)	Pass
4	Field strength of fundamental	47 CFR Part 15.249	47 CFR 15.249(a) 47 CFR 15.249(b)(1)	Pass
5	Band edge emissions (Radiated)	47 CFR Part 15.249	47 CFR 15.249(d)	Pass
6	Emissions in frequency bands (below 1GHz)	47 CFR Part 15.249	47 CFR 15.249(a) 47 CFR 15.249(d) 47 CFR 15.249(e)	Pass
7	Emissions in frequency bands (above 1GHz)	47 CFR Part 15.249	47 CFR 15.249(a) 47 CFR 15.249(d) 47 CFR 15.249(e)	Pass

TEST REPORT

Report No.: MTi251216001-1101E1

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

TEST REPORT

Report No.: MTi251216001-1101E1

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
Conducted Emission at AC power line						
1	EMI Test Receiver	Rohde&schwarz	ESCI3	101368	2025-03-14	2026-03-13
2	Artificial mains network	Schwarzbeck	NSLK 8127	183	2025-03-18	2026-03-17
3	Artificial Mains Network	Rohde & Schwarz	ESH2-Z5	100263	2025-03-18	2026-03-17
4	EMI Measurement Software	Farad	EZ-EMC Ver.EMEC-3A1	/	/	/
Occupied Bandwidth						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2025-03-18	2026-03-17
2	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2025-03-14	2026-03-13
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2025-03-14	2026-03-13
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2025-03-14	2026-03-13
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2025-03-14	2026-03-13
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2025-03-18	2026-03-17
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2025-03-14	2026-03-13
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2025-03-14	2026-03-13
9	DC Power Supply	Agilent	E3632A	MY40027695	2025-03-18	2026-03-17
10	RF Test System	Tonscend	JS1120-3 Test System Ver. V3.5.39	/	/	/
Field strength of fundamental Band edge emissions (Radiated) Emissions in frequency bands (above 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2025-03-14	2026-03-13
2	Double Ridged Broadband Horn Antenna	schwarabeck	BBHA 9120 D	2278	2025-05-27	2027-05-26
3	Amplifier	Agilent	8449B	3008A01120	2025-03-18	2026-03-17
4	MXA signal analyzer	Agilent	N9020A	MY54440859	2025-03-14	2026-03-13
5	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2025-03-14	2026-03-13
6	Horn antenna	Schwarzbeck	BBHA 9170	00987	2025-05-27	2027-05-26

TEST REPORT

Report No.: MTi251216001-1101E1

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
7	Pre-amplifier	Space-Dtronics	EWLAN18 40G	210405001	2025-03-19	2026-03-18
8	EMI Measurement Software	Farad	EZ-EMC Ver.EMEC- 3A1	/	/	/
Emissions in frequency bands (below 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESC17	101166	2025-03-14	2026-03-13
2	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2025-05-23	2027-05-22
3	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2024-03-23	2026-03-22
4	Amplifier	Hewlett-Packard	8447F	3113A06184	2025-03-18	2026-03-17
5	EMI Measurement Software	Farad	EZ-EMC Ver.EMEC- 3A1	/	/	/

TEST REPORT

Report No.: MTi251216001-1101E1

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.10-2020+COR 1-2023 section 6.2		
Procedure:	Refer to ANSI C63.10-2020+COR 1-2023 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

6.1.1 E.U.T. Operation:

Operating Environment:			
Temperature:	23 °C	Humidity:	39 %
Pre test mode:		Atmospheric Pressure:	100 kPa
Mode1			
Final test mode:		Mode1	

6.1.2 Test Setup Diagram:




TEST REPORT

Report No.: MTi251216001-1101E1

6.1.3 Test Data:

Mode1 / Line: Line / CH :HCH




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1660	45.94	10.23	56.17	65.16	-8.99	QP	
2		0.1819	31.04	10.23	41.27	54.40	-13.13	AVG	
3		0.2260	35.56	10.21	45.77	62.60	-16.83	QP	
4		0.2300	16.31	10.21	26.52	52.45	-25.93	AVG	
5		0.3100	25.16	10.21	35.37	59.97	-24.60	QP	
6		0.3140	6.57	10.21	16.78	49.86	-33.08	AVG	
7		0.6740	15.28	10.22	25.50	56.00	-30.50	QP	
8		0.7780	2.91	10.23	13.14	46.00	-32.86	AVG	
9		6.9380	8.46	10.47	18.93	60.00	-41.07	QP	
10		7.6140	-1.68	10.50	8.82	50.00	-41.18	AVG	
11		21.0180	20.55	10.84	31.39	60.00	-28.61	QP	
12		21.1580	8.35	10.84	19.19	50.00	-30.81	AVG	

TEST REPORT

Report No.: MTi251216001-1101E1

Mode1 / Line: Neutral / CH :HCH



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1740	30.79	10.17	40.96	54.77	-13.81	AVG	
2 *	0.1780	47.50	10.17	57.67	64.58	-6.91	QP	
3	0.2220	36.19	10.16	46.35	62.74	-16.39	QP	
4	0.2220	16.72	10.16	26.88	52.74	-25.86	AVG	
5	0.3100	25.16	10.16	35.32	59.97	-24.65	QP	
6	0.3100	6.98	10.16	17.14	49.97	-32.83	AVG	
7	0.6020	3.40	10.16	13.56	46.00	-32.44	AVG	
8	0.6060	20.15	10.16	30.31	56.00	-25.69	QP	
9	0.7780	3.24	10.17	13.41	46.00	-32.59	AVG	
10	0.8020	19.64	10.17	29.81	56.00	-26.19	QP	
11	20.8020	8.07	10.67	18.74	50.00	-31.26	AVG	
12	20.8380	19.66	10.67	30.33	60.00	-29.67	QP	

TEST REPORT

Report No.: MTi251216001-1101E1

6.2 Occupied Bandwidth

Test Requirement:	47 CFR 15.215(c)
Test Limit:	Refer to 47 CFR 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
Test Method:	ANSI C63.10-2020+COR 1-2023, section 6.9.2
Procedure:	a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. d) Steps a) through c) might require iteration to adjust within the specified tolerances. e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value. f) Set detection mode to peak and trace mode to max hold. g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value). h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument. i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j). j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth. k) The occupied bandwidth shall be reported by providing plot(s) of the

TEST REPORT


Report No.: MTi251216001-1101E1

	measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).
--	---

6.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.5 °C	Humidity:	44.1 %	Atmospheric Pressure:	100.7 kPa
Pre test mode:	Mode1				
Final test mode:	Mode1				

6.2.2 Test Setup Diagram:




6.2.3 Test Data:

Test Mode	Antenna	Frequency [MHz]	99% OBW [MHz]	20db BW [MHz]
FSK	Ant1	5730	10.022	9.703
FSK	Ant1	5775	10.607	10.42
FSK	Ant1	5820	9.206	8.894

TEST REPORT


Report No.: MTi251216001-1101E1

Test Graphs



TEST REPORT

Report No.: MTi251216001-1101E1



TEST REPORT

Report No.: MTi251216001-1101E1


6.3 Field strength of fundamental

Test Requirement:	Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:		
	Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
	902-928 MHz	50	500
	2400-2483.5 MHz	50	500
	5725-5875 MHz	50	500
	24.0-24.25 GHz	250	2500
The field strength of emissions in this band shall not exceed 2500 millivolts/meter.			
Test Method:	ANSI C63.10-2020+COR 1-2023 section 6.6		
Procedure:	ANSI C63.10-2020+COR 1-2023 section 6.6		

6.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.3 °C	Humidity:	45.1 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1				
Final test mode:	Mode1				

6.3.2 Test Setup Diagram:



TEST REPORT

Report No.: MTi251216001-1101E1

6.3.3 Test Data:

Mode1 / Polarization: Horizontal /CH: LCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		5726.724	80.02	4.43	84.45	114.00	-29.55	peak
2		5726.724	64.48	4.43	68.91	94.00	-25.09	AVG
3		5733.960	80.88	4.40	85.28	114.00	-28.72	peak
4	*	5733.960	65.70	4.40	70.10	94.00	-23.90	AVG

Mode1 / Polarization: Vertical /CH: LCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		5726.832	79.67	4.43	84.10	114.00	-29.90	peak
2	*	5726.832	64.36	4.43	68.79	94.00	-25.21	AVG
3		5733.942	77.63	4.40	82.03	114.00	-31.97	peak
4		5733.960	62.60	4.40	67.00	94.00	-27.00	AVG

TEST REPORT

Report No.: MTi251216001-1101E1

Mode1 / Polarization: Horizontal /CH: MCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		5771.868	78.18	4.38	82.56	114.00	-31.44	peak
2	*	5771.868	62.96	4.38	67.34	94.00	-26.66	AVG
3		5778.942	76.15	4.40	80.55	114.00	-33.45	peak
4		5778.942	61.09	4.40	65.49	94.00	-28.51	AVG

Mode1 / Polarization: Vertical /CH: MCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		5771.832	78.72	4.38	83.10	114.00	-30.90	peak
2	*	5771.832	63.46	4.38	67.84	94.00	-26.16	AVG
3		5778.888	77.61	4.40	82.01	114.00	-31.99	peak
4		5778.888	62.57	4.40	66.97	94.00	-27.03	AVG

TEST REPORT

Report No.: MTi251216001-1101E1

Mode1 / Polarization: Horizontal /CH: HCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		5816.814	76.99	4.53	81.52	114.00	-32.48	peak
2		5816.832	61.67	4.53	66.20	94.00	-27.80	AVG
3		5823.960	77.43	4.58	82.01	114.00	-31.99	peak
4	*	5823.960	62.41	4.58	66.99	94.00	-27.01	AVG

Mode1 / Polarization: Vertical /CH: HCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		5816.724	78.47	4.53	83.00	114.00	-31.00	peak
2	*	5816.742	60.01	4.53	64.54	94.00	-29.46	AVG
3		5823.978	76.94	4.58	81.52	114.00	-32.48	peak
4		5823.978	59.41	4.58	63.99	94.00	-30.01	AVG

TEST REPORT

Report No.: MTi251216001-1101E1

6.4 Band edge emissions (Radiated)

Test Requirement:	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.																										
Test Limit:	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation. <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																									
0.009-0.490	2400/F(kHz)	300																									
0.490-1.705	24000/F(kHz)	30																									
1.705-30.0	30	30																									
30-88	100 **	3																									
88-216	150 **	3																									
216-960	200 **	3																									
Above 960	500	3																									
Test Method:	ANSI C63.10-2020+COR 1-2023 section 6.6.4																										
Procedure:	ANSI C63.10-2020+COR 1-2023 section 6.6.4																										


6.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.3 °C	Humidity:	45.1 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1				
Final test mode:	Mode1				
Note:					
The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.					

TEST REPORT

Report No.: MTi251216001-1101E1

6.4.2 Test Setup Diagram:



TEST REPORT

Report No.: MTi251216001-1101E1

6.4.3 Test Data:

Mode1 / Polarization: Horizontal / CH: LCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		5700.000	27.18	3.61	30.79	74.00	-43.21	peak
2		5700.000	17.19	3.61	20.80	54.00	-33.20	AVG
3		5720.000	45.03	3.59	48.62	74.00	-25.38	peak
4		5720.000	34.94	3.59	38.53	54.00	-15.47	AVG
5		5725.000	63.07	3.58	66.65	74.00	-7.35	peak
6	*	5725.000	45.28	3.58	48.86	54.00	-5.14	AVG

Mode1 / Polarization: Vertical / CH: LCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		5700.000	26.68	3.61	30.29	74.00	-43.71	peak
2		5700.000	16.74	3.61	20.35	54.00	-33.65	AVG
3		5720.000	43.53	3.59	47.12	74.00	-26.88	peak
4		5720.000	32.94	3.59	36.53	54.00	-17.47	AVG
5		5725.000	61.07	3.58	64.65	74.00	-9.35	peak
6	*	5725.000	45.50	3.58	49.08	54.00	-4.92	AVG

TEST REPORT

Report No.: MTi251216001-1101E1

Mode1 / Polarization: Horizontal / CH: HCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		5875.000	25.00	4.11	29.11	74.00	-44.89	peak
2		5875.000	15.57	4.11	19.68	54.00	-34.32	AVG
3		5880.000	24.59	4.13	28.72	74.00	-45.28	peak
4	*	5880.000	15.79	4.13	19.92	54.00	-34.08	AVG
5		5885.000	15.66	4.15	19.81	54.00	-34.19	AVG
6		5885.000	24.55	4.15	28.70	74.00	-45.30	peak

Mode1 / Polarization: Vertical / CH: HCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		5875.000	20.50	4.11	24.61	74.00	-49.39	peak
2		5875.000	10.27	4.11	14.38	54.00	-39.62	AVG
3		5880.000	20.59	4.13	24.72	74.00	-49.28	peak
4		5880.000	10.93	4.13	15.06	54.00	-38.94	AVG
5		5885.000	20.05	4.15	24.20	74.00	-49.80	peak
6	*	5885.000	11.24	4.15	15.39	54.00	-38.61	AVG

TEST REPORT

Report No.: MTi251216001-1101E1

6.5 Emissions in frequency bands (below 1GHz)

Test Requirement:	47 CFR 15.249(a) 47 CFR 15.249(d) 47 CFR 15.249(e)																																								
Test Limit:	Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following: <table border="1"> <thead> <tr> <th>Fundamental frequency</th><th>Field strength of fundamental (millivolts/meter)</th><th>Field strength of harmonics (microvolts/meter)</th></tr> </thead> <tbody> <tr> <td>902-928 MHz</td><td>50</td><td>500</td></tr> <tr> <td>2400-2483.5 MHz</td><td>50</td><td>500</td></tr> <tr> <td>5725-5875 MHz</td><td>50</td><td>500</td></tr> <tr> <td>24.0-24.25 GHz</td><td>250</td><td>2500</td></tr> </tbody> </table> Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation. <table border="1"> <thead> <tr> <th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr> </thead> <tbody> <tr> <td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr> <tr> <td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr> <tr> <td>1.705-30.0</td><td>30</td><td>30</td></tr> <tr> <td>30-88</td><td>100 **</td><td>3</td></tr> <tr> <td>88-216</td><td>150 **</td><td>3</td></tr> <tr> <td>216-960</td><td>200 **</td><td>3</td></tr> <tr> <td>Above 960</td><td>500</td><td>3</td></tr> </tbody> </table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.		Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)	902-928 MHz	50	500	2400-2483.5 MHz	50	500	5725-5875 MHz	50	500	24.0-24.25 GHz	250	2500	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)																																							
902-928 MHz	50	500																																							
2400-2483.5 MHz	50	500																																							
5725-5875 MHz	50	500																																							
24.0-24.25 GHz	250	2500																																							
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																																							
0.009-0.490	2400/F(kHz)	300																																							
0.490-1.705	24000/F(kHz)	30																																							
1.705-30.0	30	30																																							
30-88	100 **	3																																							
88-216	150 **	3																																							
216-960	200 **	3																																							
Above 960	500	3																																							
Test Method:	ANSI C63.10-2020+COR 1-2023 section 6.5																																								

TEST REPORT


Report No.: MTi251216001-1101E1

Procedure:	ANSI C63.10-2020+COR 1-2023 section 6.5
------------	---

6.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.3 °C	Humidity:	45.1 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1				
Final test mode:	Mode1				
Note:					
The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.					
All modes of operation of the EUT were investigated, and only the worst-case results are reported. There were no emissions found below 30MHz within 20dB of the limit.					

6.5.2 Test Setup Diagram:




TEST REPORT

Report No.: MTi251216001-1101E1

6.5.3 Test Data:

Mode1 / Polarization: Horizontal / CH: LCH




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		48.6719	28.52	-7.88	20.64	40.00	-19.36	QP	
2		66.7325	25.15	-9.53	15.62	40.00	-24.38	QP	
3		143.8295	25.57	-7.37	18.20	43.50	-25.30	QP	
4		281.9946	25.96	-6.84	19.12	46.00	-26.88	QP	
5		522.7180	26.20	-2.50	23.70	46.00	-22.30	QP	
6	*	771.4486	27.12	2.44	29.56	46.00	-16.44	QP	

TEST REPORT

Report No.: MTi251216001-1101E1

Mode1 / Polarization: Vertica I/ CH: LCH



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	43.9658	27.45	-7.58	19.87	40.00	-20.13	QP	
2	68.1514	28.58	-9.80	18.78	40.00	-21.22	QP	
3	150.5378	26.20	-7.03	19.17	43.50	-24.33	QP	
4	297.2241	25.86	-6.46	19.40	46.00	-26.60	QP	
5	524.5541	27.40	-2.50	24.90	46.00	-21.10	QP	
6 *	774.1584	26.49	2.48	28.97	46.00	-17.03	QP	

TEST REPORT

Report No.: MTi251216001-1101E1

6.6 Emissions in frequency bands (above 1GHz)

Test Requirement:	47 CFR 15.249(a) 47 CFR 15.249(d) 47 CFR 15.249(e)																																								
Test Limit:	Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following: <table border="1"> <thead> <tr> <th>Fundamental frequency</th><th>Field strength of fundamental (millivolts/meter)</th><th>Field strength of harmonics (microvolts/meter)</th></tr> </thead> <tbody> <tr> <td>902-928 MHz</td><td>50</td><td>500</td></tr> <tr> <td>2400-2483.5 MHz</td><td>50</td><td>500</td></tr> <tr> <td>5725-5875 MHz</td><td>50</td><td>500</td></tr> <tr> <td>24.0-24.25 GHz</td><td>250</td><td>2500</td></tr> </tbody> </table> Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation. <table border="1"> <thead> <tr> <th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr> </thead> <tbody> <tr> <td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr> <tr> <td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr> <tr> <td>1.705-30.0</td><td>30</td><td>30</td></tr> <tr> <td>30-88</td><td>100 **</td><td>3</td></tr> <tr> <td>88-216</td><td>150 **</td><td>3</td></tr> <tr> <td>216-960</td><td>200 **</td><td>3</td></tr> <tr> <td>Above 960</td><td>500</td><td>3</td></tr> </tbody> </table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.		Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)	902-928 MHz	50	500	2400-2483.5 MHz	50	500	5725-5875 MHz	50	500	24.0-24.25 GHz	250	2500	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)																																							
902-928 MHz	50	500																																							
2400-2483.5 MHz	50	500																																							
5725-5875 MHz	50	500																																							
24.0-24.25 GHz	250	2500																																							
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																																							
0.009-0.490	2400/F(kHz)	300																																							
0.490-1.705	24000/F(kHz)	30																																							
1.705-30.0	30	30																																							
30-88	100 **	3																																							
88-216	150 **	3																																							
216-960	200 **	3																																							
Above 960	500	3																																							
Test Method:	ANSI C63.10-2020+COR 1-2023 section 6.6																																								

TEST REPORT


Report No.: MTi251216001-1101E1

Procedure:	ANSI C63.10-2020+COR 1-2023 section 6.6
------------	---

6.6.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.3 °C	Humidity:	45.1 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1				
Final test mode:	Mode1				
Note: Test frequency are from 1GHz to 40GHz, the amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported. All modes of operation of the EUT were investigated, and only the worst-case results are reported.					

6.6.2 Test Setup Diagram:



TEST REPORT

Report No.: MTi251216001-1101E1

6.6.3 Test Data:

Mode1 / Polarization: Horizontal / CH: LCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		11460.000	42.90	11.94	54.84	74.00	-19.16	peak
2		11460.000	33.33	11.94	45.27	54.00	-8.73	AVG
3		17190.000	44.52	13.59	58.11	74.00	-15.89	peak
4	*	17190.000	32.75	13.59	46.34	54.00	-7.66	AVG

Mode1 / Polarization: Vertical / CH: LCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		11460.000	42.64	11.94	54.58	74.00	-19.42	peak
2	*	11460.000	34.78	11.94	46.72	54.00	-7.28	AVG
3		17190.000	44.39	13.59	57.98	74.00	-16.02	peak
4		17190.000	32.68	13.59	46.27	54.00	-7.73	AVG

TEST REPORT

Report No.: MTi251216001-1101E1

Mode1 / Polarization: Horizontal / CH: MCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		11550.000	44.34	11.70	56.04	74.00	-17.96	peak
2	*	11550.000	35.22	11.70	46.92	54.00	-7.08	AVG
3		17325.000	45.13	14.00	59.13	74.00	-14.87	peak
4		17325.000	32.27	14.00	46.27	54.00	-7.73	AVG

Mode1 / Polarization: Vertical / CH: MCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		11550.000	43.89	11.70	55.59	74.00	-18.41	peak
2	*	11550.000	34.62	11.70	46.32	54.00	-7.68	AVG
3		17325.000	44.92	14.00	58.92	74.00	-15.08	peak
4		17325.000	32.27	14.00	46.27	54.00	-7.73	AVG

TEST REPORT

Report No.: MTi251216001-1101E1

Mode1 / Polarization: Horizontal / CH: HCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		11640.000	43.51	11.42	54.93	74.00	-19.07	peak
2		11640.000	33.81	11.42	45.23	54.00	-8.77	AVG
3		17460.000	43.87	14.49	58.36	74.00	-15.64	peak
4	*	17460.000	31.93	14.49	46.42	54.00	-7.58	AVG

Mode1 / Polarization: Vertical / CH: HCH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		11640.000	43.17	11.42	54.59	74.00	-19.41	peak
2		11640.000	33.85	11.42	45.27	54.00	-8.73	AVG
3		17460.000	45.07	14.49	59.56	74.00	-14.44	peak
4	*	17460.000	31.83	14.49	46.32	54.00	-7.68	AVG

TEST REPORT

Report No.: MTi251216001-1101E1

Photographs of the test setup

Refer to Appendix - Test Setup Photos

TEST REPORT

Report No.: MTi251216001-1101E1

Photographs of the EUT

Refer to Appendix - EUT Photos

TEST REPORT

Report No.: MTi251216001-1101E1

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****