8.5. Test graphs

DH1_Ant1_Hop





DH3_Ant1_Hop





DH5_Ant1_Hop





2DH1_Ant1_Hop





2DH3_Ant1_Hop





2DH5_Ant1_Hop





3DH1_Ant1_Hop





3DH3_Ant1_Hop





3DH5_Ant1_Hop





9. Number of Hopping Channel

9.1. Block diagram of test setup



9.2. Limits

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

9.3. Test procedure

(1) The test according to ANSI C63.10-2013 clause 7.8.3.
(2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
(3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
(4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW:	RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW:	VBW ≥ RBW.
Span:	The frequency band of operation
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold

(5) Measure the hopping number and record the results in the report.
(6) Measure and record the results in the report.

9.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃,47.8%RH	Test Date:	2024.07.19
Test Power Supply:	AC100-240V	Sample Number:	S24031501-004

Test Mode	Antenna	Frequency [MHz]	Result [Num]	Limit [Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS
3DH5	Ant1	Hop	79	≥15	PASS

9.5. Test graphs

DH5_Ant1_Hop



2DH5_Ant1_Hop



3DH5_Ant1_Hop



10. Band Edge Compliance (Conducted Method)

10.1. Block diagram of test setup



10.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

10.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.
(2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
(4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.

10.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃,47.8%RH	Test Date:	2024.07.19
Test Power Supply:	AC100-240V	Sample Number:	S24031501-004

Mode	Freq. (MHz)	Verdict
GFSK	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass
π/4-DQPSK	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass
8DPSK	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass

10.5. Test graphs

DH5_Ant1_Low_2402



DH5_Ant1_High_2480



DH5_Ant1_Low_Hop_2402



DH5_Ant1_High_Hop_2480



2DH5_Ant1_Low_2402



2DH5_Ant1_High_2480



2DH5_Ant1_Low_Hop_2402



2DH5_Ant1_High_Hop_2480



3DH5_Ant1_Low_2402



3DH5_Ant1_High_2480



3DH5_Ant1_Low_Hop_2402



3DH5_Ant1_High_Hop_2480



11. RF Conducted Spurious Emissions

11.1. Block diagram of test setup



11.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

11.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.
(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	≥Span/RBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

11.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃,47.8%RH	Test Date:	2024.07.19
Test Power Supply:	AC100-240V	Sample Number:	S24031501-004

Mode	Freq. (MHz)	Verdict
GFSK	Hopping off 2402	Pass
	Hopping off 2441	Pass
	Hopping off 2480	Pass
π/4-DQPSK	Hopping off 2402	Pass
	Hopping off 2441	Pass
	Hopping off 2480	Pass
8DPSK	Hopping off 2402	Pass
	Hopping off 2441	Pass
	Hopping off 2480	Pass

11.5. Test graphs

DH5_Ant1_2402_0~Reference



DH5_Ant1_2402_30~1000



DH5_Ant1_2402_1000~26500



DH5_Ant1_2441_0~Reference



DH5_Ant1_2441_30~1000



DH5_Ant1_2441_1000~26500



DH5_Ant1_2480_0~Reference



DH5_Ant1_2480_30~1000



DH5_Ant1_2480_1000~26500



2DH5_Ant1_2402_0~Reference



2DH5_Ant1_2402_30~1000



2DH5_Ant1_2402_1000~26500



2DH5_Ant1_2441_0~Reference



2DH5_Ant1_2441_30~1000



2DH5_Ant1_2441_1000~26500



2DH5_Ant1_2480_0~Reference



2DH5_Ant1_2480_30~1000



2DH5_Ant1_2480_1000~26500



3DH5_Ant1_2402_0~Reference



3DH5_Ant1_2402_30~1000



3DH5_Ant1_2402_1000~26500



3DH5_Ant1_2441_0~Reference



3DH5_Ant1_2441_30~1000



3DH5_Ant1_2441_1000~26500



3DH5_Ant1_2480_0~Reference



3DH5_Ant1_2480_30~1000



3DH5_Ant1_2480_1000~26500


MultiView
Spectrum
Ref Level 20.00 dBm Offset 12.63 dB RBW 100 kHz
Att 20 dB SWT 255 ms VBW 300 kHz Mode Auto Sweep
1 Frequency Sweep
1Pk View
M1[1] -11.13 dBm
2.480 230 GHz
M2[1] -47.32 dBm
5.182 850 GHz
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-70 dBm
H1 -28.680 dBm
M1
M2
1.0 GHz
30001 pts
2.55 GHz/
26.5 GHz
Measuring...
10:46:38 19.07.2024

12. Duty cycle

12.1. Block diagram of test setup



12.2. Limit

Just for Report.

12.3. Test procedure

(1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.
set the Spectrum Analyzer as below:
Centre Frequency: The centre frequency of the middle hopping channel.
Resolution BW: 10 MHz.
Video BW: 10 MHz.
Span: Zero span.
Detector: Peak.
Trace Mode: Clear Write.
Sweep: Video Trigger

(2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

(3) Calculate dwell time follow below formula:
Duty cycle= Pulse's on time / Burst cycle

12.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃,47.8%RH	Test Date:	2024.07.19
Test Power Supply:	AC100-240V	Sample Number:	S24031501-004

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
DH5	Ant1	2402	2.89	3.75	77.07	1.13
		2441	2.90	3.75	77.33	1.12
		2480	2.89	3.75	77.07	1.13
2DH5	Ant1	2402	2.90	3.76	77.13	1.13
		2441	2.89	3.75	77.07	1.13
		2480	2.89	3.75	77.07	1.13
3DH5	Ant1	2402	2.90	3.76	77.13	1.13
		2441	2.89	3.76	76.86	1.14
		2480	2.89	3.75	77.07	1.13

12.5. Test graphs

DH5_Ant1_2402



DH5_Ant1_2441



DH5_Ant1_2480



2DH5_Ant1_2402



2DH5_Ant1_2441



2DH5_Ant1_2480



3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



13. Antenna Requirements

13.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

13.2. Result

The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.

14.Radiated Emission

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2025/09/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2025/07/08
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200A	DDT-ZC01401	2024/09/20
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2025/07/11
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31

14.2. Block diagram of test setup







14.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		mV/m	dB(mV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(mV)/m (Peak) 54.0 dB(mV)/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$Limit_{3m}$(dBuV/m)= $Limit_{30m}$(dBuV/m) + 40Log(30m/3m)

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Laptop	HP	SL10H72009	HP laptops	AC Adapter Mode: TPN-CA17, HP Part No.: L25299-002, Input: 100-240V, 50/60Hz, Output: DC 19.5V, 3.33A, 65W

14.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz,110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with GFSK, π/4-DQPSK and 8DPSK, the worst case GFSK TX 2480MHz is record and reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.

14.6. Test result

PASS. (See below detailed test result)

14.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC BELOW 1G\20240718-013011_H		
Memo:	Sample Number:S24031501-004 Power Setting:NA		



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable Loss [dB]**	**AMP [dB]**	**Result [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	78.124	41.66	8.12	4.08	-30.51	23.35	40.00	16.65	QP	Horizontal
2	120.835	47.82	9.83	4.33	-30.84	31.14	43.50	12.36	QP	Horizontal
3	292.335	47.83	12.97	5.18	-30.32	35.66	46.00	10.34	QP	Horizontal
4	335.637	46.95	14.52	5.36	-30.23	36.60	46.00	9.40	QP	Horizontal
5	575.900	38.63	18.51	6.28	-29.90	33.52	46.00	12.48	QP	Horizontal
6	797.337	35.88	19.97	6.94	-29.90	32.89	46.00	13.11	QP	Horizontal

Note:
1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC BELOW 1G\20240718-013147_V		
Memo:	Sample Number:S24031501-004 Power Setting:NA		



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable Loss [dB]**	**AMP [dB]**	**Result [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	42.777	34.41	12.87	3.84	-30.81	20.31	40.00	19.69	QP	Vertical
2	119.991	46.89	10.00	4.33	-30.84	30.38	43.50	13.12	QP	Vertical
3	200.893	39.53	10.76	4.76	-30.60	24.45	43.50	19.05	QP	Vertical
4	239.888	48.04	11.79	4.94	-30.48	34.29	46.00	11.71	QP	Vertical
5	321.134	51.25	13.89	5.30	-30.26	40.18	46.00	5.82	QP	Vertical
6	797.896	39.87	19.91	6.94	-29.90	36.82	46.00	9.18	QP	Vertical

Note:
1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 2402MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\8		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	1069.700	48.84	24.44	2.99	-36.89	39.38	74.00	34.62	PK	Horizontal
2	1464.100	46.29	25.36	3.67	-36.94	38.38	74.00	35.62	PK	Horizontal
3	3850.900	46.79	30.91	5.08	-40.36	42.42	74.00	31.58	PK	Horizontal
4	4804.600	48.34	32.62	5.53	-40.15	46.34	74.00	27.66	PK	Horizontal
5	11193.200	43.21	39.21	8.25	-39.18	51.49	74.00	22.51	PK	Horizontal
6	12033.000	43.62	39.23	8.78	-39.57	52.06	74.00	21.94	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 2402MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\9		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	1117.300	46.34	24.60	3.07	-36.90	37.11	74.00	36.89	PK	Vertical
2	1525.300	46.04	25.15	3.77	-36.95	38.01	74.00	35.99	PK	Vertical
3	3794.800	46.05	30.68	5.08	-40.32	41.49	74.00	32.51	PK	Vertical
4	4804.600	51.09	32.62	5.53	-40.15	49.09	74.00	24.91	PK	Vertical
5	11458.400	41.94	39.24	8.42	-39.31	50.29	74.00	23.71	PK	Vertical
6	12119.700	42.31	39.30	8.82	-39.61	50.82	74.00	23.18	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 2441MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\10		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	1093.500	46.49	24.49	3.03	-36.89	37.12	74.00	36.88	PK	Horizontal
2	1474.300	46.16	25.40	3.69	-36.94	38.31	74.00	35.69	PK	Horizontal
3	4241.900	45.47	31.37	5.20	-40.36	41.68	74.00	32.32	PK	Horizontal
4	4881.100	45.84	33.30	5.58	-40.12	44.60	74.00	29.40	PK	Horizontal
5	10921.200	42.74	39.30	8.09	-39.06	51.07	74.00	22.93	PK	Horizontal
6	11752.500	43.06	38.95	8.60	-39.44	51.17	74.00	22.83	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 2441MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\11		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	1147.900	46.27	24.79	3.12	-36.90	37.28	74.00	36.72	PK	Vertical
2	1595.000	52.47	25.52	3.89	-36.96	44.92	74.00	29.08	PK	Vertical
3	3918.900	46.63	31.16	5.06	-40.40	42.45	74.00	31.55	PK	Vertical
4	4882.800	47.44	33.28	5.58	-40.12	46.18	74.00	27.82	PK	Vertical
5	11759.300	43.05	38.94	8.61	-39.45	51.15	74.00	22.85	PK	Vertical
6	12272.700	43.46	39.30	8.90	-39.67	51.99	74.00	22.01	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 2480MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\12		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	1159.800	47.17	24.82	3.14	-36.90	38.23	74.00	35.77	PK	Horizontal
2	1596.700	48.82	25.55	3.90	-36.96	41.31	74.00	32.69	PK	Horizontal
3	4031.100	47.08	30.96	5.07	-40.44	42.67	74.00	31.33	PK	Horizontal
4	4857.300	44.48	33.68	5.56	-40.13	43.59	74.00	30.41	PK	Horizontal
5	11322.400	42.17	39.22	8.33	-39.24	50.48	74.00	23.52	PK	Horizontal
6	12339.000	42.77	39.30	8.93	-39.69	51.31	74.00	22.69	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 2480MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\13		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	1049.300	47.09	24.40	2.95	-36.89	37.55	74.00	36.45	PK	Vertical
2	1595.000	46.01	25.52	3.89	-36.96	38.46	74.00	35.54	PK	Vertical
3	3823.700	46.29	30.79	5.08	-40.34	41.82	74.00	32.18	PK	Vertical
4	4959.300	48.78	33.12	5.63	-40.10	47.43	74.00	26.57	PK	Vertical
5	11162.600	43.03	39.24	8.23	-39.17	51.33	74.00	22.67	PK	Vertical
6	12310.100	43.15	39.30	8.92	-39.68	51.69	74.00	22.31	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

15.Band Edge Compliance

15.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2025/09/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200A	DDT-ZC01401	2024/09/20
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2025/07/08
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2025/07/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31

15.2. Block diagram of test setup



15.3. Limits

All restriction band should comply with 15.209 and RSS-Gen section 8.9 limits, other emission should be at least 20 dB below the fundamental.

15.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Laptop	HP	SL10H72009	HP laptops	AC Adapter Mode: TPN-CA17, HP Part No.: L25299-002, Input: 100-240V, 50/60Hz, Output: DC 19.5V, 3.33A, 65W

15.5. Test procedure

Same with Radiated Emission except change investigated frequency range.
Remark: All restriction band have been tested, and only the worst case is shown in report.

15.6. Test result

PASS. (See below detailed test result)

15.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 2402MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\24		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2372.730	15.50	27.19	3.56	0.00	46.25	74.00	27.75	PK	Horizontal
2	2390.000	12.19	27.26	3.57	0.00	43.02	74.00	30.98	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 2402MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\25		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2374.480	14.79	27.20	3.56	0.00	45.55	74.00	28.45	PK	Vertical
2	2390.000	11.18	27.26	3.57	0.00	42.01	74.00	31.99	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	2DH5 2402MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\26		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2377.190	13.41	27.21	3.56	0.00	44.18	74.00	29.82	PK	Horizontal
2	2390.000	11.17	27.26	3.57	0.00	42.00	74.00	32.00	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	2DH5 2402MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\27		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2361.100	13.48	27.14	3.55	0.00	44.17	74.00	29.83	PK	Vertical
2	2390.000	11.95	27.26	3.57	0.00	42.78	74.00	31.22	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	3DH5 2402MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\28		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2373.110	14.61	27.19	3.56	0.00	45.36	74.00	28.64	PK	Horizontal
2	2390.000	12.00	27.26	3.57	0.00	42.83	74.00	31.17	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	3DH5 2402MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\29		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2377.740	14.39	27.21	3.56	0.00	45.16	74.00	28.84	PK	Vertical
2	2390.000	10.74	27.26	3.57	0.00	41.57	74.00	32.43	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	3DH5 2480MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\30		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2483.500	10.00	27.53	3.62	0.00	41.15	74.00	32.85	PK	Horizontal
2	2487.003	13.70	27.55	3.62	0.00	44.87	74.00	29.13	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	3DH5 2480MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\31		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2483.500	10.06	27.53	3.62	0.00	41.21	74.00	32.79	PK	Vertical
2	2490.033	14.35	27.56	3.62	0.00	45.53	74.00	28.47	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	2DH5 2480MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\32		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2483.500	10.69	27.53	3.62	0.00	41.84	74.00	32.16	PK	Horizontal
2	2490.148	14.23	27.56	3.62	0.00	45.41	74.00	28.59	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	2DH5 2480MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\33		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2483.500	11.29	27.53	3.62	0.00	42.44	74.00	31.56	PK	Vertical
2	2494.880	14.56	27.58	3.63	0.00	45.77	74.00	28.23	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 2480MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\34		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2483.500	10.34	27.53	3.62	0.00	41.49	74.00	32.51	PK	Horizontal
2	2484.263	13.66	27.54	3.62	0.00	44.82	74.00	29.18	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-07-18	**Tested By**:	Johnson Huang
EUT:	BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**:	TROUPER™ 300
Test Mode:	DH5 2480MHz TX Mode	**Power Supply**:	AC 120V/60Hz
Condition:	Temp:24.5°C;Humi:47.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24031501-2E\FCC ABOVE 1G\35		
Memo:	Sample Number:S24031501-004 Power Setting:-13		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2483.500	11.75	27.53	3.62	0.00	42.90	74.00	31.10	PK	Vertical
2	2487.190	14.08	27.55	3.62	0.00	45.25	74.00	28.75	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

16.Power Line Conducted Emissions

16.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
EMI Test Software	Audix/TW	e3	DDT-ZC01252	/
Pulse Limiter	SCHWARZBECK	ESH3-Z2	DDT-ZC00539	2025/07/08
EMI Test Receiver	R&S	ESCI	DDT-ZC00235	2025/07/08
Two Line V-Network	R&S	ENV216	DDT-ZC00535	2025/07/08
Artificial mains	R&S	ESH2-Z5	DDT-ZC00538	2025/07/08
CE Cable 1	R&S	ESU8/RF2	DDT-ZC00566	2025/07/08

16.2. Block diagram of test setup



16.3. Limits

Frequency	Quasi-Peak Level dB(mV)	Average Level dB(mV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

16.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Laptop	HP	ADM Ryzen 5 2500U	HP laptops	AC Adapter Mode: TPN-CA17, HP Part No.: L25299-002, Input: 100-240V, 50/60Hz, Output: DC 19.5V, 3.33A, 65W

16.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.
The bandwidth of test receiver is set at 9 kHz.

16.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: "-----" means Peak detection; "-----" means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case GFSK TX 2480MHz.

16.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 1# Shield Room	D:\2024 CE report data\Q24031501-2E\FCC CE.EM6	
Test Date	: 2024-07-20	**Tested By**	: Johnson Huang
EUT	: BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**	: TROUPER™ 300
Power Supply	: AC 120V/60Hz	**Test Mode**	: BT
Condition	: TEMP:22.2°C, RH:57.5%	**LISN**	: 2023 1# ENV216/LINE
Memo	: Sample Number:S24031501-002		

Data: 1



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Over Limit (dB)	Detector	Phase
1	0.25	29.13	9.82	0.89	9.69	49.53	61.64	-12.11	QP	LINE
2	0.25	20.37	9.82	0.89	9.69	40.77	51.64	-10.87	Average	LINE
3	0.30	28.49	9.80	0.88	9.70	48.87	60.32	-11.45	QP	LINE
4	0.30	15.29	9.80	0.88	9.70	35.67	50.32	-14.65	Average	LINE
5	0.36	32.10	9.74	0.86	9.70	52.40	58.78	-6.38	QP	LINE
6	0.36	19.09	9.74	0.86	9.70	39.39	48.78	-9.39	Average	LINE
7	0.46	26.66	9.79	0.86	9.71	47.02	56.71	-9.69	QP	LINE
8	0.46	12.40	9.79	0.86	9.71	32.76	46.71	-13.95	Average	LINE
9	11.50	24.74	9.80	0.17	9.84	44.55	60.00	-15.45	QP	LINE
10	11.50	20.39	9.80	0.17	9.84	40.20	50.00	-9.80	Average	LINE
11	21.60	-0.40	9.97	0.37	9.92	19.86	60.00	-40.14	QP	LINE
12	21.60	-6.80	9.97	0.37	9.92	13.46	50.00	-36.54	Average	LINE

Note:
1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 1# Shield Room	D:\2024 CE report data\Q24031501-2E\FCC CE.EM6	
Test Date	: 2024-07-20	**Tested By**	: Johnson Huang
EUT	: BATTERY-POWERED PORTABLE SPEAKER SYSTEM WITH MULTI-CHANNEL MIXER AND LIGHTS	**Model Number**	: TROUPER™ 300
Power Supply	: AC 120V/60Hz	**Test Mode**	: BT
Condition	: TEMP:22.2°C, RH:57.5%	**LISN**	: 2023 1# ENV216/NEUTRAL
Memo	: Sample Number:S24031501-002		

Data: 4



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Over Limit (dB)	Detector	Phase
1	0.27	28.68	9.74	0.89	9.70	49.01	61.25	-12.24	QP	NEUTRAL
2	0.27	14.23	9.74	0.89	9.70	34.56	51.25	-16.69	Average	NEUTRAL
3	0.30	29.42	9.71	0.88	9.70	49.71	60.24	-10.53	QP	NEUTRAL
4	0.30	18.44	9.71	0.88	9.70	38.73	50.24	-11.51	Average	NEUTRAL
5	0.37	31.70	9.70	0.86	9.70	51.96	58.47	-6.51	QP	NEUTRAL
6	0.37	20.54	9.70	0.86	9.70	40.80	48.47	-7.67	Average	NEUTRAL
7	0.57	25.25	9.81	0.83	9.72	45.61	56.00	-10.39	QP	NEUTRAL
8	0.57	12.07	9.81	0.83	9.72	32.43	46.00	-13.57	Average	NEUTRAL
9	0.90	23.50	9.81	0.69	9.73	43.73	56.00	-12.27	QP	NEUTRAL
10	0.90	12.89	9.81	0.69	9.73	33.12	46.00	-12.88	Average	NEUTRAL
11	20.81	4.53	9.91	0.35	9.92	24.71	60.00	-35.29	QP	NEUTRAL
12	20.81	-2.81	9.91	0.35	9.92	17.37	50.00	-32.63	Average	NEUTRAL

Note:
1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

18. Photos of the EUT

Please refer to DDT-Q24031501-1E appendix I

----------End Report----------