

# INTERTEK TESTING SERVICES

---

## Analysis Report

The equipment under test (EUT) is a MICRO COMPONENT SYSTEM with Bluetooth technology operating in 2402-2480MHz. The EUT is powered by AC 100-240V, 50/60Hz. For more detail information pls. refer to the user manual.

Modulation Type: GFSK,  $\pi/4$ -DQPSK and 8-DPSK

Bluetooth Version: 2.1+EDR

Antenna Type: Integral antenna

Antenna Gain: 0 dBi

The nominal conducted output power (e.i.r.p) specified: 2dBm (Tolerance: +/-2dB)

The nominal radiated output power (e.i.r.p) specified: 2dBm (Tolerance: +/-2dB)

According to the KDB 447498:

The maximum radiated emission for the EUT is 98.5 dB $\mu$ V/m at 3m in the frequency 2.441GHz =  $[(FS \cdot D)^2 / 30]$  mW  
= 3.3 dBm which is within the production variation

The minimum radiated emission for the EUT is 96.8 dB $\mu$ V/m for at 3m in the frequency 2.402GHz =  $[(FS \cdot D)^2 / 30]$  mW  
= 1.6 dBm which is within the production variation

The maximum radiated output power specified is 4dBm = 2.51mW

The source- based time-averaging conducted output power  
= 2.51 \* Duty cycle mW  $\leq$  2.51 mW (Duty Cycle  $\leq$  100%)

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)  
= 3.0 \* 5 / sqrt (2.480) mW  
= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.