FCC RADIO TEST REPORT
FCC ID: 2AB6DAAI708DAT

Product： MID

Trade Name： vital ASC vitalize Your Life

Model Name： AAI-708DAT

Serial Model： Vital Mini 74A, AAI-27DAW, AAI-710QAW, AAI-716DM, AAI-716QM, AAI-760QR

Report No.： NTEK-2014NT0225133F2

Prepared for

AAI TECHNOLOGY (HK) LIMITED

RM5,6/F SHING CHUEN IND. BLDG.,25-27 SHING WAN ROAD,
TAI WAI, SHATIN,N.T.,HONG KONG.

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,Xixiang Street
Bao'an District, Shenzhen P.R. China
Tel.: +86-0755-61156588 Fax.: +86-0755-61156599
Website:www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name ..... : AAI TECHNOLOGY (HK) LIMITED

Address ..... : RM5,6/F SHING CHUEN IND. BLDG.,25-27 SHING WAN ROAD, TAI WAI, SHATIN,N.T.,HONG KONG.

Manufacture's Name..... : AAI Technology(HuiZhou)Co., LTD

Address ..... : AAI Technology HuiZhou industrial Park, longhai 3rd Road, Xiangshui River, Dayawan E & T Development Zone, Huizhou,China

Product description

Product name ..... : MID

Model and/or type reference : AAI-708DAT

Serial Model : Vital Mini 74A, AAI-27DAW, AAI-710QAW, AAI-716DM, AAI-716QM, AAI-760QR

Standards ..... : FCC Part15.247

Test procedure ..... ANSI C63.4-2003

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Date of Test .....:

Date (s) of performance of tests .....: 25 Feb. 2014 ~18 Mar. 2014

Date of Issue.....: 18 Mar. 2014

Test Result.....: **Pass**

Testing Engineer : Apple Huang

(Apple Huang)

Technical Manager : Brown Lu

(Brown Lu)

Authorized Signatory : Bovey Yang

(Bovey Yang)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	9
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 RADIATED EMISSION LIMITS	17
3.2.2 TEST PROCEDURE	18
3.2.3 DEVIATION FROM TEST STANDARD	18
3.2.4 TEST SETUP	19
3.2.5 EUT OPERATING CONDITIONS	20
3.2.6 TEST RESULTS	21
4 . NUMBER OF HOPPING CHANNEL	33
4.1 APPLIED PROCEDURES / LIMIT	33
4.1.1 TEST PROCEDURE	33
4.1.2 DEVIATION FROM STANDARD	33
4.1.3 TEST SETUP	33
4.1.4 EUT OPERATION CONDITIONS	33
4.1.5 TEST RESULTS	34
5 . AVERAGE TIME OF OCCUPANCY	35
5.1 APPLIED PROCEDURES / LIMIT	35
5.1.1 TEST PROCEDURE	35
5.1.2 DEVIATION FROM STANDARD	35

Table of Contents

Page

5.1.3 TEST SETUP 36
5.1.4 EUT OPERATION CONDITIONS 36
5.1.5 TEST RESULTS 37

6 . HOPPING CHANNEL SEPARATION MEASUREMENT 43

6.1 APPLIED PROCEDURES / LIMIT 43
6.1.1 TEST PROCEDURE 43
6.1.2 DEVIATION FROM STANDARD 43
6.1.3 TEST SETUP 43
6.1.4 EUT OPERATION CONDITIONS 43
6.1.5 TEST RESULTS 44

7 . BANDWIDTH TEST 50

7.1 APPLIED PROCEDURES / LIMIT 50
7.1.1 TEST PROCEDURE 50
7.1.2 DEVIATION FROM STANDARD 50
7.1.3 TEST SETUP 50
7.1.4 EUT OPERATION CONDITIONS 50
7.1.5 TEST RESULTS 51

8 . PEAK OUTPUT POWER TEST 57

8.1 APPLIED PROCEDURES / LIMIT 57
8.1.1 TEST PROCEDURE 57
8.1.2 DEVIATION FROM STANDARD 57
8.1.3 TEST SETUP 57
8.1.4 EUT OPERATION CONDITIONS 57
8.1.5 TEST RESULTS 58

9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE 64
9.1 DEVIATION FROM STANDARD 64
9.2 TEST SETUP 64
9.3 EUT OPERATION CONDITIONS 64
9.4 TEST RESULTS 65

10 . ANTENNA REQUIREMENT 72

10.1 STANDARD REQUIREMENT 72

10.2 EUT ANTENNA 72

11 . EUT TEST PHOTO 73
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd
Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.
FCC Registration No.:238937; IC Registration No.:9270A-1
CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y** ± **U**，where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**，providing a level of confidence of approximately **95** %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

<table>
<tr><td>Equipment</td><td>MID</td></tr>
<tr><td>Trade Name</td><td>vital ASC vitalize Your Life</td></tr>
<tr><td>Model Name</td><td>AAI-708DAT</td></tr>
<tr><td>Serial Model</td><td>Vital Mini 74A, AAI-27DAW, AAI-710QAW, AAI-716DM, AAI-716QM, AAI-760QR</td></tr>
<tr><td>Model Difference</td><td>All the models are the same circuit and RF module, except the model names.</td></tr>
<tr><td>Product Description</td><td>The EUT is a MID
<table>
<tr><td>Operation Frequency:</td><td>BT:2402~2480 MHz
802.11b/g/n(20MHz):
2412~2462MHz
802.11n(40MHz):2422~2452MHz</td></tr>
<tr><td>Modulation Type:</td><td>BT(1Mbps): GFSK
BT EDR(2Mbps): π/4-DQPSK
BT EDR(3Mbps): 8-DPSK
WIFI:
CCK/OFDM/DBPSK/DAPSK</td></tr>
<tr><td>Bit Rate of Transmitter</td><td>1Mbps/2Mbps/3Mbps</td></tr>
<tr><td>Number Of Channel</td><td>BT:79 CH
802.11b/g/n20MHz:11CH
802.11n40MHz:7CH</td></tr>
<tr><td>Antenna Designation:</td><td>Please see Note 3.</td></tr>
<tr><td>Output Power(Conducted):</td><td>BT(1Mbps): -0.053dBm
BT EDR(2Mbps): -0.951 dBm
BT EDR(3Mbps): -2.789dBm</td></tr>
</table>
Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</td></tr>
<tr><td>Channel List</td><td>Please refer to the Note 2.</td></tr>
<tr><td>Adapter</td><td>Model:WRP2U-050200C
Input: 100-240V~50/60Hz, 0.4Amax
Output: 5V⎓, 2.0A</td></tr>
<tr><td>Battery</td><td>DC 3.7V, 2250mAh</td></tr>
</table>

Note:

1. For a more detailed features description, please refer to the manufacturer’s specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	FPCB	N/A	1.0	BT Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	normal link

For Conducted Emission	
Final Test Mode	Description
Mode 4	normal link

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2) The EUT use new battery.

(3)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: Broadcom		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1/2/3Mbps)	DEF	DEF	DEF

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test



Radiated Spurious Emission Test



2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	MID	vital ASC vitalize Your Life	AAI-708DAT	N/A	EUT
E-2	Adapter	N/A	WRP2U-050200C	N/A	
E-3	Earphone	N/A	2688	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.8m	
C-2	NO	NO	1.2m	

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2013.07.06	2014.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2013.06.07	2014.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2013.07.06	2014.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2013.06.07	2014.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2013.06.07	2014.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2013.07.06	2014.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2013.07.06	2014.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2013.12.22	2014.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2013.06.08	2014.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2013.07.06	2014.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2013.07.06	2014.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2013.06.06	2014.06.05	1 year
2	LISN	R&S	ENV216	101313	2013.08.24	2014.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2013.08.24	2014.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2013.06.07	2014.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2013.06.07	2014.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2013.06.08	2014.06.07	1 year

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.6 TEST RESULTS

EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	L
Test Voltage ：	DC 5.0V from adapter AC 120V/60Hz	Test Mode：	Mode 4

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Detector Type
0.1660	47.23	9.59	56.82	65.15	-8.33	AVG
0.1660	30.55	9.59	40.14	55.15	-15.01	QP
0.2220	44.58	9.49	54.07	62.74	-8.67	QP
0.2220	28.55	9.49	38.04	52.74	-14.70	AVG
0.4980	34.86	9.51	44.37	56.03	-11.66	QP
0.4980	24.94	9.51	34.45	46.03	-11.58	AVG
1.0500	21.88	9.53	31.41	56.00	-24.59	QP
1.0500	15.87	9.53	25.40	46.00	-20.60	AVG
3.0300	20.41	9.57	29.98	56.00	-26.02	QP
3.0300	14.86	9.57	24.43	46.00	-21.57	AVG
24.5740	14.43	10.19	24.62	60.00	-35.38	QP
25.5740	5.33	10.17	15.50	50.00	-34.50	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	N
Test Voltage ：	DC 5.0V from adapter AC 120V/60Hz	Test Mode：	Mode 4

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Detector Type
0.1620	45.13	9.62	54.75	65.36	-10.61	QP
0.1620	31.02	9.62	40.64	55.36	-14.72	AVG
0.2700	41.58	9.51	51.09	61.12	-10.03	QP
0.2700	26.81	9.51	36.32	51.12	-14.80	AVG
0.4860	36.89	9.53	46.42	56.24	-9.82	QP
0.4860	23.13	9.53	32.66	46.24	-13.58	AVG
0.5940	30.13	9.53	39.66	56.00	-16.34	QP
0.5940	15.47	9.53	25.00	46.00	-21.00	AVG
3.0300	20.54	9.58	30.12	56.00	-25.88	QP
3.0300	12.22	9.58	21.80	46.00	-24.20	AVG
25.0540	16.21	10.30	26.51	60.00	-33.49	QP
25.0540	7.04	10.30	17.34	50.00	-32.66	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD

No deviation

3.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS

Radiated Spurious Emission (Transmitting)

30MHz~25GHz:(Scan with GFSK, π/4-DQPSK,8DPSK,the worst casw is BDR Mode (GFSK))

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
Below 1G							
36.3434	6.77	15.21	21.98	40.00	-18.02	QP	Vertical
39.8542	20.88	13.46	34.34	40.00	-5.66	QP	Vertical
104.5361	23.61	11.03	34.64	43.50	-8.86	QP	Vertical
118.1862	23.89	12.04	35.93	43.50	-7.57	QP	Vertical
204.9551	23.55	9.24	32.79	43.50	-10.71	QP	Vertical
254.7281	15.92	14.22	30.14	46.00	-15.86	QP	Vertical
63.5356	30.87	5.40	36.27	40.00	-3.73	QP	Horizontal
126.3285	22.95	12.21	35.16	43.50	-8.34	QP	Horizontal
274.1938	27.92	14.07	41.99	46.00	-4.01	QP	Horizontal
317.7010	27.09	15.35	42.44	46.00	-3.56	QP	Horizontal
360.4476	25.31	16.46	41.77	46.00	-4.23	QP	Horizontal
833.3170	15.67	27.29	42.96	46.00	-3.04	QP	Horizontal

Low Channel (2402 MHz)-Above 1G							
4804	61.04	-3.64	57.4	74	-16.6	Pk	Vertical
4804	44.48	-3.64	40.84	54	-13.16	AV	Vertical
7206	55.64	-0.95	54.69	74	-19.31	Pk	Vertical
7206	39.68	-0.95	38.73	54	-15.27	AV	Vertical
4804	61.09	-3.64	57.45	74	-16.55	Pk	Horizontal
4804	44.18	-3.64	40.54	54	-13.46	AV	Horizontal
7206	55.12	-0.95	54.17	74	-19.83	Pk	Horizontal
7206	39.55	-0.95	38.6	54	-15.4	AV	Horizontal
Mid Channel (2441 MHz)-Above 1G							
4882	60.98	-3.68	57.3	74	-16.7	Pk	Vertical
4882	44.19	-3.68	40.51	54	-13.49	AV	Vertical
7323	53.97	-0.82	53.15	74	-20.85	Pk	Vertical
4882	62.23	-3.68	58.55	74	-15.45	Pk	Horizontal
4882	44.8	-3.68	41.12	54	-12.88	AV	Horizontal
7323	55.6	-0.82	54.78	74	-19.22	Pk	Horizontal
7323	38.92	-0.82	38.1	54	-15.9	AV	Horizontal
High Channel (2480 MHz)- Above 1G							
4960	62.57	-3.59	58.98	74	-15.02	Pk	Vertical
4960	45	-3.59	41.41	54	-12.59	AV	Vertical
7440	55.01	-0.69	54.32	74	-19.68	Pk	Vertical
7440	39.35	-0.69	38.66	54	-15.34	AV	Vertical
4960	62.13	-3.59	58.54	74	-15.46	Pk	Horizontal
4960	44.98	-3.59	41.39	54	-12.61	AV	Horizontal
7440	54.9	-0.69	54.21	74	-19.79	Pk	Horizontal
7440	38.87	-0.69	38.18	54	-15.82	AV	Horizontal

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Meter Reading + Factor
Margin = Emission Level- Limit

Radiated band edge:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
1Mbps Non-hopping							
2390	59.54	-13.06	46.48	74	-27.52	peak	Vertical
2390	58.39	-13.06	45.33	74	-28.67	peak	Horizontal
2483.5	58.66	-12.78	45.88	74	-28.12	peak	Vertical
2483.5	59.20	-12.78	46.42	74	-27.58	peak	Horizontal
2Mbps Non-hopping							
2390	59.54	-13.06	46.48	74	-27.52	peak	Vertical
2390	58.67	-13.06	45.61	74	-28.39	peak	Horizontal
2483.5	59.66	-12.78	46.88	74	-27.12	peak	Vertical
2483.5	59.43	-12.78	46.65	74	-27.35	peak	Horizontal
3Mbps Non-hopping							
2390	60.28	-13.06	47.22	74	-26.78	peak	Vertical
2390	60.41	-13.06	47.35	74	-26.65	peak	Horizontal
2483.5	59.27	-12.78	46.49	74	-27.51	peak	Vertical
2483.5	59.98	-12.78	47.20	74	-26.80	peak	Horizontal

NOTE: 1.When the result(PK) less than AV limite,not record AV result.
2.Hopping enabled and disabled have evaluated,and the worest data was reported

Conducted Spurious Emissions at Antenna Port:

Low Channel -GFSK





Middle Channel -GFSK





High Channel -GFSK





Low Channel - π /4-DQPSK





Middle Channel - π /4-DQPSK





High Channel - π /4-DQPSK





Low Channel – 8-DPSK





Middle Channel - 8-DPSK





High Channel - 8-DPSK





4. NUMBER OF HOPPING CHANNEL

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW=100kHz
VB	VBW ≥ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
b. Spectrum Setting : RBW= 100kHz, VBW=100kHz, Sweep time = Auto.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	Hopping Mode		

Number of Hopping Channel	79



5. AVERAGE TIME OF OCCUPANCY

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

a. The transmitter output (antenna port) was connected to the spectrum analyzer
b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
d. Sweep Time is more than once pulse time.
e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
f. Measure the maximum time duration of one single pulse.
g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
h. Measure the maximum time duration of one single pulse.
i. A Period Time = (channel number)*0.4
DH1 Time Slot: Reading * (1600/2)*31.6/(channel number)
DH3 Time Slot: Reading * (1600/4)*31.6/(channel number)
DH5 Time Slot: Reading * (1600/6)*31.6/(channel number)

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	CH39-DH5 ,2DH5,3DH5		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH5	2441 MHz	2.97	0.32	0.4
2DH5	2441 MHz	2.93	0.31	0.4
3DH5	2441 MHz	2.95	0.31	0.4

CH39-DH5



CH39-2DH5



CH39-3DH5



EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	CH39-DH3,2DH3,3DH3		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH3	2441 MHz	1.72	0.28	0.4
2DH3	2441 MHz	1.73	0.28	0.4
3DH3	2441 MHz	1.69	0.27	0.4

CH39-DH3



CH39-2DH3



CH39-3DH3



EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	CH39-DH1,2DH1,3DH1		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2441 MHz	0.44	0.14	0.4
2DH1	2441 MHz	0.46	0.15	0.4
3DH1	2441 MHz	0.44	0.14	0.4

CH39-DH1



CH39-2DH1



CH39-3DH1



6. HOPPING CHANNEL SEPARATION MEASUREMENT

6.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (Channel Separation)
VB	100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.1.1 TEST PROCEDURE

a. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.

b. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.1.5 TEST RESULTS

EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	CH00 / CH39 /CH78 (1Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.010	**Complies**
2441 MHz	1.005	**Complies**
2480 MHz	1.000	**Complies**

Ch. Separation Limits: >20dB bandwidth

CH00 -1Mbps



CH39 -1Mbps



CH78 -1Mbps



EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	CH00 / CH39 /CH78 (2Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.000	**Complies**
2441 MHz	1.000	**Complies**
2480 MHz	1.000	**Complies**

Ch. Separation Limits: >2/3 of 20dB bandwidth

CH00 -2Mbps



CH39 -2Mbps



CH78 -2Mbps



EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	CH00 / CH39 /CH78 (3Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.000	**Complies**
2441 MHz	1.000	**Complies**
2480 MHz	1.000	**Complies**

Ch. Separation Limits: >2/3 of 20dB bandwidth

CH00



CH39


Agilent
R T
Mkr1 Δ 1.000 MHz
Ref 10 dBm
#Atten 10 dB
Ext PG -10 dB
0.057 dB
Peak
Log
10
dB/
1R
1
M1 S2
S3 FC
AA
Center 2.442 GHz
Span 2.5 MHz
#Res BW 30 kHz
#VBW 100 kHz
Sweep 5 ms (401 pts)
Freq/Channel
Center Freq
2.44150000 GHz
Start Freq
2.44025000 GHz
Stop Freq
2.44275000 GHz
CF Step
250.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Scale Type
Log Lin

CH78


Agilent
R T
Mkr1 Δ 1.000 MHz
Ref 10 dBm
#Atten 10 dB
Ext PG -10 dB
0.057 dB
Peak
Log
10
dB/
1R
1
M1 S2
S3 FC
AA
Center 2.479 GHz
Span 2.5 MHz
#Res BW 30 kHz
#VBW 100 kHz
Sweep 5 ms (401 pts)
Freq/Channel
Center Freq
2.47950000 GHz
Start Freq
2.47825000 GHz
Stop Freq
2.48075000 GHz
CF Step
250.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Scale Type
Log Lin

7. BANDWIDTH TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
b. Spectrum Setting : RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 TEST RESULTS

EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	CH00 / CH39 /C78**(1Mbps)**		

Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	918.660	**PASS**
2441 MHz	921.287	**PASS**
2480 MHz	836.591	**PASS**

CH00-1Mbps



CH39 -1Mbps



CH78 -1Mbps



EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	CH00 / CH39 /C78**(2Mbps)**		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.219	**PASS**
2441 MHz	1.209	**PASS**
2480 MHz	1.194	**PASS**

CH00 -2Mbps



CH39 -2Mbps



CH78 -2Mbps



EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	CH00 / CH39 /C78**(3Mbps)**		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.218	**PASS**
2441 MHz	1.214	**PASS**
2480 MHz	1.202	**PASS**

CH00 -3Mbps



CH39 -3Mbps



CH78 -3Mbps



8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	0.125 w or 20.96dBm	2400-2483.5	PASS

8.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

b. Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.1.5 TEST RESULTS

EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	CH00/ CH39 /CH78 (1M/2M/3Mbps Mode)		

1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	-0.053	30
CH39	2441	-3.620	30
CH78	2480	-4.391	30
2Mbps			
CH00	2402	-0.951	20.96
CH39	2441	-5.800	20.96
CH78	2480	-5.229	20.96
3Mbps			
CH00	2402	-3.649	20.96
CH39	2441	-2.789	20.96
CH78	2480	-5.171	20.96

CH00 -1Mbps



CH39 -1Mbps



CH78 -1Mbps



CH00 -2Mbps


Agilent
R T
Mkr1 2.40203 GHz
Ref 12 dBm
#Atten 10 dB
Ext PG -10 dB
-0.951 dBm
Peak
Log
10
dB/
Offst
2
dB
M1 S2
S3 FC
AA
Center 2.402 GHz
Span 10 MHz
#Res BW 3 MHz
#VBW 3 MHz
Sweep 4 ms (401 pts)
Freq/Channel
Center Freq
2.40200000 GHz
Start Freq
2.39700000 GHz
Stop Freq
2.40700000 GHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Scale Type
Log
Lin

CH39 -2Mbps



CH78 -2Mbps



CH00 -3Mbps


Agilent
R T
Mkr1 2.40193 GHz
Ref 12 dBm
#Atten 10 dB
Ext PG -10 dB
-3.649 dBm
Peak
Log
10
dB/
Offst
2
dB
M1 S2
S3 FC
AA
Center 2.402 GHz
Span 10 MHz
#Res BW 3 MHz
#VBW 3 MHz
Sweep 4 ms (401 pts)
Freq/Channel
Center Freq
2.40200000 GHz
Start Freq
2.39700000 GHz
Stop Freq
2.40700000 GHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Scale Type
Log
Lin

CH39 -3Mbps



CH78 -3Mbps



9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
e) Repeat above procedures until all measured frequencies were complete.

9.1 DEVIATION FROM STANDARD

No deviation.

9.2 TEST SETUP



9.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.4 TEST RESULTS

EUT：	MID	Model Name ：	AAI-708DAT
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	CH00/ CH78 (1M/2M/3Mbps Mode)		

Frequency Band	Delta Peak to band emission (dBc)	＞Limit (dBc)	Result
1Mbps Non-hopping			
Left-band	42.52	20	Pass
Right-band	44.03	20	Pass
2Mbps Non-hopping			
Left-band	48.38	20	Pass
Right-band	41.71	20	Pass
3Mbps Non-hopping			
Left-band	47.18	20	Pass
Right-band	41.98	20	Pass
1Mbps hopping			
Left-band	45.20	20	Pass
Right-band	42.43	20	Pass
2Mbps hopping			
Left-band	48.31	20	Pass
Right-band	39.17	20	Pass
3Mbps hopping			
Left-band	47.47	20	Pass
Right-band	41.14	20	Pass

BDR mode (GFSK): Band Edge-Left Side





BDR mode (GFSK): Band Edge-Right Side





EDR mode (π /4-DQPSK): Band Edge-Left Side





EDR mode (π /4-DQPSK): Band Edge- Right Side





EDR mode(8DPSK): Band Edge-Left Side





EDR mode(8DPSK): Band Edge-Right Side





10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is FPCB Antenna. It comply with the standard requirement.

11. EUT TEST PHOTO

Radiated Measurement Photos





CONDUCTED EMISSION Photos