

# FCC TEST REPORT

For

Wintop Electronics Co., Limited

Wireless Mouse

Model No.: WM-758, VM-758

Prepared For : Wintop Electronics Co., Limited

Address : Unit 04 7/F, Bright Way Tower 33, Mong Kok RD KL, Hong Kong

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited

Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China

Tel: (86) 755-26066544 Fax: (86) 755-26014772

Report Number : R0217050034W

Date of Test : May 09~Jun. 02, 2017

Date of Report : Jun. 02, 2017

# Contents

|                                                |    |
|------------------------------------------------|----|
| 1. General Information.....                    | 4  |
| 1.1. Client Information.....                   | 4  |
| 1.2. Description of Device (EUT).....          | 4  |
| 1.3. Auxiliary Equipment Used During Test..... | 4  |
| 1.4. Description of Test Modes.....            | 5  |
| 1.5. List of Channels.....                     | 5  |
| 1.6. Description of Test Setup.....            | 6  |
| 1.7. Test Equipment List.....                  | 7  |
| 1.8. Measurement Uncertainty.....              | 7  |
| 1.9. Description of Test Facility.....         | 8  |
| 2. Summary of Test Results.....                | 9  |
| 3. Conducted Emission Test.....                | 10 |
| 3.1. Test Standard and Limit.....              | 10 |
| 3.2. Test Setup.....                           | 10 |
| 3.3. Test Procedure.....                       | 10 |
| 3.4. Test Data.....                            | 10 |
| 4. Radiated Emission and Band Edge.....        | 11 |
| 4.1. Test Standard and Limit.....              | 11 |
| 4.2. Test Setup.....                           | 12 |
| 4.3. Test Procedure.....                       | 13 |
| 4.4. Test Data.....                            | 13 |
| 5. 20dB Bandwidth Test.....                    | 27 |
| 5.1. Test Standard and Limit.....              | 27 |
| 5.2. Test Setup.....                           | 27 |
| 5.3. Test Procedure.....                       | 27 |
| 5.4. Test Data.....                            | 27 |
| 6. Antenna Requirement.....                    | 30 |
| 6.1. Test Standard and Requirement.....        | 30 |
| 6.2. Antenna Connected Construction.....       | 30 |
| APPENDIX I -- TEST SETUP PHOTOGRAPH.....       | 31 |
| APPENDIX II -- EXTERNAL PHOTOGRAPH.....        | 32 |
| APPENDIX III -- INTERNAL PHOTOGRAPH.....       | 35 |

## TEST REPORT

Applicant : Wintop Electronics Co., Limited  
Manufacturer : Shenzhen Wintop Electronics Co., Limited  
Product Name : Wireless Mouse  
Model No. : WM-758, VM-758  
Trade Mark : N.A.  
Rating(s) : DC 3V by "AAA" Battery\*2

Test Standard(s) : FCC Part15 Subpart C, Paragraph 15.249

Test Method(s) : ANSI C63.10: 2013

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test : May 09~Jun. 02, 2017

Prepared by :



*Winkey Wang*

(Tested Engineer / Winkey Wang)

Reviewer :

*Dolly mo*

(Project Manager / Dolly Mo)

Approved & Authorized Signer :

*Tom Chen*

(Manager / Tom Chen)

## 1. General Information

### 1.1. Client Information

|              |   |                                                                                                |
|--------------|---|------------------------------------------------------------------------------------------------|
| Applicant    | : | Wintop Electronics Co., Limited                                                                |
| Address      | : | Unit 04 7/F, Bright Way Tower 33, Mong Kok RD KL, Hong Kong                                    |
| Manufacturer | : | Shenzhen Wintop Electronics Co., Limited                                                       |
| Address      | : | 2, 3, 4/F, Building 46, Xinhe Road, Shangmugu, Pinghu Town, Longgang District, Shenzhen, China |

### 1.2. Description of Device (EUT)

|                                                                                                                                    |             |                                                                                                                              |              |                 |         |                 |
|------------------------------------------------------------------------------------------------------------------------------------|-------------|------------------------------------------------------------------------------------------------------------------------------|--------------|-----------------|---------|-----------------|
| Product Name                                                                                                                       | :           | Wireless Mouse                                                                                                               |              |                 |         |                 |
| Model No.                                                                                                                          | :           | WM-758, VM-758<br>(Note: All samples are the same except the model number and colour, so we prepare “WM-758” for test only.) |              |                 |         |                 |
| Trade Mark                                                                                                                         | :           | N.A.                                                                                                                         |              |                 |         |                 |
| Test Power Supply                                                                                                                  | :           | DC 3V Battery inside                                                                                                         |              |                 |         |                 |
| Product Description                                                                                                                | :           | Operation Frequency:                                                                                                         | 2405-2470MHz |                 |         |                 |
|                                                                                                                                    |             | Number of Channel:                                                                                                           | 8 Channels   |                 |         |                 |
|                                                                                                                                    |             |                                                                                                                              | Channel      | Frequency (MHz) | Channel | Frequency (MHz) |
|                                                                                                                                    |             |                                                                                                                              | 1            | 2405            | 5       | 2440            |
|                                                                                                                                    |             |                                                                                                                              | 2            | 2413            | 6       | 2450            |
|                                                                                                                                    |             |                                                                                                                              | 3            | 2422            | 7       | 2460            |
|                                                                                                                                    |             | 4                                                                                                                            | 2430         | 8               | 2470    |                 |
|                                                                                                                                    |             | Modulation Type:                                                                                                             | FSK          |                 |         |                 |
| Antenna Type:                                                                                                                      | PCB Antenna |                                                                                                                              |              |                 |         |                 |
| Antenna Gain(Peak):                                                                                                                | 1.6 dBi     |                                                                                                                              |              |                 |         |                 |
| <b>Remark:</b> 1)For a more detailed features description, please refer to the manufacturer’s specifications or the User’s Manual. |             |                                                                                                                              |              |                 |         |                 |

### 1.3. Auxiliary Equipment Used During Test

|      |  |
|------|--|
| N.A. |  |
|------|--|

## 1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description |
|--------------|-------------|
| Mode 1       | CH01        |
| Mode 2       | CH04        |
| Mode 3       | CH08        |

| For Conducted Emission |             |
|------------------------|-------------|
| Final Test Mode        | Description |
| N/A                    | N/A         |


| For Radiated Emission |             |
|-----------------------|-------------|
| Final Test Mode       | Description |
| Mode 1                | CH01        |
| Mode 2                | CH04        |
| Mode 3                | CH08        |

## 1.5. List of Channels

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2405            | 5       | 2440            |
| 2       | 2413            | 6       | 2450            |
| 3       | 2422            | 7       | 2460            |
| 4       | 2430            | 8       | 2470            |

## 1.6. Description of Test Setup

RE



## 1.7. Test Equipment List

| Item | Equipment                      | Manufacturer            | Model No.     | Serial No.    | Last Cal.     | Cal. Interval |
|------|--------------------------------|-------------------------|---------------|---------------|---------------|---------------|
| 1.   | Two-Line V-network             | Rohde & Schwarz         | ENV216        | 100055        | Jul. 19, 2016 | 1 Year        |
| 2.   | EMI Test Receiver              | Rohde & Schwarz         | ESCI          | 100627        | Jun. 17, 2016 | 1 Year        |
| 3.   | RF Switching Unit              | Compliance Direction    | RSU-M2        | 38303         | Jun. 17, 2016 | 1 Year        |
| 4.   | Spectrum Analysis              | Agilent                 | E4407B        | US39390582    | Jul. 12, 2016 | 1 Year        |
| 5.   | Preamplifier                   | Instruments corporation | EMC011830     | 980100        | Jun. 17, 2016 | 1 Year        |
| 6.   | EMI Test Receiver              | Rohde & Schwarz         | ESPI          | 101604        | Jun. 17, 2016 | 1 Year        |
| 7.   | Double Ridged Horn Antenna     | Instruments corporation | GTH-0118      | 351600        | May 06, 2017  | 1 Year        |
| 8.   | Bilog Broadband Antenna        | Schwarzbeck             | VULB9163      | VULB 9163-289 | May 06, 2017  | 1 Year        |
| 9.   | Loop Antenna                   | Schwarzbeck             | FMZB1519      | 012           | May 11, 2017  | 1 Year        |
| 10.  | Pre-amplifier                  | SONOMA                  | 310N          | 186860        | Jun. 17, 2016 | 1 Year        |
| 11.  | EMI Test Software EZ-EMC       | SHURPLE                 | N/A           | N/A           | N/A           | N/A           |
| 12.  | Power Sensor                   | Agilent                 | KFSW150502    | 15I00041SN045 | Jun. 17, 2016 | 1 Year        |
| 13.  | MXA Spectrum Analysis          | Agilent                 | N9020A        | MY51170037    | Jun. 17, 2016 | 1 Year        |
| 14.  | MXG RF Vector Signal Generator | Agilent                 | N5182A        | MY48180656    | Jun. 17, 2016 | 1 Year        |
| 15.  | Signal Generator               | Agilent                 | E4421B        | MY41000743    | Jun. 17, 2016 | 1 Year        |
| 16.  | DC Power supply                | IV                      | IV-8080       | YQSB0096      | Jun. 17, 2016 | 1 Year        |
| 17.  | TEMP&HUMI PROGRAMMABLE CHAMBER | Bell Group              | BE-THK-150 M8 | SE-0137       | Jun. 17, 2016 | 1 Year        |

## 1.8. Measurement Uncertainty

|                        |   |                          |
|------------------------|---|--------------------------|
| Radiation Uncertainty  | : | Ur = 4.1 dB (Horizontal) |
|                        |   | Ur = 4.3 dB (Vertical)   |
|                        |   |                          |
| Conduction Uncertainty | : | Uc = 3.4dB               |

## 1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### **FCC-Registration No.: 752021**

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 06, 2016.

### **IC-Registration No.: 8058A-1**

Shenzhen Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A, June 13, 2016.

### **Test Location**

All Emissions tests were performed at

Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China

## 2. Summary of Test Results

| Standard Section                                            | Test Item           | Result |
|-------------------------------------------------------------|---------------------|--------|
| 15.203                                                      | Antenna Requirement | PASS   |
| 15.207                                                      | Conducted Emission  | N/A    |
| 15.249                                                      | Radiated Emission   | PASS   |
| 15.215(c)                                                   | 20dB Bandwidth      | PASS   |
| 15.249(c)                                                   | Band Edge           | PASS   |
| <b>Remark:</b> "N/A" is an abbreviation for Not Applicable. |                     |        |


### 3. Conducted Emission Test

#### 3.1. Test Standard and Limit

| Test Standard | FCC Part15 Section 15.207 |                                |               |
|---------------|---------------------------|--------------------------------|---------------|
| Test Limit    | Frequency                 | Maximum RF Line Voltage (dBuV) |               |
|               |                           | Quasi-peak Level               | Average Level |
|               | 150kHz~500kHz             | 66 ~ 56 *                      | 56 ~ 46 *     |
|               | 500kHz~5MHz               | 56                             | 46            |
|               | 5MHz~30MHz                | 60                             | 50            |

**Remark:** (1) \*Decreasing linearly with logarithm of the frequency.  
(2) The lower limit shall apply at the transition frequency.

#### 3.2. Test Setup



#### 3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

#### 3.4. Test Data

The EUT is powered by DC 3.0V battery inside, so there is no need to conduct this test.

## 4. Radiated Emission and Band Edge

### 4.1. Test Standard and Limit

| Test Standard | FCC Part15 C Section 15.209 and 15.205 |                                  |                |            |                          |
|---------------|----------------------------------------|----------------------------------|----------------|------------|--------------------------|
| Test Limit    | Frequency (MHz)                        | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark     | Measurement distance (m) |
|               | 0.009MHz~0.490MHz                      | 2400/F(kHz)                      | -              | -          | 300                      |
|               | 0.490MHz-1.705MHz                      | 24000/F(kHz)                     | -              | -          | 30                       |
|               | 1.705MHz-30MHz                         | 30                               | -              | -          | 30                       |
|               | 30MHz~88MHz                            | 100                              | 40.0           | Quasi-peak | 3                        |
|               | 88MHz~216MHz                           | 150                              | 43.5           | Quasi-peak | 3                        |
|               | 216MHz~960MHz                          | 200                              | 46.0           | Quasi-peak | 3                        |
|               | 960MHz~1000MHz                         | 500                              | 54.0           | Quasi-peak | 3                        |
|               | Above 1000MHz                          | 500                              | 54.0           | Average    | 3                        |
|               |                                        | -                                | 74.0           | Peak       | 3                        |

**Remark:**

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

| Test Standard | FCC Part15 C Section 15.249 |                                                    |                                                |                |         |                          |
|---------------|-----------------------------|----------------------------------------------------|------------------------------------------------|----------------|---------|--------------------------|
| Test Limit    | Frequency (MHz)             | Field Strength of fundamental ((millivolts /meter) | Field Strength of Harmonics (microvolts/meter) | Limit (dBuV/m) | Remark  | Measurement distance (m) |
|               | 2400~2483.5                 | 50                                                 | -                                              | 114.0          | Peak    | 3                        |
|               | 2400~2483.5                 | 50                                                 | -                                              | 94.0           | Average | 3                        |
|               | 2400~2483.5                 | -                                                  | 500                                            | 74.0           | Peak    | 3                        |
|               | 2400~2483.5                 | -                                                  | 500                                            | 54.0           | Average | 3                        |

**Remark:**

(1) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

## 4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

#### 4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9\*6\*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:

RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

#### 4.4. Test Data


##### PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz and above 18000MHz are attenuated more than 20dB below the permissible limits, so the results don't record in the report.

# Test Results (30~1000MHz)

Job No.: 0217050034W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: DC 3V Battery inside  
Test Mode: TX Mode Polarization: Horizontal




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/ | Over Limit (dB) | Detector | Height (cm) | degree (deg) | Remark |
|-----|-------------|------------------|---------------|-----------------|--------------|-----------------|----------|-------------|--------------|--------|
| 1   | 34.8823     | 35.92            | -14.35        | 21.57           | 40.00        | -18.43          | peak     |             |              |        |
| 2   | 42.6000     | 32.82            | -11.39        | 21.43           | 40.00        | -18.57          | peak     |             |              |        |
| 3   | 54.6429     | 32.25            | -14.90        | 17.35           | 40.00        | -22.65          | peak     |             |              |        |
| 4   | 108.2667    | 32.24            | -20.65        | 11.59           | 43.50        | -31.91          | peak     |             |              |        |
| 5   | 239.9874    | 31.80            | -18.09        | 13.71           | 46.00        | -32.29          | peak     |             |              |        |
| 6   | 393.4723    | 32.52            | -13.00        | 19.52           | 46.00        | -26.48          | peak     |             |              |        |

Note: 1) Factor = Antenna Factor + Cable Loss – Preamplifier Factor

2) Result = Reading + Factor

**Test Results (30~1000MHz)**

Job No.: 0217050034W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: DC 3V Battery inside  
Test Mode: TX Mode Polarization: Vertical



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/ | Over Limit (dB) | Detector | Height (cm) | degree (deg) | Remark |
|-----|-------------|------------------|---------------|-----------------|--------------|-----------------|----------|-------------|--------------|--------|
| 1   | 37.5479     | 37.72            | -12.30        | 25.42           | 40.00        | -14.58          | peak     |             |              |        |
| 2   | 39.7146     | 34.02            | -10.59        | 23.43           | 40.00        | -16.57          | peak     |             |              |        |
| 3   | 57.9993     | 32.88            | -15.21        | 17.67           | 40.00        | -22.33          | peak     |             |              |        |
| 4   | 83.8156     | 35.12            | -18.73        | 16.39           | 40.00        | -23.61          | peak     |             |              |        |
| 5   | 141.8262    | 31.58            | -18.47        | 13.11           | 43.50        | -30.39          | peak     |             |              |        |
| 6   | 524.5541    | 32.62            | -10.53        | 22.09           | 46.00        | -23.91          | peak     |             |              |        |

Note: 1) Factor = Antenna Factor + Cable Loss – Preamplifier Factor

2) Result = Reading + Factor

### Test Results (Above 1000MHz)

| Test Mode: CH01 (Low channel) |                   |                       |                 |                          |                |                |                 |      |          |
|-------------------------------|-------------------|-----------------------|-----------------|--------------------------|----------------|----------------|-----------------|------|----------|
| Frequency (MHz)               | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. | Detector |
| 2405.0000                     | 92.56             | 31.21                 | 2.17            | 35.30                    | 90.64          | 114.00         | -23.36          | V    | Peak     |
| 2405.0000                     | 84.02             | 31.21                 | 2.17            | 35.30                    | 82.10          | 94.00          | -11.90          | V    | AVG      |
| 4810.0000                     | 45.55             | 34.01                 | 2.56            | 34.71                    | 47.41          | 74.00          | -26.59          | V    | Peak     |
| 4810.0000                     | 39.81             | 34.01                 | 2.56            | 34.71                    | 41.67          | 54.00          | -12.33          | V    | AVG      |
| 7215.0000                     | 41.33             | 36.16                 | 2.98            | 35.15                    | 45.32          | 74.00          | -28.68          | V    | Peak     |
| 7215.0000                     | 32.65             | 36.16                 | 2.98            | 35.15                    | 36.64          | 54.00          | -17.36          | V    | AVG      |
| 9620.0000                     | *                 |                       |                 |                          |                |                |                 |      |          |
| 12025.0000                    | *                 |                       |                 |                          |                |                |                 |      |          |
| 14430.0000                    | *                 |                       |                 |                          |                |                |                 |      |          |
| 16835.0000                    | *                 |                       |                 |                          |                |                |                 |      |          |
| 2405.0000                     | 88.56             | 31.21                 | 2.17            | 35.30                    | 86.64          | 114.00         | -27.36          | H    | Peak     |
| 2405.0000                     | 85.62             | 31.21                 | 2.17            | 35.30                    | 83.70          | 94.00          | -10.30          | H    | AVG      |
| 4810.0000                     | 44.38             | 34.01                 | 2.56            | 34.71                    | 46.24          | 74.00          | -27.76          | H    | Peak     |
| 4810.0000                     | 39.56             | 34.01                 | 2.56            | 34.71                    | 41.42          | 54.00          | -12.58          | H    | AVG      |
| 7215.0000                     | 41.12             | 36.16                 | 2.98            | 35.15                    | 45.11          | 74.00          | -28.89          | H    | Peak     |
| 7215.0000                     | 34.63             | 36.16                 | 2.98            | 35.15                    | 38.62          | 54.00          | -15.38          | H    | AVG      |
| 9620.0000                     | *                 |                       |                 |                          |                |                |                 |      |          |
| 12025.0000                    | *                 |                       |                 |                          |                |                |                 |      |          |
| 14430.0000                    | *                 |                       |                 |                          |                |                |                 |      |          |
| 16835.0000                    | *                 |                       |                 |                          |                |                |                 |      |          |

| Test Mode: CH17 (Middle channel) |                   |                       |                 |                    |                |                |                 |      |          |
|----------------------------------|-------------------|-----------------------|-----------------|--------------------|----------------|----------------|-----------------|------|----------|
| Frequency (MHz)                  | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. | Detector |
| 2430.0000                        | 91.46             | 31.21                 | 2.19            | 34.60              | 90.26          | 114.00         | -23.74          | V    | Peak     |
| 2430.0000                        | 80.29             | 31.21                 | 2.19            | 34.60              | 79.09          | 94.00          | -14.91          | V    | AVG      |
| 4860.0000                        | 46.11             | 35.00                 | 2.57            | 34.58              | 49.10          | 74.00          | -24.90          | V    | Peak     |
| 4860.0000                        | 40.38             | 35.00                 | 2.57            | 34.58              | 43.37          | 54.00          | -10.63          | V    | AVG      |
| 7290.0000                        | 35.44             | 36.17                 | 3.00            | 35.14              | 39.47          | 74.00          | -34.53          | V    | Peak     |
| 7290.0000                        | 30.77             | 36.17                 | 3.00            | 35.14              | 34.80          | 54.00          | -19.20          | V    | AVG      |
| 9720.0000                        | *                 |                       |                 |                    |                |                |                 |      |          |
| 12150.0000                       | *                 |                       |                 |                    |                |                |                 |      |          |
| 14580.0000                       | *                 |                       |                 |                    |                |                |                 |      |          |
| 17010.0000                       | *                 |                       |                 |                    |                |                |                 |      |          |
| 2430.0000                        | 85.45             | 31.21                 | 2.19            | 34.60              | 84.25          | 114.00         | -29.75          | H    | Peak     |
| 2430.0000                        | 77.12             | 31.21                 | 2.19            | 34.60              | 75.92          | 94.00          | -18.08          | H    | AVG      |
| 4860.0000                        | 40.35             | 35.00                 | 2.57            | 34.58              | 43.34          | 74.00          | -30.66          | H    | Peak     |
| 4860.0000                        | 35.22             | 35.00                 | 2.57            | 34.58              | 38.21          | 54.00          | -15.79          | H    | AVG      |
| 7290.0000                        | 37.31             | 36.17                 | 3.00            | 35.14              | 41.34          | 74.00          | -32.66          | H    | Peak     |
| 7290.0000                        | 30.82             | 36.17                 | 3.00            | 35.14              | 34.85          | 54.00          | -19.15          | H    | AVG      |
| 9720.0000                        | *                 |                       |                 |                    |                |                |                 |      |          |
| 12150.0000                       | *                 |                       |                 |                    |                |                |                 |      |          |
| 14580.0000                       | *                 |                       |                 |                    |                |                |                 |      |          |
| 17010.0000                       | *                 |                       |                 |                    |                |                |                 |      |          |


| Test Mode: CH34 (High channel) |                   |                       |                 |                          |                |                |                 |      |          |
|--------------------------------|-------------------|-----------------------|-----------------|--------------------------|----------------|----------------|-----------------|------|----------|
| Frequency (MHz)                | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. | Detector |
| 2470.0000                      | 90.65             | 31.65                 | 2.20            | 36.00                    | 88.50          | 114.00         | -25.50          | V    | Peak     |
| 2470.0000                      | 83.12             | 31.65                 | 2.20            | 36.00                    | 80.97          | 94.00          | -13.03          | V    | AVG      |
| 4940.0000                      | 49.02             | 35.06                 | 2.58            | 34.79                    | 51.87          | 74.00          | -22.13          | V    | Peak     |
| 4940.0000                      | 37.63             | 35.06                 | 2.58            | 34.79                    | 40.48          | 54.00          | -13.52          | V    | AVG      |
| 7410.0000                      | 34.12             | 36.19                 | 3.02            | 34.90                    | 38.43          | 74.00          | -35.57          | V    | Peak     |
| 7410.0000                      | 30.65             | 36.19                 | 3.02            | 34.90                    | 34.96          | 54.00          | -19.04          | V    | AVG      |
| 9880.0000                      | *                 |                       |                 |                          |                |                |                 |      |          |
| 12350.0000                     | *                 |                       |                 |                          |                |                |                 |      |          |
| 14820.0000                     | *                 |                       |                 |                          |                |                |                 |      |          |
| 17290.0000                     | *                 |                       |                 |                          |                |                |                 |      |          |
| 2470.0000                      | 87.65             | 31.65                 | 2.20            | 36.00                    | 85.50          | 114.00         | -28.50          | H    | Peak     |
| 2470.0000                      | 76.02             | 31.65                 | 2.20            | 36.00                    | 73.87          | 94.00          | -20.13          | H    | AVG      |
| 4940.0000                      | 44.12             | 35.06                 | 2.58            | 34.79                    | 46.97          | 74.00          | -27.03          | H    | Peak     |
| 4940.0000                      | 39.07             | 35.06                 | 2.58            | 34.79                    | 41.92          | 54.00          | -12.08          | H    | AVG      |
| 7410.0000                      | 40.77             | 36.19                 | 3.02            | 34.90                    | 45.08          | 74.00          | -28.92          | H    | Peak     |
| 7410.0000                      | 33.62             | 36.19                 | 3.02            | 34.90                    | 37.93          | 54.00          | -16.07          | H    | AVG      |
| 9880.0000                      | *                 |                       |                 |                          |                |                |                 |      |          |
| 12350.0000                     | *                 |                       |                 |                          |                |                |                 |      |          |
| 14820.0000                     | *                 |                       |                 |                          |                |                |                 |      |          |
| 17290.0000                     | *                 |                       |                 |                          |                |                |                 |      |          |

Remark:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The test results of 9kHz-30MHz and above 18000MHz are attenuated more than 20dB below the permissible limits, so the results don't record in the report.

**Radiated Band Edge:**

Job No.: 0217050034W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: DC 3V Battery inside  
Test Mode: TX Mode CH01 Polarization: Horizontal  
Detector Peak




| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|----------------|-----------------|
| 2390.00         | 45.72             | 29.15                 | 3.41            | 34.01              | 44.27          | 74.00          | -29.73          |
| 2400.00         | 62.92             | 29.16                 | 3.43            | 34.01              | 61.50          | 74.00          | -12.50          |

Remark:

1. Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Job No.: 0217050034W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: DC 3V Battery inside  
Test Mode: TX Mode CH01 Polarization: Vertical  
Detector Peak




| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|----------------|-----------------|
| 2390.00         | 46.54             | 29.15                 | 3.41            | 34.01              | 45.09          | 74.00          | -28.91          |
| 2400.00         | 65.26             | 29.16                 | 3.43            | 34.01              | 63.84          | 74.00          | -10.16          |

Remark:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Job No.: 0217050034W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: DC 3V Battery inside  
Test Mode: TX Mode CH01 Polarization: Horizontal  
Detector AVG




| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|----------------|-----------------|
| 2390.00         | 35.63             | 29.15                 | 3.41            | 34.01                    | 34.18          | 54.00          | -19.82          |
| 2400.00         | 47.03             | 29.16                 | 3.43            | 34.01                    | 45.61          | 54.00          | -8.39           |

Remark:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Job No.: 0217050034W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: DC 3V Battery inside  
Test Mode: TX Mode CH01 Polarization: Vertical  
Detector AVG




| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|----------------|-----------------|
| 2390.00         | 35.78             | 29.15                 | 3.41            | 34.01                    | 34.33          | 54.00          | -19.67          |
| 2400.00         | 48.95             | 29.16                 | 3.43            | 34.01                    | 47.53          | 54.00          | -6.47           |

Remark:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Job No.: 0217050034W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: DC 3V Battery inside  
Test Mode: TX Mode CH08 Polarization: Horizontal  
Detector Peak




| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|----------------|-----------------|
| 2483.50         | 48.16             | 29.28                 | 3.53            | 34.03              | 46.94          | 74.00          | -27.06          |
| 2500.00         | 46.79             | 29.30                 | 3.56            | 34.03              | 45.62          | 74.00          | -28.38          |

Remark:

1. Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Job No.: 0217050034W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: DC 3V Battery inside  
Test Mode: TX Mode CH08 Polarization: Vertical  
Detector Peak




| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|----------------|-----------------|
| 2483.50         | 49.48             | 29.28                 | 3.53            | 34.03              | 48.26          | 74.00          | -25.74          |
| 2500.00         | 48.06             | 29.30                 | 3.56            | 34.03              | 46.89          | 74.00          | -27.11          |

Remark:

1. Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Job No.: 0217050034W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: DC 3V Battery inside  
Test Mode: TX Mode CH08 Polarization: Horizontal  
Detector AVG




| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|----------------|-----------------|
| 2483.50         | 38.49             | 29.28                 | 3.53            | 34.03                    | 37.27          | 54.00          | -16.73          |
| 2500.00         | 37.81             | 29.30                 | 3.56            | 34.03                    | 36.64          | 54.00          | -17.36          |

Remark:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Job No.: 0217050034W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: DC 3V Battery inside  
Test Mode: TX Mode CH08 Polarization: Vertical  
Detector AVG



| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|----------------|-----------------|
| 2483.50         | 39.94             | 29.28                 | 3.53            | 34.03                    | 38.72          | 54.00          | -15.28          |
| 2500.00         | 38.26             | 29.30                 | 3.56            | 34.03                    | 37.09          | 54.00          | -16.91          |

Remark:


1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

## 5. 20dB Bandwidth Test

### 5.1. Test Standard and Limit

|               |                             |
|---------------|-----------------------------|
| Test Standard | FCC Part15 C Section 15.249 |
|---------------|-----------------------------|

### 5.2. Test Setup




### 5.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:  
RBW = 100kHz, VBW  $\geq$  3\*RBW = 300kHz,  
Detector= Average  
Trace mode= Max hold.  
Sweep- auto couple.
4. Mark the peak frequency and -20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.


### 5.4. Test Data

|              |                  |             |           |
|--------------|------------------|-------------|-----------|
| Test Item    | : 20dB Bandwidth | Test Mode   | : TX Mode |
| Test Voltage | : DC 3V          | Temperature | : 24°C    |
| Test Result  | : PASS           | Humidity    | : 55%RH   |


| Frequency (MHz) | Bandwidth (kHz) | Result |
|-----------------|-----------------|--------|
| 2405MHZ         | 2692.0          | PASS   |
| 2430MHZ         | 2807.0          | PASS   |
| 2470MHZ         | 2717.0          | PASS   |



Test Mode: Low



Test Mode: Middle



Test Mode: High


## 6. Antenna Requirement

### 6.1. Test Standard and Requirement

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Standard | FCC Part15 Section 15.203                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Requirement   | <p>15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> |



### 6.2. Antenna Connected Construction

The antenna is a PCB Antenna which permanently attached, and the best case gain of the antenna is 1.6dBi. It complies with the standard requirement.




## APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Radiation Emission Test



## APPENDIX II -- EXTERNAL PHOTOGRAPH







## APPENDIX III -- INTERNAL PHOTOGRAPH

