FCC TEST REPORT
for
Anker Technology Co., Limited

Premium Stereo Bluetooth Speaker
Model No.: A3143

Prepared for	:	Anker Technology Co., Limited
Address	:	Room 1318-19, Hollywood Commercial Center, 610 Nathan Road, Mongkok, Kowloon, Hongkong

Prepared By	:	Shenzhen Anbotek Compliance Laboratory Limited
Address	:	1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China Tel: (86) 755-26066544 Fax: (86) 755-26014772

Report Number	:	R011505519I
Date of Test	:	May 20~ Jul. 01, 2015
Date of Report	:	Jul. 01, 2015

TABLE OF CONTENT

Description

Page

Test Report

1. GENERAL INFORMATION.....4
1.1. Description of Device (EUT).....4
1.2. Auxiliary Equipment Used during Test.....5
1.3. Description of Test Facility.....5
1.4. Measurement Uncertainty.....5
2. TEST METHODOLOGY.....6
2.1. Summary of Test Results.....6
2.2. Description of Test Modes.....6
3. CONDUCTED EMISSION TEST.....7
3.1. Block Diagram of Test Setup.....7
3.2. Power Line Conducted Emission Measurement Limits (15.207).....7
3.3. Configuration of EUT on Measurement.....7
3.4. Operating Condition of EUT.....7
3.5. Test Procedure.....8
3.6. Test equipment.....8
3.7. Power Line Conducted Emission Measurement Results.....8
4. FCC PART 15.247 REQUIREMENTS FOR DSSS & OFDM MODULATION.....11
4.1 Test Setup.....11
4.2 6dB Bandwidth.....11
4.3. Maximum Peak output power test.....14
4.4. Band Edges Measurement.....17
4.5. Peak Power Spectral Density.....28
4.6. Radiated Emissions.....31
5. ANTENNA APPLICATION.....42
5.1. Antenna requirement.....42
5.2. Result.....42
6. PHOTOGRAPH.....43
6.1 Photo of Conducted Emission Test.....43
6.2 Photo of Radiation Emission Test.....43
APPENDIX I (EXTERNAL PHOTOS).....45
APPENDIX Ⅱ(INTERNAL PHOTOS).....49

TEST REPORT

Applicant	:	Anker Technology Co., Limited
Manufacturer	:	Anker Technology Co., Limited
EUT	:	Premium Stereo Bluetooth Speaker
Model No.	:	A3143
Serial No.	:	N.A.
Trade Mark	:	ANKER
Rating	:	DC 5V, 1.5A

Measurement Procedure Used:
FCC Part15 Subpart C 2014, Paragraph 15.247

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test : May 20~ Jul. 01, 2015

Prepared by : Kebo Zhang
(Tested Engineer / Kebo Zhang)

Reviewer : Amy Ding
(Project Manager / Amy Ding)

Approved & Authorized Signer : Tom Chen
(Manager / Tom Chen)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	Premium Stereo Bluetooth Speaker
Model Number	:	A3143
Test Power Supply	:	AC 120V, 60Hz for adapter/ DC 5V(With DC 3.7V Battery inside)
Frequency	:	2402~2480MHz
Modulation	:	GFSK
Channel Spacing	:	2MHz
Number of Channels	:	40
Antenna Type	:	Integrated
Antenna Gain	:	2 dBi
Applicant	:	Anker Technology Co., Limited
Address	:	Room 1318-19, Hollywood Commercial Center, 610 Nathan Road, Mongkok, Kowloon, Hongkong
Manufacturer	:	Anker Technology Co., Limited
Address	:	Room 1318-19, Hollywood Commercial Center, 610 Nathan Road, Mongkok, Kowloon, Hongkong
Factory	:	Dongguan Taide Industrial Co., Ltd.
Address	:	Taide Industrial Park, Phase 2 Jinfenghuang Industrial District, Huangdong, Fenggang Town, Dongguan City, China
Date of receipt	:	May 20, 2015
Date of Test	:	May 20~ Jul. 01, 2015

1.2. Auxiliary Equipment Used during Test

Adapter	:	Manufacturer: Samsung M/N: ETA-U90CBC S/N: RT6FB17ZS/B-E Input: AC 100-240V, 50-60Hz, 0.35A Output: DC 5V, 2A
iPod	:	M/N: A1199 S/N: 7J712G0CVQ5 CE , FCC: DOC

1.3. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS - LAB Code: L3503
Shenzhen Anbotek Compliance Laboratory Limited., Laboratory has been assessed and in compliance with CNAS/CL01: 2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

FCC-Registration No.: 752021
Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registed and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 10, 2013.

IC-Registration No.: 8058A-1
Shenzhen Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A, February 22, 2013.

Test Location
All Emissions tests were performed at
Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China

1.4. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 4.1 dB (Horizontal) Ur = 4.3 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4dB

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10: 2013 and FCC Part 15, Paragraph 15.247.

2.1. Summary of Test Results

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107, 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15, Paragraph 15.247(b)(1)	Peak Output Power	PASS	Complies
FCC Part 15, Paragraph 15.247(a)(2)	6dB Bandwidth	PASS	Complies
FCC Part 15, Paragraph 15.247(c)	100kHz Bandwidth of Frequency Band Edges	PASS	Complies
FCC Part 15, Paragraph 15.209(a)(f)	Spurious Emission	PASS	Complies
FCC Part 15, Paragraph 15.247(a)(1)	Frequency Separation	-	N/A
FCC Part 15, Paragraph 15.247(a)(1)(iii)	Number of Hopping Frequency	-	N/A
FCC Part 15, Paragraph 15.247(a)(1)(iii)	Time of Occupancy	-	N/A
FCC Part 15, Paragraph 15.247(c)	Peak Power Density	PASS	Complies

2.2. Description of Test Modes

The EUT has been tested under operating condition.
Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel Low(2402MHz), Channel Middle(2440MHz) and Channel High(2480MHz) are chosen for the final testing.

3. Conducted Emission Test

3.1. Block Diagram of Test Setup

3.1.1. Block diagram of connection between the EUT and simulators



3.2. Power Line Conducted Emission Measurement Limits (15.207)

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

3.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4. Operating Condition of EUT

3.4.1. Setup the EUT and simulator as shown as Section 3.1.

3.4.2. Turn on the power of all equipment.

3.4.3. Let the EUT work in test mode (Charging) and measure it.

3.5. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9KHz.

The frequency range from 150KHz to 30MHz is checked.

The test results are reported on Section 3.6.

3.6. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Two-Line V-network	Rohde & Schwarz	ENV216	100055	Apr. 17, 2015	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Apr. 17, 2015	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Apr. 17, 2015	1 Year

3.7. Power Line Conducted Emission Measurement Results

PASS.

The frequency range from 150KHz to 30 MHz is investigated.

Please refer the following pages.

CONDUCTED EMISSION TEST DATA

Test Site:	1# Shielded Room
Operating Condition:	Charging
Test Specification:	AC 120V, 60Hz for adapter
Comment:	Live Line
	Tem.:25℃ Hum.:50%

SCAN TABLE: "Voltage(150K~30M)FIN"
Short Description: 150K-30M Disturbance Voltages



Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.343500	24.50	20.1	59	34.6	QP	L1	GND
0.577500	25.60	20.1	56	30.4	QP	L1	GND
1.076500	19.70	20.2	56	36.3	QP	L1	GND
4.217500	23.60	20.5	56	32.4	QP	L1	GND
8.726500	25.70	20.6	60	34.3	QP	L1	GND
28.526500	30.90	20.9	60	29.1	QP	L1	GND

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.492000	19.20	20.1	46	26.9	AV	L1	GND
0.586500	18.70	20.1	46	27.3	AV	L1	GND
1.054000	21.10	20.2	46	24.9	AV	L1	GND
4.222000	17.10	20.5	46	28.9	AV	L1	GND
11.354500	16.90	20.6	50	33.1	AV	L1	GND
28.526500	22.50	20.9	50	27.5	AV	L1	GND

CONDUCTED EMISSION TEST DATA

Test Site:	1# Shielded Room
Operating Condition:	Charging
Test Specification:	AC 120V, 60Hz for adapter
Comment:	Neutral Line
	Tem.:25℃ Hum.:50%

SCAN TABLE: "Voltage(150K~30M)FIN"
Short Description: 150K-30M Disturbance Voltages



Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	36.20	20.1	66	29.8	QP	N	GND
0.375000	22.30	20.1	58	36.1	QP	N	GND
0.478500	19.50	20.1	56	36.9	QP	N	GND
1.054000	25.40	20.2	56	30.6	QP	N	GND
9.397000	27.60	20.6	60	32.4	QP	N	GND
28.481500	32.70	20.9	60	27.3	QP	N	GND

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.181500	16.20	20.1	54	38.2	AV	N	GND
0.586500	19.60	20.1	46	26.4	AV	N	GND
1.054000	20.60	20.2	46	25.4	AV	N	GND
4.217500	17.60	20.5	46	28.4	AV	N	GND
9.550000	18.00	20.6	50	32.0	AV	N	GND
29.561500	23.20	20.9	50	26.8	AV	N	GND

4. FCC Part 15.247 Requirements for DSSS & OFDM Modulation

4.1 Test Setup



4.2 6dB Bandwidth

a. Limit

For the direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

b. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
   RBW = 100kHz, VBW⩾3*RBW =300kHz,
   Detector= Peak
   Trace mode= Max hold.
   Sweep- auto couple.
4. Mark the peak frequency and –6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

c. Test Setup See 4.1

d. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis	Agilent	E4407B	US39390582	Apr. 17, 2015	1 Year
2.	Preamplifier	Instruments corporation	EMC011830	980100	Apr. 17, 2015	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 17, 2015	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Apr. 20, 2015	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Apr. 20, 2015	1 Year
6.	Pre-amplifier	SONOMA	310N	186860	Apr. 17, 2015	1 Year
7.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A

e. Test Results

Pass.

f. Test Data

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Results
Low	2402	507.178		Pass
Mid	2440	504.066	>500	Pass
High	2480	506.468		Pass

Test Plots See the following page.

CH Low



CH Mid



CH High



4.3. Maximum Peak output power test

a. Limit

The maximum peak output power of the intentional radiator shall not exceed the following:
1. For systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt (30dBm).
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antenna of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

b. Configuration of Measurement



c. Test Procedure

This test was according the kDB 558074 9.1.2:
1. This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.
2. Set the RBW ⩾DTS bandwidth.
3. Set the VBW⩾3*RBW.
4. Set the span⩾ 3*RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use peak marker function to determine the peak amplitude level.

d. Test Equipment

Same as the equipment listed in 4.2.

e. Test Results

Pass.

g. Test Data

Channel	Frequency (MHz)	Maximum transmit power (dBm)	Limit (dBm)	Limit (watts)	Result
Low	2402	-0.511	30	1	Pass
Mid	2440	0.237			Pass
High	2480	0.879			Pass

CH Low



CH Mid



CH High



4.4. Band Edges Measurement

a. Limit

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

b. Test Procedure

1. Conducted Method:

1) Set RBW=100KHz, VBW=300KHz
2) Detector=peak
3) Sweep time= auto
4) Trace mode=max hold.

2. Radiated Method:

1) For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane. The EUT is tested in 9*6*6 Chamber.
For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane. The EUT is tested in 9*6*6 Chamber.
2) The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4) Set both RBW and VBW of spectrum analyzer to 100kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT. If pass then set Spectrum Analyzer as below:
For below 1GHz:
The resolution bandwidth and video bandwidth of test receiver/ spectrum analyzer is 120kHz.
Detector: **Quasi-Peak**
For above 1GHz Peak measurement:
The resolution bandwidth of test receiver/ spectrum analyzer is 1MHz and video bandwidth is 3MHz.
Detector: **Peak**
For above 1GHz average measurement:
The resolution bandwidth of test receiver/ spectrum analyzer is 1MHz and the video bandwidth is 1kHz.
Detector: **Peak**
5) Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

30M to 1G emissions:



1G to 40G emissions:



c. Test Equipment

Same as the equipment listed in 4.2.

d. Test Results

Pass.

e. Test Plots

See the following page.

CH Low



CH High



2402MHz
Horizontal-PEAK:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2364.000	41.33	-2.57	38.76	74.00	-35.24	peak			
2	2390.000	42.21	-2.51	39.70	74.00	-34.30	peak			
3	2400.000	50.38	-2.49	47.89	74.00	-26.11	peak			

Horizontal-AV:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2370.250	40.19	-2.56	37.63	54.00	-16.37	AVG			
2	2390.000	40.11	-2.51	37.60	54.00	-16.40	AVG			
3	2400.000	51.76	-2.49	49.27	54.00	-4.73	AVG			

2402MHz
Vertical-PEAK:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2377.750	41.54	-2.54	39.00	74.00	-35.00	peak			
2	2390.000	41.01	-2.51	38.50	74.00	-35.50	peak			
3	2400.000	49.46	-2.49	46.97	74.00	-27.03	peak			

Vertical-AV:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2371.000	42.22	-2.56	39.66	54.00	-14.34	AVG			
2	2390.000	42.07	-2.51	39.56	54.00	-14.44	AVG			
3	2400.000	50.70	-2.49	48.21	54.00	-5.79	AVG			

2480MHz
Horizontal-PEAK:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2483.500	39.79	-2.31	37.48	74.00	-36.52	peak			
2	2489.125	40.53	-2.29	38.24	74.00	-35.76	peak			

Horizontal-AV:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2483.500	39.77	-2.31	37.46	54.00	-16.54	AVG			
2	2487.563	37.59	-2.30	35.29	54.00	-18.71	AVG			

2480MHz
Vertical-PEAK:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2483.500	39.75	-2.31	37.44	74.00	-36.56	peak			
2	2488.813	39.98	-2.29	37.69	74.00	-36.31	peak			

Vertical-AV:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2483.500	41.22	-2.31	38.91	54.00	-15.09	AVG			
2	2490.563	40.58	-2.29	38.29	54.00	-15.71	AVG			

4.5. Peak Power Spectral Density

a. Limit

1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

b. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5xOBW, Sweep=500s
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

c. Test Equipment

Same as the equipment listed in 4.2.

d. Test Setup

See 3.1

e. Test Results

Pass

f. Test Data

Please refer to the following data.

g. Test Plot See the following pages

Test mode: IEEE 802.11b

Channel	Frequency (MHz)	PPSD (dBm/3KHz)	∑PPSD (dBm/3KHz)	Limit (dBm)	Result
Low	2402	-11.79	-	8.00	Pass
Mid	2440	-10.48	-	8.00	Pass
High	2480	-10.31	-	8.00	Pass

CH Low



CH Mid



CH High



4.6. Radiated Emissions

4.6.1.1. Test Limits (< 30 MHZ)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

4.6.1.2. Test Limits (≥ 30 MHZ)

FIELD STRENGTH of Fundamental: @3M	FIELD STRENGTH of Harmonics	S15.209 30 - 88 MHz	40 dBuV/m
902-928 MHZ		88 - 216 MHz	43.5
2.4-2.4835 GHz		216 - 960 MHz	46
94 dBμV/m @3m	54 dBμV/m @3m	ABOVE 960 MHz	54dBuV/m

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis	Agilent	E4407B	US39390582	Apr. 17, 2015	1 Year
2.	Preamplifier	Instruments corporation	EMC011830	980100	Apr. 17, 2015	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 17, 2015	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Apr. 20, 2015	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Apr. 20, 2015	1 Year
6.	Pre-amplifier	SONOMA	310N	186860	Apr. 17, 2015	1 Year
7.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A

4.6.2. Test Configuration:

4.6.2.1. 9k to 30MHz emissions:



4.6.2.2. 30M to 1G emissions:



4.6.2.3. 1G to 40G emissions:



4.6.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.
For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.
The turn table can rotate 360 degrees to determine the position of the maximum emission level.
The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower.
The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

Measurements are made on 9KHz to 30MHz and 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All reading are above 1GHz, peak & average values with a resolution bandwidth of 1MHz.
The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

The test results are listed in Section 4.6.4.

4.6.4. Test Results

PASS.

The EUT was tested on (BT Mode, AUX Mode, Charging) modes, only the worst data of (Charging) is attached in the following pages. Only the worst case (x orientation).

Job No.:	**011505519I**	**Polarization:**	**Horizontal**
Standard:	**(RE)FCC PART15 C _3m**	**Power Source:**	**AC 120V, 60Hz for adapter**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**24.3(C)/55%RH**
Test Mode:	**Charging**	**Distance:**	**3m**



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	56.0007	40.09	-15.03	25.06	40.00	-14.94	peak			
2	88.3421	46.83	-22.04	24.79	43.50	-18.71	peak			
3	160.9089	45.77	-22.84	22.93	43.50	-20.57	peak			
4	301.4224	50.39	-17.51	32.88	46.00	-13.12	peak			
5	375.9385	53.50	-13.35	40.15	46.00	-5.85	QP	300	0	
6	443.2943	44.06	-12.20	31.86	46.00	-14.14	peak			

Job No.:	**011505519I**	**Polarization:**	**Vertical**
Standard:	**(RE)FCC PART15 C _3m**	**Power Source:**	**AC 120V, 60Hz for adapter**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**24.3(C)/55%RH**
Test Mode:	**Charging**	**Distance:**	**3m**



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	36.5792	49.82	-13.06	36.76	40.00	-3.24	QP	100	0	
2	53.1313	46.22	-14.79	31.43	40.00	-8.57	peak			
3	59.4405	43.40	-15.34	28.06	40.00	-11.94	peak			
4	94.0979	41.89	-16.35	25.54	43.50	-17.96	peak			
5	162.0414	53.39	-17.81	35.58	43.50	-7.92	peak			
6	386.6338	47.20	-12.14	35.06	46.00	-10.94	peak			

Job No.:	**011505519I**	**Polarization:**	**Horizontal**
Standard:	**(RE)FCC PART15 C _3m**	**Power Source:**	**DC 3.7V**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**24.3(C)/55%RH**
Note:	**2402MHz**	**Distance:**	**3m**



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	10987.500	32.52	11.88	44.40	74.00	-29.60	peak			
2	10987.500	22.59	11.88	34.47	54.00	-19.53	AVG			

Job No.:	**011505519I**	**Polarization:**	**Vertical**
Standard:	**(RE)FCC PART15 C _3m**	**Power Source:**	**DC 3.7V**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**24.3(C)/55%RH**
Note:	**2402MHz**	**Distance:**	**3m**



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	7842.500	33.56	9.39	42.95	74.00	-31.05	peak			
2	7842.500	23.45	9.39	32.84	54.00	-21.16	AVG			

Job No.:	**011505519I**	**Polarization:**	**Horizontal**
Standard:	**(RE)FCC PART15 C _3m**	**Power Source:**	**DC 3.7V**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**24.3(C)/55%RH**
Note:	**2440MHz**	**Distance:**	**3m**



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	6482.500	36.25	7.58	43.83	74.00	-30.17	peak			
2	6482.500	25.89	7.58	33.47	54.00	-20.53	AVG			

Job No.:	**011505519I**	**Polarization:**	**Vertical**
Standard:	**(RE)FCC PART15 C _3m**	**Power Source:**	**DC 3.7V**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**24.3(C)/55%RH**
Note:	**2440MHz**	**Distance:**	**3m**



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	6567.500	34.97	7.68	42.65	74.00	-31.35	peak			
2	6567.500	24.79	7.68	32.47	54.00	-21.53	AVG			

Job No.:	**011505519I**	**Polarization:**	**Horizontal**
Standard:	**(RE)FCC PART15 C _3m**	**Power Source:**	**DC 3.7V**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**24.3(C)/55%RH**
Note:	**2480MHz**	**Distance:**	**3m**



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	6652.500	37.80	7.78	45.58	74.00	-28.42	peak			
2	6652.500	27.69	7.78	35.47	54.00	-18.53	AVG			

Job No.:	**011505519I**	**Polarization:**	**Vertical**
Standard:	**(RE)FCC PART15 C _3m**	**Power Source:**	**DC 3.7V**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**24.3(C)/55%RH**
Note:	**2480MHz**	**Distance:**	**3m**



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	6482.500	35.15	7.58	42.73	74.00	-31.27	peak			
2	6482.500	24.89	7.58	32.47	54.00	-21.53	AVG			

5. ANTENNA APPLICATION

5.1. Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

5.2. Result

The EUT's antenna used a integrated antenna which is permanently attached, The antenna's gain is 2dBi and meets the requirement.



6. PHOTOGRAPH

6.1 Photo of Conducted Emission Test

6.2 Photo of Radiation Emission Test





APPENDIX I (EXTERNAL PHOTOS)

Figure 1
The EUT-Overall View

Figure 2
The EUT-Top View

Figure 3
The EUT-Bottom View

Figure 4
The EUT-Front View



Figure 5
The EUT-Back View



Figure 6
The EUT-Right View



Figure 7
The EUT-Left View



APPENDIX Ⅱ(INTERNAL PHOTOS)

Figure 8
The EUT-Inside View

Figure 9
The EUT-Inside View

Figure 10
The EUT-Inside View



Figure 11
The EUT-Inside View



Figure 12
PCB of the EUT-Front View



Figure 13
PCB of the EUT-Back View



Figure 14
PCB of the EUT-Front View



Figure 15
PCB of the EUT-Back View



Figure 16
PCB of the EUT-Front View



Figure 17
PCB of the EUT-Back View



Figure 18
PCB of the EUT-Front View



Figure 19
PCB of the EUT-Back View