



Shenzhen Certification Technology Service Co., Ltd
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China.

TEST REPORT

FCC ID: 2AB85-PV0719

Applicant : vmsens industrial technology limited
Address : Room-414, Building-2, No.5 Jian Guo East Road, Chao Yang District, Beijing, China

Equipment under Test (EUT):

Name : motion tracker

Model : Mox Suit

Standards : FCC PART 15, SUBPART C : 2013 (Section 15.249)

Report No. : ST-TCB140331002

Date of Test : April 8-11, 2014

Date of Issue : April 12, 2014

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above

Authorized Signature

(Mark Zhu)
General Manager

The manufacture should ensure that all the products in series production are in conformity with the product sample detailed in this report.

If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of Shenzhen Certification Technology Service Co., Ltd. Or test done by Shenzhen Certification Technology Service Co., Ltd. Approvals in connection with, distribution or use of the product described in this report must be approved by Shenzhen Certification Technology Service Co., Ltd. Approvals in writing.

TABLE OF CONTENT

Description	Page
1 General Information	3
1.1 Description of Device (EUT)	3
1.2 Description of Test Facility	4
2 EMC Equipment List	5
3 Test Procedure	6
4 Summary of Measurement	7
4.1 Summary of test result	7
4.2 Test mode	7
5 POWER LINE CONDUCTED EMISSION	9
5.1 Conducted Emission Limits(15.209&249)	9
5.2 Test Setup	9
5.3 Test Procedure	10
5.4 Test Results	10
6 Radiation Emission	13
6.1 Radiation Emission Limits(15.209&249 (a))	13
6.2 Test Setup	14
6.3 Test Procedure	15
6.4 Test Equipment Setting For emission test.	16
6.5 Test Condition	16
6.6 Test Result	16
7 Occupied bandwidth	22
7.1 Test limit	22
7.2 Method of measurement	22
7.3 Test Setup	22
7.4 Test Results	22
8 Band Edge Check	25
8.1 Test limit	25
8.2 Test Procedure	25
8.3 Test Setup	25
8.4 Test Result	25
9 Antenna Requirement	30
9.1 Standard Requirement	30
9.2 Antenna Connected Construction	30
9.3 Result	30
10 Photographs of Test Setup	31
11 Photographs of EUT	33

1 General Information

1.1 Description of Device (EUT)

Trade Name : VMSENS

EUT : motion tracker

Model No. : Mox Suit

DIFF. : N/A

Type of Antenna : Reverse SMA connector, max gain 1 dBi

Operation Frequency : 2403-2480MHz

Channel number : 3

Modulation type : GFSK

Power Supply : DC 5V Supply by adapter with AC 120V/60Hz

Manufacturer: vmsens industrial technology limited

Adapter : Model:YW-0520

Input: AC 110~240V, 50/60Hz

Output: DC 5V, 2A

Applicant : vmsens industrial technology limited

Address : Room-414, Building-2, No.5 Jian Guo East Road, Chao Yang District, Beijing, China

Manufacturer : vmsens industrial technology limited

Address : Room-414, Building-2, No.5 Jian Guo East Road, Chao Yang District, Beijing, China

1.2 Description of Test Facility

Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
FCC Registered No.:197647

2 EMC Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
3m Semi-Anechoic	ETS-LINDGREN	N/A	SEL0017	Nov. 16, 13	1Year
Spectrum analyzer	Agilent	E4407B	MY46185649	Oct. 31, 13	1Year
Receiver	R&S	ESCI	100492	Oct. 31, 13	1Year
Receiver	R&S	ESCI	101202	Oct. 31, 13	1Year
Bilog Antenna	SCHWARZBECK	VULB 9168	9168-438	Mar.11, 14	1Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D(1201)	Mar.11, 14	1Year
ETS Horn Antenna	ETS	3160	SEL0076	Mar.11, 14	1Year
Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	Feb.20, 14	1Year
L.I.S.N.	SCHWARZBECK	NSLK8126	8126466	Oct. 31, 13	1Year
Cable	Resenberger	N/A	No.1	Oct. 31, 13	1Year
Cable	SCHWARZBECK	N/A	No.2	Oct. 31, 13	1Year
Cable	SCHWARZBECK	N/A	No.3	Oct. 31, 13	1Year
Pre-amplifier	SCHWARZBECK	BBV9743	9743-019	Oct. 31, 13	1Year
Pre-amplifier	Quietek	AP-180C	CHM-0602012	Oct. 31, 13	1Year

3 Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The test procedure used was ANSI Standard C63.4-2003 using a 50 u H LISN. Both Lines were observed. The bandwidth of the receiver was 10kHz with an appropriate sweep speed. The ambient temperature of the EUT was 25°C with a humidity of 58%.

RADIATION INTERFERENCE: The test procedure used was ANSI Standard C63.4-2003 using a ANRITSU spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a micro volt at the output of the antenna. The resolution bandwidth was 100kHz and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3MHz above 1 GHz. The ambient temperature of the EUT was 25°C with a humidity of 58%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer and cable loss. The antenna correction factors and cable loss are stated in terms of dB. The gain of the Pre-selector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF + CABLE = FS

33.20 dBuV + 10.36 dB + 0.9 dB = 44.46 dBuV/m @ 3m

ANSI STANDARD C63.4-2003 10.1.7 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSI Standard C63.4-2003 10.1.7 with the EUT 40 cm from the vertical ground wall.

4 Summary of Measurement

4.1 Summary of test result

Test Item	Test Requirement	Standard Paragraph	Result
Spurious Emission	FCC PART 15: 2013	Section 15.249&15.209	Compliance
Conduction Emission	FCC PART 15: 2013	Section 15.207	Compliance
Occupied bandwidth	FCC PART 15: 2013	Section 15.249	Compliance
Band edge Requirement	FCC PART 15: 2013	Section 15.249	Compliance
Antenna Requirement	FCC PART 15: 2013	Section 15.203	Compliance

Note: EUT can be powered with inside adapter, according to exploratory test, when powered by adapter have worse emissions, and also can make sure EUT have enough power for wireless work, so all the final test were performed with Adapter.

4.2 Test mode

Tested mode, channel information		
Mode	Channel	Frequency (MHz)
GFSK	CH1	2403
	CH2	2441
	CH3	2480

Channel list	
Channel	Frequency (MHz)
1	2403
2	2441
3	2480

4.3 Block Diagram



4.4 Assistant equipment used for test

Description : Adapter
Manufacturer : vmsens industrial technology limited
Model No. : YW-0520

4.5 Test Conditions

Temperature range	21-25℃
Humidity range	40-75%
Pressure range	86-106kPa

4.6 Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Uncertainty for Power point Conducted Emissions Test	2.50dB	
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB	Polarize: V
	2.57dB	Polarize: H
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.04dB	Polarize: V
	3.02dB	Polarize: H
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	3.84dB	Polarize: H
	3.56dB	Polarize: V
Uncertainty for radio frequency	1×10^{-9}	
Uncertainty for temperature	0.2℃	
Uncertainty for humidity	3%	
Uncertainty for DC and low frequency voltages	0.06%	

5 POWER LINE CONDUCTED EMISSION

5.1 Conducted Emission Limits(15.209&249)


Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3. The limit decreases in line with the logarithm of the frequency in the rang of 0.15 to 0.50 MHz.

5.2 Test Setup



5.3 Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4-2003 on Conducted Emission Measurement. The bandwidth of test receiver (R & S ESCS30) is set at 9 kHz.

5.4 Test Results


PASS.

Detailed information please see the following page.

.



Shenzhen Certification Technology Service Co., Ltd.
 2F, Building B, East Area of Nanchang Second Industrial Zone,
 Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
 Tel: 4006786199 Fax: +86-755-26736857
 Website: <http://www.cessz.com> Email: Service@cessz.com




Trace: 6
 Condition : FCC PART 15 B QP POL: NEUTRAL Temp: 24 °C Hum: 56 %
 EUT : Motion Tracker
 Model No : Mox Suit
 Test Mode : Link mode
 Power : DC 5V From adapter with AC 120V/60Hz
 Test Engineer: Star
 Remark :

Item	Freq MHz	Read dBuV	LISN Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	0.150	30.74	0.03	-9.72	0.10	40.59	66.00	-25.41	QP
2	0.150	18.74	0.03	-9.72	0.10	28.59	56.00	-27.41	Average
3	0.274	31.59	0.03	-9.72	0.10	41.44	60.98	-19.54	QP
4	0.274	26.59	0.03	-9.72	0.10	36.44	50.98	-14.54	Average
5	0.822	29.87	0.02	-9.71	0.10	39.70	56.00	-16.30	QP
6	0.822	21.87	0.02	-9.71	0.10	31.70	46.00	-14.30	Average
7	1.645	29.27	0.05	-9.71	0.10	39.13	56.00	-16.87	QP
8	1.645	18.27	0.05	-9.71	0.10	28.13	46.00	-17.87	Average
9	5.993	34.07	0.11	-9.61	0.14	43.93	60.00	-16.07	QP
10	5.993	25.07	0.11	-9.61	0.14	34.93	50.00	-15.07	Average
11	15.226	31.05	0.24	-9.38	0.24	40.91	60.00	-19.09	QP
12	15.226	14.05	0.24	-9.38	0.24	23.91	50.00	-26.09	Average

Remarks: Level = Read + LISN Factor - Preamp Factor + Cable loss



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 Fax: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com



Trace: 8
Condition : FCC PART 15 B QP POL: LINE Temp: 24 °C Hum: 56 %
EUT : Motion Tracker
Model No : Mox Suit
Test Mode : Link mode
Power : DC 5V From adapter with AC 120V/60Hz
Test Engineer: Star
Remark :

Item	Freq MHz	Read dBuV	LISN Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	0.273	30.83	0.03	-9.72	0.10	40.68	61.03	-20.35	QP
2	0.273	24.83	0.03	-9.72	0.10	34.68	51.03	-16.35	Average
3	1.082	27.20	0.04	-9.71	0.10	37.05	56.00	-18.95	QP
4	1.082	20.20	0.04	-9.71	0.10	30.05	46.00	-15.95	Average
5	2.707	26.91	0.07	-9.70	0.11	36.79	56.00	-19.21	QP
6	2.707	19.91	0.07	-9.70	0.11	29.79	46.00	-16.21	Average
7	4.874	29.58	0.10	-9.68	0.12	39.48	56.00	-16.52	QP
8	4.874	19.58	0.10	-9.68	0.12	29.48	46.00	-16.52	Average
9	11.933	27.16	0.26	-9.47	0.22	37.11	60.00	-22.89	QP
10	11.933	15.16	0.26	-9.47	0.22	25.11	50.00	-24.89	Average
11	20.594	29.48	0.33	-9.50	0.36	39.67	60.00	-20.33	QP
12	20.594	17.48	0.33	-9.50	0.36	27.67	50.00	-22.33	Average

Remarks: Level = Read + LISN Factor - Preamp Factor + Cable loss

6 Radiation Emission

6.1 Radiation Emission Limits(15.209&249 (a))


Frequency (MHz)	Field Strength Limits at 3 metres (watts,e.i.r.p.)		
	uV/m	dB uV/m	Measurement distance(m)
0.009-0.490	2400/F(kHz)	XX	300
0.490-1.705	24000/F(kHz)	XX	30
1.705-30	30	29.5	30
30~88	100(3nW)	40	3
88~216	150(6.8nW)	43.5	3
216~960	200(12nW)	46	3
Above960	500(75nW)	54	3
Carrier frequency		93.97(AV)	3
Carrier frequency		113.97(PK)	3

NOTE:


- a) The tighter limit applies at the band edges.
- b) Emission Level(dB uV/m)=20log Emission Level(Uv/m)

6.2 Test Setup


See the next page



Below 30MHz Test Setup



Above 30MHz Test Setup



Above 1GHz Test Setup

6.3 Test Procedure

- The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1GHz, The EUT was placed on a rotating 0.8 m high above ground, The table was rotated 360 degrees to determine the position of the highest radiation
- The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked, and then Quasi Peak Detector mode re-measured
- If Peak value complies with QP limit Below 1GHz. The EUT is deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.
- For the actual test configuration, please see the test setup photo.

6.4 Test Equipment Setting For emission test.

9KHz~150KHz	RBW 200Hz	VBW1KHz
150KHz~30MHz	RBW 9KHz	VBW 30KHz
30MHz~1GHz	RBW 120KHz	VBW 300KHz
Above 1GHz	RBW 1MHz	VBW 3MHz

6.5 Test Condition

Continual Transmitting in maximum power.

6.6 Test Result

PASS.

We have scanned the 10th harmonic from 9KHz to the EUT.
Detailed information please see the following page.


From 9KHz to 30MHz: Conclusion: **PASS**

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Below 1GHz test data:



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 FAX: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com




Condition : FCC PART 15 B 3m POL: VERTICAL
EUT : Motion Tracker
Model No : Mox Suit
Test Mode : Link mode
Power : DC 5V From adapter with AC 120V/60Hz
Test Engineer : Simple
Remark :
Temp : 24.2°C
Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	38.75	28.89	13.73	25.74	0.13	17.01	40.00	-22.99	QP
2	153.20	26.61	14.16	26.91	0.41	14.27	43.50	-29.23	QP
3	403.25	26.38	14.84	24.43	0.72	17.51	46.00	-28.49	QP
4	627.27	28.48	18.82	25.82	0.98	22.46	46.00	-23.54	QP
5	752.74	27.96	20.29	25.69	1.37	23.93	46.00	-22.07	QP
6	948.76	28.28	22.13	25.61	1.35	26.15	46.00	-19.85	QP

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 FAX: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com



Condition : FCC PART 15 B 3m POL: HORIZONTAL
EUI : Motion Tracker
Model No : Mox Suit
Test Mode : Link mode
Power : DC 5V From adapter with AC 120V/60Hz
Test Engineer : Simple
Remark :
Temp : 24.2°C
Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	32.86	26.98	13.28	25.51	0.11	14.66	40.00	-25.14	QP
2	47.66	26.03	13.59	25.82	0.08	13.88	40.00	-26.12	QP
3	161.47	26.86	14.14	26.91	0.46	14.25	43.50	-29.25	QP
4	294.11	26.74	12.67	24.18	0.74	15.97	46.00	-30.03	QP
5	472.18	26.71	16.16	24.54	0.88	19.21	46.00	-26.79	QP
6	796.18	28.90	20.68	25.66	1.40	25.32	46.00	-20.68	QP

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss

Notes: --Means other frequency and mode comply with standard requirements and at least have 20dB margin.

Radiated Emissions Result of Inside band (2403MHz)

EUT	motion tracker	Model Name	Mox Suit
Temperature	25°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V supply by Adapter
Test Mode	TX Low	Antenna polarization	Horizontal/Vertical

Channel Low(2403MHz)									
Fre. MHz	Plority H/V	Reading dBuV	Antenna Factor dB	Cable Loss dB	Amplifier Gain dB	Correct Factor dB	Measure Result dBuV/m	Limit dBuV/m	Margin dB
2403	H	93.72 (PK)	27.62	3.94	34.97	-3.41	90.31	113.97	-23.66
2403	H	88.42 (AV)	27.62	3.94	34.97	-3.41	85.01	93.97	-8.96
--	H	--	--	--	--	--	--	--	--
2403	V	91.85 (PK)	27.62	3.94	34.97	-3.41	88.44	113.97	-25.53
2403	V	86.31 (AV)	27.62	3.94	34.97	-3.41	82.90	93.97	-11.07
--	V	--	--	--	--	--	--	--	--

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1489.53	H	50.42	---	-10.27	40.15	---	74.00	54.00	-13.85	Peak
1942.13	H	50.20	---	-8.86	41.34	---	74.00	54.00	-12.66	Peak
2654.72	H	49.20	---	-6.94	42.26	---	74.00	54.00	-11.74	Peak
4806.00	H	41.22	---	0.64	41.86	---	74.00	54.00	-12.14	Peak
N/A										
1218.43	V	50.94	---	-11.52	39.42	---	74.00	54.00	-14.58	Peak
1821.56	V	49.90	---	-9.16	40.74	---	74.00	54.00	-13.26	Peak
2794.23	V	49.21	---	-6.38	42.83	---	74.00	54.00	-11.17	Peak
4806.00	V	42.77		0.64	43.41	---	74.00	54.00	-10.59	Peak
N/A										

Notes: 1 --Means other frequency and mode comply with standard requirements and at least have 20dB margin. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain
Measurement Result=Reading + Correct Factor
Margin=Measurement Result-Limit

2 -Spectrum setting:

- Peak setting 30MHz-1GHz, RBW=120KHz, VBW=300KHz.
- AV setting 30MHz-1GHz, RBW=1MHz, VBW=10Hz.

Radiated Emissions Result of Inside band (2441MHz)

EUT	motion tracker	Model Name	Mox Suit
Temperature	25°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V supply by Adapter
Test Mode	TX Mid	Antenna polarization	Horizontal/Vertical

Channel Low(2441MHz)									
Fre. MHz	Plority H/V	Reading dBuV	Antenna Factor dB	Cable Loss dB	Amplifier Gain dB	Correct Factor dB	Measure Result dBuV/m	Limit dBuV/m	Margin dB
2441	H	92.98 (PK)	27.61	3.96	34.97	-3.4	89.58	113.97	-24.39
2441	H	86.38 (AV)	27.61	3.96	34.97	-3.4	82.98	93.97	-10.99
--	H	--	--	--	--	--	--	--	--
2441	V	90.21 (PK)	27.61	3.96	34.97	-3.4	86.81	113.97	-27.16
2441	V	83.65 (AV)	27.61	3.96	34.97	-3.4	80.25	93.97	-13.72
--	V	--	--	--	--	--	--	--	--

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1231.29	H	50.94	---	-11.52	39.42	---	74.00	54.00	-14.58	Peak
2215.05	H	48.38	---	-8.13	40.25	---	74.00	54.00	-13.75	Peak
2932.16	H	47.14	---	-5.95	41.19	---	74.00	54.00	-12.81	Peak
4882.00	H	39.58	---	0.76	40.34	---	74.00	54.00	-13.66	Peak
N/A										
1305.47	V	51.35	---	-10.84	40.51	---	74.00	54.00	-13.49	Peak
2306.43	V	46.92	---	-7.46	39.46	---	74.00	54.00	-14.54	Peak
3145.07	V	45.81	---	-5.63	40.18	---	74.00	54.00	-13.82	Peak
4882.00	V	40.45		0.76	41.21	---	74.00	54.00	-12.79	Peak
N/A										

Notes: 1 --Means other frequency and mode comply with standard requirements and at least have 20dB margin. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain
Measurement Result=Reading + Correct Factor
Margin=Measurement Result-Limit

2 -Spectrum setting:

- Peak setting 30MHz-1GHz, RBW=120KHz, VBW=300KHz.
- AV setting 30MHz-1GHz, RBW=1MHz, VBW=10Hz.

Radiated Emissions Result of Inside band (2480MHz)

EUT	motion tracker	Model Name	Mox Suit
Temperature	25°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V supply by Adapter
Test Mode	TX High	Antenna polarization	Horizontal/Vertical

Channel Low(2480MHz)									
Fre. MHz	Plority H/V	Reading dBuV	Antenna Factor dB	Cable Loss dB	Amplifier Gain dB	Correct Factor dB	Measure Result dBuV/m	Limit dBuV/m	Margin dB
2480	H	91.54 (PK)	27.59	4.00	34.97	-3.38	88.16	113.97	-25.81
2480	H	85.42 (AV)	27.59	4.00	34.97	-3.38	82.04	93.97	-11.93
--	H	--	--	--	--	--	--	--	--
2480	V	87.63 (PK)	27.59	4.00	34.97	-3.38	84.25	113.97	-29.72
2480	V	80.36 (AV)	27.59	4.00	34.97	-3.38	76.98	93.97	-16.99
--	V	--	--	--	--	--	--	--	--

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1256.33	H	50.69	---	-10.96	39.73	---	74.00	54.00	-14.27	Peak
1954.17	H	49.1	---	-8.64	40.46	---	74.00	54.00	-13.54	Peak
2915.74	H	46.34	---	-5.95	40.39	---	74.00	54.00	-13.61	Peak
4960.00	H	40.31	---	0.87	41.18	---	74.00	54.00	-12.82	Peak
N/A										
1294.75	V	50.64	---	-10.96	39.68	---	74.00	54.00	-14.32	Peak
2106.41	V	49.60	---	-8.36	41.24	---	74.00	54.00	-12.76	Peak
3257.22	V	48.45	---	-5.39	43.06	---	74.00	54.00	-10.94	Peak
4960.00	V	41.00		0.87	41.87	---	74.00	54.00	-12.13	Peak
N/A										

Notes: 1 --Means other frequency and mode comply with standard requirements and at least have 20dB margin. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain
Measurement Result=Reading + Correct Factor
Margin=Measurement Result-Limit

2 -Spectrum setting:

- Peak setting 30MHz-1GHz, RBW=120KHz, VBW=300KHz.
- AV setting 30MHz-1GHz, RBW=1MHz, VBW=10Hz.

7 Occupied bandwidth


7.1 Test limit

Please refer section 15.249

7.2 Method of measurement



- a) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
- b) The test receiver RBW set 30KHz, VBW set 100KHz, Sweep time set auto.


7.3 Test Setup



7.4 Test Results

Detailed information please see the following page.





8 Band Edge Check

8.1 Test limit

Please refer section 15.249 and section 15.205.

249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in section 15.209, whichever is the lesser attenuation.

249(e) As shown in section 15.35(b), for frequencies above 1000 MHz, the above field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

8.2 Test Procedure

8.2.1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

8.2.2. Set spectrum analyzer please see the following test plot.

8.2.3. Set the spectrum analyzer as RBW, VBW=1000 KHz,

8.2.4. Max hold, view and count how many channels in the band.

8.3 Test Setup

Please see the section 6.2, Above 1GHz Test Setup.


8.4 Test Result

Pass.

Detailed information please see the following page.



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 FAX: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com




Condition : FCC PART 15_18G PEAK 3m POL: VERTICAL
EUT : motion tracker
Model No : Mox Suit
Test Mode : TX 2403MHz
Power : DC 5V Supply by adapter AC 120V/60Hz
Test Engineer : Simple
Remark :
Temp :
Hum :

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2390.00	41.16	27.62	34.97	3.92	37.73	74.00	-36.27	Peak
2	2400.00	52.59	27.62	34.97	3.94	49.18	74.00	-24.82	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss



Shenzhen Certification Technology Service Co., Ltd.
 2F, Building B, East Area of Nanchang Second Industrial Zone,
 Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
 Tel: 4006786199 FAX: +86-755-26736857
 Website: <http://www.cessz.com> Email: Service@cessz.com




Condition : FCC PART 15_18G PEAK 3m POL: HORIZONTAL
 EUT : motion tracker
 Model No : Mox Suit
 Test Mode : TX 2403MHz
 Power : DC 5V Supply by adapter AC 120V/60Hz
 Test Engineer : Simple
 Remark :
 Temp :
 Hum :

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2390.00	40.79	27.62	34.97	3.92	37.36	74.00	-36.64	Peak
2	2400.00	46.88	27.62	34.97	3.94	43.47	74.00	-30.53	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 FAX: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com




Condition : FCC PART 15_18G PEAK 3m POL: HORIZONTAL
EUT : motion tracker
Model No : Mox Suit
Test Mode : TX 2480MHz
Power : DC 5V Supply by adapter AC 120V/60Hz
Test Engineer : Simple
Remark :
Temp :
Hum :

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2483.50	51.55	27.59	34.97	4.00	48.17	74.00	-25.83	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 FAX: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com



Condition : FCC PART 15_18G PEAK 3m POL: VERTICAL
EUT : motion tracker
Model No : Mox Suit
Test Mode : TX 2480MHz
Power : DC 5V Supply by adapter AC 120V/60Hz
Test Engineer : Simple
Remark :
Temp :
Hum :

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2483.50	53.60	27.59	34.97	4.00	50.22	74.00	-23.78	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss

9 Antenna Requirement

9.1 Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2 Antenna Connected Construction


The directional gains of antenna used for transmitting is 1 dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see EUT photo for details.

9.3 Result


The EUT antenna is Reverse SMA connector Antenna. It comply with the standard requirement.

10 Photographs of Test Setup

Photographs-Radiated Emission Test Setup in Chamber Below 1G



Above 1G





Photographs-Conducted Emission Test Setup





11 Photographs of EUT



















-----END OF THE REPORT-----