



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Iconnect

Address: No.9, Aly. 58, Ln. 112, Ruiguang Rd., Neihu Dist., Taipei City Taiwan

FCC ID: 2AB877394

Product Name: IEEE 802.11ah sub 1 GHz Devices

Standard(s): 47 CFR Part 15, Subpart C(15.247)

ANSI C63.10-2013

KDB 558074 D01 15.247 Meas Guidance v05r02

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: 2403Y20305E-00B

Date Of Issue: 2025/4/2

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China

Tel: +86-769-83085888

www.ccttt.com.cn

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.1.1 General.....	6
1.1.2 Operation Frequency Detail	6
1.1.3 Accessory Information.....	7
1.2 DESCRIPTION OF TEST CONFIGURATION.....	8
1.2.1 EUT Operation Condition:.....	8
1.2.2 Support Equipment List and Details	8
1.2.3 Support Cable List and Details	8
1.2.4 Block Diagram of Test Setup.....	9
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATION RADIATED EMISSIONS	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
3.2.4 Test Procedure	17
3.2.5 Corrected Amplitude & Margin Calculation.....	17
3.3 dB EMISSION BANDWIDTH:.....	18
3.3.1 Applicable Standard.....	18
3.3.2 EUT Setup.....	18
3.3.3 Test Procedure	18
3.4 MAXIMUM CONDUCTED OUTPUT POWER:	19
3.4.1 Applicable Standard.....	19
3.4.2 EUT Setup.....	19
3.4.3 Test Procedure	19
3.5 MAXIMUM POWER SPECTRAL DENSITY	20
3.5.1 Applicable Standard.....	20
3.5.2 EUT Setup.....	20
3.5.3 Test Procedure	20
3.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE:	21
3.6.1 Applicable Standard.....	21
3.6.2 EUT Setup.....	21
3.6.3 Test Procedure	21

3.7 CONDUCTED SPURIOUS EMISSIONS	22
3.7.1 Applicable Standard.....	22
3.7.2 EUT Setup.....	22
3.7.3 Test Procedure	22
3.8 DUTY CYCLE:	23
3.8.1 EUT Setup.....	23
3.8.2 Test Procedure	23
3.9 ANTENNA REQUIREMENT.....	23
3.9.1 Applicable Standard.....	23
3.9.2 Judgment.....	23
4. TEST DATA AND RESULTS	24
4.1 AC LINE CONDUCTED EMISSIONS.....	24
4.2 RADIATED SPURIOUS EMISSIONS.....	27
4.2.1 9 kHz – 1 GHz	27
4.2.2 1 – 10 GHz.....	36
4.3 6 dB EMISSION BANDWIDTH:	48
4.4 MAXIMUM CONDUCTED OUTPUT POWER:	52
4.5 MAXIMUM POWER SPECTRAL DENSITY:	53
4.6 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE:	57
4.7 CONDUCTED SPURIOUS EMISSIONS.....	61
4.8 DUTY CYCLE	65
5. RF EXPOSURE EVALUATION	67
5.1 APPLICABLE STANDARD.....	67
5.2 PROCEDURE.....	67
5.3 MEASUREMENT RESULT	67
6. EUT PHOTOGRAPHS	68
7. TEST SETUP PHOTOGRAPHS	69

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2403Y20305E-00B	Original Report	2024/11/27
2.0	2403Y20305E-00B	Add Conducted spurious emissions data	2025/4/2

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

1.1.1 General

EUT Name:	IEEE 802.11ah sub 1 GHz Devices
Trade Name:	ALFA
EUT Model:	AHST7394S
Multiple Models:	AHSM7394S, AHSBOX-420, AHSBOX-485
Operation Frequency:	1MHz Bandwidth: 903.5-926.5 MHz 2MHz Bandwidth: 905-925 MHz 4MHz Bandwidth: 906-926 MHz
Maximum Peak Output Power (Conducted):	18.74 dBm
Modulation Type:	OFDM with BPSK, QPSK, 16-QAM, 64-QAM
Rated Input Voltage:	DC 3.3V
Sample Number:	2T1H-1
EUT Received Date:	2024/10/25
EUT Received Status:	Good
Note: The Multiple models are electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer.	

1.1.2 Operation Frequency Detail For 1MHz Bandwidth:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	903.5	9	911.5	17	919.5
2	904.5	10	912.5	18	920.5
3	905.5	11	913.5	19	921.5
4	906.5	12	914.5	20	922.5
5	907.5	13	915.5	21	923.5
6	908.5	14	916.5	22	924.5
7	909.5	15	917.5	23	925.5
8	910.5	16	918.5	24	926.5
Per section 15.31(m), the below frequencies were performed the test:					
Test Channel			Frequency (MHz)		
Lowest			903.5		
Middle			914.5		
Highest			926.5		

For 2MHz Bandwidth:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	905	7	917
2	907	8	919
3	909	9	921
4	911	10	923
5	913	11	925
6	915	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	905
Middle	915
Highest	925

For 4MHz Bandwidth:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	906	4	918
2	910	5	922
3	914	6	926

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	906
Middle	914
Highest	926

Antenna Information Detail▲:

Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Dipole	50	902-928	2 dBi

The Method of §15.203 Compliance:

- ☐ Antenna was permanently attached to the unit.
☒ Antenna use a unique type of connector to attach to the EUT.
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

1.1.3 Accessory Information

Accessory Description	Manufacturer	Model
/	/	/

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.			
Equipment Modifications:	No			
EUT Exercise Software:	ModemTestTool			
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲：				
Test Modes	Data Rate	Power Level Setting		
		Lowest	Middle	Highest
1MHz Bandwidth	MCS0	10	10	10
2MHz Bandwidth	MCS0	10	10	10
4MHz Bandwidth	MCS0	10	10	10
Note: The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the power and PSD across all data rates, bandwidths, and modulations.				

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386
Unknown	Debug board	Unknown	Unknown
Lenovo	Laptop	T460S	60PDTEK8
Lenovo	Adapter	ADLX45DLC3A	00HM613

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Power Cable	No	No	1	LISN1	DC Power Supply
Power Cable	No	No	1	DC Power Supply	EUT
Dupont thread	No	No	1	Debug board	USB TO TTL
Power Cable	No	No	1	Laptop	Adapter
Power Cable	No	No	1	Adapter	LISN2

1.2.4 Block Diagram of Test Setup

Conducted emissions:



Radiated emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	$\pm 5\%$
RF output power, conducted	$\pm 0.61\text{dB}$
Power Spectral Density, conducted	$\pm 0.61\text{ dB}$
Unwanted Emissions, radiated	9k~30MHz:4.12dB, 30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	$\pm 1.26\text{ dB}$
Temperature	$\pm 1^\circ\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 0.4\%$
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Compliant
§15.205, §15.209, §15.247(d)	Radiated Spurious emissions	Compliant
§15.247 (a)(2)	6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(d)	Conducted spurious emissions	Compliant
§15.203	Antenna Requirement	Compliant
§1.1307, §2.1091, §15.247 (i)	RF Exposure	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Radiated Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


3.2.2 EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 10 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz - 1000 MHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP/AV
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP/AV
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK

1GHz - 10GHz:

Pre-scan:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	5 kHz
	<98%	1MHz	$\geq 1/T$, not less than 5 kHz

Note: T is minimum transmission duration

Final measurement for emission identified during the pre-scan:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9–90 kHz, 110–490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

All emissions under the average limit and under the noise floor have not recorded in the report.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 dB Emission Bandwidth:

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup



3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


3.4 Maximum Conducted Output Power:

3.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.4.2 EUT Setup



3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.3

PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.


3.5 Maximum power spectral density

3.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


3.6 100 kHz Bandwidth of Frequency Band Edge:

3.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.6.2 EUT Setup



3.6.3 Test Procedure

According to ANSI C63.10-2013 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.


3.7 Conducted Spurious Emissions

3.7.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.7.2 EUT Setup



3.7.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.8 Duty Cycle:

3.8.1 EUT Setup



3.8.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.9 Antenna Requirement

3.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.9.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.

4. TEST DATA AND RESULTS

4.1 AC Line Conducted Emissions

Sample Number:	2T1H-1	Test Date:	2024/11/20
Test Site:	CE	Test Mode:	Transmitting (maximum output power mode, 2MHz Bandwidth High Channel)
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	25.5	Relative Humidity: (%)	49	ATM Pressure: (kPa)	101.1
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101132	2024/4/1	2025/3/31
R&S	EMI Test Receiver	ESR3	103104	2024/5/10	2025/5/9
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2024/1/15	2025/1/14
Audix	Test Software	E3	191218 (V9)	N/A	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Project No.: 2403Y20305E-RF
Tester: David Huang
Condition: IFBW:9 kHz Meas Time:0.025sec
Port: Line
Note: Transmitting



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.152	34.04	10.30	44.34	65.91	21.57	QP
2	0.152	10.50	10.30	20.80	55.91	35.11	Average
3	0.202	35.77	10.01	45.78	63.54	17.76	QP
4	0.202	35.05	10.01	45.06	53.54	8.48	Average
5	0.307	33.12	10.19	43.31	60.06	16.75	QP
6	0.307	32.64	10.19	42.83	50.06	7.23	Average
7	0.407	30.75	10.36	41.11	57.70	16.59	QP
8	0.407	27.68	10.36	38.04	47.70	9.66	Average
9	19.364	19.07	10.13	29.20	60.00	30.80	QP
10	19.364	15.53	10.13	25.66	50.00	24.34	Average
11	21.205	20.55	10.08	30.63	60.00	29.37	QP
12	21.205	18.14	10.08	28.22	50.00	21.78	Average

Project No.: 2403Y20305E-RF
Tester: David Huang
Condition: IFBW:9 kHz Meas Time:0.025sec
Port: neutral
Note: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.151	34.24	10.51	44.75	65.96	21.21	QP
2	0.151	10.24	10.51	20.75	55.96	35.21	Average
3	0.209	30.66	10.51	41.17	63.23	22.06	QP
4	0.209	28.45	10.51	38.96	53.23	14.27	Average
5	0.272	22.50	10.53	33.03	61.06	28.03	QP
6	0.272	4.14	10.53	14.67	51.06	36.39	Average
7	0.306	33.36	10.55	43.91	60.07	16.16	QP
8	0.306	32.88	10.55	43.43	50.07	6.64	Average
9	0.406	28.33	10.58	38.91	57.74	18.83	QP
10	0.406	24.32	10.58	34.90	47.74	12.84	Average
11	19.726	22.99	10.11	33.10	60.00	26.90	QP
12	19.726	20.51	10.11	30.62	50.00	19.38	Average

4.2 Radiated Spurious Emissions

4.2.1 9 kHz – 1 GHz

Sample Number:	2T1H-1	Test Date:	2024/11/22
Test Site:	966-2	Test Mode:	Transmitting (maximum output power mode, 2MHz Bandwidth High Channel)
Tester:	Roinin Fu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	58	ATM Pressure: (kPa)	101.6
-------------------	------	------------------------	----	---------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2023/12/1	2026/11/30
BACL	Loop Antenna	1313-1A	3110611	2023/12/4	2026/12/3
Daruikang	Coaxial Cable	BNC-JJ-RG58	C-0300-01	2024/1/11	2025/1/10
Daruikang	Coaxial Cable	BNC-JJ-RG58	C-0500-01	2024/1/11	2025/1/10
R&S	EMI Test Receiver	ESR3	102724	2024/2/29	2025/2/28
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0100-03	2023/12/4	2024/12/3
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0370-01	2023/12/4	2024/12/3
XQY	Coaxial Cable	XQY-CMR400UF-NJ-NJ-7M	24056379	2024/6/11	2025/6/10
Audix	Test Software	E3	191218 (V9)	N/A	N/A

*** Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

Project No.: 2403Y20305E-RF
Tester: Roinin Fu
Condition: RBW:0.3 kHz VBW:1 kHz SWT:0.1 sec
Polarization: Parallel
Note: Transmitting




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.009	29.37	35.60	64.97	128.42	63.45	Peak
2	0.015	30.28	31.87	62.15	123.95	61.80	Peak
3	0.024	27.32	27.52	54.84	119.97	65.13	Peak
4	0.036	22.83	23.34	46.17	116.45	70.28	Peak
5	0.108	21.76	14.26	36.02	106.92	70.90	Peak
6	0.135	27.49	13.02	40.51	105.01	64.50	Peak

Project No.: 2403Y20305E-RF
Tester: Roinin Fu
Condition: RBW:10 kHz VBW:30 kHz SWT:0.1 sec
Polarization: Parallel
Note: Transmitting




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.176	35.41	11.11	46.52	102.70	56.18	Peak
2	0.367	43.57	3.87	47.44	96.30	48.86	Peak
3	0.608	49.93	-0.28	49.65	71.89	22.24	Peak
4	1.178	46.30	-4.84	41.46	66.02	24.56	Peak
5	1.772	44.31	-6.95	37.36	69.54	32.18	Peak
6	2.371	43.13	-7.96	35.17	69.54	34.37	Peak

Project No.: 2403Y20305E-RF
Tester: Roinin Fu
Condition: RBW:0.3 kHz VBW:1 kHz SWT:0.1 sec
Polarization: Perpendicular
Note: Transmitting




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.009	30.29	35.12	65.41	128.08	62.67	Peak
2	0.015	31.85	32.03	63.88	124.15	60.27	Peak
3	0.024	26.95	27.62	54.57	120.04	65.47	Peak
4	0.029	24.03	24.95	48.98	118.26	69.28	Peak
5	0.053	20.71	20.07	40.78	113.17	72.39	Peak
6	0.135	27.64	13.02	40.66	105.01	64.35	Peak

Project No.: 2403Y20305E-RF
Tester: Roinin Fu
Condition: RBW:10 kHz VBW:30 kHz SWT:0.1 sec
Polarization: Perpendicular
Note: Transmitting




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.178	34.84	11.03	45.87	102.61	56.74	Peak
2	0.367	45.16	3.87	49.03	96.30	47.27	Peak
3	0.592	48.00	-0.10	47.90	72.13	24.23	Peak
4	1.172	45.03	-4.82	40.21	66.07	25.86	Peak
5	1.790	42.59	-7.02	35.57	69.54	33.97	Peak
6	2.371	42.08	-7.96	34.12	69.54	35.42	Peak

Project No.: 2403Y20305E-RF
Tester: Roinin Fu
Condition: RBW:0.3 kHz VBW:1 kHz SWT:0.1 sec
Polarization: Ground-parallel
Note: Transmitting




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.009	30.09	35.19	65.28	128.13	62.85	Peak
2	0.015	30.22	32.20	62.42	124.34	61.92	Peak
3	0.017	29.91	31.19	61.10	123.19	62.09	Peak
4	0.029	24.80	25.04	49.84	118.31	68.47	Peak
5	0.055	21.42	19.80	41.22	112.86	71.64	Peak
6	0.134	25.84	13.04	38.88	105.04	66.16	Peak

Project No.: 2403Y20305E-RF
Tester: Roinin Fu
Condition: RBW:10 kHz VBW:30 kHz SWT:0.1 sec
Polarization: Ground-parallel
Note: Transmitting




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.156	34.63	12.01	46.64	103.71	57.07	Peak
2	0.608	48.52	-0.28	48.24	71.89	23.65	Peak
3	1.223	45.55	-5.00	40.55	65.69	25.14	Peak
4	1.480	44.19	-5.92	38.27	64.00	25.73	Peak
5	1.790	43.10	-7.01	36.09	69.54	33.45	Peak
6	2.487	40.93	-8.03	32.90	69.54	36.64	Peak

Project No.: 2403Y20305E-RF
Tester: Roinin Fu
Condition: RBW:100 kHz VBW:300 kHz SWT:0.1 sec
Polarization: horizontal
Note: Transmitting



Project No.: 2403Y20305E-RF
Tester: Roinin Fu
Condition: RBW:100 kHz VBW:300 kHz SWT:0.1 sec
Polarization: vertical
Note: Transmitting



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	30.211	6.15	27.76	33.91	40.00	6.09	QP
2	39.854	12.82	20.64	33.46	40.00	6.54	Peak
3	71.330	18.23	14.48	32.71	40.00	7.29	QP
4	110.182	16.29	19.37	35.66	43.50	7.84	Peak
5	480.528	11.41	25.21	36.62	46.00	9.38	Peak
6	711.674	11.23	28.51	39.74	46.00	6.26	QP

4.2.2 1 – 10 GHz

Sample Number	2T1H-1	Test Date:	2024/11/12
Test Site:	966-1	Test Mode:	Transmitting
Tester:	Tao Zhu, Mack Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.7	Relative Humidity: (%)	65	ATM Pressure: (kPa)	100.8
----------------------	------	---------------------------	----	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	9912-5985	2023/12/6	2026/12/5
R&S	Spectrum Analyzer	FSV40	101591	2024/4/1	2025/3/31
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2024/1/15	2025/1/14
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2024/1/15	2025/1/14
BACL	Preamplifier	1313-A20M18G	4032311	2024/4/1	2025/3/31
Audix	Test Software	E3	191218 (V9)	N/A	N/A
JD	Multiplex Switch Test Control Set	DT7220SCU	DQ77925	2024/8/5	2025/8/4
JD	Filter Switch Unit	DT7220FSU	DQ77928	2024/8/5	2025/8/4

*** Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

1MHz Bandwidth

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				903.5	MHz		
1807.000	45.71	PK	H	1.53	47.24	74.00	26.76
1807.000	30.19	AV	H	1.53	31.72	54.00	22.28
1807.000	56.73	PK	V	1.53	58.26	74.00	15.74
1807.000	40.39	AV	V	1.53	41.92	54.00	12.08
2710.500	35.20	PK	H	4.13	39.33	74.00	34.67
2710.500	22.58	AV	H	4.13	26.71	54.00	27.29
2710.500	35.47	PK	V	4.13	39.60	74.00	34.40
2710.500	20.77	AV	V	4.13	24.90	54.00	29.10
3614.000	35.01	PK	H	7.00	42.01	74.00	31.99
3614.000	22.47	AV	H	7.00	29.47	54.00	24.53
3614.000	32.38	PK	V	7.00	39.38	74.00	34.62
3614.000	20.58	AV	V	7.00	27.58	54.00	26.42
Middle Channel:				914.5	MHz		
1829.000	48.62	PK	H	1.75	50.37	74.00	23.63
1829.000	32.47	AV	H	1.75	34.22	54.00	19.78
1829.000	59.27	PK	V	1.75	61.02	74.00	12.98
1829.000	42.87	AV	V	1.75	44.62	54.00	9.38
2743.500	34.66	PK	H	4.22	38.88	74.00	35.12
2743.500	21.82	AV	H	4.22	26.04	54.00	27.96
2743.500	35.23	PK	V	4.22	39.45	74.00	34.55
2743.500	22.41	AV	V	4.22	26.63	54.00	27.37
3658.000	34.28	PK	H	7.12	41.40	74.00	32.60
3658.000	21.59	AV	H	7.12	28.71	54.00	25.29
3658.000	34.25	PK	V	7.12	41.37	74.00	32.63
3658.000	21.17	AV	V	7.12	28.29	54.00	25.71

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
High Channel:				926.5	MHz		
1853.000	55.63	PK	H	1.99	57.62	74.00	16.38
1853.000	38.74	AV	H	1.99	40.73	54.00	13.27
1853.000	65.47	PK	V	1.99	67.46	74.00	6.54
1853.000	48.66	AV	V	1.99	50.65	54.00	3.35
2779.500	33.21	PK	H	4.21	37.42	74.00	36.58
2779.500	20.42	AV	H	4.21	24.63	54.00	29.37
2779.500	33.36	PK	V	4.21	37.57	74.00	36.43
2779.500	20.10	AV	V	4.21	24.31	54.00	29.69
3706.000	34.43	PK	H	7.33	41.76	74.00	32.24
3706.000	22.39	AV	H	7.33	29.72	54.00	24.28
3706.000	33.89	PK	V	7.33	41.22	74.00	32.78
3706.000	20.55	AV	V	7.33	27.88	54.00	26.12

2MHz Bandwidth

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				905	MHz		
1810.000	49.63	PK	H	1.56	51.19	74.00	22.81
1810.000	34.41	AV	H	1.56	35.97	54.00	18.03
1810.000	59.39	PK	V	1.56	60.95	74.00	13.05
1810.000	43.49	AV	V	1.56	45.05	54.00	8.95
2715.000	38.63	PK	H	4.13	42.76	74.00	31.24
2715.000	25.41	AV	H	4.13	29.54	54.00	24.46
2715.000	45.89	PK	V	4.13	50.02	74.00	23.98
2715.000	32.21	AV	V	4.13	36.34	54.00	17.66
3620.000	33.36	PK	H	7.02	40.38	74.00	33.62
3620.000	20.52	AV	H	7.02	27.54	54.00	26.46
3620.000	33.74	PK	V	7.02	40.76	74.00	33.24
3620.000	20.46	AV	V	7.02	27.48	54.00	26.52

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Middle Channel:				915	MHz		
1830.000	52.47	PK	H	1.76	54.23	74.00	19.77
1830.000	37.69	AV	H	1.76	39.45	54.00	14.55
1830.000	62.53	PK	V	1.76	64.29	74.00	9.71
1830.000	46.36	AV	V	1.76	48.12	54.00	5.88
2745.000	36.32	PK	H	4.21	40.53	74.00	33.47
2745.000	23.57	AV	H	4.21	27.78	54.00	26.22
2745.000	38.74	PK	V	4.21	42.95	74.00	31.05
2745.000	25.41	AV	V	4.21	29.62	54.00	24.38
3660.000	33.41	PK	H	7.13	40.54	74.00	33.46
3660.000	20.39	AV	H	7.13	27.52	54.00	26.48
3660.000	34.20	PK	V	7.13	41.33	74.00	32.67
3660.000	21.11	AV	V	7.13	28.24	54.00	25.76
High Channel:				925	MHz		
1850.000	58.41	PK	H	1.96	60.37	74.00	13.63
1850.000	43.68	AV	H	1.96	45.64	54.00	8.36
1850.000	67.19	PK	V	1.96	69.15	74.00	4.85
1850.000	48.63	AV	V	1.96	50.59	54.00	3.41
2775.000	34.88	PK	H	4.22	39.10	74.00	34.90
2775.000	22.49	AV	H	4.22	26.71	54.00	27.29
2775.000	36.32	PK	V	4.22	40.54	74.00	33.46
2775.000	23.41	AV	V	4.22	27.63	54.00	26.37
3700.000	33.69	PK	H	7.23	40.92	74.00	33.08
3700.000	20.54	AV	H	7.23	27.77	54.00	26.23
3700.000	33.74	PK	V	7.23	40.97	74.00	33.03
3700.000	21.46	AV	V	7.23	28.69	54.00	25.31


4MHz Bandwidth

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				906	MHz		
1812.000	44.38	PK	H	1.59	45.97	74.00	28.03
1812.000	32.14	AV	H	1.59	33.73	54.00	20.27
1812.000	56.65	PK	V	1.59	58.24	74.00	15.76
1812.000	44.21	AV	V	1.59	45.80	54.00	8.20
2718.000	40.78	PK	H	4.15	44.93	74.00	29.07
2718.000	28.58	AV	H	4.15	32.73	54.00	21.27
2718.000	43.75	PK	V	4.15	47.90	74.00	26.10
2718.000	31.29	AV	V	4.15	35.44	54.00	18.56
3624.000	34.22	PK	H	7.03	41.25	74.00	32.75
3624.000	22.46	AV	H	7.03	29.49	54.00	24.51
3624.000	35.02	PK	V	7.03	42.05	74.00	31.95
3624.000	23.11	AV	V	7.03	30.14	54.00	23.86
Middle Channel:				914	MHz		
1828.000	49.02	PK	H	1.74	50.76	74.00	23.24
1828.000	37.25	AV	H	1.74	38.99	54.00	15.01
1828.000	61.44	PK	V	1.74	63.18	74.00	10.82
1828.000	49.07	AV	V	1.74	50.81	54.00	3.19
2742.000	36.98	PK	H	4.21	41.19	74.00	32.81
2742.000	24.47	AV	H	4.21	28.68	54.00	25.32
2742.000	41.44	PK	V	4.21	45.65	74.00	28.35
2742.000	29.37	AV	V	4.21	33.58	54.00	20.42
3656.000	33.65	PK	H	7.12	40.77	74.00	33.23
3656.000	21.53	AV	H	7.12	28.65	54.00	25.35
3656.000	33.87	PK	V	7.12	40.99	74.00	33.01
3656.000	21.49	AV	V	7.12	28.61	54.00	25.39

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
High Channel:				926	MHz		
1852.000	54.01	PK	H	1.98	55.99	74.00	18.01
1852.000	40.30	AV	H	1.98	42.28	54.00	11.72
1852.000	65.44	PK	V	1.98	67.42	74.00	6.58
1852.000	49.30	AV	V	1.98	51.28	54.00	2.72
2778.000	35.24	PK	H	4.22	39.46	74.00	34.54
2778.000	23.11	AV	H	4.22	27.33	54.00	26.67
2778.000	37.51	PK	V	4.22	41.73	74.00	32.27
2778.000	25.46	AV	V	4.22	29.68	54.00	24.32
3704.000	33.78	PK	H	7.29	41.07	74.00	32.93
3704.000	21.69	AV	H	7.29	28.98	54.00	25.02
3704.000	34.43	PK	V	7.29	41.72	74.00	32.28
3704.000	22.54	AV	V	7.29	29.83	54.00	24.17


Worst radiation spurious emissions margin test plots for each mode

Project No.: 2403Y20305E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: horizontal
Note: SRD 1M High Channel 926.5MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1853.000	55.63	1.99	57.62	74.00	16.38	Peak
2	1853.000	38.74	1.99	40.73	54.00	13.27	Average
3	2779.500	33.21	4.21	37.42	74.00	36.58	Peak
4	2779.500	20.42	4.21	24.63	54.00	29.37	Average
5	3706.000	34.43	7.33	41.76	74.00	32.24	Peak
6	3706.000	22.39	7.33	29.72	54.00	24.28	Average

Project No.: 2403Y20305E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: vertical
Note: SRD 1M High Channel 926.5MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	1853.000	65.47	1.99	67.46	74.00	6.54	Peak
2	1853.000	48.66	1.99	50.65	54.00	3.35	Average
3	2779.500	33.36	4.21	37.57	74.00	36.43	Peak
4	2779.500	20.10	4.21	24.31	54.00	29.69	Average
5	3706.000	33.89	7.33	41.22	74.00	32.78	Peak
6	3706.000	20.55	7.33	27.88	54.00	26.12	Average

Project No.: 2403Y20305E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: horizontal
Note: SRD 2M High Channel 925MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	1850.000	58.41	1.96	60.37	74.00	13.63	Peak
2	1850.000	43.68	1.96	45.64	54.00	8.36	Average
3	2775.000	34.88	4.22	39.10	74.00	34.90	Peak
4	2775.000	22.49	4.22	26.71	54.00	27.29	Average
5	3700.000	33.69	7.23	40.92	74.00	33.08	Peak
6	3700.000	20.54	7.23	27.77	54.00	26.23	Average

Project No.: 2403Y20305E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: vertical
Note: SRD 2M High Channel 925MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	1850.000	67.19	1.96	69.15	74.00	4.85	Peak
2	1850.000	48.63	1.96	50.59	54.00	3.41	Average
3	2775.000	36.32	4.22	40.54	74.00	33.46	Peak
4	2775.000	23.41	4.22	27.63	54.00	26.37	Average
5	3700.000	33.74	7.23	40.97	74.00	33.03	Peak
6	3700.000	21.46	7.23	28.69	54.00	25.31	Average

Project No.: 2403Y20305E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: horizontal
Note: SRD 4M High Channel 926MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	1852.000	54.01	1.98	55.99	74.00	18.01	Peak
2	1852.000	40.30	1.98	42.28	54.00	11.72	Average
3	2778.000	35.24	4.22	39.46	74.00	34.54	Peak
4	2778.000	23.11	4.22	27.33	54.00	26.67	Average
5	3704.000	33.78	7.29	41.07	74.00	32.93	Peak
6	3704.000	21.69	7.29	28.98	54.00	25.02	Average

Project No.: 2403Y20305E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: vertical
Note: SRD 4M High Channel 926MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	1852.000	65.44	1.98	67.42	74.00	6.58	Peak
2	1852.000	49.30	1.98	51.28	54.00	2.72	Average
3	2778.000	37.51	4.22	41.73	74.00	32.27	Peak
4	2778.000	25.46	4.22	29.68	54.00	24.32	Average
5	3704.000	34.43	7.29	41.72	74.00	32.28	Peak
6	3704.000	22.54	7.29	29.83	54.00	24.17	Average

4.3 6 dB Emission Bandwidth:

Sample Number:	2T1H-1	Test Date:	2024/11/6
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.1	Relative Humidity: (%)	53	ATM Pressure: (kPa)	101.5
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	100147	2024/4/1	2025/3/31
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060302	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Test Mode	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
1MHz Bandwidth	903.5	0.865	≥ 0.5
	914.5	0.865	≥ 0.5
	926.5	0.861	≥ 0.5
2MHz Bandwidth	905	1.795	≥ 0.5
	915	1.795	≥ 0.5
	925	1.787	≥ 0.5
4MHz Bandwidth	906	3.628	≥ 0.5
	914	3.615	≥ 0.5
	926	3.654	≥ 0.5

1MHz Bandwidth:



2MHz Bandwidth:

4MHz Bandwidth:



4.4 Maximum Conducted Output Power:

Sample Number:	2T1H-1	Test Date:	2024/11/6
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.1	Relative Humidity: (%)	53	ATM Pressure: (kPa)	101.5
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Anritsu	Power Meter	ML2495A	1106009	2024/8/3	2025/8/2
Anritsu	Pulse Power Sensor	MA2411A	10780	2024/8/3	2025/8/2
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060302	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Mode	Test Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)	Limit (dBm)
1MHz Bandwidth	903.5	17.75	≤30
	914.5	17.93	≤30
	926.5	18.58	≤30
2MHz Bandwidth	905	18.01	≤30
	915	18.27	≤30
	925	18.74	≤30
4MHz Bandwidth	906	17.66	≤30
	914	17.76	≤30
	926	18.25	≤30

4.5 Maximum power spectral density:

Sample Number:	2T1H-1	Test Date:	2024/11/6
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.1	Relative Humidity: (%)	53	ATM Pressure: (kPa)	101.5
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	100147	2024/4/1	2025/3/31
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060302	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Test Mode	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
1MHz Bandwidth	903.5	-0.44	≤8.00
	914.5	-0.04	≤8.00
	926.5	0.1	≤8.00
2MHz Bandwidth	905	-6.3	≤8.00
	915	-5.78	≤8.00
	925	-5.64	≤8.00
4MHz Bandwidth	906	-8.98	≤8.00
	914	-8.75	≤8.00
	926	-8.57	≤8.00

1MHz Bandwidth:


Maximum power spectral density

Lowest Channel




Comment: ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 6.NOV.2024 13:17:58

Middle Channel




Comment: ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 6.NOV.2024 13:18:26

Highest Channel




Comment: ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 6.NOV.2024 13:15:57

2MHz Bandwidth:



4MHz Bandwidth:



4.6 100 kHz Bandwidth of Frequency Band Edge:

Sample Number:	2T1H-1	Test Date:	2024/11/6
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.1	Relative Humidity: (%)	53	ATM Pressure: (kPa)	101.5
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	100147	2024/4/1	2025/3/31
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060302	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Test Mode	Test Frequency (MHz)	Result (dB)	Limit (dB)
1MHz Bandwidth	903.5	49.34	≥ 20
	926.5	46.26	≥ 20
2MHz Bandwidth	905	46.84	≥ 20
	925	47.19	≥ 20
4MHz Bandwidth	906	33.78	≥ 20
	926	26.68	≥ 20


1MHz Bandwidth:



2MHz Bandwidth:



4MHz Bandwidth:



4.7 Conducted Spurious Emissions

Sample Number:	2T1H-1	Test Date:	2024/4/2
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	23.5	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101.5
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2025/3/31	2026/3/30
eastsheep	Coaxial Attenuator	2W-SMA-JK- 18G	21060302	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

1MHz Bandwidth:


Conducted Spurious Emissions

Lowest Channel




ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 2.APR.2025 16:21:23

Middle Channel



ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 2.APR.2025 16:25:53

Highest Channel




ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 2.APR.2025 16:32:41

2MHz Bandwidth:


Conducted Spurious Emissions

Lowest Channel




ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 2.APR.2025 17:04:18

Middle Channel



ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 2.APR.2025 16:42:45

Highest Channel




ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 2.APR.2025 16:40:15

4MHz Bandwidth:


Conducted Spurious Emissions

Lowest Channel




ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 2.APR.2025 17:01:05

Middle Channel



ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 2.APR.2025 16:59:15

Highest Channel



ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 2.APR.2025 16:57:43

4.8 Duty Cycle

Sample Number:	2T1H-1	Test Date:	2024/11/6
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	26.1	Relative Humidity: (%)	53	ATM Pressure: (kPa)	101.5
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	100147	2024/4/1	2025/3/31
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060302	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Mode	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)	VBW Setting (kHz)
1MHz Bandwidth	7.74	8.269	93.60	129	0.2
2MHz Bandwidth	3.558	4.519	78.73	281	0.3
4MHz Bandwidth	1.843	2.692	68.46	543	1


Duty Cycle

1MHz




Comment: ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 6.NOV.2024 13:24:13

2MHz



Comment: ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 6.NOV.2024 13:25:40

4MHz



Comment: ProjectNo.:2403Y20305E-RF Tester:LingLing Li
Date: 6.NOV.2024 13:49:11

5. RF EXPOSURE EVALUATION

5.1 Applicable Standard

FCC §15.247 (i) and subpart §1.1307

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

5.2 Procedure

According to §1.1307(b)(3)(i)

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

5.3 Measurement Result

Radio	Frequency (MHz)	$\lambda/2\pi$ (mm)	Distance (mm)	Exemption ERP (mW)	Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain (dBi)	ERP	
							dBm	mW
Wi-Fi HaLow	903.5-926.5	52.85	200	463	19	2.00	18.85	76.74

Note: The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.

Result: The device compliant the MPE-Based Exemption at 20cm distances.

6. EUT PHOTOGRAPHS

Please refer to the attachment 2403Y20305E-EXP EUT EXTERNAL PHOTOGRAPHS and
2403Y20305E-INP EUT INTERNAL PHOTOGRAPHS

7. TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2403Y20305E-00B-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====