



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

RF EXPOSURE EVALUATION

Applicant : WISOL CO., LTD

Applicant Address : 531-7, Gajang-ro, Osan-si, Gyeonggi-do, 18103, Korea

Kind of Product : AUDIO TRANSCEIVER

Equipment model name : ATM100

FCC ID : 2ABA2ATM100

Certification Number IC : 11534A-ATM100

Antenna type : PCB Antenna

Antenna Gain : ANT1, ANT2 : 4.8 dBi

* * MPE Calculations * *

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

$EIRP = P + G$	Where, P = Power input to the antenna (mW) G = Power gain of the antenna (dBi)
----------------	--

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain} / 10)$$

Power density at the specific separation:

$S = PG / (4R^2\pi)$	Where, S = Maximum power density (mW/cm ²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)
----------------------	---

The Maximum permissible exposure (MPE) for the general population is 1 mW/cm².

The power density at 20cm does not exceed the 1 mW/cm² limit.

Estimated safe separation:

$R = \sqrt{(PG / 4\pi)}$	Where, P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)
--------------------------	--



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea

Tel: +82-31-339-9970 Fax: +82-31-624-9501

www.e-ctk.com

P (dBm)	P (mW)	G (dBi)	S (mW/cm ²)	R (cm)
1.57	1.44	4.8	0.0009	20
