

FCC MPE REPORT

Certification

Applicant Name:
WISOL CO., LTD

Address:
531-7, Gajang-ro, Osan-si Gyeonggi-do, 18103, Korea

Date of Issue:

December 08, 2017

Test Site/Location:

HCT CO., LTD., 74,Seoicheon-ro 578beon-gil,Majang-myeo,Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-R-1712-E009

HCT FRN: 0005866421

ISED Registration Number: 5944A-5

FCC ID: 2ABA2SFM60R4

APPLICANT: WISOL CO., LTD

Model(s): SFM60R4

EUT Type: Sigfox Quad-mode module

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)



Report prepared by : Se Wook Park
Engineer of Telecommunication testing center



Approved by : Jong Seok Lee
Manager of Telecommunication testing center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1712-E009	December 08, 2017	- First Approval Report

RF Exposure Statement

1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3.RESULTS

3-1. Sigfox Mode

Max Peak output Power at antenna input terminal	23.500	dBm
Max Peak output Power at antenna input terminal	223.872	mW
Prediction distance	20.000	cm
Prediction frequency	920.1375	MHz
Antenna Gain(typical)	2.010	dBi
Antenna Gain(numeric)	1.589	-
Power density at prediction frequency(S)	0.0708	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.6134	mW/cm ²

3-2. Bluetooth LE Mode

Max Peak output Power at antenna input terminal	6.000	dBm
Max Peak output Power at antenna input terminal	3.981	mW
Prediction distance	20.000	cm
Prediction frequency	2480.000	MHz
Antenna Gain(typical)	4.440	dBi
Antenna Gain(numeric)	2.780	-
Power density at prediction frequency(S)	0.0022	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

Simultaneous transmission operations

1. The power density level at 20 cm is **0.0708 mW/cm²**, which is below the uncontrolled exposure limit of **0.6134 mW/cm²** at **Sigfox**.
2. The power density level at 20 cm is **0.0022 mW/cm²**, which is below the uncontrolled exposure limit of **1.0 mW/cm²** at **Bluetooth LE**.

->Simultaneous MPE 20cm is Sigfox(0.0708/1.0) + BT LE(0.0022/1.0) = 0.0730 mW/cm² < 0.6134 mW/cm²