

FCC CERTIFICATION TEST REPORT

FOR

Applicant	:	VIEVU, LLC
Address	:	105 W. John St, Seattle WA 98119, USA
Equipment under Test	:	Wearable Video Camera
Model No.	:	LE4 mini
FCC ID	:	2ABBNLE4MIN
Trade Mark	:	VIEVU
Manufacturer	:	VIEVU, LLC
Address	:	105 W. John St, Seattle WA 98119, USA

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808

Tel: +86-0769-22891499 [Http://www.dgddt.com](http://www.dgddt.com)

REPORT

TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results	5
2.	General test information.....	6
2.1.	Description of EUT	6
2.2.	Accessories of EUT.....	6
2.3.	Block diagram of EUT configuration for test	6
2.4.	Test environment conditions	7
2.5.	Deviations of test standard	7
2.6.	Test laboratory.....	7
2.7.	Measurement uncertainty	8
3.	6dB Bandwidth.....	9
3.1.	Test equipment	9
3.2.	Block diagram of test setup	9
3.3.	Limits	9
3.4.	Test Procedure.....	9
3.5.	Test Result.....	10
3.6.	Original test data	10
4.	Maximum Peak Output Power	12
4.1.	Test equipment	12
4.2.	Block diagram of test setup	12
4.3.	Limits	12
4.4.	Test Procedure.....	12
4.5.	Test Result.....	12
5.	Power Spectral Density	13
5.1.	Test equipment	13
5.2.	Block diagram of test setup	13
5.3.	Limits	13
5.4.	Test Procedure.....	13
5.5.	Test Result.....	14
5.6.	Original test data	14
6.	Emissions in non-restricted frequency bands	16
6.1.	Test equipment	16
6.2.	Block diagram of test setup	16
6.3.	Limits	16
6.4.	Test Procedure.....	16
6.5.	Test Result.....	17

6.6.	Original test data	17
7.	Emissions in restricted frequency bands	23
7.1.	Test equipment	23
7.2.	Block diagram of test setup	23
7.3.	Limit	25
7.4.	Test Procedure.....	26
7.5.	Test result	27
8.	Band Edge Compliance	31
8.1.	Test equipment	31
8.2.	Block diagram of test setup	31
8.3.	Limit	31
8.4.	Test Procedure.....	32
8.5.	Test result	32
9.	Power Line Conducted Emission	37
9.1.	Test equipment	37
9.2.	Block diagram of test setup	37
9.3.	Power Line Conducted Emission Limits(Class B).....	37
9.4.	Test Procedure.....	37
9.5.	Test Result.....	38
10.	Antenna Requirements	43
10.1.	Limit	43
10.2.	Result.....	43

TEST REPORT DECLARE

Applicant	:	VIEVU, LLC
Address	:	105 W. John St, Seattle WA 98119, USA
Equipment under Test	:	Wearable Video Camera
Model No	:	LE4 mini
FCC ID	:	2ABBNLE4MIN
Trade Mark	:	VIEVU
Manufacturer	:	VIEVU, LLC
Address	:	105 W. John St, Seattle WA 98119, USA

Test Standard Used: FCC Rules and Regulations Part 15 Subpart C: 2014

Test procedure used: ANSI C63.10:2013, ANSI C63.4:2014, KDB558074 D01 DTS Meas Guidance V03r02.

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	DDT-15Q0819-3E2		
Date of Test:	Aug. 20, 2015~Sep. 11, 2015	Date of Report:	Sep. 14, 2015

Prepared By:

Damon Hu

Damon Hu/Engineer

Approved By:



Kevin Feng/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

1. Summary of test results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
6dB Bandwidth	FCC Part 15: 15.247 KDB558074	PASS
Peak Output Power	FCC Part 15: 15.247 KDB558074	PASS
Power Spectral Density	FCC Part 15: 15.247 KDB558074	PASS
Emissions in non-restricted frequency bands	FCC Part 15: 15.247 KDB558074	PASS
Emissions in restricted frequency bands	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 ANSI C63.4:2014 KDB558074	PASS
Band Edge Compliance	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 ANSI C63.4:2014 KDB558074	PASS
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2013 ANSI C63.4:2014	PASS
Antenna requirement	FCC Part 15: 15.203	PASS
Note: N/A is an abbreviation for Not Applicable.		

2. General test information

2.1. Description of EUT

EUT* Name	:	Wearable Video Camera
Model Number	:	LE4 mini
EUT function description	:	Please reference user manual of this device
Power supply	:	DC 5V from external power adapter input AC 120V/60Hz and DC 3.7V from built-in battery
Radio Technology	:	IEEE802.11b
FCC Operation frequency	:	IEEE 802.11b: 2412MHz—2462MHz
Modulation	:	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)
Antenna Type	:	External non-standard SMA antenna, Maximum Gain: 0.5dBi
Date of Receipt	:	2015/8/19
Sample Type	:	Series production

Note1: EUT is the ab. of equipment under test.

Note2: EUT can powered from external power adapter and built-in battery, according exploration test, when built-in battery will have worse EMC performance, so all the final tests were performed built-in battery.

Channel information							
CH	Frequency	CH	Frequency	CH	Frequency	CH	Frequency
1	2412	5	2432	9	2452	/	/
2	2417	6	2437	10	2457	/	/
3	2422	7	2442	11	2462	/	/
4	2427	8	2447	/	/	/	/

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number or Type	EMC Compliance	SN
Adapter	HON-KWANG	HK-AP-050A100-US	FCC DOC	/
Adapter	SAMYA	PS30-AM501A-V	FCC DOC	/

2.3. Block diagram of EUT configuration for test



The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode as blow table.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
IEEE 802.11b	11	Low :CH1	2412
	11	Middle: CH6	2437
	11	High: CH11	2462
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.			

2.4. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

2.5. Deviations of test standard

No Deviation

2.6. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808 Tel: +86-0769-22891499 <http://www.dgddt.com>

FCC Registration Number: 270092 Industry Canada site registration number: 10288A-1

2.7. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	±1.1%
Peak Output Power(Conducted)(Spectrum analyzer)	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.38dB(3.6GHz ≤ f < 8GHz)
Peak Output Power(Conducted)(Power Sensor)	0.74dB
Power Spectral Density	0.74dB(10 MHz ≤ f < 3.6GHz);
	1.38dB(3.6GHz ≤ f < 8GHz)
Frequencies Stability	6.7×10^{-8} (Antenna couple method)
	5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.40dB(3.6GHz ≤ f < 8GHz)
	1.66dB(8GHz ≤ f < 22GHz)
Uncertainty for radio frequency (RBW<20KHz)	3×10^{-8}
Temperature	±0.4℃
Humidity	±2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	±3.14 dB (Antenna Polarize: V)
	±3.16 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-18GHz)	±4.14dB(1-6GHz)
	±4.46dB (6GHz-18Gz)
Uncertainty for Power line conduction emission test	2.44dB (150KHz-30MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. 6dB Bandwidth

3.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum analyzer	R&S	FSU	1166.1660.26	2014/10/25	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2014/10/25	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2014/10/25	1 Year

3.2. Block diagram of test setup



3.3. Limits

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 KHz

3.4. Test Procedure

- (1) Configure EUT and assistant system according clause 2.3 and 3.2
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.3.
- (4) Set the spectrum analyzer as follows:


RBW:	100KHz
VBW:	300KHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



3.5. Test Result

Mode	CH or Frequency	6dB bandwidth Result (MHz)	Mode	CH or Frequency	6dB bandwidth Result (MHz)
11b	CH1	10.02	/		
	CH6	9.94			
	CH11	9.21			
Limit: >500KHz			Conclusion: PASS		
Test Date : 2015/9/8			Test Engineer : Damon Hu		

3.6. Original test data

11b (6dB bandwidth):






4. Maximum Peak Output Power

4.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Power sensor	Agilent Technologies Inc	U2021XA	1457313	2014/10/25	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2014/10/25	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2014/10/25	1 Year

4.2. Block diagram of test setup



4.3. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.4. Test Procedure

- (1) Configure EUT and assistant system according clause 2.3 and 4.2
- (2) Connect each EUT's antenna output to power sensor by RF cable and attenuator
- (3) Configure EUT work in test mode as stated in clause 2.3.
- (4) Measure out the Average and PK output power of each antenna port
- (5) Add each antenna port's results to get the total output power of EUT.

4.5. Test Result

Mode: 11b		
CH	Type	Result (dBm)
CH1	PK	17.58
	Average	13.12
CH6	PK	18.56
	Average	14.41
CH11	PK	19.54
	Average	15.68
Limit: 30dBm		Conclusion: PASS
Test Date :2015/9/8		Test Engineer : Damon Hu

5. Power Spectral Density

5.1. Test equipment

Same with 3.1

5.2. Block diagram of test setup

Same with 3.2

5.3. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

5.4. Test Procedure

- (1) Configure EUT and assistant system according clause 2.3 and 5.2
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.3.
- (4) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	$3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


- (5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
- (6) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



5.5. Test Result

Mode: 11b		/	
CH	Result (dBm/30KHz)	/	/
CH1	2.96	/	/
CH6	5.80	/	/
CH11	4.30	/	/
Limit: 8dBm/3KHz		Conclusion: PASS	
Test Date : 2015/9/8		Test Engineer : Damon Hu	

5.6. Original test data

11b:





6. Emissions in non-restricted frequency bands

6.1. Test equipment

Same with 3.1

6.2. Block diagram of test setup

Same with 3.2

6.3. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

6.4. Test Procedure

- (1) Configure EUT and assistant system according clause 2.3 and 6.2
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.3.
- (4) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100KHz
VBW:	300KHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

- (5) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (6) Set the spectrum analyzer as follows:

RBW:	100KHz
VBW:	300KHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


- (7) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band



6.5. Test Result


EUT Set Mode	CH or Frequency	Measured Range	Result (dBm)	EUT Set Mode	CH or Frequency	Measured Range	Result (dBm)
11b	CH1	30MHz-1GHz	PASS	/	/	/	/
		1GHz-25GHz	PASS			/	/
		2.3GHz-2.43GHz	PASS			/	/
	CH6	30MHz-1GHz	PASS		/	/	/
		1GHz-25GHz	PASS			/	/
	CH11	30MHz-1GHz	PASS		/	/	/
		1GHz-25GHz	PASS			/	/
		2.45GHz-2.6GHz	PASS			/	/
Test Date : 2015/9/8				Test Engineer : Damon Hu			

6.6. Original test data


11b CH1:













11b CH6:





11b CH11:






7. Emissions in restricted frequency bands

7.1. Test equipment


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	EMI Test Receiver	R&S	ESU8	100316	2014/10/25	1 Year
2	Spectrum analyzer	R&S	FSU	1166.1660.26	2014/10/25	1 Year
3	Active Loop antenna	Schwarzbeck	FMZB 1519	1519-038	2014/11/01	1 Year
4	Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	2015/05/30	1 Year
5	Double Ridged Horn Antenna	R&S	HF907	100276	2014/11/01	1 Year
6	Pre-amplifier	A.H.	PAM-1840VH	562	2015/05/30	1 Year
7	RF Cable	R&S	R01	10403	2014/10/25	1 Year
8	RF Cable	R&S	R02	10512	2014/10/25	1 Year
9	Testing software	Audix	E3	6.111111	/	/

7.2. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9KHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

7.3. Limit

8.3.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

8.3.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(KHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(KHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1)The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz.Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer then that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30m}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30m/3m)$$

8.3.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

7.4. Test Procedure

- (1) EUT height should be 0.8m for below 1GHz at a semi - anechoic chamber while EUT height should be 1.5m for above 1GHz at full chamber or semi - anechoic chamber ground with absorbers.
- (2) Setup EUT and assistant system according clause 2.3 and 7.2
- (3) The antenna used as below table.

Test frequency range	Test antenna used	Measuring distance
9KHz-30MHz	Active Loop antenna	3 m
30MHz-1GHz	Trilog Broadband Antenna	3 m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3 m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1 m

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

- (4) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 25GHz:

- (a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

- (b) Change work frequency or channel of device if practicable.

- (c) Change modulation type of device if practicable.

- (d) Change power supply range from 85% to 115% of the rated supply voltage

- (e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 9KHz to 30MHz and 18GHz to 25GHz, so below final test was performed with frequency range from 30MHz to 18GHz.

- (5) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.

- (6) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz, 110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.
- (7) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9KHz-150KHz	200Hz
150KHz-30MHz	9KHz
30MHz-1GHz	120KHz

- (8) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure (according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure). Peak detector is used for Peak and AV measurement both.

7.5. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9KHz to 25GHz were comply with 15.209 limit.

Note1: According exploratory test no any obvious emission were detected from 9KHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in 11b, Tx CH6 mode.


Note3: For below test data, when the limit tabular marked “/” means this frequency point is the fundamental emission and no need comply with this limit.

Radiated Emission test (below 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **E:\2015 Report Data\15Q0819-3\RE.EM6**
Test Date : 2015-08-21 **Tested By** : Toby
EUT : Wearable Video Camera **Model Number** : LE4 mini
Power Supply : DC 3.7V from built-in Battery **Test Mode** : TX Mode
Condition : Temp:24.5'C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2014 VULB 9163/3m/VERTICAL
Memo :

Data: 13




Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	38.75	6.77	13.15	0.98	20.90	40.00	-19.10	QP	VERTICAL
2	49.01	3.85	14.50	1.06	19.41	40.00	-20.59	QP	VERTICAL
3	54.07	2.07	14.20	1.09	17.36	40.00	-22.64	QP	VERTICAL
4	68.39	5.38	10.15	1.19	16.72	40.00	-23.28	QP	VERTICAL
5	93.77	4.16	12.00	1.46	17.62	43.50	-25.88	QP	VERTICAL
6	287.99	5.16	14.25	2.67	22.08	46.00	-23.92	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **E:\2015 Report Data\15Q0819-3\RE.EM6**
Test Date : 2015-08-21 **Tested By** : Toby
EUT : Wearable Video Camera **Model Number** : LE4 mini
Power Supply : DC 3.7V from built-in Battery **Test Mode** : TX Mode
Condition : Temp:24.5'C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2014 VULB 9163/3m/HORIZONTAL
Memo :

Data: 14



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	42.01	1.98	14.00	1.01	16.99	40.00	-23.01	QP	HORIZONTAL
2	46.02	1.34	14.70	1.04	17.08	40.00	-22.92	QP	HORIZONTAL
3	54.26	1.81	14.20	1.09	17.10	40.00	-22.90	QP	HORIZONTAL
4	89.91	2.33	11.60	1.43	15.36	43.50	-28.14	QP	HORIZONTAL
5	94.43	4.54	12.00	1.46	18.00	43.50	-25.50	QP	HORIZONTAL
6	286.98	1.48	14.25	2.66	18.39	46.00	-27.61	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)

Freq (MHz)	Read level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector type	Polarization
11b CH1									
4824.00	36.24	35.42	29.32	8.09	50.43	74.00	-23.57	Peak	HORIZONTAL
7324.00	31.62	37.30	30.59	9.99	48.32	74.00	-25.68	Peak	HORIZONTAL
8412.00	32.18	37.67	31.59	10.45	48.71	74.00	-25.29	Peak	HORIZONTAL
10894.00	31.11	38.84	33.74	11.57	47.78	74.00	-26.22	Peak	HORIZONTAL
14413.00	30.71	41.46	35.18	13.27	50.26	74.00	-23.74	Peak	HORIZONTAL
16164.00	31.05	43.30	35.65	13.72	52.42	74.00	-21.58	Peak	HORIZONTAL
4824.00	47.41	35.42	29.32	8.09	61.60	74.00	-12.40	Peak	VERTICAL
4824.00	29.25	35.42	29.32	8.09	43.44	54.00	-10.56	Average	VERTICAL
6865.00	31.78	36.85	30.30	9.78	48.11	74.00	-25.89	Peak	VERTICAL
9432.00	31.37	37.97	32.57	10.77	47.54	74.00	-26.46	Peak	VERTICAL
13529.00	31.18	40.21	35.17	13.03	49.25	74.00	-24.75	Peak	VERTICAL
16504.00	31.08	43.70	36.06	13.77	52.49	74.00	-21.51	Peak	VERTICAL
11b CH6									
4924.00	44.13	35.59	29.34	8.16	58.54	74.00	-15.46	Peak	HORIZONTAL
4924.00	28.10	35.59	29.34	8.16	42.51	54.00	-11.49	Average	HORIZONTAL
8412.00	33.22	37.67	31.59	10.45	49.75	74.00	-24.25	Peak	HORIZONTAL
10044.00	33.04	38.42	32.94	11.11	49.63	74.00	-24.37	Peak	HORIZONTAL
16470.00	33.61	43.66	35.99	13.76	55.04	74.00	-18.96	Peak	HORIZONTAL
16470.00	19.05	43.66	35.99	13.76	40.48	54.00	-13.52	Average	HORIZONTAL
4924.00	49.09	35.59	29.34	8.16	63.50	74.00	-10.50	Peak	VERTICAL
4924.00	32.57	35.59	29.34	8.16	46.98	54.00	-7.02	Average	VERTICAL
7018.00	33.16	37.11	30.39	9.86	49.74	74.00	-24.26	Peak	VERTICAL
9177.00	33.49	37.87	32.40	10.64	49.60	74.00	-24.40	Peak	VERTICAL
11897.00	33.26	39.06	34.75	12.27	49.84	74.00	-24.16	Peak	VERTICAL
16436.00	33.54	43.62	35.99	13.75	54.92	74.00	-19.08	Peak	VERTICAL
16436.00	19.73	43.62	35.99	13.75	41.11	54.00	-12.89	Average	VERTICAL
11b CH11									
4874.00	46.49	35.51	29.33	8.14	60.81	74.00	-13.19	Peak	HORIZONTAL
4874.00	29.35	35.51	29.33	8.14	43.67	54.00	-10.33	Average	HORIZONTAL
8174.00	33.29	37.57	31.29	10.40	49.97	74.00	-24.03	Peak	HORIZONTAL
10112.00	33.16	38.45	32.97	11.13	49.77	74.00	-24.23	Peak	HORIZONTAL
14396.00	33.07	41.41	35.18	13.27	52.57	74.00	-21.43	Peak	HORIZONTAL
4874.00	52.04	35.51	29.33	8.14	66.36	74.00	-7.64	Peak	VERTICAL
4874.00	33.57	35.51	29.33	8.14	47.89	54.00	-6.11	Average	VERTICAL
7069.00	32.71	37.14	30.42	9.87	49.30	74.00	-24.70	Peak	VERTICAL
9415.00	33.77	37.97	32.57	10.77	49.94	74.00	-24.06	Peak	VERTICAL
11183.00	31.78	38.90	34.21	11.86	48.33	74.00	-25.67	Peak	VERTICAL
13699.00	32.52	40.24	34.95	13.10	50.91	74.00	-23.09	Peak	VERTICAL
Result: Pass									
Test Date : 2015/8/8					Test Engineer : Leo				


Note: Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

8. Band Edge Compliance

8.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	EMI Test Receiver	R&S	ESU8	100316	2014/10/25	1 Year
2	Spectrum analyzer	R&S	FSU	1166.1660.26	2014/10/25	1 Year
3	Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	2015/05/30	1 Year
4	Double Ridged Horn Antenna	R&S	HF907	100276	2014/11/01	1 Year
5	Pre-amplifier	A.H.	PAM0-0118	360	2014/11/01	1 Year
6	RF Cable	R&S	R01	10403	2014/10/25	1 Year
7	RF Cable	R&S	R02	10512	2014/10/25	1 Year
8	Testing software	Audix	E3	6.111111	/	/

8.2. Block diagram of test setup



8.3. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

8.4. Test Procedure

Same with clause 8.4 except change investigated frequency range from 2100MHz to 2450MHz and 2450MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worse case is shown in report.


8.5. Test result

PASS. (See below detailed test result)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **E:** \2015 Report Data\15Q0819-3\RE.EM6
Test Date : 2015-09-08 **Tested By** : Toby
EUT : Wearable Video Camera **Model Number** : LE4 mini
Power Supply : DC 3.7V from built-in Battery **Test Mode** : Tx mode 2412MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2014 HF907/3m/VERTICAL
Memo :

Data: 36



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2389.08	46.73	29.99	29.41	5.17	52.48	74.00	-21.52	Peak	VERTICAL
2	2390.00	41.49	29.99	29.41	5.17	47.24	74.00	-26.76	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **E:\2015 Report Data\15Q0819-3\RE.EM6**
Test Date : 2015-09-08 **Tested By** : Toby
EUT : Wearable Video Camera **Model Number** : LE4 mini
Power Supply : DC 3.7V from built-in Battery **Test Mode** : Tx mode 2412MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2014 HF907/3m/HORIZONTAL
Memo :

Data: 37



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2386.20	38.78	29.99	29.41	5.17	44.53	74.00	-29.47	Peak	HORIZONTAL
2	2390.00	34.50	29.99	29.41	5.17	40.25	74.00	-33.75	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **E:\2015 Report Data\15Q0819-3\RE.EM6**
Test Date : 2015-09-08 **Tested By** : Toby
EUT : Wearable Video Camera **Model Number** : LE4 mini
Power Supply : DC 3.7V from built-in Battery **Test Mode** : Tx mode 2462MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2014 HF907/3m/VERTICAL
Memo :

Data: 44



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	41.52	30.25	29.71	5.31	47.37	74.00	-26.63	Peak	VERTICAL
2	2487.52	44.84	30.30	29.71	5.31	50.74	74.00	-23.26	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **E:** \2015 Report Data\15Q0819-3\RE.EM6
Test Date : 2015-09-08 **Tested By** : Toby
EUT : Wearable Video Camera **Model Number** : LE4 mini
Power Supply : DC 3.7V from built-in Battery **Test Mode** : Tx mode 2462MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2014 HF907/3m/HORIZONTAL
Memo :

Data: 45



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	35.28	30.25	29.71	5.31	41.13	74.00	-32.87	Peak	HORIZONTAL
2	2491.04	37.71	30.30	29.73	5.31	43.59	74.00	-30.41	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

9. Power Line Conducted Emission

9.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Test Receiver	R&S	ESU8	100316	2014/10/25	1 Year
2	LISN 1	R&S	ENV216	101109	2014/10/25	1 Year
3	LISN 2	R&S	ESH2-Z5	100309	2014/10/25	1 Year
4	Pulse Limiter	R&S	ESH3-Z2	101242	2014/10/25	1 Year

9.2. Block diagram of test setup



9.3. Power Line Conducted Emission Limits(Class B)

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

9.4. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.3 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.3 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 KHz.

9.5. Test Result

PASS. (See below detailed test result)


Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “-----” means average detection; “-----” mans peak detection

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **E:\2015 report data\15Q0819-3\CE.EM6**
Test Date : 2015-08-21 **Tested By** : Damon
EUT : Wearable Video Camera **Model Number** : LE4 mini
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5'C,Humi:55%,
Press:100.1kPa **LISN** : 2014 ENV216/NEUTRAL
Memo : Adapter: HK-AP-050A100-US

Data: 10



Item (Mark)	Freq (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.26	13.36	9.60	0.02	9.85	32.83	51.47	-18.64	Average	NEUTRAL
2	0.26	18.58	9.60	0.02	9.85	38.05	61.47	-23.42	QP	NEUTRAL
3	0.41	15.16	9.61	0.03	9.86	34.66	47.73	-13.07	Average	NEUTRAL
4	0.41	20.74	9.61	0.03	9.86	40.24	57.73	-17.49	QP	NEUTRAL
5	0.48	12.71	9.61	0.03	9.87	32.22	46.32	-14.10	Average	NEUTRAL
6	0.48	19.20	9.61	0.03	9.87	38.71	56.32	-17.61	QP	NEUTRAL
7	0.53	12.83	9.61	0.04	9.87	32.35	46.00	-13.65	Average	NEUTRAL
8	0.53	19.00	9.61	0.04	9.87	38.52	56.00	-17.48	QP	NEUTRAL
9	0.78	13.60	9.61	0.08	9.86	33.15	46.00	-12.85	Average	NEUTRAL
10	0.78	18.48	9.61	0.08	9.86	38.03	56.00	-17.97	QP	NEUTRAL
11	1.43	9.47	9.61	0.06	9.87	29.01	46.00	-16.99	Average	NEUTRAL
12	1.43	14.71	9.61	0.06	9.87	34.25	56.00	-21.75	QP	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **E:\2015 report data\15Q0819-3\CE.EM6**
Test Date : 2015-08-21 **Tested By** : Damon
EUT : Wearable Video Camera **Model Number** : LE4 mini
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,
Press:100.1kPa **LISN** : 2014 ENV216/LINE
Memo : Adapter: HK-AP-050A100-US

Data: 12



Item	Freq	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.31	14.58	9.62	0.02	9.85	34.07	49.88	-15.81	Average	LINE
2	0.31	21.06	9.62	0.02	9.85	40.55	59.88	-19.33	QP	LINE
3	0.42	17.44	9.63	0.03	9.86	36.96	47.51	-10.55	Average	LINE
4	0.42	24.19	9.63	0.03	9.86	43.71	57.51	-13.80	QP	LINE
5	0.45	17.99	9.63	0.03	9.87	37.52	46.85	-9.33	Average	LINE
6	0.45	26.58	9.63	0.03	9.87	46.11	56.85	-10.74	QP	LINE
7	0.49	17.10	9.63	0.03	9.87	36.63	46.23	-9.60	Average	LINE
8	0.49	25.62	9.63	0.03	9.87	45.15	56.23	-11.08	QP	LINE
9	0.78	14.37	9.62	0.08	9.86	33.93	46.00	-12.07	Average	LINE
10	0.78	19.64	9.62	0.08	9.86	39.20	56.00	-16.80	QP	LINE
11	1.60	11.02	9.63	0.06	9.87	30.58	46.00	-15.42	Average	LINE
12	1.60	18.75	9.63	0.06	9.87	38.31	56.00	-17.69	QP	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **E:\2015 report data\15Q0819-3\CE.EM6**
Test Date : 2015-08-21 **Tested By** : Damon
EUT : Wearable Video Camera **Model Number** : LE4 mini
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5'C,Humi:55%,
Press:100.1kPa **LISN** : 2014 ENV216/LINE
Memo : Adapter: PS30-AM501A-V

Data: 14



Item (Mark)	Freq (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.15	16.37	9.61	0.01	9.84	35.83	56.00	-20.17	Average	LINE
2	0.15	27.58	9.61	0.01	9.84	47.04	66.00	-18.96	QP	LINE
3	0.17	19.36	9.61	0.01	9.84	38.82	55.12	-16.30	Average	LINE
4	0.17	28.67	9.61	0.01	9.84	48.13	65.12	-16.99	QP	LINE
5	0.41	18.81	9.63	0.03	9.86	38.33	47.73	-9.40	Average	LINE
6	0.41	26.70	9.63	0.03	9.86	46.22	57.73	-11.51	QP	LINE
7	0.64	13.33	9.62	0.06	9.86	32.87	46.00	-13.13	Average	LINE
8	0.64	20.01	9.62	0.06	9.86	39.55	56.00	-16.45	QP	LINE
9	0.78	15.06	9.62	0.08	9.86	34.62	46.00	-11.38	Average	LINE
10	0.78	22.34	9.62	0.08	9.86	41.90	56.00	-14.10	QP	LINE
11	1.41	10.97	9.62	0.05	9.87	30.51	46.00	-15.49	Average	LINE
12	1.41	17.73	9.62	0.05	9.87	37.27	56.00	-18.73	QP	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **E:\2015 report data\15Q0819-3\CE.EM6**
Test Date : 2015-08-21 **Tested By** : Damon
EUT : Wearable Video Camera **Model Number** : LE4 mini
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5'C,Humi:55%,
Press:100.1kPa **LISN** : 2014 ENV216/NEUTRAL
Memo : Adapter: PS30-AM501A-V

Data: 16



Item	Freq	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.15	16.91	9.60	0.01	9.84	36.36	56.00	-19.64	Average	NEUTRAL
2	0.15	22.52	9.60	0.01	9.84	41.97	66.00	-24.03	QP	NEUTRAL
3	0.17	18.36	9.60	0.01	9.84	37.81	55.21	-17.40	Average	NEUTRAL
4	0.17	26.20	9.60	0.01	9.84	45.65	65.21	-19.56	QP	NEUTRAL
5	0.25	13.90	9.59	0.02	9.85	33.36	51.86	-18.50	Average	NEUTRAL
6	0.25	19.27	9.59	0.02	9.85	38.73	61.86	-23.13	QP	NEUTRAL
7	0.41	15.40	9.61	0.03	9.86	34.90	47.73	-12.83	Average	NEUTRAL
8	0.41	22.20	9.61	0.03	9.86	41.70	57.73	-16.03	QP	NEUTRAL
9	0.53	13.19	9.61	0.04	9.87	32.71	46.00	-13.29	Average	NEUTRAL
10	0.53	19.09	9.61	0.04	9.87	38.61	56.00	-17.39	QP	NEUTRAL
11	0.78	13.77	9.61	0.08	9.86	33.32	46.00	-12.68	Average	NEUTRAL
12	0.78	18.31	9.61	0.08	9.86	37.86	56.00	-18.14	QP	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.

10. Antenna Requirements

10.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2. Result

The antennas used for this product are Reversed polarity non-standard unique antenna port and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0.5dBi.

END OF REPORT