



CINCH Systems

RF-CMDWS-319

**FCC 15.231:2017
Low Power Transmitter**

Report # CINC0010



NVLAP Lab Code: 200881-0



This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government of the United States of America. This Report shall not be reproduced, except in full without written approval of the laboratory.



CERTIFICATE OF TEST

Last Date of Test: July 28 2017

CINCH Systems

Model: RF-CMDWS-319

Radio Equipment Testing

Standards

Specification	Method
FCC 15.231:2017	ANSI C63.10:2013

Results

Method Clause	Test Description	Applied	Results	Comments
6.2	Powerline Conducted Emissions	No	N/A	Not required for a battery powered EUT.
6.5, 6.6	Field Strength of Fundamental	Yes	Pass	
6.5, 6.6	Spurious Radiated Emissions	Yes	Pass	
6.9.2	Occupied Bandwidth	Yes	Pass	
7.5	Duty Cycle	Yes	Pass	

Deviations From Test Standards

None

Approved By:

Tim O'Shea, General Manager

Product compliance is the responsibility of the client; therefore, the tests and equipment modes of operation represented in this report were agreed upon by the client, prior to testing. The results of this test pertain only to the sample(s) tested. The specific description is noted in each of the individual sections of the test report supporting this certificate of test. This report reflects only those tests from the referenced standards shown in the certificate of test. It does not include inspection or verification of labels, identification, marking or user information.

REVISION HISTORY



Revision Number		Description	Date	Page Number
00		None		

ACCREDITATIONS AND AUTHORIZATIONS



United States

FCC - Designated by the FCC as a Telecommunications Certification Body (TCB). Certification chambers, Open Area Test Sites, and conducted measurement facilities are listed with the FCC.

A2LA - Accredited by A2LA to ISO / IEC 17065 as a product certifier. This allows Element to certify transmitters to FCC and IC specifications.

NVLAP - Each laboratory is accredited by NVLAP to ISO 17025

Canada

ISED - Recognized by Innovation, Science and Economic Development Canada as a Certification Body (CB). Certification chambers and Open Area Test Sites are filed with ISED.

European Union

European Commission – Within Element, we have a EU Notified Body validated for the EMCD and RED Directives.

Australia/New Zealand

ACMA - Recognized by ACMA as a CAB for the acceptance of test data.

Korea

MSIP / RRA - Recognized by KCC's RRA as a CAB for the acceptance of test data.

Japan

VCCI - Associate Member of the VCCI. Conducted and radiated measurement facilities are registered.

Taiwan

BSMI – Recognized by BSMI as a CAB for the acceptance of test data.

NCC - Recognized by NCC as a CAB for the acceptance of test data.

Singapore

IDA – Recognized by IDA as a CAB for the acceptance of test data.

Israel

MOC – Recognized by MOC as a CAB for the acceptance of test data.

Hong Kong

OFCA – Recognized by OFCA as a CAB for the acceptance of test data.

Vietnam

MIC – Recognized by MIC as a CAB for the acceptance of test data.

SCOPE

For details on the Scopes of our Accreditations, please visit:


<http://portlandcustomer.element.com/ts/scope/scope.htm>

<http://gsi.nist.gov/global/docs/cabs/designations.html>

FACILITIES



California Labs OC01-13 41 Tesla Irvine, CA 92618 (949) 861-8918	Minnesota Labs MN01-08, MN10 9349 W Broadway Ave. Brooklyn Park, MN 55445 (612)-638-5136	New York Labs NY01-04 4939 Jordan Rd. Elbridge, NY 13060 (315) 554-8214	Oregon Labs EV01-12 22975 NW Evergreen Pkwy Hillsboro, OR 97124 (503) 844-4066	Texas Labs TX01-09 3801 E Plano Pkwy Plano, TX 75074 (469) 304-5255	Washington Labs NC01-05 19201 120 th Ave NE Bothell, WA 98011 (425)984-6600
NVLAP					
NVLAP Lab Code: 200676-0	NVLAP Lab Code: 200881-0	NVLAP Lab Code: 200761-0	NVLAP Lab Code: 200630-0	NVLAP Lab Code: 201049-0	NVLAP Lab Code: 200629-0
Innovation, Science and Economic Development Canada					
2834B-1, 2834B-3	2834E-1, 2834E-3	N/A	2834D-1, 2834D-2	2834G-1	2834F-1
BSMI					
SL2-IN-E-1154R	SL2-IN-E-1152R	N/A	SL2-IN-E-1017	SL2-IN-E-1158R	SL2-IN-E-1153R
VCCI					
A-0029	A-0109	N/A	A-0108	A-0201	A-0110
Recognized Phase I CAB for ACMA, BSMI, IDA, KCC/RRR, MIC, MOC, NCC, OFCA					
US0158	US0175	N/A	US0017	US0191	US0157



MEASUREMENT UNCERTAINTY



Measurement Uncertainty

When a measurement is made, the result will be different from the true or theoretically correct value. The difference is the result of tolerances in the measurement system that cannot be completely eliminated. To the extent that technology allows us, it has been our aim to minimize this error. Measurement uncertainty is a statistical expression of measurement error qualified by a probability distribution.


A measurement uncertainty estimation has been performed for each test per our internal quality document WP 342. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty (K=2) for each test is on each data sheet. Our measurement data meets or exceeds the measurement uncertainty requirements of the applicable specification; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for estimating measurement uncertainty are based upon ETSI TR 100 028 (or CISPR 16-4-2 as applicable), and are available upon request.

The following table represents the Measurement Uncertainty (MU) budgets for each of the tests that may be contained in this report.


Test	+ MU	- MU
Frequency Accuracy (Hz)	0.0007%	-0.0007%
Amplitude Accuracy (dB)	1.2 dB	-1.2 dB
Conducted Power (dB)	0.3 dB	-0.3 dB
Radiated Power via Substitution (dB)	0.7 dB	-0.7 dB
Temperature (degrees C)	0.7°C	-0.7°C
Humidity (% RH)	2.5% RH	-2.5% RH
Voltage (AC)	1.0%	-1.0%
Voltage (DC)	0.7%	-0.7%
Field Strength (dB)	5.2 dB	-5.2 dB
AC Powerline Conducted Emissions (dB)	2.4 dB	-2.4 dB

Test Setup Block Diagrams


Antenna Port Conducted Measurements



Near Field Test Fixture Measurements



Spurious Radiated Emissions





PRODUCT DESCRIPTION

Client and Equipment Under Test (EUT) Information

Company Name:	CINCH Systems
Address:	Suite 300 12075 43rd Street NE
City, State, Zip:	St. Michael, MN 55376
Test Requested By:	Jibril Aga
Model:	RF-CMDWS-319
First Date of Test:	July 28, 2017
Last Date of Test:	July 28, 2017
Receipt Date of Samples:	July 28, 2017
Equipment Design Stage:	Production
Equipment Condition:	No Damage
Purchase Authorization:	Verified

Information Provided by the Party Requesting the Test

Functional Description of the EUT:

Door and Window sensor containing a low power transmitter which operates at 319.5 MHz utilizing AM modulation (OOK)

Testing Objective:

To demonstrate compliance of the periodic radio to FCC 15.231(b) requirements.

CONFIGURATIONS



Configuration CINC0010- 1

EUT			
Description	Manufacturer	Model/Part Number	Serial Number
RF-CMDWS-319	CINCH Systems	RF-CMDWS-319	1234

Configuration CINC0010- 2

EUT			
Description	Manufacturer	Model/Part Number	Serial Number
RF-CMDWS-319 (CC CP)	CINCH Systems	RF-CMDWS-319	4321

MODIFICATIONS



Equipment Modifications

Item	Date	Test	Modification	Note	Disposition of EUT
1	7/28/2017	Duty Cycle	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Element following the test.
2	7/28/2017	Occupied Bandwidth	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Element following the test.
3	7/28/2017	Spurious Radiated Emissions	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Element following the test.
4	7/28/2017	Field Strength of Fundamental	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	Scheduled testing was completed.

FIELD STRENGTH OF FUNDAMENTAL



PSA-ESCI 2017.06.01

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data. The test data represents the configuration / operating mode/ model that produced the highest emission levels as compared to the specification limit.

MODES OF OPERATION

Transmitting at 319.5 MHz

POWER SETTINGS INVESTIGATED

Battery

CONFIGURATIONS INVESTIGATED

CINC0010 - 2

FREQUENCY RANGE INVESTIGATED

Start Frequency 319 MHz Stop Frequency 320 MHz

SAMPLE CALCULATIONS

Radiated Emissions: Field Strength = Measured Level + Antenna Factor + Cable Factor - Amplifier Gain + Distance Adjustment Factor + External Attenuation

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Filter - Low Pass	Micro-Tronics	LPM50004	LFK	9/22/2016	12 mo
Analyzer - Spectrum Analyzer	Agilent	N9010A	AFI	1/6/2017	12 mo
Cable	ESM Cable Corp.	Bilog Cables	MNH	12/1/2016	12 mo
Antenna - Biconilog	Teseq	CBL 6141B	AYD	1/6/2016	24 mo

MEASUREMENT BANDWIDTHS

Frequency Range (MHz)	Peak Data (kHz)	Quasi-Peak Data (kHz)	Average Data (kHz)
0.01 - 0.15	1.0	0.2	0.2
0.15 - 30.0	10.0	9.0	9.0
30.0 - 1000	100.0	120.0	120.0
Above 1000	1000.0	N/A	1000.0

TEST DESCRIPTION

The antennas to be used with the EUT were tested. The EUT was configured for continuous un-modulated CW operation at its single transmit frequency. The field strength of the transmit frequency was maximized by rotating the EUT, adjusting the measurement antenna height and polarization, and manipulating the EUT in 3 orthogonal planes (per ANSI C63.10:2013).

To derive average emission measurements, a duty cycle correction factor was utilized:

Duty Cycle = On time/100 milliseconds (or the period, whichever is less)

Where "On time" = $N_1L_1 + N_2L_2 + \dots$

Where N_1 is the number of type 1 pulses, L_1 is length of type 1 pulses, N_2 is the number of type 2 pulses, L_2 is the length of type 2 pulses, etc.

Therefore, Duty Cycle = $(N_1L_1 + N_2L_2 + \dots)/100\text{ms}$ or T , whichever is less. (Where T is the period of the pulse train.)

The measured values for the EUT's pulse train are as follows:

Period = 100 mSec

Pulsewidth of Type 1 Pulse = 450.5 uSec

Pulsewidth of Type 2 Pulse = 115.7 uSec

Number of Type 1 Pulses = 1

Number of Type 2 Pulses = 56

Duty Cycle = $20 \log [(1)(.4505) + (56)(.1157)/100] = -23.18 \text{ dB}$

The duty cycle correction factor of -23.18 dB was added to the peak readings to mathematically derive the average levels. Peak measurements were made with a resolution bandwidth of 100kHz and a video bandwidth of 300kHz.

FIELD STRENGTH OF FUNDAMENTAL




EmiRS 2017.07.11

PSA-ESCI 2017.06.01

Work Order:	CINC0010	Date:	07/28/17	
Project:	None	Temperature:	22.8 °C	
Job Site:	MN05	Humidity:	55.9% RH	
Serial Number:	1234	Barometric Pres.:	1022 mbar	
EUT:		RF-CMDWS-319		
Configuration:	2			
Customer:	CINCH Systems			
Attendees:	Jabril Aga			
EUT Power:	Battery			
Operating Mode:	Transmitting at 319.5MHz			
Deviations:	None			
Comments:	None			

Test Specifications				Test Method			
FCC 15.231:2017				ANSI C63.10:2013			
Run #	0	Test Distance (m)	3	Antenna Height(s)	1 to 4(m)	Results	Pass



Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Antenna Height (meters)	Azimuth (degrees)	Duty Cycle Correction Factor (dB)	External Attenuation (dB)	Polarity/ Transducer Type	Detector	Distance Adjustment (dB)	Adjusted (dBuV/m)	Spec. Limit (dBuV/m)	Compared to Spec. (dB)	Comments
319.505	69.2	19.9	1.0	211.0		0.0	Horz	PK	0.0	89.1	95.9	-6.8	EUT Horz
319.505	67.1	19.9	1.8	55.1		0.0	Vert	PK	0.0	87.0	95.9	-8.9	EUT On Side
319.510	66.7	19.9	1.8	55.1		0.0	Vert	PK	0.0	86.6	95.9	-9.3	EUT Vert
319.505	69.2	19.9	1.0	211.0	-23.2	0.0	Horz	AV	0.0	65.9	75.9	-10.0	EUT Horz
319.505	67.1	19.9	1.8	55.1	-23.2	0.0	Vert	AV	0.0	63.8	75.9	-12.1	EUT On Side
319.510	66.7	19.9	1.8	55.1	-23.2	0.0	Vert	AV	0.0	63.4	75.9	-12.5	EUT Vert
319.505	63.4	19.9	1.1	279.0		0.0	Horz	PK	0.0	83.3	95.9	-12.6	EUT On Side
319.505	62.9	19.9	1.0	208.0		0.0	Horz	PK	0.0	82.8	95.9	-13.1	EUT Vert
319.505	63.4	19.9	1.1	279.0	-23.2	0.0	Horz	AV	0.0	60.1	75.9	-15.8	EUT On Side
319.505	62.9	19.9	1.0	208.0	-23.2	0.0	Horz	AV	0.0	59.6	75.9	-16.3	EUT Vert
319.505	58.9	19.9	2.2	350.0		0.0	Vert	PK	0.0	78.8	95.9	-17.1	EUT Horz
319.505	58.9	19.9	2.2	350.0	-23.2	0.0	Vert	AV	0.0	55.6	75.9	-20.3	EUT Horz

SPURIOUS RADIATED EMISSIONS



PSA-ESCI 2017.06.01

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data. The test data represents the configuration / operating mode/ model that produced the highest emission levels as compared to the specification limit.

MODES OF OPERATION

Transmitting at 319.5MHz

POWER SETTINGS INVESTIGATED

Battery

CONFIGURATIONS INVESTIGATED

CINC0010 - 2

FREQUENCY RANGE INVESTIGATED

Start Frequency	30 MHz	Stop Frequency	8200 MHz
-----------------	--------	----------------	----------

SAMPLE CALCULATIONS

Radiated Emissions: Field Strength = Measured Level + Antenna Factor + Cable Factor - Amplifier Gain + Distance Adjustment Factor + External Attenuation

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Filter - Low Pass	Micro-Tronics	LPM50004	LFK	9/22/2016	12 mo
Analyzer - Spectrum Analyzer	Agilent	N9010A	AFI	1/6/2017	12 mo
Cable	ESM Cable Corp.	Double Ridge Guide Horn Cables	MNI	12/1/2016	12 mo
Amplifier - Pre-Amplifier	Miteq	AMF-3D-00100800-32-13P	AVT	2/14/2017	12 mo
Antenna - Double Ridge	ETS Lindgren	3115	AJA	6/23/2016	24 mo
Cable	ESM Cable Corp.	Bilog Cables	MNH	12/1/2016	12 mo
Amplifier - Pre-Amplifier	Miteq	AM-1616-1000	AVO	12/1/2016	12 mo
Antenna - Biconilog	Teseq	CBL 6141B	AYD	1/6/2016	24 mo

MEASUREMENT BANDWIDTHS

Frequency Range (MHz)	Peak Data (kHz)	Quasi-Peak Data (kHz)	Average Data (kHz)
0.01 - 0.15	1.0	0.2	0.2
0.15 - 30.0	10.0	9.0	9.0
30.0 - 1000	100.0	120.0	120.0
Above 1000	1000.0	N/A	1000.0

TEST DESCRIPTION

The highest gain antenna of each type to be used with the EUT was tested. The EUT was configured for the required transmit frequency in each operational band and the modes as showed in the data sheets.

For each configuration, the spectrum was scanned throughout the specified range as part of the exploratory investigation of the emissions. These "pre-scans" are not included in the report. Final measurements on individual emissions were then made and included in this test report.

The individual emissions from the EUT were maximized by rotating the EUT on a turntable, adjusting the position of the EUT and EUT antenna in three orthogonal axis, and adjusting the measurement antenna height and polarization (per ANSI C63.10). A preamp and high pass filter (and notch filter) were used for this test in order to provide sufficient measurement sensitivity.

Measurements were made with the required detectors and annotated on the data for each individual point using the following annotation:

QP = Quasi-Peak Detector

PK = Peak Detector

AV = RMS Detector

To derive average emission measurements, a duty cycle correction factor was utilized:

Duty Cycle = On time/100 milliseconds (or the period, whichever is less)

Where "On time" = $N1L1 + N2L2 + \dots$

Where N1 is the number of type 1 pulses, L1 is length of type 1 pulses, N2 is the number of type 2 pulses, L2 is the length of type 2 pulses, etc.

Therefore, Duty Cycle = $(N1L1 + N2L2 + \dots)/100\text{mS}$ or T, whichever is less. Where T is the period of the pulse train.

The measured values for the EUT's pulse train are as follows:

Period = 100 mSec

Pulsewidth of Type 1 Pulse = 450.5 uSec

Pulsewidth of Type 2 Pulse = 115.7 uSec

Number of Type 1 Pulses = 1

Number of Type 2 Pulses = 56

Duty Cycle = $20 \log [(1)(.4505) + (56)(.1157)/100] = -23.18 \text{ dB}$

The duty cycle correction factor of -23.18 dB was added to the peak readings to mathematically derive the average levels. Peak measurements were made with a resolution bandwidth of 100kHz and a video bandwidth of 300kHz for measurements at or below 1GHz. Above 1GHz, a resolution bandwidth of 1MHz and a video bandwidth of 3MHz was used.

SPURIOUS RADIATED EMISSIONS




EmiRS 2017.07.11

PSA-ESCI 2017.06.01

Work Order:	CINC0010	Date:	07/28/17	
Project:	None	Temperature:	22.8 °C	
Job Site:	MN05	Humidity:	55.9% RH	
Serial Number:	1234	Barometric Pres.:	1022 mbar	Tested by: Dustin Sparks, Chris Patterson
EUT:	RF-CMDWS-319			
Configuration:	2			
Customer:	CINCH Systems			
Attendees:	Jabril Aga			
EUT Power:	Battery			
Operating Mode:	Transmitting at 319.5MHz			
Deviations:	None			
Comments:	None			

Test Specifications	FCC 15.231:2017	Test Method	ANSI C63.10:2013
---------------------	-----------------	-------------	------------------

Run #	1	Test Distance (m)	3	Antenna Height(s)	1 to 4(m)	Results	Pass
-------	---	-------------------	---	-------------------	-----------	---------	------



Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Antenna Height (meters)	Azimuth (degrees)	Duty Cycle Correction Factor (dB)	External Attenuation (dB)	Polarity/ Transducer Type	Detector	Distance Adjustment (dB)	Adjusted (dBuV/m)	Spec. Limit (dBuV/m)	Compared to Spec. (dB)	Comments
1917.017	63.2	-3.5	1.0	78.0		0.0	Vert	PK	0.0	59.7	75.9	-16.2	EUT on side
1917.025	62.7	-3.5	1.2	239.0		0.0	Horz	PK	0.0	59.2	75.9	-16.7	EUT horizontal
1917.017	63.2	-3.5	1.0	78.0	-23.2	0.0	Vert	AV	0.0	36.5	55.9	-19.4	EUT on side
1917.025	62.7	-3.5	1.2	239.0	-23.2	0.0	Horz	AV	0.0	36.0	55.9	-19.9	EUT horizontal
958.535	30.6	13.3	2.9	250.9		10.0	Horz	PK	0.0	53.9	75.9	-22.0	EUT horizontal
1597.592	56.8	-5.1	1.0	286.0		0.0	Horz	PK	0.0	51.7	74.0	-22.3	EUT horizontal
1277.992	59.9	-6.3	1.6	134.1		0.0	Horz	PK	0.0	53.6	75.9	-22.3	EUT horizontal
639.015	36.2	7.0	1.3	159.1		10.0	Horz	PK	0.0	53.2	75.9	-22.7	EUT horizontal
639.010	36.1	7.0	1.0	333.0		10.0	Vert	PK	0.0	53.1	75.9	-22.8	EUT on side
639.020	35.0	7.0	1.0	265.9		10.0	Vert	PK	0.0	52.0	75.9	-23.9	EUT on side
1597.625	54.9	-5.1	1.0	0.0		0.0	Vert	PK	0.0	49.8	74.0	-24.2	EUT on side
639.030	34.4	7.0	1.2	340.0		10.0	Horz	PK	0.0	51.4	75.9	-24.5	EUT vertical
958.535	30.6	13.3	2.9	250.9	-23.2	10.0	Horz	AV	0.0	30.7	55.9	-25.2	EUT horizontal
1597.592	56.8	-5.1	1.0	286.0	-23.2	0.0	Horz	AV	0.0	28.5	54.0	-25.5	EUT horizontal

Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Antenna Height (meters)	Azimuth (degrees)	Duty Cycle Correction Factor (dB)	External Attenuation (dB)	Polarity/ Transducer Type	Detector	Distance Adjustment (dB)	Adjusted (dBuV/m)	Spec. Limit (dBuV/m)	Compared to Spec. (dB)	Comments
1277.992	59.9	-6.3	1.6	134.1	-23.2	0.0	Horz	AV	0.0	30.4	55.9	-25.5	EUT horizontal
639.015	36.2	7.0	1.3	159.1	-23.2	10.0	Horz	AV	0.0	30.0	55.9	-25.9	EUT horizontal
639.010	36.1	7.0	1.0	333.0	-23.2	10.0	Vert	AV	0.0	29.9	55.9	-26.0	EUT on side
958.530	26.6	13.3	1.0	58.1		10.0	Vert	PK	0.0	49.9	75.9	-26.0	EUT on side
639.020	32.1	7.0	4.0	245.0		10.0	Horz	PK	0.0	49.1	75.9	-26.8	EUT on side
639.020	35.0	7.0	1.0	265.9	-23.2	10.0	Vert	AV	0.0	28.8	55.9	-27.1	EUT on side
1597.625	54.9	-5.1	1.0	0.0	-23.2	0.0	Vert	AV	0.0	26.6	54.0	-27.4	EUT on side
639.030	34.4	7.0	1.2	340.0	-23.2	10.0	Horz	AV	0.0	28.2	55.9	-27.7	EUT vertical
1278.042	54.3	-6.3	1.0	139.0		0.0	Vert	PK	0.0	48.0	75.9	-27.9	EUT on side
958.530	26.6	13.3	1.0	58.1	-23.2	10.0	Vert	AV	0.0	26.7	55.9	-29.2	EUT on side
639.020	32.1	7.0	4.0	245.0	-23.2	10.0	Horz	AV	0.0	25.9	55.9	-30.0	EUT on side
639.000	28.9	7.0	1.0	45.0		10.0	Vert	PK	0.0	45.9	75.9	-30.0	EUT horizontal
1278.042	54.3	-6.3	1.0	139.0	-23.2	0.0	Vert	AV	0.0	24.8	55.9	-31.1	EUT on side
639.000	28.9	7.0	1.0	45.0	-23.2	10.0	Vert	AV	0.0	22.7	55.9	-33.2	EUT horizontal

OCCUPIED BANDWIDTH



XMit 2017.02.08

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Cal. Due
Filter - Low Pass	Micro-Tronics	LPM50004	LFK	9/22/2016	9/22/2017
Amplifier - Pre-Amplifier	Miteq	AM-1616-1000	AVO	12/1/2016	12/1/2017
Cable	ESM Cable Corp.	Bilog Cables	MNH	12/1/2016	12/1/2017
Antenna - Biconilog	Teseq	CBL 6141B	AYD	1/6/2016	1/6/2018
Analyzer - Spectrum Analyzer	Agilent	N9010A	AFI	1/6/2017	1/6/2018

TEST DESCRIPTION

The measurement was made in a radiated configuration of the fundamental with the carrier fully maximized for its highest radiated power. The EUT was transmitting at its maximum data rate.

The 20 dB occupied bandwidth is required to be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz.

OCCUPIED BANDWIDTH



XMM 2017.02.08


EUT: RF-CMDWS-319		Work Order: CINC0010	
Serial Number: 1234		Date: 07/28/17	
Customer: CINCH Systems		Temperature: 22.8 °C	
Attendees: Jabril Aga		Humidity: 55.6% RH	
Project: None		Barometric Pres.: 1022 mbar	
Tested by: Dustin Sparks, Chris Patterson		Power: Battery	
Job Site: MN07			
TEST SPECIFICATIONS		Test Method	
FCC 15.231:2017		ANSI C63.10:2013	
COMMENTS			
Transmitting at 319.5MHz			
DEVIATIONS FROM TEST STANDARD			
None			
Configuration #	1	Signature <i>Dustin Sparks</i>	
		Value (kHz)	Limit (kHz)
319.5		34.09	798.8
			Result
			Pass

OCCUPIED BANDWIDTH



XMM 2017.02.08

319.5						
				Value (kHz)	Limit (kHz)	Result
				34.09	798.8	Pass



DUTY CYCLE



XMIT 2017.02.08

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Cal. Due
Filter - Low Pass	Micro-Tronics	LPM50004	LFK	9/22/2016	9/22/2017
Analyzer - Spectrum Analyzer	Agilent	N9010A	AFI	1/6/2017	1/6/2018
Amplifier - Pre-Amplifier	Miteq	AM-1616-1000	AVO	12/1/2016	12/1/2017
Cable	ESM Cable Corp.	Bilog Cables	MNH	12/1/2016	12/1/2017
Antenna - Biconilog	Teseq	CBL 6141B	AYD	1/6/2016	1/6/2018

TEST DESCRIPTION

The measurement was made in a radiated configuration of the fundamental with the carrier fully maximized for its highest radiated power. For software controlled or pre-programmed devices, the manufacturer shall declare the duty cycle class or classes for the equipment under test. For manually operated or event dependant devices, with or without software controlled functions, the manufacturer shall declare whether the device once triggered, follows a pre-programmed cycle, or whether the transmission is constant until the trigger is released or manually reset. The manufacturer shall also give a description of the application for the device and include a typical usage pattern. The typical usage pattern as declared by the manufacturer shall be used to determine the duty cycle and hence the duty class.

Where an acknowledgement is required, the additional transmitter on-time shall be included and declared by the manufacturer.

To derive average emission measurements, a duty cycle correction factor was utilized:

Duty Cycle = On time/100 milliseconds (or the period, whichever is less)

Where "On time" = $N1L1 + N2L2 + \dots$

Where N1 is the number of type 1 pulses, L1 is length of type 1 pulses, N2 is the number of type 2 pulses, L2 is the length of type 2 pulses, etc.

Therefore, Duty Cycle = $(N1L1 + N2L2 + \dots)/100\text{mS}$ or T, whichever is less. (Where T is the period of the pulse train.)

The measured values for the EUT's pulse train are as follows:

Period = 100 mSec
Pulsewidth of Type 1 Pulse = 450.5 uSec
Pulsewidth of Type 2 Pulse = 115.7 uSec
Number of Type 1 Pulses = 1
Number of Type 2 Pulses = 56

Duty Cycle = $20 \log [(1)(.4505) + (56)(.1157)/100] = -23.18 \text{ dB}$

The duty cycle correction factor of -23.18 dB was added to the peak readings to mathematically derive the average levels. Peak measurements were made with a resolution bandwidth of 100kHz and a video bandwidth of 300kHz.

DUTY CYCLE



XMI 2017.02.08


EUT: RF-CMDWS-319		Work Order: CINC0010	
Serial Number: 1234		Date: 07/28/17	
Customer: CINCH Systems		Temperature: 23.8 °C	
Attendees: Jabril Aga		Humidity: 52.9% RH	
Project: None		Barometric Pres.: 1021 mbar	
Tested by: Dustin Sparks, Chris Patterson		Power: Battery	
		Job Site: MN05	
TEST SPECIFICATIONS			
FCC 15.231:2017		Test Method	
		0	
COMMENTS			
Transmitting at 319.5MHz			
DEVIATIONS FROM TEST STANDARD			
None			
Configuration #	1	Signature <i>Dustin Sparks</i>	
		Value	Limit
1 Sec		See Test Description	N/A
10 Sec		See Test Description	N/A
20 mSec		See Test Description	N/A
		Result	
		N/A	N/A
		N/A	N/A

DUTY CYCLE




XMI 2017.02.08

1 Sec				
	Value	Limit	Result	
	See Test Description	N/A	N/A	



10 Sec				
	Value	Limit	Result	
	See Test Description	N/A	N/A	



DUTY CYCLE



XMM 2017.02.08

20 mSec		
	Value	Limit
	See Test Description	N/A
		Result
		N/A

