TEST REPORT

Report No.:	8427EU010907W4
Applicant:	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address:	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.
Product Name:	Smart Digital Calendar
Model No.:	FA3269T
Trademark:	N/A
FCC ID:	2ABC5-E0129
Test Standard(s):	47 CFR Part 15 Subpart E
Test Result:	Pass
Date of Receipt:	Jan. 09, 2026
Test Date:	Jan. 09, 2026 – Feb. 05, 2026
Date of Issue:	Feb. 06, 2026

ISSUED BY:

SHENZHEN EU TESTING LABORATORY LIMITED

SHENZHEN EU TESTING LABORATORY LIMITED APPROVED

Prepared by:

Mikey Zhu

Mikey Zhu/ Engineer

Reviewed and Approved by:

Sally Zhang

Sally Zhang/ Manager

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China

Website: www.eu-test.com

Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Revision Record

Report Version	Issued Date	Description	Status
V0	Feb. 06, 2026	Original	Valid

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Table of Contents

1 COVER PAGE 1
2 GENERAL INFORMATION 5
2.1 APPLICANT INFORMATION 5
2.2 MANUFACTURER INFORMATION 5
2.3 FACTORY INFORMATION 5
2.4 GENERAL DESCRIPTION OF E.U.T. 5
2.5 TECHNICAL INFORMATION OF E.U.T. 6
3 TEST SUMMARY 11
3.1 TEST STANDARD 11
3.2 TEST VERDICT 11
3.3 TEST LABORATORY 12
4 TEST CONFIGURATION 13
4.1 TEST ENVIRONMENT 13
4.2 TEST EQUIPMENT 13
4.3 DESCRIPTION OF SUPPORT UNIT 14
4.4 TEST MODE 14
4.5 DESCRIPTION OF CALCULATION 14
4.6 MEASUREMENT UNCERTAINTY 15
4.7 DEVIATION FROM STANDARDS 15
4.8 ABNORMALITIES FROM STANDARD CONDITION 15
5 TEST ITEMS 16
5.1 ANTENNA REQUIREMENT 16
5.1.1 Test Requirement 16
5.1.2 Antenna Anti-Replacement Construction 16
5.1.3 Antenna Gain 16
5.2 CONDUCTED EMISSION AT AC POWER LINE 17
5.2.1 Test Requirement 17
5.2.2 Test Setup Diagram 17
5.2.3 Test Procedure 17
5.2.4 Test Data 17
5.3 EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH 20
5.3.1 Test Requirement 20
5.3.2 Test Setup Diagram 20
5.3.3 Test Procedure 21
5.3.4 Test Data 21
5.4 MAXIMUM CONDUCTED OUTPUT POWER 22
5.4.1 Test Requirement 22
5.4.2 Test Setup Diagram 23
5.4.3 Test Procedure 23
5.4.4 Test Data 24
5.5 POWER SPECTRAL DENSITY 25
5.5.1 Test Requirement 25
5.5.2 Test Setup Diagram 26
5.5.3 Test Procedure 26
5.5.4 Test Data 26
5.6 BAND EDGE EMISSIONS (RESTRICTED FREQUENCY BANDS) 27
5.6.1 Test Requirement 27
5.6.2 Test Setup Diagram 28
5.6.3 Test Procedure 29
5.6.4 Test Data 29

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.7 UNDESIRABLE EMISSIONS 30
5.7.1 Test Requirement 57
5.7.2 Test Setup Diagram 58
5.7.3 Test Procedure 59
5.7.4 Test Data 60
5.8 FREQUENCY STABILITY 69
5.8.1 Test Requirement 69
5.8.2 Test Setup Diagram 69
5.8.3 Test Procedure 69
5.8.4 Test Data 70
ANNEX A TEST SETUP PHOTOS 71
ANNEX B EXTERNAL PHOTOS 71
ANNEX C INTERNAL PHOTOS 71
ANNEX G TEST DATA 71

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

2 General Information

2.1 Applicant Information

Applicant	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.

2.2 Manufacturer Information

Manufacturer	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.

2.3 Factory Information

Factory	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.

2.4 General Description of E.U.T.

Product Name	Smart Digital Calendar
Model No. Under Test	FA3269T
List Model No.	N/A
Description of Model differentiation	N/A
Rating(s)	Adapter power supply: 12V⎓5A (Adapter Input: 100-240V~, 50/60Hz, 1.5A; Output: 12.0V⎓5.0A, 60.0W)
Adapter	Model No.: ADS-60FW-12N 12060EPCU Input: 100-240V~, 50/60Hz, 1.5A Output: 12.0V⎓5.0A, 60.0W Manufacturer: SHENZHEN HONOR ELECTRONIC CO., LTD.
Product Type	☐ Mobile ☐ Portable ☒ Fix Location
Test Sample No.	-1/2(Normal Sample), -2/2(Engineering Sample)
Hardware Version	R155-V2.0
Software Version	N/A
Remark	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.5 Technical Information of E.U.T.

Network and Wireless Connectivity	Bluetooth (BDR+EDR+BLE) WiFi 2.4G: 802.11b, 802.11g, 802.11n(HT20/40), 802.11ax(HEW20/40) WiFi 5G: 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80) and 802.11ax(HEW20/40/80) U-NII-1/3

The requirement for the following technical information of the EUT was tested in this report:

Technology	**WiFi 5G**
Operation Mode	☒ a ☒ n(HT20) ☒ n(HT40) ☒ ac(VHT20) ☒ ac(VHT40) ☒ ac(VHT80) ☐ ac(VHT160) ☒ ax(HEW20) ☒ ax(HEW40) ☒ ax(HEW80) ☐ ax(HEW160)
Operating Frequency	U-NII-1: 5150 MHz to 5250 MHz U-NII-3: 5725 MHz to 5850 MHz
Modulation Technology	OFDM, OFDMA
Function	☒ Client device ☐ Master device
Modulation Type	☒ 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) ☒ 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) ☒ 802.11ac: OFDM (64QAM, 16QAM, QPSK, BPSK, 256QAM) ☒ 802.11ax: OFDMA (4096QAM, 1024QAM, 256QAM, 64QAM, 16QAM, BPSK, QPSK)
Transfer Rate (Mbps) (Single RF path)	☒ 802.11a: 54/ 48/ 36/ 24/ 18/ 12/ 9/ 6 Mbps ☒ 802.11n: up to 150 Mbps ☒ 802.11ac: up to VHT-MCS9 ☒ 802.11ax up to 1201 Mbps
Antenna System (eg., MIMO, Smart Antenna)	N/A
Categorization as Correlated or Completely Uncorrelated	N/A
Antenna Type	FPC Antenna
Antenna Gain(Peak)	U-NII-1: 5150 MHz to 5250 MHz: 2.24 dBi U-NII-3: 5725 MHz to 5850 MHz: 2.24 dBi
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

All channels were listed on the following table:

20 MHz Bandwidth		40 MHz Bandwidth		80 MHz Bandwidth	
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
36	**5180**	**38**	**5190**	**42**	**5210**
40	**5200**	**46**	**5230**	**155**	**5775**
44	5220	**151**	**5755**	/	/
48	**5240**	**159**	**5795**	/	/
149	**5745**	/	/	/	/
153	5765	/	/	/	/
157	**5785**	/	/	/	/
161	5805	/	/	/	/
165	**5825**	/	/	/	/

802.11ax RU configuration table							
Mode	Full RU (SU)	RU_26	RU_52	RU_106	RU_242	RU_484	RU_996
802.11ax (HEW20)	√	--	--	--	--	--	--
802.11ax (HEW40)	√	--	--	--	--	--	--
802.11ax (HEW80)	√	--	--	--	--	--	--

The Lowest frequency, the middle frequency and the highest frequency of channel were selected to perform the test, and the selected channels see below:

✧ **For 802.11a/n(HT20)/ac(VHT20)/ax(HEW20)**

U-NII-1 (5150 - 5250 MHz)			U-NII-3 (5725 - 5850 MHz)		
Channel Number	Channel	Frequency (MHz)	Channel Number	Channel	Frequency (MHz)
36	Low	5180	149	Low	5745
40	Mid	5200	157	Mid	5785
48	High	5240	165	High	5825

✧ **For 802.11n(HT40)/ac(VHT40)/ax(HEW40)**

U-NII-1 (5150 - 5250 MHz)			U-NII-3 (5725 - 5850 MHz)		
Channel Number	Channel	Frequency (MHz)	Channel Number	Channel	Frequency (MHz)
38	Low	5190	151	Low	5755
46	High	5230	159	High	5795

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

✧ **For 802.11 ac(VHT80)/ax(HEW80)**

U-NII-1 (5150 - 5250 MHz)			U-NII-3 (5725 - 5850 MHz)		
Channel Number	Channel	Frequency (MHz)	Channel Number	Channel	Frequency (MHz)
42	Mid	5210	155	Mid	5775

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Test Items	Mode	Data Rate	Modulation Type	U-NII-1	U-NII-3
				Channel	Channel
RF Output Power	11a	6	BPSK	48/44/36	165/157/149
	11n(20 MHz)	6.5		48/44/36	165/157/149
	11n(40 MHz)	13.5		46/38	159/151
	11ac(20 MHz)	6.5		48/44/36	165/157/149
	11ac(40 MHz)	13.5		46/38	159/151
	11ac(80 MHz)	29.3		42	155
	11ax(20 MHz)	4		48/44/36	165/157/149
	11ax(40 MHz)	8		46/38	159/151
	11ax(80 MHz)	17		42	155
Emission Bandwidth & 99% Occupied Bandwidth	11a	6	BPSK	48/44/36	165/157/149
	11n(20 MHz)	6.5		48/44/36	165/157/149
	11n(40 MHz)	13.5		46/38	159/151
	11ac(20 MHz)	6.5		48/44/36	165/157/149
	11ac(40 MHz)	13.5		46/38	159/151
	11ac(80 MHz)	29.3		42	155
	11ax(20 MHz)	4		48/44/36	165/157/149
	11ax(40 MHz)	8		46/38	159/151
	11ax(80 MHz)	17		42	155
6 dB bandwidth	11a	6	BPSK	48/44/36	165/157/149
	11n(20 MHz)	6.5		48/44/36	165/157/149
	11n(40 MHz)	13.5		46/38	159/151
	11ac(20 MHz)	6.5		48/44/36	165/157/149
	11ac(40 MHz)	13.5		46/38	159/151
	11ac(80 MHz)	29.3		42	155
	11ax(20 MHz)	4		48/44/36	165/157/149
	11ax(40 MHz)	8		46/38	159/151
	11ax(80 MHz)	17		42	155
Power Spectral Density	11a	6	BPSK	48/44/36	165/157/149
	11n(20 MHz)	6.5		48/44/36	165/157/149
	11n(40 MHz)	13.5		46/38	159/151
	11ac(20 MHz)	6.5		48/44/36	165/157/149
	11ac(40 MHz)	13.5		46/38	159/151
	11ac(80 MHz)	29.3		42	155
	11ax(20 MHz)	4		48/44/36	165/157/149
	11ax(40 MHz)	8		46/38	159/151
	11ax(80 MHz)	17		42	155
Band Edge (Restricted-band)	11a	6	BPSK	48/44/36	165/157/149
	11n(20 MHz)	6.5		48/44/36	165/157/149
	11n(40 MHz)	13.5		46/38	159/151
	11ac(20 MHz)	6.5		48/44/36	165/157/149

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Test Items	Mode	Data Rate	Modulation Type	U-NII-1	U-NII-3
				Channel	Channel
	11ac(40 MHz)	13.5		46/38	159/151
	11ac(80 MHz)	29.3		42	155
	11ax(20 MHz)	4		48/44/36	165/157/149
	11ax(40 MHz)	8		46/38	159/151
	11ax(80 MHz)	17		42	155
Undesirable Emissions	11a	6	BPSK	48/44/36	165/157/149
	11n(20 MHz)	6.5		48/44/36	165/157/149
	11n(40 MHz)	13.5		46/38	159/151
	11ac(20 MHz)	6.5		48/44/36	165/157/149
	11ac(40 MHz)	13.5		46/38	159/151
	11ac(80 MHz)	29.3		42	155
	11ax(20 MHz)	4		48/44/36	165/157/149
	11ax(40 MHz)	8		46/38	159/151
	11ax(80 MHz)	17		42	155

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart E	Unlicensed National Information Infrastructure Devices
2	ANSI C63.10-2020+Cor 1-2023	American National Standard for Testing Unlicensed Wireless Devices
3	KDB Publication 789033 D02v02r01	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E

Remark:
Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

3.2 Test Verdict

No.	Description	FCC Part No.	Verdict	Remark
1	Antenna Requirement	15.203	Pass	Note [1]
2	Conducted Emission at AC Power Line	15.207 15.407(b)(9)	Pass	--
3	Emission Bandwidth and Occupied Bandwidth	U-NII 1: No limits, only for report use. U-NII 3: 15.407(e)	Pass	--
4	Maximum Conducted Output Power	15.407(a)(1)(i) 15.407(a)(1)(ii) 15.407(a)(1)(iii) 15.407(a)(1)(iv) 15.407(a)(3)(i)	Pass	--
5	Power Spectral Density	15.407(a)(1)(i) 15.407(a)(1)(ii) 15.407(a)(1)(iii) 15.407(a)(1)(iv) 15.407(a)(3)(i)	Pass	--
6	Band Edge emissions (Radiated)	15.407(b)(1) 15.407(b)(4) 15.407(b)(10)	Pass	--
7	Undesirable Emissions	15.407(b)(1) 15.407(b)(4) 15.407(b)(9) 15.407(b)(10)	Pass	--
8	Frequency Stability	15.407(g)	Pass	--

Note [1]: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.
Note [2]: N/A" denotes test is not applicable in this test report.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Designation Number	CN1368
Test Firm Registration Number	952583

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%	
Atmospheric Pressure	86 kPa to 106 kPa	
Temperature	NT (Normal Temperature)	+15℃ to +35℃
Working Voltage of the EUT	NV (Normal Voltage)	120VAC, 60Hz for adapter

4.2 Test Equipment

Conducted Emission at AC power line					
Equipment	**Manufacturer**	**Model No**	**Serial No**	**Cal. Date**	**Cal. Due Date**
L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	EE-004	2026/01/07	2027/01/06
EMI Test Receiver	Rohde & Schwarz	ESCI	EE-005	2026/01/07	2027/01/06
Test Software	Ferrari Technology	EZ-EMC	EE-014	N.C.R	N.C.R

Radiated Emission and RF Test					
Equipment	**Manufacturer**	**Model No**	**Serial No**	**Cal Date**	**Cal Due Date**
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026/01/07	2027/01/06
Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	EE-007	2026/01/13	2029/01/12
Double Ridged Horn Antenna	A-INFOMW	LB-10180-NF	EE-008	2026/01/11	2029/01/10
Pre-amplifier	Agilent	8447D	EE-009	2026/01/07	2027/01/06
Pre-amplifier	Agilent	8449B	EE-010	2026/01/07	2027/01/06
MXA Signal Analyzer	Agilent	N9020A	EE-011	2026/01/07	2027/01/06
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2026/01/07	2027/01/06
Test Software	Farad	EZ-EMC	EE-015	N.C.R	N.C.R
MIMO Power Measurement Module	TSTPASS	TSPS 2023R	EE-016	2026/01/07	2027/01/06
RF Test Software	TSTPASS	TS32893 V2.0	EE-017	N.C.R	N.C.R
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	EE-402	2025/02/14	2026/02/13
Loop Antenna	TESEQ	HLA6121	EE-403	2025/02/14	2026/02/13
Spectrum Analyzer	ROHDE & SCHWARZ	FSP40	EE-404	2025/02/14	2026/02/13
MXG RF Analog Signal Generator	Agilent	N5181A	EE-406	2025/02/14	2026/02/13
DRG Horn Antenna (up to 40GHz)	SCHWARZBECK	BBHA 9170	EE-410	2025/02/14	2026/02/13
Pre-amplifier	SKET	LNPA-1840-50	EE-411	2025/02/14	2026/02/13
Constant Temperature Humidity Chamber	Guangxin	GXP-401	ES-002	2025/07/29	2026/07/28
Power Sensor	ROHDE&SCHWARZN	NRP18S	ES-420	2025/02/14	2026/02/13

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

4.3 Description of Support Unit

No.	Title	Manufacturer	Model No.	Serial No.
1	Adapter	refer to clause 2.4	refer to clause 2.4	--

4.4 Test Mode

No.	Test Modes	Description
TM1	802.11a mode	Keep the EUT in 802.11a transmitting mode.
TM2	802.11n(HT20) mode	Keep the EUT in 802.11n(HT20) transmitting mode.
TM3	802.11n(HT40) mode	Keep the EUT in 802.11n(HT40) transmitting mode.
TM4	802.11ac(VHT20) mode	Keep the EUT in 802.11ac(VHT20) transmitting mode.
TM5	802.11ac(VHT40) mode	Keep the EUT in 802.11ac(VHT40) transmitting mode.
TM6	802.11ac(VHT80) mode	Keep the EUT in 802.11ac(VHT80) transmitting mode.
TM7	802.11ax(HEW20) mode	Keep the EUT in 802.11ax(HEW20) transmitting mode.
TM8	802.11ax(HEW40) mode	Keep the EUT in 802.11ax(HEW40) transmitting mode.
TM9	802.11ax(HEW80) mode	Keep the EUT in 802.11ax(HEW80) transmitting mode.

4.5 Description of Calculation

4.5.1. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS (dBuV/m) = RA (dBuV) + AF (dB/m) + CL (dB) – AG (dB)

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

4.5.2. Disturbance Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

CD (dBuV) = RA (dBuV) + PL (dB) + CL (dB)

Where	CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

4.6 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.
This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test Item	Measurement Uncertainty
Conducted Emission	2.64 dB
Occupied Channel Bandwidth	70 kHz
RF output power, conducted	1.04 dB
Power Spectral Density, conducted	0.91 dB
Time of Occupancy (Dwell Time)	1.8 %
Unwanted Emissions, conducted	2.72 dB
Radiated Emission (9kHz- 30MHz)	Ur = 2.50 dB
Radiated Emission (30MHz- 1GHz)	Ur = 2.70 dB (Horizontal)
	Ur = 2.70 dB (Vertical)
Radiated Emission (1GHz- 18GHz)	Ur = 3.50 dB (Horizontal)
	Ur = 3.50 dB (Vertical)
Radiated Emission (18GHz- 40GHz)	Ur = 5.15 dB (Horizontal)
	Ur = 5.24 dB (Vertical)
Temperature	0.8°C
Humidity	4%

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Condition

None.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5 Test Items

5.1 Antenna requirement

5.1.1 Test Requirement

Test Requirement	According to FCC §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded. If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.2 Conducted Emission at AC Power Line

5.2.1 Test Requirement

Test Requirement	Except as shown in paragraphs (b)and (c)of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN).
Test Limit	

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Test Method	ANSI C63.10-2020+Cor 1-2023 section 6.2

5.2.2 Test Setup Diagram



5.2.3 Test Procedure

The EUT is put on the plane 0.8 m high above the ground by insulating support and connected to the AC mains through Line Impedance Stability Network (L.I.S.N). This provided a 50ohm coupling impedance for the tested equipment. Both sides of AC line are investigated to find out the maximum conducted emission according to the test standard regulations during conducted emission measurement.
The bandwidth of the field strength meter (R&S Test Receiver ESCI) is set at 9kHz in 150kHz~30MHz.
The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.
Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.2.4 Test Data

PASS.
During the test, pre-scan all modes, and found the U-NII-1 / 802.11n(HT20) is worse case, the report only record this mode.

Conducted Emission Test Data

Test Site:	Shielded Room #1
Test Mode:	TM2/ CH Middle(U-NII-1)
Comments:	Live Line



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	42.99	9.95	52.94	66.00	-13.06	QP	P	
2	0.1500	27.38	9.95	37.33	56.00	-18.67	AVG	P	
3	0.2893	37.17	9.99	47.16	60.54	-13.38	QP	P	
4	0.2893	29.44	9.99	39.43	50.54	-11.11	AVG	P	
5	0.3750	41.58	10.01	51.59	58.39	-6.80	QP	P	
6 *	0.3750	35.23	10.01	45.24	48.39	-3.15	AVG	P	
7	0.9735	24.61	10.04	34.65	56.00	-21.35	QP	P	
8	0.9735	16.26	10.04	26.30	46.00	-19.70	AVG	P	
9	14.4600	22.71	9.97	32.68	60.00	-27.32	QP	P	
10	14.4600	14.68	9.97	24.65	50.00	-25.35	AVG	P	
11	23.2800	20.10	10.14	30.24	60.00	-29.76	QP	P	
12	23.2800	9.31	10.14	19.45	50.00	-30.55	AVG	P	

Note: Level = Reading + Factor Margin = Level - Limit

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Conducted Emission Test Data

Test Site:	Shielded Room #1
Test Mode:	TM2/ CH Middle(U-NII-1)
Comments:	Neutral Line



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1544	40.75	9.98	50.73	65.76	-15.03	QP	P	
2	0.1544	23.37	9.98	33.35	55.76	-22.41	AVG	P	
3	0.2535	33.42	10.01	43.43	61.64	-18.21	QP	P	
4	0.2535	27.34	10.01	37.35	51.64	-14.29	AVG	P	
5	0.3795	39.63	10.04	49.67	58.29	-8.62	QP	P	
6 *	0.3795	31.26	10.04	41.30	48.29	-6.99	AVG	P	
7	1.0809	25.60	10.06	35.66	56.00	-20.34	QP	P	
8	1.0809	11.53	10.06	21.59	46.00	-24.41	AVG	P	
9	13.8975	24.94	9.99	34.93	60.00	-25.07	QP	P	
10	13.8975	16.99	9.99	26.98	50.00	-23.02	AVG	P	
11	23.2935	21.54	10.13	31.67	60.00	-28.33	QP	P	
12	23.2935	11.18	10.13	21.31	50.00	-28.69	AVG	P	

Note: Level = Reading + Factor Margin = Level - Limit

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.3 Emission Bandwidth and Occupied Bandwidth

5.3.1 Test Requirement

Test Requirement	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. U-NII 3, U-NII 4: Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.
Test Method	ANSI C63.10-2020+Cor 1-2023 section 12.5

5.3.2 Test Setup Diagram



5.3.3 Test Procedure

Emission bandwidth:
a) Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
b) Set the VBW > RBW.
c) Detector = peak.
d) Trace mode = max hold.
e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

Occupied bandwidth:
a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2.
d) Step a) through step c) might require iteration to adjust within the specified range.
e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
g)If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
h)The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled.
Tabular data may be reported in addition to the plot(s).

6 dB emission bandwidth:
a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) ≥ 3 >= RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Data

PASS.
Please refer to Annex G for details.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.4 Maximum Conducted Output Power

5.4.1 Test Requirement

Test Requirement	For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm). For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations. For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
Test Method	ANSI C63.10-2020+Cor 1-2023, section 12.4

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.4.2 Test Setup Diagram



5.4.3 Test Procedure

Method SA-2 uses trace averaging across ON and OFF times of the EUT transmissions, followed by duty cycle correction. The procedure for this method is as follows:
a) Measure the duty cycle *D* of the transmitter output signal as described in 12.2.
b) Set span to encompass the entire 99% OBW of the signal.
c) Set RBW = 1 MHz.
d) Set VBW ≥ 3 MHz.
e) Number of points in sweep ≥ [2 × span / RBW]. (This gives bin-to-bin spacing ≤ RBW / 2, so that narrowband signals are not lost between frequency bins.)
f) Sweep time = auto.
g) Detector = Power averaging (rms), if available. Otherwise, use sample detector mode.
h) Do not use sweep triggering. Allow the sweep to "free run."
i) Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
j) Compute power by integrating the spectrum across the 99% OBW of the signal using the instrument's band-power measurement function with band limits set equal to the EBW or OBW band-edges. If the instrument does not have a band-power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 99% OBW of the spectrum.
k) Add [10 log (1 / *D*)], where *D* is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add [10 log (1 / 0.25)] = 6 dB if the duty cycle is 25%.

Method SA-3 uses rms detection with max-hold. The procedure for this method is as follows:
a) Set span to encompass the entire 99% OBW of the signal.
b) Set sweep trigger to "free run."
c) Set RBW = 1 MHz.
d) Set VBW ≥ 3 MHz
e) Number of points in sweep ≥ [2 × span / RBW]. (This gives bin-to-bin spacing ≤ RBW / 2, so that narrowband signals are not lost between frequency bins.)
f) Sweep time ≤ [(number of points in sweep) × *T*], where *T* is defined in 12.2. If this gives a sweep time less than the auto sweep time of the instrument, then method SA-3A shall not be used. (The purpose of this step is so that averaging time in each bin is less than or equal to the minimum time of a transmission.)

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

g) Detector = Power averaging (rms).
h) Trace mode = max-hold.
i) Allow max-hold to run for at least 60 s or longer as needed to allow the trace to stabilize.
j) Compute power by integrating the spectrum across the 99% OBW of the signal using the instrument's band-power measurement function with band limits set equal to the EBW or OBW band-edges. If the instrument does not have a band-power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 99% OBW of the spectrum.

5.4.4 Test Data

PASS.

Please refer to Annex G for details.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.5 Power Spectral Density

5.5.1 Test Requirement

Test Requirement	For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations. For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For the band 5.725-5.850 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
Test Method	ANSI C63.10-2020+Cor 1-2023, section 12.6

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.5.2 Test Setup Diagram



5.5.3 Test Procedure

a) Create an average power spectrum for the EUT operating mode being tested by following the instructions in 12.3.2 for measuring maximum conducted output power using a spectrum analyzer or EMI receiver; that is, select the appropriate test method (SA-1, SA-2, SA-3, or their respective alternatives) and apply it up to, but not including, the step labeled, “Compute power….” (This procedure is required even if the maximum conducted output power measurement was performed using the power meter method PM.)
b) Use the peak search function on the instrument to find the peak of the spectrum.
c) Make the following adjustments to the peak value of the spectrum, if applicable:
1) If method SA-2 or SA-2A was used, then add [10 log (1 / D)], where D is the duty cycle, to the peak of the spectrum.
2) If method SA-3A was used and the linear mode was used in step h) of 12.3.2.7, add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
d) The result is the PPSD.
e) The procedure in item a) through item c) requires the use of 1 MHz resolution bandwidth to satisfy the 1 MHz measurement bandwidth specified by some regulatory authorities. This requirement also permits use of resolution bandwidths less than 1 MHz “provided that the measured power is integrated to show the total power over the measurement bandwidth” (i.e., 1 MHz). If measurements are performed using a reduced resolution bandwidth and integrated over 1 MHz bandwidth, the following adjustments to the procedures apply:
1) Set RBW >= 1 / T, where T is defined in 12.2 a).
2) Set VBW >= [3 × RBW].
Care shall be taken such that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

5.5.4 Test Data

PASS.

Please refer to Annex G for details.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.6 Band edge Emissions (Restricted frequency bands)

5.6.1 Test Requirement

Test Requirement

Frequency band 5150-5350 MHz:
For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

Frequency band 5725-5850 MHz:
Devices operating in the band 5725-5850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:
a) 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;
b) 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
c) 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
d) -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.

If radiated measurements are performed, field strength is then converted to EIRP as follows, Where:
E is the field strength in V/m;
d is the measurement distance in meters.
EIRP is the equivalent isotopically radiated power in watts.ii) Working in dB units, the above equation is equivalent to.EIRP [dBm] = E [dBuV/m] + 20 log (d [meters]) - 104.77
Or, if d is 3 meters:
EIRP [dBm] = E [dBuV/m] - 95.23

Operating Band	Frequency	EIRP Limit	Value
5150-5250MHz	Above 1GHz	-27dBm/MHz(68.23dBuV/m)@3m	Peak
5250-5350MHz	Above 1GHz	-27dBm/MHz(68.23dBuV/m)@3m	Peak
5470-5725MHz	Above 1GHz	-27dBm/MHz(68.23dBuV/m)@3m	Peak
5725-5850 MHz	1GHz-5.65GHz	-27 dBm/MHz(68.23dBuV/m)@3m	Peak
	5.65GHz-5.7GHz	-27dBm/MHz to 10dBm/MHz* (68.23dBuV/m to 105.23dBuV/m) *	Peak
	5.7GHz-5.72GHz	10dBm/MHz to 15.6dBm/MHz* (105.6dBuV/m to 110.83dBuV/m) *	Peak
	5.72GHz-5.725GHz	15.6dBm/MHz to 27dBm/MHz* (110.8dBuV/m to 122.23dBuV/m) *	Peak
	5.85GHz-	27dBm/MHz to 15.6dBm/MHz*	Peak

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

	5.855GHz	(122.2dBuV/m to110.83dBuV/m)*	
	5.855GHz-5.875GHz	15.6dBm/MHz to 10dBm/MHz* (110.8dBuV/m to 105.63dBuV/m*	Peak
	5.875GHz-5.925GHz	10dBm/MHz to -27dBm/MHz* (105.6dBuV/m to 68.23dBuV/m) *	Peak
	Above 5.925GHz	-27 dBm/MHz(68.2dBuV/m)@3m	Peak

Restricted frequency bands:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

Test Method	ANSI C63.10-2020+Cor 1-2023, section 12.7.4, section 12.7.5, section 12.7.6;

5.6.2 Test Setup Diagram



Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com



5.6.3 Test Procedure

a) Cabinet emissions measurements—A radiated test shall be performed to confirm that cabinet emissions are below the emission limits. For the cabinet-emission measurements the antenna may be replaced by a termination matching the nominal impedance of the antenna.
b) Impedance matching—Conducted tests shall be performed using equipment that matches the nominal impedance of the antenna assembly used with the EUT.
c) EIRP calculation—A value representative of an upper bound on out-of-band antenna gain (in dBi) shall be added to the measured antenna-port conducted emission power to compute EIRP within the specified measurement bandwidth. (For emissions in the restricted-bands, additional calculations are required to convert EIRP to field strength at the specified distance.) The upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater.86 However, for devices that operate in multiple bands using the same transmit antenna, the highest gain of the antenna within the operating band nearest to the out-of-band frequency being measured may be used, in lieu of the overall highest gain, when measuring emissions at frequencies within 20% of the absolute frequency at the nearest edge of that band, but in no case shall a value less than 2 dBi be selected.
d) EIRP corrections for multiple outputs—For devices with multiple outputs occupying the same or overlapping frequency ranges in the same band (e.g., MIMO or beamforming devices), compute the total EIRP as follows:
1) Compute EIRP for each output, as described in step c).
2) Follow the procedures specified in Clause 14 for summing emissions across the outputs, or correcting emission levels measured on individual outputs by [10 log (N_{ANT})], where NANT is the number of outputs.
Add the array gain term specified in 14.6.4 for out-of-band and spurious signals.[87]

5.6.4 Test Data

PASS.

Please refer to the following pages.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11a					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.18	5.79	54.97	68.23	-13.27	PK	PASS
H	5350.00	44.73	6.45	51.18	68.23	-17.05	PK	PASS
V	5150.00	49.49	5.79	55.28	68.23	-12.96	PK	PASS
V	5350.00	46.94	6.45	53.39	68.23	-14.85	PK	PASS
H	5150.00	35.57	5.79	41.36	54.00	-12.65	AV	PASS
H	5350.00	31.58	6.45	38.03	54.00	-15.97	AV	PASS
V	5150.00	34.61	5.79	40.40	54.00	-13.61	AV	PASS
V	5350.00	31.63	6.45	38.08	54.00	-15.92	AV	PASS

Test Mode: 802.11a					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.97	5.79	53.76	68.23	-14.47	PK	PASS
H	5350.00	44.91	6.45	51.36	68.23	-16.88	PK	PASS
V	5150.00	49.92	5.79	55.71	68.23	-12.52	PK	PASS
V	5350.00	45.41	6.45	51.86	68.23	-16.37	PK	PASS
H	5150.00	34.54	5.79	40.33	54.00	-13.67	AV	PASS
H	5350.00	33.15	6.45	39.60	54.00	-14.40	AV	PASS
V	5150.00	34.08	5.79	39.87	54.00	-14.14	AV	PASS
V	5350.00	31.41	6.45	37.86	54.00	-16.15	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11n(HT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.68	5.79	54.47	68.23	-13.77	PK	PASS
H	5350.00	46.40	6.45	52.85	68.23	-15.38	PK	PASS
V	5150.00	47.35	5.79	53.14	68.23	-15.09	PK	PASS
V	5350.00	45.14	6.45	51.59	68.23	-16.64	PK	PASS
H	5150.00	35.88	5.79	41.67	54.00	-12.33	AV	PASS
H	5350.00	32.00	6.45	38.45	54.00	-15.55	AV	PASS
V	5150.00	34.75	5.79	40.54	54.00	-13.47	AV	PASS
V	5350.00	33.08	6.45	39.53	54.00	-14.48	AV	PASS

Test Mode: 802.11n(HT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.43	5.79	53.22	68.23	-15.01	PK	PASS
H	5350.00	44.70	6.45	51.15	68.23	-17.09	PK	PASS
V	5150.00	49.03	5.79	54.82	68.23	-13.41	PK	PASS
V	5350.00	46.73	6.45	53.18	68.23	-15.05	PK	PASS
H	5150.00	34.95	5.79	40.74	54.00	-13.27	AV	PASS
H	5350.00	31.28	6.45	37.73	54.00	-16.28	AV	PASS
V	5150.00	35.23	5.79	41.02	54.00	-12.98	AV	PASS
V	5350.00	32.90	6.45	39.35	54.00	-14.65	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11n(HT40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.30	5.79	55.09	68.23	-13.15	PK	PASS
H	5350.00	44.16	6.45	50.61	68.23	-17.63	PK	PASS
V	5150.00	48.47	5.79	54.26	68.23	-13.97	PK	PASS
V	5350.00	44.08	6.45	50.53	68.23	-17.71	PK	PASS
H	5150.00	36.90	5.79	42.69	54.00	-11.31	AV	PASS
H	5350.00	31.22	6.45	37.67	54.00	-16.34	AV	PASS
V	5150.00	34.21	5.79	40.00	54.00	-14.00	AV	PASS
V	5350.00	31.42	6.45	37.87	54.00	-16.14	AV	PASS

Test Mode: 802.11n(HT40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.74	5.79	55.53	68.23	-12.71	PK	PASS
H	5350.00	46.75	6.45	53.20	68.23	-15.04	PK	PASS
V	5150.00	48.97	5.79	54.76	68.23	-13.48	PK	PASS
V	5350.00	46.07	6.45	52.52	68.23	-15.71	PK	PASS
H	5150.00	35.91	5.79	41.70	54.00	-12.31	AV	PASS
H	5350.00	33.42	6.45	39.87	54.00	-14.13	AV	PASS
V	5150.00	34.71	5.79	40.50	54.00	-13.50	AV	PASS
V	5350.00	32.64	6.45	39.09	54.00	-14.91	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ac(VHT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.06	5.79	52.85	68.23	-15.39	PK	PASS
H	5350.00	46.67	6.45	53.12	68.23	-15.12	PK	PASS
V	5150.00	48.33	5.79	54.12	68.23	-14.11	PK	PASS
V	5350.00	45.91	6.45	52.36	68.23	-15.88	PK	PASS
H	5150.00	36.38	5.79	42.17	54.00	-11.84	AV	PASS
H	5350.00	32.95	6.45	39.40	54.00	-14.60	AV	PASS
V	5150.00	36.10	5.79	41.89	54.00	-12.11	AV	PASS
V	5350.00	32.98	6.45	39.43	54.00	-14.58	AV	PASS

Test Mode: 802.11ac(VHT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.16	5.79	54.95	68.23	-13.29	PK	PASS
H	5350.00	46.48	6.45	52.93	68.23	-15.30	PK	PASS
V	5150.00	47.88	5.79	53.67	68.23	-14.56	PK	PASS
V	5350.00	46.02	6.45	52.47	68.23	-15.76	PK	PASS
H	5150.00	36.53	5.79	42.32	54.00	-11.69	AV	PASS
H	5350.00	33.21	6.45	39.66	54.00	-14.35	AV	PASS
V	5150.00	36.80	5.79	42.59	54.00	-11.42	AV	PASS
V	5350.00	32.11	6.45	38.56	54.00	-15.45	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11 ac(VHT40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.45	5.79	53.24	68.23	-15.00	PK	PASS
H	5350.00	46.80	6.45	53.25	68.23	-14.99	PK	PASS
V	5150.00	47.72	5.79	53.51	68.23	-14.73	PK	PASS
V	5350.00	46.16	6.45	52.61	68.23	-15.62	PK	PASS
H	5150.00	36.12	5.79	41.91	54.00	-12.10	AV	PASS
H	5350.00	31.94	6.45	38.39	54.00	-15.62	AV	PASS
V	5150.00	34.93	5.79	40.72	54.00	-13.28	AV	PASS
V	5350.00	32.71	6.45	39.16	54.00	-14.84	AV	PASS

Test Mode: 802.11 ac(VHT40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.88	5.79	55.67	68.23	-12.56	PK	PASS
H	5350.00	44.00	6.45	50.45	68.23	-17.78	PK	PASS
V	5150.00	48.42	5.79	54.21	68.23	-14.02	PK	PASS
V	5350.00	46.38	6.45	52.83	68.23	-15.40	PK	PASS
H	5150.00	35.55	5.79	41.34	54.00	-12.66	AV	PASS
H	5350.00	31.54	6.45	37.99	54.00	-16.02	AV	PASS
V	5150.00	35.89	5.79	41.68	54.00	-12.32	AV	PASS
V	5350.00	33.40	6.45	39.85	54.00	-14.15	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ac(VHT80)					CH: 5210 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.93	5.79	53.72	68.23	-14.51	PK	PASS
H	5350.00	45.64	6.45	52.09	68.23	-16.15	PK	PASS
V	5150.00	49.64	5.79	55.43	68.23	-12.81	PK	PASS
V	5350.00	46.17	6.45	52.62	68.23	-15.62	PK	PASS
H	5150.00	36.06	5.79	41.85	54.00	-12.16	AV	PASS
H	5350.00	32.77	6.45	39.22	54.00	-14.78	AV	PASS
V	5150.00	36.62	5.79	42.41	54.00	-11.59	AV	PASS
V	5350.00	33.25	6.45	39.70	54.00	-14.30	AV	PASS

Test Mode: 802.11 ac(VHT80)					CH: 5210 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.22	5.79	53.01	68.23	-15.23	PK	PASS
H	5350.00	44.74	6.45	51.19	68.23	-17.05	PK	PASS
V	5150.00	48.89	5.79	54.68	68.23	-13.55	PK	PASS
V	5350.00	45.80	6.45	52.25	68.23	-15.99	PK	PASS
H	5150.00	35.08	5.79	40.87	54.00	-13.13	AV	PASS
H	5350.00	32.44	6.45	38.89	54.00	-15.12	AV	PASS
V	5150.00	36.58	5.79	42.37	54.00	-11.64	AV	PASS
V	5350.00	32.88	6.45	39.33	54.00	-14.68	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ax(HEW20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.52	5.79	53.31	68.23	-14.93	PK	PASS
H	5350.00	46.47	6.45	52.92	68.23	-15.32	PK	PASS
V	5150.00	48.29	5.79	54.08	68.23	-14.15	PK	PASS
V	5350.00	44.34	6.45	50.79	68.23	-17.44	PK	PASS
H	5150.00	34.95	5.79	40.74	54.00	-13.27	AV	PASS
H	5350.00	31.77	6.45	38.22	54.00	-15.78	AV	PASS
V	5150.00	35.20	5.79	40.99	54.00	-13.01	AV	PASS
V	5350.00	31.87	6.45	38.32	54.00	-15.69	AV	PASS

Test Mode: 802.11ax(HEW20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.29	5.79	55.08	68.23	-13.16	PK	PASS
H	5350.00	46.46	6.45	52.91	68.23	-15.32	PK	PASS
V	5150.00	47.37	5.79	53.16	68.23	-15.07	PK	PASS
V	5350.00	44.70	6.45	51.15	68.23	-17.08	PK	PASS
H	5150.00	34.01	5.79	39.80	54.00	-14.20	AV	PASS
H	5350.00	31.06	6.45	37.51	54.00	-16.50	AV	PASS
V	5150.00	35.16	5.79	40.95	54.00	-13.06	AV	PASS
V	5350.00	32.17	6.45	38.62	54.00	-15.38	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ax(HEW40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.44	5.79	53.23	68.23	-15.01	PK	PASS
H	5350.00	46.40	6.45	52.85	68.23	-15.38	PK	PASS
V	5150.00	47.61	5.79	53.40	68.23	-14.83	PK	PASS
V	5350.00	46.85	6.45	53.30	68.23	-14.93	PK	PASS
H	5150.00	36.71	5.79	42.50	54.00	-11.50	AV	PASS
H	5350.00	33.05	6.45	39.50	54.00	-14.51	AV	PASS
V	5150.00	35.31	5.79	41.10	54.00	-12.91	AV	PASS
V	5350.00	31.51	6.45	37.96	54.00	-16.05	AV	PASS

Test Mode: 802.11ax(HEW40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.61	5.79	53.40	68.23	-14.83	PK	PASS
H	5350.00	46.87	6.45	53.32	68.23	-14.92	PK	PASS
V	5150.00	47.55	5.79	53.34	68.23	-14.90	PK	PASS
V	5350.00	45.96	6.45	52.41	68.23	-15.82	PK	PASS
H	5150.00	34.71	5.79	40.50	54.00	-13.50	AV	PASS
H	5350.00	32.12	6.45	38.57	54.00	-15.43	AV	PASS
V	5150.00	34.66	5.79	40.45	54.00	-13.56	AV	PASS
V	5350.00	33.80	6.45	40.25	54.00	-13.76	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ax(HEW80)					CH: 5210 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.88	5.79	55.67	68.23	-12.56	PK	PASS
H	5350.00	45.26	6.45	51.71	68.23	-16.53	PK	PASS
V	5150.00	49.79	5.79	55.58	68.23	-12.66	PK	PASS
V	5350.00	45.28	6.45	51.73	68.23	-16.50	PK	PASS
H	5150.00	35.28	5.79	41.07	54.00	-12.94	AV	PASS
H	5350.00	32.00	6.45	38.45	54.00	-15.55	AV	PASS
V	5150.00	35.91	5.79	41.70	54.00	-12.30	AV	PASS
V	5350.00	31.78	6.45	38.23	54.00	-15.78	AV	PASS

Test Mode: 802.11ax(HEW80)					CH: 5210 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.65	5.79	53.44	68.23	-14.79	PK	PASS
H	5350.00	45.98	6.45	52.43	68.23	-15.81	PK	PASS
V	5150.00	48.93	5.79	54.72	68.23	-13.51	PK	PASS
V	5350.00	46.09	6.45	52.54	68.23	-15.69	PK	PASS
H	5150.00	35.90	5.79	41.69	54.00	-12.32	AV	PASS
H	5350.00	33.72	6.45	40.17	54.00	-13.83	AV	PASS
V	5150.00	34.84	5.79	40.63	54.00	-13.37	AV	PASS
V	5350.00	31.72	6.45	38.17	54.00	-15.83	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11a					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	43.59	7.55	51.14	68.23	-17.10	PK	PASS
H	5700.00	48.91	7.56	56.47	105.23	-48.76	PK	PASS
H	5720.00	49.05	7.59	56.64	110.83	-54.19	PK	PASS
H	5725.00	50.96	7.68	58.64	122.23	-63.60	PK	PASS
V	5650.00	44.87	7.55	52.42	68.23	-15.82	PK	PASS
V	5700.00	48.03	7.56	55.59	105.23	-49.65	PK	PASS
V	5720.00	47.55	7.59	55.14	110.83	-55.69	PK	PASS
V	5725.00	52.56	7.68	60.24	122.23	-62.00	PK	PASS
H	5650.00	28.38	7.55	35.93	54.00	-18.07	AV	PASS
H	5700.00	33.49	7.56	41.05	54.00	-12.96	AV	PASS
H	5720.00	32.06	7.59	39.65	54.00	-14.35	AV	PASS
H	5725.00	35.80	7.68	43.48	54.00	-10.52	AV	PASS
V	5650.00	30.52	7.55	38.07	54.00	-15.93	AV	PASS
V	5700.00	33.51	7.56	41.07	54.00	-12.94	AV	PASS
V	5720.00	32.44	7.59	40.03	54.00	-13.97	AV	PASS
V	5725.00	36.17	7.68	43.85	54.00	-10.16	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11a					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	49.35	7.55	56.90	122.23	-65.33	PK	PASS
H	5855.00	47.52	7.56	55.08	110.83	-55.75	PK	PASS
H	5875.00	47.95	7.59	55.54	105.23	-49.69	PK	PASS
H	5925.00	43.51	7.68	51.19	68.23	-17.05	PK	PASS
V	5850.00	51.15	7.55	58.70	122.23	-63.54	PK	PASS
V	5855.00	47.08	7.56	54.64	110.83	-56.20	PK	PASS
V	5875.00	45.43	7.59	53.02	105.23	-52.21	PK	PASS
V	5925.00	44.40	7.68	52.08	68.23	-16.15	PK	PASS
H	5850.00	35.63	7.55	43.18	54.00	-10.82	AV	PASS
H	5855.00	32.03	7.56	39.59	54.00	-14.42	AV	PASS
H	5875.00	33.61	7.59	41.20	54.00	-12.80	AV	PASS
H	5925.00	30.97	7.68	38.65	54.00	-15.35	AV	PASS
V	5850.00	35.84	7.55	43.39	54.00	-10.62	AV	PASS
V	5855.00	35.32	7.56	42.88	54.00	-11.13	AV	PASS
V	5875.00	33.63	7.59	41.22	54.00	-12.79	AV	PASS
V	5925.00	30.87	7.68	38.55	54.00	-15.45	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	44.05	7.55	51.60	68.23	-16.64	PK	PASS
H	5700.00	48.68	7.56	56.24	105.23	-48.99	PK	PASS
H	5720.00	49.50	7.59	57.09	110.83	-53.74	PK	PASS
H	5725.00	51.48	7.68	59.16	122.23	-63.07	PK	PASS
V	5650.00	43.96	7.55	51.51	68.23	-16.72	PK	PASS
V	5700.00	45.19	7.56	52.75	105.23	-52.48	PK	PASS
V	5720.00	48.53	7.59	56.12	110.83	-54.72	PK	PASS
V	5725.00	51.63	7.68	59.31	122.23	-62.93	PK	PASS
H	5650.00	28.78	7.55	36.33	54.00	-17.68	AV	PASS
H	5700.00	31.66	7.56	39.22	54.00	-14.79	AV	PASS
H	5720.00	34.66	7.59	42.25	54.00	-11.75	AV	PASS
H	5725.00	35.60	7.68	43.28	54.00	-10.73	AV	PASS
V	5650.00	31.92	7.55	39.47	54.00	-14.54	AV	PASS
V	5700.00	32.44	7.56	40.00	54.00	-14.01	AV	PASS
V	5720.00	32.49	7.59	40.08	54.00	-13.92	AV	PASS
V	5725.00	36.50	7.68	44.18	54.00	-9.83	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT20)					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	51.40	7.55	58.95	122.23	-63.28	PK	PASS
H	5855.00	48.01	7.56	55.57	110.83	-55.27	PK	PASS
H	5875.00	48.06	7.59	55.65	105.23	-49.58	PK	PASS
H	5925.00	45.94	7.68	53.62	68.23	-14.61	PK	PASS
V	5850.00	51.35	7.55	58.90	122.23	-63.34	PK	PASS
V	5855.00	49.32	7.56	56.88	110.83	-53.95	PK	PASS
V	5875.00	45.78	7.59	53.37	105.23	-51.86	PK	PASS
V	5925.00	44.07	7.68	51.75	68.23	-16.48	PK	PASS
H	5850.00	36.66	7.55	44.21	54.00	-9.80	AV	PASS
H	5855.00	32.87	7.56	40.43	54.00	-13.57	AV	PASS
H	5875.00	32.83	7.59	40.42	54.00	-13.59	AV	PASS
H	5925.00	28.49	7.68	36.17	54.00	-17.83	AV	PASS
V	5850.00	35.61	7.55	43.16	54.00	-10.85	AV	PASS
V	5855.00	34.75	7.56	42.31	54.00	-11.69	AV	PASS
V	5875.00	31.54	7.59	39.13	54.00	-14.88	AV	PASS
V	5925.00	31.25	7.68	38.93	54.00	-15.08	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT40)					CH Low: 5755 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	46.07	7.55	53.62	68.23	-14.61	PK	PASS
H	5700.00	46.85	7.56	54.41	105.23	-50.83	PK	PASS
H	5720.00	49.84	7.59	57.43	110.83	-53.40	PK	PASS
H	5725.00	52.51	7.68	60.19	122.23	-62.04	PK	PASS
V	5650.00	43.31	7.55	50.86	68.23	-17.37	PK	PASS
V	5700.00	47.42	7.56	54.98	105.23	-50.25	PK	PASS
V	5720.00	49.07	7.59	56.66	110.83	-54.18	PK	PASS
V	5725.00	49.40	7.68	57.08	122.23	-65.15	PK	PASS
H	5650.00	28.31	7.55	35.86	54.00	-18.14	AV	PASS
H	5700.00	31.09	7.56	38.65	54.00	-15.36	AV	PASS
H	5720.00	34.36	7.59	41.95	54.00	-12.06	AV	PASS
H	5725.00	34.09	7.68	41.77	54.00	-12.24	AV	PASS
V	5650.00	30.33	7.55	37.88	54.00	-16.12	AV	PASS
V	5700.00	32.43	7.56	39.99	54.00	-14.01	AV	PASS
V	5720.00	34.47	7.59	42.06	54.00	-11.94	AV	PASS
V	5725.00	34.51	7.68	42.19	54.00	-11.82	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT40)					CH High: 5795 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	50.99	7.55	58.54	122.23	-63.70	PK	PASS
H	5855.00	49.85	7.56	57.41	110.83	-53.42	PK	PASS
H	5875.00	47.78	7.59	55.37	105.23	-49.86	PK	PASS
H	5925.00	45.14	7.68	52.82	68.23	-15.41	PK	PASS
V	5850.00	51.63	7.55	59.18	122.23	-63.06	PK	PASS
V	5855.00	48.35	7.56	55.91	110.83	-54.92	PK	PASS
V	5875.00	46.99	7.59	54.58	105.23	-50.65	PK	PASS
V	5925.00	43.99	7.68	51.67	68.23	-16.56	PK	PASS
H	5850.00	35.96	7.55	43.51	54.00	-10.50	AV	PASS
H	5855.00	32.38	7.56	39.94	54.00	-14.07	AV	PASS
H	5875.00	30.20	7.59	37.79	54.00	-16.22	AV	PASS
H	5925.00	31.84	7.68	39.52	54.00	-14.48	AV	PASS
V	5850.00	35.87	7.55	43.42	54.00	-10.59	AV	PASS
V	5855.00	33.84	7.56	41.40	54.00	-12.60	AV	PASS
V	5875.00	32.96	7.59	40.55	54.00	-13.46	AV	PASS
V	5925.00	29.97	7.68	37.65	54.00	-16.35	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	46.57	7.55	54.12	68.23	-14.12	PK	PASS
H	5700.00	47.20	7.56	54.76	105.23	-50.47	PK	PASS
H	5720.00	48.72	7.59	56.31	110.83	-54.53	PK	PASS
H	5725.00	52.60	7.68	60.28	122.23	-61.95	PK	PASS
V	5650.00	46.42	7.55	53.97	68.23	-14.26	PK	PASS
V	5700.00	48.97	7.56	56.53	105.23	-48.70	PK	PASS
V	5720.00	48.36	7.59	55.95	110.83	-54.88	PK	PASS
V	5725.00	51.55	7.68	59.23	122.23	-63.01	PK	PASS
H	5650.00	31.33	7.55	38.88	54.00	-15.12	AV	PASS
H	5700.00	31.63	7.56	39.19	54.00	-14.82	AV	PASS
H	5720.00	33.22	7.59	40.81	54.00	-13.19	AV	PASS
H	5725.00	35.52	7.68	43.20	54.00	-10.81	AV	PASS
V	5650.00	29.27	7.55	36.82	54.00	-17.18	AV	PASS
V	5700.00	30.39	7.56	37.95	54.00	-16.06	AV	PASS
V	5720.00	32.86	7.59	40.45	54.00	-13.55	AV	PASS
V	5725.00	34.64	7.68	42.32	54.00	-11.68	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT20)					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	49.61	7.55	57.16	122.23	-65.07	PK	PASS
H	5855.00	50.93	7.56	58.49	110.83	-52.35	PK	PASS
H	5875.00	46.94	7.59	54.53	105.23	-50.71	PK	PASS
H	5925.00	46.40	7.68	54.08	68.23	-14.15	PK	PASS
V	5850.00	51.46	7.55	59.01	122.23	-63.22	PK	PASS
V	5855.00	50.78	7.56	58.34	110.83	-52.50	PK	PASS
V	5875.00	48.61	7.59	56.20	105.23	-49.03	PK	PASS
V	5925.00	43.81	7.68	51.49	68.23	-16.74	PK	PASS
H	5850.00	36.83	7.55	44.38	54.00	-9.63	AV	PASS
H	5855.00	32.44	7.56	40.00	54.00	-14.00	AV	PASS
H	5875.00	31.52	7.59	39.11	54.00	-14.89	AV	PASS
H	5925.00	31.01	7.68	38.69	54.00	-15.31	AV	PASS
V	5850.00	37.52	7.55	45.07	54.00	-8.94	AV	PASS
V	5855.00	33.23	7.56	40.79	54.00	-13.22	AV	PASS
V	5875.00	30.09	7.59	37.68	54.00	-16.32	AV	PASS
V	5925.00	31.56	7.68	39.24	54.00	-14.76	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT40)					CH Low: 5755 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	44.58	7.55	52.13	68.23	-16.10	PK	PASS
H	5700.00	47.40	7.56	54.96	105.23	-50.28	PK	PASS
H	5720.00	48.51	7.59	56.10	110.83	-54.74	PK	PASS
H	5725.00	52.14	7.68	59.82	122.23	-62.42	PK	PASS
V	5650.00	45.92	7.55	53.47	68.23	-14.77	PK	PASS
V	5700.00	47.60	7.56	55.16	105.23	-50.07	PK	PASS
V	5720.00	48.69	7.59	56.28	110.83	-54.55	PK	PASS
V	5725.00	51.19	7.68	58.87	122.23	-63.36	PK	PASS
H	5650.00	30.45	7.55	38.00	54.00	-16.00	AV	PASS
H	5700.00	33.25	7.56	40.81	54.00	-13.19	AV	PASS
H	5720.00	35.26	7.59	42.85	54.00	-11.15	AV	PASS
H	5725.00	34.07	7.68	41.75	54.00	-12.26	AV	PASS
V	5650.00	31.58	7.55	39.13	54.00	-14.88	AV	PASS
V	5700.00	31.36	7.56	38.92	54.00	-15.08	AV	PASS
V	5720.00	32.48	7.59	40.07	54.00	-13.93	AV	PASS
V	5725.00	36.25	7.68	43.93	54.00	-10.08	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT40)					CH High: 5795 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	49.74	7.55	57.29	122.23	-64.95	PK	PASS
H	5855.00	48.35	7.56	55.91	110.83	-54.93	PK	PASS
H	5875.00	46.83	7.59	54.42	105.23	-50.81	PK	PASS
H	5925.00	45.09	7.68	52.77	68.23	-15.46	PK	PASS
V	5850.00	50.38	7.55	57.93	122.23	-64.31	PK	PASS
V	5855.00	49.20	7.56	56.76	110.83	-54.08	PK	PASS
V	5875.00	47.55	7.59	55.14	105.23	-50.09	PK	PASS
V	5925.00	44.87	7.68	52.55	68.23	-15.69	PK	PASS
H	5850.00	36.04	7.55	43.59	54.00	-10.41	AV	PASS
H	5855.00	32.69	7.56	40.25	54.00	-13.75	AV	PASS
H	5875.00	31.29	7.59	38.88	54.00	-15.12	AV	PASS
H	5925.00	30.85	7.68	38.53	54.00	-15.47	AV	PASS
V	5850.00	35.61	7.55	43.16	54.00	-10.85	AV	PASS
V	5855.00	34.98	7.56	42.54	54.00	-11.47	AV	PASS
V	5875.00	31.36	7.59	38.95	54.00	-15.05	AV	PASS
V	5925.00	29.65	7.68	37.33	54.00	-16.67	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT80)					CH: 5775 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	45.05	7.55	52.60	68.23	-15.63	PK	PASS
H	5700.00	47.54	7.56	55.10	105.23	-50.13	PK	PASS
H	5720.00	48.44	7.59	56.03	110.83	-54.81	PK	PASS
H	5725.00	51.00	7.68	58.68	122.23	-63.55	PK	PASS
V	5650.00	44.54	7.55	52.09	68.23	-16.14	PK	PASS
V	5700.00	46.36	7.56	53.92	105.23	-51.32	PK	PASS
V	5720.00	49.74	7.59	57.33	110.83	-53.50	PK	PASS
V	5725.00	49.96	7.68	57.64	122.23	-64.59	PK	PASS
H	5650.00	28.94	7.55	36.49	54.00	-17.51	AV	PASS
H	5700.00	32.41	7.56	39.97	54.00	-14.04	AV	PASS
H	5720.00	34.45	7.59	42.04	54.00	-11.97	AV	PASS
H	5725.00	37.82	7.68	45.50	54.00	-8.50	AV	PASS
V	5650.00	29.86	7.55	37.41	54.00	-16.60	AV	PASS
V	5700.00	30.47	7.56	38.03	54.00	-15.98	AV	PASS
V	5720.00	35.37	7.59	42.96	54.00	-11.04	AV	PASS
V	5725.00	36.85	7.68	44.53	54.00	-9.48	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT80)					CH: 5775 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	50.30	7.55	57.85	122.23	-64.38	PK	PASS
H	5855.00	48.44	7.56	56.00	110.83	-54.83	PK	PASS
H	5875.00	48.85	7.59	56.44	105.23	-48.79	PK	PASS
H	5925.00	45.26	7.68	52.94	68.23	-15.29	PK	PASS
V	5850.00	50.33	7.55	57.88	122.23	-64.35	PK	PASS
V	5855.00	47.36	7.56	54.92	110.83	-55.92	PK	PASS
V	5875.00	48.18	7.59	55.77	105.23	-49.46	PK	PASS
V	5925.00	44.95	7.68	52.63	68.23	-15.60	PK	PASS
H	5850.00	36.76	7.55	44.31	54.00	-9.70	AV	PASS
H	5855.00	35.34	7.56	42.90	54.00	-11.11	AV	PASS
H	5875.00	31.97	7.59	39.56	54.00	-14.45	AV	PASS
H	5925.00	31.65	7.68	39.33	54.00	-14.67	AV	PASS
V	5850.00	35.12	7.55	42.67	54.00	-11.33	AV	PASS
V	5855.00	33.68	7.56	41.24	54.00	-12.77	AV	PASS
V	5875.00	32.43	7.59	40.02	54.00	-13.99	AV	PASS
V	5925.00	31.03	7.68	38.71	54.00	-15.30	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	44.33	7.55	51.88	68.23	-16.35	PK	PASS
H	5700.00	47.07	7.56	54.63	105.23	-50.61	PK	PASS
H	5720.00	48.64	7.59	56.23	110.83	-54.61	PK	PASS
H	5725.00	49.55	7.68	57.23	122.23	-65.01	PK	PASS
V	5650.00	45.21	7.55	52.76	68.23	-15.48	PK	PASS
V	5700.00	48.39	7.56	55.95	105.23	-49.29	PK	PASS
V	5720.00	49.28	7.59	56.87	110.83	-53.96	PK	PASS
V	5725.00	49.83	7.68	57.51	122.23	-64.73	PK	PASS
H	5650.00	30.48	7.55	38.03	54.00	-15.98	AV	PASS
H	5700.00	32.38	7.56	39.94	54.00	-14.07	AV	PASS
H	5720.00	34.73	7.59	42.32	54.00	-11.68	AV	PASS
H	5725.00	36.62	7.68	44.30	54.00	-9.71	AV	PASS
V	5650.00	29.13	7.55	36.68	54.00	-17.33	AV	PASS
V	5700.00	32.88	7.56	40.44	54.00	-13.57	AV	PASS
V	5720.00	33.90	7.59	41.49	54.00	-12.51	AV	PASS
V	5725.00	35.29	7.68	42.97	54.00	-11.04	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW20)					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	49.73	7.55	57.28	122.23	-64.95	PK	PASS
H	5855.00	48.27	7.56	55.83	110.83	-55.00	PK	PASS
H	5875.00	47.77	7.59	55.36	105.23	-49.87	PK	PASS
H	5925.00	43.99	7.68	51.67	68.23	-16.57	PK	PASS
V	5850.00	52.12	7.55	59.67	122.23	-62.56	PK	PASS
V	5855.00	50.28	7.56	57.84	110.83	-52.99	PK	PASS
V	5875.00	45.15	7.59	52.74	105.23	-52.50	PK	PASS
V	5925.00	46.76	7.68	54.44	68.23	-13.80	PK	PASS
H	5850.00	34.69	7.55	42.24	54.00	-11.76	AV	PASS
H	5855.00	35.74	7.56	43.30	54.00	-10.70	AV	PASS
H	5875.00	32.47	7.59	40.06	54.00	-13.95	AV	PASS
H	5925.00	31.73	7.68	39.41	54.00	-14.59	AV	PASS
V	5850.00	35.45	7.55	43.00	54.00	-11.00	AV	PASS
V	5855.00	33.97	7.56	41.53	54.00	-12.47	AV	PASS
V	5875.00	33.95	7.59	41.54	54.00	-12.47	AV	PASS
V	5925.00	30.00	7.68	37.68	54.00	-16.32	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW40)					CH Low: 5755 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	44.60	7.55	52.15	68.23	-16.09	PK	PASS
H	5700.00	46.91	7.56	54.47	105.23	-50.77	PK	PASS
H	5720.00	49.72	7.59	57.31	110.83	-53.53	PK	PASS
H	5725.00	49.09	7.68	56.77	122.23	-65.47	PK	PASS
V	5650.00	43.63	7.55	51.18	68.23	-17.06	PK	PASS
V	5700.00	48.03	7.56	55.59	105.23	-49.65	PK	PASS
V	5720.00	48.83	7.59	56.42	110.83	-54.42	PK	PASS
V	5725.00	51.56	7.68	59.24	122.23	-62.99	PK	PASS
H	5650.00	31.43	7.55	38.98	54.00	-15.03	AV	PASS
H	5700.00	30.11	7.56	37.67	54.00	-16.34	AV	PASS
H	5720.00	35.85	7.59	43.44	54.00	-10.56	AV	PASS
H	5725.00	36.61	7.68	44.29	54.00	-9.71	AV	PASS
V	5650.00	28.77	7.55	36.32	54.00	-17.68	AV	PASS
V	5700.00	32.95	7.56	40.51	54.00	-13.49	AV	PASS
V	5720.00	35.39	7.59	42.98	54.00	-11.02	AV	PASS
V	5725.00	35.47	7.68	43.15	54.00	-10.85	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW40)					CH High: 5795 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	52.86	7.55	60.41	122.23	-61.82	PK	PASS
H	5855.00	50.16	7.56	57.72	110.83	-53.12	PK	PASS
H	5875.00	47.43	7.59	55.02	105.23	-50.21	PK	PASS
H	5925.00	46.87	7.68	54.55	68.23	-13.68	PK	PASS
V	5850.00	51.57	7.55	59.12	122.23	-63.12	PK	PASS
V	5855.00	50.09	7.56	57.65	110.83	-53.19	PK	PASS
V	5875.00	45.32	7.59	52.91	105.23	-52.32	PK	PASS
V	5925.00	46.18	7.68	53.86	68.23	-14.38	PK	PASS
H	5850.00	34.38	7.55	41.93	54.00	-12.07	AV	PASS
H	5855.00	33.31	7.56	40.87	54.00	-13.14	AV	PASS
H	5875.00	30.62	7.59	38.21	54.00	-15.80	AV	PASS
H	5925.00	28.60	7.68	36.28	54.00	-17.72	AV	PASS
V	5850.00	37.93	7.55	45.48	54.00	-8.52	AV	PASS
V	5855.00	33.60	7.56	41.16	54.00	-12.84	AV	PASS
V	5875.00	31.53	7.59	39.12	54.00	-14.89	AV	PASS
V	5925.00	31.83	7.68	39.51	54.00	-14.49	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW80)					CH: 5775 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	44.25	7.55	51.80	68.23	-16.44	PK	PASS
H	5700.00	47.08	7.56	54.64	105.23	-50.59	PK	PASS
H	5720.00	49.99	7.59	57.58	110.83	-53.26	PK	PASS
H	5725.00	51.35	7.68	59.03	122.23	-63.21	PK	PASS
V	5650.00	43.39	7.55	50.94	68.23	-17.30	PK	PASS
V	5700.00	46.34	7.56	53.90	105.23	-51.34	PK	PASS
V	5720.00	50.62	7.59	58.21	110.83	-52.62	PK	PASS
V	5725.00	50.40	7.68	58.08	122.23	-64.16	PK	PASS
H	5650.00	29.54	7.55	37.09	54.00	-16.92	AV	PASS
H	5700.00	31.69	7.56	39.25	54.00	-14.76	AV	PASS
H	5720.00	33.31	7.59	40.90	54.00	-13.10	AV	PASS
H	5725.00	37.67	7.68	45.35	54.00	-8.66	AV	PASS
V	5650.00	31.05	7.55	38.60	54.00	-15.40	AV	PASS
V	5700.00	32.93	7.56	40.49	54.00	-13.52	AV	PASS
V	5720.00	33.93	7.59	41.52	54.00	-12.49	AV	PASS
V	5725.00	37.87	7.68	45.55	54.00	-8.46	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW80)					CH: 5775 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	51.59	7.55	59.14	122.23	-63.09	PK	PASS
H	5855.00	48.29	7.56	55.85	110.83	-54.98	PK	PASS
H	5875.00	47.33	7.59	54.92	105.23	-50.31	PK	PASS
H	5925.00	44.12	7.68	51.80	68.23	-16.44	PK	PASS
V	5850.00	51.80	7.55	59.35	122.23	-62.88	PK	PASS
V	5855.00	49.56	7.56	57.12	110.83	-53.71	PK	PASS
V	5875.00	47.10	7.59	54.69	105.23	-50.55	PK	PASS
V	5925.00	44.07	7.68	51.75	68.23	-16.48	PK	PASS
H	5850.00	34.07	7.55	41.62	54.00	-12.38	AV	PASS
H	5855.00	34.58	7.56	42.14	54.00	-11.86	AV	PASS
H	5875.00	30.61	7.59	38.20	54.00	-15.80	AV	PASS
H	5925.00	31.01	7.68	38.69	54.00	-15.31	AV	PASS
V	5850.00	35.10	7.55	42.65	54.00	-11.36	AV	PASS
V	5855.00	35.34	7.56	42.90	54.00	-11.10	AV	PASS
V	5875.00	33.54	7.59	41.13	54.00	-12.88	AV	PASS
V	5925.00	28.55	7.68	36.23	54.00	-17.77	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.7 Undesirable Emissions

5.7.1 Test Requirement

Test Requirement

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
For transmitters operating solely in the 5.725-5.850 GHz band:
All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

[1]Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
[2]Above 38.6

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35apply to these measurements.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

	Above 960 | 500 | 3 ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. Note: 1) Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)]. 2) In the emission tables above, the tighter limit applies at the band edges. 3) For above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit. 4) For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). 5) EIRP=(E*d))^2)/30 Where: E is the field strength in V/m; d is the measurement distance in meters; EIRP is the equivalent isotropically radiated power in watts. 6) Working in dB units, the above equation is equivalent to: EIRP[dBm]=E[dBμV/m]+20 log(d[meters])-104.77 7) Or, if d is 3 meters: EIRP[dBm]=E[dBμV/m]-95.2
Test Method	ANSI C63.10-2020+Cor 1-2023, section 12.7.4, section 12.7.5, section 12.7.6.

5.7.2 Test Setup Diagram



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

5.7.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power.
Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.
The power of the EUT transmitting frequency should be ignored.
All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.
Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
For 9kHz to 150kHz, Set the spectrum analyzer as:
RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:
RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:
RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:
RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.
RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.7.4 Test Data

PASS.
Please to see the following pages.
The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.
For test of 30MHz-1GHz, during the test, pre-scan all modes, and found the U-NII-1 / 802.11n(HT20) is worse case, the report only record this mode.
For test of 1GHz-40GHz, during the test, pre-scan all modes, and found the U-NII-1 / 802.11n(HT20) & U-NII-3 / 802.11n(HT20) is worse case, the report only record this mode.
The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Radiated Emission Test Data (30-1000MHz)

Test Site:	**966 Chamber #1**	**Polarization:**	**Horizontal**
Distance:	**3m**	**Test Mode:**	**U-NII-1/TM2/ CH Middle**



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	113.7143	49.03	-16.54	32.49	43.50	-11.01	QP	P	
2	212.2695	46.31	-14.64	31.67	43.50	-11.83	QP	P	
3	299.3158	46.10	-12.00	34.10	46.00	-11.90	QP	P	
4 !	601.4265	48.38	-6.20	42.18	46.00	-3.82	QP	P	
5 !	821.7103	45.33	-3.55	41.78	46.00	-4.22	QP	P	
6 *	887.6099	44.69	-2.32	42.37	46.00	-3.63	QP	P	

Note: Level = Reading + Factor **Margin = Level - Limit**

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Radiated Emission Test Data (30-1000MHz)

Test Site:	**966 Chamber #1**	**Polarization:**	**Vertical**
Distance:	**3m**	**Test Mode:**	**U-NII-1/TM2/ CH Middle**



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	52.2078	45.93	-14.32	31.61	40.00	-8.39	QP	P	
2	121.9755	51.29	-17.03	34.26	43.50	-9.24	QP	P	
3	150.5377	53.36	-18.66	34.70	43.50	-8.80	QP	P	
4	299.3158	46.91	-11.96	34.95	46.00	-11.05	QP	P	
5 *	813.1115	46.27	-3.76	42.51	46.00	-3.49	QP	P	
6 !	906.4824	42.44	-2.24	40.20	46.00	-5.80	QP	P	

Note: Level = Reading + Factor **Margin = Level - Limit**

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3220.19	47.18	0.07	47.26	68.23	-20.97	PK	PASS
V	7514.07	42.72	9.84	52.56	68.23	-15.67	PK	PASS
V	9517.90	36.09	13.21	49.30	68.23	-18.93	PK	PASS
V	10362.25	43.48	13.79	57.27	68.23	-10.97	PK	PASS
V	14008.56	37.38	17.34	54.72	68.23	-13.51	PK	PASS
V	15541.00	*	*	*	68.23	*	PK	PASS
H	3200.00	46.88	-0.87	46.01	68.23	-22.22	PK	PASS
H	7500.50	42.88	9.83	52.71	68.23	-15.52	PK	PASS
H	9500.50	36.15	13.14	49.29	68.23	-18.94	PK	PASS
H	10362.00	43.12	13.79	56.91	68.23	-11.32	PK	PASS
H	14003.74	36.54	17.33	53.88	68.23	-14.35	PK	PASS
H	15541.25	*	*	*	68.23	*	PK	PASS
V	3220.19	32.58	0.07	32.65	54.00	-21.35	AV	PASS
V	7514.07	28.15	9.84	37.99	54.00	-16.01	AV	PASS
V	9517.90	24.22	13.21	37.42	54.00	-16.58	AV	PASS
V	10362.25	31.37	13.79	45.16	54.00	-8.84	AV	PASS
V	14008.56	22.23	17.34	39.57	54.00	-14.43	AV	PASS
V	15541.00	*	*	*	54.00	*	AV	PASS
H	3200.00	34.59	-0.87	33.72	54.00	-20.28	AV	PASS
H	7500.50	28.36	9.83	38.19	54.00	-15.81	AV	PASS
H	9500.50	24.53	13.14	37.67	54.00	-16.33	AV	PASS
H	10362.00	31.35	13.79	45.14	54.00	-8.86	AV	PASS
H	14003.74	24.61	17.33	41.95	54.00	-12.05	AV	PASS
H	15541.25	*	*	*	54.00	*	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Middle: 5200 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3419.12	45.79	-0.06	45.73	68.23	-22.50	PK	PASS
V	8009.83	40.19	10.35	50.54	68.23	-17.69	PK	PASS
V	9705.59	37.66	13.20	50.86	68.23	-17.37	PK	PASS
V	10401.75	44.62	13.91	58.53	68.23	-9.70	PK	PASS
V	14319.56	35.68	17.46	53.14	68.23	-15.09	PK	PASS
V	15600.25	*	*	*	68.23	*	PK	PASS
H	3415.86	46.63	-0.07	46.56	68.23	-21.67	PK	PASS
H	8006.35	40.69	10.34	51.03	68.23	-17.20	PK	PASS
H	9704.48	35.64	13.20	48.84	68.23	-19.39	PK	PASS
H	10401.50	44.54	13.91	58.45	68.23	-9.78	PK	PASS
H	14315.62	36.26	17.46	53.71	68.23	-14.52	PK	PASS
H	15602.25	*	*	*	68.23	*	PK	PASS
V	3419.12	33.23	-0.06	33.17	54.00	-20.83	AV	PASS
V	8009.83	28.61	10.35	38.96	54.00	-15.04	AV	PASS
V	9705.59	23.99	13.20	37.19	54.00	-16.81	AV	PASS
V	10401.75	30.27	13.91	44.18	54.00	-9.82	AV	PASS
V	14319.56	22.96	17.46	40.42	54.00	-13.58	AV	PASS
V	15600.25	*	*	*	54.00	*	AV	PASS
H	3415.86	33.15	-0.07	33.07	54.00	-20.93	AV	PASS
H	8006.35	30.16	10.34	40.50	54.00	-13.50	AV	PASS
H	9704.48	23.49	13.20	36.69	54.00	-17.31	AV	PASS
H	10401.50	31.21	13.91	45.12	54.00	-8.88	AV	PASS
H	14315.62	24.57	17.46	42.03	54.00	-11.97	AV	PASS
H	15602.25	*	*	*	54.00	*	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3704.22	46.51	1.09	47.60	68.23	-20.63	PK	PASS
V	8204.02	40.74	10.86	51.60	68.23	-16.63	PK	PASS
V	9820.66	37.65	13.24	50.89	68.23	-17.34	PK	PASS
V	10481.00	44.23	13.96	58.19	68.23	-10.04	PK	PASS
V	14702.05	35.62	17.56	53.19	68.23	-15.04	PK	PASS
V	15720.25	*	*	*	68.23	*	PK	PASS
H	3710.44	46.18	1.10	47.28	68.23	-20.95	PK	PASS
H	8205.20	41.13	10.86	51.99	68.23	-16.24	PK	PASS
H	9807.63	37.57	13.23	50.80	68.23	-17.43	PK	PASS
H	10481.50	42.68	13.96	56.64	68.23	-11.59	PK	PASS
H	14714.48	35.76	17.59	53.35	68.23	-14.88	PK	PASS
H	15721.00	*	*	*	68.23	*	PK	PASS
V	3704.22	33.45	1.09	34.54	54.00	-19.46	AV	PASS
V	8204.02	30.75	10.86	41.61	54.00	-12.39	AV	PASS
V	9820.66	24.43	13.24	37.66	54.00	-16.34	AV	PASS
V	10481.00	32.32	13.96	46.28	54.00	-7.72	AV	PASS
V	14702.05	24.75	17.56	42.31	54.00	-11.69	AV	PASS
V	15720.25	*	*	*	54.00	*	AV	PASS
H	3710.44	34.36	1.10	35.46	54.00	-18.54	AV	PASS
H	8205.20	29.95	10.86	40.82	54.00	-13.18	AV	PASS
H	9807.63	23.45	13.23	36.69	54.00	-17.31	AV	PASS
H	10481.50	30.60	13.96	44.56	54.00	-9.44	AV	PASS
H	14714.48	22.73	17.59	40.32	54.00	-13.68	AV	PASS
H	15721.00	*	*	*	54.00	*	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3219.78	45.66	-0.80	44.86	68.23	-23.37	PK	PASS
V	7514.79	42.29	9.84	52.14	68.23	-16.09	PK	PASS
V	9516.05	35.76	13.20	48.96	68.23	-19.27	PK	PASS
V	11492.50	43.30	15.22	58.52	68.23	-9.71	PK	PASS
V	14019.49	36.93	17.36	54.28	68.23	-13.95	PK	PASS
V	17236.00	*	*	*	68.23	*	PK	PASS
H	3200.25	47.33	-0.87	46.46	68.23	-21.77	PK	PASS
H	7501.50	42.85	9.83	52.68	68.23	-15.55	PK	PASS
H	9500.75	37.31	13.14	50.45	68.23	-17.78	PK	PASS
H	11490.50	42.22	15.22	57.44	68.23	-10.79	PK	PASS
H	14014.96	37.73	17.35	55.08	68.23	-13.15	PK	PASS
H	17236.00	*	*	*	68.23	*	PK	PASS
V	3219.78	32.08	-0.80	31.29	54.00	-22.71	AV	PASS
V	7514.79	28.49	9.84	38.34	54.00	-15.66	AV	PASS
V	9516.05	24.71	13.20	37.91	54.00	-16.09	AV	PASS
V	11492.50	30.53	15.22	45.75	54.00	-8.25	AV	PASS
V	14019.49	24.95	17.36	42.31	54.00	-11.69	AV	PASS
V	17236.00	*	*	*	54.00	*	AV	PASS
H	3200.25	33.80	-0.87	32.93	54.00	-21.07	AV	PASS
H	7501.50	28.32	9.83	38.16	54.00	-15.84	AV	PASS
H	9500.75	24.93	13.14	38.07	54.00	-15.93	AV	PASS
H	11490.50	31.69	15.22	46.91	54.00	-7.09	AV	PASS
H	14014.96	24.21	17.35	41.57	54.00	-12.43	AV	PASS
H	17236.00	*	*	*	54.00	*	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Middle: 5785 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3410.59	47.78	-0.10	47.69	68.23	-20.54	PK	PASS
V	8017.11	42.86	10.36	53.22	68.23	-15.01	PK	PASS
V	9704.79	37.01	13.20	50.21	68.23	-18.02	PK	PASS
V	11570.75	44.64	15.31	59.95	68.23	-8.28	PK	PASS
V	14307.45	36.01	17.44	53.45	68.23	-14.78	PK	PASS
V	17356.50	*	*	*	68.23	*	PK	PASS
H	3412.91	46.04	-0.09	45.96	68.23	-22.27	PK	PASS
H	8012.88	41.94	10.35	52.29	68.23	-15.94	PK	PASS
H	9707.67	36.87	13.20	50.07	68.23	-18.16	PK	PASS
H	11570.50	44.08	15.31	59.39	68.23	-8.84	PK	PASS
H	14315.64	35.45	17.45	52.90	68.23	-15.33	PK	PASS
H	17357.00	*	*	*	68.23	*	PK	PASS
V	3410.59	34.92	-0.10	34.82	54.00	-19.18	AV	PASS
V	8017.11	30.27	10.36	40.63	54.00	-13.37	AV	PASS
V	9704.79	23.19	13.20	36.39	54.00	-17.61	AV	PASS
V	11570.75	31.23	15.31	46.54	54.00	-7.46	AV	PASS
V	14307.45	24.87	17.44	42.32	54.00	-11.68	AV	PASS
V	17356.50	*	*	*	54.00	*	AV	PASS
H	3412.91	34.46	-0.09	34.37	54.00	-19.63	AV	PASS
H	8012.88	28.07	10.35	38.43	54.00	-15.57	AV	PASS
H	9707.67	23.81	13.20	37.01	54.00	-16.99	AV	PASS
H	11570.50	32.32	15.31	47.63	54.00	-6.37	AV	PASS
H	14315.64	24.59	17.45	42.05	54.00	-11.95	AV	PASS
H	17357.00	*	*	*	54.00	*	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH High: 5825MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3716.38	46.92	1.11	48.02	68.23	-20.21	PK	PASS
V	8210.48	42.45	10.88	53.33	68.23	-14.90	PK	PASS
V	9805.77	37.15	13.23	50.38	68.23	-17.85	PK	PASS
V	11651.75	43.64	15.39	59.03	68.23	-9.20	PK	PASS
V	14712.27	35.23	17.58	52.81	68.23	-15.42	PK	PASS
V	17476.25	*	*	*	68.23	*	PK	PASS
H	3701.35	46.84	1.09	47.94	68.23	-20.29	PK	PASS
H	8204.63	42.37	10.86	53.23	68.23	-15.00	PK	PASS
H	9802.29	37.16	13.23	50.39	68.23	-17.84	PK	PASS
H	11652.00	44.83	15.39	60.22	68.23	-8.01	PK	PASS
H	14710.22	36.70	17.58	54.28	68.23	-13.95	PK	PASS
H	17475.50	*	*	*	68.23	*	PK	PASS
V	3716.38	34.00	1.11	35.11	54.00	-18.89	AV	PASS
V	8210.48	29.58	10.88	40.46	54.00	-13.54	AV	PASS
V	9805.77	24.39	13.23	37.62	54.00	-16.38	AV	PASS
V	11651.75	31.31	15.39	46.70	54.00	-7.31	AV	PASS
V	14712.27	23.15	17.58	40.73	54.00	-13.27	AV	PASS
V	17476.25	*	*	*	54.00	*	AV	PASS
H	3701.35	32.82	1.09	33.91	54.00	-20.09	AV	PASS
H	8204.63	29.77	10.86	40.63	54.00	-13.37	AV	PASS
H	9802.29	22.13	13.23	35.36	54.00	-18.64	AV	PASS
H	11652.00	31.70	15.39	47.09	54.00	-6.91	AV	PASS
H	14710.22	24.53	17.58	42.11	54.00	-11.89	AV	PASS
H	17475.50	*	*	*	54.00	*	AV	PASS

Remark:
1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.8 Frequency Stability

5.8.1 Test Requirement

Test Requirement	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

5.8.2 Test Setup Diagram



5.8.3 Test Procedure

✧ **Frequency stability with respect to ambient temperature**

a) Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn ON the EUT and tune it to one of the number of frequencies.

b) Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument through an attenuator if necessary.

NOTE-An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.

c) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).

d) Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters energize only the heater circuit.

e) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.

f) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 min, 5 min, and 10 min after the EUT is energized. Four measurements in total are made.

g) Measure the frequency at each of frequencies.

h) Switch OFF the EUT but do not switch OFF the oscillator heater.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

i) Lower the chamber temperature by not more than 10 ℃, and allow the temperature inside the chamber to stabilize.
j) Repeat step f through step i) down to the lowest specified temperature.

✧ **Frequency stability when varying supply voltage**
Unless otherwise specified, these tests shall be made at ambient room temperature (+15 °C to +25 °C). a) An antenna shall be connected to the antenna output terminals of the EUT if possible. If the EUT is equipped with or uses an adjustable-length antenna, then it shall be fully extended.
Supply the EUT with nominal voltage or install a new or fully charged battery in the EUT. Turn ON the EUT and couple its output to a frequency counter or other frequency measuring instrument.
NOTE An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.
b) Tune the EUT to one of the number of frequencies. Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).
c) Measure the frequency at each of the frequencies.
d) Repeat the above procedure at 85% and 115% of the nominal supply voltage.

5.8.4 Test Data

PASS.
Please refer to Annex G for details.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

ANNEX A TEST SETUP PHOTOS

Please refer to the document “8427EU010907W-AA.PDF”

ANNEX B EXTERNAL PHOTOS

Please refer to the document “8427EU010907W-AB.PDF”

ANNEX C INTERNAL PHOTOS

Please refer to the document “8427EU010907W-AC.PDF”

ANNEX G TEST DATA

Please refer to the document “8427EU010907W-AG.PDF”

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the “inspection and testing dedicated stamp” or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com