

TEST REPORT

FCC ID..... :	2ABC5-E0133	
Test Report No..... :	TCT260128E052	
Date of issue..... :	Mar. 24, 2026	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	SHENZHEN ELECTRON TECHNOLOGY CO., LTD.	
Address..... :	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.	
Manufacturer's name ... :	SHENZHEN ELECTRON TECHNOLOGY CO., LTD.	
Address..... :	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.	
Standard(s)	FCC CFR Title 47 Part 15 Subpart C Section 15.247 FCC KDB 558074 D01 15.247 Meas Guidance v05r02 FCC KDB 662911 D01 Multiple Transmitter Output v02r01 ANSI C63.10-2020+Cor 1-2023	
Product Name..... :	Android Tablet	
Trade Mark	N/A	
Model/Type reference..... :	KDS2485T	
Rating(s)..... :	Adapter Information: Model: FJ-SW729S1205000U Input: AC 100-240V, 50/60Hz, 1.5A Max Output: DC 12V, 5A OR DC 48V, 1.25A(POE power supply)	
Date of receipt of test item	Jan. 27, 2026	
Date (s) of performance of test..... :	Jan. 27, 2026 ~ Mar. 24, 2026	
Tested by (+signature) ... :	Yannie ZHONG	<i>Yannie Zhong</i>
Check by (+signature).... :	Brews XU	<i>Brews Xu</i>
Approved by (+signature):	Beryl ZHAO	<i>Beryl Zhao</i>

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
1.3. Operation Frequency	4
2. Test Result Summary	5
3. General Information.....	6
3.1. Test environment and mode.....	6
3.2. Description of Support Units.....	7
4. Facilities and Accreditations	8
4.1. Facilities	8
4.2. Location	8
5. Measurement Uncertainty	8
6. Test Results and Measurement Data	9
6.1. Antenna requirement	9
6.2. Conducted Emission.....	10
6.3. Maximum Conducted (Peak) Output Power	14
6.4. Emission Bandwidth	15
6.5. Power Spectral Density.....	16
6.6. Conducted Band Edge and Spurious Emission Measurement	17
6.7. Radiated Spurious Emission Measurement.....	19
Appendix A: Test Result of Conducted Test	
Appendix B: Photographs of Test Setup	
Appendix C: Photographs of EUT	

1. General Product Information

1.1. EUT description

Product Name.....:	Android Tablet
Model/Type reference.....:	KDS2485T
Sample Number.....:	TCT260128E039-0101
Operation Frequency	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)/802.11ax(HE20))
Channel Separation.....:	5MHz
Number of Channel	11 for 802.11b/802.11g/802.11n(HT20)/802.11ax(HE20)
Modulation Technology	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n: Orthogonal Frequency Division Multiplexing (OFDM) 802.11ax: Orthogonal Frequency-Division Multiple Access (OFDMA)
Data speed	802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps 802.11g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps 802.11n/802.11ax: Up to 150Mbps
Antenna Type.....:	FPC Antenna
Antenna Gain.....:	ANT1: 2.79dBi ANT2: 2.86dBi
Rating(s).....:	Adapter Information: Model: FJ-SW729S1205000U Input: AC 100-240V, 50/60Hz, 1.5A Max Output: DC 12V, 5A OR DC 48V, 1.25A(POE power supply)

Note: 1. The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

2. 802.11ax not support partial RU mode, all test configurations are solely applicable to Full RU.

3. SISO: 802.11b/g; MIMO: 802.11n/ax

1.2. Model(s) list

None.

1.3. Operation Frequency

For 802.11b/g/n(HT20)/ax(HE20)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	--	--

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11b/802.11g/802.11n(HT20)/802.11ax(HE20)

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The Highest channel	2462MHz

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (b)(4)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3)	PASS
6dB Emission Bandwidth	§15.247 (a)(2)	PASS
Power Spectral Density	§15.247 (e)	PASS
Conducted Band Edge and Spurious Emission	§15.247(d)	PASS
Spurious Emission	§15.205/§15.209	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. General Information

3.1. Test environment and mode

Operating Environment:		
Condition	Conducted Emission	Radiated Emission
Temperature:	22.8 °C	22.8 °C
Humidity:	49 % RH	51 % RH
Atmospheric Pressure:	1010 mbar	1010 mbar
Test Software:		
Software Information:	CMD	
Power Level:	Default	
Test Mode:		
Engineer mode:	Keep the EUT in continuous transmitting by select channel and modulations with max duty cycle.	
The sample was placed 0.8m & 1.5m for the measurement below & above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case (Z axis) are shown in Test Results of the following pages.		

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	6.5Mbps
802.11ax(HE20)	6.5Mbps

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- A2LA-No.: 4320.01

SHENZHEN TONGCE TESTING LAB

The testing lab has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

5. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	Occupied Bandwidth	± 57.74 kHz
5	All emissions, radiated(<1 GHz)	± 4.56 dB
6	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
7	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(b)(4)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b)(4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
E.U.T Antenna:	
The WIFI antenna is FPC antenna which permanently attached, and the best case gain of the antenna is 2.86dBi @ANT2.	

6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10-2020+Cor 1-2023														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane 40cm Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test Mode:	Transmitting Mode														
Test Procedure:	1. The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10-2020+Cor 1-2023 on conducted measurement.														
Test Result:	PASS														


6.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)					
Equipment	Manufacturer	Model	Serial Number	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCI3	100898	Jun. 26, 2025	Jun. 25, 2026
LISN	Schwarzbeck	NSLK 8126	8126453	Jan. 16, 2026	Jan. 15, 2027
10db Attenuator	R&S	ESH3-Z2	102720	Dec. 15, 2025	Dec. 14, 2026
Line-5	TCT	CE-05	/	Jun. 26, 2025	Jun. 25, 2026
EMI Test Software	EZ_EMG	EMEC-3A1	1.1.4.2	/	/

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



No.	Frequency (MHz)	QP Value (dBμV)	QP Limit (dBμV)	QP Margin (dB)	AVG Value (dBμV)	AVG Limit (dBμV)	AVG Margin (dB)	Result	Line
1	0.182	51.57	64.40	-12.83	33.92	54.40	-20.48	Pass	Line 1
2	0.218	47.35	62.89	-15.54	29.42	52.89	-23.47	Pass	Line 1
3	0.250	44.40	61.76	-17.36	26.23	51.76	-25.53	Pass	Line 1
4	0.322	43.01	59.66	-16.65	27.29	49.66	-22.37	Pass	Line 1
5	0.394	42.01	57.98	-15.97	27.55	47.98	-20.43	Pass	Line 1
6	0.430	41.93	57.25	-15.32	30.93	47.25	-16.32	Pass	Line 1

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard


Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



No.	Frequency (MHz)	QP Value (dBμV)	QP Limit (dBμV)	QP Margin (dB)	AVG Value (dBμV)	AVG Limit (dBμV)	AVG Margin (dB)	Result	Line
1	0.178	50.83	64.58	-13.75	38.48	54.58	-16.10	Pass	Neutral
2	0.214	46.45	63.05	-16.60	34.56	53.05	-18.49	Pass	Neutral
3	0.250	43.72	61.76	-18.04	32.32	51.76	-19.44	Pass	Neutral
4	0.286	43.35	60.64	-17.29	30.85	50.64	-19.79	Pass	Neutral
5	0.394	44.40	57.98	-13.58	33.16	47.98	-14.82	Pass	Neutral
6	0.426	44.21	57.33	-13.12	35.13	47.33	-12.20	Pass	Neutral

Note 1: Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Note 2: Measurements were conducted in all three channels (high, middle, low) and all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11ax(HE20), and the worst case Mode (Highest channel and 802.11ax(HE20), ANT1) was submitted only.

6.3. Maximum Conducted (Peak) Output Power

6.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB 558074 D01 v05r02
Limit:	30dBm
Test Setup:	 The diagram illustrates the test setup. On the left is a green power meter with a screen and two ports. A black RF cable connects one of its ports to a yellow rectangular device on the right labeled 'EUT' (Equipment Under Test).
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the power meter by RF cable. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Measure the Peak output power and record the results in the test report.
Test Result:	PASS

6.3.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Power Meter	KEYSIGHT	U2021XA	MY55080002	Jun. 26, 2025	Jun. 25, 2026

6.4. Emission Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB 558074 D01 v05r02
Limit:	>500kHz
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. Set to the maximum power setting and enable the EUT transmit continuously. 2. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% ~5% of OBW. Set the Video bandwidth (VBW) $\geq 3 \times$ RBW. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 3. Measure and record the results in the test report.
Test Result:	PASS

6.4.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFtest	MW100-RFCB	MW210531TCT	Sep. 17, 2025	Sep. 16, 2026

6.5. Power Spectral Density

6.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB 558074 D01 v05r02
Limit:	The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$. Video bandwidth VBW $\geq 3 \times \text{RBW}$. Set the span to at least 1.5 times the OBW. 4. Detector = Peak, Sweep time = auto couple. 5. Trace mode =max hold. Use the peak marker function to determine the maximum power level. 6. Measure and record the results in the test report.
Test Result:	PASS

6.5.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFTest	MW100-RFCB	MW210531TCT	Sep. 17, 2025	Sep. 16, 2026

6.6. Conducted Band Edge and Spurious Emission Measurement

6.6.1. Test Specification


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 v05r02
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	 The diagram illustrates the test setup. On the left is a green Spectrum Analyzer with a blue screen. A black RF cable connects its input port to the input of a yellow rectangular box labeled 'EUT' (Equipment Under Test).
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d). 4. Measure and record the results in the test report. 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS


6.6.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFTest	MW100-RFCB	MW210531TCT	Sep. 17, 2025	Sep. 16, 2026


6.7. Radiated Spurious Emission Measurement

6.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209					
Test Method:	ANSI C63.10-2020+Cor 1-2023					
Frequency Range:	9 kHz to 25 GHz					
Measurement Distance:	3 m					
Antenna Polarization:	Horizontal & Vertical					
Operation mode:	Transmitting mode with modulation					
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark	
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
Peak		1MHz	10Hz	Average Value		
Limit:	Frequency		Field Strength (microvolts/meter)		Measurement Distance (meters)	
	0.009-0.490		2400/F(KHz)		300	
	0.490-1.705		24000/F(KHz)		30	
	1.705-30		30		30	
	30-88		100		3	
	88-216		150		3	
	216-960		200		3	
	Above 960		500		3	
	Frequency		Field Strength (microvolts/meter)		Measurement Distance (meters)	Detector
	Above 1GHz		500		3	Average
			5000		3	Peak
	Test setup:	For radiated emissions below 30MHz				
						
		30MHz to 1GHz				



Above 1GHz



Test Procedure:

1. For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which

	maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. 3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level 4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. 5. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=120 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f > 1$ GHz for peak measurement. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test results:	PASS


6.7.2. Test Instruments

Radiated Emission Test Site (966)					
Equipment	Manufacturer	Model	Serial Number	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCI7	100529	Jan. 16, 2026	Jan. 15, 2027
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 26, 2025	Jun. 25, 2026
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Jan. 16, 2026	Jan. 15, 2027
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Apr. 11, 2025	Apr. 10, 2026
Pre-amplifier	HP	8447D	2727A05017	Jun. 26, 2025	Jun. 25, 2026
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 30, 2025	Jun. 29, 2026
Broadband Antenna	Schwarzbeck	VULB9163	340	Jun. 29, 2025	Jun. 28, 2026
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jun. 29, 2025	Jun. 28, 2026
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Jan. 17, 2026	Jan. 16, 2027
Coaxial cable	SKET	RE-03-D	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-03-M	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-03-L	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-04-D	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-04-M	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-04-L	/	Jun. 27, 2025	Jun. 26, 2026
Antenna Mast	Keleto	RE-AM	/	/	/
EMI Test Software	EZ_EMCC	FA-03A2 RE+	1.1.4.2	/	/

6.7.3. Test Data

Please refer to following diagram for individual
Below 1GHz

Horizontal:




Site 3m Anechoic Chamber2

Polarization: **Horizontal**

Temperature: 22.8(C) Humidity: 51 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	222.1697	54.39	-20.54	33.85	46.00	-12.15	QP	P	
2	297.4847	39.59	-17.61	21.98	46.00	-24.02	QP	P	
3	370.7023	41.04	-15.89	25.15	46.00	-20.85	QP	P	
4	444.8514	41.37	-13.70	27.67	46.00	-18.33	QP	P	
5	593.0496	41.97	-10.45	31.52	46.00	-14.48	QP	P	
6	890.7277	34.90	-6.26	28.64	46.00	-17.36	QP	P	

Vertical:



Site 3m Anechoic Chamber2

Polarization: **Vertical**

Temperature: 22.8(C)

Humidity: 51 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	32.7486	54.89	-19.39	35.50	40.00	-4.50	QP	P	
2	86.2000	45.82	-22.39	23.43	40.00	-16.57	QP	P	
3	147.9214	42.79	-17.39	25.40	43.50	-18.10	QP	P	
4	222.1697	60.12	-20.54	39.58	46.00	-6.42	QP	P	
5	446.4140	42.44	-13.66	28.78	46.00	-17.22	QP	P	
6	668.1422	44.62	-8.46	36.16	46.00	-9.84	QP	P	

Note: 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11ax(HE20),), and the worst case Mode (Highest channel and 802.11ax, MIMO) was submitted only.

3. Freq. = Emission frequency in MHz

Measurement (dBuV/m) = Reading level (dBuV) + Corr. Factor (dB)

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

Limit (dBuV/m) = Limit stated in standard

Margin (dB) = Measurement (dBuV/m) – Limits (dBuV/m)


* is meaning the worst frequency has been tested in the test frequency range.

Test Result of Radiated Spurious at Band edges

Lowest channel 2412:

Horizontal:


110.0 dBuV/m



No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
1	2310.000	50.51	-14.18	36.33	74.00	-37.67	peak	
2	2310.000	41.52	-14.18	27.34	54.00	-26.66	AVG	
3 *	2386.488	52.05	-14.26	37.79	54.00	-16.21	AVG	
4	2386.563	57.86	-14.26	43.60	74.00	-30.40	peak	
5	2390.000	52.19	-14.26	37.93	74.00	-36.07	peak	
6	2390.000	45.09	-14.26	30.83	54.00	-23.17	AVG	

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

Vertical:




No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
1	2310.000	49.95	-14.18	35.77	74.00	-38.23	peak	
2	2310.000	41.33	-14.18	27.15	54.00	-26.85	AVG	
3	2390.000	53.29	-14.26	39.03	74.00	-34.97	peak	
4 *	2390.000	44.19	-14.26	29.93	54.00	-24.07	AVG	

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

Highest channel 2462:

Horizontal:




No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measurement(dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
1	2483.500	55.22	-14.10	41.12	74.00	-32.88	peak	
2	2483.500	49.04	-14.10	34.94	54.00	-19.06	AVG	
3 *	2487.039	57.58	-14.09	43.49	54.00	-10.51	AVG	
4	2487.070	61.64	-14.09	47.55	74.00	-26.45	peak	
5	2500.000	54.19	-14.07	40.12	74.00	-33.88	peak	
6	2500.000	43.97	-14.07	29.90	54.00	-24.10	AVG	

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

Vertical:



No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
1	2483.500	53.33	-14.10	39.23	74.00	-34.77	peak	
2 *	2483.500	44.68	-14.10	30.58	54.00	-23.42	AVG	
3	2500.000	53.51	-14.07	39.44	74.00	-34.56	peak	
4	2500.000	44.18	-14.07	30.11	54.00	-23.89	AVG	

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)
3. Measurements were conducted in all modulation (802.11b, 802.11g, 802.11n(HT20), 802.11ax(HE20)), and the worst case Mode 802.11b, ANT1 was submitted only.

Above 1GHz

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	54.38	---	-9.48	44.90	---	74	54	-9.10
7236	H	50.21	---	-1.34	48.87	---	74	54	-5.13
---	H	---	---	---	---	---	---	---	---
4824	V	53.40	---	-9.48	43.92	---	74	54	-10.08
7236	V	48.76	---	-1.34	47.42	---	74	54	-6.58
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	53.07	---	-9.37	43.70	---	74	54	-10.30
7311	H	50.62	---	-1.17	49.45	---	74	54	-4.55
---	H	---	---	---	---	---	---	---	---
4874	V	52.18	---	-9.37	42.81	---	74	54	-11.19
7311	V	50.98	---	-1.17	49.81	---	74	54	-4.19
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	54.95	---	-9.26	45.69	---	74	54	-8.31
7386	H	50.39	---	-1.01	49.38	---	74	54	-4.62
---	H	---	---	---	---	---	---	---	---
4924	V	52.26	---	-9.26	43.00	---	74	54	-11.00
7386	V	47.59	---	-1.01	46.58	---	74	54	-7.42
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Modulation Type: 802.11g

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	55.46	---	-9.48	45.98	---	74	54	-8.02
7236	H	46.49	---	-1.34	45.15	---	74	54	-8.85
---	H	---	---	---	---	---	---	---	---
4824	V	55.68	---	-9.48	46.20	---	74	54	-7.80
7236	V	49.75	---	-1.34	48.41	---	74	54	-5.59
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	55.47	---	-9.37	46.10	---	74	54	-7.90
7311	H	47.84	---	-1.17	46.67	---	74	54	-7.33
---	H	---	---	---	---	---	---	---	---
4874	V	56.07	---	-9.37	46.70	---	74	54	-7.30
7311	V	49.80	---	-1.17	48.63	---	74	54	-5.37
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	54.27	---	-9.26	45.01	---	74	54	-8.99
7386	H	50.01	---	-1.01	49.00	---	74	54	-5.00
---	H	---	---	---	---	---	---	---	---
4924	V	52.36	---	-9.26	43.10	---	74	54	-10.90
7386	V	47.16	---	-1.01	46.15	---	74	54	-7.85
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Modulation Type: 802.11n (HT20)

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	55.66	---	-9.48	46.18	---	74	54	-7.82
7236	H	49.05	---	-1.34	47.71	---	74	54	-6.29
---	H	---	---	---	---	---	---	---	---
4824	V	54.73	---	-9.48	45.25	---	74	54	-8.75
7236	V	47.68	---	-1.34	46.34	---	74	54	-7.66
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	53.77	---	-9.37	44.40	---	74	54	-9.60
7311	H	47.92	---	-1.17	46.75	---	74	54	-7.25
---	H	---	---	---	---	---	---	---	---
4874	V	55.75	---	-9.37	46.38	---	74	54	-7.62
7311	V	49.41	---	-1.17	48.24	---	74	54	-5.76
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	54.49	---	-9.26	45.23	---	74	54	-8.77
7386	H	50.32	---	-1.01	49.31	---	74	54	-4.69
---	H	---	---	---	---	---	---	---	---
4924	V	54.43	---	-9.26	45.17	---	74	54	-8.83
7386	V	48.63	---	-1.01	47.62	---	74	54	-6.38
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Modulation Type: 802.11ax (HE20)

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	54.58	---	-9.48	45.10	---	74	54	-8.90
7236	H	46.27	---	-1.34	44.93	---	74	54	-9.07
---	H	---	---	---	---	---	---	---	---
4824	V	56.54	---	-9.48	47.06	---	74	54	-6.94
7236	V	46.17	---	-1.34	44.83	---	74	54	-9.17
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	55.10	---	-9.37	45.73	---	74	54	-8.27
7311	H	50.22	---	-1.17	49.05	---	74	54	-4.95
---	H	---	---	---	---	---	---	---	---
4874	V	53.51	---	-9.37	44.14	---	74	54	-9.86
7311	V	46.93	---	-1.17	45.76	---	74	54	-8.24
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	52.88	---	-9.26	43.62	---	74	54	-10.38
7386	H	50.55	---	-1.01	49.54	---	74	54	-4.46
---	H	---	---	---	---	---	---	---	---
4924	V	53.16	---	-9.26	43.90	---	74	54	-10.10
7386	V	47.02	---	-1.01	46.01	---	74	54	-7.99
---	V	---	---	---	---	---	---	---	---

Note:

- Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
- Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
- Data of measurement shown “---”in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
- All the restriction bands are compliance with the limit of 15.209, and only worst condition report(ANT1 for 802.11b/g, MIMO for 802.11n/ax)


Appendix A: Test Result of Conducted Test

1. Duty Cycle


1.1 Test Result

Ant1									
Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	/	/	12.417	12.440	99.82	0.01	0.03
		2437	/	/	12.416	12.440	99.81	0.01	0.00
		2462	/	/	12.416	12.440	99.81	0.01	0.00
802.11g	SISO	2412	/	/	2.065	2.084	99.09	0.04	0.07
		2437	/	/	2.064	2.083	99.09	0.04	0.04
		2462	/	/	2.065	2.084	99.09	0.04	0.07
802.11n (HT20)	MIMO	2412	/	/	1.921	1.939	99.07	0.04	0.03
		2437	/	/	1.921	1.940	99.02	0.04	0.03
		2462	/	/	1.920	1.940	98.97	0.05	0.03
802.11ax (HEW20)	MIMO	2412	SU	/	1.489	1.508	98.74	0.06	0.03
		2437	SU	/	1.489	1.508	98.74	0.06	0.07
		2462	SU	/	1.489	1.507	98.81	0.05	0.07


1.2 Test Graph




802.11b HCH 2462MHz Ant1 (SISO) NTV




802.11g LCH 2412MHz Ant1 (SISO) NTV




802.11g MCH 2437MHz Ant1 (SISO) NTNV




802.11g HCH 2462MHz Ant1 (SISO) NTNV




802.11n(HT20) LCH 2412MHz Ant1 (MIMO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (MIMO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (MIMO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (MIMO) NTN



802.11ax(HEW20) MCH 2437MHz SU / Ant1 (MIMO) NTNv



802.11ax(HEW20) HCH 2462MHz SU / Ant1 (MIMO) NTNv



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	12.878	/	Pass
		2437	/	/	1	12.925	/	Pass
		2462	/	/	1	12.930	/	Pass
802.11g	SISO	2412	/	/	1	17.583	/	Pass
		2437	/	/	1	17.480	/	Pass
		2462	/	/	1	17.489	/	Pass
802.11n (HT20)	MIMO	2412	/	/	1	18.333	/	Pass
		2437	/	/	1	18.293	/	Pass
		2462	/	/	1	18.291	/	Pass
802.11ax (HEW20)	MIMO	2412	SU	/	1	19.128	/	Pass
		2437	SU	/	1	19.170	/	Pass
		2462	SU	/	1	19.192	/	Pass


2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	6dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	8.211	≥ 0.5	Pass
		2437	/	/	1	8.216	≥ 0.5	Pass
		2462	/	/	1	8.220	≥ 0.5	Pass
802.11g	SISO	2412	/	/	1	16.374	≥ 0.5	Pass
		2437	/	/	1	16.289	≥ 0.5	Pass
		2462	/	/	1	16.217	≥ 0.5	Pass
802.11n (HT20)	MIMO	2412	/	/	1	17.499	≥ 0.5	Pass
		2437	/	/	1	17.462	≥ 0.5	Pass
		2462	/	/	1	17.550	≥ 0.5	Pass
802.11ax (HEW20)	MIMO	2412	SU	/	1	18.334	≥ 0.5	Pass
		2437	SU	/	1	18.209	≥ 0.5	Pass
		2462	SU	/	1	18.240	≥ 0.5	Pass


Only worst condition report(ANT 1)

2.2 Test Graph


2.2.1 OBW




802.11b HCH 2462MHz Ant1 (SISO) NTV




802.11g LCH 2412MHz Ant1 (SISO) NTV




802.11g MCH 2437MHz Ant1 (SISO) NTNV




802.11g HCH 2462MHz Ant1 (SISO) NTNV




802.11n(HT20) LCH 2412MHz Ant1 (MIMO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (MIMO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (MIMO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (MIMO) NTN




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (MIMO) NTN




802.11ax(HEW20) HCH 2462MHz SU / Ant1 (MIMO) NTN




2.2.2 6dB BW




802.11b HCH 2462MHz Ant1 (SISO) NTV




802.11g LCH 2412MHz Ant1 (SISO) NTV




802.11g MCH 2437MHz Ant1 (SISO) NTNV




802.11g HCH 2462MHz Ant1 (SISO) NTNV




802.11n(HT20) LCH 2412MHz Ant1 (MIMO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (MIMO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (MIMO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (MIMO) NTN



802.11ax(HEW20) MCH 2437MHz SU / Ant1 (MIMO) NTNv



802.11ax(HEW20) HCH 2462MHz SU / Ant1 (MIMO) NTNv



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Peak Conducted Output Power (dBm)				Verdict
					ANT1	ANT2	MIMO	Limit	
802.11b	SISO	2412	/	/	16.29	18.72	/	<=30	Pass
		2437	/	/	17.17	18.35	/	<=30	Pass
		2462	/	/	17.46	18.76	/	<=30	Pass
802.11g	SISO	2412	/	/	20.24	21.15	/	<=30	Pass
		2437	/	/	20.78	21.69	/	<=30	Pass
		2462	/	/	21.29	21.91	/	<=30	Pass
802.11n (HT20)	MIMO	2412	/	/	20.24	21.11	23.71	<=30	Pass
		2437	/	/	20.78	21.33	24.07	<=30	Pass
		2462	/	/	21.22	21.61	24.43	<=30	Pass
802.11ax (HEW20)	MIMO	2412	SU	/	21.35	22.54	25.00	<=30	Pass
		2437	SU	/	21.95	23.05	25.55	<=30	Pass
		2462	SU	/	22.41	23.14	25.80	<=30	Pass
Note1: Antenna Gain: Ant1: 2.79dBi; Ant2: 2.86dBi;									
Note2: Directional Gain: Uncorrelated(Directional Gain =5.84dBi)									


4. Maximum Power Spectral Density

4.1 Test Result


Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm)				Verdict
					ANT1	ANT2	MIMO	Limit	
802.11b	SISO	2412	/	/	-5.48	1.08	/	<=8	Pass
		2437	/	/	-8.59	-7.09	/	<=8	Pass
		2462	/	/	-8.07	-6.70	/	<=8	Pass
802.11g	SISO	2412	/	/	-13.31	-10.47	/	<=8	Pass
		2437	/	/	-12.49	-10.16	/	<=8	Pass
		2462	/	/	-11.45	-10.04	/	<=8	Pass
802.11n (HT20)	MIMO	2412	/	/	-12.67	-11.72	-10.89	<=8	Pass
		2437	/	/	-12.82	-11.58	-10.48	<=8	Pass
		2462	/	/	-12.33	-11.91	-10.76	<=8	Pass
802.11ax (HEW20)	MIMO	2412	SU	/	-12.90	-12.53	-11.63	<=8	Pass
		2437	SU	/	-13.14	-12.37	-11.11	<=8	Pass
		2462	SU	/	-13.42	-12.15	-10.18	<=8	Pass

Note1: Antenna Gain: Ant1: 2.79dBi; Ant2: 2.86dBi;
 Note2: Directional Gain: Uncorrelated(Directional Gain = 5.84dBi)


4.2 Test Graph




802.11b MCH 2437MHz Ant1 (SISO) NTN




802.11b MCH 2437MHz Ant2 (SISO) NTN




802.11b HCH 2462MHz Ant1 (SISO) NTNV




802.11b HCH 2462MHz Ant2 (SISO) NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11g MCH 2437MHz Ant1 (SISO) NTN




802.11g MCH 2437MHz Ant2 (SISO) NTN




802.11g HCH 2462MHz Ant1 (SISO) NTV




802.11g HCH 2462MHz Ant2 (SISO) NTV




802.11n(HT20) LCH 2412MHz Ant1 (MIMO) NTN




802.11n(HT20) LCH 2412MHz Ant2 (MIMO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (MIMO) NTVN




802.11n(HT20) MCH 2437MHz Ant2 (MIMO) NTVN




802.11n(HT20) HCH 2462MHz Ant1 (MIMO) NTNV




802.11n(HT20) HCH 2462MHz Ant2 (MIMO) NTNV




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (MIMO) NTNv




802.11ax(HEW20) LCH 2412MHz SU / Ant2 (MIMO) NTNv




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (MIMO) NTN




802.11ax(HEW20) MCH 2437MHz SU / Ant2 (MIMO) NTN



802.11ax(HEW20) HCH 2462MHz SU / Ant1 (MIMO) NTNv



802.11ax(HEW20) HCH 2462MHz SU / Ant2 (MIMO) NTNv



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)
802.11b	SISO	2412	/	/	1	5.65
					2	7.79
		2437	/	/	1	6.71
					2	7.97
		2462	/	/	1	7.15
					2	8.24
802.11g	SISO	2412	/	/	1	0.47
					2	1.67
		2437	/	/	1	0.81
					2	2.11
		2462	/	/	1	1.27
					2	2.16
802.11n (HT20)	MIMO	2412	/	/	1	0.31
					2	1.76
		2437	/	/	1	1.00
					2	1.88
		2462	/	/	1	1.14
					2	2.00
802.11ax (HEW20)	MIMO	2412	SU	/	1	0.53
					2	1.70
		2437	SU	/	1	0.81
					2	2.19
		2462	SU	/	1	1.39
					2	2.44

5.1.2 CSE


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	/	/	1	5.65	-14.35	Pass
					2	7.79	-12.21	Pass
		2437	/	/	1	6.71	-13.29	Pass
					2	7.97	-12.03	Pass
		2462	/	/	1	7.15	-12.85	Pass
					2	8.24	-11.76	Pass
802.11g	SISO	2412	/	/	1	0.47	-19.53	Pass
					2	1.67	-18.33	Pass
		2437	/	/	1	0.81	-19.19	Pass
					2	2.11	-17.89	Pass
		2462	/	/	1	1.27	-18.73	Pass
					2	2.16	-17.84	Pass
802.11n (HT20)	MIMO	2412	/	/	1	0.31	-19.69	Pass
					2	1.76	-18.24	Pass
		2437	/	/	1	1.00	-19.00	Pass
					2	1.88	-18.12	Pass
		2462	/	/	1	1.14	-18.86	Pass
					2	2.00	-18.00	Pass
802.11ax (HEW20)	MIMO	2412	SU	/	1	0.53	-19.47	Pass
					2	1.70	-18.30	Pass
		2437	SU	/	1	0.81	-19.19	Pass

					2	2.19	-17.81	Pass
		2462	SU	/	1	1.39	-18.61	Pass
					2	2.44	-17.56	Pass




5.2 Test Graph

5.2.1 Ref



802.11b MCH 2437MHz Ant1 (SISO) NTN



802.11b MCH 2437MHz Ant2 (SISO) NTN

