FCC TEST REPORT

Product	:	In-wall Smart Dimmer Switch
Trade mark	:	iDevices In-wall Dimmer Switch
Model/Type reference	:	IDEV0009
Report Number	:	1612300603RFC-1
Date of Issue	:	February 9, 2017
FCC ID	:	2ABDJ-DIMMER
Test Standards	:	47 CFR Part 15 Subpart C
Test result	:	PASS

Prepared for:

iDevices, LLC

136 Simsbury Rd Building 12, Avon, Connecticut 06001, United States

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Tested by: Hoping Chen
Hoping Chen
Engineer

Reviewed by: Leo Lai
Leo Lai
Senior Supervisor

Approved by:
Billy Li
Technical Director

Date: February 9, 2017

UnionTrust Laboratories UnionTrust * Certified *

Version

Version No.	Date	Description
V1.0	February 9, 2017	Original

Content

Page

1 GENERAL INFORMATION 4
1.1 CLIENT INFORMATION 4
1.2 GENERAL DESCRIPTION OF EUT 4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD 4
1.4 DESCRIPTION OF SUPPORT UNITS 5
1.5 TEST LOCATION 5
1.6 TEST FACILITY 5
1.7 DEVIATION FROM STANDARDS 5
1.8 ABNORMALITIES FROM STANDARD CONDITIONS 5
1.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER 5
1.10 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2) 6
2 TEST SUMMARY 7
3 EQUIPMENT LIST 8
4 TEST REQUIREMENT 10
4.1 TEST SETUP 10
4.1.1 For Conducted test setup 10
4.1.2 For Radiated Emissions test setup 10
4.1.3 For Conducted Emissions test setup 11
4.2 TEST ENVIRONMENT 11
4.3 SYSTEM TEST CONFIGURATION 11
4.4 TEST CONDITION 12
4.4.1 Test channel 12
4.4.2 Duty Cycle 12
5 RADIO TECHNICAL REQUIREMENTS SPECIFICATION 13
5.1 ANTENNA REQUIREMENT 13
5.2 CONDUCTED PEAK OUTPUT POWER 14
5.3 6DB BANDWIDTH 15
5.4 POWER SPECTRAL DENSITY 18
5.5 CONDUCTED OUT OF BAND EMISSION 21
5.6 RADIATED SPURIOUS EMISSIONS 27
5.7 BAND EDGE MEASUREMENTS (RADIATED) 33
5.8 CONDUCTED EMISSIONS 36
APPENDIX 1 PHOTOGRAPHS OF TEST SETUP 37
APPENDIX 2 PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS 37

1 General Information

1.1 Client Information

Applicant:	iDevices, LLC
Address of Applicant:	136 Simsbury Rd Building 12, Avon, Connecticut 06001, United States
Manufacturer:	EWIG INDUSTRIES MACAO COMMERCIAL OFFSHORE LTD
Address of Manufacturer:	11/F, Houtex Industial Building E16 Hung To Road, Kwun Tung Kawloon, Hong Kong

1.2 General Description of EUT

Product Name:	In-wall Smart Dimmer Switch
Model No.(EUT):	IDEV0009
Add Model No.:	N/A
Trade Mark:	iDevices In-wall Dimmer Switch
EUT Supports Radio application:	Bluetooth V4.0 BLE only Wlan 2.4GHz 802.11b/g/n(HT20)
Power Supply:	120Vac/60Hz
USB Micro-B Plug Cable:	N/A
Sample Received Date:	January 25, 2017
Sample Tested Date:	January 25, 2017 to February 9, 2017

1.3 Product Specification subjective to this standard

Operation Frequency:	2400MHz-2483.5MHz
Bluetooth Version:	V4.0 BLE
Modulation Technique:	DTS
Modulation Type:	GFSK
Number of Channel:	40
Channel Separation:	2MHz
Sample Type:	Mobile production
Antenna Type:	PCB Antenna
Antenna Gain:	3.3 dBi
Normal Test Voltage:	5Vdc from USB-to-Serial Adapter
Software Version:	-
Hardware Version:	iDev 036 Rev E

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

1.4 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Brand	Model No.	Certification	Supplied by
Laptop	Lenovo	E450	FCC ID and DOC	UnionTrust
USB Isolator	TITAN	USB-ISO-M	FCC DOC	Applicant
iDevices Tag Connect Programmer	-	iDev 046 Rev B	-	Applicant

2) Cable

Cable No.	Description	Connector Type	Cable Type/Length	Supplied by
1	Antenna cable	SMA	0.2m(Shielded)	UnionTrust
2	USB Cable	USB	1.2m(shielded)	Applicant

1.5 Test Location

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109

Telephone: +86 (0) 755 2823 0888 Fax: +86 (0) 755 2823 0886

Tests were sub-contracted. (FCC 47 CFR Part 15 Subpart C Section 15.205/15.207/15.209)

Compliance Certification Services (Shenzhen) Inc.

No.10-1 Mingkeda Logistics Park, No.18 Huanguan South RD. Guan lan Town, Baoan Distr, Shenzhen, Guangdong, China.

Tel: 86 0755 28055000 Fax: 86 0755 29055221

1.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

Compliance Certification Services (Shenzhen) Inc.

FCC Registration Number is **441872**.

1.7 Deviation from Standards

None.

1.8 Abnormalities from Standard Conditions

None.

1.9 Other Information Requested by the Customer

None.

1.10 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	3.8 dB
2	Conducted emission 150KHz-30MHz	3.4 dB
3	Radiated emission 9KHz-30MHz	4.9 dB
4	Radiated emission 30MHz-1GHz	4.7 dB
5	Radiated emission 1GHz-18GHz	5.1 dB
6	Radiated emission 18GHz-26GHz	5.2 dB
7	Radiated emission 26GHz-40GHz	5.2 dB

2 Test Summary

Tests for radiated and conducted emissions were performed. All measurements were performed according to the 2013 version of ANSI C63.10

Test Item	Test Requirement	Test method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2013	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013	See remark 1
Conducted Peak Output Power	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3)	KDB 558074 D01 v03r05, Section 9.1.2	PASS
6dB Bandwidth	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2)	KDB 558074 D01 v03r05, Section 8.1	PASS
Power Spectral Density	FCC 47 CFR Part 15 Subpart C Section 15.247 (e)	KDB 558074 D01 v03r05, Section 10.2	PASS
Conducted Out of Band Emission	FCC 47 CFR Part 15 Subpart C Section 15.247(d)	KDB 558074 D01 v03r05, Section 11	PASS
Radiated Spurious Emissions	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	KDB 558074 D01 v03r05, Section 12.1	PASS
Band Edge Measurements (Radiated)	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	KDB 558074 D01 v03r05, Section 12.1	PASS

Remark:
Tx: In this whole report Tx (or tx) means Transmitter.
Rx: In this whole report Rx (or rx) means Receiver.
RF: In this whole report RF means Radiated Frequency.
CH: In this whole report CH means channel.
N/A: Not application,

1. There is a separate report for the AC Power Line Conducted Emission test.

3 Equipment List

3M Semi/full-anechoic Chamber						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date (mm-dd-yyyy)**	**Cal. Due date (mm-dd-yyyy)**
☒	PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	02-21-2016	02-20-2017
☒	Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
☒	Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
☒	Controller	CT	N/A	N/A	N.C.R	N.C.R
☒	Bilog Antenna	SCHAFFNER	CBL6143	5063	02-22-2016	02-21-2017
☒	Horn Antenna	SCHWARZBECK	BBHA9120	D286	02-21-2016	02-20-2017
☒	Loop Antenna	COM-POWER	AL-130	121044	02-21-2016	02-20-2017
☒	High Noise Amplifier	Agilent	8449B	3008A01838	02-22-2016	02-21-2017
☒	Horn Antenna	Schwarzbeck	BBHA9120	D286	02-22-2016	02-21-2017
☒	Temp. / Humidity Meter	Anymetre	JR913	N/A	02-22-2016	02-21-2017
☒	Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
☒	Test S/W	FARAO	LZ-RF / CCS-SZ-3A2			

RF test system						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date (mm-dd-yyyy)**	**Cal. Due date (mm-dd-yyyy)**
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	12-22-2016	12-22-2017
☐	Receiver	R&S	ESR7	1316.3003K07-101181-K3	12-22-2016	12-22-2017
☐	Receiver	R&S	ESIB26	100114	12-22-2016	12-22-2017
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	12-22-2016	12-22-2017
☐	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430023	12-22-2016	12-22-2017
☐	EXG-B RF Analog Signal Generator	KEYSIGHT	N5171B	MY53051777	01-09-2016	01-08-2018
☐	MXG X-Series RF Vector Signal Generator	KEYSIGHT	N5182B	MY51350267	01-08-2016	01-07-2018
☐	4ch. Simultaneous Sampling 14 Bits 2MS/s	KEYSIGHT	U2531A	TW55193502	11-09-2015	11-08-2017
☐	Universal Radio Communication Tester	R&S	CMU200	114713	12-22-2016	12-22-2017
☐	Band rejection filter (5150MHz~5880MHz)	micro-tronics	BRM50716	G1868	06-15-2016	06-14-2017
☐	Band rejection filter (2400MHz~2500MHz)	micro-tronics	BRM50702	G248	06-21-2016	06-20-2017
☐	DC Source	KIKUSUI	PWR400L	LK003024	09-21-2016	09-20-2017

☐	Temp & Humidity chamber	Ispec	GL(U)04K A(W)	1692H201P3	09-21-2016	09-20-2017

4 Test Requirement

4.1 Test setup

4.1.1 For Conducted test setup



4.1.2 For Radiated Emissions test setup

Radiated Emissions setup:



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1GHz

4.1.3 For Conducted Emissions test setup

Conducted Emissions setup



4.2 Test Environment

Operating Environment:	
Temperature:	24.6 °C
Humidity:	47 % RH
Atmospheric Pressure:	100.25 Kpa

4.3 System Test Configuration

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by DC5V from a USB-to-Serial Adapter. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in (see table below) orientation.

Frequency Band(GHz)	Mode	Antenna Port	Worst-case Orientation
Below 1GHz	1TX	Chain 0	X-Portrait
Above 1GHz	1TX	Chain 0	X-Portrait

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.4 Test Condition

4.4.1 Test channel

Modulation Type	Data Rate (Mbps)	Tx/Rx	RF Channel		
			Low(L)	Middle(M)	High(H)
GFSK	1	2402MHz ~2480 MHz	Channel 0	Channel 19	Channel 39
			2402MHz	2440MHz	2480MHz
Transmitting mode: Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.					

4.4.2 Duty Cycle

Procedure: KDB 558074 Zero-Span Spectrum Analyzer Method.

Results:

Modulation Type	Data rates (Mbps)	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)
GFSK	1	0.389	0.625	0.6224	62.24	2.059	2.57
Remark: 1) Duty cycle= On Time/ Period 2) Duty Cycle factor = 10 * log(1/ Duty cycle)							

The test plot as follows:

Test Mode: GFSK_ 1Mbps



5 Radio Technical Requirements Specification

Reference documents for testing:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicesed Wireless Devices
4	KDB 558074 D01 DTS Meas Guidance v03r05	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

5.1 Antenna Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:	

Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is 3.3 dBi.

5.2 Conducted Peak Output Power

Test Requirement: FCC 47 CFR Part 15 Subpart C Section15.247 (b)(3)

Test Method: KDB 558074 D01 v03r05, Section 9.1.2

Limit: For systems using digital modulation in the 2400-2483.5 MHz bands: 1 Watt.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter.
2. Measure out each test modes' peak or average output power, record the power level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.1.1 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Maximum Conducted Power:

Modulation Type	Channel	Frequency (MHz)	Maximum Conducted Peak Power (dBm)	Maximum Conducted Peak Power (mW)
GFSK	0	2402	2.81	1.91
	19	2440	2.73	1.87
	39	2480	2.89	1.95

5.3 6dB Bandwidth

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2)

Test Method: KDB 558074 D01 v03r05, Section 8.1

Limit: For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:
a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) ≥ 3 x RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.1.1 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Occupied Bandwidth:

Modulation Type	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limit	Result (Pass / Fail)
GFSK	0	2402	0.7806	1.1357	> 500 kHz	Pass
	19	2440	0.7780	1.1050	> 500 kHz	Pass
	39	2480	0.7702	1.0971	> 500 kHz	Pass

The test plot as follows:

2402MHz



2440MHz



2480MHz


Agilent Spectrum Analyzer - Occupied BW
RF 50 Ω DC
SENSE:INT SOURCE OFF ALIGN AUTO 04:54:16 PM Feb 08, 2017
Center Freq 2.480000000 GHz
Center Freq: 2.480000000 GHz
Trig: Free Run Avg|Hold:>10/10
#Atten: 20 dB
#IFGain:Low
Radio Std: None
Radio Device: BTS
Frequency
Ref Offset 11 dB
10 dB/div Ref 10.00 dBm
Log
0.00
-10.0
-20.0
-30.0
-40.0
-50.0
-60.0
-70.0
-80.0
Center Freq
2.480000000 GHz
Center 2.48 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 2 MHz
Sweep 1 ms
CF Step
200.000 kHz
Auto Man
Occupied Bandwidth
1.0971 MHz
Total Power 9.43 dBm
Transmit Freq Error 63.065 kHz
OBW Power 99.00 %
x dB Bandwidth 770.2 kHz
x dB -6.00 dB
Freq Offset
0 Hz
MSG
STATUS

5.4 Power Spectral Density

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (e)

Test Method: KDB 558074 D01 v03r05, Section 10.2

Limit: For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Use the following spectrum analyzer settings:

a) Set analyzer center frequency to DTS channel center frequency.
b) Set the span to 1.5 times the DTS bandwidth.
c) Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
d) Set the VBW ≥ 3 x RBW.
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum amplitude level within the RBW.
j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.1.1 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Modulation Type	Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Result (Pass / Fail)
GFSK	0	2402	-12.669	8	Pass
	19	2440	-12.266	8	Pass
	39	2480	-12.110	8	Pass

The test plot as follows:

2402MHz



2440MHz



2480MHz


Agilent Spectrum Analyzer - Swept SA
Average/Hold Number 10
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>10/10
04:55:42 PM Feb 08, 2017
Ref Offset 11 dB
10 dB/div
Log
Ref 20.00 dBm
Mkr1 2.480 041 6 GHz
-12.110 dBm
Center 2.4800000 GHz
#Res BW 3.0 kHz
#VBW 10 kHz
Span 1.155 MHz
Sweep 121.8 ms (1001 pts)
Meas Setup
Avg/Hold Num
10
Avg Type
Log-Pwr (Video)
Auto Man
Limits
N dB Points
-3.01 dB
On Off
PhNoise Opt
Wide-offset
Auto Man
ADC Dither
Medium
Auto Man
More
1 of 2

5.5 Conducted Out of Band Emission

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247(d)

Test Method: KDB 558074 D01 v03r05, Section 11

Limit: In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Use the following spectrum analyzer settings:

Step 1:Measurement Procedure REF

a) Set instrument center frequency to DTS channel center frequency.
b) Set the span to ≥ 1.5 times the DTS bandwidth.
c) Set the RBW = 100 kHz.
d) Set the VBW ≥ 3 x RBW.
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum PSD level.
j) Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Step 2:Measurement Procedure OOBE

a) Set RBW = 100 kHz.
b) Set VBW ≥ 300 kHz.
c) Detector = peak.
d) Sweep = auto couple.
e) Trace Mode = max hold.
f) Allow trace to fully stabilize.
g) Use the peak marker function to determine the maximum amplitude level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.1.1 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

The test plot as follows:

Test Mode: BLE

2402MHz

In-Band Reference Level



Out of Band


Agilent Spectrum Analyzer - Swept SA
Marker 1 3.880502350078 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>10/10
05:02:04 PM Feb 08, 2017
Ref Offset 11 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 3.880 5 GHz
-42.133 dBm
-17.87 dBm
Start 30 MHz
#Res BW 1.0 MHz
#VBW 3.0 MHz
Stop 25.00 GHz
Sweep 42.00 ms (30000 pts)
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

2440MHz

In-Band Reference Level



Out of Band



2480MHz

In-Band Reference Level





Out of Band


Agilent Spectrum Analyzer - Swept SA
Marker 1 18.844689822994 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>10/10
05:03:54 PM Feb 08, 2017
Ref Offset 11 dB
10 dB/div
Log
Ref 20.00 dBm
Mkr1 18.844 7 GHz
-43.435 dBm
-17.74 dBm
Start 30 MHz
#Res BW 1.0 MHz
#VBW 3.0 MHz
Stop 25.00 GHz
Sweep 42.00 ms (30000 pts)
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

5.6 Radiated Spurious Emissions

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

Test Method: KDB 558074 D01 v03r05, Section 12.1

Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBµV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

The emissions were measured using the following resolution bandwidths:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Harmonic and Spurious emissions that were identified as coming from the EUT were checked in Peak and in Average Mode. The high frequency, which started from 10 to 26.5GHz, Peak measurements and average measurements are made. All emissions were determined to have a peak-to-average ratio of less than 20dB.

Test Procedure:

Below 1GHz test procedure as below:

a) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both

horizontal and vertical polarizations of the antenna are set to make the measurement.

d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading.

e) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f) Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel

Above 1GHz test procedure as below:

g) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).

h) Test the EUT in the lowest channel , the Highest channel

i) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.

j) Repeat above procedures until all frequencies measured was complete.

Test Setup: Refer to section 4.1.2 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Radiated Emission Test Data (9 KHz ~ 30MHz)

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (Above 18 GHz)

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (30MHz ~ 1 GHz Worst Case)

Channel	Lowest Channel	**Ant. Polar.**	Horizontal



.No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	131.85	54.62	-20.84	33.78	43.50	9.72	QP
2	180.35	60.49	-22.95	37.54	43.50	5.96	QP
3	240.49	62.46	-21.48	40.98	46.00	5.02	QP
4*	323.91	60.65	-18.72	41.93	46.00	4.07	QP
5	384.05	54.77	-16.45	38.32	46.00	7.68	QP
6	708.03	48.28	-11.91	36.37	46.00	9.63	QP

Channel	Lowest Channel	Ant. Polar.	Vertical



.No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1*	60.07	59.22	-23.98	35.24	40.00	4.76	QP
2	131.85	55.72	-20.84	34.88	43.50	8.62	QP
3	144.46	54.63	-21.48	33.15	43.50	10.35	QP
4	240.49	57.31	-21.48	35.83	46.00	10.17	QP
5	264.74	57.67	-20.19	37.48	46.00	8.52	QP
6	456.80	47.68	-15.27	32.41	46.00	13.59	QP

Radiated Emission Test Data (Above 1GHz Worst Case**):**

Tx_2402 MHz						
.No.	Frequency (MHz)	Result (dBuV)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Polar.
1	1342.0000	44.09	74.00	29.91	Peak	Horizontal
2	1648.0000	42.79	74.00	31.21	Peak	Horizontal
3	2503.0000	42.06	74.00	31.94	Peak	Horizontal
4	3223.0000	41.73	74.00	32.27	Peak	Horizontal
5	4150.0000	42.30	74.00	31.70	Peak	Horizontal
6	4888.0000	44.84	74.00	29.16	Peak	Horizontal
7	1594.0000	46.72	74.00	27.28	Peak	Vertical
8	1720.0000	44.52	74.00	29.48	Peak	Vertical
9	2557.0000	42.33	74.00	31.67	Peak	Vertical
10	2845.0000	42.06	74.00	31.94	Peak	Vertical
11	3520.0000	41.32	74.00	32.68	Peak	Vertical
12	4807.0000	45.41	74.00	28.59	Peak	Vertical

Tx_2440 MHz						
.No.	Frequency (MHz)	Result (dBuV)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Polar.
1	1324.0000	44.22	74.00	29.78	Peak	Horizontal
2	1486.0000	43.08	74.00	30.92	Peak	Horizontal
3	1666.0000	41.89	74.00	32.11	Peak	Horizontal
4	2548.0000	42.21	74.00	31.79	Peak	Horizontal
5	3205.0000	41.55	74.00	32.45	Peak	Horizontal
6	4123.0000	42.56	74.00	31.44	Peak	Horizontal
7	1594.0000	45.87	74.00	28.13	Peak	Vertical
8	1738.0000	42.97	74.00	31.03	Peak	Vertical
9	2512.0000	42.77	74.00	31.23	Peak	Vertical
10	3106.0000	41.37	74.00	32.63	Peak	Vertical
11	3583.0000	41.58	74.00	32.42	Peak	Vertical
12	4132.0000	42.72	74.00	31.28	Peak	Vertical

Tx_2480 MHz						
.No.	Frequency (MHz)	Result (dBuV)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Polar.
1	1324.0000	44.45	74.00	29.55	Peak	Horizontal
2	1765.0000	40.99	74.00	33.01	Peak	Horizontal
3	2485.0000	42.22	74.00	31.78	Peak	Horizontal
4	2827.0000	41.41	74.00	32.59	Peak	Horizontal
5	3574.0000	41.64	74.00	32.36	Peak	Horizontal
6	4618.0000	44.17	74.00	29.83	Peak	Horizontal
7	1351.0000	43.43	74.00	30.57	Peak	Vertical
8	1594.0000	44.44	74.00	29.56	Peak	Vertical
9	2593.0000	42.56	74.00	31.44	Peak	Vertical
10	2828.0000	41.98	74.00	32.02	Peak	Vertical
11	3511.0000	41.31	74.00	32.69	Peak	Vertical
12	3844.0000	41.37	74.00	32.63	Peak	Vertical

Note:

1) *The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:*

   Final Test Level =Receiver Reading - Correct Factor

   Correct Factor = Preamplifier Factor– Antenna Factor–Cable Factor

2) *Scan from 9 KHz to 25 GHz, the disturbance above 10 GHz and below 30 MHz was very low, the amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.*

3) *Since peak data above 1 GHz are lower the average limit, so the average data are pass, no need for testing.*

5.7 Band Edge Measurements (Radiated)

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

Test Method: KDB 558074 D01 v03r05, Section 12.1

Limit:

Frequency	Limit (dBμV/m @3m)	Remark
30MHz-88MHz	40.0	Quasi-peak Value
88MHz-216MHz	43.5	Quasi-peak Value
216MHz-960MHz	46.0	Quasi-peak Value
960MHz-1GHz	54.0	Quasi-peak Value
Above 1GHz	54.0	Average Value
	74.0	Peak Value

Test Procedure: Radiated band edge measurements at 2390MHz and 2483MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).

1. Use radiated spurious emission test procedure described in 5.6 clause. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.

Test Setup: Refer to section 4.1.2 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Frequency (MHz)	2402	Ant. Polar.	Horizontal

Detector: Peak



Detector: AV



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2390.000	53.303	74	42.425	54	Pass
2389.600	55.344	74	-	-	Pass

Frequency (MHz)	2402		Ant. Polar.	Vertical	
Detector: Peak			Detector: AV		
					
Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2390.000	53.758	74	42.324	54	Pass

Frequency (MHz)	2480		Ant. Polar.	Horizontal	
Detector: Peak			Detector: AV		
					
Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2483.500	59.067	74	42.335	54	Pass

Frequency (MHz)	2480	Ant. Polar.	Vertical
Detector: Peak		Detector: AV	





Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2483.500	55.992	74	42.501	54	Pass
2483.625	57.059	74	-	-	Pass

5.8 Conducted Emissions

Test Requirement: 47 CFR Part 15C Section 15.207
Test Method: ANSI C63.10
Test Frequency Range: 150KHz to 30MHz
Limit:

Frequency range (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

NOTE : The lower limit is applicable at the transition frequency

Test Procedure: Test frequency range :150KHz-30MHz

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Test Setup: Refer to section 4.1.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: See note 1.

Note: 1. There is a separate report for the AC Power Line Conducted Emission test.

APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

See test photographs attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photographs.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.