RF TEST REPORT

SIEMIC
GLOBAL TESTING & CERTIFICATIONS
YOUR CHOICE FOR- TCB FCB CB NB CAB RCB

Report No.: 15070325-FCC-R1

Supersede Report No.: N/A

Applicant	JIANGSU SHUANGSHUANG TECHNOLOGY CO.,LTD
Product Name	tablet PC
Model No.	TQ10A11
Serial No.	/
Test Standard	FCC Part 15.247: 2014, ANSI C63.10: 2013
Test Date	April 27 to May 29, 2015
Issue Date	May 29, 2015
Test Result	☑ Pass ☐ Fail
Equipment complied with the specification	☑
Equipment did not comply with the specification	☐

Wiky.Jam	Chris You	
Wiky.Jam Test Engineer	Chris You Checked By	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.

In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY 5

2. CUSTOMER INFORMATION 5

3. TEST SITE INFORMATION 5

4. EQUIPMENT UNDER TEST (EUT) INFORMATION 6

5. TEST SUMMARY 8

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS 9

6.1 ANTENNA REQUIREMENT 9

6.2 CHANNEL SEPARATION 10

6.3 20DB BANDWIDTH 14

6.4 PEAK OUTPUT POWER 18

6.5 NUMBER OF HOPPING CHANNEL 22

6.6 TIME OF OCCUPANCY (DWELL TIME) 24

6.7 BAND EDGE 28

6.8 AC POWER LINE CONDUCTED EMISSIONS 36

6.9 RADIATED SPURIOUS EMISSIONS 40

ANNEX A. TEST INSTRUMENT 45

ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS 46

ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT 51

ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST 54

ANNEX E. DECLARATION OF SIMILARITY 55

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15070325-FCC-R1	NONE	Original	May 29, 2015

2. Customer information

Applicant Name	JIANGSU SHUANGSHUANG TECHNOLOGY CO.,LTD
Applicant Add	No.188,West Coastal Road，Haian County，Jiangsu Province,P,R.China.
Manufacturer	JIANGSU SHUANGSHUANG HIGH TECHNOLOGY CO.,LTE
Manufacturer Add	No.188,West Coastal Road，Haian County，Jiangsu Province,P,R.China.

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	tablet PC
Main Model:	TQ10A11
Serial Model:	/
Date EUT received:	April 24, 2015
Test Date(s):	April 27 to May 29, 2015
Equipment Category :	DSS
Antenna Gain:	Bluetooth: 2dBi WIFI: 2dBi
Type of Modulation:	802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK
RF Operating Frequency (ies):	WIFI:802.11b/g/n(20M): 2412-2462 MHz WIFI:802.11n(40M): 2422-2452 MHz Bluetooth: 2402-2480 MHz
Max. Output Power:	GFSK:5.76 dBm
Number of Channels:	WIFI :802.11b/g/n(20M): 11CH WIFI :802.11n(40M): 7CH Bluetooth: 79CH
Port:	Power Port, Earphone Port, USB Port
Input Power:	Battery: Model: BR1364AQ Spec: 3.7V 1300mAh 4.81Wh Adapter: Model: PC X301 Input: AC 100-240V; 50/60Hz 0.15A Max Output: DC 5.0V; 0.5A

Trade Name : /

FCC ID: 2ABDT-TQ10A11

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance

Measurement Uncertainty

Emissions		
Test Item	**Description**	**Uncertainty**
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited.
The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

a. Antenna must be permanently attached to the unit.
b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.
And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 1 antennas:
A permanently attached PIFA antenna for BluetoothWIFI, the gain is 2dBi for Bluetooth/WIFI.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1016mbar
Test date :	May 26, 2015
Tested By :	Wiky.Jam

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	☑
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span - Video (or Average) Bandwidth (VBW) ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.		

Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Channel Separation measurement result

Type/ Modulation	CH	CH Freq (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.005	0.709	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.711	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.709	Pass
	Adjacency Channel	2479			
CH Separation π /4 DQPSK	Low Channel	2402	1.005	0.890	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.867	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.869	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.005	0.878	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.878	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.868	Pass
	Adjacency Channel	2479			

Test Plots

Channel Separation measurement result



GFSK - Low Channel



GFSK - Middle Channel



GFSK - High Channel



π /4 DPSK - Low Channel



π /4 DQPSK - Middle Channel



π /4 DQPSK - High Channel



8DPSK - Low Channel



8DPSK - Middle Channel



8DPSK - High Channel

6.3 20dB Bandwidth

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1016mbar
Test date :	May 26, 2015
Tested By :	Wiky.Jam

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a)(1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	☑
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW ≥ 1% of the 20 dB bandwidth - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference		

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Measurement result

Modulation	CH	CH Freq (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.064	0.9365
	Mid	2441	1.067	0.9282
	High	2480	1.063	0.9265
π /4 DQPSK	Low	2402	1.335	1.1939
	Mid	2441	1.301	1.1818
	High	2480	1.304	1.1744
8-DPSK	Low	2402	1.317	1.2069
	Mid	2441	1.317	1.1938
	High	2480	1.302	1.1910

Test Plots

20dB Bandwidth measurement result



GFSK - Low Channel



GFSK - Middle Channel



GFSK - High Channel



π /4 DPSK - Low Channel



π /4 DQPSK - Middle Channel



π /4 DQPSK - High Channel



8DPSK - Low Channel



8DPSK - Middle Channel



8DPSK - High Channel

6.4 Peak Output Power

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1016mbar
Test date :	May 26, 2015
Tested By :	Wiky.Jam

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b)(2)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☑
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☑
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	☐
	f)	DSSS in 902-928MHz, 2400-2483.5MHz, 5725-5850MHz: ≤ 1 Watt	☐
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW > the 20 dB bandwidth of the emission being measured - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold		

	- Allow the trace to stabilize. - Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Peak Output Power measurement result

Type	Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	5.44	125	Pass
		Mid	2441	**5.54**	125	Pass
		High	2480	5.53	125	Pass
	π /4 DQPSK	Low	2402	**5.52**	125	Pass
		Mid	2441	5.00	125	Pass
		High	2480	4.39	125	Pass
	8-DPSK	Low	2402	**5.76**	125	Pass
		Mid	2441	5.39	125	Pass
		High	2480	4.68	125	Pass

Test Plots

Output Power measurement result



GFSK Output power - Low CH 2402



GFSK Output power - Mid CH 2441



GFSK Output power - High CH 2480



π /4 DQPSK Output power - Low CH 2402



π /4 DQPSK Output power - Mid CH 2441



π /4 DQPSK Output power - High CH 2480



8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441



8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1016mbar
Test date :	May 26, 2015
Tested By :	Wiky.Jam

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a)(1)(iii)	a)	FHSS in 2400-2483.5MHz ≥ 15 channels	☑
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: The EUT must have its hopping function enabled. - Span = the frequency band of operation - RBW ≥ 1% of the span - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).		
Remark			
Result	☑ Pass	☐ Fail	

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	π /4 DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots

Number of Hopping Channels measurement result



GFSK



π /4DQPSK



8DPSK

6.6 Time of Occupancy (Dwell Time)

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1016mbar
Test date :	May 26, 2015
Tested By :	Wiky.Jam

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a)(1)(iii)	a)	Dwell Time < 0.4s	☑
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW ≥ RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time		
Remark			
Result	☑ Pass ☐ Fail		

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Dwell Time measurement result

Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.863	305.387	400	Pass
		Mid	2.878	306.987	400	Pass
		High	2.878	306.987	400	Pass
	π /4 DQPSK	Low	2.878	306.987	400	Pass
		Mid	2.848	303.787	400	Pass
		High	2.863	305.387	400	Pass
	8-DPSK	Low	2.878	306.987	400	Pass
		Mid	2.848	303.787	400	Pass
		High	2.878	306.987	400	Pass
Note: Dwell time=Pulse Time (ms) × (1600 ÷ 6 ÷ 79) ×31.6						

Test Plots

Dwell Time measurement result



GFSK - Low CH 2402



GFSK - Mid CH 2441



GFDK - High CH 2480



π /4 DQPSK - Low CH 2402



π /4 DQPSK - Mid CH 2441



π /4 DQPSK - High CH 2480



8DPSK - Low CH 2402



8DPSK - Mid CH 2441



8DPSK - High CH 2480

6.7 Band Edge

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1016mbar
Test date :	May 29, 2015
Tested By :	Wiky.Jam

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a)(1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☑
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only - 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. - 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,		

	and make sure the instrument is operated in its linear range. - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☐ Yes ☑ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Plots

GFSK Mode:



GFSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



GFSK-Hopping Right Side-PK

Note: F1 is frequency 2483.5MHz



GFSK-Hopping Left Side-AV

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Note: (no need if PK value less than the AV limit)

GFSK-Hopping Right Side-AV



GFSK-Left Side-PK

Note: F1 is frequency 2400MHz



GFSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



GFSK-Left Side-AV

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Note: (no need if PK value less than the AV limit)

GFSK-Right Side-AV

π /4 DQPSK Mode:



π /4 DQPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



π /4 DQPSK-Hopping Right Side-PK

Note: F1 is frequency 2483.5MHz



π /4 DQPSK-Hopping Left-AV

Note: (no need if PK value less than the AV limit)

π /4 DQPSK-Hopping Right-AV



π /4 DQPSK-Left Side-PK

Note: F1 is frequency 2400MHz



π /4 DQPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



π /4 DQPSK-Left Side-AV

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Note: (no need if PK value less than the AV limit)

π /4 DQPSK-Right Side-AV

8-DPSK Mode:



8DPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



8DPSK-Hopping Right Side-PK

Note: F1 is frequency 2483.5MHz



8DPSK-Hopping Left-AV

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Note: (no need if PK value less than the AV limit)

8DPSK-Hopping Right-AV



8DPSK-Left Side-PK

Note: F1 is frequency 2400MHz



8DPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



8DPSK-Left Side-AV

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Note: (no need if PK value less than the AV limit)

8DPSK-Right Side-AV

6.8 AC Power Line Conducted Emissions

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1016mbar
Test date :	May 26, 2015
Tested By :	Wiky.Jam

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>47CFR§15.207,</td><td>a)</td><td>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.
<table>
<tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBμV)</th></tr>
<tr><th>QP</th><th>Average</th></tr>
<tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr>
<tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr>
<tr><td>5 ~ 30</td><td>60</td><td>50</td></tr>
</table></td><td>☑</td></tr>
<tr><td>Test Setup</td><td colspan="3"> 

Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</td></tr>
<tr><td>Procedure</td><td colspan="3">1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.
2. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</td></tr>
</table>

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode:	Bluetooth Mode



Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Comment
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)	
1	L1	0.1695	16.34	QP	13.13	29.47	64.98	-35.51	
2	L1	0.1695	12.76	AVG	13.13	25.89	54.98	-29.09	
3	L1	0.3531	25.21	QP	12.45	37.66	58.89	-21.23	
4	L1	0.3531	22.52	AVG	12.45	34.97	48.89	-13.92	
5	L1	0.4703	32.91	QP	12.01	44.92	56.51	-11.59	
6	L1	0.4703	30.43	AVG	12.01	42.44	46.51	-4.07	
7	L1	0.9331	22.95	QP	11.47	34.42	56.00	-21.58	
8	L1	0.9331	18.49	AVG	11.47	29.96	46.00	-16.04	
9	L1	2.2555	22.13	QP	11.40	33.53	56.00	-22.47	
10	L1	2.2555	16.59	AVG	11.40	27.99	46.00	-18.01	
11	L1	2.9977	22.26	QP	11.40	33.66	56.00	-22.34	
12	L1	2.9977	17.97	AVG	11.40	29.37	46.00	-16.63	

Test Mode:	Bluetooth Mode



Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Comment
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)	
1	N	0.2481	19.71	QP	12.84	32.55	61.82	-29.27	
2	N	0.2481	10.61	AVG	12.84	23.45	51.82	-28.37	
3	N	0.4703	29.84	QP	12.01	41.85	56.51	-14.66	
4	N	0.4703	16.86	AVG	12.01	28.87	46.51	-17.64	
5	N	0.9977	19.64	QP	11.40	31.04	56.00	-24.96	
6	N	0.9977	7.55	AVG	11.40	18.95	46.00	-27.05	
7	N	1.1422	20.81	QP	11.42	32.23	56.00	-23.77	
8	N	1.1422	10.29	AVG	11.42	21.71	46.00	-24.29	
9	N	1.7477	21.80	QP	11.49	33.29	56.00	-22.71	
10	N	1.7477	15.42	AVG	11.49	26.91	46.00	-19.09	
11	N	2.5602	22.24	QP	11.60	33.84	56.00	-22.16	
12	N	2.5602	15.20	AVG	11.60	26.80	46.00	-19.20	

6.9 Radiated Spurious Emissions

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1016mbar
Test date :	May 26, 2015
Tested By :	Wiky.Jam

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>47CFR§15.205, §15.209, §15.247(d)</td><td>a)</td><td>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges
<table>
<tr><th>Frequency range (MHz)</th><th>Field Strength (μV/m)</th></tr>
<tr><td>30 – 88</td><td>100</td></tr>
<tr><td>88 – 216</td><td>150</td></tr>
<tr><td>216 960</td><td>200</td></tr>
<tr><td>Above 960</td><td>500</td></tr>
</table></td><td>☑</td></tr>
<tr><td>Test Setup</td><td colspan="3"> 
</td></tr>
<tr><td>Procedure</td><td colspan="3">1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:</td></tr>
</table>

	a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode:	Bluetooth Mode

Below 1GHz



Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree	Comment
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )	
1	H	71.0803	41.93	peak	-13.62	28.31	40.00	-11.69	100	233	
2	H	79.5209	40.80	peak	-13.77	27.03	40.00	-12.97	100	222	
3	H	180.0165	38.37	peak	-9.89	28.48	43.50	-15.02	100	282	
4	H	426.5210	34.35	peak	-3.66	30.69	46.00	-15.31	100	177	
5	H	533.8321	37.68	peak	-1.10	36.58	46.00	-9.42	100	177	
6	H	854.0247	30.27	peak	3.88	34.15	46.00	-11.85	100	158	

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree	Comment
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )	
1	V	31.7313	36.43	QP	-1.53	34.90	40.00	-5.10	100	179	
2	V	33.4449	36.86	QP	-2.79	34.07	40.00	-5.93	100	152	
3	V	76.4442	46.20	QP	-13.75	32.45	40.00	-7.55	100	186	
4	V	79.4230	46.91	QP	-13.77	33.14	40.00	-6.86	100	73	
5	V	426.5210	37.72	peak	-3.66	34.06	46.00	-11.94	100	14	
6	V	533.8321	35.19	peak	-1.10	34.09	46.00	-11.91	100	231	

Test Mode:	Transmitting Mode

Mode: GFSK (Worst Case)

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	37.29	AV	V	33.83	6.86	31.72	46.26	54	-7.74
4804	35.51	AV	H	33.83	6.86	31.72	44.48	54	-9.52
4804	46.64	PK	V	33.83	6.86	31.72	55.61	74	-18.39
4804	47.83	PK	H	33.83	6.86	31.72	56.8	74	-17.2

Middle Channel (2441 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4882	36.83	AV	V	33.86	6.82	31.82	45.69	54	-8.31
4882	34.71	AV	H	33.86	6.82	31.82	43.57	54	-10.43
4882	47.92	PK	V	33.86	6.82	31.82	56.78	74	-17.22
4882	47.34	PK	H	33.86	6.82	31.82	56.2	74	-17.8

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	36.59	AV	V	33.9	6.76	31.92	45.33	54	-8.67
4960	37.42	AV	H	33.9	6.76	31.92	46.16	54	-7.84
4960	48.13	PK	V	33.9	6.76	31.92	56.87	74	-17.13
4960	48.62	PK	H	33.9	6.76	31.92	57.36	74	-16.64

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/18/2014	09/17/2015	☑
Line Impedance	LI-125A	191106	09/26/2014	09/25/2015	☑
Line Impedance	LI-125A	191107	09/26/2014	09/25/2015	☑
LISN	ISN T800	34373	09/26/2014	09/25/2015	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/25/2014	09/24/2015	☑
Transient Limiter	LIT-153	531118	09/02/2014	09/01/2015	☑
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/18/2014	09/17/2015	☑
Power Splitter	1#	1#	09/02/2014	09/01/2015	☑
DC Power Supply	E3640A	MY40004013	09/18/2014	09/17/2015	☑
Radiated Emissions					
EMI test receiver	ESL6	100262	09/18/2014	09/17/2015	☑
Positioning Controller	UC3000	MF780208282	11/20/2014	11/19/2015	☑
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/02/2014	09/01/2015	☑
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/25/2015	03/24/2016	☑
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/22/2014	09/21/2015	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/25/2014	09/24/2015	☑
Universal Radio Communication Tester	CMU200	121393	09/26/2014	09/25/2015	☑

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT Extemal Photo

Whole Package - Top View



Adapter - Front View



EUT - Front View

EUT - Rear View



EUT - Top View



EUT - Bottom View

EUT - Left View



EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1



WIFI/BT - Antenna View

Battery - Top View



Battery - Bottom View



Mainborad With Shielding - Front View



Mainborad Without Shielding - Front View



Mainborad With Shielding - rear View



Mainborad Without Shielding - rear View

LCD – Rear View



LCD - Front View

Annex B.iii. Photograph: Test Setup Photo

Conducted Emissions Test Setup Front View

Conducted Emissions Test Setup Side View

Radiated Spurious Emissions Test Setup Below 1GHz



Radiated Spurious Emissions Test Setup Above 1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Annex C. il. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Calibration Date	Calibration Due Date
N/A	N/A	N/A	N/A	N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Annex E. DECLARATION OF SIMILARITY