

Qingdao Yeelink Information Technology Co., Ltd.

SAR COMPLIANCE REPORT

Report Type:
FCC SAR assessment report

Model:
YLLDDXN01

REPORT NUMBER:
2404B1379SHA-003

ISSUE DATE:
May 23, 2024

DOCUMENT CONTROL NUMBER:
TTRFFCCSAR-01_V2 © 2022 Intertek



Applicant: Qingdao Yeelink Information Technology Co., Ltd
10F-B4, Building B, Qingdao International Innovation Park, No.1
Keyuan Weiyi Road, Laoshan District, Qingdao City, Shandong
Province, P.R.China

Manufacturer: Qingdao Yeelink Information Technology Co., Ltd
10F-B4, Building B, Qingdao International Innovation Park, No.1
Keyuan Weiyi Road, Laoshan District, Qingdao City, Shandong
Province, P.R.China

FCC ID: 2ABEU-YLLDDXN01

IC: 27677-YLLDDXN01

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

447498 D04 Interim General RF Exposure Guidance v01
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:**REVIEWED BY:**

Project Engineer
Damon Ding



Reviewer
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
2404B1379SHA-003	Rev. 01	Initial issue of report	May 23, 2024

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Yeelight Natural Light Floor Lamp Controller
Model:	YLLDDXN01
Description of EUT:	The EUT is Yeelight Natural Light Floor Lamp Controller, it supports bluetooth functions, there is only one model, There is a spare PCB power board. We test it and list the worst results in this report.
Rating:	DC 3V
Category of EUT:	Class B
EUT type:	☒ Table top ☐ Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	2024.4.7
Date of test:	2024.4.11-2024.4.23

1.2 Technical Specification

Frequency Band:	2400MHz ~ 2483.5MHz
Support Standards:	Bluetooth LE 5.0
Type of Modulation:	GFSK
Channel Number:	40
Channel Separation:	2MHz
Antenna Information:	0.2 dBi, PCB antenna

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road (North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

Tests were sub-contracted.

Name:	Shenzhen UnionTrust Quality and Technology Co., Ltd.
Address:	Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng Science and Technology Park, Longhua District, Shenzhen, China
Telephone:	+86 (0) 755 2823 0888
Telefax:	+86 (0) 755 2823 0886

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L969
	FCC Accredited Lab Designation Number: CN1194
	IC Registration Lab CAB identifier.: CN0032
	VCCI Registration Lab Member No: 4142 (Registration No.: C-20097, T-20098, R-20135, G-20130)
	A2LA Accreditation Lab Certificate Number: 4312.01

2 SAR Assessment

Test result: Pass

2.1 SAR Test Exclusion Limit

This method shall only be used at separation distances up to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula below:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

f is in GHz, d is the separation distance (cm), and ERP_{20cm} is per Formula above.

The example values shown in below are for illustration only.

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
300		39	65	88	110	129	148	166	184	201	217
450		22	44	67	89	112	135	158	180	203	226
835		9	25	44	66	90	116	145	175	207	240
1900		3	12	26	44	66	92	122	157	195	236
2450		3	10	22	38	59	83	111	143	179	219
3600		2	8	18	32	49	71	96	125	158	195
5800		1	6	14	25	40	58	80	106	136	169

2.2 Assessment Results

As we can see from the BLE test report 2404B1379SHA-002:

The highest EIRP adjusted with tune-up tolerance is: 2.37dBm=1.726mW

1.726mW < 3mW (Test Exclusion Thresholds of 2450MHz at 5mm).

Therefore, the SAR requirement is deemed to be satisfied without test.

***** END *****