

FCC Part 22H & 24E Measurement and Test Report

For

Shenzhen Ruifenghuizhi Technology Co., Ltd.

Room 607B, East Block, NanFang Building, Futian District, Shenzhen,
China.

FCC ID: 2ABEYRF-V9

FCC Rules: FCC Part 22H, FCC Part 24E

Product Description: Real time tracker & alarm

Tested Model: RF-V9

Report No.: STR14048358I-1

Tested Date: 2014-04-24 to 2014-05-12

Issued Date: 2014-05-14

Tested By: Silin Chen / Engineer

Reviewed By: Lahm Peng / EMC Manager

Approved & Authorized By: Jandy So / PSQ Manager

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
2. SUMMARY OF TEST RESULTS	7
3. RF EXPOSURE	8
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
4. ANTENNA REQUIREMENT	9
4.1 STANDARD APPLICABLE.....	9
4.2 EVALUATION INFORMATION	9
5. RF OUTPUT POWER.....	10
5.1 STANDARD APPLICABLE.....	10
5.2 TEST EQUIPMENT LIST AND DETAILS	10
5.3 TEST PROCEDURE.....	10
5.4 ENVIRONMENTAL CONDITIONS	11
5.5 SUMMARY OF TEST RESULTS/PLOTS	11
6. PEAK-TO-AVERAGE RADIO (PAR) OF TRANSMITTER.....	14
6.1 STANDARD APPLICABLE.....	14
6.2 TEST EQUIPMENT LIST AND DETAILS	14
6.3 TEST PROCEDURE.....	14
6.4 ENVIRONMENTAL CONDITIONS	14
6.5 SUMMARY OF TEST RESULTS	15
7. EMISSION BANDWIDTH.....	16
7.1 STANDARD APPLICABLE.....	16
7.2 TEST EQUIPMENT LIST AND DETAILS	16
7.3 TEST PROCEDURE.....	16
7.4 ENVIRONMENTAL CONDITIONS	16
7.5 SUMMARY OF TEST RESULTS/PLOTS	17
8. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL.....	24
8.1 STANDARD APPLICABLE.....	24
8.2 TEST EQUIPMENT LIST AND DETAILS	24
8.3 TEST PROCEDURE.....	24
8.4 ENVIRONMENTAL CONDITIONS	24
8.5 SUMMARY OF TEST RESULTS/PLOTS	25
9. SPURIOUS RADIATED EMISSIONS.....	41
9.1 MEASUREMENT UNCERTAINTY	41
9.2 STANDARD APPLICABLE.....	41
9.3 TEST EQUIPMENT LIST AND DETAILS	41
9.4 TEST PROCEDURE.....	41
9.5 ENVIRONMENTAL CONDITIONS	42
9.6 SUMMARY OF TEST RESULTS/PLOTS	42
10. FREQUENCY STABILITY	52
10.1 STANDARD APPLICABLE.....	52
10.2 TEST EQUIPMENT LIST AND DETAILS	52
10.3 TEST PROCEDURE.....	52
10.4 ENVIRONMENTAL CONDITIONS	53
10.5 SUMMARY OF TEST RESULTS/PLOTS	53

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Ruifenghuizhi Technology Co., Ltd.
Address of applicant: Room 607B, East Block, NanFang Building, Futian District, Shenzhen, China.

Manufacturer: Shenzhen Ruifenghuizhi Technology Co., Ltd.
Address of manufacturer: Room 607B, East Block, NanFang Building, Futian District, Shenzhen, China.

General Description of EUT	
Product Name:	Real time tracker & alarm
Brand Name:	ReachFar
Model No.:	RF-V9
Adding Mode:	RF-V6, RF-V7, RF-V11, RF-V10, RF-V12
Software Version:	f009_v350_GD_140118
Hardware Version:	RFGSM-F009V50MB
IMEI:	860996000085461
Rated Voltage:	DC 3.7V
Battery:	380mAh
Device Category:	Portable Device
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The other model listed in the report has different appearance only of RF-V9 without circuit and electronic construction changed, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
2G	
Support Networks:	GSM, GPRS
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS 850: 824~849MHz GSM/GPRS 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS 850: 869~894MHz GSM/GPRS 1900: 1930~1990MHz
Max. RF Power(Conducted):	GSM850: 32.02dBm, GSM1900: 29.02dBm
Type of Modulation:	GMSK
Type of Emission:	GSM(GSM850): 256KGXW GPRS(GSM850): 255KG7W GSM(PCS1900): 259KGXW GPRS(PCS1900): 260KG7W
Antenna Type:	Internal Antenna
Antenna Gain:	GSM850: -1.0dBi GSM1900: -2.0dBi
GPRS Class:	Class 12

1.2 Test Standards

The following report is prepared on behalf of the Shenzhen Ruifenghuizhi Technology Co., Ltd. in accordance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with TIA/EIA 603-C: 2004 and ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GSM 850	Low, Middle, High Channels
TM2	GPRS 850	Low, Middle, High Channels
TM3	GSM 1900	Low, Middle, High Channels
TM4	GPRS 1900	Low, Middle, High Channels

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EDGE	824.2 MHz	128
		836.6 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EDGE	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
Note: the transmitter has been tested on the communications mode of GSM, GPRS, compliance test and record the worst case.			

EUT Equipment List and Details			
Description	Manufacturer	Model	Serial Number
AC ADAPTOR	L.T.E	ND-05000500U	/
DC Car Charger	/	/	/
Power Adapter	/	/	/

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	0.8	Shielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.203	Antenna Requirement	Compliant
§ 1.1307, § 2.1093	RF Exposure	Compliant
§ 22.913 (a), § 24.232 (c)	RF Output Power	Compliant
§ 22.917 (b), § 24.238 (b)	Emission Bandwidth	Compliant
§ 22.917 (a), § 24.238 (a),	Spurious Emissions at Antenna Terminal	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Radiation Emissions	Compliant
§ 22.917 (a), § 24.238 (a)	Out of Band Emissions	Compliant
§ 22.355, § 24.235	Frequency Stability	Compliant

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a internal antenna, fulfill the requirement of this section.

5. RF Output Power

5.1 Standard Applicable

According to §22.913(a)(2), The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.


According to §24.232 (c), no any case may the peak output power of mobile or portable station transmitter exceed 2 Watt EIRP.

5.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2014-05-07	2015-05-06
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-07	2015-05-06
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-07	2015-05-06
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-07	2015-05-06
Horn Antenna	ETS	3117	00086197	2014-05-07	2015-05-06
Universal Radio Communication Tester	Rohde & Schwarz	CMU200	112012	2014-05-07	2015-05-06
Signal Generator	R&S	SMR20	100047	2014-05-07	2015-05-06

5.3 Test Procedure

Conducted output power test method:



Radiated power test method:

1. The setup of EUT is according with per TIA/EIA Standard 603C and ANSI C63.4-2003 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

5.4 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.5 Summary of Test Results/Plots

Radiated Power

ERP For GSM Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Corrected Ampl.	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	29.18	1.5	0	H	1.5	0	27.68	38.45
824.2	32.34	1.5	0	V	1.5	0	30.84	38.45
Middle Channel								
28.03	28.74	1.5	0	H	1.5	0	27.24	38.45
31.37	32.52	1.5	0	V	1.5	0	31.02	38.45
High Channel								
848.8	28.66	1.5	0	H	1.5	0	27.16	38.45
848.8	32.14	1.5	0	V	1.5	0	30.64	38.45

Note: Corrected = Substitute - Cable loss + Antenna Gain

EIRP For GSM Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Corrected Ampl.	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
1850.2	18.46	1.5	0	H	1.9	7.7	24.26	33.0
1850.2	20.99	1.5	0	V	1.9	7.7	26.79	33.0
Middle Channel								
1880.0	18.54	1.5	0	H	1.9	7.7	24.34	33.0
1880.0	20.41	1.5	0	V	1.9	7.7	26.21	33.0
High Channel								
1909.8	19.18	1.5	0	H	1.9	7.7	24.98	33.0
1909.8	21.22	1.5	0	V	1.9	7.7	27.02	33.0

Note: Corrected = Substitute - Cable loss + Antenna Gain

ERP For GPRS Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Corrected Ampl.	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	28.74	1.5	0	H	1.5	0	27.24	38.45
824.2	32.27	1.5	0	V	1.5	0	30.77	38.45
Middle Channel								
836.6	28.84	1.5	0	H	1.5	0	27.34	38.45
836.6	32.45	1.5	0	V	1.5	0	30.95	38.45
High Channel								
848.8	28.41	1.5	0	H	1.5	0	26.91	38.45
848.8	32.15	1.5	0	V	1.5	0	30.65	38.45

Note: Corrected = Substitute - Cable loss + Antenna Gain

EIRP For GPRS Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Corrected Ampl.	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	18.35	1.5	0	H	1.9	7.7	24.15	33.0
1850.2	20.94	1.5	0	V	1.9	7.7	26.74	33.0
Middle Channel								
1880.0	18.41	1.5	0	H	1.9	7.7	24.21	33.0
1880.0	20.40	1.5	0	V	1.9	7.7	26.20	33.0
High Channel								
1909.8	18.12	1.5	0	H	1.9	7.7	23.92	33.0
1909.8	21.26	1.5	0	V	1.9	7.7	27.06	33.0

Note: Corrected = Substitute - Cable loss + Antenna Gain

Max. Conducted Output Power

For GSM Mode

Test Mode	Channel	Frequency (MHz)	Output Power (dBm)	FCC Part 22.913 Limit (dBm)
GSM850	Low Channel	824.2	31.84	38.45
	Middle Channel	836.6	32.02	38.45
	High Channel	848.8	31.64	38.45
PCS1900	Low Channel	1850.2	28.79	33.0
	Middle Channel	1880.0	28.21	33.0
	High Channel	1909.8	29.02	33.0

For GPRS Mode

Band	Channel	Frequency (MHz)	Output Power(dBm)			
			Slot 1	Slot 2	Slot 3	Slot 4
GSM850	128	824.2	31.77	30.75	29.35	28.28
	190	836.6	31.95	30.90	29.46	28.38
	251	848.8	31.65	30.67	29.12	28.04
PCS1900	512	1850.2	28.74	28.24	27.06	26.30
	661	1880.0	28.20	27.44	26.19	25.42
	810	1909.8	29.06	28.62	26.98	26.11

6. Peak-to-average Radio (PAR) of Transmitter

6.1 Standard Applicable

According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


6.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B	US41192821	2014-05-07	2015-05-06
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	112012	2014-05-07	2015-05-06

6.3 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded.

Test Configuration for the emission bandwidth testing:



6.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

6.5 Summary of Test Results

For Cellular Band

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR (dB)	Limit (dB)
GSM	128	824.2	36.02	31.84	4.18	13
	190	836.6	36.15	32.02	4.13	13
	251	848.8	35.82	31.64	4.18	13
GPRS	128	824.2	32.32	28.79	3.53	13
	190	836.6	32.06	28.21	3.85	13
	251	848.8	32.67	29.02	3.65	13

For PCS Band

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR	Limit
GSM	512	1850.2	35.89	31.77	4.12	13
	661	1880.0	36.10	31.95	4.15	13
	810	1909.8	35.98	31.65	4.33	13
GPRS	512	1850.2	32.24	28.74	3.50	13
	661	1880.0	32.01	28.20	3.81	13
	810	1909.8	32.59	29.06	3.53	13

7. Emission Bandwidth

7.1 Standard Applicable

According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


7.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B	US41192821	2014-05-07	2015-05-06
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	112012	2014-05-07	2015-05-06

7.3 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



7.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

7.5 Summary of Test Results/Plots

For Cellular Band


Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	128	824.2	252.0953	337.627
	190	836.6	254.4473	334.945
	251	848.8	256.2339	335.279
GPRS	128	824.2	254.7773	337.856
	190	836.6	255.1046	337.521
	251	848.8	254.6933	337.783

For PCS Band


Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	512	1850.2	254.8397	341.035
	661	1880.0	254.3078	341.978
	810	1909.8	258.6290	349.748
GPRS	512	1850.2	254.2392	340.435
	661	1880.0	255.8463	343.395
	810	1909.8	259.5024	343.635

Please refer to the following test plots:


For Cellular Band
GSM Low Channel




GSM Middle Channel




GSM High channel




GPRS Low Channel




GPRS Middle Channel




GPRS High Channel




For PCS Band
GSM Low Channel




GSM Middle Channel




GSM High channel




GPRS Low Channel



GPRS Middle Channel



GPRS High Channel



8. Out of Band Emissions at Antenna Terminal

8.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


8.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B	US41192821	2014-05-07	2015-05-06
Rohde & Schwarz	Spectrum Analyzer	FSP	836079/035	2014-05-07	2015-05-06
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	112012	2014-05-07	2015-05-06

8.3 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10th harmonic.

Test Configuration for the out of band emissions testing:




8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


8.5 Summary of Test Results/Plots

Please refer to the following test plots For Cellular Band

GSM Low Channel 30MHz to 1GHz




Above 1GHz




GSM Middle Channel


30MHz to 1GHz




Above 1GHz



GSM High Channel
30MHz to 1GHz




Above 1GHz



GSM Low Band Emission




GSM High Band Emission




GPRS Low Channel

30MHz to 1GHz




Above 1GHz




GPRS Middle Channel

30MHz to 1GHz




Above 1GHz




GPRS High Channel


30MHz to 1GHz




Above 1GHz




GPRS Low Band Emission




GPRS High Band Emission



For PCS Band
GSM Low Channel
30MHz to 1GHz




Above 1GHz




GSM Middle Channel

30MHz to 1GHz




Above 1GHz




GSM High Channel


30MHz to 1GHz




Above 1GHz




GSM Low Band Emission




GSM High Band Emission



GPRS Low Channel
30MHz to 1GHz




Above 1GHz




GPRS Middle Channel

30MHz to 1GHz




Above 1GHz




GPRS High Channel


30MHz to 1GHz



Above 1GHz



GPRS Low Band Emission



GPRS High Band Emission



9. Spurious Radiated Emissions

9.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.20 dB.

9.2 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

9.3 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-07	2015-05-06
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-07	2015-05-06
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-07	2015-05-06
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-07	2015-05-06
Horn Antenna	ETS	3117	00086197	2014-05-07	2015-05-06
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2014-04-20	2015-04-19
Universal Radio Communication Tester	Rohde & Schwarz	CMU200	112012	2014-05-07	2015-05-06
Signal Generator	R&S	SMR20	100047	2014-05-07	2015-05-06

9.4 Test Procedure

1. The setup of EUT is according with per TIA/EIA Standard 603C and ANSI C63.4-2003 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB = $43 + 10 \log_{10}$ (power out in Watts)

9.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

9.6 Summary of Test Results/Plots

According to the data below, the FCC Part 22.917 and 24.238 standards, and had the worst margin of:


-29.59 dB at 5550.6 MHz in the Vertical polarization, PCS Band GPRS Mode, 9 kHz to 20 GHz, 3Meters

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Spurious Emission From 30MHz to 1GHz

For Cellular Band_GSM Mode


Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	739.6604	-76.39	29.87	-46.52	-13.00	-33.52	ERP
2	900.1474	-77.00	31.18	-45.82	-13.00	-32.82	ERP

Note: Result=Reading+ Correct, Margin= Result- Limit


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	36.2541	-77.52	20.89	-56.63	-13.00	-43.63	ERP
2	750.1082	-77.94	29.58	-48.36	-13.00	-35.36	ERP
3	958.7943	-76.69	29.96	-46.73	-13.00	-33.73	ERP

Note: Result=Reading+ Correct, Margin= Result- Limit


For Cellular Band_GPRS Mode
Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	739.6604	-76.39	29.87	-46.52	-13.00	-33.52	ERP
2	900.1474	-77.00	31.18	-45.82	-13.00	-32.82	ERP

Note: Result=Reading+ Correct, Margin= Result- Limit


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	36.2541	-77.52	20.89	-56.63	-13.00	-43.63	ERP
2	393.4723	-79.58	23.04	-56.54	-13.00	-43.54	ERP
3	750.1082	-77.94	29.58	-48.36	-13.00	-35.36	ERP

Note: Result=Reading+ Correct, Margin= Result- Limit


For PCS Band_GSM Mode
Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	744.8661	-76.59	29.74	-46.85	-13.00	-33.85	ERP
2	900.1474	-77.91	31.18	-46.73	-13.00	-33.73	ERP

Note: Result=Reading+ Correct, Margin= Result- Limit


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	36.2541	-77.52	20.89	-56.63	-13.00	-43.63	ERP
2	750.1082	-77.94	29.58	-48.36	-13.00	-35.36	ERP
3	887.6099	-78.51	30.95	-47.56	-13.00	-34.56	ERP

Note: Result=Reading+ Correct, Margin= Result- Limit


For PCS Band_GPRS Mode
Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	656.5300	-76.31	26.70	-49.61	-13.00	-36.61	ERP
2	881.4067	-77.87	30.83	-47.04	-13.00	-34.04	ERP

Note: Result=Reading+ Correct, Margin= Result- Limit

Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	36.7661	-76.87	20.96	-55.91	-13.00	-42.91	ERP
2	277.0935	-79.46	20.81	-58.65	-13.00	-45.65	ERP
3	704.2259	-77.98	27.73	-50.25	-13.00	-37.25	ERP

Note: Result=Reading+ Correct, Margin= Result- Limit

*Spurious Emissions Above 1GHz**For Cellular Band_GSM Mode*

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (824.2MHz)						
1648.4	-56.55	-0.63	-57.18	-13.00	-44.18	H
2472.6	-59.27	15.78	-43.49	-13.00	-30.49	H
1648.4	-60.23	13.66	-46.57	-13.00	-33.57	V
2472.6	-60.77	15.78	-44.99	-13.00	-31.99	V
Middle Channel (836.6MHz)						
1673.2	-59.10	16.53	-42.57	-13.00	-29.57	H
2509.8	-59.39	15.98	-43.41	-13.00	-30.41	H
1673.2	-59.72	15.15	-44.57	-13.00	-31.57	V
2509.8	-60.03	15.78	-44.25	-13.00	-31.25	V
High Channel (848.8MHz)						
1697.6	-56.56	-0.63	-57.19	-13.00	-44.19	H
2546.4	-60.30	13.77	-46.53	-13.00	-33.53	H
1697.6	-56.96	-0.63	-57.59	-13.00	-44.59	V
2546.4	-59.45	10.18	-49.27	-13.00	-36.27	V

Note: Result=Reading+ Correct, Margin= Result- Limit

For Cellular Band_GPRS Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (824.2MHz)						
1648.4	-55.05	-0.63	-55.68	-13.00	-42.68	H
2472.6	-60.81	15.03	-45.78	-13.00	-32.78	H
1648.4	-52.55	-0.63	-53.18	-13.00	-40.18	V
2472.6	-59.12	16.38	-42.74	-13.00	-29.74	V
Middle Channel (836.6MHz)						
1673.2	-56.53	-0.63	-57.16	-13.00	-44.16	H
2509.8	-59.37	15.37	-44.00	-13.00	-31.00	H
1673.2	-58.26	-0.63	-58.89	-13.00	-45.89	V
2509.8	-59.98	16.32	-43.66	-13.00	-30.66	V
High Channel (848.8MHz)						
1697.6	-57.30	-0.63	-57.93	-13.00	-44.93	H
2546.4	-59.29	10.17	-49.12	-13.00	-36.12	H
1697.6	-58.57	15.78	-42.79	-13.00	-29.79	V
2546.4	-59.41	16.50	-42.91	-13.00	-29.91	V

Note: Result=Reading+ Correct, Margin= Result- Limit

For PCS Band_GSM Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1850.2MHz)						
3700.4	-57.64	-0.75	-58.39	-13.00	-45.39	H
5550.6	-59.33	6.91	-52.42	-13.00	-39.42	H
3700.4	-59.37	10.27	-49.10	-13.00	-36.10	V
5550.6	-59.25	15.25	-44.00	-13.00	-31.00	V
Middle Channel (1880MHz)						
3760.0	-59.45	14.98	-44.47	-13.00	-31.47	H
5640.0	-59.97	17.02	-42.95	-13.00	-29.95	H
3760.0	-59.80	15.77	-44.03	-13.00	-31.03	V
5640.0	-59.29	16.34	-42.95	-13.00	-29.95	V
High Channel (1909.8MHz)						
3819.6	-57.88	9.92	-47.96	-13.00	-34.96	H
5729.4	-57.84	13.47	-44.37	-13.00	-31.37	H
3819.6	-60.70	16.97	-43.73	-13.00	-30.73	V
5729.4	-60.05	15.46	-44.59	-13.00	-31.59	V

Note: Result=Reading+ Correct, Margin= Result- Limit

For PCS Band_GPRS Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1850.2MHz)						
3700.4	-59.66	10.24	-49.42	-13.00	-36.42	H
5550.6	-59.53	13.86	-45.67	-13.00	-32.67	H
3700.4	-58.99	15.33	-43.66	-13.00	-30.66	V
5550.6	-59.61	17.02	-42.59	-13.00	-29.59	V
Middle Channel (1880MHz)						
3760.0	-52.35	-0.50	-52.85	-13.00	-39.85	H
5640.0	-59.09	16.38	-42.71	-13.00	-29.71	H
3760.0	-54.42	-0.50	-54.92	-13.00	-41.92	V
5640.0	-59.29	16.34	-42.95	-13.00	-29.95	V
High Channel (1909.8MHz)						
3819.6	-59.49	15.33	-44.16	-13.00	-31.16	H
5729.4	-60.50	17.00	-43.50	-13.00	-30.50	H
3819.6	-56.43	-0.38	-56.81	-13.00	-43.81	V
5729.4	-59.47	14.01	-45.46	-13.00	-32.46	V

Note: Result=Reading+ Correct, Margin= Result- Limit

Testing is carried out with frequency rang 9kHz to 20GHz, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, and the result is not record.

10. Frequency Stability

10.1 Standard Applicable

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Cellular Band

Frequency range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	N/A	N/A
929 to 960	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

10.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B-ESA	US41192821	2014-05-07	2015-05-06
Rohde & Schwarz	Universal Radio Communication	CMU200	112012	2014-05-07	2015-05-06
GONGWEN	Moisture Test Chamber	GDS-150	SEMT-0013	2014-05-07	2015-05-06

10.3 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

Temperature:	Supply Voltage
20°C	85-115% of declared nominal voltage
-30°C to +50°C	Normal

10.4 Environmental Conditions

Temperature:	20°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

10.5 Summary of Test Results/Plots

For Cellular Band GSM Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	46	0.0440
40	3.7	30	0.0520
30	3.7	21	0.0254
20	3.7	25	0.0315
10	3.7	32	0.0392
0	3.7	38	0.0504
-10	3.7	46	0.0492
-20	3.7	40	0.0445
-30	3.7	48	0.0412

For PCS Band GSM Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-73	-0.0384
40	3.7	-69	-0.0361
30	3.7	-51	-0.0425
20	3.7	-67	-0.0351
10	3.7	-48	-0.0354
0	3.7	-37	-0.0497
-10	3.7	-43	-0.0324
-20	3.7	-57	-0.0404
-30	3.7	-53	-0.0381

For Cellular Band GPRS Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	63	0.0592
40	3.7	57	0.0546
30	3.7	46	0.0456
20	3.7	36	0.0472
10	3.7	28	0.0349
0	3.7	37	0.0474
-10	3.7	42	0.0490
-20	3.7	45	0.0342
-30	3.7	48	0.0469

For PCS Band GPRS Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-30	-0.0351
40	3.7	-19	-0.0360
30	3.7	-21	-0.0357
20	3.7	-27	-0.0456
10	3.7	-30	-0.0520
0	3.7	-38	-0.0489
-10	3.7	-46	-0.0349
-20	3.7	-43	-0.0367
-30	3.7	-50	-0.0325

So, Frequency Stability Versus Input Voltage is:

Reference Frequency(Middle Channel): GSM 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	34	0.0421
	3.7	25	0.0326
	4.2	38	0.0425
Reference Frequency(Middle Channel): GSM 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-72	-0.0402
	3.7	-67	-0.0420
	4.2	-70	-0.0390
Reference Frequency(Middle Channel): GPRS 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	44	0.0501
	3.7	36	0.0428
	4.2	42	0.0467
Reference Frequency(Middle Channel): GPRS 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-33	-0.0325
	3.7	-27	-0.0268
	4.2	-38	-0.0315

***** END OF REPORT *****