



TEST REPORT

Report No. : CHTEW20040163 Report Verification: 
Project No. : SHT2004006501EW
FCC ID : 2ABFESPRM20
Applicant's name : General Sensing Systems LLC
Address : 250 CLEARBROOK RD, STE 260
Manufacturer : General Sensing Systems LLC
Address : 250 CLEARBROOK RD, STE 260
Test item description : Gimbal
Trade Mark : Gimbal
Model/Type reference : SPRM20
Listed Model(s) : -
Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of receipt of test sample : Apr.09, 2020
Date of testing : Apr.10, 2020- Apr.20, 2020
Date of issue : Apr.21, 2020
Result : PASS

Compiled by
(Position+Printed name+Signature): File administrator Fanghui Zhu 
Supervised by
(Position+Printed name+Signature): Project Engineer Kiki Kong 
Approved by
(Position+Printed name+Signature): RF Manager Hans Hu 

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd.
Address : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road,
Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
<u>4.</u>	<u>TEST CONFIGURATION</u>	<u>7</u>
4.1.	Test frequency list	7
4.2.	Test mode	7
4.3.	Support unit used in test configuration and system	7
4.4.	Testing environmental condition	8
4.5.	Measurement uncertainty	8
4.6.	Equipment Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>11</u>
5.1.	Antenna Requirement	11
5.2.	AC Conducted Emission	12
5.3.	Peak Output Power	15
5.4.	Power Spectral Density	16
5.5.	6dB bandwidth	17
5.6.	99% Occupied Bandwidth	18
5.7.	Duty Cycle	19
5.8.	Conducted Band edge and Spurious Emission	20
5.9.	Radiated Band edge Emission	22
5.10.	Radiated Spurious Emission	24
<u>6.</u>	<u>APPENDIX REPORT</u>	<u>28</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- [FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- [ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2020-04-21	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result
5.1	Antenna Requirement	15.203/15.247(c)	PASS
5.2	AC Conducted Emission	15.207	PASS
5.3	Peak Output Power	15.247(b)(3)	PASS
5.4	Power Spectral Density	15.247(e)	PASS
5.5	6dB Bandwidth	15.247(a)(2)	PASS
5.6	99% Occupied Bandwidth	-	PASS ^{*1}
5.7	Duty cycle	-	PASS ^{*1}
5.8	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS
5.9	Radiated Band Edge Emission	15.205/15.209	PASS
5.10	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS

Note:

- The measurement uncertainty is not included in the test result.
- ^{*1}: No requirement on standard, only report these test data.

3. SUMMARY

3.1. Client Information

Applicant:	General Sensing Systems LLC
Address:	250 CLEARBROOK RD, STE 260
Manufacturer:	General Sensing Systems LLC
Address:	250 CLEARBROOK RD, STE 260

3.2. Product Description

Name of EUT:	Gimbal
Trade Mark:	Gimbal
Model No.:	SPRM20
Listed Model(s):	-
Power supply:	DC 3.7V
Battery information:	Model: LT18650 3.7V 4000mAh

3.3. Radio Specification Description

Bluetooth version:	V4.2
Support function*2:	BLE
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	PCB Antenna
Antenna gain:	-0.68 dBi

Note:

*2: only show the RF function associated with this report.

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Qualifications	Type	Accreditation Number
	CNAS	L1225
	A2LA	3902.01
	FCC	762235
	Canada	5377A

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

Channel	Frequency (MHz)
00	2402
01	2404
:	:
19	2440
:	:
38	2478
39	2480

4.2. Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

4.3. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?					
✓ No					
Item	Equipement	Trade Name	Model No.	FCC ID	Power cord
1					
2					

4.4. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.5. Measurement uncertainty

Test Item	Measurement Uncertainty
AC Conducted Emission (150kHz~30MHz)	3.02 dB
Radiated Emission (30MHz~1000MHz)	4.90 dB
Radiated Emissions (1GHz~25GHz)	4.96 dB
Peak Output Power	0.51 dB
Power Spectral Density	0.51 dB
Conducted Spurious Emission	0.51 dB
6dB Bandwidth	70 Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.6. Equipment Used during the Test

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2019/10/26	2020/10/25
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2019/10/23	2020/10/22
●	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2019/10/23	2020/10/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLE X 142	EF-NM-BNCM-2M	2019/10/23	2020/10/22
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-6th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2019/10/26	2020/10/25
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2018/04/02	2021/04/01
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2020/04/05	2023/04/04
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2019/11/14	2020/11/13
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2019/08/21	2020/08/20
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX 104	501184/4	2019/05/27	2020/05/26
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-7th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2021/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2019/10/26	2020/10/25
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2020/04/01	2023/03/31
●	Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	25841	2018/10/11	2021/10/10
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2018/10/11	2021/10/11
●	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2019/11/14	2020/11/13
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2019/05/23	2020/05/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-03	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

● RF Conducted Method						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	FSV40	100048	2019/10/26	2020/10/25
●	Spectrum Analyzer	Agilent	N9020A	MY50510187	2019/10/26	2020/10/25
●	Power Meter	Anritsu	ML249A	N/A	2019/10/26	2020/10/25
○	Radio communication tester	R&S	CMW500	137688-Lv	2019/10/26	2020/10/25

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

The antenna type is a PCB antenna, the directional gain of the antenna less than 6 dBi

I

5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Test Line:

L

**MEASUREMENT RESULT: "GM2004135053_fin"**

4/13/2020 4:36PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.177000	52.00	10.0	65	12.6	QP	L1	GND
0.240000	42.30	10.0	62	19.8	QP	L1	GND
0.294000	41.70	10.1	60	18.7	QP	L1	GND
0.411000	39.00	10.1	58	18.6	QP	L1	GND
0.595500	36.30	10.1	56	19.7	QP	L1	GND
0.699000	33.50	10.1	56	22.5	QP	L1	GND


MEASUREMENT RESULT: "GM2004135053_fin2"

4/13/2020 4:36PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.177000	39.90	10.0	55	14.7	AV	L1	GND
0.235500	32.90	10.0	52	19.4	AV	L1	GND
0.294000	33.90	10.1	50	16.5	AV	L1	GND
0.411000	30.70	10.1	48	16.9	AV	L1	GND
0.532500	26.40	10.1	46	19.6	AV	L1	GND
0.591000	28.00	10.1	46	18.0	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM2004135054_fin"**

4/13/2020 4:38PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.177000	50.80	10.0	65	13.8	QP	N	GND
0.240000	41.30	10.0	62	20.8	QP	N	GND
0.298500	38.80	10.1	60	21.5	QP	N	GND
0.352500	36.70	10.1	59	22.2	QP	N	GND
0.411000	35.70	10.1	58	21.9	QP	N	GND
0.933000	29.30	10.1	56	26.7	QP	N	GND

MEASUREMENT RESULT: "GM2004135054_fin2"

4/13/2020 4:38PM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.172500	35.40	10.0	55	19.4	AV	N	GND
0.235500	31.90	10.0	52	20.4	AV	N	GND
0.294000	33.20	10.1	50	17.2	AV	N	GND
0.411000	29.80	10.1	48	17.8	AV	N	GND
0.591000	27.10	10.1	46	18.9	AV	N	GND
19.072500	27.90	10.5	50	22.1	AV	N	GND

5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10 and KDB 558074 D01 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
4. Record the measurement data.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data

Please refer to appendix A on the appendix report


5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
 $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$, $VBW \geq 3 \times RBW$
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data

Please refer to appendix B on the appendix report


5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = DTS channel center frequency
Span = 2 x DTS bandwidth
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data


Please refer to appendix C on the appendix report

5.6. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = channel center frequency
Span $\geq 1.5 \times \text{OBW}$
RBW = 1%~5%OBW
VBW $\geq 3 \times \text{RBW}$
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data


Please refer to appendix D on the appendix report

5.7. Duty Cycle

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span=zero span, Frequency=centered channel, RBW= 1 MHz, VBW $\geq$ RBW
Sweep=as necessary to capture the entire dwell time,
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE:

Please refer to the clause 4.2

TEST Data


Please refer to appendix E on the appendix report

5.8. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure
Center frequency=DTS channel center frequency
The span = 1.5 times the DTS bandwidth.
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

3. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST Data

Please refer to appendix F on the appendix report


5.9. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
 - a) Span shall wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

 - VBW=10Hz, When duty cycle is no less than 98 percent
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Margin = Limit – Level
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

Test channel		CH00			Polarity		Horizontal	
	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
	2310.000	44.62	-2.34	42.28	74.00	31.72	Horizontal	PK
	2310.000	42.28	-2.34	39.94	54.00	14.06	Horizontal	AV
	2390.000	44.22	-2.41	41.81	74.00	32.19	Horizontal	PK
	2390.000	42.11	-2.41	39.70	54.00	14.30	Horizontal	AV
Test channel		CH00			Polarity		Vertical	
	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
	2310.000	43.78	-2.34	41.44	74.00	32.56	Vertical	PK
	2310.000	41.43	-2.34	39.09	54.00	14.91	Vertical	AV
	2390.000	44.37	-2.41	41.96	74.00	32.04	Vertical	PK
	2390.000	42.19	-2.41	39.78	54.00	14.22	Vertical	AV

Test channel		CH39			Polarity		Horizontal	
	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
	2483.500	50.55	-2.15	48.40	74.00	25.60	Horizontal	PK
	2483.500	48.26	-2.15	46.11	54.00	7.89	Horizontal	AV
	2500.000	46.56	-2.10	44.46	74.00	29.54	Horizontal	PK
	2500.000	44.52	-2.10	42.42	54.00	11.58	Horizontal	AV
Test channel		CH39			Polarity		Vertical	
	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
	2483.500	48.01	-2.15	45.86	74.00	28.14	Vertical	PK
	2483.500	46.15	-2.15	44.00	54.00	10.00	Vertical	AV
	2500.000	43.31	-2.10	41.21	74.00	32.79	Vertical	PK
	2500.000	41.25	-2.10	39.15	54.00	14.85	Vertical	AV

5.10. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz		Quasi-peak
0.49 MHz ~ 1.705 MHz	$24000/F(\text{kHz}) @30\text{m}$	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + $40 \cdot \log(300/3)$ = Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m + $40 \cdot \log(30/3)$ = Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


➤ 9 kHz ~ 30 MHz



➤ 30 MHz ~ 1 GHz



➤ Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

 - VBW=10Hz, When duty cycle is no less than 98 percent
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Margin = Limit – Level
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

TEST DATA FOR 9 kHz ~ 30 MHz


The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

TEST DATA FOR 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH39 which it was worst case, so only show the worst case's data on this report.

Polarization:

Horizontal


**MEASUREMENT RESULT: "GM2004146105_red"**

4/14/2020 8:17PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
86.260000	21.50	-13.1	40.0	18.5	QP	300.0	193.00	HORIZONTAL
140.580000	26.20	-13.1	43.5	17.3	QP	100.0	27.00	HORIZONTAL
214.300000	27.40	-8.9	43.5	16.1	QP	100.0	347.00	HORIZONTAL
309.360000	32.00	-5.6	46.0	14.0	QP	100.0	12.00	HORIZONTAL
313.240000	31.70	-5.5	46.0	14.3	QP	100.0	360.00	HORIZONTAL
955.380000	37.10	9.1	46.0	8.9	QP	100.0	52.00	HORIZONTAL

Polarization:

Vertical

**MEASUREMENT RESULT: "GM2004146104_red"**

4/14/2020 8:13PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
45.520000	32.30	-7.6	40.0	7.7	QP	100.0	350.00	VERTICAL
72.680000	33.70	-13.5	40.0	6.3	QP	100.0	202.00	VERTICAL
171.620000	23.40	-12.0	43.5	20.1	QP	100.0	310.00	VERTICAL
196.840000	30.80	-8.2	43.5	12.7	QP	100.0	110.00	VERTICAL
427.700000	31.20	-1.8	46.0	14.8	QP	100.0	255.00	VERTICAL
922.400000	36.00	8.7	46.0	10.0	QP	100.0	310.00	VERTICAL

TEST DATA FOR 1 GHz ~ 25 GHz

Test channel				CH00			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1345.156	31.86	-5.57	26.29	74.00	47.71	Horizontal	PK
4804.062	36.81	7.06	43.87	74.00	30.13	Horizontal	PK
7256.875	29.14	15.02	44.16	74.00	29.84	Horizontal	PK
9526.093	30.69	17.77	48.46	74.00	25.54	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1236.468	33.41	-5.74	27.67	74.00	46.33	Vertical	PK
3164.937	32.03	0.66	32.69	74.00	41.31	Vertical	PK
4804.062	34.38	7.06	41.44	74.00	32.56	Vertical	PK
8202.750	31.77	16.01	47.78	74.00	26.22	Vertical	PK

Test channel				CH19			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1242.343	33.32	-5.72	27.60	74.00	46.40	Horizontal	PK
3128.218	31.81	0.47	32.28	74.00	41.72	Horizontal	PK
4878.968	38.98	7.15	46.13	74.00	27.87	Horizontal	PK
9351.312	30.53	17.63	48.16	74.00	25.84	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1229.125	34.31	-5.75	28.56	74.00	45.44	Vertical	PK
2993.093	31.95	-0.08	31.87	74.00	42.13	Vertical	PK
4880.437	34.60	7.15	41.75	74.00	32.25	Vertical	PK
8916.562	30.16	15.97	46.13	74.00	27.87	Vertical	PK

Test channel				CH39			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1207.093	33.46	-5.81	27.65	74.00	46.35	Horizontal	PK
3150.250	32.13	0.58	32.71	74.00	41.29	Horizontal	PK
4959.750	37.53	7.58	45.11	74.00	28.89	Horizontal	PK
9292.562	31.21	17.83	49.04	74.00	24.96	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1287.875	34.24	-5.60	28.64	74.00	45.36	Vertical	PK
3176.687	31.96	0.72	32.68	74.00	41.32	Vertical	PK
4961.218	36.47	7.59	44.06	74.00	29.94	Vertical	PK
9304.312	29.72	17.90	47.62	74.00	26.38	Vertical	PK

6APPENDIX REPORT

APPENDIX REPORT

Project No.	SHT2004006501EW	Radio Specification	Bluetooth BLE
Test sample No.	YPHT20040065002	Model No.	SPRM20
Start test date	2020/4/20	Finish date	2020/4/20
Temperature	25°C	Humidity	50%
Test Engineer	Jinyue.Yan	Auditor	<i>William.wang</i>


Appendix clause	Test item	Result
A	Peak Output Power	PASS
B	Power Spectral Density	PASS
C	6 dB Bandwidth	PASS
D	99% Occupied Bandwidth	PASS
E	Duty cycle	PASS
F	Band edge and Spurious Emissions (conducted)	PASS

Appendix A: Peak Output Power

Type	Channel	Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
BT-BLE	00	-1.52	-1.54	≤30.00	Pass
	19	-1.32	-1.33		
	39	-2.10	-2.12		

Appendix B: Power Spectral Density


Type	Channel	Power Spectral Density(dBm/3KHz)	Limit (dBm/3KHz)	Result
BT-BLE	00	-17.25	≤8.00	Pass
	19	-16.93		
	39	-17.85		




Appendix C: 6dB bandwidth

Type	Channel	6dB Bandwidth(kHz)	Limit (kHz)	Result
BT-BLE	00	752.00	≥500	Pass
	19	746.00		
	39	752.00		


CH00



CH19




CH39




Appendix D: 99% Occupied Bandwidth

Type	Channel	99% Occupied Bandwidth(MHz)	Limit (kHz)	Result
BT-BLE	00	1.03	-	Pass
	19	1.03		
	39	1.03		


CH00



CH19




CH39






Appendix E: Duty cycle




Test Frequency (MHz)	T _{on} time for single burst (ms)	T _{period} (ms)	Duty cycle	1/T _{on} time (kHz)
2440	0.38	0.63	60.3%	2.6






Appendix F: Band edge and Spurious Emissions (conducted)

Test Item:	Band edge																																										
CH00	MultiView Spectrum Ref Level 10.50 dBm Offset 1.00 dB BW 100 kHz ATT 20 dB SW 1.05 ms VBW 300 kHz Mode Auto Sweep Count 300/300 Frequency Sweep 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm -80 dBm 2.31 GHz 1001 pts 9.5 MHz/ 2.405 GHz M1[1] -2.46 dBm 2.402000 GHz M2[1] -50.17 dBm 2.400000 GHz 2 Marker Table <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.4022 GHz</td><td>-2.46 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-50.17 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-71.49 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-73.10 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.399775 GHz</td><td>-49.21 dBm</td><td></td><td></td></tr></tbody></table> Date: 20/APR/2020 13:32:24	Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.4022 GHz	-2.46 dBm			M2	1		2.4 GHz	-50.17 dBm			M3	1		2.39 GHz	-71.49 dBm			M4	1		2.31 GHz	-73.10 dBm			M5	1		2.399775 GHz	-49.21 dBm		
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																					
M1	1		2.4022 GHz	-2.46 dBm																																							
M2	1		2.4 GHz	-50.17 dBm																																							
M3	1		2.39 GHz	-71.49 dBm																																							
M4	1		2.31 GHz	-73.10 dBm																																							
M5	1		2.399775 GHz	-49.21 dBm																																							
CH39	MultiView Spectrum Ref Level 10.50 dBm Offset 1.00 dB BW 100 kHz ATT 20 dB SW 1.02 ms VBW 300 kHz Mode Auto Sweep Count 100/100 Frequency Sweep 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm -80 dBm 2.478 GHz 1001 pts 2.2 MHz/ 2.5 GHz M1[1] -3.06 dBm 2.479989 GHz M2[1] -58.89 dBm 2.483300 GHz 2 Marker Table <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.479989 GHz</td><td>-3.06 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4833 GHz</td><td>-58.89 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-73.86 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.483698 GHz</td><td>-54.79 dBm</td><td></td><td></td></tr></tbody></table> Date: 20/APR/2020 13:42:06	Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.479989 GHz	-3.06 dBm			M2	1		2.4833 GHz	-58.89 dBm			M3	1		2.5 GHz	-73.86 dBm			M4	1		2.483698 GHz	-54.79 dBm									
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																					
M1	1		2.479989 GHz	-3.06 dBm																																							
M2	1		2.4833 GHz	-58.89 dBm																																							
M3	1		2.5 GHz	-73.86 dBm																																							
M4	1		2.483698 GHz	-54.79 dBm																																							

Test Item:	SE
CH00 Reference level	 Ref Level 30.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SWI 1.04 ms VBW 300 kHz Mode Auto Sweep Count 100/100 MI[1] 2.27 dBm 2.4022400 GHz CF 2.402 GHz 1001 pts 3.0 MHz/ Span 30.0 MHz Date: 20/4PR,2000 13:35:53
CH00 30MHz~1000MHz	 Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SWI 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 MI[1] -60.21 dBm 999.9520 MHz 30.0 MHz 30001 pts 97.0 MHz/ 1.0 GHz Date: 20/4PR,2000 13:36:00
CH00 1GHz~26GHz	 Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 36 dB SWI 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 MI[1] -66.24 dBm 25.875633 GHz 1.0 GHz 30001 pts 2.5 GHz/ 26.0 GHz Date: 20/4PR,2000 13:36:25

CH19
Reference levelCH19
30MHz~1000MHzCH19
1GHz~26GHz

CH39 Reference level	 Ref Level 30.00 dBm Offset 1.00 dB RBW 100 kHz Att 30.0 dB SWF 1.04 ms VBW 300 kHz Mode Auto Sweep Count 100/100 MI[1] -2.87 dBm 2.480000 GHz CF 2.48 GHz 1001 pts 3.0 MHz/ Span 30.0 MHz Date: 20/4PR,2020 13:42:13
CH39 30MHz~1000MHz	 Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30.0 dB SWF 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 MI[1] -60.56 dBm 552.1170 MHz H1 -22.870 dBm 30.0 MHz 30001 pts 97.0 MHz/ 1.0 GHz Date: 20/4PR,2020 13:42:29
CH39 1GHz~26GHz	 Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30.0 dB SWF 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 MI[1] -47.35 dBm 25.743333 GHz H1 -22.870 dBm 1.0 GHz 30001 pts 2.5 GHz/ 26.0 GHz Date: 20/4PR,2020 13:42:45

-----End of Report-----