

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: 2ABFG-YRDC2

Equipment Under Test : Yale Smart Opener-Garage
Model Name : YRDC-2
Variant Model Name(s) : Refer to the page 3
Applicant : iRevo-ASSAABLOY Korea
Manufacturer : iRevo-ASSAABLOY Korea
Date of Receipt : 2022.10.11
Date of Test(s) : 2022.10.13 ~ 2022.11.28
Date of Issue : 2022.12.02

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.
We are responsible for all the information of this test report except for the data(※) provided by the customer.

Tested by:



Taek Kim

Technical
Manager:



Jinhyoung Cho

SGS Korea Co., Ltd. Gunpo Laboratory



SGS Korea Co., Ltd.

4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

<http://www.sgsgroup.kr>

Report Number: F690501-RF-RTL003611

Page: 2 of 6

INDEX

Table of Contents

Page

1. General Information -----	3
2. RF Exposure Evaluation -----	5

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Telephone : +82 31 688 0901

FAX : +82 31 688 0921

1.2. Details of Applicant

Applicant : iRevo-ASSA ABLOY Korea

Address : 10f of JEI PLATZ Bldg., 186, Gasandigital 1-ro, Geumcheon-gu, Seoul, South Korea, 08502

Contact Person : Jang, Soo-kyung

Phone No. : +82 2 2107 5741

1.3. Details of Manufacturer

Company : Same as applicant

Address : Same as applicant

1.4. Description of EUT

Kind of Product	Yale Smart Opener-Garage
Model Name	YRDC-2
Variant Model Name	IES-D320W
Serial Number	Conducted Sample: 001 Radiated Sample: 002
Power Supply	DC 5 V ~ 24 V
Frequency Range	2 402 MHz ~ 2 480 MHz (Bluetooth Low Energy)
Modulation Technique	GFSK
Number of Channels	40 channels (Bluetooth Low Energy)
Antenna Type	Dielectric Chip Antenna
Antenna Gain*	1.37 dB i
H/W Version	1.0
S/W Version	1.0
FVIN	N/A

1.5. Test Report Revision

Revision	Report Number	Date of Issue	Description
0	F690501-RF-RTL003611	2022.12.02	Initial

1.6. Description of Variant Model

Model Name	Description
YRDC-2	- Basic Model
IES-D320W	- Same as basic model, The only difference is the model name

Note;

All the test was performed with basic model.

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1 500	-	-	f/300	6
1 500-100 000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1 500	-	-	f/1500	30
<u>1 500-100 000</u>	-	-	<u>1.0</u>	<u>30</u>

2.1.1. Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data
Test Mode : Normal Operation

2.1.4. Output Power into Antenna & RF Exposure Evaluation Distance

Bluetooth Low Energy

- Maximum Tune up Tolerance

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
2 400 ~ 2 483.5	5	2.5	1.37	0.001 534	1

WLAN (2.4G)

- Maximum tune up tolerance

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
2 400 ~ 2 483.5	15	1	3.00	0.015 803	1

Note;

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 cm between the radiator and your body.
- The antenna gain of this transmitter is less than 6 dB i and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.
- According to KDB 447498 D01 RF Exposure Guidance 4.1.
- The RF exposure was evaluated by output average power of tune-up procedure considering tolerance. So, Maximum peak conducted power may exceed the power mentioned in this report.

Simultaneous transmission of RF Exposure test exclusion for worst case configuration.

Confirm the sum result of individual MPES ratio is ≤ 1.0 ;

Bluetooth Low Energy + WLAN : $(0.001\ 534 / 1) + (0.015\ 803 / 1) = 0.017\ 337 \leq 1.0$

- End of the Test Report -