FCC RF Test Report

APPLICANT	**:**	**Linktel Inc.**
EQUIPMENT	**:**	**PChomeTalk Phone for Skype 3G**
BRAND NAME	**:**	**PChomeTalk**
MODEL NAME	**:**	**PT2**
FCC ID	**:**	**2ABGCPT2**
STANDARD	**:**	**FCC Part 15 Subpart C §15.247**
CLASSIFICATION	**:**	**(DTS) Digital Transmission System**

The product was received on Jul. 30, 2014 and testing was completed on Sep. 19, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC.
No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification subjective to this standard 5
1.5 Modification of EUT 5
1.6 Testing Location 6
1.7 Applicable Standards 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **7**

2.1 Carrier Frequency Channel 7
2.2 Pre-Scanned RF Power 8
2.3 Test Mode 9
2.4 Connection Diagram of Test System 10
2.5 Support Unit used in test configuration and system 11
2.6 EUT Operation Test Setup 11
2.7 Measurement Results Explanation Example 11

3 TEST RESULT **12**

3.1 6dB Bandwidth Measurement 12
3.2 Output Power Measurement 15
3.3 Power Spectral Density Measurement 18
3.4 Conducted Band Edges and Spurious Emission Measurement 21
3.5 Radiated Band Edges and Spurious Emission Measurement 34
3.6 AC Conducted Emission Measurement 38
3.7 Antenna Requirements 42

4 LIST OF MEASURING EQUIPMENT **43**

5 UNCERTAINTY OF EVALUATION **44**

APPENDIX A. SETUP PHOTOGRAPHS

APPENDIX B. RADIATED SPURIOUS EMISSION

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR473003B	Rev. 01	Initial issue of report	Sep. 26, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	RSS-210 A8.2(a)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.2	15.247(b)	RSS-210 A8.4	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	RSS-210 A8.2(b)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	RSS-210 A8.5	Conducted Band Edges	≤ 20dBc	Pass	-
			Conducted Spurious Emission		Pass	-
3.5	15.247(d)	RSS-210 A8.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.98 dB at 2483.520 MHz
3.6	15.207	RSS-Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 9.70 dB at 0.182/0.190 MHz
3.7	15.203 & 15.247(b)	RSS-210 A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Linktel Inc.
24F/B, 105, Sec. 2, Tun-Hwa S. Rd., Taipei 106, Taiwan

1.2 Manufacturer

Mobiwire Mobiles (Ningbo) Co., Ltd.
Mobiwire Mobiles, No. 999 Dacheng East Road, Fenghua, Zhejiang, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	PChomeTalk Phone for Skype 3G
Brand Name	PChomeTalk
Model Name	PT2
FCC ID	2ABGCPT2
EUT supports Radios application	GSM/GPRS/WCDMA/HSPA WLAN 11b/g/n HT20/HT40 Bluetooth v3.0 EDR
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 13.45 dBm (0.0221 W) 802.11g : 16.31 dBm (0.0428 W) 802.11n HT20 : 16.52 dBm (0.0449 W) 802.11n HT40 : 16.15 dBm (0.0412 W)
Antenna Type	Fixed Internal Antenna type with gain 0.00 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	**Sporton Site No.**		
	TH02-HY	CO05-HY	03CH09-HY

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ANSI C63.4-2003

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b mode				
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps
Peak Power (dBm)	**13.45**	13.43	13.41	13.32

2.4GHz 802.11g mode								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Peak Power (dBm)	**16.31**	16.24	16.20	16.27	16.03	16.15	15.92	15.95

2.4GHz 802.11n HT20 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	**16.52**	16.47	16.41	16.18	16.33	16.22	16.32	16.37

2.4GHz 802.11n HT40 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	**16.15**	16.07	15.59	15.68	15.77	15.62	15.74	15.53

2.3 Test Mode

Final results of test modes, data rates and test channels are shown as following table.

Test Cases				
	Test Items	**Mode**	**Data Rate**	**Test Channel**
Conducted TCs	**6dB BW Power Spectral Density**	**802.11b**	**1 Mbps**	**1/6/11**
		802.11g	**6 Mbps**	**1/6/11**
		802.11n HT20	**MCS0**	**1/6/11**
		802.11n HT40	**MCS0**	**3/6/9**
	Output Power	**802.11b**	**1 Mbps**	**1/6/11**
		802.11g	**6 Mbps**	**1/6/11**
		802.11n HT20	**MCS0**	**1/6/11**
		802.11n HT40	**MCS0**	**3/6/9**
	Conducted Band Edge	**802.11b**	**1 Mbps**	**1/11**
		802.11g	**6 Mbps**	**1/11**
		802.11n HT20	**MCS0**	**1/11**
		802.11n HT40	**MCS0**	**3/9**
	Conducted Spurious Emission	**802.11b**	**1 Mbps**	**1/6/11**
		802.11g	**6 Mbps**	**1/6/11**
		802.11n HT20	**MCS0**	**1/6/11**
		802.11n HT40	**MCS0**	**3/6/9**
Radiated TCs	**Radiated Band Edge**	**802.11b**	**1 Mbps**	**1/11**
		802.11g	**6 Mbps**	**1/11**
		802.11n HT20	**MCS0**	**1/11**
		802.11n HT40	**MCS0**	**3/9**
	Radiated Spurious Emission	**802.11b**	**1 Mbps**	**1/6/11**
		802.11g	**6 Mbps**	**1/6/11**
		802.11n HT20	**MCS0**	**1/6/11**
		802.11n HT40	**MCS0**	**3/6/9**
AC Conducted Emission	Mode 1 : WCDMA Band V Idle + Bluetooth Link + WLAN Link + Camera + Earphone + Battery + USB Cable (Data Link with Notebook)			

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<EUT with USB Cable (Link with Notebook) Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
6.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
7.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Occupied Bandwidth

Test Band :	2.4GHz	Temperature :	21~26℃
Test Engineer :	Osolemio Chang	Relative Humidity :	45~54%

Mod.	Data Rate	N_{TX}	Channel	Freq. (MHz)	-	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412		10.08	0.5	Pass
11b	1Mbps	1	6	2437		10.08	0.5	Pass
11b	1Mbps	1	11	2462		10.04	0.5	Pass
11g	6Mbps	1	1	2412		15.12	0.5	Pass
11g	6Mbps	1	6	2437		15.68	0.5	Pass
11g	6Mbps	1	11	2462		15.52	0.5	Pass
HT20	MCS0	1	1	2412	-	15.12	0.5	Pass
HT20	MCS0	1	6	2437		15.44	0.5	Pass
HT20	MCS0	1	11	2462		15.40	0.5	Pass
HT40	MCS0	1	3	2422		35.24	0.5	Pass
HT40	MCS0	1	6	2437		35.20	0.5	Pass
HT40	MCS0	1	9	2452		35.20	0.5	Pass

Minimum 6dB Bandwidth



Date: 18.SEP.2014 00:10:23

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Test Mode :	2.4GHz	Temperature :	21~26℃
Test Engineer :	Osolemio Chang	Relative Humidity :	45~54%

Mod.	Data Rate	N_{TX}	Channel	Freq. (MHz)	RF Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	13.45	30	0.00	Pass
11b	1Mbps	1	6	2437	13.06	30	0.00	Pass
11b	1Mbps	1	11	2462	12.88	30	0.00	Pass
11g	6Mbps	1	1	2412	15.98	30	0.00	Pass
11g	6Mbps	1	6	2437	16.31	30	0.00	Pass
11g	6Mbps	1	11	2462	15.87	30	0.00	Pass
HT20	MCS0	1	1	2412	16.27	30	0.00	Pass
HT20	MCS0	1	6	2437	16.52	30	0.00	Pass
HT20	MCS0	1	11	2462	16.21	30	0.00	Pass
HT40	MCS0	1	3	2422	15.65	30	0.00	Pass
HT40	MCS0	1	6	2437	16.15	30	0.00	Pass
HT40	MCS0	1	9	2452	15.57	30	0.00	Pass

Note: Measured power (dBm) has offset with cable loss.

3.2.6 Test Result of Average output Power (Reporting Only)

Test Mode :	2.4GHz	Temperature :	21~26℃
Test Engineer :	Osolemio Chang	Relative Humidity :	45~54%

Mod.	Data Rate	N_{TX}	Channel	Freq. (MHz)	Duty Factor (dB)	Average Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	0.09	10.86	30	0.00	Pass
11b	1Mbps	1	6	2437	0.09	10.33	30	0.00	Pass
11b	1Mbps	1	11	2462	0.09	10.12	30	0.00	Pass
11g	6Mbps	1	1	2412	0.47	7.22	30	0.00	Pass
11g	6Mbps	1	6	2437	0.47	7.97	30	0.00	Pass
11g	6Mbps	1	11	2462	0.47	6.63	30	0.00	Pass
HT20	MCS0	1	1	2412	0.56	7.35	30	0.00	Pass
HT20	MCS0	1	6	2437	0.56	8.25	30	0.00	Pass
HT20	MCS0	1	11	2462	0.56	6.98	30	0.00	Pass
HT40	MCS0	1	3	2422	1.01	5.42	30	0.00	Pass
HT40	MCS0	1	6	2437	1.01	7.10	30	0.00	Pass
HT40	MCS0	1	9	2452	1.01	4.85	30	0.00	Pass

Note: Measured power (dBm) has offset with cable loss and duty factor.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Test Mode :	2.4GHz	Temperature :	21~26℃
Test Engineer :	Osolemio Chang	Relative Humidity :	45~54%

Mod.	Data Rate	N_{TX}	Channel	Freq. (MHz)	Peak Power Density (dBm/3kHz)	Max. Limits (dBm/3kHz)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	-12.24	8	0.00	Pass
11b	1Mbps	1	6	2437	-12.78	8	0.00	Pass
11b	1Mbps	1	11	2462	-13.21	8	0.00	Pass
11g	6Mbps	1	1	2412	-17.07	8	0.00	Pass
11g	6Mbps	1	6	2437	-17.10	8	0.00	Pass
11g	6Mbps	1	11	2462	-18.60	8	0.00	Pass
HT20	MCS0	1	1	2412	-18.59	8	0.00	Pass
HT20	MCS0	1	6	2437	-17.31	8	0.00	Pass
HT20	MCS0	1	11	2462	-18.19	8	0.00	Pass
HT40	MCS0	1	3	2422	-23.78	8	0.00	Pass
HT40	MCS0	1	6	2437	-22.37	8	0.00	Pass
HT40	MCS0	1	9	2452	-25.02	8	0.00	Pass

Note: Measured power density (dBm) has offset with cable loss.

Worst Case Power Density (dBm/3kHz)



Date: 17.SEP.2014 23:07:30

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	21~26℃
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Osolemio Chang

WLAN 802.11b Channel 01

100kHz PSD reference Level



Date: 17.SEP.2014 22:33:42

Low Channel Plot



Date: 17.SEP.2014 22:34:15

Spurious Emission 30MHz~3GHz



Date: 17.SEP.2014 22:36:25

Spurious Emission 2GHz~25GHz



Date: 17.SEP.2014 22:36:43

Test Mode :	802.11b	**Temperature :**	21~26℃
Test Band :	2.4GHz Mid.	**Relative Humidity :**	45~54%
Test Channel :	06	**Test Engineer :**	Osolemio Chang

WLAN 802.11b Channel 06

100kHz PSD reference Level



Date: 17.SEP.2014 23:02:44

Spurious Emission 30MHz~3GHz



Date: 17.SEP.2014 23:03:05

Spurious Emission 2GHz~25GHz



Date: 17.SEP.2014 23:03:23

Test Mode :	802.11b	**Temperature :**	21~26℃
Test Band :	2.4GHz High	**Relative Humidity :**	45~54%
Test Channel :	11	**Test Engineer :**	Osolemio Chang

WLAN 802.11b Channel 11

100kHz PSD reference Level



Date: 17.SEP.2014 23:13:13

High Channel Plot



Date: 17.SEP.2014 23:13:29

Spurious Emission 30MHz~3GHz



Date: 17.SEP.2014 23:13:55

Spurious Emission 2GHz~25GHz



Date: 17.SEP.2014 23:14:13

Test Mode :	802.11g	**Temperature :**	21~26℃
Test Band :	2.4GHz Low	**Relative Humidity :**	45~54%
Test Channel :	01	**Test Engineer :**	Osolemio Chang

WLAN 802.11g Channel 01

100kHz PSD reference Level



Date: 17.SEP.2014 23:18:55

Low Channel Plot



Date: 17.SEP.2014 23:21:22

Spurious Emission 30MHz~3GHz



Date: 17.SEP.2014 23:20:38

Spurious Emission 2GHz~25GHz



Date: 17.SEP.2014 23:20:56

Test Mode :	802.11g	Temperature :	21~26℃
Test Band :	2.4GHz Mid.	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Osolemio Chang

WLAN 802.11g Channel 06

100kHz PSD reference Level



Date: 17.SEP.2014 23:25:52

Spurious Emission 30MHz~3GHz



Date: 17.SEP.2014 23:26:21

Spurious Emission 2GHz~25GHz



Date: 17.SEP.2014 23:26:39

Test Mode :	802.11g	Temperature :	21~26℃
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Osolemio Chang

WLAN 802.11g Channel 11

100kHz PSD reference Level



Date: 17.SEP.2014 23:34:54

High Channel Plot



Date: 17.SEP.2014 23:35:14

Spurious Emission 30MHz~3GHz



Date: 17.SEP.2014 23:35:36

Spurious Emission 2GHz~25GHz



Date: 17.SEP.2014 23:35:54

Test Mode :	802.11n HT20	Temperature :	21~26℃
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Osolemio Chang

WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level



Date: 17.SEP.2014 23:55:13

Low Channel Plot



Date: 17.SEP.2014 23:56:57

Spurious Emission 30MHz~3GHz



Date: 17.SEP.2014 23:55:58

Spurious Emission 2GHz~25GHz



Date: 17.SEP.2014 23:56:16

Test Mode :	802.11n HT20	Temperature :	21~26℃
Test Band :	2.4GHz Mid.	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Osolemio Chang

WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11n HT20	Temperature :	21~26℃
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Osolemio Chang

WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level



Date: 18.SEP.2014 00:05:46

High Channel Plot



Date: 18.SEP.2014 00:06:27

Spurious Emission 30MHz~3GHz



Date: 18.SEP.2014 00:06:52

Spurious Emission 2GHz~25GHz



Date: 18.SEP.2014 00:07:10

Test Mode :	802.11n HT40	**Temperature :**	21~26℃
Test Band :	2.4GHz Low	**Relative Humidity :**	45~54%
Test Channel :	03	**Test Engineer :**	Osolemio Chang

WLAN 802.11n HT40 Channel 03

100kHz PSD reference Level



Date: 18.SEP.2014 00:11:14

Low Channel Plot



Date: 18.SEP.2014 00:13:11

Spurious Emission 30MHz~3GHz



Date: 18.SEP.2014 00:17:35

Spurious Emission 2GHz~25GHz



Date: 18.SEP.2014 00:17:54

Test Mode :	802.11n HT40	Temperature :	21~26℃
Test Band :	2.4GHz Mid.	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Osolemio Chang

WLAN 802.11n HT40 Channel 06

100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11n HT40	**Temperature :**	21~26℃
Test Band :	2.4GHz High	**Relative Humidity :**	45~54%
Test Channel :	09	**Test Engineer :**	Osolemio Chang

WLAN 802.11n HT40 Channel 09

100kHz PSD reference Level



Date: 18.SEP.2014 00:28:32

High Channel Plot



Date: 18.SEP.2014 00:29:38

Spurious Emission 30MHz~3GHz



Date: 18.SEP.2014 00:30:03

Spurious Emission 2GHz~25GHz



Date: 18.SEP.2014 00:30:21

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(μs)	1/T(kHz)	VBW Setting
802.11b	97.90	8400.00	0.12	300Hz
802.11g	89.74	1400.00	0.71	1kHz
2.4GHz 802.11n HT20	87.84	1300.00	0.77	1kHz
2.4GHz 802.11n HT40	79.27	650.00	1.54	3kHz

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges & Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Note: Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

Test Engineer :	Ian Liang and Bill Chang	**Temperature :**	23~25°C
		Relative Humidity :	35~45%

The test results refer Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	**Temperature :**	20~22℃
Test Engineer :	Kai-Chun Chu	**Relative Humidity :**	46~48%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Function Type :	WCDMA Band V Idle + Bluetooth Link + WLAN Link + Camera + Earphone + Battery + USB Cable (Data Link with Notebook)		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.190000	54.3	Off	L1	19.3	9.7	64.0
0.246000	43.9	Off	L1	19.4	18.0	61.9
0.310000	37.6	Off	L1	19.4	22.4	60.0
0.374000	35.3	Off	L1	19.4	23.1	58.4
0.494000	31.0	Off	L1	19.4	25.1	56.1
4.662000	26.2	Off	L1	19.6	29.8	56.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.190000	39.1	Off	L1	19.3	14.9	54.0
0.246000	30.0	Off	L1	19.4	21.9	51.9
0.310000	24.5	Off	L1	19.4	25.5	50.0
0.374000	20.1	Off	L1	19.4	28.3	48.4
0.494000	16.6	Off	L1	19.4	29.5	46.1
4.662000	14.8	Off	L1	19.6	31.2	46.0

Test Mode :	Mode 1	Temperature :	20~22℃℃
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~48%%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band V Idle + Bluetooth Link + WLAN Link + Camera + Earphone + Battery + USB Cable (Data Link with Notebook)		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.182000	54.7	Off	N	19.4	9.7	64.4
0.238000	44.2	Off	N	19.4	18.0	62.2
0.310000	35.8	Off	N	19.4	24.2	60.0
0.406000	31.7	Off	N	19.4	26.0	57.7
0.534000	31.4	Off	N	19.4	24.6	56.0
3.558000	26.1	Off	N	19.6	29.9	56.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.182000	38.0	Off	N	19.4	16.4	54.4
0.238000	25.3	Off	N	19.4	26.9	52.2
0.310000	20.8	Off	N	19.4	29.2	50.0
0.406000	21.1	Off	N	19.4	26.6	47.7
0.534000	21.2	Off	N	19.4	24.8	46.0
3.558000	17.8	Off	N	19.6	28.2	46.0

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 09, 2014	Aug. 06, 2014~ Sep. 18, 2014	Jun. 08, 2015	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	1036004	300MHz~40GHz	Aug. 17, 2013	Aug. 06, 2014~ Aug. 08, 2014	Aug. 16, 2014	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	1036004	300MHz~40GHz	Aug. 09, 2014	Aug. 09, 2014~ Sep. 18, 2014	Aug. 08, 2015	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz	Aug. 17, 2013	Aug. 06, 2014~ Aug. 08, 2014	Aug. 16, 2014	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz	Aug. 09, 2014	Aug. 09, 2014~ Sep. 18, 2014	Aug. 08, 2015	Conducted (TH02-HY)
EMI Test Receiver	Agilent	N9038A	MY53290053	20Hz to 26.5GHz	Jan. 08, 2014	Sep. 18, 2014~ Sep. 19, 2014	Jan. 07, 2015	Radiation (03CH09-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jul. 28, 2014	Sep. 18, 2014~ Sep. 19, 2014	Jul. 27, 2016	Radiation (03CH09-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 03, 2013	Sep. 18, 2014~ Sep. 19, 2014	Oct. 02, 2014	Radiation (03CH09-HY)
Double Ridged Guide Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Apr. 16, 2014	Sep. 18, 2014~ Sep. 19, 2014	Apr. 15, 2015	Radiation (03CH09-HY)
Bilog Antenna	TESEQ	CBL 6111D	37059	30MHz ~ 1GHz	Jan. 23, 2014	Sep. 18, 2014~ Sep. 19, 2014	Jan. 22, 2015	Radiation (03CH09-HY)
Preamplifier	EMEC	EM01M06G	60584	100MHz ~ 6GHz	Jul. 15, 2014	Sep. 18, 2014~ Sep. 19, 2014	Jul. 14, 2015	Radiation (03CH09-HY)
Preamplifier	EMCI	EMC051845	SN980048	1GHz ~ 18GHz	Jul. 17, 2014	Sep. 18, 2014~ Sep. 19, 2014	Jul. 16, 2015	Radiation (03CH09-HY)
Preamplifier	MITEQ	JS44-18004000-33-8P	1840917	18GHz~40GHz	Jun. 09, 2014	Sep. 18, 2014~ Sep. 19, 2014	Jun. 08, 2015	Radiation (03CH09-HY)
Preamplifier	Sonoma-Instrument	310 N	187282	10MHz~1GHz	Apr. 28, 2014	Sep. 18, 2014~ Sep. 19, 2014	Apr. 27, 2015	Radiation (03CH09-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz~40GHz	Oct. 23, 2013	Sep. 18, 2014~ Sep. 19, 2014	Oct. 22, 2014	Radiation (03CH09-HY)
Turn Table	ChainTek	T-200S	1308028	0~360 deg	N/A	Sep. 18, 2014~ Sep. 19, 2014	N/A	Radiation (03CH09-HY)
Antenna Mast	ChainTek	MBS-400	1308049	1m~4m	N/A	Sep. 18, 2014~ Sep. 19, 2014	N/A	Radiation (03CH09-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Nov. 15, 2013	Aug. 05, 2014	Nov. 14, 2014	Conduction (CO05-HY)
LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 12, 2013	Aug. 05, 2014	Dec. 11, 2014	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz ~ 30MHz	Dec. 04, 2013	Aug. 05, 2014	Dec. 03, 2014	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 05, 2014	N/A	Conduction (CO05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.26**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.7**