TEST REPORT

APPLICANT	:	Reliance Communications LLC
PRODUCT NAME	:	Orbic Fun Pro 5G
MODEL NAME	:	R678L5SFP
BRAND NAME	:	Orbic
FCC ID	:	2ABGH-R678L5SFP
STANDARD(S)	:	47 CFR Part 15 Subpart C
RECEIPT DATE	:	2023-11-28
TEST DATE	:	2023-12-06 to 2024-02-23
ISSUE DATE	:	2024-04-25

Edited by: Peng Mi (Rapporteur)

Approved by: Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB
Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China
Tel: 86-755-36698555 Fax: 86-755-36698525
Http://www.morlab.cn E-mail: service@morlab.cn

DIRECTORY

1. Technical Information ····· 3
1.1. Applicant and Manufacturer Information ····· 3
1.2. Equipment Under Test (EUT) Description ····· 3
1.3. Test Standards and Results ····· 5
1.4. Environmental Conditions ····· 6
2. 47 CFR Part 15C Requirements ····· 7
2.1. Antenna Requirement ····· 7
2.2. Conducted Emission ····· 8
2.3. Radiated Emission ····· 12
2.4. Frequency Tolerance ····· 19
2.5. 20 dB Bandwidth ····· 21
Annex A Test Uncertainty ····· 23
Annex B Testing Laboratory Information ····· 24

Change History		
Version	Date	Reason for change
1.0	2024-04-25	First edition

1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Reliance Communications LLC
Applicant Address:	555 Wireless Blvd. Hauppauge, NY 11788, USA
Manufacturer:	Unimaxcomm
Manufacturer Address:	35F,HBC HuiLong Center Building-II Minzhi Street,Longhua, Shenzhen, P.R. China 518110

1.2. Equipment Under Test (EUT) Description

Product Name:	Orbic Fun Pro 5G	
Sample No.:	4#	
Hardware Version:	V1.0	
Software Version:	R678L5SFP_v1.0.18_LVZ	
Operating Frequency:	13.56MHz	
Modulation Type:	ASK	
Antenna Type:	Loop Antenna	
Accessory Information:	Battery	
	Brand Name:	Orbic
	Model No.:	BTE-5004
	Serial No.:	N/A
	Capacity:	4870mAh
	Rated Voltage:	3.87V
	Charge Limit:	4.45V
	Manufacturer:	Shenzhen Aerospace Electronic Co.,Ltd.

Accessory Information:	AC Adapter	
	Brand Name:	Orbic
	Model No.:	OACH023US1
	Serial No.:	N/A
	Rated Input:	5V⎓3A; 9V⎓2A; 12V⎓1.5A
	Rated Output:	100-240V~50/60Hz, 0.5A
	Manufacturer 1:	WATAI ELECTRONICS PRIVATE LIMITED
	Manufacturer 2:	KANGYIN ELECTRONIC TECHNOLOGY CO.,LTD
	USB Cable	
	Model No.:	HX-YLMK-06
	Manufacturer:	HUIZHOU WASHIN ELECTRONICS CO.,LTD

Note 1: This is a variant report of original report (Report No.: SZ23080316W10, FCC ID: 2ABGH-R678L5S). Based on the similarity between before, only change the product name, model name, software version, FCC ID, appearance and antenna, the others are the same as before. No other changes, all RF parameters remain the same. The changes do not affect the test results.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-15 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS$_{Note1}$	No deviation
2	15.207	Conducted Emission	Jan. 01, 2024 to Feb. 04, 2024	Wang Deyong	PASS$_{Note1}$	No deviation
3	15.209 15.225(a) (b) (c)(d)	Radiated Emission	Jan. 19 to 22, 2024	Gao Jianrou	PASS$_{Note1}$	No deviation
4	15.225(e)	Frequency Tolerance	Dec. 27, 2023	He Yuyang	PASS$_{Note1}$	No deviation
5	15.215(c)	20dB Bandwidth	Feb. 23, 2024	Gao Jianrou	PASS$_{Note1}$	No deviation

Note 1: The test results of these test items in this report refer to the test report (Report No.: SZ23080316W10).

Note 2: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013. The EUT has been tested under continuous operating condition.

Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 4: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.4. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR Part 15C Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Test Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Conducted Emission

2.2.1. Test Requirement

According to FCC section 15.207, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

(a) The lower limit shall apply at the band edges.

(b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.2.2. Test Setup



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides 50Ω/50μH of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

2.2.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A.Test Setup:

Test Mode: EUT+ USB Cable + Adapter +13.56MHz TX

Test voltage: AC 120V/60Hz

The measurement results are obtained as below:

$E\ [dB\mu V] = U_R + L_{Cable\ loss}\ [dB] + A_{Factor}$

U_R: Receiver Reading

A_{Factor}: Voltage division factor of LISN

B.Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.3885	44.44	37.09	58.10	48.10	Line	PASS
2	0.4200	47.25	41.51	57.45	47.45		PASS
3	0.4740	45.27	39.26	56.44	46.44		PASS
4	0.8744	40.06	32.77	56.00	46.00		PASS
5	14.3082	41.79	30.25	60.00	50.00		PASS
6	15.3289	39.76	30.07	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.3840	45.27	34.97	58.19	48.19	Neutral	PASS
2	0.4515	47.79	41.50	56.85	46.85		PASS
3	0.5010	44.41	37.39	56.00	46.00		PASS
4	0.6270	38.85	32.10	56.00	46.00		PASS
5	0.7890	38.41	31.54	56.00	46.00		PASS
6	14.5950	42.70	30.22	60.00	50.00		PASS

2.3. Radiated Emission

2.3.1. Test Requirement

Radiated Emission <30MHz (9 kHz-30MHz, E-field)

According to FCC section 15.225, for <30MHz, Radiated emissions were measured according to ANSIC63.4. The EUT was set to transmit at the highest output power. The EUT was set 30 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10KHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT)

There was no detected Restricted bands and Radiated Spurious emission below 30MHz. The 30m limit was converted to 3m Limit using square factor(x) as it was found by measurements as follows;

3 m Limit(dBuV/m) = 20log(X)+40log(30/3)= 20log(15848)+40log(30/3) = 124dBuV

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency Range (MHz)	Field Strength@30m		Field Strength@3m
	μV/m	dBμV/m	dBμV/m
Below 13.110	30	29.5	69.5
13.110 ~ 13.410	106	40.5	80.5
13.410 ~ 13.553	334	50.5	90.5
13.553 ~13.567	15.848	84	124
13.567 ~ 13.710	334	50.5	90.5
13.710 ~14.010	106	40.5	80.5
Above 14.010	30	29.5	69.5

NOTE: a) Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].

b) In the emission tables above, the tighter limit applies at the band edges.

Radiated Emission >30MHz (30MHz-1GHz, E-field)

According to FCC section 15.205, the field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency Range (MHz)	Field Strength	
	μV/m	dBμV/m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

NOTE: a) Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].

b) In the emission tables above, the tighter limit applies at the band edges.

2.3.2. Test Setup

1) For radiated emissions below 30MHz



2) For radiated emissions from 30MHz to 1GHz



The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating

Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

In the frequency range of 9 kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) was used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector. For measurements frequency range from 0.009MHz to 0.15MHz, the resolution bandwidth is set to 200Hz. For measurements frequency range from 0.15MHz to 30MHz the resolution bandwidth is set to 9kHz.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video bandwidth is set to 3MHz for peak measurements and as applicable for average measurements.

2.3.3. Test Result

A.Radiated Emission <30MHz (9kHz-30MHz, parallel)



No.	Frequency (MHz)	Detector Type	Level at 3m (dBμV/m)	Limit at 3m (dBμV/m)
1	0.0091	Quasi Peak	55.84	108.42
2	0.0626	Quasi Peak	61.31	91.67
3	0.1251	Quasi Peak	54.34	85.66
4	0.25	Quasi Peak	62.07	79.65
5	0.315	Quasi Peak	54.05	77.64
6	13.56	Quasi Peak	68.19	124.0

B.Radiated Emission <30MHz (9kHz-30MHz, perpendicular)



No.	Frequency (MHz)	Detector Type	Level at 3m (dBμV/m)	Limit at 3m (dBμV/m)
1	0.0091	Quasi Peak	55.29	108.42
2	0.0626	Quasi Peak	61.31	91.67
3	0.1251	Quasi Peak	53.84	85.66
4	0.25	Quasi Peak	62.01	79.65
5	0.31	Quasi Peak	53.48	77.78
6	13.56	Quasi Peak	59.50	124.0

C.Radiated Emission >30MHz (30MHz-1GHz)



(30MHz – 1GHz, Test Antenna Horizontal)

No.	Fre. MHz	Pk dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	45.520	30.94	N/A	N/A	N/A	40.00	N/A	H	PASS
2	99.840	33.65	N/A	N/A	N/A	43.50	N/A	H	PASS
3	238.550	33.16	N/A	N/A	N/A	46.00	N/A	H	PASS
4	444.190	35.01	N/A	N/A	N/A	46.00	N/A	H	PASS
5	704.150	37.72	N/A	N/A	N/A	46.00	N/A	H	PASS
6	933.070	40.46	N/A	N/A	N/A	46.00	N/A	H	PASS



(30MHz – 1GHz, Test Antenna Vertical)

No.	Fre. MHz	Pk dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	39.700	31.80	N/A	N/A	N/A	40.00	N/A	V	PASS
2	108.570	33.83	N/A	N/A	N/A	43.50	N/A	V	PASS
3	239.520	32.50	N/A	N/A	N/A	46.00	N/A	V	PASS
4	353.010	34.45	N/A	N/A	N/A	46.00	N/A	V	PASS
5	575.140	36.96	N/A	N/A	N/A	46.00	N/A	V	PASS
6	879.720	40.24	N/A	N/A	N/A	46.00	N/A	V	PASS

2.4. Frequency Tolerance

2.4.1. Test Requirement

According to FCC section 15.225, the devices operating in the 13.553~13.567 MHz shall maintain the carrier frequency within 0.01% of the operating frequency over the temperature variation of -20°C to +50°C using an environmental chamber. The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

2.4.2. Test Setup



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT was measured by transmitter mode continuously.

2.4.3. Test Result

Operating Frequency: 13,560,000 Hz
Deference Voltage: 3.60V
Deviant Limit: ±0.01%

VOLTAGE (%)	Test Conditions		Fre. Dev. (Hz)	Deviation (%)	Verdict
	Power (VDC)	Temperature (°C)			
100	3.60	-20	282	0.00208	PASS
100		-10	273	0.00201	
100		0	256	0.00189	
100		+10	247	0.00182	
100		+20	255	0.00188	
100		+25	260	0.00192	
100		+30	266	0.00196	
100		+40	274	0.00202	
100		+50	279	0.00206	
85	3.06	+20	281	0.00207	
115	4.14	+20	256	0.00189	

2.5. 20 dB Bandwidth

2.5.1. Standard Applicable

According to FCC section 15.215(c), the 20dB bandwidth should be contained within the frequency band designated in the rule section under which the EUT is operated, it was measured with a spectrum analyzer connected the EUT while the EUT is operating in transmission mode.

2.5.2. Test Setup



2.5.3. Test Result

Centre Frequency	Measurement		Limit		Verdict
	20 dB Bandwidth (kHz)	Frequency Range (MHz)	20dB Bandwidth (kHz)	Frequency Range(MHz)	
13.56MHz	1.91	13. 55904 to 13.56095	14	13.553 to 13.567	PASS

1



Annex A Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Radiated Emission:	±3.1dB
Conducted Emission:	±1.8dB
Bandwidth:	±5%
Frequency Tolerance:	±5%

Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.

4. Test Equipments Utilized

4.1 Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2023.06.21	2024.06.20
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2023.07.01	2024.06.30
Test Antenna - Loop	1520-022	FMZB1519	Schwarzbeck	2023.06.26	2024.06.25
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09
DC Power Supply	1709D361010	IV3610	IVYTECH	2023.09.19	2024.09.18
Temperature Chamber	12108015	DTL-003S101	YOMA	2023.09.19	2024.09.18

4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2023.02.09	2024.02.08
				2024.01.25	2025.01.24
LISN	8127449	NSLK 8127	Schwarzbeck	2023.02.21	2024.02.20
				2024.02.02	2025.02.01
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2023.06.27	2024.06.26
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	N/A	N/A

4.3 Test Software Utilized

Model	Software Version	Manufacturer
MORLAB EMCR	Version 1.2	MORLAB
TS+ -[JS32-CE]	Version 2.5.0.0	Tonscend
PMM Emission Suite	Version 2.02	narda

END OF REPORT