

FCC REPORT

Applicant: Shenzhen TongFang Information Technologies CO.,LTD

Address of Applicant: Floor3, Building D, TongFang Information Harbour, LangShan Road, NanShan, Shenzhen, China

Equipment Under Test (EUT)

Product Name: Smart POS

Model No.: B9S2, B9S*, A9S*(* stand for:0-9)

FCC ID: 2ABKZ-GC791903

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247:2013

Date of sample receipt: December 15, 2014

Date of Test: December 16-17, 2014

Date of report issued: December 18, 2014

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.


This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS International Electrical Approvals or testing done by GTS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by GTS International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Version No.	Date	Description
00	December 18, 2014	Original

Prepared By:



Date:

December 18, 2014

Project Engineer

Check By:



Date:

December 18, 2014

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE	6
5.4 DESCRIPTION OF SUPPORT UNITS	6
5.5 TEST FACILITY	7
5.6 TEST LOCATION	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	9
7.1 ANTENNA REQUIREMENT:	9
7.2 CONDUCTED EMISSIONS	10
7.3 BAND EDGES	13
7.3.1 Radiated Emission Method	13
7.4 SPURIOUS EMISSION	18
7.4.1 Radiated Emission Method	18
8 TEST SETUP PHOTO	33
9 EUT CONSTRUCTIONAL DETAILS	34

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	15.207	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Shenzhen TongFang Information Technologies CO.,LTD
Address of Applicant:	Floor3, Building D, TongFang Information Harbour, LangShan Road, NanShan, Shenzhen, China
Manufacturer:	Shenzhen TongFang Information Technologies CO.,LTD
Address of Manufacturer:	Floor3, Building D, TongFang Information Harbour, LangShan Road, NanShan, Shenzhen, China

5.2 General Description of EUT

Product Name:	Smart POS
Model No.:	B9S2, B9S*, A9S*(* stand for:0-9)
Operation Frequency:	802.11b/802.11g/802.11n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
Channel numbers:	802.11b/802.11g /802.11n(HT20): 11 802.11(HT40): 7
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(H20)/802.11n(H40): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	Integral Antenna
Antenna gain:	2.00dBi (declare by Applicant)
Power supply:	Model No.: FEF0500200A1WU Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 2A DC 3.7V Li-ion Battery

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

5.3 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:				
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.				
Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13Mbps

5.4 Description of Support Units

None.

5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS —Registration No.: CNAS L5775**

CNAS has accredited Global United Technology Services Co., Ltd. To ISO/IEC 17025 General Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 28, 2013.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.

5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

Tel: 0755-27798480

Fax: 0755-27798960


6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 28 2014	Mar. 27 2015
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	July 01 2014	June 30 2015
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	July 01 2014	June 30 2015
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	July 01 2014	June 30 2015
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 27 2014	June 26 2015
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 28 2014	Mar. 27 2015
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	Mar. 29 2014	Mar. 28 2015
10	Coaxial Cable	GTS	N/A	GTS211	Mar. 29 2014	Mar. 28 2015
11	Coaxial cable	GTS	N/A	GTS210	Mar. 29 2014	Mar. 28 2015
12	Coaxial Cable	GTS	N/A	GTS212	Mar. 29 2014	Mar. 28 2015
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	July 01 2014	June 30 2015
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	July 01 2014	June 30 2015
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 27 2014	June 26 2015
16	Band filter	Amindeon	82346	GTS219	Mar. 29 2014	Mar. 28 2015


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	July 08 2014	July 07 2015

7 Test results and Measurement Data

7.1 Antenna requirement:


Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
<i>The antenna is Integral antenna, the best case gain of the antenna is 2.0dBi</i> 	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207		
Test Method:	ANSI C63.4:2003		
Test Frequency Range:	150KHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:			
	Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.		
Test Instruments:	Refer to section 6.0 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass		

Measurement data

Line:




Trace: 28

Site : Shielded room
Condition : FCC PART15 CLASSB QP LISN-2013 LINE
Job No. : 2163RF
Test mode : WiFi mode
Test Engineer: Mike

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.154	52.05	0.15	0.12	52.32	65.78	-13.46	QP
2	0.192	48.12	0.14	0.13	48.39	63.93	-15.54	QP
3	0.233	46.30	0.12	0.12	46.54	62.35	-15.81	QP
4	0.269	45.27	0.11	0.11	45.49	61.16	-15.67	QP
5	0.444	41.59	0.12	0.11	41.82	56.98	-15.16	QP
6	0.813	39.55	0.14	0.13	39.82	56.00	-16.18	QP

Neutral:



Trace: 30

Site : Shielded room
Condition : FCC PART15 CLASSB QP LISN-2013 NEUTRAL
Job No. : 2163RF
Test mode : WiFi mode
Test Engineer: Mike


	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.152	43.76	0.07	0.12	43.95	65.91	-21.96	QP
2	0.179	41.37	0.07	0.13	41.57	64.55	-22.98	QP
3	0.312	38.09	0.06	0.10	38.25	59.93	-21.68	QP
4	0.454	39.45	0.06	0.11	39.62	56.80	-17.18	QP
5	0.654	37.54	0.07	0.13	37.74	56.00	-18.26	QP
6	1.636	32.89	0.09	0.14	33.12	56.00	-22.88	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Band edges

7.3.1 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.4: 2003				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		RMS	1MHz	3MHz	Average
Limit:	Frequency		Limit (dBuV/m @3m)		Value
	Above 1GHz		54.00		Average
			74.00		Peak
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.3 for details				
Test results:	Pass				

Measurement data:

Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	47.12	27.59	5.38	30.18	49.91	74.00	-24.09	Horizontal
2400.00	54.62	27.58	5.39	30.18	57.41	74.00	-16.59	Horizontal
2390.00	48.49	27.59	5.38	30.18	51.28	74.00	-22.72	Vertical
2400.00	55.19	27.58	5.39	30.18	57.98	74.00	-16.02	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	35.19	27.59	5.38	30.18	37.98	54.00	-16.02	Horizontal
2400.00	42.99	27.58	5.39	30.18	45.78	54.00	-8.22	Horizontal
2390.00	36.64	27.59	5.38	30.18	39.43	54.00	-14.57	Vertical
2400.00	43.77	27.58	5.39	30.18	46.56	54.00	-7.44	Vertical

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	45.84	27.53	5.47	29.93	48.91	74.00	-25.09	Horizontal
2500.00	43.11	27.55	5.49	29.93	46.22	74.00	-27.78	Horizontal
2483.50	47.17	27.53	5.47	29.93	50.24	74.00	-23.76	Vertical
2500.00	44.77	27.55	5.49	29.93	47.88	74.00	-26.12	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	34.87	27.53	5.47	29.93	37.94	54.00	-16.06	Horizontal
2500.00	31.83	27.55	5.49	29.93	34.94	54.00	-19.06	Horizontal
2483.50	36.41	27.53	5.47	29.93	39.48	54.00	-14.52	Vertical
2500.00	33.54	27.55	5.49	29.93	36.65	54.00	-17.35	Vertical

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	48.24	27.59	5.38	30.18	51.03	74.00	-22.97	Horizontal
2400.00	56.10	27.58	5.39	30.18	58.89	74.00	-15.11	Horizontal
2390.00	49.68	27.59	5.38	30.18	52.47	74.00	-21.53	Vertical
2400.00	56.98	27.58	5.39	30.18	59.77	74.00	-14.23	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	35.98	27.59	5.38	30.18	38.77	54.00	-15.23	Horizontal
2400.00	43.90	27.58	5.39	30.18	46.69	54.00	-7.31	Horizontal
2390.00	37.53	27.59	5.38	30.18	40.32	54.00	-13.68	Vertical
2400.00	44.77	27.58	5.39	30.18	47.56	54.00	-6.44	Vertical

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	47.43	27.53	5.47	29.93	50.50	74.00	-23.50	Horizontal
2500.00	44.35	27.55	5.49	29.93	47.46	74.00	-26.54	Horizontal
2483.50	48.99	27.53	5.47	29.93	52.06	74.00	-21.94	Vertical
2500.00	46.21	27.55	5.49	29.93	49.32	74.00	-24.68	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.83	27.53	5.47	29.93	38.90	54.00	-15.10	Horizontal
2500.00	32.58	27.55	5.49	29.93	35.69	54.00	-18.31	Horizontal
2483.50	37.47	27.53	5.47	29.93	40.54	54.00	-13.46	Vertical
2500.00	34.33	27.55	5.49	29.93	37.44	54.00	-16.56	Vertical

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	48.14	27.59	5.38	30.18	50.93	74.00	-23.07	Horizontal
2400.00	55.98	27.58	5.39	30.18	58.77	74.00	-15.23	Horizontal
2390.00	49.58	27.59	5.38	30.18	52.37	74.00	-21.63	Vertical
2400.00	56.83	27.58	5.39	30.18	59.62	74.00	-14.38	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	35.91	27.59	5.38	30.18	38.70	54.00	-15.30	Horizontal
2400.00	43.83	27.58	5.39	30.18	46.62	54.00	-7.38	Horizontal
2390.00	37.45	27.59	5.38	30.18	40.24	54.00	-13.76	Vertical
2400.00	44.68	27.58	5.39	30.18	47.47	54.00	-6.53	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	47.29	27.53	5.47	29.93	50.36	74.00	-23.64	Horizontal
2500.00	44.24	27.55	5.49	29.93	47.35	74.00	-26.65	Horizontal
2483.50	48.84	27.53	5.47	29.93	51.91	74.00	-22.09	Vertical
2500.00	46.09	27.55	5.49	29.93	49.20	74.00	-24.80	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.75	27.53	5.47	29.93	38.82	54.00	-15.18	Horizontal
2500.00	32.52	27.55	5.49	29.93	35.63	54.00	-18.37	Horizontal
2483.50	37.38	27.53	5.47	29.93	40.45	54.00	-13.55	Vertical
2500.00	34.26	27.55	5.49	29.93	37.37	54.00	-16.63	Vertical

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	48.25	27.59	5.38	30.18	51.04	74.00	-22.96	Horizontal
2400.00	56.13	27.58	5.39	30.18	58.92	74.00	-15.08	Horizontal
2390.00	49.70	27.59	5.38	30.18	52.49	74.00	-21.51	Vertical
2400.00	57.01	27.58	5.39	30.18	59.80	74.00	-14.20	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	35.99	27.59	5.38	30.18	38.78	54.00	-15.22	Horizontal
2400.00	43.92	27.58	5.39	30.18	46.71	54.00	-7.29	Horizontal
2390.00	37.54	27.59	5.38	30.18	40.33	54.00	-13.67	Vertical
2400.00	44.78	27.58	5.39	30.18	47.57	54.00	-6.43	Vertical

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	47.45	27.53	5.47	29.93	50.52	74.00	-23.48	Horizontal
2500.00	44.37	27.55	5.49	29.93	47.48	74.00	-26.52	Horizontal
2483.50	49.02	27.53	5.47	29.93	52.09	74.00	-21.91	Vertical
2500.00	46.24	27.55	5.49	29.93	49.35	74.00	-24.65	Vertical

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.84	27.53	5.47	29.93	38.91	54.00	-15.09	Horizontal
2500.00	32.59	27.55	5.49	29.93	35.70	54.00	-18.30	Horizontal
2483.50	37.49	27.53	5.47	29.93	40.56	54.00	-13.44	Vertical
2500.00	34.34	27.55	5.49	29.93	37.45	54.00	-16.55	Vertical


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

7.4 Spurious Emission

7.4.1 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.4: 2003				
Test Frequency Range:	30MHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		RMS	1MHz	3MHz	Average
Limit:	Frequency		Limit (dBuV/m @3m)		Value
	30MHz-88MHz		40.00		Quasi-peak
	88MHz-216MHz		43.50		Quasi-peak
	216MHz-960MHz		46.00		Quasi-peak
	960MHz-1GHz		54.00		Quasi-peak
	Above 1GHz		54.00		Average
			74.00		Peak
Test setup:	Below 1GHz				
					
Test setup:	Above 1GHz				

	
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Remark:

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis which it is worse case.

Measurement Data

■ Below 1GHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
34.76	37.31	14.30	0.61	20.50	31.72	40.00	-8.28	Vertical
60.49	37.10	14.56	0.86	20.50	32.02	40.00	-7.98	Vertical
121.12	35.19	12.29	1.37	20.78	28.07	43.50	-15.43	Vertical
408.95	40.55	17.26	2.90	21.00	39.71	46.00	-6.29	Vertical
455.91	42.05	17.58	3.11	20.93	41.81	46.00	-4.19	Vertical
625.08	31.56	20.54	3.82	20.71	35.21	46.00	-10.79	Vertical
31.40	34.66	14.32	0.57	20.50	29.05	40.00	-10.95	Horizontal
47.99	30.36	15.36	0.75	20.50	25.97	40.00	-14.03	Horizontal
97.80	31.13	15.03	1.17	20.50	26.83	43.50	-16.67	Horizontal
364.26	35.38	16.46	2.69	21.08	33.45	46.00	-12.55	Horizontal
432.55	40.35	17.53	3.01	20.96	39.93	46.00	-6.07	Horizontal
625.08	32.69	20.54	3.82	20.71	36.34	46.00	-9.66	Horizontal

■ Above 1GHz

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	33.28	31.79	8.62	32.10	41.59	74.00	-32.41	Vertical
7236.00	27.71	36.19	11.68	31.97	43.61	74.00	-30.39	Vertical
9648.00	28.31	38.07	14.16	31.56	48.98	74.00	-25.02	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	32.61	31.79	8.62	32.10	40.92	74.00	-33.08	Horizontal
7236.00	27.52	36.19	11.68	31.97	43.42	74.00	-30.58	Horizontal
9648.00	27.86	38.07	14.16	31.56	48.53	74.00	-25.47	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	23.11	31.79	8.62	32.10	31.42	54.00	-22.58	Vertical
7236.00	17.24	36.19	11.68	31.97	33.14	54.00	-20.86	Vertical
9648.00	17.46	38.07	14.16	31.56	38.13	54.00	-15.87	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	22.41	31.79	8.62	32.10	30.72	54.00	-23.28	Horizontal
7236.00	16.81	36.19	11.68	31.97	32.71	54.00	-21.29	Horizontal
9648.00	16.49	38.07	14.16	31.56	37.16	54.00	-16.84	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	33.21	31.85	8.66	32.12	41.60	74.00	-32.40	Vertical
7311.00	28.57	36.37	11.71	31.91	44.74	74.00	-29.26	Vertical
9748.00	28.22	38.27	14.25	31.56	49.18	74.00	-24.82	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	33.87	31.85	8.66	32.12	42.26	74.00	-31.74	Horizontal
7311.00	27.30	36.37	11.71	31.91	43.47	74.00	-30.53	Horizontal
9748.00	28.15	38.27	14.25	31.56	49.11	74.00	-24.89	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	24.15	31.85	8.66	32.12	32.54	54.00	-21.46	Vertical
7311.00	16.91	36.37	11.71	31.91	33.08	54.00	-20.92	Vertical
9748.00	17.49	38.27	14.25	31.56	38.45	54.00	-15.55	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	24.04	31.85	8.66	32.12	32.43	54.00	-21.57	Horizontal
7311.00	16.41	36.37	11.71	31.91	32.58	54.00	-21.42	Horizontal
9748.00	17.88	38.27	14.25	31.56	38.84	54.00	-15.16	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	37.91	31.90	8.70	32.15	46.36	74.00	-27.64	Vertical
7386.00	28.72	36.49	11.76	31.83	45.14	74.00	-28.86	Vertical
9848.00	31.14	38.62	14.31	31.77	52.30	74.00	-21.70	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	37.52	31.90	8.70	32.15	45.97	74.00	-28.03	Horizontal
7386.00	27.78	36.49	11.76	31.83	44.20	74.00	-29.80	Horizontal
9848.00	27.38	38.62	14.31	31.77	48.54	74.00	-25.46	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	28.98	31.90	8.70	32.15	37.43	54.00	-16.57	Vertical
7386.00	18.68	36.49	11.76	31.83	35.10	54.00	-18.90	Vertical
9848.00	19.68	38.62	14.31	31.77	40.84	54.00	-13.16	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	27.99	31.90	8.70	32.15	36.44	54.00	-17.56	Horizontal
7386.00	17.20	36.49	11.76	31.83	33.62	54.00	-20.38	Horizontal
9848.00	16.67	38.62	14.31	31.77	37.83	54.00	-16.17	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	32.47	31.79	8.62	32.10	40.78	74.00	-33.22	Vertical
7236.00	27.20	36.19	11.68	31.97	43.10	74.00	-30.90	Vertical
9648.00	27.94	38.07	14.16	31.56	48.61	74.00	-25.39	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	31.93	31.79	8.62	32.10	40.24	74.00	-33.76	Horizontal
7236.00	27.07	36.19	11.68	31.97	42.97	74.00	-31.03	Horizontal
9648.00	27.52	38.07	14.16	31.56	48.19	74.00	-25.81	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	22.36	31.79	8.62	32.10	30.67	54.00	-23.33	Vertical
7236.00	16.75	36.19	11.68	31.97	32.65	54.00	-21.35	Vertical
9648.00	17.11	38.07	14.16	31.56	37.78	54.00	-16.22	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	21.77	31.79	8.62	32.10	30.08	54.00	-23.92	Horizontal
7236.00	16.38	36.19	11.68	31.97	32.28	54.00	-21.72	Horizontal
9648.00	16.16	38.07	14.16	31.56	36.83	54.00	-17.17	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	32.54	31.85	8.66	32.12	40.93	74.00	-33.07	Vertical
7311.00	28.15	36.37	11.71	31.91	44.32	74.00	-29.68	Vertical
9748.00	27.92	38.27	14.25	31.56	48.88	74.00	-25.12	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	33.30	31.85	8.66	32.12	41.69	74.00	-32.31	Horizontal
7311.00	26.93	36.37	11.71	31.91	43.10	74.00	-30.90	Horizontal
9748.00	27.87	38.27	14.25	31.56	48.83	74.00	-25.17	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	23.54	31.85	8.66	32.12	31.93	54.00	-22.07	Vertical
7311.00	16.50	36.37	11.71	31.91	32.67	54.00	-21.33	Vertical
9748.00	17.20	38.27	14.25	31.56	38.16	54.00	-15.84	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	23.51	31.85	8.66	32.12	31.90	54.00	-22.10	Horizontal
7311.00	16.05	36.37	11.71	31.91	32.22	54.00	-21.78	Horizontal
9748.00	17.61	38.27	14.25	31.56	38.57	54.00	-15.43	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	36.76	31.90	8.70	32.15	45.21	74.00	-28.79	Vertical
7386.00	27.99	36.49	11.76	31.83	44.41	74.00	-29.59	Vertical
9848.00	30.62	38.62	14.31	31.77	51.78	74.00	-22.22	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	36.55	31.90	8.70	32.15	45.00	74.00	-29.00	Horizontal
7386.00	27.14	36.49	11.76	31.83	43.56	74.00	-30.44	Horizontal
9848.00	26.90	38.62	14.31	31.77	48.06	74.00	-25.94	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	27.92	31.90	8.70	32.15	36.37	54.00	-17.63	Vertical
7386.00	17.98	36.49	11.76	31.83	34.40	54.00	-19.60	Vertical
9848.00	19.18	38.62	14.31	31.77	40.34	54.00	-13.66	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	27.08	31.90	8.70	32.15	35.53	54.00	-18.47	Horizontal
7386.00	16.58	36.49	11.76	31.83	33.00	54.00	-21.00	Horizontal
9848.00	16.21	38.62	14.31	31.77	37.37	54.00	-16.63	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	32.20	31.79	8.62	32.10	40.51	74.00	-33.49	Vertical
7236.00	27.03	36.19	11.68	31.97	42.93	74.00	-31.07	Vertical
9648.00	27.82	38.07	14.16	31.56	48.49	74.00	-25.51	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	31.70	31.79	8.62	32.10	40.01	74.00	-33.99	Horizontal
7236.00	26.92	36.19	11.68	31.97	42.82	74.00	-31.18	Horizontal
9648.00	27.41	38.07	14.16	31.56	48.08	74.00	-25.92	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	22.11	31.79	8.62	32.10	30.42	54.00	-23.58	Vertical
7236.00	16.59	36.19	11.68	31.97	32.49	54.00	-21.51	Vertical
9648.00	16.99	38.07	14.16	31.56	37.66	54.00	-16.34	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	21.55	31.79	8.62	32.10	29.86	54.00	-24.14	Horizontal
7236.00	16.23	36.19	11.68	31.97	32.13	54.00	-21.87	Horizontal
9648.00	16.05	38.07	14.16	31.56	36.72	54.00	-17.28	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	32.32	31.85	8.66	32.12	40.71	74.00	-33.29	Vertical
7311.00	28.00	36.37	11.71	31.91	44.17	74.00	-29.83	Vertical
9748.00	27.81	38.27	14.25	31.56	48.77	74.00	-25.23	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	33.11	31.85	8.66	32.12	41.50	74.00	-32.50	Horizontal
7311.00	26.81	36.37	11.71	31.91	42.98	74.00	-31.02	Horizontal
9748.00	27.77	38.27	14.25	31.56	48.73	74.00	-25.27	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	23.33	31.85	8.66	32.12	31.72	54.00	-22.28	Vertical
7311.00	16.37	36.37	11.71	31.91	32.54	54.00	-21.46	Vertical
9748.00	17.10	38.27	14.25	31.56	38.06	54.00	-15.94	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	23.33	31.85	8.66	32.12	31.72	54.00	-22.28	Horizontal
7311.00	15.93	36.37	11.71	31.91	32.10	54.00	-21.90	Horizontal
9748.00	17.52	38.27	14.25	31.56	38.48	54.00	-15.52	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	36.38	31.90	8.70	32.15	44.83	74.00	-29.17	Vertical
7386.00	27.75	36.49	11.76	31.83	44.17	74.00	-29.83	Vertical
9848.00	30.45	38.62	14.31	31.77	51.61	74.00	-22.39	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	36.23	31.90	8.70	32.15	44.68	74.00	-29.32	Horizontal
7386.00	26.93	36.49	11.76	31.83	43.35	74.00	-30.65	Horizontal
9848.00	26.74	38.62	14.31	31.77	47.90	74.00	-26.10	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	27.57	31.90	8.70	32.15	36.02	54.00	-17.98	Vertical
7386.00	17.74	36.49	11.76	31.83	34.16	54.00	-19.84	Vertical
9848.00	19.01	38.62	14.31	31.77	40.17	54.00	-13.83	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	26.77	31.90	8.70	32.15	35.22	54.00	-18.78	Horizontal
7386.00	16.38	36.49	11.76	31.83	32.80	54.00	-21.20	Horizontal
9848.00	16.05	38.62	14.31	31.77	37.21	54.00	-16.79	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

- 1 Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2 “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	31.25	31.81	8.63	32.11	39.58	74.00	-34.42	Vertical
7266.00	26.43	36.28	11.69	31.94	42.46	74.00	-31.54	Vertical
9688.00	27.39	38.13	14.21	31.52	48.21	74.00	-25.79	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4844.00	30.90	31.81	8.63	32.11	39.23	74.00	-34.77	Horizontal
7266.00	26.40	36.28	11.69	31.94	42.43	74.00	-31.57	Horizontal
9688.00	27.02	38.13	14.21	31.52	47.84	74.00	-26.16	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	21.24	31.81	8.63	32.11	29.57	54.00	-24.43	Vertical
7266.00	16.01	36.28	11.69	31.94	32.04	54.00	-21.96	Vertical
9688.00	16.58	38.13	14.21	31.52	37.40	54.00	-16.60	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4844.00	20.80	31.81	8.63	32.11	29.13	54.00	-24.87	Horizontal
7266.00	15.72	36.28	11.69	31.94	31.75	54.00	-22.25	Horizontal
9688.00	15.67	38.13	14.21	31.52	36.49	54.00	-17.51	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	31.53	31.85	8.66	32.12	39.92	74.00	-34.08	Vertical
7311.00	27.51	36.37	11.71	31.91	43.68	74.00	-30.32	Vertical
9748.00	27.46	38.27	14.25	31.56	48.42	74.00	-25.58	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	32.45	31.85	8.66	32.12	40.84	74.00	-33.16	Horizontal
7311.00	26.37	36.37	11.71	31.91	42.54	74.00	-31.46	Horizontal
9748.00	27.45	38.27	14.25	31.56	48.41	74.00	-25.59	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	22.61	31.85	8.66	32.12	31.00	54.00	-23.00	Vertical
7311.00	15.89	36.37	11.71	31.91	32.06	54.00	-21.94	Vertical
9748.00	16.76	38.27	14.25	31.56	37.72	54.00	-16.28	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	22.71	31.85	8.66	32.12	31.10	54.00	-22.90	Horizontal
7311.00	15.51	36.37	11.71	31.91	31.68	54.00	-22.32	Horizontal
9748.00	17.21	38.27	14.25	31.56	38.17	54.00	-15.83	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	35.03	31.88	8.68	32.13	43.46	74.00	-30.54	Vertical
7356.00	26.90	36.45	11.75	31.86	43.24	74.00	-30.76	Vertical
9808.00	29.84	38.43	14.29	31.68	50.88	74.00	-23.12	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4904.00	35.09	31.88	8.68	32.13	43.52	74.00	-30.48	Horizontal
7356.00	26.18	36.45	11.75	31.86	42.52	74.00	-31.48	Horizontal
9808.00	26.17	38.43	14.29	31.68	47.21	74.00	-26.79	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:



Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	26.32	31.88	8.68	32.13	34.75	54.00	-19.25	Vertical
7356.00	16.92	36.45	11.75	31.86	33.26	54.00	-20.74	Vertical
9808.00	18.43	38.43	14.29	31.68	39.47	54.00	-14.53	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4904.00	25.71	31.88	8.68	32.13	34.14	54.00	-19.86	Horizontal
7356.00	15.65	36.45	11.75	31.86	31.99	54.00	-22.01	Horizontal
9808.00	15.51	38.43	14.29	31.68	36.55	54.00	-17.45	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:


- 1 Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2 “*”, means this data is the too weak instrument of signal is unable to test.


8 Test Setup Photo



Radiated Emission




9 EUT Constructional Details




































-----end-----