

FCC PART 22H, PART 24E
MEASUREMENT AND TEST REPORT

For

Posh Mobile Limited

1011A, 10/F., Harbour Centre Tower 1, No. 1 Hok Cheung St., Hung Hom, Kowloon, Hong Kong

FCC ID: 2ABN6X511C

Report Type: Original Report	Product Type: Kick
Test Engineer: Costa Dong	<i>Costa Dong</i>
Report Number: RDG160721004-00C	
Report Date: 2016-08-16	
Reviewed By: Jerry Zhang EMC Manager	<i>Jerry Zhang</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
JUSTIFICATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
CONFIGURATION OF TEST SETUP	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
TEST RESULT	9
FCC §2.1047 - MODULATION CHARACTERISTIC	10
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER.....	11
APPLICABLE STANDARD	11
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS.....	15
TEST DATA	15
FCC §2.1049, §22.917, §22.905 & §24.238- OCCUPIED BANDWIDTH	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST DATA	23
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST EQUIPMENT LIST AND DETAILS.....	29
TEST DATA	29
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST DATA	35
FCC §22.917(A) & §24.238(A) - BAND EDGES.....	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS.....	38
TEST DATA	38

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY.....47
 APPLICABLE STANDARD47
 TEST PROCEDURE47
 TEST EQUIPMENT LIST AND DETAILS.....48
 TEST DATA48

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Posh Mobile Limited*'s product, model number: *X511 (FCC ID: 2ABN6X511C)* (the "EUT") in this report was a *Kick*, which was measured approximately: 14.5 cm (L) x 7.2 cm (W) x 0.8cm (H), rated input voltage: DC3.7V rechargeable Li-ion battery or DC5V charging from adapter.

Adapter information:

PART NO.: U02-5V/1A

MODEL: SC/5WM500100-US

INPUT: 100-240V ~ 50/60Hz 0.4A

OUTPUT: DC 5V, 1000mA

Note: The series product, model X511 and X511C are electrically identical, the difference them is the model name, we selected X511 for fully testing, the details was explained in the attached declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 160721004 (Assigned by BACL, Dongguan). The EUT was received on 2016-07-22.

Objective

This report is prepared on behalf of *Posh Mobile Limited* in accordance with: Part 2-Subpart J, Part 22-Subpart H, Part 24-Subpart E of the Federal Communications Commission's rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, spurious emissions at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ABN6X511C

FCC Part 15C DSS submissions with FCC ID: 2ABN6X511C

FCC Part 15C DTS submissions with FCC ID: 2ABN6X511C

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D-2010.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp.(Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FINAL

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D-2010.

The test items were performed with the EUT operating at testing mode.


Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
R&S	Universal Radio Communication Tester	CMU200	109038
R&S	Universal Radio Communication Tester	CMW500	T-03-EM342
N/A	ANTENNA	N/A	N/A

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310, §2.1093	RF Exposure	Compliance
§2.1046; § 22.913 (a); § 24.232 (c);	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	Occupied Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a)	Spurious Radiation Emissions	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

FCC §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliant, please refer to the SAR report: RDG160721004-20.

FINAL

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FINAL

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

Test Procedure

GSM/GPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM + GPRS or GSM + EGSM

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting

> Slot configuration > Uplink/Gamma

> 33 dBm for GPRS 850

> 30 dBm for GPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desired test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

Slot Config > Unchanged (if already set under MS signal)

TCH > choose desired test channel

Hopping > Off

Main Timeslot > 3

Network Coding Scheme > CS4 (GPRS)

Bit Stream > 2E9-1 PSR Bit Stream

AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection Press Signal on to turn on the signal and change settings

WCDMA-Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c / β_d	8/15

WCDMA HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_d (SF)	64			
	β_c / β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs} = \beta_{hs} / \beta_c$	30/15			

WCDMA HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA A General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs}=\beta_{hs}/\beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCI	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18		E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27

HSPA+

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

Sub-test	β_c (Note 3)	β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0).

Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default.

Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.

DC-HSDPA

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		

Radiated method:

ANSI/TIA 603-D section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
R&S	Spectrum Analyzer	FSEM	DE23437	2015-11-23	2016-11-22
ETS LINDGREN	Horn Antenna	3115	000 527 35	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
Giga	Signal Generator	E8247C	MY43321350	2014-10-16	2016-10-15
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
TDK RF	Horn Antenna	HRN-0118	130 084	2015-09-06	2018-09-06
N/A	Coaxial Cable	14m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	8m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA10-5RN	OE01203239	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-01	N/A	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-02	N/A	2016-05-06	2017-05-06
N/A	Two-way Splitter	ODP-1-6-2S	OE0120142	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	30.5°C
Relative Humidity:	50 %
ATM Pressure:	100 kPa

The testing was performed by Costa Dong on 2016-08-14.

Conducted Power**Cellular Band (Part 22H) & PCS Band (Part 24E)**

Band	Channel No.	Peak Output Power (dBm)				
		GSM	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot
Cellular	128	32.64	32.63	32.15	30.75	29.72
	190	32.66	32.57	31.98	30.58	29.37
	251	32.74	32.79	32.15	30.52	29.27
PCS	512	29.72	29.55	28.74	26.89	25.73
	661	29.66	29.76	28.86	26.98	25.82
	810	29.77	29.83	28.97	27.27	26.13

WCDMA Band II


Mode	3GPP Sub Test	Average Output Power (dBm)					
		Low Channel (Ave. Power)	Low Channel (PAR)	Middle Channel (Ave. Power)	Middle Channel (PAR)	High Channel (Ave. Power)	High Channel (PAR)
Rel 99 (QPSK)	1	22.61	2.36	22.64	1.96	22.78	2.28
HSDPA (QPSK)	1	21.56	2.26	21.64	1.99	21.79	2.26
	2	21.59	2.28	21.64	1.98	21.73	2.24
	3	21.55	2.26	21.63	1.98	21.80	2.31
	4	21.52	2.28	21.60	2.01	21.76	2.33
HSUPA (QPSK)	1	21.59	2.27	21.60	1.95	21.81	2.27
	2	21.55	2.27	21.62	1.99	21.77	2.28
	3	21.55	2.24	21.67	1.94	21.78	2.28
	4	21.57	2.26	21.61	2.01	21.78	2.32
	5	21.51	2.27	21.59	1.94	21.77	2.25
DC-HSDPA (QPSK)	1	21.56	2.28	21.62	1.96	21.80	2.27
	2	21.55	2.28	21.60	1.93	21.75	2.29
	3	21.50	2.27	21.56	1.97	21.76	2.25
	4	21.55	2.24	21.62	1.93	21.73	2.29
HSPA+ (16QAM)	1	21.53	2.26	21.60	1.96	21.76	2.30

WCDMA Band V


Mode	3GPP Sub Test	Average Output Power (dBm)					
		Low Channel (Ave. Power)	Low Channel (PAR)	Middle Channel (Ave. Power)	Middle Channel (PAR)	High Channel (Ave. Power)	High Channel (PAR)
Rel 99 (QPSK)	1	22.98	2.88	22.75	2.72	22.75	2.92
HSDPA (QPSK)	1	21.88	2.80	21.69	2.70	21.72	2.90
	2	21.84	2.76	21.66	2.76	21.71	2.96
	3	21.87	2.76	21.64	2.74	21.67	2.96
	4	21.82	2.80	21.62	2.74	21.63	2.89
HSUPA (QPSK)	1	21.88	2.76	21.66	2.76	21.71	2.88
	2	21.87	2.78	21.63	2.69	21.68	2.95
	3	21.81	2.81	21.65	2.70	21.70	2.92
	4	21.85	2.79	21.63	2.76	21.67	2.93
DC-HSDPA (QPSK)	5	21.83	2.80	21.63	2.77	21.68	2.95
	1	21.87	2.80	21.68	2.72	21.70	2.91
	2	21.84	2.80	21.63	2.73	21.64	2.90
	3	21.85	2.77	21.59	2.75	21.63	2.87
	4	21.82	2.79	21.57	2.77	21.64	2.87
HSPA+ (16QAM)	1	21.81	2.80	21.64	2.72	21.66	2.94

Note: peak-to-average ratio (PAR) <13 dB.

Peak-to-average ratio (PAR)


WCDMA Band II**Low Channel**

Date: 14.AUG.2016 20:51:38

Middle Channel

Date: 14.AUG.2016 20:51:00


High Channel



Date: 14.AUG.2016 20:51:20


WCDMA Band V

Low Channel




Date: 14.AUG.2016 20:49:22

Middle Channel



Date: 14.AUG.2016 20:49:38

High Channel



Date: 14.AUG.2016 20:49:49

ERP & EIRP

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 850 Middle Channel								
836.600	H	107.31	32.4	0.0	1	31.4	38.45	7.1
836.600	V	100.66	28.9	0.0	1	27.9	38.45	10.6
WCDMA Band V Middle Channel								
836.600	H	96.39	21.5	0.0	1	20.5	38.45	17.95
836.600	V	88.69	16.9	0.0	1	15.9	38.45	22.55
PCS 1900 Middle Channel								
1880.000	H	89.95	18.4	11.7	1.4	28.7	33.0	4.3
1880.000	V	81.88	10.4	11.7	1.4	20.7	33.0	12.3
WCDMA Band II Middle Channel								
1880.000	H	82.37	10.8	11.7	1.4	21.1	33.0	11.9
1880.000	V	73.92	2.5	11.7	1.4	12.8	33.0	20.2

FCC §2.1049, §22.917, §22.905 & §24.238- OCCUPIED BANDWIDTH


Applicable Standard

FCC §2.1049, §22.917, §22.905, §24.238

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE23437	2015-11-23	2016-11-22
R&S	Spectrum Analyzer	FSEM	831259/019	2016-07-28	2017-07-27
R&S	Universal Radio Communication Tester	CMU200	109 038	2016-07-28	2017-07-27
R&S	Wideband Radio Communication Tester	CMW500	1201.002K50-146520-wh	2015-12-19	2016-12-19
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA10-5RN	OE01203239	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-01	N/A	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-02	N/A	2016-05-06	2017-05-06
N/A	Two-way Splitter	ODP-1-6-2S	OE0120142	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	30.5 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa


The testing was performed by Costa Dong on 2016-08-14.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots.



Band	Channel No.	Mode	99% Occupied Bandwidth (MHz)	26 dB Occupied Bandwidth (MHz)
Cellular	190	GSM	0.248	0.313
PCS	661	PCS	0.246	0.315
WCDMA Band II	9400	Rel 99	4.228	4.870
	9400	HSDPA	4.228	4.749
	9400	HSUPA	4.228	4.830
WCDMA Band V	4175	Rel 99	4.168	4.729
	4175	HSDPA	4.168	4.709
	4175	HSUPA	4.168	4.729

GMSK 850 Cellular Band



GMSK PCS Band



REL99 Band II**HSDPA Band II**

[illegible]

Ref Lvl 30 dBm

Delta 1 [T1] -0.11 dB

4.72945892 MHz

RBW 100 kHz

VBW 300 kHz

SWT 5 ms

Unit dBm

14 dB Offset

D1 17.59 dBm

D2 -8.31 dBm

1MAX

1MA


Center 836.6 MHz

1 MHz

Span 10 MHz


Date: 14.AUG.2016 19:45:47

HSDPA Band V



Date: 14.AUG.2016 19:42:13

HSUPA Band V



Date: 14.AUG.2016 19:43:06

FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) , §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
R&S	Spectrum Analyzer	FSEM	831259/019	2016-07-28	2017-07-27
R&S	Universal Radio Communication Tester	CMU200	109 038	2016-07-28	2017-07-27
R&S	Wideband Radio Communication Tester	CMW500	1201.002K50-146520-wh	2015-12-19	2016-12-19
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA10-5RN	OE01203239	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-01	N/A	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-02	N/A	2016-05-06	2017-05-06
N/A	Two-way Splitter	ODP-1-6-2S	OE0120142	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA10-5RN	OE01203239	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-01	N/A	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-02	N/A	2016-05-06	2017-05-06
N/A	Two-way Splitter	ODP-1-6-2S	OE0120142	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).



Test Data**Environmental Conditions**

Temperature:	30.5 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa


The testing was performed by Costa Dong on 2016-08-14.

Please refer to the following plots.


GSM850_Middle Channel



PCS 1900_ Middle Channel



Fundamental



Ref Lvl 30 dBm

Marker 1 [T1] -43.43 dBm 1.00000000 GHz

RBW 100 kHz VBW 300 kHz RF Att 30 dBm

SWT 245 ms Unit dBm


14 dB Offset

1MAX


-D1 -13 dBm

Start 30 MHz 97 MHz/ Stop 1 GHz

Date: 14.AUG.2016 19:14:50



	Marker 1 [T1]	RBW	100 kHz	RF Att	30 dB
	Ref Lvl	-42.46 dBm	VBW	300 kHz	
	30 dBm	953.34669339 MHz	SWT	245 ms	Unit



FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917, § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg(\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \text{ Log}_{10}(\text{power out in Watts})$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2016-08-03	2017-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
R&S	Spectrum Analyzer	FSEM	DE23437	2015-11-23	2016-11-22
ETS LINDGREN	Horn Antenna	3115	000 527 35	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
HP	Signal Generator	E4422B	MY41000355	2015-11-23	2016-11-22
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
TDK RF	Horn Antenna	HRN-0118	130 084	2015-09-06	2018-09-06
N/A	Coaxial Cable	14m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	8m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	2m	N/A	2016-05-06	2017-05-06
Mini Circuit	High Pass Filter	VHF-3100+	31251	2016-05-06	2017-05-06
Mini Circuit	High Pass Filte	VHF-1200+	N/A	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	30.5 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa

The testing was performed by Costa Dong on 2016-08-14.

EUT Operation Mode: Transmitting

Cellular Band

30MHz-10 GHz

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM850, Frequency:836.600 MHz								
1673.200	H	55.78	-45.3	10.6	1.5	-36.2	-13.0	23.2
1673.200	V	54.54	-46.8	10.6	1.5	-37.7	-13.0	24.7
2509.800	H	49.55	-48.5	13.1	2.8	-38.2	-13.0	25.2
2509.800	V	46.55	-50.5	13.1	2.8	-40.2	-13.0	27.2
3346.400	H	46.81	-50.6	13.8	1.7	-38.5	-13.0	25.5
3346.400	V	40.35	-56.8	13.8	1.7	-44.7	-13.0	31.7
134.700	H	36.31	-70.1	0.0	0.3	-70.4	-13.0	57.4
303.500	V	34.58	-70	0.0	0.5	-70.5	-13.0	57.5
WCDMA Band V R99, Frequency:836.600 MHz								
1673.200	H	44.52	-56.6	10.6	1.5	-47.5	-13.0	34.5
1673.200	V	40.13	-61.2	10.6	1.5	-52.1	-13.0	39.1
2509.800	H	33.60	-64.4	13.1	2.8	-54.1	-13.0	41.1
2509.800	V	32.01	-65.1	13.1	2.8	-54.8	-13.0	41.8
134.700	H	36.32	-70	0.0	0.3	-70.3	-13.0	57.3
303.500	V	34.01	-70.5	0.0	0.5	-71.0	-13.0	58.0

PCS Band**30MHz-20GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM1900, Frequency:1880.000 MHz								
3760.000	H	43.68	-50.6	13.8	2.9	-39.7	-13.0	26.7
3760.000	V	42.62	-50.4	13.8	2.9	-39.5	-13.0	26.5
5640.000	H	44.95	-46.7	14.0	2.1	-34.8	-13.0	21.8
5640.000	V	44.61	-47.1	14.0	2.1	-35.2	-13.0	22.2
7520.000	H	45.88	-41.7	13.2	2.9	-31.4	-13.0	18.4
7520.000	V	41.44	-46	13.2	2.9	-35.7	-13.0	22.7
134.700	H	35.88	-70.5	0.0	0.3	-70.8	-13.0	57.8
303.500	V	33.98	-70.6	0.0	0.5	-71.1	-13.0	58.1
WCDMA Band II, R99, Frequency:1880.000 MHz								
3760.000	H	44.81	-49.5	13.8	2.9	-38.6	-13.0	25.6
3760.000	V	40.64	-52.4	13.8	2.9	-41.5	-13.0	28.5
5640.000	H	32.36	-59.3	14.0	2.1	-47.4	-13.0	34.4
5640.000	V	32.17	-59.5	14.0	2.1	-47.6	-13.0	34.6
134.700	H	35.79	-70.6	0.0	0.3	-70.9	-13.0	57.9
303.500	V	34.17	-70.4	0.0	0.5	-70.9	-13.0	57.9

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE23437	2015-11-23	2016-11-22
R&S	Universal Radio Communication Tester	CMU200	109 038	2016-07-28	2017-07-27
R&S	Wideband Radio Communication Tester	CMW500	1201.002K50-146520-wh	2015-12-19	2016-12-19
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA10-5RN	OE01203239	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-01	N/A	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-02	N/A	2016-05-06	2017-05-06
N/A	Two-way Splitter	ODP-1-6-2S	OE0120142	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA10-5RN	OE01203239	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-01	N/A	2016-05-06	2017-05-06
Pasternack	RF Coaxial Cable	RF-02	N/A	2016-05-06	2017-05-06
N/A	Two-way Splitter	ODP-1-6-2S	OE0120142	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	30.5 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa

The testing was performed by Costa Dong on 2016-08-14.


Test Mode: Transmitting

Test Result: Compliant. Please refer to the following plots.


GSM 850, Left Band Edge



GSM 850, Right Band Edge




GSM 1900, Left Band Edge




Date: 14.AUG.2016 20:49:09

GSM 1900, Right Band Edge




Date: 14.AUG.2016 20:49:57


REL99 Band II, Left Band Edge




REL99 Band II, Right Band Edge




HSDPA Band II, Left Band Edge




HSDPA Band II, Right Band Edge



HSUPA Band II, Left Band Edge




HSUPA Band II, Right Band Edge




WCDMA Band V

REL99 Band V, Left Band Edge




Date: 14.AUG.2016 19:50:19

REL99 Band V Right Band Edge




Date: 14.AUG.2016 19:52:01


HSDPA Band V, Left Band Edge




HSDPA Band V, Right Band Edge



HSUPA Band V, Left Band Edge



HSUPA Band V, Right Band Edge



FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY**Applicable Standard**

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile > 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set from 85% to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Dongzhixu	High Temperature Test Chamber	DP1000	201105083-4	2015-09-10	2016-09-09
R&S	Universal Radio Communication Tester	CMU200	109 038	2016-07-28	2017-07-27
R&S	Wideband Radio Communication Tester	CMW500	1201.002K50-146520-wh	2015-12-19	2016-12-19
UNI-T	Multimeter	UT39A	M130199938	2016-04-02	2017-04-02
Pasternack	RF Coaxial Cable	RF-01	/	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	30.5 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa

The testing was performed by Costa Dong on 2016-08-14.

Cellular Band (Part 22H)

GMSK, Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	16	0.019	2.5
-20	3.7	13	0.016	2.5
-10	3.7	9	0.011	2.5
0	3.7	5	0.006	2.5
10	3.7	8	0.010	2.5
20	3.7	10	0.012	2.5
30	3.7	12	0.014	2.5
40	3.7	12	0.014	2.5
50	3.7	8	0.010	2.5
25	3.5	7	0.008	2.5
25	4.2	7	0.008	2.5

PCS Band (Part 24E)

GMSK, Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	17	0.009	2.5
-20	3.7	17	0.009	2.5
-10	3.7	22	0.012	2.5
0	3.7	19	0.010	2.5
10	3.7	18	0.010	2.5
20	3.7	18	0.010	2.5
30	3.7	18	0.010	2.5
40	3.7	15	0.008	2.5
50	3.7	17	0.009	2.5
25	3.5	20	0.011	2.5
25	4.2	23	0.012	2.5

WCDMA Band V: Re199

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	-17	-0.020	2.5
-20	3.7	-11	-0.013	2.5
-10	3.7	-15	-0.018	2.5
0	3.7	-12	-0.014	2.5
10	3.7	-6	-0.007	2.5
20	3.7	-8	-0.010	2.5
30	3.7	-12	-0.014	2.5
40	3.7	-9	-0.011	2.5
50	3.7	-7	-0.008	2.5
25	3.5	-9	-0.011	2.5
25	4.2	-13	-0.016	2.5

WCDMA Band II: Re199

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	-10	-0.005	Pass
-20	3.7	-12	-0.006	Pass
-10	3.7	-12	-0.006	Pass
0	3.7	-7	-0.004	Pass
10	3.7	-11	-0.006	Pass
20	3.7	-10	-0.005	Pass
30	3.7	-15	-0.008	Pass
40	3.7	-12	-0.006	Pass
50	3.7	-9	-0.005	Pass
25	3.5	-10	-0.005	Pass
25	4.2	-12	-0.006	Pass

WCDMA Band V: HSUPA

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	-20	-0.024	2.5
-20	3.7	-16	-0.019	2.5
-10	3.7	-16	-0.019	2.5
0	3.7	-10	-0.012	2.5
10	3.7	-7	-0.008	2.5
20	3.7	-10	-0.012	2.5
30	3.7	-11	-0.013	2.5
40	3.7	-11	-0.013	2.5
50	3.7	-16	-0.019	2.5
25	3.5	-10	-0.012	2.5
25	4.2	-9	-0.011	2.5

WCDMA Band II: HSUPA

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	-8	-0.004	Pass
-20	3.7	-6	-0.003	Pass
-10	3.7	-8	-0.004	Pass
0	3.7	-5	-0.003	Pass
10	3.7	-15	-0.008	Pass
20	3.7	-9	-0.005	Pass
30	3.7	-11	-0.006	Pass
40	3.7	-10	-0.005	Pass
50	3.7	-17	-0.009	Pass
25	3.5	-11	-0.006	Pass
25	4.2	-6	-0.003	Pass

WCDMA Band V: HSDPA

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	-15	-0.018	2.5
-20	3.7	-12	-0.014	2.5
-10	3.7	-13	-0.016	2.5
0	3.7	-12	-0.014	2.5
10	3.7	-12	-0.014	2.5
20	3.7	-7	-0.008	2.5
30	3.7	-7	-0.008	2.5
40	3.7	-9	-0.011	2.5
50	3.7	-13	-0.016	2.5
25	3.5	-8	-0.010	2.5
25	4.2	-7	-0.008	2.5

WCDMA Band II: HSDPA

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	-7	-0.004	Pass
-20	3.7	-9	-0.005	Pass
-10	3.7	-5	-0.003	Pass
0	3.7	-14	-0.007	Pass
10	3.7	-11	-0.006	Pass
20	3.7	-17	-0.009	Pass
30	3.7	-15	-0.008	Pass
40	3.7	-14	-0.007	Pass
50	3.7	-14	-0.007	Pass
25	3.5	-8	-0.004	Pass
25	4.2	-7	-0.004	Pass

Note: The fundamental emissions stay within the authorized bands of operation based on the frequency deviation measured is small.

***** END OF REPORT *****