

FCC RF Test Report


APPLICANT : Nyle Oswind Parry Limited Liability Company
EQUIPMENT : Tablet PC
MODEL NAME : GQY56XZ
FCC ID : 2AB06-0725
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The testing completed on Apr. 25, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Product Feature of Equipment Under Test	5
1.3 Product Specification subjective to this standard	6
1.4 Modification of EUT	6
1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.6 Testing Location	7
1.7 Applicable Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode	9
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration	11
2.4 Measurement Results Explanation Example	11
3 TEST RESULT	12
3.1 Conducted Output Power and ERP/EIRP Measurement	12
3.2 Peak-to-Average Ratio	14
3.3 99% Occupied Bandwidth and 26dB Bandwidth Measurement	28
3.4 Band Edge Measurement	48
3.5 Conducted Spurious Emission Measurement	55
3.6 Field Strength of Spurious Radiation Measurement	71
3.7 Frequency Stability Measurement	79
4 LIST OF MEASURING EQUIPMENT	83
5 UNCERTAINTY OF EVALUATION	84

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG432436-09A	Rev. 01	Initial issue of report	Jul. 29, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.3	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	N/A	PASS	-
3.4	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	$< 43 + 10\log_{10}(P[\text{Watts}])$	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	$< 43 + 10\log_{10}(P[\text{Watts}])$	PASS	-
3.6	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	$< 43 + 10\log_{10}(P[\text{Watts}])$	PASS	Under limit 20.34 dB at 2509.000 MHz
3.7	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

Nyle Oswind Parry Limited Liability Company

7027 Old Madison Pike, Suite 108, Huntsville, Alabama 35806

1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Model Name	GQY56XZ
FCC ID	2ABO6-0725
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE <2.4GHz band> WLAN 11b/g/n HT20 WLAN 11ac VHT20 Bluetooth v4.0 EDR/LE <5GHz band> WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.3 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 31.90 dBm GSM1900 : 29.30 dBm WCDMA Band V : 22.80 dBm WCDMA Band II : 23.20 dBm
Antenna Type	Fixed Internal Antenna
Antenna Gain	GSM850 and Band V: -0.40 dBi GSM1900 and Band II: 1.70dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA:16QAM (Downlink) HSUPA: QPSK (Uplink)

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	0.86	0.0072 ppm	246KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.26	0.0060 ppm	244KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.11	0.0155 ppm	4M18F9W
Part 24	GSM1900 GPRS class 8	GMSK	1.26	0.0160 ppm	244KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.51	0.0048 ppm	246KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.31	0.0021 ppm	4M18F9W

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH02-HY	03CH06-HY

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01
- FCC KDB 412172 D01 Determining ERP and ERIP v01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 8 Link	■ GPRS class 8 Link
	■ EDGE class 8 Link	■ EDGE class 8 Link
GSM 1900	■ GPRS class 8 Link	■ GPRS class 8 Link
	■ EDGE class 8 Link	■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

Note: The maximum power levels are chosen to test as the worst case configuration as follows:

GPRS multi-slot class 8 mode for GMSK modulation,

EDGE multi-slot class 8 mode for 8PSK modulation,

RMC 12.2Kbps mode for WCDMA band V,


RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

Conducted Power Measurement Results:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	31.80	31.80	31.90	29.20	29.20	29.30
GPRS class 10	31.60	31.70	31.80	28.70	28.60	28.90
EGPRS class 8	26.60	26.60	26.70	25.40	25.20	25.30
EGPRS class 10	26.50	26.60	26.60	25.30	25.10	25.20

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
RMC 12.2K	22.80	22.70	22.70	23.20	23.00	22.80
HSDPA Subtest-1	21.20	21.30	21.30	21.70	21.60	21.30
HSDPA Subtest-2	21.30	21.20	21.20	21.60	21.50	21.40
HSDPA Subtest-3	21.20	21.30	21.30	21.70	21.60	21.40
HSDPA Subtest-4	21.30	21.30	21.30	21.60	21.50	21.30
HSUPA Subtest-1	21.40	21.30	21.20	22.30	22.20	22.10
HSUPA Subtest-2	20.40	20.30	20.20	20.80	20.70	20.80
HSUPA Subtest-3	21.40	21.30	21.20	21.40	21.30	21.20
HSUPA Subtest-4	20.40	20.40	20.30	20.70	20.70	20.70
HSUPA Subtest-5	21.80	21.90	21.80	22.30	22.30	22.20

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	iPod Earphone	Apple	N/A	N/A	Unshielded, 1.0 m	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Conducted Output Power and ERP/EIRP Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for Band 850.

The EIRP of mobile transmitters must not exceed 2 Watts for Band 1900.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band ($G_T - L_C = -0.40$ dB)									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power P_T (dBm)	31.8	31.8	31.9	26.6	26.6	26.7	22.8	22.7	22.7
Conducted Power P_T (Watts)	1.51	1.51	1.55	0.46	0.46	0.47	0.19	0.19	0.19
ERP(dBm)	29.25	29.25	29.35	24.05	24.05	24.15	20.25	20.15	20.15
ERP(Watts)	0.84	0.84	0.86	0.25	0.25	0.26	0.11	0.10	0.10

PCS Band ($G_T - L_C = 1.70$ dB)									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power P_T (dBm)	29.2	29.2	29.3	25.4	25.2	25.3	23.2	23.0	22.8
Conducted Power P_T (Watts)	0.83	0.83	0.85	0.35	0.33	0.34	0.21	0.20	0.19
EIRP(dBm)	30.90	30.90	31.00	27.10	26.90	27.00	24.90	24.70	24.50
EIRP(Watts)	1.23	1.23	1.26	0.51	0.49	0.50	0.31	0.30	0.28

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. Set EUT to transmit at maximum output power.
3. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
4. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
Record the maximum PAPR level associated with a probability of 0.1%.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio


Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Peak-to-Average Ratio (dB)	0.20	0.24	0.20	3.56	3.24	3.20	3.16	3.04	3.00

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.20	0.20	0.24	3.48	3.36	3.16	3.24	3.24	3.16

3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

Peak-to-Average Ratio on Channel 128 (824.2 MHz)




Date: 25.APR.2014 15:58:52

Peak-to-Average Ratio on Channel 189 (836.4 MHz)




Date: 25.APR.2014 15:59:17

Peak-to-Average Ratio on Channel 251 (848.8 MHz)



Date: 25.APR.2014 15:59:42


Peak-to-Average Ratio on Channel 251 (848.8 MHz)



Date: 25.APR.2014 11:12:53


Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Date: 25.APR.2014 13:38:54

Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 25.APR.2014 13:38:17


Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 25.APR.2014 13:39:30


Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Date: 25.APR.2014 14:13:39

Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 25.APR.2014 14:14:13


Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 25.APR.2014 14:15:00


Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 4132 (826.4 MHz)




Date: 25.APR.2014 15:21:22

Peak-to-Average Ratio on Channel 4182 (836.4 MHz)



Date: 25.APR.2014 15:21:50


Peak-to-Average Ratio on Channel 4233 (846.6 MHz)



Date: 25.APR.2014 15:22:32


Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)




Date: 25.APR.2014 14:44:23

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 25.APR.2014 14:45:26

Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 25.APR.2014 14:45:56

3.3 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.3.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.3.4 Test Setup



3.3.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	242.00	242.00	246.00	240.00	242.00	244.00
26dB BW (kHz)	316.00	316.00	314.00	308.00	294.00	288.00

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	244.00	244.00	244.00	246.00	246.00	246.00
26dB BW (kHz)	316.00	316.00	308.00	312.00	300.00	308.00


Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.18	4.18	4.18
26dB BW (MHz)	4.68	4.68	4.68

PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.18	4.18	4.18
26dB BW (MHz)	4.68	4.68	4.68

3.3.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 25.APR.2014 10:24:42

26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 25.APR.2014 10:22:26

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 25.APR.2014 10:25:11

26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 25.APR.2014 10:22:55

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 25.APR.2014 10:25:39


26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 25.APR.2014 10:23:23


Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 25.APR.2014 11:25:37

26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 25.APR.2014 11:18:10

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 25.APR.2014 11:26:05

26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 25.APR.2014 11:14:40

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 25.APR.2014 11:26:34


26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 25.APR.2014 11:19:07


Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 25.APR.2014 13:42:00

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 25.APR.2014 13:40:10

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 25.APR.2014 13:42:28

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 25.APR.2014 13:40:39

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 25.APR.2014 13:42:57


26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 25.APR.2014 13:41:08


Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 25.APR.2014 14:19:51

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 25.APR.2014 14:17:48

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 25.APR.2014 14:20:20

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 25.APR.2014 14:18:16

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 25.APR.2014 14:20:48


26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 25.APR.2014 14:18:45


Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 25.APR.2014 15:28:27

26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 25.APR.2014 15:26:28

1 SA
MAXH

Ref 30 dBm Att 30 dB SWT 300 ms 837.74000000 MHz

OBW 4.180000000 MHz
Temp 1 [T1 OBW] 2.81 dBm
834.300000000 MHz
Temp 2 [T1 OBW] 3.56 dBm
836.480000000 MHz

30dB

Center 836.4 MHz 1 MHz/ Span 10 MHz

Ref 30 dBm +Att 30 dB +SWT 300 ms 835.52000000 MHz


30 Offset 16 dB

ndB [T1] 26.00 dB
BW 4.680000000 MHz -9.42 dBm
Temp 1 [T1 ndB]
834.060000000 MHz
Temp 2 [T2 ndB]
836.740000000 MHz -9.36 dBm

Center 836.4 MHz 1 MHz/ Span 10 MHz


Report No. : FG432436-09A
Report Version : Rev. 01
Page Number : 43 of 84
Report Template No.: BU5-FG22/24 Version 1.1

99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 25.APR.2014 15:29:24


26dB Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 25.APR.2014 15:27:25


Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 25.APR.2014 14:54:16

26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 25.APR.2014 14:52:04

99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 25.APR.2014 14:54:44

26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 25.APR.2014 14:52:32

99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 25.APR.2014 14:55:13

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 25.APR.2014 14:53:01

3.4 Band Edge Measurement

3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Band Edge


Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 25.APR.2014 10:33:28


Higher Band Edge Plot on Channel 251 (848.8 MHz)



Date: 25.APR.2014 10:30:40


Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 25.APR.2014 11:35:28


Higher Band Edge Plot on Channel 251 (848.8 MHz)



Date: 25.APR.2014 11:31:42


Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 25.APR.2014 13:48:46


Higher Band Edge Plot on Channel 810 (1909.8 MHz)



Date: 25.APR.2014 13:46:01


Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 25.APR.2014 14:26:37


Higher Band Edge Plot on Channel 810 (1909.8 MHz)



Date: 25.APR.2014 14:24:05


Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

Lower Band Edge Plot on Channel 4132 (826.4 MHz)



Date: 25.APR.2014 15:36:50


Higher Band Edge Plot on Channel 4233 (846.6 MHz)



Date: 25.APR.2014 15:33:27


Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)



Date: 25.APR.2014 15:04:52

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 25.APR.2014 14:59:43

3.5 Conducted Spurious Emission Measurement

3.5.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Spurious Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 25.APR.2014 10:42:52

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 25.APR.2014 10:43:02

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 25.APR.2014 10:43:11


Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 25.APR.2014 10:43:19


Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 25.APR.2014 11:39:05

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 25.APR.2014 11:39:16

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 25.APR.2014 11:39:24


Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 25.APR.2014 11:39:33


Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 25.APR.2014 13:51:11

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 25.APR.2014 13:51:20

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 25.APR.2014 13:51:32

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 25.APR.2014 13:51:41


Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 25.APR.2014 13:51:49


Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 25.APR.2014 14:30:53

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 25.APR.2014 14:31:01

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 25.APR.2014 14:31:12

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 25.APR.2014 14:31:20


Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 25.APR.2014 14:31:29


Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 25.APR.2014 15:39:40

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 25.APR.2014 15:39:52

The screenshot displays a Spectrum Analyzer interface with the following settings and data:


- Reference Level:** 0 dBm
- Attenuation:** 0 dB
- RBW (Resolution Bandwidth):** 1 MHz
- VBW (Video Bandwidth):** 3 MHz
- SWT (Sweep Time):** 500 ms
- Marker 1 [T1]:** 3.11200000 GHz, -51.08 dBm
- Offset:** 23.5 dB
- Start Frequency:** 3 GHz
- Stop Frequency:** 7 GHz
- Center Frequency:** 400 MHz
- Trace 1:** A blue trace showing a noisy signal centered around -51 dBm.
- Trace 2:** A red horizontal line representing a reference level at -13 dBm.
- Grid:** A 10x10 grid is visible on the plot area.
- Labels:** The y-axis is labeled from -100 to 0 dBm in increments of 10. The x-axis is labeled with frequency values: Start 3 GHz, 400 MHz/, and Stop 7 GHz.

[illegible]

Report No. : FG432436-09A
Report Version : Rev. 01
Page Number : 67 of 84
Report Template No.: BU5-FG22/24 Version 1.1


Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 25.APR.2014 15:07:29

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 25.APR.2014 15:07:37

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 25.APR.2014 15:07:49

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 25.APR.2014 15:07:57

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 25.APR.2014 15:08:05

3.6 Field Strength of Spurious Radiation Measurement

3.6.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.6.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.6.5 Test Result of Field Strength of Spurious Radiated

<Middle Channel>

Band :	GSM850	Temperature :	21~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	44~48%						
Test Engineer :	Gavin Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-46.10	-13	-33.1	-55.46	-47.56	1.88	5.49	H	Pass
2509	-35.49	-13	-22.49	-47.51	-37.12	2.44	6.22	H	Pass
3345	-51.12	-13	-38.12	-65.53	-54.57	2.47	8.07	H	Pass

Band :	GSM850	Temperature :	21~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	44~48%						
Test Engineer :	Gavin Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1672	-46.78	-13	-33.78	-55.09	-48.24	1.88	5.49	V	Pass
2509	-45.48	-13	-32.48	-57.07	-47.11	2.44	6.22	V	Pass
3345	-50.67	-13	-37.67	-65.47	-54.12	2.47	8.07	V	Pass

<Middle Channel>

Band :	GSM850					Temperature :	21~24°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	44~48%		
Test Engineer :	Gavin Wu					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-49.79	-13	-36.79	-58.95	-51.25	1.88	5.49	H	Pass
2509	-43.51	-13	-30.51	-55.34	-45.14	2.44	6.22	H	Pass
3345	-50.33	-13	-37.33	-65.59	-53.78	2.47	8.07	H	Pass

Band :	GSM850	Temperature :	21~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	44~48%						
Test Engineer :	Gavin Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-49.80	-13	-36.8	-58.44	-51.26	1.88	5.49	V	Pass
2509	-50.88	-13	-37.88	-62.83	-52.51	2.44	6.22	V	Pass
3345	-49.18	-13	-36.18	-65.03	-52.63	2.47	8.07	V	Pass

<Middle Channel>

Band :	GSM1900	Temperature :	21~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	44~48%						
Test Engineer :	Gavin Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-47.01	-13	-34.01	-66.47	-53.26	2.56	8.81	H	Pass
5636	-43.01	-13	-30.01	-67.69	-50.75	2.96	10.70	H	Pass
7520	-39.35	-13	-26.35	-67.22	-48.25	3.22	12.12	H	Pass

Band :	GSM1900	Temperature :	21~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	44~48%						
Test Engineer :	Gavin Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	loss	Gain	(H/V)	
3760	-47.26	-13	-34.26	-66.09	-53.51	2.56	8.81	V	Pass
5636	-44.83	-13	-31.83	-68.33	-52.57	2.96	10.70	V	Pass
7520	-40.68	-13	-27.68	-67.68	-49.58	3.22	12.12	V	Pass

<Middle Channel>

Band :	GSM1900	Temperature :	21~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	44~48%						
Test Engineer :	Gavin Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-48.01	-13	-35.01	-66.30	-54.26	2.56	8.81	H	Pass
5636	-43.83	-13	-30.83	-67.66	-51.57	2.96	10.70	H	Pass
7520	-40.88	-13	-27.88	-68.18	-49.78	3.22	12.12	H	Pass

Band :	GSM1900	Temperature :	21~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	44~48%						
Test Engineer :	Gavin Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
3760	-47.27	-13	-34.27	-66.41	-53.52	2.56	8.81	V	Pass
5636	-44.01	-13	-31.01	-68.80	-51.75	2.96	10.70	V	Pass
7520	-40.35	-13	-27.35	-67.36	-49.25	3.22	12.12	V	Pass

<Middle Channel>

Band :	WCDMA Band V	Temperature :	21~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	44~48%						
Test Engineer :	Gavin Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-49.10	-13	-36.1	-57.87	-50.56	1.88	5.49	H	Pass
2509	-52.15	-13	-39.15	-64.01	-53.78	2.44	6.22	H	Pass
3345	-51.12	-13	-38.12	-65.64	-54.57	2.47	8.07	H	Pass

Band :	WCDMA Band V	Temperature :	21~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	44~48%						
Test Engineer :	Gavin Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1672	-50.79	-13	-37.79	-59.86	-52.25	1.88	5.49	V	Pass
2509	-54.12	-13	-41.12	-64.82	-55.75	2.44	6.22	V	Pass
3345	-49.53	-13	-36.53	-64.74	-52.98	2.47	8.07	V	Pass

<Middle Channel>

Band :	WCDMA Band II					Temperature :	21~24°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	44~48%		
Test Engineer :	Gavin Wu					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line..								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-47.01	-13	-34.01	-66.15	-53.26	2.56	8.81	H	Pass
5636	-43.11	-13	-30.11	-67.74	-50.85	2.96	10.70	H	Pass
7520	-40.67	-13	-27.67	-67.96	-49.57	3.22	12.12	H	Pass

Band :	WCDMA Band II	Temperature :	21~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	44~48%						
Test Engineer :	Gavin Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
3760	-46.01	-13	-33.01	-65.07	-52.26	2.56	8.81	V	Pass
5636	-42.13	-13	-29.13	-66.39	-49.87	2.96	10.70	V	Pass
7520	-40.36	-13	-27.36	-67.33	-49.26	3.22	12.12	V	Pass

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.7.5 Test Setup



3.7.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0072	0.0060	PASS
40	0.0048	0.0048	
30	0.0024	0.0012	
20(Ref.)	0.0000	0.0000	
10	0.0012	0.0024	
0	0.0024	0.0024	
-10	N/A-note	N/A-note	
-20	N/A-note	N/A-note	
-30	N/A-note	N/A-note	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0021	0.0048	PASS
40	0.0160	0.0032	
30	0.0144	0.0021	
20(Ref.)	0.0000	0.0000	
10	0.0154	0.0011	
0	0.0000	0.0005	
-10	N/A-note	N/A-note	
-20	N/A-note	N/A-note	
-30	N/A-note	N/A-note	

Note: Device does not turn on, no transmission of signal.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0048	PASS
40	0.0155	
30	0.0132	
20(Ref.)	0.0000	
10	0.0108	
0	0.0120	
-10	N/A-note	
-20	N/A-note	
-30	N/A-note	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0021	PASS
40	0.0016	
30	0.0005	
20(Ref.)	0.0000	
10	0.0005	
0	0.0005	
-10	N/A-note	
-20	N/A-note	
-30	N/A-note	

Note: Device does not turn on, no transmission of signal.

3.7.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS class 8	4.20	0.0012	2.5	PASS
		3.70	0.0024		
		BEP	0.0036		
	EDGE class 8	4.20	0.0012		
		3.70	0.0012		
		BEP	0.0000		
GSM 1900 CH661	GPRS class 8	4.20	0.0149		
		3.70	0.0005		
		BEP	0.0011		
	EDGE class 8	4.20	0.0027		
		3.70	0.0016		
		BEP	0.0032		
WCDMA Band V CH4182	RMC 12.2Kbps	4.20	0.0120		
		3.70	0.0108		
		BEP	0.0132		
WCDMA Band II CH9400	RMC 12.2Kbps	4.20	0.0005		
		3.70	0.0000		
		BEP	0.0011		

Note:

1. Normal Voltage = 3.70V.
2. Battery End Point (BEP) = 3.40 V.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
System Simulator	Rohde & Schwarz	CMU200	117995	N/A	Aug. 01, 2013	Apr. 25, 2014	Jul. 31, 2014	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 09, 2014	Apr. 25, 2014	Jun. 08, 2015	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D3SP	TBN-930701	N/A	Jul. 19, 2013	Apr. 25, 2014	Jul. 18, 2014	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP30	101067	9kHz ~ 30GHz	Nov. 20, 2013	Apr. 12, 2014	Nov. 19, 2014	Radiation (03CH06-HY)
Spectrum Analyzer	Agilent	E4408B	MY44211030	9kHz ~ 26.5GHz	Dec. 02, 2013	Apr. 12, 2014	Dec. 01, 2014	Radiation (03CH06-HY)
EMI Test Receiver	R&S	ESVS10	834468/0003	20MHz ~ 1000MHz	May 06, 2014	Apr. 12, 2014	May 05, 2015	Radiation (03CH06-HY)
Bilog Antenna	Schaffner	CBL6112B	2885	30MHz ~ 2GHz	Oct. 10, 2013	Apr. 12, 2014	Oct. 09, 2014	Radiation (03CH06-HY)
Double Ridge Horn Antenna	EMCO	3117	00066583	1GHz ~ 18GHz	Aug. 02, 2013	Apr. 12, 2014	Aug. 01, 2014	Radiation (03CH06-HY)
Amplifier	SONOMA	310N	186713	9kHz ~ 1GHz	Apr. 16, 2014	Apr. 12, 2014	Apr. 15, 2015	Radiation (03CH06-HY)
Pre Amplifier	EMCI	EMC051845	SN980048	1GHz ~ 18GHz	Jul. 18, 2013	Apr. 12, 2014	Jul. 17, 2014	Radiation (03CH06-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz ~ 40GHz	Oct. 03, 2013	Apr. 12, 2014	Oct. 02, 2014	Radiation (03CH06-HY)
Preamplifier	Agilent	8449B	3008A01917	1GHz ~ 26.5GHz	Apr. 10, 2014	Apr. 12, 2014	Apr. 09, 2015	Radiation (03CH06-HY)
Turn Table	INN-CO	DS2000	420/650/00	0 ~ 360 degree	N/A	Apr. 12, 2014	N/A	Radiation (03CH06-HY)
Antenna Mast	MF	MF-7802	MF780208212	1 m ~ 4 m	N/A	Apr. 12, 2014	N/A	Radiation (03CH06-HY)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.50
---	------