RADIO TEST REPORT

Report No: STS1510021F02

Issued for

Inspira Technologies LLC

1901 4th Ave Suite 210 San Diego, CA 92101 United States

Product Name:	Tablet PC
Brand Name:	Astro Tab
Model No.:	A735
Series Model:	N/A
FCC ID:	2ABQ6A735
Test Standard:	FCC Part 15.247

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.
1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com

TEST RESULT CERTIFICATION

Applicant's name..... : Inspira Technologies LLC

Address..... : 1901 4th Ave Suite 210 San Diego, CA 92101 United States

Manufacture's Name ..... : SHENZHEN HENGLONGSHENG TECHNOLOGY CO. LIMITED

Address..... : 4F,B4 Building,3rd Industrial Zone,Fenghuanggang,Bao'an District Shenzhen, China

Product description

Product name..... : Tablet PC

Model and/or type reference : A735

Series Model ..... : N/A

Standards..... : FCC Part15.247

Test procedure..... : ANSI C63.10-2013 and ANSI C63.4-2014

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test..... :

Date (s) of performance of tests..... : 14 Oct. 2015 ~21 Oct. 2015

Date of Issue ..... : 22 Oct. 2015

Test Result ..... : **Pass**

Testing Engineer **:** (Jin Ming)

Technical Manager : (Vita Li)

Authorized Signatory **:** (Bovey Yang)

Table of Contents Page

1. SUMMARY OF TEST RESULTS 6
1.1 TEST FACTORY 7
1.2 MEASUREMENT UNCERTAINTY 7
2. GENERAL INFORMATION 8
2.1 GENERAL DESCRIPTION OF EUT 8
2.2 DESCRIPTION OF TEST MODES 10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TEST 11
2.4 DESCRIPTION OF SUPPORT UNITS 11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS 12
3. EMC EMISSION TEST 13
3.1 CONDUCTED EMISSION MEASUREMENT 13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS 13
3.1.2 TEST RESULT 14
3.2 RADIATED EMISSION MEASUREMENT 16
3.2.1 RADIATED EMISSION LIMITS 16
3.2.2 TEST PROCEDURE 17
3.2.3 TEST SETUP 18
3.2.4 EUT OPERATING CONDITIONS 19
3.2.5 TEST RESULT 20
4. CONDUCTED SPURIOUS EMISSIONS 26
4.1 APPLIED PROCEDURES / LIMIT 26
4.2 TEST PROCEDURE 26
4.3 DEVIATION FROM STANDARD 26
4.4 TEST SETUP 26
4.5 EUT OPERATION CONDITIONS 26
4.6 TEST RESULTS 27
5. POWER SPECTRAL DENSITY TEST 39
5.1 APPLIED PROCEDURES / LIMIT 39
5.2 TEST PROCEDURE 39
5.3 DEVIATION FROM STANDARD 39
5.4 TEST SETUP 39
5.5 EUT OPERATION CONDITIONS 39
5.6 TEST RESULTS 40
6. BANDWIDTH TEST 48

Table of Contents Page

6.1 APPLIED PROCEDURES / LIMIT 48
6.2 TEST PROCEDURE 48
6.3 DEVIATION FROM STANDARD 48
6.4 TEST SETUP 48
6.5 EUT OPERATION CONDITIONS 48
6.6 TEST RESULTS 49
7. PEAK OUTPUT POWER TEST 57
7.1 APPLIED PROCEDURES / LIMIT 57
7.2 TEST PROCEDURE 57
7.3 DEVIATION FROM STANDARD 57
7.4 TEST SETUP 57
7.5 EUT OPERATION CONDITIONS 57
7.6 TEST RESULTS 58
8. ANTENNA REQUIREMENT 59
8.1 STANDARD REQUIREMENT 59
8.2 EUT ANTENNA 59
APPENDIX - PHOTOS OF TEST SETUP 60

Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	22 Oct. 2015	STS1510021F02	ALL	Initial Issue

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b) (reference KDB 558074 d05 v02. /9.1.2)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Conducted Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.
Add. : 1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China

CNAS Registration No.: L7649;

FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	±2.88dB
2	Conducted Emission (150KHz-30MHz)	±2.67dB
3	RF power,conducted	±0.70dB
4	Spurious emissions,conducted	±1.19dB
5	All emissions,radiated(<1G) 30MHz-200MHz	±2.83dB
6	All emissions,radiated(<1G) 200MHz-1000MHz	±2.94dB
7	All emissions,radiated(>1G)	±3.03dB
8	Temperature	±0.5°C
9	Humidity	±2%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

<table>
<tr><td>Equipment</td><td>Tablet PC</td></tr>
<tr><td>Trade Name</td><td>Astro Tab</td></tr>
<tr><td>Model Name</td><td>A735</td></tr>
<tr><td>Series Model</td><td>N/A</td></tr>
<tr><td>Model Difference</td><td>N/A</td></tr>
<tr><td>Product Description</td><td>The EUT is a Tablet PC
<table>
<tr><td>Operation Frequency:</td><td>802.11b/g/n 20: 2412~2462 MHz
802.11n 40: 2422~2452MHz</td></tr>
<tr><td>Modulation Type:</td><td>CCK/OFDM/DBPSK/DAPSK</td></tr>
<tr><td>Bit Rate of Transmitter</td><td>802.11b:11/5.5/2/1 Mbps
802.11g:54/48/36/24/18/12/9/6Mbps
802.11n(20/40MHz):300/150/144.44/130/117/115.56/104/86.67/78/52/6.5Mbps</td></tr>
<tr><td>Number Of Channel</td><td>802.11b/g/n20: 11CH
802.11n 40: 7CH</td></tr>
<tr><td>Antenna Designation:</td><td>Please see Note 3.</td></tr>
<tr><td>Antenna Gain (dBi)</td><td>0 dbi</td></tr>
</table></td></tr>
<tr><td>Channel List</td><td>Please refer to the Note 2.</td></tr>
<tr><td>Adapter</td><td>Power supply and ADP（rating）:
Input:100-240V AC,50/60Hz 350mA
Output:5V,1500mA</td></tr>
<tr><td>Battery</td><td>Rated Voltage:3.7V
capacity : 2600mAh</td></tr>
<tr><td>Hardware version number</td><td>N/A</td></tr>
<tr><td>Software versioning number</td><td>N/A</td></tr>
<tr><td>Connecting I/O Port(s)</td><td>Please refer to the User's Manual</td></tr>
</table>

Note:

1 For a more detailed features description, please refer to the manufacturer’s specifications or the User's Manual.

2

Channel List for 802.11b/g/n(20MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	06	2437	09	2452		
04	2427	07	2442				
05	2432	08	2447				

3 Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	Astro Tab	A735	PIFA Antenna	N/A	0	N/A

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Low
Mode 2	Middle
Mode 3	High
Mode 4	Charging + Keeping TX mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Charging + Keeping TX mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	Low
Mode 2	Middle
Mode 3	High
Mode 4	Charging + Keeping TX mode

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

(3)We have be tested for all avaiable U.S. voltage and frequencies(For 120V 60Hz) for which the device is capable of operation.

(4) We measured emission at 802.11b, g, n(HT20) and n(HT40) mode from 9KHz to 25GHz, and recorded worst case at 802.11b mode.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TEST



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	Tablet PC	Astro Tab	A735	N/A	EUT
E-2	Adapter	N/A	JHD-AP012U-050150BB	N/A	EUT
E-3	Earphone	N/A	N/A	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	unshielded	NO	80cm	N/A
C-2	unshielded	NO	100cm	N/A

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
(3) PC is FCC DOC approved

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	102086	2014.11.20	2015.11.19
LISN	R&S	ENV216	101242	2014.10.25	2015.10.24
LISN	EMCO	3810/2NM	000-23625	2014.10.25	2015.10.24
MXA SIGNAL Analyzer	Agilent	Agilent	N9020A	2014.10.25	2015.10.24

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Spectrum Analyzer	Agilent	E4407B	MY50140340	2014.10.25	2015.10.24
Test Receiver	R&S	ESCI	101427	2014.10.25	2015.10.24
Bilog Antenna	TESEQ	CBL6111D	34678	2014.11.25	2015.11.24
Horn Antenna	Schwarzbeck	BBHA 9120D(1201)	9120D-1343	2015.03.06	2016.03.05
50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.06	2016.06.05
PreAmplifier	Agilent	8449B	60538	2014.10.25	2015.10.24
Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07

RF Connected Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Spectrum Analyzer	Agilent	E4407B	MY50140340	2014.10.25	2015.10.24
Test Receiver	R&S	ESCI	101427	2014.10.25	2015.10.24
MXA SIGNAL Analyzer	Agilent	N9020A	MY49100060	2014.10.25	2015.10.24
50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.06	2016.06.05
Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2014.10.25	2015.10.24

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

3.1.2 TEST RESULT

EUT:	Tablet PC	Model Name.:	A735
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	L
Test Voltage:	DC 5V from Adapter AC120V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1824	47.18	10.00	57.18	64.38	-7.20	QP
0.1824	15.77	10.00	25.77	54.38	-28.61	AVG
0.4100	33.44	10.17	43.61	57.65	-14.04	QP
0.4100	9.54	10.17	19.71	47.65	-27.94	AVG
0.8580	30.61	9.95	40.56	56.00	-15.44	QP
0.8580	7.16	9.95	17.11	46.00	-28.89	AVG
1.8900	29.79	9.99	39.78	56.00	-16.22	QP
1.8900	7.65	9.99	17.64	46.00	-28.36	AVG
5.2220	25.63	10.20	35.83	60.00	-24.17	QP
5.2220	5.59	10.20	15.79	50.00	-34.21	AVG
25.0300	29.28	10.50	39.78	60.00	-20.22	QP
25.0300	10.22	10.50	20.72	50.00	-29.28	AVG

Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT:	Tablet PC	Model Name.:	A735
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	N
Test Voltage:	DC 5V from Adapter AC120V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1540	43.87	10.72	54.59	65.78	-11.19	QP
0.1540	17.64	10.72	28.36	55.78	-27.42	AVG
0.3060	36.58	9.91	46.49	60.08	-13.59	QP
0.3060	15.37	9.91	25.28	50.08	-24.80	AVG
0.6940	26.19	10.00	36.19	56.00	-19.81	QP
0.6940	3.41	10.00	13.41	46.00	-32.59	AVG
1.8020	26.14	10.00	36.14	56.00	-19.86	QP
1.8020	5.76	10.00	15.76	46.00	-30.24	AVG
5.9100	22.81	10.20	33.01	60.00	-26.99	QP
5.9100	4.28	10.20	14.48	50.00	-35.52	AVG
26.6100	24.70	10.71	35.41	60.00	-24.59	QP
26.6100	16.45	10.71	27.16	50.00	-22.84	AVG

Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

6 dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&205(a), then the Part 15.247&209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1MHz /10 Hz(duty cycle more than 98%)

Receiver Parameter	**Setting**
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 TEST RESULT

9KHz-30MHz

EUT：	Tablet PC	Model Name. ：	A735
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V from Adapter with AC 120V/60Hz
Test Mode ：	Link mode	Polarization ：	--

Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

NOTE:
The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.

30MHz - 1000MHz

EUT：	Tablet PC	Model Name. ：	A735
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V from Adapter with AC 120V/60Hz
Test Mode ：	Mode 4	Polarization ：	Horizontal

Frequency	Reading	Correct	Result	Limit	Margin	Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
98.8324	25.96	11.41	37.37	43.50	-6.13	QP
148.4410	23.17	13.18	36.35	43.50	-7.15	QP
197.8926	27.96	10.42	38.38	43.50	-5.12	QP
346.8091	20.30	18.10	38.40	46.00	-7.60	QP
552.8832	14.38	24.91	39.29	46.00	-6.71	QP
744.8660	11.07	28.09	39.16	46.00	-6.84	QP

Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



30MHz - 1000MHz

EUT：	Tablet PC	Model Name. ：	A735
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V from Adapter with AC 120V/60Hz
Test Mode ：	Mode 4	Polarization ：	Vertical

Frequency	Reading	Correct	Result	Limit	Margin	Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
49.3594	24.38	9.00	33.38	40.00	-6.62	QP
98.8324	23.01	11.41	34.42	43.50	-9.08	QP
148.4410	22.76	13.18	35.94	43.50	-7.56	QP
346.8091	15.62	18.10	33.72	46.00	-12.28	QP
554.8252	13.13	24.95	38.08	46.00	-7.92	QP
893.8567	11.17	29.55	40.72	46.00	-5.28	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Above 1000MHz

EUT：	Tablet PC	Model Name ：	A735
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V from Adapter with AC 120V/60Hz

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11b/2412 MHz)							
4824.20	62.63	-3.58	59.05	74	-14.95	PK	Vertical
4824.21	43.62	-3.58	40.04	54	-13.96	AV	Vertical
7236.14	58.72	-0.8	57.92	74	-16.08	PK	Vertical
7236.12	37.66	-0.8	36.86	54	-17.14	AV	Vertical
4824.20	58.58	-3.58	55	74	-19	PK	Horizontal
4824.22	40.41	-3.58	36.83	54	-17.17	AV	Horizontal
Mid Channel (802.11b/2437 MHz)							
4874.09	63.95	-3.56	60.39	74	-13.61	PK	Vertical
4874.07	47.83	-3.56	44.27	54	-9.73	AV	Vertical
7311.21	59.83	-0.78	59.05	74	-14.95	PK	Vertical
7311.21	42.98	-0.78	42.2	54	-11.8	AV	Vertical
4874.17	59.67	-3.56	56.11	74	-17.89	PK	Horizontal
4874.15	43.67	-3.56	40.11	54	-13.89	AV	Horizontal
High Channel (802.11b/2462 MHz)							
4944.26	59.80	-3.54	56.26	74	-17.74	PK	Vertical
4944.31	43.67	-3.54	40.13	54	-13.87	AV	Vertical
7416.33	59.92	-0.75	59.17	74	-14.83	PK	Vertical
7416.31	43.89	-0.75	43.14	54	-10.86	AV	Vertical
4944.26	59.80	-3.54	56.26	74	-17.74	PK	Horizontal
4944.30	43.88	-3.54	40.34	54	-13.66	AV	Horizontal

Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11b, 802.11g, 802.11n (HT-20), 802.11n (HT-40), the worst case is 802.11b.

3.2.6 TEST RESULTS (Band edge)

EUT：	Tablet PC	Model Name ：	A735
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V from Adapter with AC 120V/60Hz

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
802.11 b							
2390.0	66.93	-12.99	53.94	74	-20.06	PK	Vertical
2390.0	53.95	-12.99	40.96	54	-13.04	AV	Vertical
2390.0	66.02	-12.99	53.03	74	-20.97	PK	Horizontal
2390.0	51.67	-12.99	38.68	54	-15.32	AV	Horizontal
2483.6	66.01	-12.78	53.23	74	-20.77	PK	Vertical
2483.6	52.08	-12.78	39.3	54	-14.7	AV	Vertical
2483.6	66.74	-12.78	53.96	74	-20.04	PK	Horizontal
2483.6	53.14	-12.78	40.36	54	-13.64	AV	Horizontal
802.11 g							
2390.0	66.67	-12.99	53.68	74	-20.32	PK	Vertical
2390.0	54.08	-12.99	41.09	54	-12.91	AV	Vertical
2390.0	65.98	-12.99	52.99	74	-21.01	PK	Horizontal
2390.0	51.59	-12.99	38.6	54	-15.4	AV	Horizontal
2483.6	66.01	-12.78	53.23	74	-20.77	PK	Vertical
2483.6	51.71	-12.78	38.93	54	-15.07	AV	Vertical
2483.6	67.06	-12.78	54.28	74	-19.72	PK	Horizontal
2483.6	52.91	-12.78	40.13	54	-13.87	AV	Horizontal

802.11 n20							
2390.0	66.96	-12.99	53.97	74	-20.03	PK	Vertical
2390.0	53.60	-12.99	40.61	54	-13.39	AV	Vertical
2390.0	65.84	-12.99	52.85	74	-21.15	PK	Horizontal
2390.0	51.56	-12.99	38.57	54	-15.43	AV	Horizontal
2483.6	65.42	-12.78	52.64	74	-21.36	PK	Vertical
2483.6	51.83	-12.78	39.05	54	-14.95	AV	Vertical
2483.6	67.04	-12.78	54.26	74	-19.74	PK	Horizontal
2483.6	53.10	-12.78	40.32	54	-13.68	AV	Horizontal
802.11 n40							
2390.0	66.83	-12.99	53.84	74	-20.16	PK	Vertical
2390.0	52.93	-12.99	39.94	54	-14.06	AV	Vertical
2390.0	67.66	-12.99	54.67	74	-19.33	PK	Horizontal
2390.0	52.13	-12.99	39.14	54	-14.86	AV	Horizontal
2483.6	68.82	-12.78	56.04	74	-17.96	PK	Vertical
2483.6	52.06	-12.78	39.28	54	-14.72	AV	Vertical
2483.6	69.05	-12.78	56.27	74	-17.73	PK	Horizontal
2483.6	52.04	-12.78	39.26	54	-14.74	AV	Horizontal
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.							
Low measurement frequencies is range from 2310 to 2400 MHz, high measurement frequencies is range from 2483.5 to 2500 MHz. Only show the worst point data of the emissions in the frequency 2310-2400 MHz and 2483.5-2500 MHz.							

4. CONDUCTED SPURIOUS EMISSIONS

4.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

.

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2430 MHz Upper Band Edge: 2450 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP

The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX b Mode /CH01, CH06, CH11		

CH 01



CH 06


Agilent Spectrum Analyzer - Swept SA
Marker 1 2.439605000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
06:53:46 PM Oct 12, 2015
Ref Offset 0.5 dB
10 dB/div
Ref 4.98 dBm
Log
Mkr1 2.440 GHz
-0.017 dBm
-20.02 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.39 s (8001 pts)
1 N 1 f 2.440 GHz -0.017 dBm
2 N 1 f 24.950 GHz -51.423 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
MSG
STATUS

CH 11


Agilent Spectrum Analyzer - Swept SA
Center Freq 12.515000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
06:58:21 PM Oct 12, 2015
Ref Offset 0.5 dB
10 dB/div
Ref 4.65 dBm
Log
Mkr1 2.458 GHz
-0.354 dBm
-20.35 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.39 s (8001 pts)
1 N 1 f 2.458 GHz -0.354 dBm
2 N 1 f 24.750 GHz -49.052 dBm
Frequency
Auto Tune
Center Freq
12.515000000 GHz
Start Freq
30.000000 MHz
Stop Freq
25.000000000 GHz
CF Step
2.497000000 GHz
Auto
Man
Freq Offset
0 Hz
MSG
STATUS

Band edge

CH 01



CH 11



EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX g Mode /CH01, CH06, CH11		

CH 01



CH06



CH 11


Agilent Spectrum Analyzer - Swept SA
RL
RF
50 Ω AC
SENSE:INT
ALIGN AUTO
07:22:55 PM Oct 12, 2015
Center Freq 12.515000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
TRACE 1 2 3 4 5 6
TYPE M WWWWW
DET P P P P P P
Ref Offset 0.5 dB
10 dB/div
Log
Ref -0.05 dBm
Mkr1 2.458 GHz
-5.05 dBm
-10.1
-20.1
-30.1
-40.1
-50.1
-60.1
-70.1
-80.1
-90.1
-26.36 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.39 s (8001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.458 GHz -5.05 dBm
2 N 1 f 24.850 GHz -51.822 dBm
Frequency
Auto Tune
Center Freq
12.515000000 GHz
Start Freq
30.000000 MHz
Stop Freq
25.000000000 GHz
CF Step
2.497000000 GHz
Auto
Man
Freq Offset
0 Hz
MSG
STATUS

Band edge

CH 01



CH11



EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX n Mode(20M) /CH01, CH06, CH11		

CH 01



CH 06



CH 11


Agilent Spectrum Analyzer - Swept SA
RL
RF
50 Ω AC
SENSE:INT
ALIGN AUTO
07:34:04 PM Oct 12, 2015
Avg Type: Log-Pwr
TRACE 1 2 3 4 5 6
TYPE M WWWWW
DET P P P P P
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Ref Offset 0.5 dB
10 dB/div
Log
Ref -0.67 dBm
Mkr1 2.468 GHz
-5.668 dBm
-10.7
-20.7
-30.7
-40.7
-50.7
-60.7
-70.7
-80.7
-90.7
-25.67 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.39 s (8001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.468 GHz -5.668 dBm
2 N 1 f 24.750 GHz -51.391 dBm
3
4
5
6
7
8
9
10
11
12
MSG
STATUS
Trace/Det
Select Trace 1
Clear Write
Trace Average
Max Hold
Min Hold
View/Blank View
More 1 of 3

Band edge

CH 01



CH 11

EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX n Mode(40M) /CH03, CH06, CH09		

CH 03



CH06


Agilent Spectrum Analyzer - Swept SA
Marker 1 2.430241250000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
07:39:52 PM Oct 12, 2015
Ref Offset 0.5 dB
10 dB/div
Log
Ref -2.67 dBm
Mkr1 2.430 GHz
-7.671 dBm
-27.67 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.39 s (8001 pts)
1 N 1 f 2.430 GHz -7.671 dBm
2 N 1 f 24.800 GHz -47.125 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

CH09


Agilent Spectrum Analyzer - Swept SA
Center Freq 12.515000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
07:44:08 PM Oct 12, 2015
Ref Offset 0.5 dB
10 dB/div
Log
Ref -5.04 dBm
Mkr1 2.468 GHz
-10.042 dBm
-30.04 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.39 s (8001 pts)
1 N 1 f 2.468 GHz -10.042 dBm
2 N 1 f 24.725 GHz -49.905 dBm
Frequency
Auto Tune
Center Freq
12.515000000 GHz
Start Freq
30.000000 MHz
Stop Freq
25.000000000 GHz
CF Step
2.497000000 GHz
Auto
Man
Freq Offset
0 Hz

Band edge

CH03



CH 09



5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the 100 kHz ≥ RBW ≥ 3 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS

EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX b Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-14.328	8	PASS
2437 MHz	-15.167	8	PASS
2462 MHz	-13.522	8	PASS

TX CH01



TX CH06



TX CH11



EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX g Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-18.273	8	PASS
2437 MHz	-17.511	8	PASS
2462 MHz	-16.281	8	PASS

TX CH01



TX CH06



TX CH11



EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX n Mode(20M) /CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-18.783	8	PASS
2437 MHz	-20.673	8	PASS
2462 MHz	-17.183	8	PASS

TX CH01



TX CH06



TX CH11



EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX n Mode(40M) /CH03, CH06, CH09		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-22.600	8	PASS
2437 MHz	-21.865	8	PASS
2452 MHz	-22.440	8	PASS

TX CH03



TX CH06



TX CH09



6. BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

6.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW≥3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be≥6 dB.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX b Mode /CH01, CH06, CH11		

Frequency	6dB Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	10.05	>=500KHz	PASS
2437 MHz	10.06	>=500KHz	PASS
2462 MHz	10.05	>=500KHz	PASS

TX CH 01



TX CH 06



TX CH 11



EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX g Mode /CH01, CH06, CH11		

Frequency	6dB Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	16.40	>=500KHz	PASS
2437 MHz	16.39	>=500KHz	PASS
2462 MHz	16.41	>=500KHz	PASS

TX CH 01



TX CH 06



TX CH 11



EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX n Mode(20M) /CH01, CH06, CH11		

Frequency	6dB Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	17.62	>=500KHz	PASS
2437 MHz	17.60	>=500KHz	PASS
2462 MHz	17.60	>=500KHz	PASS

TX CH 01



TX CH 06



TX CH 11



EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX n Mode(40M) /CH03, CH06, CH09		

Frequency	6dB Bandwidth (MHz)	Channel Separation (KHz)	Result
2422 MHz	36.08	>=500KHz	PASS
2437 MHz	36.06	>=500KHz	PASS
2452 MHz	36.05	>=500KHz	PASS

TX CH 03



TX CH 06



TX CH 09



7. PEAK OUTPUT POWER TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.2 TEST PROCEDURE

a. The EUT was directly connected to the Power Sensor&PC

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

EUT：	Tablet PC	Model Name ：	A735
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX b/g/n(20M,40M) Mode /CH01, CH06, CH11		

TX 802.11b Mode			
Test Channe	Frequency (MHz)	Peak Conducted Output Power (dBm)	LIMIT dBm
CH01	2412	9.1	30
CH06	2437	9.3	30
CH11	2462	9.6	30

TX 802.11g Mode			
Test Channe	Frequency (MHz)	Peak Conducted Output Power (dBm)	LIMIT dBm
CH01	2412	7.7	30
CH06	2437	8.1	30
CH11	2462	8.7	30

TX 802.11n20 Mode			
Test Channe	Frequency (MHz)	Peak Conducted Output Power (dBm)	LIMIT dBm
CH01	2412	7.7	30
CH06	2437	8.2	30
CH11	2462	8.7	30

TX 802.11n40 Mode			
Test Channe	Frequency (MHz)	Peak Conducted Output Power (dBm)	LIMIT dBm
CH03	2422	7.2	30
CH06	2437	7.5	30
CH09	2452	7.9	30

8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is PIFA Antenna. It comply with the standard requirement.

APPENDIX - PHOTOS OF TEST SETUP

Radiated Measurement Photos





Conducted Measurement Photos

※※※※※END OF THE REPORT※※※※※