



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 Fax: +86-755-26636041

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.249

Report Reference No.: CTL1507302114-WF

Compiled by:
(position+printed name+signature)

Jacky Chen
(File administrators)

Jacky Chen

Tested by:
(position+printed name+signature)

Allen Wang
(Test Engineer)

Allen Wang

Approved by:
(position+printed name+signature)

Tracy Qi
(Manager)

Tracy Qi

Product Name.....: Car Entertainment System

Model/Type reference.....: X358

List Model(s).....: HW-9543

Trade Mark.....: XO VISION

FCC ID.....: 2ABQZ-X358

Applicant's name.....: Hopwell Electronics

Address of applicant.....: RM 1507, Tower A, Viking Technology & Business Centre, 93 Ta Chuen Ping St, Kwai Chung, Hong Kong

Test Firm.....: Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm.....: Floor 1-A, Baisha Technology Park, No.3011, Shaheixi Road, Nanshan District, Shenzhen, China 518055

Test specification.....:

Standard.....: FCC Part 15.249: Operation within the bands 920-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz and 24.0 - 24.25 GHz.

TRF Originator.....: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF.....: Dated 2011-01

Date of Receipt.....: July 30, 2015

Date of Test Date.....: July 31, 2015 –Aug. 09, 2015

Data of Issue.....: Aug. 10, 2015

Result.....: Positive

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL1507302114-WF	Aug.10, 2015 Date of issue
--------------------------	-------------------------	-------------------------------

Equipment under Test : Car Entertainment System

Model /Type : X358

Listed Models : HW-9543

Applicant : Hopwell Electronics

Address : RM 1507, Tower A, Viking Technology & Business
Centre, 93 Ta Chuen Ping St, Kwai Chung, Hong
Kong

Manufacturer : Hopwell Electronics

Address : No.88 Hulong Road, Tiantoujiao, Qiaotou Town,
Dongguan City, China

Test result	Pass *
--------------------	---------------

* In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

**** Modified History ****


Version	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	2015-08-10	CTL1507302114-WF	Tracy Qi



Table of Contents

Page

1. SUMMARY.....	5
1.1. TEST STANDARDS.....	5
1.2. TEST DESCRIPTION.....	5
1.3. TEST FACILITY	6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	6
2. GENERAL INFORMATION.....	7
2.1. ENVIRONMENTAL CONDITIONS	7
2.2. GENERAL DESCRIPTION OF EUT	7
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY.....	7
2.4. EQUIPMENTS USED DURING THE TEST	8
2.5. RELATED SUBMITTAL(S) / GRANT (S).....	8
2.6. MODIFICATIONS.....	8
3. TEST CONDITIONS AND RESULTS	9
3.1. CONDUCTED EMISSIONS TEST	9
3.2. RADIATED EMISSIONS AND BAND EDGE	10
3.3. OCCUPIED BANDWIDTH MEASUREMENT.....	16
3.4. ANTENNA REQUIREMENT.....	17
4. TEST SETUP PHOTOS OF THE EUT	21
5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	22



1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.249:2014](#) Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz.

[ANSI C63.10: 2013](#) American National Standard for Testing Unlicensed Wireless Devices

1.2. Test Description

FCC PART 15.249		
FCC Part 15.249(a)	Field Strength of Fundamental	PASS
FCC Part 15.209	Spurious Emission	PASS
FCC Part 15.209	Band edge	PASS
FCC Part 15.215(c)	20dB bandwidth	PASS
FCC Part 15.207	Conducted Emission	N/A
FCC Part 15.203	Antenna Requirement	PASS



1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	Car Entertainment System
Model/Type reference:	X358
Power supply:	DC 12V from battery
Bluetooth	
Version:	Supported BT2.1+EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Monopole Antenna
Antenna gain:	1.0dBi

Note: For more details, please refer to the user's manual of the EUT.

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

Operation Frequency :

Channel	Frequency (MHz)
00	2402
01	2403
:	:
38	2440
39	2441
40	2442
:	:
77	2479
78	2480

2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2015/06/02	2016/06/01
EMI Test Receiver	R&S	ESCI	103710	2015/06/02	2016/06/01
Spectrum Analyzer	Agilent	E4407B	MY41440676	2015/05/21	2016/05/20
Controller	EM Electronics	Controller EM 1000	N/A	2015/05/21	2016/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2015/05/19	2016/05/18
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2015/05/19	2016/05/18
Amplifier	Agilent	8349B	3008A02306	2015/05/19	2016/05/18
Amplifier	Agilent	8447D	2944A10176	2015/05/19	2016/05/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2015/05/20	2016/05/19
High-Pass Filter	K&L	9SH10-2700/X1 2750-O/O	N/A	2015/05/20	2016/05/19
High-Pass Filter	K&L	41H10-1375/U1 2750-O/O	N/A	2015/05/20	2016/05/19
RF Cable	HUBER+SUHNER	RG214	N/A	2015/05/20	2016/05/19

The calibration interval was one year

2.5. Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended for FCC ID: 2ABQZ-X358 filing to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Not applicable to this device, which is battery supply.

3.2. Radiated Emissions and Band Edge

Limit

According 15.249, the field strength of emissions from intentional radiators operated within 2400MHz-2483.5 MHz shall not exceed 94dB μ V/m (50mV/m):

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz

**Test Procedure**

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.

TEST RESULTS

Remark:

1. We measured Radiated Emission at GFSK, $\pi/4$ DQPSK and 8DPSK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
2. For below 1GHz testing recorded worst at GFSK DH5 low channel.

For 9 KHz-30MHz


Frequency (MHz)	Corrected Reading (dBuV/m)@3m	FCC Limit (dBuV/m) @3m	Margin (dB)	Detector	Result
0.10	56.87	107.60	50.73	QP	PASS
1.57	51.50	63.69	12.19	QP	PASS
15.86	57.69	69.54	11.85	QP	PASS
20.59	47.85	69.54	21.69	QP	PASS

For 30MHz-1GHz

Horizontal

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength				Transducer
Start	Stop	Detector	Meas. Time	IF Bandw.		
Frequency	Frequency					
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	JB1	

***MEASUREMENT RESULT: "CTL150806608_red"***


8/6/2015 9:44AM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
53.280000	34.50	8.3	40.0	5.5	---	0.0	0.00	HORIZONTAL
179.380000	39.90	13.3	43.5	3.6	---	0.0	0.00	HORIZONTAL
214.300000	37.30	14.3	43.5	6.2	---	0.0	0.00	HORIZONTAL
251.160000	38.90	14.2	46.0	7.1	---	0.0	0.00	HORIZONTAL
278.320000	42.40	15.4	46.0	3.6	---	0.0	0.00	HORIZONTAL
359.800000	38.40	17.3	46.0	7.6	---	0.0	0.00	HORIZONTAL

Vertical

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength				Transducer
Start	Stop	Detector	Meas. Time	IF Bandw.		
Frequency	Frequency					
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	JB1	

***MEASUREMENT RESULT: "CTL150806607_red"***

8/6/2015 9:43AM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
53.280000	35.20	8.3	40.0	4.8	---	0.0	0.00	VERTICAL
179.380000	38.70	13.3	43.5	4.8	---	0.0	0.00	VERTICAL
251.160000	41.70	14.2	46.0	4.3	---	0.0	0.00	VERTICAL
270.560000	42.30	15.2	46.0	3.7	---	0.0	0.00	VERTICAL
342.340000	40.60	16.7	46.0	5.4	---	0.0	0.00	VERTICAL
431.580000	40.90	18.9	46.0	5.1	---	0.0	0.00	VERTICAL

For 1GHz to 25GHz**GFSK Mode (above 1GHz)**

Frequency(MHz):				2402		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2402.00	97.58	PK	114	16.42	63.96	28.92	4.70	0.00	33.62
1	2402.00	90.51	AV	94	3.49	56.89	28.92	4.70	0.00	33.62
2	2390.00	38.69	PK	74	35.31	5.06	28.93	4.70	0.00	33.63
2	2390.00	--	AV	54	--	--	--	--	--	--
3	2400.00	45.74	PK	74	28.26	12.06	28.96	4.72	0.00	33.68
3	2400.00	--	AV	54	--	--	--	--	--	--
4	4804.00	57.65	PK	74	16.35	53.14	33.49	6.91	35.89	4.51
4	4804.00	45.14	AV	54	8.86	40.63	33.49	6.91	35.89	4.51
5	5175.75	40.33	PK	74	33.67	33.01	34.49	7.13	34.29	7.32
5	5175.75	--	AV	54	--	--	--	--	--	--
6	7206.00	42.54	PK	74	31.46	31.43	36.95	9.18	35.03	11.11
6	7206.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2402		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2402.00	98.65	PK	114	15.35	65.25	28.78	4.61	0.00	33.40
1	2402.00	90.33	AV	94	3.67	56.93	28.78	4.61	0.00	33.40
2	2390.00	38.74	PK	74	35.26	5.42	28.72	4.60	0.00	33.32
2	2390.00	--	AV	54	--	--	--	--	--	--
3	2400.00	43.20	PK	74	30.8	9.81	28.78	4.61	0.00	33.39
3	2400.00	--	AV	54	--	--	--	--	--	--
4	4804.00	56.22	PK	74	17.78	51.71	33.49	6.91	35.89	4.51
4	4804.00	47.58	AV	54	6.42	43.07	33.49	6.91	35.89	4.51
5	5120.25	41.33	PK	74	32.67	34.13	34.37	7.10	34.27	7.20
5	5120.25	--	AV	54	--	--	--	--	--	--
6	7206.00	46.30	PK	74	27.7	35.19	36.95	9.18	35.03	11.11
6	7206.00	--	AV	54	--	--	--	--	--	--

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

Frequency(MHz):				2441		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2441.00	97.54	PK	114	16.46	64.03	28.85	4.66	0.00	33.51
1	2441.00	90.98	AV	94	3.02	57.47	28.85	4.66	0.00	33.51
2	4230.35	42.52	PK	74	31.48	37.82	32.82	6.54	34.67	4.70
2	4230.35	--	AV	54	--	--	--	--	--	--
3	4882.00	55.74	PK	74	18.26	49.48	33.60	6.95	34.30	6.26
3	4882.00	48.63	AV	54	5.37	42.37	33.60	6.95	34.30	6.26
4	5010.75	41.40	PK	74	32.6	34.57	34.02	7.04	34.22	6.83
4	5010.75	--	AV	54	--	--	--	--	--	--
5	7323.00	45.74	PK	74	28.26	34.04	37.46	9.23	35.00	11.70
5	7323.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2441		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2441.00	98.54	PK	114	15.46	65.03	28.85	4.66	0.00	33.51
1	2441.00	91.74	AV	94	2.26	58.23	28.85	4.66	0.00	33.51
2	3888.75	42.54	PK	74	31.46	37.85	33.29	6.28	34.88	4.69
2	3888.75	--	AV	54	--	--	--	--	--	--
3	4882.00	56.35	PK	74	17.65	49.99	33.60	6.95	34.19	6.36
3	4882.00	47.48	AV	54	6.52	41.12	33.60	6.95	34.19	6.36
4	5125.50	42.41	PK	74	31.59	35.08	34.38	7.10	34.16	7.33
4	5125.50	--	AV	54	--	--	--	--	--	--
5	7323.00	45.54	PK	74	28.46	33.84	37.46	9.23	35.00	11.70
5	7323.00	--	AV	54	--	--	--	--	--	--

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

Frequency(MHz):				2480		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	97.54	PK	114	16.46	63.92	28.92	4.70	0.00	33.62
1	2480.00	89.54	AV	94	4.46	55.92	28.92	4.70	0.00	33.62
2	2483.50	46.25	PK	74	27.75	12.62	28.93	4.70	0.00	33.63
2	2483.50	--	AV	54	--	--	--	--	--	--
3	2500.00	39.41	PK	74	34.59	5.73	28.96	4.72	0.00	33.68
3	2500.00	--	AV	54	--	--	--	--	--	--
4	4960.00	56.22	PK	74	17.78	51.30	33.84	7.00	35.92	4.92
4	4960.00	47.42	AV	54	6.58	42.50	33.84	7.00	35.92	4.92
5	5175.50	43.25	PK	74	30.75	35.93	34.49	7.13	34.29	7.32
5	5175.50	--	AV	54	--	--	--	--	--	--
6	7440.00	40.26	PK	74	33.74	28.31	37.64	9.28	34.97	11.95
6	7440.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2480		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	98.64	PK	114	15.36	65.02	28.92	4.70	0.00	33.62
1	2480.00	90.26	AV	94	3.74	56.64	28.92	4.70	0.00	33.62
2	2483.50	44.45	PK	74	29.55	10.82	28.93	4.70	0.00	33.63
2	2483.50	--	AV	54	--	--	--	--	--	--
3	2500.00	37.87	PK	74	36.13	4.19	28.96	4.72	0.00	33.68
3	2500.00	--	AV	54	--	--	--	--	--	--
4	4960.00	57.16	PK	74	16.84	52.24	33.84	7.00	35.92	4.92
4	4960.00	42.63	AV	54	11.37	37.71	33.84	7.00	35.92	4.92
5	5510.50	41.54	PK	74	32.46	33.89	34.75	7.32	34.41	7.65
5	5510.50	--	AV	54	--	--	--	--	--	--
6	7440.00	40.15	PK	74	33.85	28.20	37.64	9.28	34.97	11.95
6	7440.00	--	AV	54	--	--	--	--	--	--

REMARKS:


1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

3.3. Occupied Bandwidth Measurement

Limit

N/A

Test Configuration



Test Procedure


The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Results

Modulation	Channel	99% OBW (MHz)	20dB bandwidth (MHz)	Result
GFSK	CH00	0.725	0.558	Pass
	CH39	0.722	0.557	
	CH78	0.726	0.558	
$\pi/4$ DQPSK	CH00	1.103	1.151	
	CH39	1.106	1.155	
	CH78	1.105	1.157	
8DPSK	CH00	1.111	1.159	
	CH39	1.108	1.153	
	CH78	1.105	1.159	

Test plot as follows:



The image shows a screenshot of an Agilent spectrum analyzer. The top bar displays the Agilent logo and the frequency 2.402 GHz. Below this, the 'Occupied Bandwidth' is shown as 1.1029 MHz. The main display area shows a spectrum plot with a blue trace. The y-axis is labeled '#Peak Log 10 dB/Offset 0.5 dB' and the x-axis is labeled 'Center 2.402 GHz'. The plot shows a signal with a peak at 2.402 GHz. The peak is marked with a diamond and labeled '1.1029 MHz'. The plot also shows a 'Span 3 MHz' and a 'Sweep 5 ms'. The right side of the screen shows a control panel with buttons for 'Trace/View', 'Clear Write', 'Max Hold', 'Min Hold', 'View', 'Blank', and 'More'. The bottom of the screen shows a summary of the measurements: 'Occupied Bandwidth 1.1029 MHz', 'Occ BW % Pwr 99.00 %', 'x dB -20.00 dB', 'Transmit Freq Error -22.365 kHz', and 'x dB Bandwidth 1.151 MHz'.

The screen displays the 'Occupied Bandwidth' measurement results. At the top, the channel frequency is set to 2.441 GHz. The measurement parameters are: Center 2.441 GHz, Res BW 30 kHz, Span 3 MHz, and Sweep 5 ms. The graph shows a blue trace of the signal spectrum. Two cursors are placed on the trace, indicating a bandwidth of 1.1059 MHz. The power level is 99.00% and the power offset is -20.00 dB. The transmit frequency error is -23.134 kHz and the bandwidth error is 1.155 MHz.

Parameter	Value
Center	2.441 GHz
Res BW	30 kHz
Span	3 MHz
Sweep	5 ms
Occupied Bandwidth	1.1059 MHz
Occ BW % Pwr	99.00 %
x dB	-20.00 dB
Transmit Freq Error	-23.134 kHz
x dB Bandwidth	1.155 MHz

Agilent R T

Ch Freq 2.48 GHz Trig Free

Occupied Bandwidth

Ref 10 dBm Atten 20 dB

#Peak
Log
10
dB/
Offset
0.5
dB


Center 2.48 GHz Span 3 MHz
#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms

Occupied Bandwidth Occ BW % Pwr 99.00 %
1.1051 MHz x dB -20.00 dB

Transmit Freq Error -24.038 kHz
x dB Bandwidth 1.157 MHz

Trace/View
Trace 1 Trace 2
Clear View
Max Hold
Min Hold
View
Blank
More
1 of 2

CH78



3.4. Antenna Requirement

Standard Applicable


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.




Antenna Connected Construction

The antenna used in this product is an internal Antenna, The directional gains of antenna used for transmitting is 1 dBi.




BT
antenna

4. Test Setup Photos of the EUT







5. External and Internal Photos of the EUT

External Photos of EUT













Internal Photos of EUT





BT Antenna









***** End of Report *****