RF TEST REPORT

Report No.:	SET2023-02499
Product Name:	RemindTag
Model No.:	IVF-BT11
FCC ID:	2ABREIVF-BT11
Applicant:	Xiamen Innov Information Technology Co.,LTD
Address:	No.943,Tonglong Second RD,Hongtang Town,Tong an District,Xiamen city , Fujian Province
Dates of Testing:	2023.02.22-2023.03.17
Issued by:	CCIC Southern Testing Co., Ltd.
Lab Location:	Electronic Testing Building, No. 43 Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China.
	Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of 38 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

Test Report

Product Name.....:	RemindTag
Brand Name.....:	xminnov
Trade Name.....:	xminnov
Applicant.....:	Xiamen Innov Information Technology Co.,LTD
Applicant Address.....:	No.943,Tonglong Second RD,Hongtang Town,Tong an District,Xiamen city , Fujian Province
Manufacturer.....:	Xiamen Innov Information Technology Co.,LTD
Manufacturer Address .....:	No.943,Tonglong Second RD,Hongtang Town,Tong an District,Xiamen city , Fujian Province
Test Standards.....:	47 CFR Part 15 Subpart C ANSI C63.10-2013
Test Result .....:	PASS

Tested by .....: Kim Li 2023.03.21

Kim Li, Test Engineer

Reviewed by .....: Chris You 2023.03.21

Chris You, Senior Engineer

Approved by .....: Yang Fan 2023.03.21

Yang Fan, Manager

TABLE OF CONTENTS

RF TEST REPORT **1**

1. GENERAL INFORMATION **5**

1.1. EUT Description 5

1.2. Test Standards and Results 6

1.3. Table for Supporting Units 7

1.4. EUT Operation Test Setup 7

1.5. Test environment and mode 7

1.6. Laboratory Facilities 8

2. TEST REQUIREMENTS **9**

2.1. Antenna requirement 9

2.2. Maximum Conducted Output Power 10

2.3. 6dB and 99% Bandwidth 12

2.4. Power spectral density (PSD) 14

2.5. Conducted Band Edges and Spurious Emissions 16

2.6. Radiated Band Edge and Spurious Emission 18

3. LIST OF MEASURING EQUIPMENT **26**

4. UNCERTAINTY OF EVALUATION **27**

APPENDIX A **28**

Change History		
Issue	Date	Reason for change
1.0	2023.03.21	First edition

1. General Information

1.1. EUT Description

Product Name	RemindTag
Hardware Version	IVF-BT11-V1.1
Software Version	20221031
EUT supports Radios application	Bluetooth LE V5.0
Frequency Range	2402MHz~2480MHz
Channel Number	40
Bit Rate of Transmitter	1/2Mbps
Modulation Type	GFSK
Antenna Type	PCB Antenna
Antenna Gain	0.4dBi
Power supply	DC 3V

Note 1: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

Note 2: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

1.2. Test Standards and Results

The purpose of the report is to conduct testing according to the following FCC certification standards:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart C	Radio Frequency Devices
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3	KDB 558074 D01 15.247 Meas Guidance v05r02	Cuidance for Compliance Measurement on Digital Transmission Systems, Frequency Hopping Spread Spectrum Systems, and Hybrid System Devices Operating under Section 15.247 of the FCC Rules

Test detailed items/section required by FCC rules and results are as below:

No.	Section in CFR 47	Description	Result
1	15.203 15.247(c)	Antenna Requirement	PASS
2	15.247(b)(3)	Peak Conducted Output Power	PASS
3	15.247(a)(2)	6dB and 99% Bandwidth	PASS
4	15.247(d)	Conducted Band Edges and Spurious Emission	PASS
5	15.247(e)	Power spectral density (PSD)	PASS
6	15.209 15.205 15.247(d)	Radiated Band Edges and Spurious Emission	PASS

Note 1: The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10-2013.

Note 2: These RF tests were performed according to the method of measurements prescribed in KDB 558074 D01 15.247 Meas Guidance v05r02.

40 channels are provided for Bluetooth LE

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz
Note: Channel 0, 19 &20 selected for GFSK.							

Test Items	Modulation Type	Data Rate	Channel
Peak Conducted Output Power Power Spectral Density 6dB and 99% Bandwidth Conducted Spurious Emission Radiated Spurious Emission	GFSK	1Mbps/2Mbps	0/19/39
Band Edge	GFSK	1Mbps/2Mbps	0/39

1.3. Table for Supporting Units

No.	Equipment	Brand Name	Model Name	Manufacturer	Serial No.	Note
1	Laptop	HP	TPN-Q221	HP	5CD14347QB	FCC DOC

1.4. EUT Operation Test Setup

For RF test items, an engineering test program was provided and enable to make EUT transmitting.

1.5. Test environment and mode

During the measurement, the environmental conditions were within the listed ranges:

Operating Environment	
Temperature	15°C - 35°C
Humidity	30% -60%
Atmospheric Pressure	86KPa-106KPa
Test mode:	
Continuously transmitting mode	Keep the EUT in continuous transmitting with modulation

1.6. Laboratory Facilities

FCC-Registration No.: 406086

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until April 19th, 2023.

ISED Registration: 11185A-1

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until Jun. 30th, 2023.

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

2. Test Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

And according to FCC 47 CFR Section 15.247(c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

2.1.2. Antenna Information

Antenna Category: PCB Antenna

The PCB antenna is directly connected to the EUT's antenna port and cannot be removed.

Antenna General Information:

No.	EUT	Operating frequency range	Ant. Type	Ant. Gain
1	RemindTag	2402-2480MHz	PCB	0.4dBi

2.1.3. Result: comply

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Maximum Conducted Output Power

2.2.1. Limit of Peak Output Power

For DTSs employing digital modulation techniques operating in the bands 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W.

2.2.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.2.3. Test Setup



2.2.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 Section 11.9.1.1.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings:

   RBW ≥ DTS bandwidth / VBW ≥ 3*RBW / Sweep time: Auto couple / Detector mode: Peak / Trace mode: Max hold / Allow trace to fully stabilize / Use peak marker function to determine the peak amplitude level.
5. Record the measurement results in the test report.

2.2.5. Test Result of Peak Output Power

Please refer to Appendix A for detail.

2.3. 6dB and 99% Bandwidth

2.3.1. Limit of 6dB and 99% Bandwidth

The minimum 6 dB Occupied bandwidth shall be at least 500 kHz.

2.3.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.3.3. Test Setup



2.3.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 Section 11.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the spectrum analyzer “Channel Bandwidth” function to easurement the 6dB EBW and 99% OBW.
5. For 6dB EBW Use the following spectrum analyzer settings:
   RBW: 100kHz / VBW: 300kHz / Detector: Peak / Trace mode: Max hold / Sweep time: Auto couple / Allow trace to fully stabilize.
6. For 99% OBW Use the following spectrum analyzer settings:
   Set RBW = approximately 1% EBW or 1.5 times to 5.0 times the OBW, VBW $\geq 3 \times$ RBW.
7. Record the measurement results in the test report.

2.3.5. Test Results of 6dB Bandwidth

Please refer to Appendix A for detail.

2.4. Power spectral density (PSD)

2.4.1. Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

2.4.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.4.3. Test Setup



2.4.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 Section 11.10.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings:

   Set instrument center frequency to DTS channel center frequency / Set the span to 1.5 times the DTS bandwidth / RBW:3kHz / VBW:10kHz / Detector: Peak / Sweep time: Auto couple / Trace mode: Max hold / Allow trace to fully stabilize / Use the peak marker function to determine the maximum power level.
5. Record the measurement results in the test report.

2.4.5. Test Results of Power spectral density

Please refer to Appendix A for detail.

2.5. Conducted Band Edges and Spurious Emissions

2.5.1. Limit of Conducted Band Edges and Spurious Emissions

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is perating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that.

2.5.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.5.3. Test Setup



2.5.4. Test Procedure

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 Section 11.11 and 11.13.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings:

   Reference level measurement: Set spectrum analyzer center frequency to DTS channel center frequency / Set the span to ≥1.5 times the DTS bandwidth / RBW: 100kHz / VBW: 300kHz / Detector: Peak / Sweep time: Auto couple / Trace mode: Max hold / Allow trace to fully stabilize / Use the peak marker function to determine the maximum PSD level and attenuate it by 20dB.

   Emission level measurement: Set the center frequency and span to encompass frequency range to be measured / RBW: 100kHz / VBW: 300kHz / Detector: Peak / Sweep time: Auto couple / Trace mode: Max hold / Allow trace to fully stabilize / Use the peak marker function to determine the maximum amplitude level.
6. Record the measurement results in the test report.

2.5.5. Test Results of Conducted Band Edges and Spurious Emissions

Please refer to Appendix A for detail.

2.6. Radiated Band Edge and Spurious Emission

2.6.1. Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level. If the transmitter uses an RMS average conducted power limit, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the estricted bands, as defi ned in §15.205(a), must also comply with the radiated emission limits specifi ed in §15.209(a).

§15.209(a) Radiated emission limits:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Restricted bands of operation refer to §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41	/	/	/
Note: [1]Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. [2]Above 38.6.			

2.6.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.6.3. Test Setup

For radiated emissions from 9 kHz to 30 MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



2.6.4. Test Procedures

1. The EUT was placed on the top of a rotating table 0.8m for below 1GHz and 1.5m for above 1GHz above the ground at a 3 meters semi-anechoic chamber.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on thetop of a variable height antenna tower.
3. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported.Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then

reported in a data sheet.

7. For the radiated emission test above 1GHz:

   Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is ≥ 1/T(Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

2.6.5. Test Results of Radiated Band Edge and Spurious Emission

For 9 kHz to 30MHz

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

For 30MHz to 1000MHz



Frequency (MHz)	QuasiPeak (dB µ V/m)	Bandwidth (kHz)	Corr.Factor (dB/m)	Antenna height (cm)	Limit (dB µ V/m)	Margin (dB)	Polarity
31.020000	20.10	120.000	19.3	100.0	40.0	19.90	Horizontal
55.060000	12.00	120.000	8.6	100.0	40.0	28.00	Horizontal
168.050000	18.60	120.000	12.5	100.0	43.5	24.90	Horizontal
183.060000	19.10	120.000	11.0	100.0	43.5	24.40	Horizontal
745.050000	23.40	120.000	21.9	100.0	46.0	22.60	Horizontal
947.050000	26.70	120.000	24.3	100.0	46.0	19.30	Horizontal

Test Result : Pass

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB).
3. Margin value = Limit value – Emission Level.
4. The other emission levels were very low against the limit.
5. All of the EUT Configure Mode were tested and found GFSK-1Mbps-2402MHz mode is the worst mode, the worst case is recorded in this report.



Frequency (MHz)	QuasiPeak (dB µ V/m)	Bandwidth (kHz)	Corr.Factor (dB/m)	Antenna height (cm)	Limit (dB µ V/m)	Margin (dB)	Polarity
30.000000	20.84	120.000	19.3	100.0	40.0	19.16	Vertical
59.060000	11.00	120.000	8.6	100.0	40.0	29.00	Vertical
103.650000	15.73	120.000	10.9	100.0	43.5	27.77	Vertical
181.050000	16.40	120.000	11.0	100.0	43.5	27.10	Vertical
763.050000	23.43	120.000	22.1	100.0	46.0	22.57	Vertical
906.050000	28.40	120.000	24.3	100.0	46.0	17.60	Vertical

Test Result : Pass

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB).
3. Margin value = Limit value – Emission Level.
4. The other emission levels were very low against the limit.
5. All of the EUT Configure Mode were tested and found GFSK-1Mbps-2402MHz mode is the worst mode, the worst case is recorded in this report.

For 1GHz to 25GHz

GFSK_2402MHz									
Frequency (MHz)	Emssion Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
2390.00	44.89	74.00	-29.11	1.40	180	43.59	1.30	Horizontal	Peak
2390.00	36.73	54.00	-17.27	1.40	180	35.43	1.30	Horizontal	Average
4804.00	56.07	74.00	-17.93	1.40	180	49.67	6.40	Horizontal	Peak
4804.00	50.69	54.00	-3.31	1.40	180	44.29	6.40	Horizontal	Average
7206.00	59.05	74.00	-14.95	1.40	180	49.75	9.30	Horizontal	Peak
7206.00	53.00	54.00	-1.00	1.40	180	43.70	9.30	Horizontal	Average
2390.00	44.76	74.00	-29.24	1.60	150	43.46	1.30	Vertical	Peak
2390.00	36.72	54.00	-17.28	1.60	150	35.42	1.30	Vertical	Average
4804.00	55.66	74.00	-18.34	1.60	150	49.26	6.40	Vertical	Peak
4804.00	50.96	54.00	-3.04	1.60	150	44.56	6.40	Vertical	Average
7206.00	59.78	74.00	-14.22	1.60	150	50.48	9.30	Vertical	Peak
7206.00	51.85	54.00	-2.15	1.60	150	42.55	9.30	Vertical	Average
GFSK_2440MHz									
Frequency (MHz)	Emssion Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
4880.00	56.48	74.00	-17.52	1.40	180	50.08	6.40	Horizontal	Peak
4880.00	50.59	54.00	-3.41	1.40	180	44.19	6.40	Horizontal	Average
7320.00	58.58	74.00	-15.42	1.40	180	49.18	9.40	Horizontal	Peak
7320.00	53.15	54.00	-0.85	1.40	180	43.75	9.40	Horizontal	Average
4880.00	55.40	74.00	-18.60	1.60	150	49.00	6.40	Vertical	Peak
4880.00	51.25	54.00	-2.75	1.60	150	44.85	6.40	Vertical	Average
7320.00	59.62	74.00	-14.38	1.60	150	50.22	9.40	Vertical	Peak
7320.00	52.25	54.00	-1.75	1.60	150	42.85	9.40	Vertical	Average

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)

3. Margin value = Emission Level – Limit value

4.The emission levels of other frequencies are very lower than the limit and not show in test report.

GFSK_2480MHz									
Frequency (MHz)	Emssion Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
2483.50	45.09	74.00	-28.91	1.40	180	42.49	2.60	Horizontal	Peak
2483.50	37.90	54.00	-16.10	1.40	180	35.30	2.60	Horizontal	Average
4960.00	57.87	74.00	-16.13	1.40	180	51.17	6.70	Horizontal	Peak
4960.00	52.75	54.00	-1.25	1.40	180	46.05	6.70	Horizontal	Average
7440.00	59.43	74.00	-14.57	1.40	180	49.93	9.50	Horizontal	Peak
7440.00	53.16	54.00	-0.84	1.40	180	43.66	9.50	Horizontal	Average
2483.50	45.28	74.00	-28.72	1.60	150	42.68	2.60	Vertical	Peak
2483.50	37.07	54.00	-16.93	1.60	150	34.47	2.60	Vertical	Average
4960.00	52.78	74.00	-21.22	1.60	150	46.08	6.70	Vertical	Peak
4960.00	47.01	54.00	-6.99	1.60	150	40.31	6.70	Vertical	Average
7440.00	57.08	74.00	-16.92	1.60	150	47.58	9.50	Vertical	Peak
7440.00	49.49	54.00	-4.51	1.60	150	39.99	9.50	Vertical	Average

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)

3. Margin value = Emission Level – Limit value

4.The emission levels of other frequencies are very lower than the limit and not show in test report.

3. List of measuring equipment

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Power Meter	R&S	NRP-Z31	A141001975	2022.04.21	2023.04.20
2	EMI Test Receiver	ROHDE&SCHWARZ	ESW26	A180502935	2022.07.21	2023.07.20
3	5M Anechoic Chamber	Albatross	SAC-5MAC 12.8x6.8x6.4m	A0304210	2022.06.17	2025.06.16
4	Loop Antenna	Schwarz beck	HFH2-Z2	A0304220	2022.05.02	2025.05.01
5	Broadband antenna (30MHz~1GHz)	R&S	HL562	A0304224	2020.06.19	2023.06.18
6	EMI Horn Ant. (1-18G)	ETC	1209	A150402241	2021.01.02	2024.01.01
7	Horn antenna (18GHz~26.5GHz)	AR	AT4510	A0804450	2020.06.19	2023.06.18
8	Amplifier 30M~1GHz	MILMEGA	80RF1000-10004	A140101634	2020.09.22	2023.09.21
9	Amplifier 1G~18GHz	MILMEGA	AS0104R-800/400	A160302517	2022.12.13	2023.12.12
10	Spectrum Analyzer	KEYSIGHT	N9030A	A160702554	2023.02.20	2024.02.19
11	Test Receiver	R&S	ESIB7	A0501375	2022.04.18	2023.04.17
12	Broadband Ant.	2786	ETC	A150402240	2021.09.16	2024.03.03
13	3M Anechoic Chamber	Albatross	SAC-3MAC 9*6*6m	A0412375	2019.03.26	2023.03.25
14	Test Receiver	KEYSIGHT	N9038A	A141202036	2022.07.21	2023.07.20
15	LISN	ROHDE&SCHWARZ	ENV216	A140701847	2022.07.21	2023.07.20
16	Cable	MATCHING PAD	W7	/	2022.07.21	2023.07.20

4. Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence . The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of AC Power Line Conducted Emission Measurement (150kHz~30MHz)

Measuring Uncertainty for a level of confidence of 95%(U=2Uc(y))	2.8dB

Uncertainty of Radiated Emission Measurement (9kHz~30MHz)

Measuring Uncertainty for a level of confidence of 95%(U=2Uc(y))	3.5dB

Uncertainty of Radiated Emission Measurement (30MHz~1GHz)

Measuring Uncertainty for a level of confidence of 95%(U=2Uc(y))	3.91dB

Uncertainty of Radiated Emission Measurement (1GHz~18GHz)

Measuring Uncertainty for a level of confidence of 95%(U=2Uc(y))	4.5dB

Uncertainty of Radiated Emission Measurement (18GHz~40GHz)

Measuring Uncertainty for a level of confidence of 95%(U=2Uc(y))	4.9dB

Uncertainty of RF Conducted Measurement (9kHz~40GHz)

Measuring Uncertainty for a level of confidence of 95%(U=2Uc(y))	1.3dB

Appendix A

RF Output Power

Test Result and Data

1MHz Bandwidth						
Test Frequency	Conducted Power(dBm)	Ant. Gain (dBi)	EIRP (dBm)	Conducted Power Limit (dBm)	EIRP Limit(dBm)	Result
2402	-2.056	0.4	-1.656	30	36.02	Pass
2440	-1.965	0.4	-1.565	30	36.02	Pass
2480	-1.981	0.4	-1.581	30	36.02	Pass

2MHz Bandwidth						
Test Frequency	Conducted Power(dBm)	Ant. Gain (dBi)	EIRP (dBm)	Conducted Power Limit (dBm)	EIRP Limit(dBm)	Result
2402	-2.048	0.4	-1.648	30	36.02	Pass
2440	-1.983	0.4	-1.583	30	36.02	Pass
2480	-1.998	0.4	-1.598	30	36.02	Pass

Output Power：2402MHz - 1MHz Bandwidth	Output Power：2402MHz - 2MHz Bandwidth
	
Output Power：2440MHz - 1MHz Bandwidth	**Output Power：2440MHz - 2MHz Bandwidth**
	
Output Power：2480MHz - 1MHz Bandwidth	**Output Power：2480MHz - 2MHz Bandwidth**
	

Power Spectral Density
Test Result and Data

1MHz Bandwidth			
Test Frequency	PSD(dBm/3kHz)	Limit(dBm/3kHz)	Result
2402	-14.672	8	Pass
2440	-14.631		Pass
2480	-14.639		Pass

2MHz Bandwidth			
Test Frequency	PSD(dBm/3kHz)	Limit(dBm/3kHz)	Result
2402	-19.035	8	Pass
2440	-19.048		Pass
2480	-18.933		Pass

Power spectral density：2402MHz - 1MHz Bandwidth	Power spectral density：2402MHz - 2MHz Bandwidth
	
Power spectral density：2440MHz - 1MHz Bandwidth	Power spectral density：2440MHz - 2MHz Bandwidth
	
Power spectral density：2480MHz - 1MHz Bandwidth	Power spectral density：2480MHz - 2MHz Bandwidth
	

6dB and 99% Occupied BandWidth

Test Result and Data

1MHz Bandwidth			
Test Frequency	6dBOccupy Bandwidth(kHz)	Min Limit(kHz)	Result
2402	687.393	>500	Pass
2440	682.438		Pass
2480	681.677		Pass

2MHz Bandwidth			
Test Frequency	6dBOccupy Bandwidth(kHz)	Min Limit(kHz)	Result
2402	1133.425	>500	Pass
2440	1131.186		Pass
2480	1122.826		Pass

BLE 99% Occupied Bandwidth - 1MHz Bandwidth			
Test Frequency	99% Occupy Bandwidth(MHz)	Limit(MHz)	Result
2402	1.030	N/A	Pass
2440	1.030		Pass
2480	1.031		Pass

BLE 99% Occupied Bandwidth - 2MHz Bandwidth			
Test Frequency	99% Occupy Bandwidth(MHz)	Limit(MHz)	Result
2402	2.051	N/A	Pass
2440	2.051		Pass
2480	2.053		Pass

1MHz Bandwidth:

6dB Bandwidth：2402MHz	99% Bandwidth：2402MHz
	
6dB Bandwidth：2440MHz	99% Bandwidth：2440MHz
	
6dB Bandwidth：2480MHz	99% Bandwidth：2480MHz
	

2MHz Bandwidth:

6dB Bandwidth：2402MHz	99% Bandwidth：2402MHz
	
6dB Bandwidth：2440MHz	99% Bandwidth：2440MHz
	
6dB Bandwidth：2480MHz	99% Bandwidth：2480MHz
	

Conducted Band Edges and Spurious Emissions
Test Result and Data
1MHz Bandwidth:

,Plot ,1Transmitter Spurious Emission ： 2402,Referecy Level	,Plot ,1Transmitter Spurious Emission ： 2440,Referecy Level
	
,Plot ,1Transmitter Spurious Emission ： 2480,Referecy Level	,Plot ,2Conducted Emission：2402 ,Band Edge
	
,Plot ,2Conducted Emission：2440 ,Band Edge	,Plot ,2Conducted Emission：2480 ,Band Edge
	

,Plot ,3Transmitter Spurious Emission ： 2402,30MHz~2310MHz	,Plot ,3Transmitter Spurious Emission ： 2440,30MHz~2310MHz
	
,Plot ,3Transmitter Spurious Emission ： 2480,30MHz~2310MHz	,Plot ,4Transmitter Spurious Emission ： 2402,2500MHz~25000MHz
	
,Plot ,4Transmitter Spurious Emission ： 2440,2500MHz~25000MHz	,Plot ,4Transmitter Spurious Emission ： 2480,2500MHz~25000MHz
	

2MHz Bandwidth:

,Plot ,1Transmitter Spurious Emission ： 2402,Referecy Level	,Plot ,1Transmitter Spurious Emission ： 2440,Referecy Level
	
,Plot ,1Transmitter Spurious Emission ： 2480,Referecy Level	,Plot ,2Conducted Emission：2402 ,Band Edge
	
,Plot ,2Conducted Emission：2440 ,Band Edge	,Plot ,2Conducted Emission：2480 ,Band Edge
	

,Plot ,3Transmitter Spurious Emission ： 2402,30MHz~2310MHz	,Plot ,3Transmitter Spurious Emission ： 2440,30MHz~2310MHz
	
,Plot ,3Transmitter Spurious Emission ： 2480,30MHz~2310MHz	,Plot ,4Transmitter Spurious Emission ： 2402,2500MHz~25000MHz
	
,Plot ,4Transmitter Spurious Emission ： 2440,2500MHz~25000MHz	,Plot ,4Transmitter Spurious Emission ： 2480,2500MHz~25000MHz
	

END OF REPORT