

Sky Light Imaging Limited

Application
For
Certification

FCC ID: 2ABT4HPC02

Parrot Cloud Camera

Model: HPC02B
Additional Model: HPC02A

WiFi Transceiver

Report No.: 160801031SZN-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-15]

Prepared and Checked by:

Approved by:

Sign on file

Jenner Liu
Engineer

Kidd Yang
Senior Project Engineer
Date: September 07, 2016

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF no.: FCC 15C_Tx_c

Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch

6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751 Website: www.china.intertek-etlsemko.com

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Product Labeling
<i>EXHIBIT 7:</i>	Technical Specifications
<i>EXHIBIT 8:</i>	Instruction Manual
<i>EXHIBIT 9:</i>	Confidentiality Request
<i>EXHIBIT 10:</i>	Miscellaneous Information
<i>EXHIBIT 11:</i>	Test Equipment List

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

Parrot Cloud Camera

Model: HPC02B

Additional Model: HPC02A

FCC ID: 2ABT4HPC02

This report concerns (check one) Original Grant ☒ Class II Change ☐

Equipment Type: DTS - Part 15 Digital Transmission Systems (WiFi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until :
date

Company Name agrees to notify the Commission by:
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-15] Edition] provision.

Report prepared by:

Jenner Liu
Intertek Testing Services Shenzhen Ltd.
Kejiyuan Branch
6F, Block D, Huahan Building, Langshan Road,
Nanshan District, Shenzhen, P. R. China
Phone: (86 755) 8614 0639
Fax: (86 755) 8614 6751

INTERTEK TESTING SERVICES

Table of Contents

1.0	Summary of Test results	2
2.0	<u>General Description</u>	4
2.1	Product Description	4
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology.....	5
2.4	Test Facility	5
3.0	<u>System Test Configuration</u>.....	7
3.1	Justification	7
3.2	EUT Exercising Software	7
3.3	Special Accessories	8
3.4	Measurement Uncertainty	8
3.5	Equipment Modification	8
3.6	Support Equipment List and Description	8
4.0	<u>Measurement Results</u>	10
4.1	Maximum Conducted Output Power at Antenna Terminals.....	10
4.2	Minimum 6 dB RF Bandwidth.....	12
4.3	Maximum Power Density Reading	18
4.4	Out of Band Conducted Emissions.....	24
4.5	Out of Band Radiated Emissions.....	37
4.6	Transmitter Radiated Emissions in Restricted Bands	38
4.7	Field Strength Calculation	39
4.8	Radiated Spurious Emission	40
4.9	Conducted Emission	52
4.10	Radiated Emissions from Digital Section of Transceiver.....	55
4.11	Transmitter Duty Cycle Calculation and Measurements	56
5.0	<u>Equipment Photographs</u>	58
6.0	<u>Product Labelling</u>.....	60
7.0	<u>Technical Specifications</u>	62
8.0	<u>Instruction Manual</u>	64
9.0	<u>Confidentiality Request</u>	66
10.0	<u>Discussion of Pulse Desensitization</u>	68
11.0	<u>Test Equipment List</u>.....	70

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

INTERTEK TESTING SERVICES

EXHIBIT 1

SUMMARY OF TEST RESULTS

INTERTEK TESTING SERVICES

1.0 Summary of Test results

Parrot Cloud Camera

Model: HPC02B

Additional Model: HPC02A

FCC ID: 2ABT4HPC02

TEST	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

EXHIBIT 2

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is a Parrot Cloud Camera with Wi-Fi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing. The EUT was powered by AC/DC adapter with input of 100-240Vac, 50/60Hz, 0.35A and output of 5Vdc, 1.0A. For more detailed features description, please refer to the user's manual.

The Model: HPC02A is the same as the Model: HPC02B in hardware aspect, the electrical part are the same except HPC02A without TF Card slot, they are differences in appearance and model number as trading purpose.

HPC02A and HPC02B were tested respectively, only the worst data was reported in this report.

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM, CCK, DQPSK, DBPSK.

Antenna Type: Integral Antenna.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

INTERTEK TESTING SERVICES

2.2 Related Submittal(s) Grants

This is an application for certification of:

DTS- Part 15 Digital Transmission Systems (Wi-Fi transmitter portion), and there is no corresponding unit for certification.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013) and KDB 558074 D01 v03r05. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.4 Test Facility

The Semi-Anechoic chamber and shield room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, Block D, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

EXHIBIT 3
SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by AC/DC Adapter (Input: 120Vac, 60Hz, Output: 5Vdc, 1.0A) during the testing. Only the worst case data was reported.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m up to 1GHz and 1.5 m above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

The rear of unit shall be flushed with the rear of the table when it was powered by adapter up to 1GHz and placed in the centre of turntable above 1GHz.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

INTERTEK TESTING SERVICES

3.3 Special Accessories

N/A.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

3.5 Equipment Modification

Any modifications installed previous to testing by Sky Light Imaging Limited will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

3.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
TF Card	SanDisk	4G
Adapter	G-TiDE	ASSA54A-050100 Input: AC 100~240V, 50/60Hz, 0.35A; Output: DC 5.0V, 1.0A

INTERTEK TESTING SERVICES

EXHIBIT 4

MEASUREMENT RESULTS

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter have a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (Antenna Gain = 2.0dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	17.2	52.481
Middle Channel: 2437	18.1	64.565
High Channel: 2462	18.1	64.565

IEEE 802.11g (Antenna Gain = 2.0dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	20.5	112.202
Middle Channel: 2437	20.1	102.329
High Channel: 2462	20.0	100.000

INTERTEK TESTING SERVICES

IEEE 802.11n-HT20 (Antenna Gain = 2.0dBi) (16QAM, 6.5Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	19.0	79.433
Middle Channel: 2437	17.6	57.544
High Channel: 2462	17.6	57.544

Cable loss: 0.5 dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 20.5dBm

For RF Exposure, the information is saved with filename: RF exposure.pdf.

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a)(2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v03r05. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	10.140
2437	10.140
2462	10.140

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	16.320
2437	16.320
2462	16.320

IEEE 802.11n-HT20 (16QAM, 6.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	17.340
2437	17.520
2462	17.220

The test plots are attached as below.



TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001


INTERTEK TESTING SERVICES

802.11b




TRF no.: FCC 15C_TX_b
 FCC ID: 2ABT4HPC02
 Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES





802.11g





TRF no.: FCC 15C_TX_b
 FCC ID: 2ABT4HPC02
 Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES




INTERTEK TESTING SERVICES

802.11 n-HT20



TRF no.: FCC 15C_TX_b
FCC ID: 2ABT4HPC02
Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v03r05.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/3 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	4.82
2437	3.05
2462	3.01

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	1.78
2437	1.66
2462	1.72

IEEE 802.11n-HT20 (16QAM, 6.5Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	1.12
2437	0.34
2462	-0.40

The test plots are attached as below.



TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001


INTERTEK TESTING SERVICES

802.11b




TRF no.: FCC 15C_TX_b
FCC ID: 2ABT4HPC02
Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES





802.11g





TRF no.: FCC 15C_TX_b
FCC ID: 2ABT4HPC02
Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES




INTERTEK TESTING SERVICES

802.11 n-HT20



TRF no.: FCC 15C_TX_b
FCC ID: 2ABT4HPC02
Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited
Date of Test: August 09 , 2016
Model: HPC02B

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v03r05.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n-HT20.



The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

The test plots are attached as below.

INTERTEK TESTING SERVICES

802.11b

Channel 01 (2412MHz) Reference Level: 4.82dBm




TRF no.: FCC 15C_TX_b


FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES




Channel 06 (2437MHz) Reference Level: 3.05dBm




TRF no.: FCC 15C_TX_b
 FCC ID: 2ABT4HPC02
 Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES





Channel 11 (2462MHz) Reference Level: 3.01dBm



TRF no.: FCC 15C_TX_b
FCC ID: 2ABT4HPC02
Report No.: 160801031SZN-001



INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES

802.11g

Channel 01 (2412MHz) Reference Level: 1.78dBm




TRF no.: FCC 15C_TX_b


FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES




Channel 06 (2437MHz) Reference Level: 1.66dBm




TRF no.: FCC 15C_TX_b
FCC ID: 2ABT4HPC02
Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES





Channel 11 (2462MHz) Reference Level: 1.72dBm



TRF no.: FCC 15C_TX_b
 FCC ID: 2ABT4HPC02
 Report No.: 160801031SZN-001



INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES

802.11 n-HT20

Channel 01 (2412MHz) Reference Level: 1.12dBm




TRF no.: FCC 15C_TX_b


FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES




Channel 06 (2437MHz) Reference Level: 0.34dBm




TRF no.: FCC 15C_TX_b
 FCC ID: 2ABT4HPC02
 Report No.: 160801031SZN-001



INTERTEK TESTING SERVICES



Channel 11 (2462MHz) Reference Level: -0.40dBm



TRF no.: FCC 15C_TX_b
 FCC ID: 2ABT4HPC02
 Report No.: 160801031SZN-001



TRF no.: FCC 15C_TX_b
FCC ID: 2ABT4HPC02
Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- ☒ Not required, since all emissions are more than 20dB below fundamental
☐ See attached data sheet

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited
Date of Test: August 09 , 2016
Model: HPC02B

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited
Date of Test: August 09 , 2016
Model: HPC02B

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission (802.11 b) at 2389.890MHz is passed by 4.7 dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

INTERTEK TESTING SERVICES


Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016


Model: HPC02B

Worst Case Operating Mode: 802.11 n-HT20 (TX-Channel 01)

Horizontal



Vertical



TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	30.000	32.5	20.0	17.8	30.3	40.0	-9.7
Horizontal	256.010	39.2	20.0	14.3	33.5	46.0	-12.5
Horizontal	479.595	35.3	20.0	20.3	35.6	46.0	-10.4
Vertical	30.970	32.4	20.0	17.3	29.7	40.0	-10.3
Vertical	53.280	38.7	20.0	8.5	27.2	40.0	-12.8
Vertical	119.240	39.0	20.0	9.3	28.3	43.5	-15.2

- NOTES: 1. Quasi-Peak detector is used except for others stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. All emissions are below the QP limit.

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

Mode: 802.11b (TX-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4824.000	59.3	36.1	34.2	57.4	74.0	-16.6
Horizontal	*2387.870	62.6	36.2	28.2	54.6	74.0	-19.4

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4824.000	44.2	36.1	34.2	42.3	54.0	-11.7
Horizontal	*2387.870	52.3	36.2	28.2	44.3	54.0	-9.7

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

Mode: 802.11b (TX-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	57.3	36.1	34.6	55.8	74.0	-18.2
Horizontal	*7311.000	51.6	35.6	37.1	53.1	74.0	-20.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	42.9	36.1	34.6	41.4	54.0	-12.6
Horizontal	*7311.000	38.6	35.6	37.1	40.1	54.0	-13.9

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

Mode: 802.11b (TX-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	56.4	36.1	34.6	54.9	74.0	-19.1
Horizontal	*7386.000	53.9	35.6	37.2	55.5	74.0	-18.5
Horizontal	*2485.130	61.7	36.3	28.0	53.4	74.0	-20.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	40.4	36.1	34.6	38.9	54.0	-15.1
Horizontal	*7386.000	39.0	35.6	37.2	40.6	54.0	-13.4
Horizontal	*2485.130	50.8	36.3	28.0	42.5	54.0	-11.5

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

Mode: 802.11g (TX-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	64.2	36.1	34.2	62.3	74.0	-11.7
Horizontal	*2389.900	64.5	35.6	27.8	56.7	74.0	-17.3

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	46.4	36.1	34.2	44.5	54.0	-9.5
Horizontal	*2389.900	52.8	35.6	27.8	45.0	54.0	-9.0

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

Mode: 802.11g (TX-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	61.7	36.1	34.6	60.2	74.0	-13.8
Horizontal	*7311.000	56.3	35.6	37.1	57.8	74.0	-16.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	43.0	36.1	34.6	41.5	54.0	-12.5
Horizontal	*7311.000	42.2	35.6	37.1	43.7	54.0	-10.3

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

Mode: 802.11g (TX-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	61.0	36.1	34.6	59.5	74.0	-14.5
Horizontal	*7386.000	56.7	35.6	37.2	58.3	74.0	-15.7
Horizontal	*2483.620	69.5	35.6	28.0	61.9	74.0	-12.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	45.7	36.1	34.6	44.2	54.0	-9.8
Horizontal	*7386.000	41.9	35.6	37.2	43.5	54.0	-10.5
Horizontal	*2483.620	54.3	35.6	28.0	46.7	54.0	-7.3

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited
 Date of Test: August 09 , 2016
 Model: HPC02B
 Mode: 802.11 n-HT20 (TX-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	59.5	36.1	34.2	57.6	74.0	-16.4
Horizontal	*2389.890	72.1	35.6	27.8	64.3	74.0	-9.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	43.9	36.1	34.2	42.0	54.0	-12.0
Horizontal	*2389.890	57.1	35.6	27.8	49.3	54.0	-4.7

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited
 Date of Test: August 09 , 2016
 Model: HPC02B
 Mode: 802.11 n-HT20 (TX-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	59.8	36.1	34.2	57.9	74.0	-16.1
Horizontal	*7311.000	53.9	35.6	37.1	55.4	74.0	-18.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	43.9	36.1	34.2	42.0	54.0	-12.0
Horizontal	*7311.000	39.1	35.6	37.1	40.6	54.0	-13.4

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited
 Date of Test: August 09 , 2016
 Model: HPC02B
 Mode: 802.11 n-HT20 (TX-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	59.7	36.1	34.6	58.2	74.0	-15.8
Horizontal	*7386.000	53.4	35.6	37.2	55.0	74.0	-19.0
Horizontal	*2483.740	69.7	35.6	27.8	61.9	74.0	-12.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	43.8	36.1	34.6	42.3	54.0	-11.7
Horizontal	*7386.000	39.0	35.6	37.2	40.6	54.0	-13.4
Horizontal	*2483.740	56.3	35.6	27.8	48.5	54.0	-5.5

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

4.9 Conducted Emission

Worst Case Conducted emission at 0.462MHz is Passed by 13.7 dB margin

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

INTERTEK TESTING SERVICES


Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

Worst Case Operating Mode: 802.11 n-HT20 (TX-Channel 01)

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.230	36.8	L1	9.5	25.6	62.4
0.294	35.6	L1	9.6	24.8	60.4
1.218	34.1	L1	9.6	21.9	56.0
4.470	27.9	L1	9.7	28.1	56.0
9.522	33.4	L1	9.7	26.6	60.0
29.734	43.7	L1	10.9	16.3	60.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.230	30.2	L1	9.5	22.2	52.4
0.294	29.5	L1	9.6	20.9	50.4
1.218	28.5	L1	9.6	17.5	46.0
4.470	17.3	L1	9.7	28.7	46.0
9.522	24.3	L1	9.7	25.7	50.0
29.734	30.4	L1	10.9	19.6	50.0

TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES


Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 01)

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.170	38.9	N	9.6	26.1	65.0
0.406	38.1	N	9.6	19.6	57.7
0.462	39.4	N	9.6	17.3	56.7
1.102	34.6	N	9.6	21.4	56.0
4.834	26.9	N	9.6	29.1	56.0
29.894	37.5	N	11.0	22.5	60.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.170	31.7	N	9.6	23.3	55.0
0.406	32.2	N	9.6	15.5	47.7
0.462	33.0	N	9.6	13.7	46.7
1.102	29.0	N	9.6	17.0	46.0
4.834	19.8	N	9.6	26.2	46.0
29.894	24.8	N	11.0	25.2	50.0

TRF no.: FCC 15C_TX_b

FCC ID: 2ABT4HPC02

Report No.: 160801031SZN-001

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

☒ Not required - No digital part

☐ Test results are attached

☐ Included in the separated report.

INTERTEK TESTING SERVICES

Applicant: Sky Light Imaging Limited

Date of Test: August 09 , 2016

Model: HPC02B

4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

EXHIBIT 5

EQUIPMENT PHOTOGRAPHS

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.doc & internal photos.pdf.

EXHIBIT 6

PRODUCT LABELLING

INTERTEK TESTING SERVICES

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

EXHIBIT 7

TECHNICAL SPECIFICATIONS

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 8
INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 9
CONFIDENTIALITY REQUEST

9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 10

MISCELLANEOUS INFORMATION

10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

EXHIBIT 11
TEST EQUIPMENT LIST

INTERTEK TESTING SERVICES

11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	23-May-2016	23-May-2017
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	23-May-2016	23-May-2017
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	15-Sep-2015	15-Sep-2016
SZ185-01	EMI Receiver	R&S	ESCI	100547	23-Jan-2016	23-Jan-2017
SZ061-09	Horn Antenna	ETS	3115	00092346	31-Oct-2015	31-Oct-2016
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	01-Sep-2015	01-Sep-2016
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	11-May-2016	11-May-2017
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	14-Jun-2016	14-Jun-2017
SZ056-06	Spectrum Analyzer	R&S	FSV40	101101	02-Jul-2016	02-Jul-2017
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	23-Jan-2016	23-Jan-2017
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	16-Apr-2016	16-Apr-2018
SZ062-02	RF Cable	RADIAL	RG 213U	--	30-Jun-2016	30-Dec-2016
SZ062-05	RF Cable	RADIAL	0.04-26.5GHz	--	06-Apr-2016	06-Oct-2016
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	--	06-Apr-2016	06-Oct-2016
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	--	23-May-2016	23-May-2017