



APPENDIX M

: MODULAR APPROVAL LETTER

	Requirements	EUT Conditions	Comply (Y/N)
Single Modular Approval Requirements			
1	The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with Part 15 limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation.	Shield is over the radio circuit module. Refer to the external photos.	Y
2	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.	All inputs to the modules are buffered through logic or microprocessor inputs. Refer to the Chip (RP-S2470) datasheet	Y
3	The modular transmitter must have its own power supply regulation. This is intended to ensure that the module will comply with Part 15 requirements regardless of the design of the power supplying circuitry in the device into which the module is installed.	Refer to the schematics	Y
4	The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). Any antenna used with the module must be approved with the module, either at the time of initial authorization or through a Class II permissive change. The "professional installation" provision of Section 15.203 may not be applied to modules.	Patch Antenna. Dipole Antenna Refer to the internal photos.	Y
5	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)).	The Module was tested in stand-alone configuration via a USB extension cable. Refer to the test setup photos.	Y
6	The modular transmitter must be labeled with its own FCC ID number, and, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.	Refer to the user manual	Y
7	The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured.	Refer to the user manual.	Y
8	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance.	Refer to the RF exposure statement for more details.	Y

Sincerely,



Jaehee Kang / General Manager
NEWRUN Inc.

1. INTRODUCTION

This guide explains features and specifications of RP-S2470 provided by RadioPulse. 'RP-S2470' mark in contents means that the feature is only applied to the RP-S2470.



1.1. Features

RF Transceiver

- ▶ Single-chip 2.4GHz RF Transceiver
- ▶ Low Power Consumption
- ▶ No External T/R Switch or Filter needed
- ▶ On-chip VCO, LNA, and PA
- ▶ Programmable Output Power up to +10dBm
- ▶ Direct Sequence Spread Spectrum
- ▶ O-QPSK Modulation
- ▶ Scalable Data Rate including 250Kbps specified in IEEE802.15.4: 31.25Kbps ~ 1Mbps
- ▶ RSSI Measurement
- ▶ Compliant to IEEE802.15.4

Hardwired MAC

- ▶ Two 256-byte circular FIFOs
- ▶ FIFO management
- ▶ AES Encryption/Decryption Engine(128 bit)
- ▶ CRC-16 Computation and Check

8051-Compatible MCU

- ▶ 8051 Compatible (single cycle execution)
- ▶ 64KB Embedded Flash Memory
- ▶ 6KB Data Memory
- ▶ 128-byte CPU dedicated Memory