

FCC - TEST REPORT

Report Number : **68.760.17.444.01** Date of Issue: January 17, 2018

Model : **7033-30-00, 7033-10-00, 7033-30-00, 7033-70-00**

Product Type : Label printer

Applicant : LEITZ ACCO Brands GmbH & Co., KG

Address : Siemensstrasse 64, 70469 Stuttgart, GERMANY

Production Facility : Longtech Plastic & Metal Works (shenzhen) Ltd.

Address : No. 14-15 Block, Jinbi Industrial Zone Huangtian,

Xixiang Town, Baoan District, 518128 Shenzhen,

PEOPLE'S REPUBLIC OF CHINA

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including
Appendices : 38

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1. Table of Contents

1.	Table of Contents	2
2.	Details about the Test Laboratory	3
3.	Description of the Equipment Under Test	4
4.	Summary of Test Standards.....	5
5.	Summary of Test Results.....	6
6.	General Remarks.....	7
7.	Systems test configuration	8
8.	Emission Test Result	9
8.1	Conducted Emission Test at AC mains terminals 150kHz – 30MHz	9
8.2	Radiated Emission Test 30MHz – 18000MHz.....	13
9.	Test Equipment List	37
10.	Measurement System Uncertainty.....	38



2. Details about the Test Laboratory

Details about the Test Laboratory

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13, Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2, Nanshan District,
Shenzhen City, 518052,
P. R. China

FCC Registration Number: 514049

Telephone: 86 755 8828 6998
Fax: 86 755 8828 5299

3. Description of the Equipment Under Test

Product: Label printer

Model no.: 7033-30-00

Brand Name: NIL

Options and accessories: DC Cable: 1.15m with one core, Shielded, Undetachable
AC Cable: 1.4m, Unshielded, Detachable
USB Cable: 1.94m, Shielded, Detachable

Rating: 24VDC, 4.0A (Supplied by Switching Power Adapter)
or 24VDC, 2405mAh (Supplied by Leltz Icon Battery Pack)
Switching Power Adapter (M/N: SRPS-09604), manufactured by
Shanghai ShenRui Electric Co., Ltd with the follow ratings:
Input: 100-240VAC, 2-1.2A, 50/60Hz
Output: 24VDC, 4.0A

Description of the EUT: 7033-30-00, 7033-10-00, 7033-30-00 and 7033-70-00 are the same
expect the model name and color of appearance.

Auxiliary Equipment (cable) Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N
Laptop	LENOVO	X240	L34015282
Laptop	LENOVO	T460S	PC-0DBR0H

4. Summary of Test Standards

Test Standards	
FCC Part 15 Subpart B 10-1-16 Edition	Unintentional Radiators

5. Summary of Test Results

Emission Tests				
FCC Part 15 Subpart B, 10-1-16 Edition				
Test Condition Class B	Pages	Test Result		
		Pass	Fail	N/A
Conducted Emission on AC 150kHz to 30MHz	9	☒	☐	☐
Radiated Emission (3 semi-anechoic chamber) 30MHz to 1000MHz	13	☒	☐	☐
Radiated Emission (3 semi-anechoic chamber) 1GHz to 18GHz	21	☒	☐	☐

6. General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2ABUI70333000 complies with Section 15.107, 15.109 of the FCC Part 15, Subpart B Rules.

7033-30-00, 7033-10-00, 7033-30-00 and 7033-70-00 are the same expect the model name and color of appearance. So the EMC full tests were applied on 7033-30-00, other models were deemed to fulfil the EMC requirement without the further test.

SUMMARY:

All tests according to the regulations cited on page 5 were

☒ - Performed

☐ - Not Performed

The Equipment under Test

☒ - **Fulfills** the general approval requirements.

☐ - **Does not** fulfill the general approval requirements.

Sample Received Date: August 07, 2017

Testing Start Date: August 07, 2017

Testing End Date: January 08, 2018

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:

Prepared by:

Trevor You



Nick Huang

Trevor You
EMC Senior Project Engineer

Nick Huang
EMC Project Engineer

7. Systems test configuration

Auxiliary Equipment Used during Test:


DESCRIPTION	MANUFACTURE R	MODEL NO.(SHIELD)	S/N(LENGTH)
Laptop	LENOVO	X240	L34015282
Laptop	LENOVO	T460S	PC-0DBR0H

8. Emission Test Result

8.1 Conducted Emission Test at AC mains terminals 150kHz – 30MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Test specification : Power Line, Live
 Comment : AC 120V/60Hz
 Date of test : 04 September 2017

Temperature (°C): 23.7 Relative Humidity (%): 58.4 Atmospheric Pressure(mbar) : 1007



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr.* (dB)
0.162000	45.91	---	65.36	19.45	L1	10.2
0.234000	38.43	---	62.31	23.88	L1	10.2
0.530000	33.78	---	56.00	22.22	L1	10.2
0.938000	30.39	---	56.00	25.61	L1	10.2
6.402000	25.71	---	60.00	34.29	L1	10.5
17.630000	28.16	---	60.00	31.84	L1	10.9

Final Result


Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr.* (dB)
---	---	---	---	---	---	---

Remark: "*" Correct factor=cable loss + LISN factor

Conducted Emission Test at AC mains terminals 150kHz – 30MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Test specification : Power Line, Neutral
 Comment : AC 120V/60Hz
 Date of test : 04 September 2017

Temperature (°C): 23.7 Relative Humidity (%): 58.4 Atmospheric Pressure(mbar) : 1007



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr.* (dB)
0.170000	45.95	---	64.96	19.01	N	10.3
0.206000	41.29	---	63.37	22.07	N	10.3
0.538000	33.49	---	56.00	22.51	N	10.4
1.018000	26.67	---	56.00	29.33	N	10.4
1.546000	26.32	---	56.00	29.68	N	10.4
18.122000	28.44	---	60.00	31.56	N	11.4

Final Result


Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr.* (dB)
---	---	---	---	---	---	---

Remark: "*" Correct factor=cable loss + LISN factor

Conducted Emission Test at AC mains terminals 150kHz – 30MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Test specification : Power Line, Live
 Comment : AC 120V/60Hz
 Date of test : 21 December 2017

Temperature (°C): 24.2 Relative Humidity (%): 58.6 Atmospheric Pressure(mbar) : 1009



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr.* (dB)
0.530000	24.15	---	56.00	31.85	L1	10.2
0.702000	18.88	---	56.00	37.12	L1	10.2
0.922000	18.25	---	56.00	37.75	L1	10.2
1.274000	18.31	---	56.00	37.69	L1	10.2
1.506000	17.66	---	56.00	38.34	L1	10.2
16.230000	28.63	---	60.00	31.37	L1	10.8

Final Result


Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr.* (dB)
---	---	---	---	---	---	---

Remark: "*" Correct factor=cable loss + LISN factor

Conducted Emission Test at AC mains terminals 150kHz – 30MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Test specification : Power Line, Live
 Comment : AC 120V/60Hz
 Date of test : 21 December 2017

Temperature (°C): 24.2 Relative Humidity (%): 58.6 Atmospheric Pressure(mbar) : 1009



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr.* (dB)
0.530000	24.15	---	56.00	31.85	L1	10.2
0.702000	18.88	---	56.00	37.12	L1	10.2
0.922000	18.25	---	56.00	37.75	L1	10.2
1.274000	18.31	---	56.00	37.69	L1	10.2
1.506000	17.66	---	56.00	38.34	L1	10.2
16.230000	28.63	---	60.00	31.37	L1	10.8

Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr.* (dB)
---	---	---	---	---	---	---


Remark: "*" Correct factor=cable loss + LISN factor

8.2 Radiated Emission Test 30MHz – 18000MHz

Radiated Emission Test 30MHz – 1000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Horizontal
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
99.779375	33.31	43.50	10.19	200.0	H	227.0	16.2
281.654375	35.08	46.00	10.92	200.0	H	190.0	18.8
338.035625	35.99	46.00	10.01	100.0	H	0.0	20.3
509.968125	31.86	46.00	14.14	100.0	H	88.0	23.5
707.423750	37.47	46.00	8.53	100.0	H	170.0	27.3
779.385625	40.82	46.00	5.18	200.0	H	162.0	28.8

Final_Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---		---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss

Radiated Emission Test 30MHz – 1000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Vertical
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
32.788750	31.56	40.00	8.44	100.0	V	326.0	15.4
50.145938	37.05	40.00	2.95	153.0	V	45.0	18.0
104.144375	33.78	43.50	9.72	100.0	V	298.0	16.3
220.483750	33.50	46.00	12.50	100.0	V	16.0	16.7
282.018125	34.70	46.00	11.30	100.0	V	161.0	19.2
755.256875	42.96	46.00	3.04	100.0	V	0.0	28.7

Final_Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
50.145938	31.08	40.00	8.92	153.0	V	45.0	18.0

Remark: "*" Corrector factor = Antenna Factor + Cable Loss

Radiated Emission Test 30MHz – 1000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Horizontal
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
66.071875	24.79	40.00	15.21	100.0	H	311.0	15.1
155.433125	26.96	43.50	16.54	200.0	H	98.0	13.0
259.950625	32.86	46.00	13.14	100.0	H	253.0	17.9
292.748750	37.38	46.00	8.62	100.0	H	42.0	19.1
337.186875	35.90	46.00	10.10	100.0	H	97.0	20.2
695.783750	36.14	46.00	9.86	100.0	H	144.0	27.3

Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---	---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss

Radiated Emission Test 30MHz – 1000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Vertical
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
45.580625	34.54	40.00	5.46	100.0	V	0.0	18.0
121.786250	31.63	43.50	11.87	100.0	V	310.0	14.3
220.483750	34.95	46.00	11.05	100.0	V	0.0	16.7
319.605625	34.12	46.00	11.88	200.0	V	154.0	19.6
691.540000	36.90	46.00	9.10	200.0	V	0.0	27.6
760.531250	37.42	46.00	8.58	100.0	V	0.0	28.9

Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---	---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss

Radiated Emission Test 30MHz – 1000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Horizontal
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
96.748125	31.09	43.50	12.41	200.0	H	282.0	15.6
207.873750	36.17	43.50	7.33	200.0	H	135.0	16.1
285.231250	41.49	46.00	4.51	100.0	H	125.0	18.8
688.266250	39.84	46.00	6.16	200.0	H	227.0	27.1
808.466562	41.81	46.00	4.19	100.0	H	180.0	28.9
860.683750	38.21	46.00	7.79	100.0	H	207.0	29.6

Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
808.466562	39.00	46.00	7.00	100.0	H	180.0	28.8

Remark: "*" Corrector factor = Antenna Factor + Cable Loss

Radiated Emission Test 30MHz – 1000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Vertical
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
36.001875	36.42	40.00	3.58	100.0	V	310.0	15.9
71.952500	32.38	40.00	7.62	200.0	V	108.0	13.1
104.116875	43.00	43.50	0.50	128.0	V	8.0	16.2
140.155625	36.84	43.50	6.66	100.0	V	0.0	13.0
220.544375	31.55	46.00	14.45	200.0	V	355.0	16.7
285.170625	33.61	46.00	12.39	200.0	V	99.0	19.2

Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
104.116875	31.78	43.50	11.72	128.0	V	8.0	16.3

Remark: "*" Corrector factor = Antenna Factor + Cable Loss

Radiated Emission Test 30MHz – 1000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Horizontal
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
136.275625	28.79	43.50	14.71	200.0	H	115.0	12.6
199.446875	33.03	43.50	10.47	100.0	H	78.0	16.1
218.077188	38.56	46.00	7.44	128.0	H	70.0	16.4
262.618125	36.72	46.00	9.28	100.0	H	78.0	18.1
295.355625	37.94	46.00	8.06	100.0	H	115.0	19.2
701.785625	37.84	46.00	8.16	100.0	H	0.0	27.4

Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
218.077188	31.82	46.00	14.18	128.0	H	70.0	16.3

Remark: "*" Corrector factor = Antenna Factor + Cable Loss

Radiated Emission Test 30MHz – 1000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Vertical
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
155.311875	24.75	43.50	18.75	200.0	V	0.0	13.4
210.359375	31.53	43.50	11.97	200.0	V	0.0	16.3
286.928750	35.71	46.00	10.29	200.0	V	35.0	19.3
494.104688	41.72	46.00	4.28	300.0	V	61.0	23.9
549.980625	31.90	46.00	14.10	200.0	V	155.0	24.7
698.511875	36.44	46.00	9.56	200.0	V	35.0	27.8

Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
494.104688	31.23	46.00	14.77	300.0	V	61.0	23.9

Remark: "*" Corrector factor = Antenna Factor + Cable Loss

Radiated Emission Test 1000MHz – 3000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Horizontal
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
1060.916667	43.49	---	74.00	30.51	100.0	H	354.0	-15.3
1123.666667	46.92	---	74.00	27.08	100.0	H	297.0	-14.9
1580.666667	40.40	---	74.00	33.60	100.0	H	330.0	-12.1
2163.000000	42.05	---	74.00	31.95	100.0	H	297.0	-8.7
2852.166667	47.67	---	74.00	26.33	100.0	H	354.0	-6.0

Final Result


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---		---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 1000MHz – 3000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Vertical
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
1201.916667	42.78	---	74.00	31.22	100.0	V	106.0	-14.2
1604.416667	45.97	---	74.00	28.03	100.0	V	10.0	-11.9
1604.416667	---	44.39	54.00	9.61	100.0	V	10.0	-11.9
1679.916667	45.98	---	74.00	28.02	100.0	V	10.0	-10.8
1999.166667	44.40	---	74.00	29.60	100.0	V	106.0	-9.0
2787.083333	46.70	---	74.00	27.30	100.0	V	38.0	-6.4

Final Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---		---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 1000MHz – 3000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Horizontal
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
1282.333333	44.03	---	74.00	29.97	100.0	H	63.0	-13.9
1649.000000	47.55	---	74.00	26.45	100.0	H	63.0	-11.6
2363.500000	53.89	---	74.00	20.11	100.0	H	222.0	-8.2
2570.500000	44.94	---	74.00	29.06	100.0	H	287.0	-7.5
2855.333333	44.45	---	74.00	29.55	100.0	H	136.0	-6.0

Final Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---		---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 1000MHz – 3000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Vertical
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
1597.833333	40.95	---	74.00	33.05	100.0	V	152.0	-11.9
1716.750000	44.00	---	74.00	30.00	100.0	V	174.0	-10.8
1801.250000	46.46	---	74.00	27.54	100.0	V	86.0	-10.2
2355.583333	49.03	---	74.00	24.97	100.0	V	97.0	-8.0
2394.166667	48.30	---	74.00	25.70	100.0	V	349.0	-7.9
2394.166667	---	48.11	54.00	5.89	100.0	V	349.0	-7.9
2478.000000	47.38	---	74.00	26.62	100.0	V	290.0	-7.9
2681.916667	46.54	---	74.00	27.46	100.0	V	119.0	-6.7
2681.916667	---	45.77	54.00	8.23	100.0	V	119.0	-6.7
2921.500000	44.08	---	74.00	29.92	100.0	V	247.0	-5.5

Final Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---	---	---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 1000MHz – 3000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Horizontal
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
1183.000000	45.10	---	74.00	28.90	100.0	H	76.0	-14.5
1857.583333	43.97	---	74.00	30.03	100.0	H	349.0	-9.5
2053.416667	46.79	---	74.00	27.21	100.0	H	76.0	-9.1
2478.500000	47.26	---	74.00	26.74	100.0	H	44.0	-8.0
2478.500000	---	45.60	54.00	8.40	100.0	H	44.0	-8.0
2656.500000	46.48	---	74.00	27.52	100.0	H	141.0	-6.9
2797.583333	48.34	---	74.00	25.66	100.0	H	141.0	-6.3
2797.583333	---	45.97	54.00	8.03	100.0	H	141.0	-6.3
2870.583333	47.88	---	74.00	26.12	100.0	H	44.0	-5.9

Final Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---		---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 1000MHz – 3000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Vertical
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
1598.166667	44.64	---	74.00	29.36	100.0	V	144.0	-11.9
1664.750000	46.92	---	74.00	27.08	100.0	V	123.0	-11.2
1791.916667	44.59	---	74.00	29.41	100.0	V	89.0	-10.3
2658.166667	50.31	---	74.00	23.69	100.0	V	89.0	-6.8
2742.583333	49.36	---	74.00	24.64	100.0	V	22.0	-6.3

Final_Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---		---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 1000MHz – 3000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Horizontal
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
1117.666667	48.94	---	74.00	25.06	100.0	H	181.0	-14.9
1691.583333	41.62	---	74.00	32.38	100.0	H	299.0	-11.5
2196.083333	44.99	---	74.00	29.01	100.0	H	0.0	-8.6
2301.833333	49.58	---	74.00	24.42	100.0	H	136.0	-8.3
2710.500000	43.92	---	74.00	30.08	100.0	H	0.0	-6.6
2751.250000	48.19	---	74.00	25.81	100.0	H	299.0	-6.4

Final_Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---	---	---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 1000MHz – 3000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Vertical
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
1166.166667	40.93	---	74.00	33.07	100.0	V	173.0	-14.4
1795.583333	45.77	---	74.00	28.23	100.0	V	319.0	-10.3
1968.750000	46.56	---	74.00	27.44	100.0	V	341.0	-9.2
1968.750000	---	45.54	54.00	8.46	100.0	V	341.0	-9.2
2675.916667	47.12	---	74.00	26.88	100.0	V	151.0	-6.8
2933.333333	48.56	---	74.00	25.44	100.0	V	341.0	-5.5

Final_Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---		---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 3000MHz – 18000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Horizontal
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
4812.500000	40.51	---	74.00	33.49	100.0	H	197.0	0.3
6001.250000	41.63	---	74.00	32.37	100.0	H	0.0	2.1
7242.500000	48.94	---	74.00	25.06	100.0	H	335.0	2.7
7244.375000	---	46.27	54.00	7.73	100.0	H	335.0	2.8
9273.750000	41.62	---	74.00	32.38	100.0	H	0.0	5.2
11681.250000	44.36	---	74.00	29.64	100.0	H	134.0	8.0
16510.625000	48.05	---	74.00	25.95	100.0	H	335.0	15.9
17835.000000	48.92	---	74.00	25.08	100.0	H	0.0	18.0

Final_Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---	---	---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 3000MHz – 18000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Vertical
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
3215.625000	40.60	---	74.00	33.40	100.0	V	73.0	-3.5
6932.500000	43.42	---	74.00	30.58	100.0	V	123.0	3.0
10222.500000	42.77	---	74.00	31.23	100.0	V	0.0	6.1
13718.750000	45.24	---	74.00	28.76	100.0	V	301.0	11.2
14776.875000	48.09	---	74.00	25.91	100.0	V	49.0	14.3
14785.625000	---	45.12	54.00	8.88	100.0	V	0.0	14.3
17900.000000	---	47.24	54.00	6.76	100.0	V	0.0	18.3
17921.250000	50.31	---	74.00	23.69	100.0	V	0.0	18.3

Final_Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---	---	---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 3000MHz – 18000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Horizontal
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
3215.625000	41.13	---	74.00	32.87	100.0	H	140.0	-3.5
4799.375000	49.28	---	74.00	24.72	100.0	H	303.0	0.3
4802.500000	---	45.66	54.00	8.34	100.0	H	303.0	0.3
6472.500000	41.65	---	74.00	32.35	100.0	H	0.0	2.3
7260.625000	---	44.17	54.00	9.83	100.0	H	0.0	2.9
7261.250000	49.38	---	74.00	24.62	100.0	H	0.0	2.9
10535.625000	43.48	---	74.00	30.52	100.0	H	203.0	6.5
13495.625000	43.69	---	74.00	30.31	100.0	H	128.0	10.7
17190.000000	48.43	---	74.00	25.57	100.0	H	103.0	16.7

Final Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---		---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 3000MHz – 18000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Vertical
 Comment : AC 120V/60Hz
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
3326.250000	46.08	---	74.00	27.92	100.0	V	355.0	-2.9
4511.250000	45.22	---	74.00	28.78	100.0	V	0.0	-0.4
7670.625000	43.14	---	74.00	30.86	100.0	V	108.0	3.8
9643.750000	48.28	---	74.00	25.72	100.0	V	0.0	6.3
12076.250000	44.55	---	74.00	29.45	100.0	V	108.0	8.9
16305.625000	48.69	---	74.00	25.31	100.0	V	0.0	15.6
17807.500000	50.78	---	74.00	23.22	100.0	V	0.0	18.1
17961.875000	---	47.48	54.00	6.52	100.0	V	0.0	18.5

Final Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---	---	---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 3000MHz – 18000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Horizontal
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
3215.625000	42.62	---	74.00	31.38	100.0	H	225.0	-3.5
6338.750000	43.13	---	74.00	30.87	100.0	H	187.0	2.1
10914.375000	43.01	---	74.00	30.99	100.0	H	212.0	6.8
14332.500000	46.21	---	74.00	27.79	100.0	H	200.0	12.9
14804.375000	---	46.01	54.00	7.99	100.0	H	312.0	14.3
14941.250000	47.74	---	74.00	26.26	100.0	H	262.0	14.2
16937.500000	---	47.38	54.00	6.62	100.0	H	0.0	15.9
17988.125000	50.63	---	74.00	23.37	100.0	H	212.0	18.4

Final_Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---	---	---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 3000MHz – 18000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : USB Print
 Tested on : Vertical
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
3085.000000	45.44	---	74.00	28.56	100.0	V	147.0	-4.0
3433.750000	46.48	---	74.00	27.52	100.0	V	352.0	-2.7
7504.375000	41.37	---	74.00	32.63	100.0	V	345.0	3.8
9154.375000	42.49	---	74.00	31.51	100.0	V	160.0	4.8
12058.125000	49.30	---	74.00	24.70	100.0	V	0.0	9.0
12061.250000	---	46.57	54.00	7.43	100.0	V	0.0	9.0
17851.875000	---	47.57	54.00	6.43	100.0	V	222.0	18.2
17916.875000	50.34	---	74.00	23.66	100.0	V	135.0	18.3

Final Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---	---	---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 3000MHz – 18000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Horizontal
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
3429.375000	47.24	---	74.00	26.76	100.0	H	46.0	-2.7
6976.875000	42.37	---	74.00	31.63	100.0	H	0.0	2.7
10886.875000	43.15	---	74.00	30.85	100.0	H	0.0	6.7
14472.500000	---	45.12	54.00	8.88	100.0	H	71.0	13.4
14527.500000	47.96	---	74.00	26.04	100.0	H	0.0	13.5
16715.625000	48.31	---	74.00	25.69	100.0	H	0.0	16.2
17800.625000	---	47.19	54.00	6.81	100.0	H	134.0	17.9
17896.250000	50.68	---	74.00	23.32	100.0	H	334.0	18.1

Final_Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---	---	---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

Radiated Emission Test 3000MHz – 18000MHz

EUT : Label printer
 Model No. : 7033-30-00
 Test requirement : FCC Part 15 Subpart B
 Test method : ANSI C63.4
 Operating mode : WIFI Print
 Tested on : Vertical
 Comment : DC 24V (Supplied by Leltz Icon Battery Pack)
 Date of test : 14 December 2017

Temperature (°C): 23.5 Relative Humidity (%): 55.7 Atmospheric Pressure(mbar) : 1004



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
3333.125000	47.89	---	74.00	26.11	100.0	V	185.0	-2.9
6945.625000	42.99	---	74.00	31.01	100.0	V	0.0	3.0
11624.375000	42.41	---	74.00	31.59	100.0	V	258.0	7.8
14765.000000	---	44.87	54.00	9.13	100.0	V	85.0	14.3
14765.000000	47.38	---	74.00	26.62	100.0	V	85.0	14.3
16956.250000	48.88	---	74.00	25.12	100.0	V	97.0	16.1
17913.125000	50.79	---	74.00	23.21	100.0	V	22.0	18.3
17958.750000	---	47.90	54.00	6.10	100.0	V	353.0	18.5

Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. * (dB/m)
---	---	---	---	---	---	---	---	---

Remark: "*" Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain

9. Test Equipment List

Radiated Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2018-7-14
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	2018-7-14
Horn Antenna	Rohde & Schwarz	HF907	102294	2018-7-14
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2018-7-14
Signal Generator	Rohde & Schwarz	SMY01	839369/005	2018-7-7
Attenuator	Agilent	8491A	MY39264334	2018-7-7
3m Semi-anechoic chamber	TDK	9X6X6	----	2019-5-29
Test software	Rohde & Schwarz	EMC32	Version 9.15.00	N/A

Conducted Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 3	101782	2018-7-14
LISN	Rohde & Schwarz	ENV4200	100249	2018-7-14
LISN	Rohde & Schwarz	ENV432	101318	2018-12-18
LISN	Rohde & Schwarz	ENV216	100326	2018-7-14
ISN	Rohde & Schwarz	ENY81	100177	2018-7-14
ISN	Rohde & Schwarz	ENY81-CA6	101664	2018-7-14
High Voltage Probe	Rohde & Schwarz	TK9420(VT9420)	9420-584	2018-7-14
RF Current Probe	Rohde & Schwarz	EZ-17	100816	2018-7-14
Attenuator	Shanghai Huaxiang	TS2-26-3	080928189	2018-7-7
Test software	Rohde & Schwarz	EMC32	Version9.15.00	N/A

10. Measurement System Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.99dB; Vertical: 4.97dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-18000MHz	Horizontal: 4.96dB; Vertical: 4.95dB;
Uncertainty for Conducted Emission 150kHz-30MHz (for test using AMN ENV216 or ENV4200)	3.46dB