



Compliance Certification Services Inc.

Report No: C140325S01-SF

FCC ID: 2ABV9-T160D

Date of Issue :March 31, 2014

GSM 850-Right Head Cheek Low CH128	2
GSM 850-Right Head Tilted Low CH128.....	3
GSM 850-Left Head Cheek Low CH128	4
GSM 850-Left Head Tilted Low CH128.....	6
PCS 1900-Right Head Cheek Middle CH661	7
PCS 1900-Right Head Tilted Middle CH661.....	8
PCS 1900-Left Head Cheek Middle CH661	9
PCS 1900-Left Head Tilted Middle CH661.....	10
GPRS 850-Body Front High CH251	12
GPRS 850-Body Rear High CH251	13
GSM 850-Body Rear Low CH128.....	15
GPRS 1900-Body Front Middle CH661	16
GPRS 1900-Body Rear Middle CH661	17
PCS 1900-Body Rear Middle CH661.....	19



Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

GSM 850-Right Head Cheek Low CH128

DUT: 2G feature phone; Type: T160d; Serial: N/A

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.896$ S/m; $\epsilon_r = 41.182$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GSM850/Right Head Cheek Low CH128/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.534 W/kg


GSM850/Right Head Cheek Low CH128/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.689 V/m; Power Drift = 0.20 dB

Peak SAR (extrapolated) = 0.638 W/kg

SAR(1 g) = 0.483 W/kg; SAR(10 g) = 0.348 W/kg

Maximum value of SAR (measured) = 0.573 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

GSM 850-Right Head Tilted Low CH128

DUT: 2G feature phone; Type: T160d; Serial: N/A

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.896$ S/m; $\epsilon_r = 41.182$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GSM850/Right Head Tilted Low CH128/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.327 W/kg

GSM850/Right Head Tilted Low CH128/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 18.153 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.400 W/kg

SAR(1 g) = 0.297 W/kg; SAR(10 g) = 0.210 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.356 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

GSM 850-Left Head Cheek Low CH128**DUT: 2G feature phone; Type: T160d; Serial: N/A**

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.896$ S/m; $\epsilon_r = 41.182$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GSM850/Left Head Cheek Low CH128/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.579 W/kg


GSM850/Left Head Cheek Low CH128/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 19.447 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.700 W/kg

SAR(1 g) = 0.494 W/kg; SAR(10 g) = 0.351 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.595 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

GSM 850-Left Head Tilted Low CH128**DUT: 2G feature phone; Type: T160d; Serial: N/A**

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.896$ S/m; $\epsilon_r = 41.182$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GSM850/Left Head Tilted Low CH128/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.343 W/kg


GSM850/Left Head Tilted Low CH128/Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.611 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.433 W/kg

SAR(1 g) = 0.304 W/kg; SAR(10 g) = 0.210 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.372 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

PCS 1900-Right Head Cheek Middle CH661**DUT: 2G feature phone; Type: T160d; Serial: N/A**

Communication System: Generic GSM; Communication System Band: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.406$ S/m; $\epsilon_r = 38.518$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

PCS1900/Right Head Cheek Middle CH661/Area Scan (7x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.613 W/kg


PCS1900/Right Head Cheek Middle CH661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.124 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.933 W/kg

SAR(1 g) = 0.437 W/kg; SAR(10 g) = 0.213 W/kg

Maximum value of SAR (measured) = 0.668 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

PCS 1900-Right Head Tilted Middle CH661**DUT: 2G feature phone; Type: T160d; Serial: N/A**

Communication System: Generic GSM; Communication System Band: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.406$ S/m; $\epsilon_r = 38.518$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

PCS1900/Right Head Tilted Middle CH661/Area Scan (7x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.654 W/kg


PCS1900/Right Head Tilted Middle CH661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.067 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.941 W/kg

SAR(1 g) = 0.441 W/kg; SAR(10 g) = 0.214 W/kg

Maximum value of SAR (measured) = 0.678 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

PCS 1900-Left Head Cheek Middle CH661**DUT: 2G feature phone; Type: T160d; Serial: N/A**

Communication System: Generic GSM; Communication System Band: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.406$ S/m; $\epsilon_r = 38.518$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

PCS1900/Left Head Cheek Middle CH661/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.640 W/kg


PCS1900/Left Head Cheek Middle CH661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.610 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.496 W/kg; SAR(10 g) = 0.246 W/kg

Maximum value of SAR (measured) = 0.747 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

PCS 1900-Left Head Tilted Middle CH661

DUT: 2G feature phone; Type: T160d; Serial: N/A

Communication System: Generic GSM; Communication System Band: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.406$ S/m; $\epsilon_r = 38.518$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

PCS1900/Left Head Tilted Middle CH661/Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.716 W/kg


PCS1900/Left Head Tilted Middle CH661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 15.544 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 1.15 W/kg

SAR(1 g) = 0.545 W/kg; SAR(10 g) = 0.265 W/kg

Maximum value of SAR (measured) = 0.802 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

GPRS 850-Body Front High CH251**DUT: 2G feature phone; Type: T160d; Serial: N/A**

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:2.0797

Medium parameters used: $f = 849$ MHz; $\sigma = 0.968$ S/m; $\epsilon_r = 52.759$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS 850/GPRS850 Body Front High CH251/Area Scan (10x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.408 W/kg

GPRS 850/GPRS850 Body Front High CH251/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.339 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.462 W/kg

SAR(1 g) = 0.346 W/kg; SAR(10 g) = 0.250 W/kg

Maximum value of SAR (measured) = 0.412 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

GPRS 850-Body Rear High CH251

DUT: 2G feature phone; Type: T160d; Serial: N/A

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:2.0797

Medium parameters used: $f = 849$ MHz; $\sigma = 0.968$ S/m; $\epsilon_r = 52.759$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS 850/GPRS850 Body Rear High CH251/Area Scan (10x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.617 W/kg

GPRS 850/GPRS850 Body Rear High CH251/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm


Reference Value = 25.089 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.724 W/kg

SAR(1 g) = 0.531 W/kg; SAR(10 g) = 0.378 W/kg

Maximum value of SAR (measured) = 0.637 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

GSM 850-Body Rear Low CH128

DUT: 2G feature phone; Type: T160d; Serial: N/A

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.943$ S/m; $\epsilon_r = 53.006$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GSM 850/GSM850 Body Rear Low CH128/Area Scan (10x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.412 W/kg


GSM 850/GSM850 Body Rear Low CH128/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.356 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.485 W/kg

SAR(1 g) = 0.359 W/kg; SAR(10 g) = 0.256 W/kg

Maximum value of SAR (measured) = 0.429 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

GPRS 1900-Body Front Middle CH661**DUT: 2G feature phone; Type: T160d; Serial: N/A**

Communication System: Generic GPRS; Communication System Band: GPRS1900; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.561$ S/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)


GPRS 1900/Body Front Middle CH661/Area Scan (10x7x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.200 W/kg**GPRS 1900/Body Front Middle CH661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.142 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.286 W/kg

SAR(1 g) = 0.142 W/kg; SAR(10 g) = 0.074 W/kg

Maximum value of SAR (measured) = 0.208 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

GPRS 1900-Body Rear Middle CH661**DUT: 2G feature phone; Type: T160d; Serial: N/A**

Communication System: Generic GPRS; Communication System Band: GPRS1900; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.561$ S/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)


GPRS 1900/Body Rear Middle CH661/Area Scan (8x7x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.725 W/kg**GPRS 1900/Body Rear Middle CH661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 5.851 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 1.23 W/kg

SAR(1 g) = 0.576 W/kg; SAR(10 g) = 0.273 W/kg

Maximum value of SAR (measured) = 0.867 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 3/27/2014

PCS 1900-Body Rear Middle CH661

DUT: 2G feature phone; Type: T160d; Serial: N/A

Communication System: Generic GSM; Communication System Band: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.561$ S/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

PCS 1900/Body Rear Middle CH661/Area Scan (10x7x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.450 W/kg

PCS 1900/Body Rear Middle CH661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.501 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.697 W/kg

SAR(1 g) = 0.347 W/kg; SAR(10 g) = 0.171 W/kg

Maximum value of SAR (measured) = 0.506 W/kg

