

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)
Report No.: RFBICK-WTW-P25020498
FCC ID: 2ABXRBM5284F
Product: Bluetooth Module
Brand: Braveridge
Model No.: BVMCN52840FWSLR
Received Date: 2025/2/19
Test Date: 2025/2/27 ~ 2025/3/5
Issued Date: 2025/5/9
Applicant: Braveridge Co., Ltd.
Address: 3-27-2 Susenji Nishi-Ku, Fukuoka City, Fukuoka Prefecture, 819-0373
Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories
Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
Test Location(1): No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan
Test Location(2): No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
FCC Registration / 788550 / TW0003 for Test Location(1)
Designation Number: 281270 / TW0032 for Test Location(2)

Approved by: _____

Jeremy Lin

Jeremy Lin / Project Engineer

, Date: _____

2025/5/9

This test report consists of 95 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Gina Liu / Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description	7
3.2 Antenna Description of EUT	7
3.3 Channel List	7
3.4 Test Mode Applicability and Tested Channel Detail	8
3.5 Duty Cycle of Test Signal	9
3.6 Test Program Used and Operation Descriptions	13
3.7 Connection Diagram of EUT and Peripheral Devices	13
3.8 Configuration of Peripheral Devices and Cable Connections	13
4 Test Instruments	14
4.1 RF Output Power	14
4.2 Power Spectral Density	14
4.3 6 dB Bandwidth	14
4.4 Conducted Out of Band Emissions	14
4.5 AC Power Conducted Emissions	15
4.6 Unwanted Emissions below 1 GHz	16
4.7 Unwanted Emissions above 1 GHz	17
5 Limits of Test Items.....	18
5.1 RF Output Power	18
5.2 Power Spectral Density	18
5.3 6 dB Bandwidth	18
5.4 Conducted Out of Band Emissions	18
5.5 AC Power Conducted Emissions	18
5.6 Unwanted Emissions below 1 GHz	18
5.7 Unwanted Emissions above 1 GHz	19
6 Test Arrangements	20
6.1 RF Output Power	20
6.1.1 Test Setup	20
6.1.2 Test Procedure	20
6.2 Power Spectral Density	20
6.2.1 Test Setup	20
6.2.2 Test Procedure	20
6.3 6 dB Bandwidth	21
6.3.1 Test Setup	21
6.3.2 Test Procedure	21
6.4 Conducted Out of Band Emissions	21
6.4.1 Test Setup	21
6.4.2 Test Procedure	21
6.5 AC Power Conducted Emissions	22
6.5.1 Test Setup	22
6.5.2 Test Procedure	22
6.6 Unwanted Emissions below 1 GHz	23
6.6.1 Test Setup	23
6.6.2 Test Procedure	24
6.7 Unwanted Emissions above 1 GHz	25
6.7.1 Test Setup	25
6.7.2 Test Procedure	25
7 Test Results of Test Item	26

7.1	RF Output Power.....	26
7.2	Power Spectral Density	30
7.3	6 dB Bandwidth	34
7.4	Conducted Out of Band Emissions	38
7.5	AC Power Conducted Emissions	46
7.6	Unwanted Emissions below 1 GHz	50
7.7	Unwanted Emissions above 1 GHz.....	54
8	Pictures of Test Arrangements	94
9	Information of the Testing Laboratories	95

Release Control Record

Issue No.	Description	Date Issued
RFBICK-WTW-P25020498	Original release.	2025/5/9

1 Certificate

Product: Bluetooth Module

Brand: Braveridge

Test Model: BVMCN52840FWSLR

Sample Status: Engineering sample

Applicant: Braveridge Co., Ltd.

Test Date: 2025/2/27 ~ 2025/3/5

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)

Measurement ANSI C63.10-2013

procedure: KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -15.24 dB at 0.18200 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -3.1 dB at 31.94 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -6.8 dB at 2483.50 MHz
15.203	Antenna Requirement	Pass	No antenna connector is used.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
RF Output Power	-	1.371 dB
Power Spectral Density	-	1.017 dB
6 dB Bandwidth	-	206.5 Hz
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.79 dB
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.90 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3 dB
	30 MHz ~ 1 GHz	2.93 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	1.76 dB
	18 GHz ~ 40 GHz	1.77 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	Bluetooth Module
Brand	Braveridge
Test Model	BVMCN52840FWSLR
Status of EUT	Engineering sample
Power Supply Rating	Nominal for high-power variants: 3.7Vdc Nominal for low-power variant: 3.0Vdc
Modulation Type	GFSK
Modulation Technology	DTS
Transfer Rate	1MBaud with 1Mbps transfer rate 1MBaud with coded 125Kbps transfer rate 1MBaud with coded 500Kbps transfer rate 2MBaud with 2Mbps transfer rate
Operating Frequency	2.402 GHz ~ 2.48 GHz
Number of Channel	40
Output Power	6.237 mW (7.95 dBm)

Note: The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Antenna NO.	RF Chain NO.	Brand	Model	Antenna Net Gain(dBi)	Frequency range (GHz)	Antenna Type	Connector Type
1	Chain 0	TAIYO YUDEN	TSA5NA2K2G45NS001T	1.9	2.4 ~ 2.4835	Monopole	none(like solder)

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

3.3 Channel List

40 channels are provided for BT-LE:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. EUT can be used in the following ways: X-axis/ Y-axis/ Z-axis. Pre-scan these ways and find the worst case as a representative test condition. 2. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
Worst Case:	1. EUT Worst Condition: X-AXIS

Following channel(s) was (were) selected for the final test as listed below:

Test Item	EUT Configure Mode	Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power	A, B	BT-LE 1M	37, 17, 39	GFSK	1Mb/s
		BT-LE 2M	37, 17, 39	GFSK	2Mb/s
		BT-LE 125K	37, 17, 39	GFSK	125k/s
		BT-LE 500K	37, 17, 39	GFSK	500k/s
Power Spectral Density	A, B	BT-LE 1M	37, 17, 39	GFSK	1Mb/s
		BT-LE 2M	37, 17, 39	GFSK	2Mb/s
		BT-LE 125K	37, 17, 39	GFSK	125k/s
		BT-LE 500K	37, 17, 39	GFSK	500k/s
6 dB Bandwidth / Conducted Out of Band Emissions	A, B	BT-LE 1M	37, 17, 39	GFSK	1Mb/s
		BT-LE 2M	37, 17, 39	GFSK	2Mb/s
		BT-LE 125K	37, 17, 39	GFSK	125k/s
		BT-LE 500K	37, 17, 39	GFSK	500k/s
AC Power Conducted Emissions	A	BT-LE 500K	37	GFSK	500kb/s
	B	BT-LE 1M	37	GFSK	1Mb/s
Unwanted Emissions below 1 GHz	A	BT-LE 500K	37	GFSK	500kb/s
	B	BT-LE 1M	37	GFSK	1Mb/s
Unwanted Emissions above 1 GHz	A, B	BT-LE 1M	37, 17, 39	GFSK	1Mb/s
		BT-LE 2M	37, 17, 39	GFSK	2Mb/s
		BT-LE 125K	37, 17, 39	GFSK	125k/s
		BT-LE 500K	37, 17, 39	GFSK	500k/s
EUT Configure Mode:	A	DC 3V			
	B	DC 3.7V			

3.5 Duty Cycle of Test Signal


Mode A

BT-LE 1M: Duty cycle = 2.15 ms / 2.5 ms x 100% = 86.0%, duty factor = $10 \cdot \log(1/\text{Duty cycle}) = 0.66 \text{ dB}$


BT-LE 2M: Duty cycle = 1.09 ms / 1.86 ms x 100% = 58.6%, duty factor = $10 \cdot \log(1/\text{Duty cycle}) = 2.32 \text{ dB}$

BT-LE 125K: Duty cycle = 17.2 ms / 17.44 ms x 100% = 98.6%

BT-LE 500K: Duty cycle = 4.58 ms / 4.98 ms x 100% = 92.0%, duty factor = $10 \cdot \log(1/\text{Duty cycle}) = 0.36 \text{ dB}$




Duty Cycle Analysis



BT-LE 125K

Duty Cycle Analysis



BT-LE 500K


Mode B

BT-LE 1M: Duty cycle = $2.15 \text{ ms} / 2.49 \text{ ms} \times 100\% = 86.3\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 0.64 \text{ dB}$


BT-LE 2M: Duty cycle = $1.09 \text{ ms} / 1.87 \text{ ms} \times 100\% = 58.3\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 2.34 \text{ dB}$

BT-LE 125K: Duty cycle = $17.2 \text{ ms} / 17.4 \text{ ms} \times 100\% = 98.6\%$

BT-LE 500K: Duty cycle = $4.6 \text{ ms} / 5 \text{ ms} \times 100\% = 92.0\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 0.36 \text{ dB}$




Duty Cycle Analysis



BT-LE 125K

Duty Cycle Analysis




BT-LE 500K

3.6 Test Program Used and Operation Descriptions

Controlling software Direct Test Mode v2.4.2 has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	DC Power Supply	Topward	6603A	725906	N/A	Provided by Lab
B	Converting board	N/A	N/A	N/A	N/A	Supplied by applicant
C	Laptop	HP	ZBOOK14	N/A	N/A	Supplied by applicant
D	Converting board	N/A	N/A	N/A	N/A	Supplied by applicant

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	Console Cable	1	0.15	No	No	Supplied by applicant
2	USB Cable	1	1	Yes	No	Supplied by applicant
3	DC Cable	1	1	No	No	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Peak Power Analyzer Keysight	8990B	MY51000538	2024/4/29	2025/4/28
Wideband Power Sensor Keysight	N1923A	MY58200003	2024/6/17	2025/6/16

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2025/3/5

4.2 Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Signal & Spectrum Analyzer R&S	FSV3044	101105	2025/2/25	2026/2/24
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2025/3/5

4.3 6 dB Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.4 Conducted Out of Band Emissions

Refer to section 4.2 to get the tested date and information of the instruments.

4.5 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance	E1-011279	04	2024/11/28	2025/11/27
	E1-011280	05	2024/11/28	2025/11/27
	E1-011311	09	2024/11/28	2025/11/27
DC-LISN Schwarzbeck	NNBM 8126G	8126G-069	2024/11/5	2025/11/4
EMI Test Receiver R&S	ESCI	100613	2024/11/25	2025/11/24
Fixed Attenuator Mini-Circuits	HAT-10+	PAD-COND1-01	2025/1/5	2026/1/4
LISN R&S	ENV216	101826	2024/3/25	2025/3/24
	ESH3-Z5	100311	2024/9/5	2025/9/4
RF Coaxial Cable Woken	5D-FB	Cable-cond1-01	2025/1/5	2026/1/4
Software BVADT	BVADT_Cond_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2024/8/28	2025/8/27

Notes:

1. The test was performed in HY - Conduction 1.
2. Tested Date: 2025/3/3

4.6 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower Max-Full	MFT-151SS-0.5T	N/A	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-1213	2024/10/14	2025/10/13
EXA Signal Analyzer Agilent	N9010A	MY52220207	2024/12/30	2025/12/29
Loop Antenna TESEQ	HLA 6121	45745	2024/8/21	2025/8/20
MXE EMI Receiver Keysight	N9038B	MY60180019	2025/1/15	2026/1/14
Preamplifier EMCI	EMC330N	980782	2025/1/14	2026/1/13
RF Coaxial Cable EMCI	EMCCFD400-NM-NM-500	201233	2025/1/14	2026/1/13
	EMCCFD400-NM-NM-3000	201235	2025/1/14	2026/1/13
	EMCCFD400-NM-NM-9000	201236(with PAD)	2025/1/14	2026/1/13
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table Max-Full	MF-7802BS	N/A	N/A	N/A
Turn Table Controller Max-Full	MF-7802BS	MF780208674	N/A	N/A

Notes:

1. The test was performed in WM - 966 chamber 8.
2. Tested Date: 2025/3/3

4.7 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower Max-Full	MFT-151SS-0.5T	N/A	N/A	N/A
EXA Signal Analyzer Agilent	N9010A	MY52220207	2024/12/30	2025/12/29
Horn Antenna RFSPIN	DRH18-E	210103A18E	2024/11/10	2025/11/9
Horn Antenna Schwarzbeck	BBHA 9170	9170-1049	2024/11/10	2025/11/9
MXE EMI Receiver Keysight	N9038B	MY60180019	2025/1/15	2026/1/14
Preamplifier EMCI	EMC118A45SE	980808	2024/12/26	2025/12/25
	EMC184045SE	980788	2025/1/14	2026/1/13
RF Coaxial Cable EMCI	EMC101G-KM-KM-2000	201254	2025/1/14	2026/1/13
	EMC101G-KM-KM-3000	201258	2025/1/14	2026/1/13
	EMC101G-KM-KM-5000	201261	2025/1/14	2026/1/13
	EMC104-SM-SM-1000	210102	2025/1/14	2026/1/13
	EMC104-SM-SM-3000	201231	2025/1/14	2026/1/13
	EMC104-SM-SM-9000	201243	2025/1/14	2026/1/13
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table Max-Full	MF-7802BS	N/A	N/A	N/A
Turn Table Controller Max-Full	MF-7802BS	MF780208674	N/A	N/A

Notes:

1. The test was performed in WM - 966 chamber 8.
2. Tested Date: 2025/2/27 ~ 2025/3/5

5 Limits of Test Items

5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

5.2 Power Spectral Density

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

5.3 6 dB Bandwidth

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

5.4 Conducted Out of Band Emissions

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

5.5 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.6 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.7 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3


Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup



6.1.2 Test Procedure

Peak Power:


A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average Power:

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

6.2 Power Spectral Density

6.2.1 Test Setup




6.2.2 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: 3 kHz.
- Set the VBW $\geq 3 \times$ RBW.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

6.3 6 dB Bandwidth

6.3.1 Test Setup




6.3.2 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Conducted Out of Band Emissions

6.4.1 Test Setup



6.4.2 Test Procedure

MEASUREMENT PROCEDURE REF


- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW ≥ 300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.5 AC Power Conducted Emissions

6.5.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.5.2 Test Procedure


- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.6 Unwanted Emissions below 1 GHz

6.6.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.7 Unwanted Emissions above 1 GHz

6.7.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver/spectrum analyzer was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	3 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyong Wang
--------------	-------	---------------------------	--------------	------------	--------------

Mode A

For Peak Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
37	2402	6.166	7.90	30	Pass
17	2440	6.138	7.88	30	Pass
39	2480	5.902	7.71	30	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the output power limit shall not be reduced.

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
37	2402	6.166	7.90	30	Pass
17	2440	6.138	7.88	30	Pass
39	2480	5.916	7.72	30	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the output power limit shall not be reduced.

BT-LE 125K

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
37	2402	6.18	7.91	30	Pass
17	2440	6.138	7.88	30	Pass
39	2480	5.916	7.72	30	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the output power limit shall not be reduced.

BT-LE 500K

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
37	2402	6.194	7.92	30	Pass
17	2440	6.152	7.89	30	Pass
39	2480	5.902	7.71	30	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the output power limit shall not be reduced.

For Average Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
37	2402	6.138	7.88
17	2440	6.109	7.86
39	2480	5.875	7.69

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
37	2402	6.152	7.89
17	2440	6.124	7.87
39	2480	5.875	7.69

BT-LE 125K

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
37	2402	6.152	7.89
17	2440	6.109	7.86
39	2480	5.888	7.70

BT-LE 500K

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
37	2402	6.152	7.89
17	2440	6.124	7.87
39	2480	5.875	7.69

Input Power:	3.7 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyong Wang
--------------	---------	---------------------------	--------------	------------	--------------

Mode B

For Peak Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
37	2402	6.209	7.93	30	Pass
17	2440	6.138	7.88	30	Pass
39	2480	5.929	7.73	30	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the output power limit shall not be reduced.

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
37	2402	6.237	7.95	30	Pass
17	2440	6.152	7.89	30	Pass
39	2480	5.943	7.74	30	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the output power limit shall not be reduced.

BT-LE 125K

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
37	2402	6.209	7.93	30	Pass
17	2440	6.152	7.89	30	Pass
39	2480	5.929	7.73	30	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the output power limit shall not be reduced.

BT-LE 500K

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
37	2402	6.223	7.94	30	Pass
17	2440	6.138	7.88	30	Pass
39	2480	5.916	7.72	30	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the output power limit shall not be reduced.

For Average Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
37	2402	6.18	7.91
17	2440	6.109	7.86
39	2480	5.902	7.71

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
37	2402	6.194	7.92
17	2440	6.109	7.86
39	2480	5.916	7.72

BT-LE 125K

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
37	2402	6.166	7.90
17	2440	6.124	7.87
39	2480	5.902	7.71

BT-LE 500K

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
37	2402	6.18	7.91
17	2440	6.095	7.85
39	2480	5.902	7.71

7.2 Power Spectral Density

Input Power:	3 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyong Wang
--------------	-------	---------------------------	--------------	------------	--------------

Mode A

BT-LE 1M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
37	2402	-9.44	8	Pass
17	2440	-9.91	8	Pass
39	2480	-10.69	8	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the power density limit shall not be reduced.

BT-LE 2M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
37	2402	-11.44	8	Pass
17	2440	-11.72	8	Pass
39	2480	-12.29	8	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the power density limit shall not be reduced.

BT-LE 125K

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
37	2402	0.42	8	Pass
17	2440	0.24	8	Pass
39	2480	-0.38	8	Pass





Note: The antenna gain is 1.9 dBi < 6 dBi, so the power density limit shall not be reduced.

BT-LE 500K

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
37	2402	0.23	8	Pass
17	2440	0.05	8	Pass
39	2480	-0.65	8	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the power density limit shall not be reduced.

Spectrum Plot of Maximum Value



Input Power:	3.7 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyong Wang
--------------	---------	---------------------------	--------------	------------	--------------

Mode B

BT-LE 1M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
37	2402	-9.34	8	Pass
17	2440	-9.94	8	Pass
39	2480	-10.70	8	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the power density limit shall not be reduced.

BT-LE 2M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
37	2402	-11.45	8	Pass
17	2440	-11.74	8	Pass
39	2480	-12.29	8	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the power density limit shall not be reduced.

BT-LE 125K

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
37	2402	0.45	8	Pass
17	2440	0.24	8	Pass
39	2480	-0.38	8	Pass





Note: The antenna gain is 1.9 dBi < 6 dBi, so the power density limit shall not be reduced.

BT-LE 500K

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
37	2402	0.23	8	Pass
17	2440	0.03	8	Pass
39	2480	-0.65	8	Pass

Note: The antenna gain is 1.9 dBi < 6 dBi, so the power density limit shall not be reduced.

Spectrum Plot of Maximum Value



7.3 6 dB Bandwidth

Input Power:	3 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyong Wang
--------------	-------	---------------------------	--------------	------------	--------------

Mode A

BT-LE 1M

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
37	2402	0.69	0.5	Pass
17	2440	0.71	0.5	Pass
39	2480	0.72	0.5	Pass

BT-LE 2M

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
37	2402	1.16	0.5	Pass
17	2440	1.16	0.5	Pass
39	2480	1.16	0.5	Pass





BT-LE 125K

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
37	2402	0.61	0.5	Pass
17	2440	0.61	0.5	Pass
39	2480	0.62	0.5	Pass

BT-LE 500K

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
37	2402	0.7	0.5	Pass
17	2440	0.71	0.5	Pass
39	2480	0.71	0.5	Pass

Spectrum Plot of Minimum Value



Input Power:	3.7 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyong Wang
--------------	---------	---------------------------	--------------	------------	--------------

Mode B

BT-LE 1M

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
37	2402	0.69	0.5	Pass
17	2440	0.71	0.5	Pass
39	2480	0.7	0.5	Pass

BT-LE 2M

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
37	2402	1.15	0.5	Pass
17	2440	1.16	0.5	Pass
39	2480	1.16	0.5	Pass





BT-LE 125K

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
37	2402	0.62	0.5	Pass
17	2440	0.61	0.5	Pass
39	2480	0.62	0.5	Pass

BT-LE 500K

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
37	2402	0.7	0.5	Pass
17	2440	0.71	0.5	Pass
39	2480	0.71	0.5	Pass

Spectrum Plot of Minimum Value




7.4 Conducted Out of Band Emissions


Input Power:	3 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyoung Wang
--------------	-------	---------------------------	--------------	------------	---------------

Mode A


BT-LE 1M



BT-LE 2M



BT-LE 125K




BT-LE 500K



Input Power:	3.7 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyoung Wang
--------------	---------	---------------------------	--------------	------------	---------------

Mode B


BT-LE 1M



BT-LE 2M



BT-LE 125K



BT-LE 500K



7.5 AC Power Conducted Emissions


Mode A

RF Mode	BT-LE 500K	Channel	CH 0 : 2404 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Charles Hsiao		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18200	9.68	38.38	29.47	48.06	39.15	64.39	54.39	-16.33	-15.24
2	0.19000	9.68	38.90	28.14	48.58	37.82	64.04	54.04	-15.46	-16.22
3	0.30600	9.70	33.43	22.43	43.13	32.13	60.08	50.08	-16.95	-17.95
4	1.50600	9.81	11.71	2.94	21.52	12.75	56.00	46.00	-34.48	-33.25
5	8.90600	10.01	15.69	14.29	25.70	24.30	60.00	50.00	-34.30	-25.70
6	13.28600	10.09	16.97	11.17	27.06	21.26	60.00	50.00	-32.94	-28.74

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	BT-LE 500K	Channel	CH 0 : 2404 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Charles Hsiao		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.19000	9.67	37.86	28.33	47.53	38.00	64.04	54.04	-16.51	-16.04
2	0.26200	9.69	29.88	15.53	39.57	25.22	61.37	51.37	-21.80	-26.15
3	0.28600	9.70	31.94	18.36	41.64	28.06	60.64	50.64	-19.00	-22.58
4	0.31000	9.70	33.33	22.38	43.03	32.08	59.97	49.97	-16.94	-17.89
5	1.46600	9.81	12.01	3.24	21.82	13.05	56.00	46.00	-34.18	-32.95
6	12.66600	10.18	18.58	13.97	28.76	24.15	60.00	50.00	-31.24	-25.85

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Mode B

RF Mode	BT-LE 1M	Channel	CH 0 : 2404 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Charles Hsiao		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18200	9.68	38.37	29.44	48.05	39.12	64.39	54.39	-16.34	-15.27
2	0.25400	9.69	32.78	21.24	42.47	30.93	61.63	51.63	-19.16	-20.70
3	0.27800	9.69	28.56	12.71	38.25	22.40	60.88	50.88	-22.63	-28.48
4	0.32600	9.70	26.77	11.68	36.47	21.38	59.55	49.55	-23.08	-28.17
5	1.47800	9.81	12.19	2.92	22.00	12.73	56.00	46.00	-34.00	-33.27
6	11.81000	10.07	16.72	15.47	26.79	25.54	60.00	50.00	-33.21	-24.46

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	BT-LE 1M	Channel	CH 0 : 2404 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Charles Hsiao		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17800	9.67	37.96	29.14	47.63	38.81	64.58	54.58	-16.95	-15.77
2	0.19400	9.67	36.33	26.14	46.00	35.81	63.86	53.86	-17.86	-18.05
3	0.30200	9.70	35.10	23.84	44.80	33.54	60.19	50.19	-15.39	-16.65
4	0.73000	9.77	15.56	8.29	25.33	18.06	56.00	46.00	-30.67	-27.94
5	1.49800	9.81	12.19	3.50	22.00	13.31	56.00	46.00	-34.00	-32.69
6	12.66600	10.18	18.53	13.90	28.71	24.08	60.00	50.00	-31.29	-25.92

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



7.6 Unwanted Emissions below 1 GHz


Mode A

RF Mode	BT-LE 500K	Channel	CH 0 : 2404 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	114.39	32.1 QP	43.5	-11.4	1.14 H	157	47.5	-15.4
2	191.99	32.0 QP	43.5	-11.5	1.19 H	64	47.7	-15.7
3	232.73	32.5 QP	46.0	-13.5	1.67 H	209	47.2	-14.7
4	480.08	37.1 QP	46.0	-8.9	1.67 H	263	44.5	-7.4
5	716.76	36.4 QP	46.0	-9.6	1.04 H	47	39.2	-2.8
6	864.20	29.6 QP	46.0	-16.4	1.16 H	220	30.4	-0.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	BT-LE 500K	Channel	CH 0 : 2404 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	31.94	36.9 QP	40.0	-3.1	1.57 V	77	51.1	-14.2
2	62.01	31.9 QP	40.0	-8.1	1.05 V	206	45.9	-14.0
3	296.75	34.7 QP	46.0	-11.3	1.67 V	322	46.8	-12.1
4	480.08	35.9 QP	46.0	-10.1	1.67 V	277	43.3	-7.4
5	713.85	31.8 QP	46.0	-14.2	1.95 V	206	34.6	-2.8
6	783.69	32.2 QP	46.0	-13.8	1.17 V	4	33.5	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




Mode B

RF Mode	BT-LE 1M	Channel	CH 0 : 2404 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	114.39	35.7 QP	43.5	-7.8	1.14 H	292	51.1	-15.4
2	234.67	33.0 QP	46.0	-13.0	1.64 H	333	47.5	-14.5
3	296.75	30.5 QP	46.0	-15.5	1.05 H	274	42.6	-12.1
4	480.08	38.5 QP	46.0	-7.5	1.75 H	195	45.9	-7.4
5	717.73	35.7 QP	46.0	-10.3	1.62 H	209	38.5	-2.8
6	859.35	30.5 QP	46.0	-15.5	1.17 H	7	31.3	-0.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	BT-LE 1M	Channel	CH 0 : 2404 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	31.94	36.9 QP	40.0	-3.1	1.57 V	331	51.1	-14.2
2	62.98	30.6 QP	40.0	-9.4	1.87 V	7	44.6	-14.0
3	296.75	35.1 QP	46.0	-10.9	1.05 V	262	47.2	-12.1
4	479.11	34.7 QP	46.0	-11.3	1.13 V	326	42.1	-7.4
5	723.55	31.4 QP	46.0	-14.6	1.57 V	185	34.0	-2.6
6	783.69	31.7 QP	46.0	-14.3	1.67 V	296	33.0	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.7 Unwanted Emissions above 1 GHz

Mode A

RF Mode	BT-LE 125K	Channel	CH 37 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.9 PK	74.0	-16.1	1.46 H	71	26.1	31.8
2	2390.00	46.0 AV	54.0	-8.0	1.46 H	71	14.2	31.8
3	*2402.00	103.5 PK			1.46 H	71	71.7	31.8
4	*2402.00	102.3 AV			1.46 H	71	70.5	31.8
5	4804.00	52.4 PK	74.0	-21.6	2.44 H	99	49.5	2.9
6	4804.00	42.5 AV	54.0	-11.5	2.44 H	99	39.6	2.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.7 PK	74.0	-16.3	3.30 V	244	25.9	31.8
2	2390.00	45.8 AV	54.0	-8.2	3.30 V	244	14.0	31.8
3	*2402.00	102.1 PK			3.30 V	244	70.3	31.8
4	*2402.00	101.2 AV			3.30 V	244	69.4	31.8
5	4804.00	50.8 PK	74.0	-23.2	3.44 V	203	47.9	2.9
6	4804.00	38.6 AV	54.0	-15.4	3.44 V	203	35.7	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 125K	Channel	CH 17 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	105.5 PK			1.26 H	77	73.7	31.8
2	*2440.00	104.6 AV			1.26 H	77	72.8	31.8
3	4880.00	52.7 PK	74.0	-21.3	2.37 H	99	49.7	3.0
4	4880.00	42.9 AV	54.0	-11.1	2.37 H	99	39.9	3.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	103.5 PK			3.47 V	236	71.7	31.8
2	*2440.00	102.6 AV			3.47 V	236	70.8	31.8
3	4880.00	50.8 PK	74.0	-23.2	3.58 V	197	47.8	3.0
4	4880.00	38.6 AV	54.0	-15.4	3.58 V	197	35.6	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 125K	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	102.5 PK			1.22 H	60	70.6	31.9
2	*2480.00	101.6 AV			1.22 H	60	69.7	31.9
3	2483.50	57.1 PK	74.0	-16.9	1.22 H	60	25.2	31.9
4	2483.50	45.8 AV	54.0	-8.2	1.22 H	60	13.9	31.9
5	4960.00	52.7 PK	74.0	-21.3	2.47 H	93	49.5	3.2
6	4960.00	42.8 AV	54.0	-11.2	2.47 H	93	39.6	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	100.5 PK			3.37 V	236	68.6	31.9
2	*2480.00	99.6 AV			3.37 V	236	67.7	31.9
3	2483.50	56.2 PK	74.0	-17.8	3.37 V	236	24.3	31.9
4	2483.50	45.3 AV	54.0	-8.7	3.37 V	236	13.4	31.9
5	4960.00	50.8 PK	74.0	-23.2	3.51 V	193	47.6	3.2
6	4960.00	38.6 AV	54.0	-15.4	3.51 V	193	35.4	3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 500K	Channel	CH 37 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.0 PK	74.0	-17.0	1.46 H	71	25.2	31.8
2	2390.00	45.8 AV	54.0	-8.2	1.46 H	71	14.0	31.8
3	*2402.00	103.9 PK			1.46 H	71	72.1	31.8
4	*2402.00	102.7 AV			1.46 H	71	70.9	31.8
5	4804.00	52.4 PK	74.0	-21.6	2.35 H	93	49.5	2.9
6	4804.00	42.7 AV	54.0	-11.3	2.35 H	93	39.8	2.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.7 PK	74.0	-17.3	3.39 V	242	24.9	31.8
2	2390.00	45.6 AV	54.0	-8.4	3.39 V	242	13.8	31.8
3	*2402.00	102.2 PK			3.39 V	242	70.4	31.8
4	*2402.00	101.6 AV			3.39 V	242	69.8	31.8
5	4804.00	50.5 PK	74.0	-23.5	3.50 V	201	47.6	2.9
6	4804.00	38.3 AV	54.0	-15.7	3.50 V	201	35.4	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 500K	Channel	CH 17 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	105.5 PK			1.23 H	76	73.7	31.8
2	*2440.00	104.5 AV			1.23 H	76	72.7	31.8
3	4880.00	52.6 PK	74.0	-21.4	2.39 H	94	49.6	3.0
4	4880.00	42.9 AV	54.0	-11.1	2.39 H	94	39.9	3.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	103.5 PK			3.40 V	239	71.7	31.8
2	*2440.00	102.5 AV			3.40 V	239	70.7	31.8
3	4880.00	50.7 PK	74.0	-23.3	3.52 V	191	47.7	3.0
4	4880.00	38.5 AV	54.0	-15.5	3.52 V	191	35.5	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 500K	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	102.7 PK			1.22 H	61	70.8	31.9
2	*2480.00	101.7 AV			1.22 H	61	69.8	31.9
3	2483.50	57.1 PK	74.0	-16.9	1.22 H	61	25.2	31.9
4	2483.50	45.9 AV	54.0	-8.1	1.22 H	61	14.0	31.9
5	4960.00	52.6 PK	74.0	-21.4	2.44 H	98	49.4	3.2
6	4960.00	42.8 AV	54.0	-11.2	2.44 H	98	39.6	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	100.8 PK			3.42 V	237	68.9	31.9
2	*2480.00	99.8 AV			3.42 V	237	67.9	31.9
3	2483.50	56.4 PK	74.0	-17.6	3.42 V	237	24.5	31.9
4	2483.50	45.4 AV	54.0	-8.6	3.42 V	237	13.5	31.9
5	4960.00	50.8 PK	74.0	-23.2	3.55 V	192	47.6	3.2
6	4960.00	38.5 AV	54.0	-15.5	3.55 V	192	35.3	3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 1M	Channel	CH 37 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.1 PK	74.0	-16.9	1.46 H	71	25.3	31.8
2	2390.00	46.0 AV	54.0	-8.0	1.46 H	71	14.2	31.8
3	*2402.00	104.2 PK			1.46 H	71	72.4	31.8
4	*2402.00	103.3 AV			1.46 H	71	71.5	31.8
5	4804.00	52.4 PK	74.0	-21.6	2.34 H	95	49.5	2.9
6	4804.00	42.9 AV	54.0	-11.1	2.34 H	95	40.0	2.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.0 PK	74.0	-17.0	3.40 V	235	25.2	31.8
2	2390.00	45.2 AV	54.0	-8.8	3.40 V	235	13.4	31.8
3	*2402.00	102.1 PK			3.40 V	235	70.3	31.8
4	*2402.00	101.0 AV			3.40 V	235	69.2	31.8
5	4804.00	50.2 PK	74.0	-23.8	3.55 V	194	47.3	2.9
6	4804.00	38.3 AV	54.0	-15.7	3.55 V	194	35.4	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 1M	Channel	CH 17 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	105.4 PK			1.26 H	71	73.6	31.8
2	*2440.00	104.3 AV			1.26 H	71	72.5	31.8
3	4880.00	52.4 PK	74.0	-21.6	2.37 H	98	49.4	3.0
4	4880.00	42.8 AV	54.0	-11.2	2.37 H	98	39.8	3.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	103.5 PK			3.39 V	235	71.7	31.8
2	*2440.00	102.4 AV			3.39 V	235	70.6	31.8
3	4880.00	50.6 PK	74.0	-23.4	3.55 V	203	47.6	3.0
4	4880.00	38.4 AV	54.0	-15.6	3.55 V	203	35.4	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 1M	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	102.8 PK			1.64 H	62	70.9	31.9
2	*2480.00	101.6 AV			1.64 H	62	69.7	31.9
3	2483.50	56.9 PK	74.0	-17.1	1.64 H	62	25.0	31.9
4	2483.50	46.0 AV	54.0	-8.0	1.64 H	62	14.1	31.9
5	4960.00	52.4 PK	74.0	-21.6	2.42 H	101	49.2	3.2
6	4960.00	42.7 AV	54.0	-11.3	2.42 H	101	39.5	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	100.8 PK			3.41 V	239	68.9	31.9
2	*2480.00	99.7 AV			3.41 V	239	67.8	31.9
3	2483.50	56.4 PK	74.0	-17.6	3.41 V	239	24.5	31.9
4	2483.50	45.6 AV	54.0	-8.4	3.41 V	239	13.7	31.9
5	4960.00	50.6 PK	74.0	-23.4	3.52 V	198	47.4	3.2
6	4960.00	38.4 AV	54.0	-15.6	3.52 V	198	35.2	3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	Channel	CH 37 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.0 PK	74.0	-17.0	1.46 H	71	25.2	31.8
2	2390.00	45.9 AV	54.0	-8.1	1.46 H	71	14.1	31.8
3	*2402.00	103.6 PK			1.46 H	71	71.8	31.8
4	*2402.00	100.0 AV			1.46 H	71	68.2	31.8
5	4804.00	51.6 PK	74.0	-22.4	2.39 H	97	48.7	2.9
6	4804.00	42.4 AV	54.0	-11.6	2.39 H	97	39.5	2.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.7 PK	74.0	-17.3	3.41 V	246	24.9	31.8
2	2390.00	45.5 AV	54.0	-8.5	3.41 V	246	13.7	31.8
3	*2402.00	101.2 PK			3.41 V	246	69.4	31.8
4	*2402.00	98.8 AV			3.41 V	246	67.0	31.8
5	4804.00	50.2 PK	74.0	-23.8	3.55 V	200	47.3	2.9
6	4804.00	38.0 AV	54.0	-16.0	3.55 V	200	35.1	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	Channel	CH 17 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	104.9 PK			1.18 H	76	73.1	31.8
2	*2440.00	102.1 AV			1.18 H	76	70.3	31.8
3	4880.00	51.8 PK	74.0	-22.2	2.31 H	101	48.8	3.0
4	4880.00	42.5 AV	54.0	-11.5	2.31 H	101	39.5	3.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	102.9 PK			3.44 V	235	71.1	31.8
2	*2440.00	100.2 AV			3.44 V	235	68.4	31.8
3	4880.00	50.6 PK	74.0	-23.4	3.57 V	192	47.6	3.0
4	4880.00	38.4 AV	54.0	-15.6	3.57 V	192	35.4	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	104.2 PK			1.19 H	62	72.3	31.9
2	*2480.00	101.5 AV			1.19 H	62	69.6	31.9
3	2483.50	58.7 PK	74.0	-15.3	1.19 H	62	26.8	31.9
4	2483.50	47.0 AV	54.0	-7.0	1.19 H	62	15.1	31.9
5	4960.00	51.8 PK	74.0	-22.2	2.47 H	93	48.6	3.2
6	4960.00	42.4 AV	54.0	-11.6	2.47 H	93	39.2	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	102.2 PK			3.41 V	237	70.3	31.9
2	*2480.00	99.5 AV			3.41 V	237	67.6	31.9
3	2483.50	58.0 PK	74.0	-16.0	3.41 V	237	26.1	31.9
4	2483.50	46.2 AV	54.0	-7.8	3.41 V	237	14.3	31.9
5	4960.00	50.6 PK	74.0	-23.4	3.53 V	202	47.4	3.2
6	4960.00	38.7 AV	54.0	-15.3	3.53 V	202	35.5	3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

Mode B

RF Mode	BT-LE 125K	Channel	CH 37 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.7 PK	74.0	-16.3	1.46 H	70	25.9	31.8
2	2390.00	45.7 AV	54.0	-8.3	1.46 H	70	13.9	31.8
3	*2402.00	103.0 PK			1.46 H	70	71.2	31.8
4	*2402.00	102.0 AV			1.46 H	70	70.2	31.8
5	4804.00	52.6 PK	74.0	-21.4	2.43 H	100	49.7	2.9
6	4804.00	42.6 AV	54.0	-11.4	2.43 H	100	39.7	2.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.6 PK	74.0	-16.4	3.31 V	244	25.8	31.8
2	2390.00	45.5 AV	54.0	-8.5	3.31 V	244	13.7	31.8
3	*2402.00	101.6 PK			3.31 V	244	69.8	31.8
4	*2402.00	100.8 AV			3.31 V	244	69.0	31.8
5	4804.00	50.7 PK	74.0	-23.3	3.44 V	203	47.8	2.9
6	4804.00	38.4 AV	54.0	-15.6	3.44 V	203	35.5	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 125K	Channel	CH 17 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	105.1 PK			1.05 H	66	73.3	31.8
2	*2440.00	104.0 AV			1.05 H	66	72.2	31.8
3	4880.00	52.7 PK	74.0	-21.3	2.33 H	102	49.7	3.0
4	4880.00	42.8 AV	54.0	-11.2	2.33 H	102	39.8	3.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	103.3 PK			3.37 V	241	71.5	31.8
2	*2440.00	102.2 AV			3.37 V	241	70.4	31.8
3	4880.00	50.8 PK	74.0	-23.2	3.47 V	202	47.8	3.0
4	4880.00	38.7 AV	54.0	-15.3	3.47 V	202	35.7	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 125K	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	103.0 PK			1.00 H	64	71.1	31.9
2	*2480.00	101.8 AV			1.00 H	64	69.9	31.9
3	2483.50	57.2 PK	74.0	-16.8	1.00 H	64	25.3	31.9
4	2483.50	46.0 AV	54.0	-8.0	1.00 H	64	14.1	31.9
5	4960.00	52.8 PK	74.0	-21.2	2.38 H	103	49.6	3.2
6	4960.00	42.9 AV	54.0	-11.1	2.38 H	103	39.7	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	100.9 PK			3.37 V	241	69.0	31.9
2	*2480.00	99.8 AV			3.37 V	241	67.9	31.9
3	2483.50	56.4 PK	74.0	-17.6	3.37 V	241	24.5	31.9
4	2483.50	45.6 AV	54.0	-8.4	3.37 V	241	13.7	31.9
5	4960.00	50.8 PK	74.0	-23.2	3.49 V	197	47.6	3.2
6	4960.00	38.5 AV	54.0	-15.5	3.49 V	197	35.3	3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 500K	Channel	CH 37 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.8 PK	74.0	-17.2	1.46 H	71	25.0	31.8
2	2390.00	45.7 AV	54.0	-8.3	1.46 H	71	13.9	31.8
3	*2402.00	103.6 PK			1.46 H	71	71.8	31.8
4	*2402.00	102.4 AV			1.46 H	71	70.6	31.8
5	4804.00	52.2 PK	74.0	-21.8	2.36 H	91	49.3	2.9
6	4804.00	42.3 AV	54.0	-11.7	2.36 H	91	39.4	2.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.6 PK	74.0	-17.4	3.40 V	242	24.8	31.8
2	2390.00	45.5 AV	54.0	-8.5	3.40 V	242	13.7	31.8
3	*2402.00	101.8 PK			3.40 V	242	70.0	31.8
4	*2402.00	100.9 AV			3.40 V	242	69.1	31.8
5	4804.00	50.4 PK	74.0	-23.6	3.50 V	200	47.5	2.9
6	4804.00	38.0 AV	54.0	-16.0	3.50 V	200	35.1	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 500K	Channel	CH 17 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	105.2 PK			1.01 H	64	73.4	31.8
2	*2440.00	104.2 AV			1.01 H	64	72.4	31.8
3	4880.00	52.7 PK	74.0	-21.3	2.41 H	92	49.7	3.0
4	4880.00	42.9 AV	54.0	-11.1	2.41 H	92	39.9	3.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	103.3 PK			3.32 V	243	71.5	31.8
2	*2440.00	102.3 AV			3.32 V	243	70.5	31.8
3	4880.00	50.7 PK	74.0	-23.3	3.50 V	197	47.7	3.0
4	4880.00	38.6 AV	54.0	-15.4	3.50 V	197	35.6	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 500K	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	103.0 PK			1.22 H	62	71.1	31.9
2	*2480.00	102.0 AV			1.22 H	62	70.1	31.9
3	2483.50	57.4 PK	74.0	-16.6	1.22 H	62	25.5	31.9
4	2483.50	46.1 AV	54.0	-7.9	1.22 H	62	14.2	31.9
5	4960.00	52.7 PK	74.0	-21.3	2.39 H	94	49.5	3.2
6	4960.00	42.8 AV	54.0	-11.2	2.39 H	94	39.6	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	101.1 PK			3.37 V	244	69.2	31.9
2	*2480.00	100.1 AV			3.37 V	244	68.2	31.9
3	2483.50	57.1 PK	74.0	-16.9	3.37 V	244	25.2	31.9
4	2483.50	45.7 AV	54.0	-8.3	3.37 V	244	13.8	31.9
5	4960.00	50.8 PK	74.0	-23.2	3.49 V	206	47.6	3.2
6	4960.00	38.6 AV	54.0	-15.4	3.49 V	206	35.4	3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 1M	Channel	CH 37 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.0 PK	74.0	-17.0	1.45 H	70	25.2	31.8
2	2390.00	45.9 AV	54.0	-8.1	1.45 H	70	14.1	31.8
3	*2402.00	103.8 PK			1.45 H	70	72.0	31.8
4	*2402.00	102.5 AV			1.45 H	70	70.7	31.8
5	4804.00	52.2 PK	74.0	-21.8	2.35 H	95	49.3	2.9
6	4804.00	42.6 AV	54.0	-11.4	2.35 H	95	39.7	2.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.9 PK	74.0	-17.1	3.40 V	235	25.1	31.8
2	2390.00	45.0 AV	54.0	-9.0	3.40 V	235	13.2	31.8
3	*2402.00	102.0 PK			3.40 V	235	70.2	31.8
4	*2402.00	101.0 AV			3.40 V	235	69.2	31.8
5	4804.00	50.0 PK	74.0	-24.0	3.55 V	194	47.1	2.9
6	4804.00	38.1 AV	54.0	-15.9	3.55 V	194	35.2	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 1M	Channel	CH 17 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	105.2 PK			1.01 H	65	73.4	31.8
2	*2440.00	104.0 AV			1.01 H	65	72.2	31.8
3	4880.00	52.4 PK	74.0	-21.6	2.42 H	99	49.4	3.0
4	4880.00	42.7 AV	54.0	-11.3	2.42 H	99	39.7	3.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	103.3 PK			3.33 V	240	71.5	31.8
2	*2440.00	102.1 AV			3.33 V	240	70.3	31.8
3	4880.00	50.5 PK	74.0	-23.5	3.49 V	205	47.5	3.0
4	4880.00	38.4 AV	54.0	-15.6	3.49 V	205	35.4	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 1M	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	103.0 PK			1.00 H	64	71.1	31.9
2	*2480.00	101.8 AV			1.00 H	64	69.9	31.9
3	2483.50	57.0 PK	74.0	-17.0	1.00 H	64	25.1	31.9
4	2483.50	46.0 AV	54.0	-8.0	1.00 H	64	14.1	31.9
5	4960.00	52.5 PK	74.0	-21.5	2.39 H	97	49.3	3.2
6	4960.00	42.7 AV	54.0	-11.3	2.39 H	97	39.5	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	101.1 PK			3.32 V	248	69.2	31.9
2	*2480.00	99.9 AV			3.32 V	248	68.0	31.9
3	2483.50	56.5 PK	74.0	-17.5	3.32 V	248	24.6	31.9
4	2483.50	45.7 AV	54.0	-8.3	3.32 V	248	13.8	31.9
5	4960.00	50.7 PK	74.0	-23.3	3.43 V	206	47.5	3.2
6	4960.00	38.4 AV	54.0	-15.6	3.43 V	206	35.2	3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	Channel	CH 37 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Charles Hsiao		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.8 PK	74.0	-17.2	1.45 H	70	25.0	31.8
2	2390.00	45.8 AV	54.0	-8.2	1.45 H	70	14.0	31.8
3	*2402.00	102.8 PK			1.45 H	70	71.0	31.8
4	*2402.00	99.3 AV			1.45 H	70	67.5	31.8
5	4804.00	51.5 PK	74.0	-22.5	2.39 H	97	48.6	2.9
6	4804.00	42.2 AV	54.0	-11.8	2.39 H	97	39.3	2.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.7 PK	74.0	-17.3	3.41 V	246	24.9	31.8
2	2390.00	45.6 AV	54.0	-8.4	3.41 V	246	13.8	31.8
3	*2402.00	100.6 PK			3.41 V	246	68.8	31.8
4	*2402.00	96.7 AV			3.41 V	246	64.9	31.8
5	4804.00	50.4 PK	74.0	-23.6	3.58 V	199	47.5	2.9
6	4804.00	38.3 AV	54.0	-15.7	3.58 V	199	35.4	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	Channel	CH 17 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	105.1 PK			1.04 H	66	73.3	31.8
2	*2440.00	102.3 AV			1.04 H	66	70.5	31.8
3	4880.00	51.7 PK	74.0	-22.3	2.39 H	91	48.7	3.0
4	4880.00	42.5 AV	54.0	-11.5	2.39 H	91	39.5	3.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	103.2 PK			3.37 V	241	71.4	31.8
2	*2440.00	100.4 AV			3.37 V	241	68.6	31.8
3	4880.00	50.6 PK	74.0	-23.4	3.50 V	203	47.6	3.0
4	4880.00	38.5 AV	54.0	-15.5	3.50 V	203	35.5	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68 % RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	104.4 PK			1.23 H	63	72.5	31.9
2	*2480.00	101.6 AV			1.23 H	63	69.7	31.9
3	2483.50	58.5 PK	74.0	-15.5	1.23 H	63	26.6	31.9
4	2483.50	47.2 AV	54.0	-6.8	1.23 H	63	15.3	31.9
5	4960.00	51.9 PK	74.0	-22.1	2.38 H	97	48.7	3.2
6	4960.00	42.4 AV	54.0	-11.6	2.38 H	97	39.2	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	102.5 PK			3.37 V	247	70.6	31.9
2	*2480.00	99.7 AV			3.37 V	247	67.8	31.9
3	2483.50	58.1 PK	74.0	-15.9	3.37 V	247	26.2	31.9
4	2483.50	46.2 AV	54.0	-7.8	3.37 V	247	14.3	31.9
5	4960.00	50.7 PK	74.0	-23.3	3.43 V	205	47.5	3.2
6	4960.00	38.7 AV	54.0	-15.3	3.43 V	205	35.5	3.2


Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.


Plot of Band Edge

Mode A


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--




BT-LE 125K Channel 39




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--

BT-LE 500K Channel 37




BT-LE 500K Channel 39


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--

BT-LE 1M Channel 37




BT-LE 1M Channel 39


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--

BT-LE 2M Channel 37




BT-LE 2M Channel 39


Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)




Vertical (Average)


Plot of Band Edge

Mode B


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--




BT-LE 125K Channel 39




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--

BT-LE 500K Channel 37




BT-LE 500K Channel 39


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--

BT-LE 1M Channel 37




BT-LE 1M Channel 39


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--

BT-LE 2M Channel 37




BT-LE 2M Channel 39


Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---