



FCC PART 15.247 TEST REPORT

For

ROAM Data Inc.

101 Federal Street, Suite 700, Boston, Massachusetts, United States

FCC ID: 2ABY6-RP450BT

Report Type: Original Report	Product Type: RP457 Mobile Payment Terminal
Report Number: RXM170112050-00A	
Report Date: 2017-03-21	
Oscar Ye	
Reviewed By: Engineer	
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE.....	10
APPLICABLE STANDARD	10
FCC §15.203 – ANTENNA REQUIREMENT	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	12
EUT SETUP	12
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
CORRECTED FACTOR & MARGIN CALCULATION	13
TEST RESULTS SUMMARY	13
TEST DATA	13
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	18
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	20
APPLICABLE STANDARD	20
TEST PROCEDURE	20
TEST DATA	20
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	27

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST DATA	33
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST DATA	36
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST DATA	52
FCC §15.247(d) - BAND EDGES TESTING	54
APPLICABLE STANDARD	54
TEST PROCEDURE	54
TEST DATA	54

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *ROAM Data Inc.* 's product, model number: *RP457 (FCC ID: 2ABY6-RP450BT)* in this report is an *RP457 Mobile Payment Terminal*, which was measured approximately: 6.5 cm (L) *6.5 cm (W) *2.0 cm (H), rated with input voltage: DC 3.7 V battery or DC 5V from USB port.

** All measurement and test data in this report was gathered from production sample serial number: 170112050 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2017-01-12.*

Objective

This test report is prepared on behalf of *ROAM Data Inc.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS and FCC Part 15.225 DXX submissions with FCC ID: 2ABY6-RP450BT.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		± 3.26 dB
RF conducted test with spectrum		± 0.9 dB
RF Output Power with Power meter		± 0.5 dB
Radiated emission	30MHz~1GHz	± 5.91 dB
	Above 1GHz	± 4.92 dB
Occupied Bandwidth		± 0.5 kHz
Temperature		± 1.0 °C
Humidity		$\pm 6\%$

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.10-2013.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

Software “FactoryTool V2.28 2” was used.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Lenovo	PC	T400	R8-LXAXE 09/12
DELL	Mouse	MOC5UO	G1900NKD
DELL	Adapter	LA90PM130	CN-06C3W2-72438-6BT-194A-A03

External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-Shielding Detachable USB Cable	1.5	PC	U disk
Un-Shielding Detachable USB Cable	1.5	PC	Mouse
Un-shielding Detachable USB Cable	1.0	EUT	PC
Un-shielding Detachable AC Cable	0.9	Adapter	LISN 1
Un-shielding Un-detachable DC Cable	0.9	Adapter	PC
Un-shielding Detachable RJ45 Cable	3.0	PC	Network

Block Diagram of Test Setup

For conducted emission



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conducted test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2016-11-25	2017-11-25
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2016-10-10	2017-10-10
Rohde & Schwarz	Pulse limiter	ESH3-Z2	879940/0058	2016-06-19	2017-06-18
MICRO-COAX	Coaxial line	UFB-293B-1-0480-50X50	97F0173	2016-09-08	2017-09-08
Rohde & Schwarz	CE Test software	EMC 32	V 09.10.0	NCR	NCR
Radiation test					
Sonoma Instrunent	Amplifier	330	171377	2016-12-12	2017-12-12
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-25
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-09-08	2017-09-08
EMCO	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-25
ETS	Horn Antenna	3115	6229	2016-01-11	2019-01-10
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR
haojintech	Coaxial Cable	Cable-1	001	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-2	002	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-3	003	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-4	004	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-5	005	2016-12-12	2017-12-12
RF Conducted test					
BACL	TS 8997 Cable-01	T-KS-EMC086	T-KS-EMC086	2016-12-09	2017-12-08
BACL	RF cable	KS-LAB-012	KS-LAB-012	2016-12-15	2017-12-15
WEINSCHL	3dB Attenuator	5326	N/A	2016-06-18	2017-06-18
Agilent	Power Meter	N1912A	MY5000492	2016-11-17	2017-11-16
Agilent	Power Sensor	N1921A	MY54210024	2016-11-17	2017-11-16
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2016-09-21	2017-09-21

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

For worst case:

Frequency (MHz)	Maximum conducted Tune-up power		Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
	Power (dBm)	Power (mW)				
2480	6.0	3.98	5	1.3	3.0	Yes

Result: No SAR test is required

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for bluetooth which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	24 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Layne Li on 2017-02-15.

EUT operation mode: Transmitting

AC 120V/60 Hz, Line:


Full Spectrum



Frequency (MHz)	QuasiPeak (dBμV)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.380000	---	25.76	9.000	L1	10.1	22.52	48.28	Compliance
0.380000	28.78	---	9.000	L1	10.1	29.50	58.28	Compliance
0.790000	---	18.76	9.000	L1	9.9	27.24	46.00	Compliance
0.790000	22.16	---	9.000	L1	9.9	33.84	56.00	Compliance
3.370000	---	15.54	9.000	L1	9.9	30.46	46.00	Compliance
3.370000	25.70	---	9.000	L1	9.9	30.30	56.00	Compliance
4.380000	---	15.20	9.000	L1	9.9	30.80	46.00	Compliance
4.380000	24.59	---	9.000	L1	9.9	31.41	56.00	Compliance
6.970000	---	19.90	9.000	L1	10.0	30.10	50.00	Compliance
6.970000	35.43	---	9.000	L1	10.0	24.57	60.00	Compliance
20.940000	---	15.06	9.000	L1	10.4	34.94	50.00	Compliance
20.940000	21.06	---	9.000	L1	10.4	38.94	60.00	Compliance

AC 120V/60 Hz, Neutral

Full Spectrum




Frequency (MHz)	QuasiPeak (dBμV)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170000	---	14.83	9.000	N	10.2	40.13	54.96	Compliance
0.170000	34.00	---	9.000	N	10.2	30.96	64.96	Compliance
0.380000	---	22.46	9.000	N	10.1	25.82	48.28	Compliance
0.380000	25.26	---	9.000	N	10.1	33.02	58.28	Compliance
1.670000	---	17.33	9.000	N	9.9	28.67	46.00	Compliance
1.670000	24.69	---	9.000	N	9.9	31.31	56.00	Compliance
2.360000	---	18.28	9.000	N	9.9	27.72	46.00	Compliance
2.360000	26.54	---	9.000	N	9.9	29.46	56.00	Compliance
4.890000	---	21.10	9.000	N	9.9	24.90	46.00	Compliance
4.890000	28.12	---	9.000	N	9.9	27.88	56.00	Compliance
7.140000	---	19.90	9.000	N	9.9	30.10	50.00	Compliance
7.140000	35.44	---	9.000	N	9.9	24.56	60.00	Compliance

Note:

- 1) Corrected Amplitude = Reading + Correction Factor
- 2) Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation
- 3) Margin = Limit – Corrected Amplitude

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, 205 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(L_m)}$ is less than $+ U_{cispr}$, if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Layne Li on 2017-02-15.

EUT operation mode: Transmitting

30 MHz -25 GHz: (Scan with GFSK, $\pi/4$ -DQPSK, 8-DPSK mode, the worst case is BDR Mode (GFSK))

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2402 MHz)									
154.62	44.77	QP	238	2.1	H	-12.08	32.69	43.5	10.81
2402.00	102.95	PK	62	1.6	H	-6.19	96.76	/	/
2402.00	92.52	Ave.	62	1.6	H	-6.19	86.33	/	/
2402.00	97.43	PK	250	1.1	V	-6.19	91.24	/	/
2402.00	86.89	Ave.	250	1.1	V	-6.19	80.70	/	/
2355.69	68.52	PK	273	1.3	H	-6.19	62.33	74	11.67
2355.69	54.47	Ave.	273	1.3	H	-6.19	48.28	54	5.72
2345.43	68.46	PK	148	1.4	H	-6.42	62.04	74	11.96
2345.43	54.50	Ave.	148	1.4	H	-6.42	48.08	54	5.92
2490.14	67.61	PK	12	1.5	H	-5.97	61.64	74	12.36
2490.14	54.24	Ave.	12	1.5	H	-5.97	48.27	54	5.73
4804.00	50.14	PK	55	1.6	H	1.6	51.74	74	22.26
4804.00	35.93	Ave.	55	1.6	H	1.6	37.53	54	16.47

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2441 MHz)									
154.62	43.92	QP	88	1.3	H	-12.08	31.84	43.5	11.66
2441.00	103.13	PK	184	1.4	H	-6.19	96.94	/	/
2441.00	92.11	Ave.	184	1.4	H	-6.19	85.92	/	/
2441.00	97.95	PK	113	1.9	V	-6.19	91.76	/	/
2441.00	87.94	Ave.	113	1.9	V	-6.19	81.75	/	/
2373.64	68.25	PK	249	2.5	H	-6.19	62.06	74	11.94
2373.64	54.37	Ave.	249	2.5	H	-6.19	48.18	54	5.82
2367.39	68.13	PK	21	1.2	H	-6.19	61.94	74	12.06
2367.39	54.25	Ave.	21	1.2	H	-6.19	48.06	54	5.94
2497.45	68.18	PK	215	2.0	H	-5.97	62.21	74	11.79
2497.45	54.14	Ave.	215	2.0	H	-5.97	48.17	54	5.83
4882.00	52.28	PK	93	1.2	H	1.83	54.11	74	19.89
4882.00	36.88	Ave.	93	1.2	H	1.83	38.71	54	15.29
High Channel (2480 MHz)									
154.62	44.69	QP	81	2.4	H	-12.08	32.61	43.5	10.89
2480.00	102.98	Ave.	274	1.1	H	-5.97	97.01	/	/
2480.00	92.57	PK	274	1.1	H	-5.97	86.60	/	/
2480.00	98.81	Ave.	316	1.8	V	-5.97	92.84	/	/
2480.00	88.4	PK	316	1.8	V	-5.97	82.43	/	/
2386.79	68.28	PK	304	1.5	H	-6.19	62.09	74	11.91
2386.79	54.43	Ave.	304	1.5	H	-6.19	48.24	54	5.76
2490.86	67.66	PK	230	1.9	H	-5.97	61.69	74	12.31
2490.86	54.13	Ave.	230	1.9	H	-5.97	48.16	54	5.84
2486.37	68.26	PK	175	1.8	H	-5.97	62.29	74	11.71
2486.37	54.25	Ave.	175	1.8	H	-5.97	48.28	54	5.72
4960.00	53.04	PK	82	2.4	H	2.06	55.10	74	18.90
4960.00	38.09	Ave.	82	2.4	H	2.06	40.15	54	13.85

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Ada Yu on 2017-02-13.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	≥Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.004	0.697	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.693	Pass
	Adjacent	2442			
	High	2480	1.004	0.697	Pass
	Adjacent	2479			
EDR (π/4-DQPSK)	Low	2402	1.004	0.850	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.850	Pass
	Adjacent	2442			
	High	2480	1.004	0.854	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.004	0.829	Pass
	Adjacent	2403			
	Middle	2441	0.998	0.834	Pass
	Adjacent	2442			
	High	2480	1.004	0.838	Pass
	Adjacent	2479			

Note: Limit = 20 dB bandwidth *2/3


BDR (GFSK): Low Channel




BDR (GFSK): Middle Channel




BDR (GFSK): High Channel




EDR ($\pi/4$ -DQPSK): Low Channel




EDR ($\pi/4$ -DQPSK): Middle Channel




EDR ($\pi/4$ -DQPSK): High Channel




EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data**Environmental Conditions**

Temperature:	22~24 °C
Relative Humidity:	45~50 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Ada Yu from 2017-02-13 to 2017-02-14.

Test Result: Compliance. Please refer to following table and plots.

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	1.046
	Middle	2441	1.040
	High	2480	1.046
EDR ($\pi/4$ -DQPSK)	Low	2402	1.275
	Middle	2441	1.275
	High	2480	1.281
EDR (8DPSK)	Low	2402	1.244
	Middle	2441	1.251
	High	2480	1.257

Ref Lvl 23.5 dBm BW 1.04609218 MHz SWT 8.5 ms Unit dBm

3.5 dB Offset

Marker 1 [T1 ndB] 0.15 dBm

2.40199098 GHz

20.00 dB

1.04609218 MHz

-18.23 dBm

2.40146794 GHz


-18.92 dBm

2.40251403 GHz


Center 2.402 GHz 300 kHz/ Span 3 MHz

Date: 14.FEB.2017 17:16:55


BDR (GFSK): Middle Channel




BDR (GFSK): High Channel





EDR ($\pi/4$ -DQPSK): Low Channel




EDR ($\pi/4$ -DQPSK): Middle Channel




EDR ($\pi/4$ -DQPSK): High Channel**EDR (8DPSK): Low Channel**

EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa


The testing was performed by Ada Yu on 2017-02-13.



EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥ 15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥ 15
EDR (8DPSK)	2400-2483.5	79	≥ 15

BDR (GFSK): Number of Hopping Channels



EDR ($\pi/4$ -DQPSK): Number of Hopping Channels**EDR (8DPSK): Number of Hopping Channels**

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Test Data**Environmental Conditions**

Temperature:	22~24 °C
Relative Humidity:	45~50 %
ATM Pressure:	100.0~101.0 kPa


The testing was performed by Ada Yu from 2017-02-13 to 2017-02-14.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to following table and plots.

Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.389	0.124	0.4	Pass
		Middle	0.389	0.124	0.4	Pass
		High	0.389	0.124	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.663	0.266	0.4	Pass
		Middle	1.663	0.266	0.4	Pass
		High	1.663	0.266	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	2.916	0.311	0.4	Pass
		Middle	2.916	0.311	0.4	Pass
		High	2.916	0.311	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	2DH 1	Low	0.397	0.127	0.4	Pass
		Middle	0.397	0.127	0.4	Pass
		High	0.397	0.127	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH 3	Low	1.665	0.266	0.4	Pass
		Middle	1.665	0.266	0.4	Pass
		High	1.665	0.266	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH 5	Low	2.991	0.319	0.4	Pass
		Middle	2.991	0.319	0.4	Pass
		High	2.991	0.319	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH 1	Low	0.397	0.127	0.4	Pass
		Middle	0.397	0.127	0.4	Pass
		High	0.397	0.127	0.4	Pass
		Note: 3DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH 3	Low	1.665	0.266	0.4	Pass
		Middle	1.665	0.266	0.4	Pass
		High	1.665	0.266	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH 5	Low	2.911	0.311	0.4	Pass
		Middle	2.911	0.311	0.4	Pass
		High	2.911	0.311	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				


BDR (GFSK): Pulse time, Low Channel, DH1




Pulse time, Middle Channel, DH1




Pulse time, High Channel, DH1




Pulse time, Low Channel, DH3



Pulse time, Middle Channel, DH3



Pulse time, High Channel, DH3



Ref Lvl 23.5 dBm Delta 1 [T1] -2.47 dB RBW 1 MHz RF Att 40 dB

23.5 dBm 2.915832 ms SWT 5 ms Unit dBm

3.5 dB Offset

Center 2.402 GHz 500 μ s/



Date: 13.FEB.2017 16:26:48

Ref Lvl 23.5 dBm Delta 1 [T1] -2.44 dB VBW 3 MHz RBW 1 MHz RF Att 40 dB


3.5 dB Offset 2.915832 ms Unit dBm

Center 2.441 GHz 500 MHz


Date: 13.FEB.2017 16:27:12

Pulse time, High Channel, DH5**EDR ($\pi/4$ -DQPSK):
Pulse time, Low Channel, 2DH1**


Pulse time, Middle Channel, 2DH1




Pulse time, High Channel, 2DH1




Pulse time, Low Channel, 2DH3




Pulse time, Middle Channel, 2DH3




Pulse time, High Channel, 2DH3




Pulse time, Low Channel, 2DH5




Pulse time, Middle Channel, 2DH5




Pulse time, High Channel, 2DH5




EDR (8DPSK): Pulse time, Low Channel, 3DH1




Pulse time, Middle Channel, 3DH1



Pulse time, High Channel, 3DH1



Pulse time, Low Channel, 3DH3



Ref Lvl 23.5 dBm Delta 1 [T1] -1.26 dB RBW 1 MHz RF Att 40 dB

23.5 dBm 1.664529 ms SWT 3 ms Unit dBm


3.5 dB Offset

Center 2.441 GHz 300 μ s/div


Date: 14.FEB.2017 17:34:59

Delta 1 [T1] -1.49 dB
Delta 2 [T2] -1.49 dB
Delta 3 [T3] -1.49 dB
Delta 4 [T4] -1.49 dB
Delta 5 [T5] -1.49 dB
Delta 6 [T6] -1.49 dB
Delta 7 [T7] -1.49 dB
Delta 8 [T8] -1.49 dB
Delta 9 [T9] -1.49 dB
Delta 10 [T10] -1.49 dB
Delta 11 [T11] -1.49 dB
Delta 12 [T12] -1.49 dB
Delta 13 [T13] -1.49 dB
Delta 14 [T14] -1.49 dB
Delta 15 [T15] -1.49 dB
Delta 16 [T16] -1.49 dB
Delta 17 [T17] -1.49 dB
Delta 18 [T18] -1.49 dB
Delta 19 [T19] -1.49 dB
Delta 20 [T20] -1.49 dB
Delta 21 [T21] -1.49 dB
Delta 22 [T22] -1.49 dB
Delta 23 [T23] -1.49 dB
Delta 24 [T24] -1.49 dB
Delta 25 [T25] -1.49 dB
Delta 26 [T26] -1.49 dB
Delta 27 [T27] -1.49 dB
Delta 28 [T28] -1.49 dB
Delta 29 [T29] -1.49 dB
Delta 30 [T30] -1.49 dB
Delta 31 [T31] -1.49 dB
Delta 32 [T32] -1.49 dB
Delta 33 [T33] -1.49 dB
Delta 34 [T34] -1.49 dB
Delta 35 [T35] -1.49 dB
Delta 36 [T36] -1.49 dB
Delta 37 [T37] -1.49 dB
Delta 38 [T38] -1.49 dB
Delta 39 [T39] -1.49 dB
Delta 40 [T40] -1.49 dB
Delta 41 [T41] -1.49 dB
Delta 42 [T42] -1.49 dB
Delta 43 [T43] -1.49 dB
Delta 44 [T44] -1.49 dB
Delta 45 [T45] -1.49 dB
Delta 46 [T46] -1.49 dB
Delta 47 [T47] -1.49 dB
Delta 48 [T48] -1.49 dB
Delta 49 [T49] -1.49 dB
Delta 50 [T50] -1.49 dB
Delta 51 [T51] -1.49 dB
Delta 52 [T52] -1.49 dB
Delta 53 [T53] -1.49 dB
Delta 54 [T54] -1.49 dB
Delta 55 [T55] -1.49 dB
Delta 56 [T56] -1.49 dB
Delta 57 [T57] -1.49 dB
Delta 58 [T58] -1.49 dB
Delta 59 [T59] -1.49 dB
Delta 60 [T60] -1.49 dB
Delta 61 [T61] -1.49 dB
Delta 62 [T62] -1.49 dB
Delta 63 [T63] -1.49 dB
Delta 64 [T64] -1.49 dB
Delta 65 [T65] -1.49 dB
Delta 66 [T66] -1.49 dB
Delta 67 [T67] -1.49 dB
Delta 68 [T68] -1.49 dB
Delta 69 [T69] -1.49 dB
Delta 70 [T70] -1.49 dB
Delta 71 [T71] -1.49 dB
Delta 72 [T72] -1.49 dB
Delta 73 [T73] -1.49 dB
Delta 74 [T74] -1.49 dB
Delta 75 [T75] -1.49 dB
Delta 76 [T76] -1.49 dB
Delta 77 [T77] -1.49 dB
Delta 78 [T78] -1.49 dB
Delta 79 [T79] -1.49 dB
Delta 80 [T80] -1.49 dB
Delta 81 [T81] -1.49 dB
Delta 82 [T82] -1.49 dB
Delta 83 [T83] -1.49 dB
Delta 84 [T84] -1.49 dB
Delta 85 [T85] -1.49 dB
Delta 86 [T86] -1.49 dB
Delta 87 [T87] -1.49 dB
Delta 88 [T88] -1.49 dB
Delta 89 [T89] -1.49 dB
Delta 90 [T90] -1.49 dB
Delta 91 [T91] -1.49 dB
Delta 92 [T92] -1.49 dB
Delta 93 [T93] -1.49 dB
Delta 94 [T94] -1.49 dB
Delta 95 [T95] -1.49 dB
Delta 96 [T96] -1.49 dB
Delta 97 [T97] -1.49 dB
Delta 98 [T98] -1.49 dB
Delta 99 [T99] -1.49 dB
Delta 100 [T100] -1.49 dB
Delta 101 [T101] -1.49 dB
Delta 102 [T102] -1.49 dB
Delta 103 [T103] -1.49 dB
Delta 104 [T104] -1.49 dB
Delta 105 [T105] -1.49 dB
Delta 106 [T106] -1.49 dB
Delta 107 [T107] -1.49 dB
Delta 108 [T108] -1.49 dB
Delta 109 [T109] -1.49 dB
Delta 110 [T110] -1.49 dB
Delta 111 [T111] -1.49 dB
Delta 112 [T112] -1.49 dB
Delta 113 [T113] -1.49 dB
Delta 114 [T114] -1.49 dB
Delta 115 [T115] -1.49 dB
Delta 116 [T116] -1.49 dB
Delta 117 [T117] -1.49 dB
Delta 118 [T118] -1.49 dB
Delta 119 [T119] -1.49 dB
Delta 120 [T120] -1.49 dB
Delta 121 [T121] -1.49 dB
Delta 122 [T122] -1.49 dB
Delta 123 [T123] -1.49 dB
Delta 124 [T124] -1.49 dB
Delta 125 [T125] -1.49 dB
Delta 126 [T126] -1.49 dB
Delta 127 [T127] -1.49 dB
Delta 128 [T128] -1.49 dB
Delta 129 [T129] -1.49 dB
Delta 130 [T130] -1.49 dB
Delta 131 [T131] -1.49 dB
Delta 132 [T132] -1.49 dB
Delta 133 [T133] -1.49 dB
Delta 134 [T134] -1.49 dB
Delta 135 [T135] -1.49 dB
Delta 136 [T136] -1.49 dB
Delta 137 [T137] -1.49 dB
Delta 138 [T138] -1.49 dB
Delta 139 [T139] -1.49 dB
Delta 140 [T140] -1.49 dB
Delta 141 [T141] -1.49 dB
Delta 142 [T142] -1.49 dB
Delta 143 [T143] -1.49 dB
Delta 144 [T144] -1.49 dB
Delta 145 [T145] -1.49 dB
Delta 146 [T146] -1.49 dB
Delta 147 [T147] -1.49 dB
Delta 148 [T148] -1.49 dB
Delta 149 [T149] -1.49 dB
Delta 150 [T150] -1.49 dB
Delta 151 [T151] -1.49 dB
Delta 152 [T152] -1.49 dB
Delta 153 [T153] -1.49 dB
Delta 154 [T154] -1.49 dB
Delta 155 [T155] -1.49 dB
Delta 156 [T156] -1.49 dB
Delta 157 [T157] -1.49 dB
Delta 158 [T158] -1.49 dB
Delta 159 [T159] -1.49 dB
Delta 160 [T160] -1.49 dB
Delta 161 [T161] -1.49 dB
Delta 162 [T162] -1.49 dB
Delta 163 [T163] -1.49 dB
Delta 164 [T164] -1.49 dB
Delta 165 [T165] -1.49 dB
Delta 166 [T166] -1.49 dB
Delta 167 [T167] -1.49 dB
Delta 168 [T168] -1.49 dB
Delta 169 [T169] -1.49 dB
Delta 170 [T170] -1.49 dB
Delta 171 [T171] -1.49 dB
Delta 172 [T172] -1.49 dB
Delta 173 [T173] -1.49 dB
Delta 174 [T174] -1.49 dB
Delta 175 [T175] -1.49 dB
Delta 176 [T176] -1.49 dB
Delta 177 [T177] -1.49 dB
Delta 178 [T178] -1.49 dB
Delta 179 [T179] -1.49 dB
Delta 180 [T180] -1.49 dB
Delta 181 [T181] -1.49 dB
Delta 182 [T182] -1.49 dB
Delta 183 [T183] -1.49 dB
Delta 184 [T184] -1.49 dB
Delta 185 [T185] -1.49 dB
Delta 186 [T186] -1.49 dB
Delta 187 [T187] -1.49 dB
Delta 188 [T188] -1.49 dB
Delta 189 [T189] -1.49 dB
Delta 190 [T190] -1.49 dB
Delta 191 [T191] -1.49 dB
Delta 192 [T192] -1.49 dB
Delta 193 [T193] -1.49 dB
Delta 194 [T194] -1.49 dB
Delta 195 [T195] -1.49 dB
Delta 196 [T196] -1.49 dB
Delta 197 [T197] -1.49 dB
Delta 198 [T198] -1.49 dB
Delta 199 [T199] -1.49 dB
Delta 200 [T200] -1.49 dB
Delta 201 [T201] -1.49 dB
Delta 202 [T202] -1.49 dB
Delta 203 [T203] -1.49 dB
Delta 204 [T204] -1.49 dB
Delta 205 [T205] -1.49 dB
Delta 206 [T206] -1.49 dB
Delta 207 [T207] -1.49 dB
Delta 208 [T208] -1.49 dB
Delta 209 [T209] -1.49 dB
Delta 210 [T210] -1.49 dB
Delta 211 [T211] -1.49 dB
Delta 212 [T212] -1.49 dB
Delta 213 [T213] -1.49 dB
Delta 214 [T214] -1.49 dB
Delta 215 [T215] -1.49 dB
Delta 216 [T216] -1.49 dB
Delta 217 [T217] -1.49 dB
Delta 218 [T218] -1.4


Pulse time, Low Channel, 3DH5



Pulse time, Middle Channel, 3DH5



Pulse time, High Channel, 3DH5



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Ada Yu on 2017-02-13.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

Mode	Channel	Frequency (MHz)	Reading Power (dBm)	Peak Output Power (mW)	Limit (mW)
BDR (GFSK)	Low	2402	4.17	2.61	1000
	Middle	2441	4.68	2.94	1000
	High	2480	4.56	2.86	1000
EDR ($\pi/4$-DQPSK)	Low	2402	4.93	3.11	1000
	Middle	2441	5.30	3.39	1000
	High	2480	5.18	3.30	1000
EDR (8DPSK)	Low	2402	5.55	3.60	1000
	Middle	2441	5.93	3.92	1000
	High	2480	5.80	3.80	1000

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions


Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Ada Yu on 2017-02-13.


EUT operation mode: Transmitting



Test Result: Compliance. Please refer to following plots.

BDR (GFSK): Band Edge-Left Side




BDR (GFSK): Band Edge-Right Side




EDR ($\pi/4$ -DQPSK): Band Edge-Left Side**EDR ($\pi/4$ -DQPSK): Band Edge-Right Side**

EDR (8DPSK): Band Edge-Left Side



BDR (8DPSK): Band Edge-Right Side



***** END OF REPORT *****