



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number:AN0433-PCB400110

Product Name: Antenna

Specification For Approval

Date: 2024.9.27

Version: 1.0

客户名称

Customer:

神牛

客户料号

Customer P/N:

122-40111-000

腾祥料号

T X P/N:

AN0433-PCB400110

规格描述

Description :

433MHz PCB 天线

Tengxiang Checked By: 腾祥审核		Customer Approved By: 客户审核	
DRAWN 制作	路婷	TESTED BY 检测	
CHECKED BY 审核	胡超	CHECKED BY 审核	
Q.C.DEPT. 品管	江美如	Q.C.DEPT. 品管	
APPROVED BY 核准	韦佳	APPROVEDBY 核准	



NO.53 Shatou ShaChong Road, ChangAn Town, Guangdong province, China

中国广东省东莞市长安镇沙头区沙涌路 53 号

TEL:86-769-81873082 FAX:86-769-82663788

<http://www.tenxiang.cn>



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number:AN0433-PCB400110

Product Name: Antenna

Index:

1. Specification (规格)
2. Characteristics and Reliability Test (产品特性和可靠性测试标准)
3. Antenna - S Parameter Test Data (样品测试数据)
4. Antenna - Radiation Pattern Test Data (辐射模式测试数据)
5. Mechanical and Packing Drawing (图纸包装规范)


Revision History (变更履历)

Revision	Date	Change Notification	Description
1.0	2024.9.27	初版	

Product Number: AN0433-PCB400110

Product Name: Antenna

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency 频率	433 MHz
S.W.R. 驻波比	≤ 2.0
Polarization 极化方式	Linear
Impedance 阻抗	50 Ohm
B. Material & Mechanical Characteristics	
Cable Type 线材规格	/
Connector Type 连接器规格	/
C. Environmental	
Storage Temperature 存储温度	- 40°C ~ +80 °C
Operation Temperature 工作温度	- 40°C ~ +80 °C

Product Number: AN0433-PCB400110

Product Name: Antenna


2. Characteristics and Reliability Test

Test Items 测试项目		Test Condition and Procedure 测试方法	Requirements 要求	Result 结果
1	V.S.W.R. 电压驻波比	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
2	Insertion Loss 插入损失	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
3	Solderability 可焊性	GB / T2423.28-2005 Temp: 260±5° C; Duration: 5 seconds 温度 260±5° C; 持续 5 秒	Tin evenly on full 上锡均匀饱满	PASS
4	Pull Test 拉力	Holding with individual specification; force applied to axis of terminal 单独定义产品端子拉力	1. Directive DUT specification 2. Frequency Tol. ≤5% 符合待测物规范; 频率偏移 ≤5%	PASS
5	Dimension 尺寸	Inspection of dimension, color, material, package, surface process. 检查尺寸, 颜色, 材料, 包装, 表面处理	Directive DUT specification 符合待测物规范	PASS
6	Salt Spray 盐雾	GB / T 2423.17-2008 Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%; Time: 24H 温度 35°C; 湿度 ≥95%; 盐水浓度 ≥5%; 测试 24H	1. No Visual Damage 2. Frequency Tol. ≤5% 无明显外观不良; 频率偏移 ≤5%	PASS
7	RoHS	With Reference to IEC 62321:2008 with flow chart 参考 IEC 62321 测试流程	Directive RoHS 2015/863/EU 符合 RoHS 2015/863/EU 标准	PASS


Product Number: AN0433-PCB400110

Product Name: Antenna

3. Antenna - S Parameter Test Data



4. Mechanical Drawing See attached files



HF ☐

RoHS ☒

REACH ☐

CONFIDENTIAL

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			

焊接區 (OSP)

布線區

40.0±0.2

11.0±0.2

Ø0.4 (通孔导电)

AN0433-PCB400110

背面

正面

备注:

- 1.材质: PCB(FR4) T=1.0mm
- 2.颜色/表面处理: 双面过黑油;白色印字
- 3.尺寸: 带*为重点尺寸;带Cpk尺寸需做制程能力管控(≧1.33)
- 4.公差: 未标注公差请参照标准公差.



Tengxiang Electronics Co., Ltd.

TITLE: 433MHz PCB

PART NO.: AN0433-PCB400110

CUSTOMER P/N: /

APP BY	CHK BY	RF BY	DES BY	UNITS: mm	Tolerance
			SY	SCALE: 1/1	X.X ±0.10
			2024.06.28	REVISION: A	X.XX ±0.05
					X° ±1

产品包装规范

PACKING CRITERION

Date: 2024.07.22

Page: 1 of 1


Part Number : AN0433-PCB400110

Revision : A

Name: Antenna


Customer : ALL

1 . Enter PE bag。




100pcs/ PE bag

2.PACKING。



8000pcs/Carton

3. SEALING。




SIDE

ITEM NO:
QTY: PCS
N W: KGS
G W: KGS
MEAS

FRONT

C/NO
MADE IN CHINA



APPROVED BY : YCX

CHECKED BY : HC

DESIGNED BY : SY Y