



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number:AN2400-FPC288BX

Product Name: Antenna

Specification For Approval

Date: 2024.10.24

Version: 1.0

客户名称

Customer:

神牛

客户料号

Customer P/N:

122-80081-000

腾祥料号

T X P/N:

AN2400-FPC288BX

规格描述

Description : 2.4GFPC 天线 0.81mm 黑色线 L=55mm +IPEX (2代)

Tengxiang Checked By: 腾祥审核		Customer Approved By: 客户审核	
DRAWN 制作	路婷	TESTED BY 检测	
CHECKED BY 审核	胡超	CHECKED BY 审核	
Q.C.DEPT. 品管	江美如	Q.C.DEPT. 品管	
APPROVED BY 核准	韦佳	APPROVEDBY 核准	



NO.53 Shatou ShaChong Road, ChangAn Town, Guangdong province, China

中国广东省东莞市长安镇沙头区沙涌路 53 号

TEL:86-769-81873082 FAX:86-769-82663788

<http://www.tenxiang.cn>



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number:AN2400-FPC288BX

Product Name: Antenna

Index:

- 1. Specification (规格)
- 2. Characteristics and Reliability Test (产品特性和可靠性测试标准)
- 3. Antenna - S Parameter Test Data (样品测试数据)
- 4. Antenna - Radiation Pattern Test Data (辐射模式测试数据)
- 5. Mechanical and Packing Drawing (图纸包装规范)

Revision History (变更履历)

Revision	Date	Change Notification	Description
1.0	2024.10.24	初版	

Product Number: AN2400-FPC288BX

Product Name: Antenna

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency 频率	2400-2500MHz
S.W.R. 驻波比	≤ 2.0
Antenna Gain 增益	0.36dBi
Polarization 极化方式	Linear
Impedance 阻抗	50 Ohm
B. Material & Mechanical Characteristics	
Cable Type 线材规格	OD0.81mm ,Black
Connector Type 连接器规格	I-PEX
C. Environmental	
Storage Temperature 存储温度	- 40°C ~ +80 °C
Operation Temperature 工作温度	- 40°C ~ +80 °C

Product Number: AN2400-FPC288BX

Product Name: Antenna


2. Characteristics and Reliability Test

Test Items 测试项目		Test Condition and Procedure 测试方法	Requirements 要求	Result 结果
1	V.S.W.R. 电压驻波比	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
2	Insertion Loss 插入损失	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
3	Antenna Gain 天线增益	Set DUT on Antenna Chamber; make individual calibration to test 设置天线暗室参数进行测试	Directive DUT specification 符合待测物规范	PASS
4	Solderability 可焊性	GB / T2423.28-2005 Temp: 260±5° C; Duration: 5 seconds 温度 260±5° C; 持续 5 秒	Tin evenly on full 上锡均匀饱满	PASS
5	Pull Test 拉力	Holding with individual specification; force applied to axis of terminal .单独定义产品端子拉力	1. Directive DUT specification 2. Frequency Tol. ≤5% 符合待测物规范; 频率偏移 ≤5%	PASS
6	Dimension 尺寸	Inspection of dimension, color, material, package, surface process. 检查尺寸, 颜色, 材料, 包装, 表面处理	Directive DUT specification 符合待测物规范	PASS
7	Salt Spray 盐雾	GB / T 2423.17-2008 Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%; Time: 24H 温度 35°C; 湿度 ≥95%; 盐水浓度 ≥5%; 测试 24H	1. No Visual Damage 2. Frequency Tol. ≤5% 无明显外观不良; 频率偏移 ≤5%	PASS
8	RoHS	With Reference to IEC 62321:2008 with flow chart 参考 IEC 62321 测试流程	Directive RoHS 2015/863/EU 符合 RoHS 2015/863/EU 标准	PASS

Product Number:AN2400-FPC288BX

Product Name: Antenna

3. Antenna - S Parameter Test Data



4. Antenna - Radiation Pattern Test Data

Frequency ID	1	2	3	4	5	6	7	8	9	10	11
Frequency (MHz)	2400.0	2410.0	2420.0	2430.0	2440.0	2450.0	2460.0	2470.0	2480.0	2490.0	2500.0
Gain (dBi)	0.15	0.25	0.30	0.33	0.36	0.34	0.26	0.24	0.20	0.15	0.10
Efficiency (%)	33.57	34.73	33.06	33.36	34.52	35.04	35.69	33.84	32.69	33.60	32.20

Product Number:AN2400-FPC288BX





Product Name: Antenna

XZ





YZ

XY





2400MHz



2450MHz



2500MHz



5. Mechanical Drawing See attached files

1	2	3	4	5	6	7	8																			
HF☐ RoHS2.0☒ REACH☐ CONFIDENTIAL					<table><tr><td>SIGN</td><td>DATE</td><td>DESCRIPTION</td><td>APPROVER</td></tr><tr><td>△</td><td></td><td></td><td></td></tr><tr><td>△</td><td></td><td></td><td></td></tr><tr><td>△</td><td></td><td></td><td></td></tr></table>			SIGN	DATE	DESCRIPTION	APPROVER	△				△				△						
SIGN	DATE	DESCRIPTION	APPROVER																							
△																										
△																										
△																										
E								E																		
D								D																		
C	二代端子 28.55±0.2 1.7 2.2 55.0±3.0 6.35±0.2 1 2							C																		
B	Note: 1.Mark* is important dimension;"Cpk "Identify for process control(CpK≥ 1.33). 2.Tolerance:Unmarked tolerance refer to the standard tolerance please. 3.Pay attention to the direction of the connector.							B																		
A	<table><tr><td>2</td><td>CCABLE-081-055BX</td><td>Coaxial Cable</td><td>OD0.81</td><td>Black</td><td>1</td></tr><tr><td>1</td><td>AN2400-FPC285063-2</td><td>FPC</td><td></td><td>Black</td><td>1</td></tr><tr><td>No.</td><td>Part Number</td><td>Name</td><td>Material</td><td>Finish</td><td>Q'ty</td></tr></table>							2	CCABLE-081-055BX	Coaxial Cable	OD0.81	Black	1	1	AN2400-FPC285063-2	FPC		Black	1	No.	Part Number	Name	Material	Finish	Q'ty	A
2	CCABLE-081-055BX	Coaxial Cable	OD0.81	Black	1																					
1	AN2400-FPC285063-2	FPC		Black	1																					
No.	Part Number	Name	Material	Finish	Q'ty																					
1	2	3	4	5	6	7	8																			



Tengxiang Electronics Co., Ltd.

TITLE: Antenna

PART NO.: AN2400-FPC288BX

CUSTOMER P/N: /

APP BY

CHK BY

RF BY

DES BY



Tolerance

YCX

HC

WJ

SY

UNITS: mm

X.X ±0.5

2024.10.23

2024.10.23

2024.10.23

2024.10.23

SCALE: 1/1

X.XX ±0.2

REVISION: A

X° ±1

产品包装规范


PACKING CRITERION

Date: 2024.10.23

Page: 1 of 1


Part Number : AN2400-FPC288BX	Revision : A
Name: Antenna	Customer : ALL

1 . Enter PE bag。




100pcs/ PE bag

2.PACKING。




8000pcs/Carton


3. SEALING。



SIDE



FRONT



APPROVED BY : YCX CHECKED BY : HC DESIGNED BY : SY Y