

Mach Speed Technologies, LLC

Application
For
Certification

FCC ID: 2ABYR-G410

Tablet PC

Model: Trio Stealth G4 10.1 v2

WiFi Transceiver

Report No.: 140926001SZN-004

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-13]

Prepared and Checked by:

Approved by:

Sign on file
William Chen
Project Engineer

Andy Yan
Senior Project Engineer
Date: 15 October 2014

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF no.: FCC 15C_Tx_b

Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch

6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751 Website: www.china.intertek-etlsemko.com

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Product Labeling
<i>EXHIBIT 7:</i>	Technical Specifications
<i>EXHIBIT 8:</i>	Instruction Manual
<i>EXHIBIT 9:</i>	Confidentiality Request
<i>EXHIBIT 10:</i>	Miscellaneous Information
<i>EXHIBIT 11:</i>	Test Equipment List

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

MODEL: Trio Stealth G4 10.1 v2

FCC ID: 2ABYR-G410

This report concerns (check one) Original Grant ☒ Class II Change ☐

Equipment Type: DTS - Part 15 Digital Transmission Systems (WiFi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until :
date

Company Name agrees to notify the Commission by:
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-13 Edition] provision.

Report prepared by:

Willam Chen
Intertek Testing Services Shenzhen Ltd.
Kejiyuan Branch
6F, D Block, Huahan Building, Langshan Road,
Nanshan District, Shenzhen, P. R. China
Phone: (86 755) 8614 0627
Fax: (86 755) 8614 6751

INTERTEK TESTING SERVICES

Table of Contents

1.0 <u>Summary of test results</u>	2
2.0 <u>General Description</u>	4
2.1 Product Description	4
2.2 Related Submittal(s) Grants	5
2.3 Test Methodology	5
2.4 Test Facility	5
3.0 <u>System Test Configuration</u>	7
3.1 Justification	7
3.2 EUT Exercising Software	8
3.3 Special Accessories	8
3.4 Measurement Uncertainty	8
3.5 Equipment Modification	8
3.6 Support Equipment List and Description	8
4.0 <u>Measurement Results</u>	10
4.1 Maximum Conducted Output Power at Antenna Terminals	10
4.2 Minimum 6dB RF Bandwidth	12
4.3 Maximum Power Density	20
4.4 Out of Band Conducted Emissions	28
4.5 Out of Band Radiated Emissions	41
4.6 Transmitter Radiated Emissions in Restricted Bands	42
4.7 Field Strength Calculation	43
4.8 Radiated Spurious Emission	44
4.9 Conducted Emission	58
4.10 Radiated Emission from Digital Section of ransceiver	61
4.11 Transmitter Duty Cycle Calculation and Measurements	62
5.0 <u>Equipment Photographs</u>	64
6.0 <u>Product Labelling</u>	66
7.0 <u>Technical Specifications</u>	68
8.0 <u>Instruction Manual</u>	70
9.0 <u>Confidentiality Request</u>	72
10.0 <u>Miscellaneous Information</u>	74
11.0 <u>Test Equipment List</u>	76

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

INTERTEK TESTING SERVICES

EXHIBIT 1

SUMMARY OF TEST RESULTS

INTERTEK TESTING SERVICES

1.0 Summary of Test

Mach Speed Technologies, LLC
MODEL: Trio Stealth G4 10.1 v2

FCC ID: 2ABYR-G410

TEST	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

INTERTEK TESTING SERVICES

EXHIBIT 2

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is a Tablet PC with internal WiFi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing and 2422-2452MHz for 802.11n-HT40, 7 channels with 5MHz channel spacing. The EUT can be powered by a 3.7 VDC rechargeable battery which can be charged by an USB Power Adapter with Output: DC 5 V, 2 A. For more detailed features description, please refer to the user's manual.

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM, CCK.

Antenna Type: Integral antenna.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

INTERTEK TESTING SERVICES

2.2 Related Submittal(s) Grants

This is an application for certification of:

DTS- Part 15 Digital Transmission Systems (WiFi transmitter portion)

Remaining portions are subject to the following procedures:

1. Receiver portion of WiFi: exempt from technical requirement of this Part.
2. For BT 2.1+EDR mode, BT 4.0 mode and PC Download mode please refer to the report with report No.: 140926001SZN-002, 140926001SZN-003, 14100378HKG-001.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009) and KDB 558074. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.4 Test Facility

The Anechoic chamber to collect the radiated data and shield room used to collect the conducted data are Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch. and located at 6F, Block D, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

INTERTEK TESTING SERVICES

EXHIBIT 3

SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables and accessories were manipulated to produce worst case emissions. The EUT was powered by 3.7 VDC fully charged rechargeable battery charged by an USB Power Adapter with AC 120V, 60Hz input during the test. Only the worst case data was reported.

The signal is maximized through rotation and placement on the ground. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

Power Parameters of IEEE 802.11b/g/n

Test software setting of IEEE 802.11b/g/n			
Channel No.	Output Power Level	Data rate	Modulation type
1,6,11	16.0	802.11b: 1-11Mbps	802.11b: CCK
	16.0	802.11g: 6-54Mbps	802.11g: BPSK, QPSK, 16QAM
1,6,11	16.0	802.11n-HT20: 6.5-65Mbps	802.11n: BPSK, QPSK, 16QAM,
3,6,9	15.0	802.11n-HT40: 13.5-135Mbps	802.11n: BPSK, QPSK, 16QAM, 64QAM

We test all data rate and only the worst – case data is shown in the report.

TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

3.3 Special Accessories

N/A

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

3.5 Equipment Modification

Any modifications installed previous to testing by Mach Speed Technologies, LLC will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

3.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
Router	TP-Link	S535D24
USB Cable	trio	shielded with one ferrite core, Length 102cm
Micro SD card	SanDisk	SDSDQ-2048-P36M
Adaptor	trio	Model: PGAE0500200U1UL Input: AC100-240V, 50/60Hz, 0.3 A Output: DC 5V, 2A
Headphone	NA	Unshielded, Length 150cm

INTERTEK TESTING SERVICES

EXHIBIT 4

MEASUREMENT RESULTS

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

- [x] The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter have a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (Antenna Gain = 1.6dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	19.80	95.50
Middle Channel: 2437	20.37	108.89
High Channel: 2462	20.80	120.23

IEEE 802.11g (Antenna Gain = 1.6dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	21.40	138.04
Middle Channel: 2437	23.15	206.54
High Channel: 2462	23.31	214.29

IEEE 802.11n-HT20 (Antenna Gain = 1.6dBi) (16QAM, 6.5Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	21.43	139.00
Middle Channel: 2437	22.97	198.15
High Channel: 2462	22.15	164.06

INTERTEK TESTING SERVICES

IEEE 802.11n-HT40 (Antenna Gain = 1.6dBi) (64QAM, 13.5Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2422	19.86	96.83
Middle Channel: 2437	22.00	158.49
High Channel: 2452	20.24	105.68

Cable loss: 0.5 dB External Attenuation: 0 dB

EUT max. output level (dBm)= 23.31dBm

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	10.0
2437	10.0
2462	9.6

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	15.5
2437	15.7
2462	15.3
IEEE 802.11n-HT20 (16QAM, 6.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	16.1
2437	15.9
2462	15.3



INTERTEK TESTING SERVICES

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2422	35.2
2437	35.5
2452	35.3

The test plots are attached as below.


INTERTEK TESTING SERVICES

802.11b




TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES



Date: 9.OCT.2014 10:35:29



802.11g



Date: 9.OCT.2014 10:42:38

TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410



INTERTEK TESTING SERVICES



TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410


INTERTEK TESTING SERVICES

802.11 n-HT20




TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES



Date: 9.OCT.2014 10:52:02


802.11 n-HT40




Date: 9.OCT.2014 10:54:46

TRF no.: FCC 15C_TX_b
 FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES



Date: 9.OCT.2014 10:57:23



Date: 9.OCT.2014 10:59:01

TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW. If the measured value exceed limit, reduce the RBW (no less than 3KHz) to retest.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/ 3 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	5.98
2437	6.78
2462	7.60

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	2.99
2437	4.57
2462	4.04

IEEE 802.11n-HT20 (16QAM, 6.5Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	2.94
2437	4.56
2462	3.87

INTERTEK TESTING SERVICES

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2422	-1.58
2437	0.75
2452	-0.30


Cable loss: 0.5 dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function


The test plots are attached as below.

INTERTEK TESTING SERVICES

802.11b




Date: 9.OCT.2014 14:00:55




Date: 9.OCT.2014 13:59:19

TRF no.: FCC 15C_TX_b
 FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES




802.11g




TRF no.: FCC 15C_TX_b
 FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES



Date: 9.OCT.2014 11:10:58




Date: 9.OCT.2014 11:10:03


TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

802.11 n-HT20




Date: 9.OCT.2014 14:09:14




Date: 9.OCT.2014 11:07:30

TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES




802.11 n-HT40




TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES



Date: 9.OCT.2014 11:05:05



Date: 9.OCT.2014 11:04:11

TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n-HT20 and 13.5Mbps for 802.11n-HT40.


The test plots showed all spurious emission up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

The test plots are attached as below.


INTERTEK TESTING SERVICES

802.11b

Channel 01 (2412MHz) Reference Level: 5.98dBm



Date: 9.OCT.2014 14:19:45




Date: 9.OCT.2014 14:15:50


TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Channel 06 (2437MHz) Reference Level: 6.78dBm



Date: 9.OCT.2014 14:20:33




Date: 9.OCT.2014 14:21:06


TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Channel 11 (2462MHz) Reference Level: 7.60dBm



Date: 9.OCT.2014 14:22:17




Date: 9.OCT.2014 14:21:48

TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410


INTERTEK TESTING SERVICES

802.11g

Channel 01 (2412MHz) Reference Level: 2.99dBm



Date: 9.OCT.2014 14:24:32




Date: 9.OCT.2014 14:25:53


TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Channel 06 (2437MHz) Reference Level: 4.57dBm



Date: 9.OCT.2014 14:36:55




Date: 9.OCT.2014 14:27:44


TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Channel 11 (2462MHz) Reference Level: 4.04 dBm



Date: 9.OCT.2014 14:38:10




Date: 9.OCT.2014 14:39:22

TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410


INTERTEK TESTING SERVICES

802.11 n-HT20

Channel 01 (2412MHz) Reference Level: 2.94dBm



Date: 9.OCT.2014 14:41:00




Date: 9.OCT.2014 14:40:22


TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Channel 06 (2437MHz) Reference Level: 4.56dBm



Date: 9.OCT.2014 14:41:44




Date: 9.OCT.2014 14:42:29


TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Channel 11 (2462MHz) Reference Level: 3.87 dBm



Date: 9.OCT.2014 14:47:16




Date: 9.OCT.2014 14:46:15


TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

802.11 n-HT40 Channel 03 (2422MHz) Reference Level: -1.58dBm



Date: 9.OCT.2014 14:49:30




Date: 9.OCT.2014 14:50:53


TRF no.: FCC 15C_TX_b
 FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Channel 06 (2437MHz) Reference Level: 0.75dBm



Date: 9.OCT.2014 14:52:56




Date: 9.OCT.2014 14:52:19


TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Channel 09 (2452MHz) Reference Level: -0.30dBm



Date: 9.OCT.2014 14:54:49



Date: 9.OCT.2014 14:55:50

TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- ☒ Not required, since all emissions are more than 20dB below fundamental
- ☐ See attached data sheet

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where FS = Field Strength in dB μ V/m
 RA = Receiver Amplitude (including preamplifier) in dB μ V
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB
 PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$\begin{aligned} RA &= 62.0 \text{ dB}\mu\text{V} \\ AF &= 7.4 \text{ dB} \\ CF &= 1.6 \text{ dB} \\ AG &= 29.0 \text{ dB} \\ PD &= 0 \text{ dB} \\ FS &= 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m} \end{aligned}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission (802.11b) at 4874.00MHz is passed by 6.4dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC

Date of Test: 9 October 2014

Model: Trio Stealth G4 10.1 v2

Worst Case Operating Mode: Transmit (802.11g Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	133.305	32.3	20.0	9.0	21.3	43.5	-22.2
Horizontal	157.555	31.7	20.0	10.6	22.3	43.5	-21.2
Horizontal	613.940	26.1	20.0	22.7	28.8	46.0	-17.2
Vertical	37.275	36.2	20.0	14.9	31.1	40.0	-8.9
Vertical	47.945	42.3	20.0	10.6	32.9	40.0	-7.1
Vertical	205.570	34.8	20.0	11.8	26.6	43.5	-16.9

- NOTES:
1. Quasi-Peak detector is used except for others stated.
 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. All emissions are below the QP limit.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

Mode: 802.11b (TX-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	66.6	36.7	28.5	58.4	74.0	-15.6
Horizontal	7236.000	59.2	36.7	34.2	56.7	74.0	-17.3
Horizontal	*2390.000	48.9	36.2	28.2	40.9	74.0	-33.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	52.7	36.7	28.5	44.5	54.0	-9.5
Horizontal	7236.000	43.9	36.7	34.2	41.4	54.0	-12.6
Horizontal	*2390.000	34.5	36.2	28.2	26.5	54.0	-27.5

- NOTES: 1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

Mode: 802.11b (TX-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	55.7	36.7	34.6	53.6	74.0	-20.4
Horizontal	*7311.000	57.0	36.7	37.1	57.4	74.0	-16.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	49.7	36.7	34.6	47.6	54.0	-6.4
Horizontal	*7311.000	42.2	36.7	37.1	42.6	54.0	-11.4

- NOTES: 1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

Mode: 802.11b (TX-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	61.7	36.7	28.5	53.5	74.0	-20.5
Horizontal	*7386.000	59.6	36.7	34.6	57.5	74.0	-16.5
Horizontal	9848.000	59.7	36.7	37.2	60.2	74.0	-13.8
Horizontal	*2483.500	52.2	36.2	28.0	44.0	74.0	-30.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	51.8	36.7	28.5	43.6	54.0	-10.4
Horizontal	*7386.000	43.3	36.7	34.6	41.2	54.0	-12.8
Horizontal	9848.000	44.4	36.7	37.2	44.9	54.0	-9.1
Horizontal	*2483.500	36.5	36.2	28.0	28.3	54.0	-25.7

- NOTES: 1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

Mode: 802.11g (TX-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	61.8	36.7	28.5	53.6	74.0	-20.4
Horizontal	7236.000	59.1	36.7	34.2	56.6	74.0	-17.4
Horizontal	*2390.000	48.2	36.2	28.2	40.2	74.0	-33.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	44.0	36.7	28.5	35.8	54.0	-18.2
Horizontal	7236.000	44.0	36.7	34.2	41.5	54.0	-12.5
Horizontal	*2390.000	33.8	36.2	28.2	25.8	54.0	-28.2

- NOTES:
1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

Mode: 802.11g (TX-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	54.4	36.7	34.6	52.3	74.0	-21.7
Horizontal	*7311.000	56.4	36.7	37.1	56.8	74.0	-17.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	37.4	36.7	34.6	35.3	54.0	-18.7
Horizontal	*7311.000	41.2	36.7	37.1	41.6	54.0	-12.4

- NOTES: 1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

Mode: 802.11g (TX-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	58.6	36.7	28.5	50.4	74.0	-23.6
Horizontal	*7386.000	58.5	36.7	34.6	56.4	74.0	-17.6
Horizontal	9848.000	60.5	36.7	37.2	61.0	74.0	-13.0
Horizontal	*2483.500	52.4	36.2	28.0	44.2	74.0	-29.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	43.4	36.7	28.5	35.2	54.0	-18.8
Horizontal	*7386.000	43.2	36.7	34.6	41.1	54.0	-12.9
Horizontal	9848.000	44.4	36.7	37.2	44.9	54.0	-9.1
Horizontal	*2483.500	36.6	36.2	28.0	28.4	54.0	-25.6

NOTES: 1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

Mode: 802.11 n-HT20 (TX-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	60.9	36.7	28.5	52.7	74.0	-21.3
Horizontal	7236.000	60.5	36.7	34.2	58.0	74.0	-16.0
Horizontal	*2388.000	48.1	36.2	28.2	40.1	74.0	-33.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	44.1	36.7	28.5	35.9	54.0	-18.1
Horizontal	7236.000	44.9	36.7	34.2	42.4	54.0	-11.6
Horizontal	*2388.000	33.5	36.2	28.2	25.5	54.0	-28.5

- NOTES: 1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

Mode: 802.11 n-HT20 (TX-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	54.8	36.7	34.2	52.3	74.0	-21.7
Horizontal	*7311.000	56.4	36.7	37.1	56.8	74.0	-17.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	37.7	36.7	34.2	35.2	54.0	-18.8
Horizontal	*7311.000	41.2	36.7	37.1	41.6	54.0	-12.4

- NOTES: 1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

Mode: 802.11 n-HT20 (TX-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	59.2	36.7	28.5	51.0	74.0	-23.0
Horizontal	*7386.000	60.1	36.7	34.6	58.0	74.0	-16.0
Horizontal	9848.000	60.1	36.7	37.2	60.6	74.0	-13.4
Horizontal	*2483.500	51.8	36.2	28.0	43.6	74.0	-30.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	43.3	36.7	28.5	35.1	54.0	-18.9
Horizontal	*7386.000	43.2	36.7	34.6	41.1	54.0	-12.9
Horizontal	9848.000	45.3	36.7	37.2	45.8	54.0	-8.2
Horizontal	*2483.500	36.4	36.2	28.0	28.2	54.0	-25.8

NOTES: 1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
 Model: Trio Stealth G4 10.1 v2
 Mode: 802.11 n-HT40 (TX-Channel 03)

Date of Test: 9 October 2014

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	59.3	36.7	28.5	51.1	74.0	-22.9
Horizontal	9688.000	62.9	36.7	34.2	60.4	74.0	-13.6
Horizontal	*2390.000	48.8	36.2	27.7	40.3	74.0	-33.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	43.8	36.7	28.5	35.6	54.0	-18.4
Horizontal	9688.000	47.6	36.7	34.2	45.1	54.0	-8.9
Horizontal	*2390.000	34.0	36.2	27.7	25.5	54.0	-28.5

- NOTES: 1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

Mode: 802.11 n-HT40 (TX-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	53.4	36.7	34.2	50.9	74.0	-23.1
Horizontal	*7311.000	56.6	36.7	37.1	57.0	74.0	-17.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	38.2	36.7	34.2	35.7	54.0	-18.3
Horizontal	*7311.000	41.4	36.7	37.1	41.8	54.0	-12.2

- NOTES: 1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

Mode: 802.11 n-HT40 (TX-Channel 09)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	54.4	36.7	34.6	52.3	74.0	-21.7
Horizontal	*7356.000	56.9	36.7	37.0	57.2	74.0	-16.8
Horizontal	*2483.500	52.9	36.7	28.0	44.2	74.0	-29.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	38.3	36.7	34.6	36.2	54.0	-17.8
Horizontal	*7356.000	42.2	36.7	37.0	42.5	54.0	-11.5
Horizontal	*2483.500	36.9	36.7	28.0	28.2	54.0	-25.8

NOTES: 1. Peak detector Data unless otherwise stated. Above 1000 MHz, RBW=1MHz, VBW=3MHz is used for Peak measurement, RBW=1MHz, VBW=10Hz is used for Average measurement.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

4.9 Conducted Emission

Worst Case Conducted Configuration
At

0.486 MHz

Judgement: Passed by 1.9 dB margin


For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
 Model: Trio Stealth G4 10.1 v2
 Worst Case Operating Mode: WiFi link
 Line: Live

Date of Test: 9 October 2014

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μV)	Line	Corr. (dB)	Margin (dB)	Limit (dB μV)
0.182	55.3	L1	9.8	9.1	64.4
0.366	51.5	L1	9.8	7.1	58.6
0.486	54.3	L1	9.8	1.9	56.2
0.550	48.9	L1	9.8	7.1	56.0
0.726	48.8	L1	10.0	7.2	56.0
1.674	44.8	L1	9.9	11.2	56.0

Result Table AV

Frequency (MHz)	CAverage (dB μV)	Line	Corr. (dB)	Margin (dB)	Limit (dB μV)
0.182	43.7	L1	9.8	10.7	54.4
0.366	40.7	L1	9.8	7.9	48.6
0.486	42.7	L1	9.8	3.5	46.2
0.550	37.2	L1	9.8	8.8	46.0
0.726	36.2	L1	10.0	9.8	46.0
1.674	31.4	L1	9.9	14.6	46.0

TRF no.: FCC 15C_TX_b
 FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC


Date of Test: 9 October 2014

Model: Trio Stealth G4 10.1 v2

Worst Case Operating Mode: WiFi link

Line: Neutral

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μV)	Line	Corr. (dB)	Margin (dB)	Limit (dB μV)
0.178	53.3	N	10.0	11.3	64.6
0.366	49.4	N	10.1	9.2	58.6
0.442	50.7	N	10.1	6.3	57.0
0.486	47.4	N	10.1	8.8	56.2
0.550	43.5	N	10.2	12.5	56.0
0.806	39.4	N	10.2	16.6	56.0

Result Table AV

Frequency (MHz)	CAverage (dB μV)	Line	Corr. (dB)	Margin (dB)	Limit (dB μV)
0.178	34.2	N	10.0	20.4	54.6
0.366	32.6	N	10.1	16.0	48.6
0.442	33.6	N	10.1	13.4	47.0
0.486	31.5	N	10.1	14.7	46.2
0.550	27.6	N	10.2	18.4	46.0
0.806	24.2	N	10.2	21.8	46.0

TRF no.: FCC 15C_TX_b
FCC ID: 2ABYR-G410

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

☐ Not required - No digital part

☐ Test results are attached

☒ Included in the separated report.

INTERTEK TESTING SERVICES

Applicant: Mach Speed Technologies, LLC
Model: Trio Stealth G4 10.1 v2

Date of Test: 9 October 2014

4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEF function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

INTERTEK TESTING SERVICES

EXHIBIT 5

EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.doc & internal photos.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 6

PRODUCT LABELLING

INTERTEK TESTING SERVICES

6.0 **Product Labeling**

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 7

TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

INTERTEK TESTING SERVICES

EXHIBIT 8

INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

EXHIBIT 9

CONFIDENTIALITY REQUEST

INTERTEK TESTING SERVICES

9.0 **Confidentiality Request**

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 10

MISCELLANEOUS INFORMATION

INTERTEK TESTING SERVICES

10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

INTERTEK TESTING SERVICES

EXHIBIT 11

TEST EQUIPMENT LIST

INTERTEK TESTING SERVICES

11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-03	BiConiLog Antenna	ETS	3142C	00066460	28-Jun-14	28-Jun-15
SZ185-01	EMI Receiver	R&S	ESCI	100547	10-Mar-14	10-Mar-15
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	03-Sep-14	03-Sep-15
SZ061-08	Horn Antenna	ETS	3115	00092346	26-Oct-13	26-Oct-14
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	29-Apr-14	29-Apr-15
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	10-Mar-14	10-Mar-15
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	10-Mar-14	10-Mar-15
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	19-Apr-14	19-Apr-15
SZ062-02	RF Cable	RADIAL	RG 213U	--	08-Jul-14	08-Jan-15
SZ062-05	RF Cable	RADIAL	0.04-26.5GHz	--	19-Apr-14	19-Oct-14
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	--	19-Apr-14	19-Oct-14
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	--	21-May-14	21-May-15
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	09-Nov-13	09-Nov-14
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	09-Nov-13	09-Nov-14
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	09-Nov-13	09-Nov-14
SZ188-03	Shielding Room	ETS	RFD-100	4100	22-Aug-14	22-Aug-15