FCC PART 15C
TEST REPORT

No. I21Z62312-IOT01

for

OnePlus Technology (Shenzhen) Co., Ltd.

Smart Phone

Model Name: GN2200

FCC ID: 2ABZ2-AA455

with

Hardware Version: 11

Software Version: GN2200_11_A.02

Issued Date: 2022-1-10

Note:

The test results in this test report relate only to the devices specified in this report.This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email:cttl_terminals@caict.ac.cn, website: www.chinattl.com

©Copyright. All rights reserved by CTTL.

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I21Z62312-IOT01	Rev.0	1st edition	2022-1-10

©Copyright. All rights reserved by CTTL.

CONTENTS

1. Test Laboratory 5
   1.1. Introduction &Accreditation 5
   1.2. Testing Location 5
   1.3. Testing Environment 6
   1.4. Project data 6
   1.5. Signature 6
2. Client Information 7
   2.1. Applicant Information 7
   2.2. Manufacturer Information 7
3. Equipment Under Test (EUT) and Ancillary Equipment (AE) 8
   3.1. About EUT 8
   3.2. Internal Identification of EUT 8
   3.3. Internal Identification of AE 8
   3.4. Normal Accessory setting 8
   3.5. General Description 8
4. Reference Documents 9
   4.1. Documents supplied by applicant 9
   4.2. Reference Documents for testing 9
5. Test Results 10
   5.1. Summary of Test Results 10
   5.2. Statements 10
6. Test Facilities Utilized 11
7. Measurement Uncertainty 12
   7.1. Peak Output Power - Conducted 12
   7.2. Frequency Band Edges - Conducted 12
   7.3. Frequency Band Edges - Radiated 12
   7.4. Transmitter Spurious Emission - Conducted 12
   7.5. Transmitter Spurious Emission - Radiated 12
   7.6. Time of Occupancy (Dwell Time) 12
   7.7. 20dB Bandwidth 13
   7.8. Carrier Frequency Separation 13
   7.9. AC Powerline Conducted Emission 13

ANNEX A: EUT parameters 14

ANNEX B: Detailed Test Results 15
   B.1. Measurement Method 15
   B.2. Peak Output Power 16
   B.3. Frequency Band Edges – Conducted 18
   B.4. Frequency Band Edges –Radiated 25
   B.5. Transmitter Spurious Emission - Conducted 30
   B.6. Transmitter Spurious Emission - Radiated 55
   B.7. Time of Occupancy (Dwell Time) 65
   B.8. 20dB Bandwidth 76

©Copyright. All rights reserved by CTTL.

B.9. Carrier Frequency Separation 82
B.10. Number of Hopping Channels 85
B.11. AC Powerline Conducted Emission 89
ANNEX C: Accreditation Certificate 93

©Copyright. All rights reserved by CTTL.

1. Test Laboratory

1.1. Introduction &Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (ISED#: 24849). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Conducted testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China100191

Radiated testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, 100191, P. R. China

©Copyright. All rights reserved by CTTL.

1.3. Testing Environment

Normal Temperature: 15-35℃

Relative Humidity: 20-75%

1.4. Project data

Testing Start Date: 2021-11-17

Testing End Date: 2022-1-10

1.5. Signature

Wu Le

(Prepared this test report)

Sun Zhenyu

(Reviewed this test report)

Zhu Liang

(Approved this test report)

©Copyright. All rights reserved by CTTL.

2. Client Information

2.1. Applicant Information

Company Name:	OnePlus Technology (Shenzhen) Co., Ltd.
Address /Post:	18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen
City:	Shenzhen
Postal Code:	/
Country:	China
Telephone:	86 755 61898696-7023
Fax:	/

2.2. Manufacturer Information

Company Name:	OnePlus Technology (Shenzhen) Co., Ltd.
Address /Post:	18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen
City:	Shenzhen
Postal Code:	/
Country:	China
Telephone:	86 755 61898696-7023
Fax:	/

©Copyright. All rights reserved by CTTL.

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Smart Phone
Model Name	GN2200
FCC ID	2ABZ2-AA455
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation	GFSK/π/4 DQPSK/8DPSK
Number of Channels	79
Power Supply	3.87V DC by Battery
Antenna gain	-4.0dBi

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
EUT1	866966050025092	11	GN2200_11_A.02	2021-11-16
EUT2	866966050026140	11	GN2200_11_A.02	2021-11-22

*EUT ID: is used to identify the test sample in the lab internally. The HW and SW versions were provided by the applicant.

3.3. Internal Identification of AE

AE ID*	Description		
AE1	Battery	/	Inbuilt

*AE ID: is used to identify the test sample in the lab internally.

3.4. Normal Accessory setting

Fully charged battery should be used during the test.

3.5. General Description

The Equipment Under Test (EUT) is a model of Smart Phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfill the test. Samples undergoing test were selected by the Client.

©Copyright. All rights reserved by CTTL.

4. Reference Documents

4.1. Documents supplied by applicant

EUT parameters, referring to Annex A for detailed information, is supplied by the client or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz.	2019
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	June,2013

©Copyright. All rights reserved by CTTL.

5. Test Results

5.1. Summary of Test Results

Abbreviations used in this clause:

P Pass, The EUT complies with the essential requirements in the standard.

F Fail, The EUT does not comply with the essential requirements in the standard

NA Not Applicable, The test was not applicable

NP Not Performed, The test was not performed by CTTL

SUMMARY OF MEASUREMENT RESULTS	Sub-clause	Verdict
Peak Output Power	15.247 (b)(1)	**P**
Frequency Band Edges- Conducted	15.247 (d)	**P**
Frequency Band Edges- Radiated	15.247, 15.205, 15.209	**P**
Transmitter Spurious Emission - Conducted	15.247 (d)	**P**
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	**P**
Time of Occupancy (Dwell Time)	15.247 (a) (1)(iii)	**P**
20dB Bandwidth	15.247 (a)(1)	**NA**
Carrier Frequency Separation	15.247 (a)(1)	**P**
Number of hopping channels	15.247 (a)(iii)	**P**
AC Powerline Conducted Emission	15.107, 15.207	**P**

Please refer to **ANNEX A** for detail.

The measurement is made according to ANSI C63.10.

5.2. Statements

CTTL has evaluated the test cases requested by the applicant /manufacturer as listed in section 5.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

©Copyright. All rights reserved by CTTL.

6. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ26	100024	R&S	1 year	2022-03-25
2	Bluetooth Tester	CBT	100315	R&S	1 year	2023-01-22
3	LISN	ENV216	101200	R&S	1 year	2022-05-30
4	Test Receiver	ESCI	100344	R&S	1 year	2022-02-23
5	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	FSW67	103290	R&S	1 year	2022-01-20
2	BiLog Antenna	VULB9163	9163-1223	Schwarzbeck	1 year	2022-03-22
3	EMI Antenna	3115	0016725	ETS-Lindgren	1 year	2022-07-01

©Copyright. All rights reserved by CTTL.

7. Measurement Uncertainty

7.1. Peak Output Power - Conducted

Measurement Uncertainty:

Measurement Uncertainty (k=2)	0.66dB

7.2. Frequency Band Edges - Conducted

Measurement Uncertainty:

Measurement Uncertainty (k=2)	0.66dB

7.3. Frequency Band Edges - Radiated

Measurement Uncertainty:

Measurement Uncertainty (k=2)	/

7.4. Transmitter Spurious Emission - Conducted

Measurement Uncertainty:

Frequency Range	Uncertainty (k=2)
30 MHz ~ 8 GHz	1.22dB
8 GHz ~ 12.75 GHz	1.51dB
12.7GHz ~ 26 GHz	1.51dB

7.5. Transmitter Spurious Emission - Radiated

Measurement Uncertainty:

Frequency Range	Uncertainty(dBm) (k=2)
9kHz-30MHz	/
30MHz ≤ f ≤ 1GHz	5.40
1GHz ≤ f ≤18GHz	4.32
18GHz ≤ f ≤40GHz	5.26

7.6. Time of Occupancy (Dwell Time)

Measurement Uncertainty:

Measurement Uncertainty (k=2)	0.88ms

©Copyright. All rights reserved by CTTL.

7.7. 20dB Bandwidth

Measurement Uncertainty:

Measurement Uncertainty (k=2)	61.936Hz

7.8. Carrier Frequency Separation

Measurement Uncertainty:

Measurement Uncertainty (k=2)	61.936Hz

7.9. AC Powerline Conducted Emission

Measurement Uncertainty:

Measurement Uncertainty (k=2)	3.08dB

©Copyright. All rights reserved by CTTL.

ANNEX A: EUT parameters

Disclaimer: The antenna gain provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

©Copyright. All rights reserved by CTTL.

ANNEX B: Detailed Test Results

B.1. Measurement Method

B.1.1. Conducted Measurements

The measurement is made according to ANSI C63.10.

1). Connect the EUT to the test system correctly.

2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).

3). Set the EUT to the required channel.

4). Set the EUT hopping mode (hopping or hopping off).

5). Set the spectrum analyzer to start measurement.

6). Record the values. Vector Signal Analyzer



B.1.2. Radiated Emission Measurements

The measurement is made according to ANSI C63.10

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 3MHz;



©Copyright. All rights reserved by CTTL.

B.2. Peak Output Power

B.2.1. Peak Output Power – Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.5

a) Use the following spectrum analyzer settings:

- Span: 6MHz
- RBW: 3MHz
- VBW: 3MHz
- Sweep time: 2.5ms
- Detector function: peak
- Trace: max hold

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power.

Measurement Limit:

Standard	Limits	
FCC Part 15.247 (b)(1)	Bandwidth≤1MHz	30dBm (1W)
	Bandwidth＞1MHz	21dBm (125mW)

Measurement Results:

For GFSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	12.57	13.08	13.27	P

For π/4 DQPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	11.92	12.30	12.54	P

For 8DPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	12.11	12.59	12.70	P

Conclusion: PASS

©Copyright. All rights reserved by CTTL.

B.2.2. E.I.R.P.

The radiated E.I.R.P. is listed below:

Antenna gain = -4.0dBi

For GFSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
E.I.R.P (dBm)	8.57	9.08	9.27	P

Forπ/4 DQPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
E.I.R.P (dBm)	7.92	8.30	8.54	P

For 8DPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
E.I.R.P (dBm)	8.11	8.59	8.70	P

Note: E.I.R.P. are calculated with the antenna gain.

Conclusion: PASS

©Copyright. All rights reserved by CTTL.

B.3. Frequency Band Edges – Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.6

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).

– Span: 10 MHz
– Resolution Bandwidth: 100 kHz
– Video Bandwidth: 300 kHz
– Sweep Time:Auto
– Detector: Peak
– Trace: max hold

Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.

Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	< -20

Measurement Result:

For GFSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.1	-59.14	P
	Hopping ON	Fig.2	-63.73	P
78	Hopping OFF	Fig.3	-69.37	P
	Hopping ON	Fig.4	-64.77	P

For π/4 DQPSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.5	-56.86	P
	Hopping ON	Fig.6	-62.53	P
78	Hopping OFF	Fig.7	-67.04	P
	Hopping ON	Fig.8	-62.91	P

For 8DPSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.9	-57.40	P
	Hopping ON	Fig.10	-62.04	P
78	Hopping OFF	Fig.11	-63.73	P

©Copyright. All rights reserved by CTTL.

	Hopping ON	Fig.12	-62.47	P

Conclusion: PASS

Test graphs as below



Fig.1. Frequency Band Edges: GFSK, Channel 0, Hopping Off



Fig.2. Frequency Band Edges: GFSK, Channel 0, Hopping On

©Copyright. All rights reserved by CTTL.



Fig.3. Frequency Band Edges: GFSK, Channel 78, Hopping Off



Fig.4. Frequency Band Edges: GFSK, Channel 78, Hopping On

©Copyright. All rights reserved by CTTL.



Fig.5. Frequency Band Edges: π/4 DQPSK, Channel 0, Hopping Off



Fig.6. Frequency Band Edges: π/4 DQPSK, Channel 0, Hopping On

©Copyright. All rights reserved by CTTL.



Fig.7. Frequency Band Edges: π/4 DQPSK, Channel 78, Hopping Off



Fig.8. Frequency Band Edges: π/4 DQPSK, Channel 78, Hopping On

©Copyright. All rights reserved by CTTL.



Fig.9. Frequency Band Edges: 8DPSK, Channel 0, Hopping Off



Fig.10. Frequency Band Edges: 8DPSK, Channel 0, Hopping On

©Copyright. All rights reserved by CTTL.



Fig.11. Frequency Band Edges: 8DPSK, Channel 78, Hopping Off



Fig.12. Frequency Band Edges: 8DPSK, Channel 78, Hopping On

©Copyright. All rights reserved by CTTL.

B.4. Frequency Band Edges –Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 &6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency (MHz)	Field strength(μV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Set up:

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m and the table height shall be 1.5 m.

The EUT and transmitting antenna shall be centered on the turntable.

Test Condition

The EUT shall be tested 1 near top, 1 near middle, and 1 near bottom. Set the unlicensed wireless device to operate in continuous transmit mode. For unlicensed wireless devices unable to be configured for 100% duty cycle even in test mode, configure the system for the maximum duty cycle supported.

When required for unlicensed wireless devices, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Exploratory radiated emissions measurements

Exploratory radiated measurements shall be performed at the measurement distance or at a closer distance than that specified for compliance to determine the emission characteristics of the EUT and, if applicable, the EUT configuration that produces the maximum level of emissions. The frequencies of maximum emission may be determined by manually positioning the antenna close to the EUT, and then moving the antenna over all sides of the EUT while observing a spectral

©Copyright. All rights reserved by CTTL.

display. It is advantageous to have prior knowledge of the frequencies of emissions, although this may be determined from such a near-field scan. The near-field scan shall only be used to determine the frequency but not the amplitude of the emissions. Where exploratory measurements are not adequate to determine the worst-case operating modes and are used only to identify the frequencies of the highest emissions, additional preliminary tests can be required.
For emissions from the EUT, the maximum level shall be determined by rotating the EUT and its antenna through 0° to 360°. For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored.
Broadband antennas and a spectrum analyzer or a radio-noise meter with a panoramic display are often useful in this type of test. If either antenna height or EUT azimuth are not fully measured during exploratory testing, then complete testing can be required at the OATS or semi-anechoic chamber when the final full spectrum testing is performed.

Final radiated emissions measurements
The final measurements are using the orientation and equipment arrangement of the EUT based on the measurement results found during the preliminary (exploratory) measurements, the EUT arrangement, appropriate modulation, and modes of operation that produce the emissions that have the highest amplitude relative to the limit shall be selected for the final measurement.
For emissions from the EUT, the maximum level shall be determined by rotating the EUT and its antenna through 0° to 360°. Final measurements for the EUT require a measurement antenna height scan of 1 m to 4 m and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored.
For each mode selected, record the frequency and amplitude of the highest fundamental emission (if applicable), as well as the frequency and amplitude of the six highest spurious emissions relative to the limit. Emissions more than 20 dB below the limit do not need to be reported.
This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

The receiver references:

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100kHz/300kHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

©Copyright. All rights reserved by CTTL.

EUT ID: EUT1

Measurement Results:

Mode	Channel	Frequency Range	Test Results	Conclusion
GFSK	0	2.31GHz ~2.43GHz	Fig.13	P
	78	2.45GHz ~2.5GHz	Fig.14	P

Mode	Channel	Frequency Range	Test Results	Conclusion
π/4 DQPSK	0	2.31GHz ~2.43GHz	Fig.15	P
	78	2.45GHz ~2.5GHz	Fig.16	P

Mode	Channel	Frequency Range	Test Results	Conclusion
8DPSK	0	2.31GHz ~2.43GHz	Fig.17	P
	78	2.45GHz ~2.5GHz	Fig.18	P

Conclusion: PASS

Test graphs as below



Fig.13. Frequency Band Edges: GFSK, Channel 0, 2.31 GHz – 2.45GHz



Fig.14. Frequency Band Edges: GFSK, Channel 78, ch11, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL.



Fig.15. Frequency Band Edges: π/4 DQPSK, Channel 0, 2.31 GHz - 2.45GHz



Fig.16. Frequency Band Edges: π/4 DQPSK, Channel 78, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL.



Fig.17. Frequency Band Edges: 8DPSK, Channel 0, 2.31 GHz - 2.45GHz



Fig.18. Frequency Band Edges: 8DPSK, Channel 78, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL.

B.5. Transmitter Spurious Emission - Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.8

Measurement Procedure – Reference Level

1. Set the RBW = 100 kHz.

2. Set the VBW = 300 kHz.

3. Set the span to 5-30 % greater than the EBW.

4. Detector = peak.

5. Sweep time = auto couple.

6. Trace mode = max hold.

7. Allow trace to fully stabilize.

8. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

Measurement Procedure - Unwanted Emissions

1. Set RBW = 100 kHz.

2. Set VBW = 300 kHz.

3. Set span to encompass the spectrum to be examined.

4. Detector = peak.

5. Trace Mode = max hold.

6. Sweep = auto couple.

7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

Measurement Results:

For GFSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0	Center Frequency	Fig.19	P

©Copyright. All rights reserved by CTTL.

2402 MHz	30 MHz ~ 1 GHz	Fig.20	P
	1 GHz ~ 3 GHz	Fig.21	P
	3 GHz ~ 10 GHz	Fig.22	P
	10 GHz ~ 26 GHz	Fig.23	P
Ch 39 2441 MHz	Center Frequency	Fig.24	P
	30 MHz ~ 1 GHz	Fig.25	P
	1 GHz ~ 3 GHz	Fig.26	P
	3 GHz ~ 10 GHz	Fig.27	P
	10 GHz ~ 26 GHz	Fig.28	P
Ch 78 2480 MHz	Center Frequency	Fig.29	P
	30 MHz ~ 1 GHz	Fig.30	P
	1 GHz ~ 3 GHz	Fig.31	P
	3 GHz ~ 10 GHz	Fig.32	P
	10 GHz ~ 26 GHz	Fig.33	P

For π/4 DQPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.34	P
	30 MHz ~ 1 GHz	Fig.35	P
	1 GHz ~ 3 GHz	Fig.36	P
	3 GHz ~ 10 GHz	Fig.37	P
	10 GHz ~ 26 GHz	Fig.38	P
Ch 39 2441 MHz	Center Frequency	Fig.39	P
	30 MHz ~ 1 GHz	Fig.40	P
	1 GHz ~ 3 GHz	Fig.41	P
	3 GHz ~ 10 GHz	Fig.42	P
	10 GHz ~ 26 GHz	Fig.43	P
Ch 78 2480 MHz	Center Frequency	Fig.44	P
	30 MHz ~ 1 GHz	Fig.45	P
	1 GHz ~ 3 GHz	Fig.46	P
	3 GHz ~ 10 GHz	Fig.47	P
	10 GHz ~ 26 GHz	Fig.48	P

For 8DPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.49	P
	30 MHz ~ 1 GHz	Fig.50	P
	1 GHz ~ 3 GHz	Fig.51	P
	3 GHz ~ 10 GHz	Fig.52	P
	10 GHz ~ 26 GHz	Fig.53	P

©Copyright. All rights reserved by CTTL.

Ch 39 2441 MHz	Center Frequency	Fig.54	P
	30 MHz ~ 1 GHz	Fig.55	P
	1 GHz ~ 3 GHz	Fig.56	P
	3 GHz ~ 10 GHz	Fig.57	P
	10 GHz ~ 26 GHz	Fig.58	P
Ch 78 2480 MHz	Center Frequency	Fig.59	P
	30 MHz ~ 1 GHz	Fig.60	P
	1 GHz ~ 3 GHz	Fig.61	P
	3 GHz ~ 10 GHz	Fig.62	P
	10 GHz ~ 26 GHz	Fig.63	P

Conclusion: PASS

Test graphs as below



Fig.19. Conducted spurious emission: GFSK, Channel 0,2402MHz

©Copyright. All rights reserved by CTTL.



Fig.20. Conducted spurious emission: GFSK, Channel 0, 30MHz - 1GHz



Fig.21. Conducted spurious emission: GFSK, Channel 0, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.22. Conducted spurious emission: GFSK, Channel 0, 3GHz - 10GHz



Fig.23. Conducted spurious emission: GFSK, Channel 0,10GHz - 26GHz

©Copyright. All rights reserved by CTTL.



Fig.24. Conducted spurious emission: GFSK, Channel 39, 2441MHz



Fig.25. Conducted spurious emission: GFSK, Channel 39, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL.



Fig.26. Conducted spurious emission: GFSK, Channel 39, 1GHz – 3GHz



Fig.27. Conducted spurious emission: GFSK, Channel 39, 3GHz – 10GHz

©Copyright. All rights reserved by CTTL.



Fig.28. Conducted spurious emission: GFSK, Channel 39, 10GHz – 26GHz



Fig.29. Conducted spurious emission: GFSK, Channel 78, 2480MHz

©Copyright. All rights reserved by CTTL.



Fig.30. Conducted spurious emission: GFSK, Channel 78, 30MHz - 1GHz



Fig.31. Conducted spurious emission: GFSK, Channel 78, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.32. Conducted spurious emission: GFSK, Channel 78, 3GHz - 10GHz



Fig.33. Conducted spurious emission: GFSK, Channel 78, 10GHz - 26GHz

©Copyright. All rights reserved by CTTL.



Fig.34. Conducted spurious emission: π/4 DQPSK, Channel 0,2402MHz



Fig.35. Conducted spurious emission: π/4 DQPSK, Channel 0, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL.



Fig.36. Conducted spurious emission: π/4 DQPSK, Channel 0, 1GHz - 3GHz



Fig.37. Conducted spurious emission: π/4 DQPSK, Channel 0, 3GHz - 10GHz

©Copyright. All rights reserved by CTTL.



Fig.38. Conducted spurious emission: π/4 DQPSK, Channel 0,10GHz - 26GHz



Fig.39. Conducted spurious emission: π/4 DQPSK, Channel 39, 2441MHz

©Copyright. All rights reserved by CTTL.



Fig.40. Conducted spurious emission: π/4 DQPSK, Channel 39, 30MHz - 1GHz



Fig.41. Conducted spurious emission: π/4 DQPSK, Channel 39, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.42. Conducted spurious emission: π/4 DQPSK, Channel 39, 3GHz - 10GHz



Fig.43. Conducted spurious emission: π/4 DQPSK, Channel 39, 10GHz – 26GHz

©Copyright. All rights reserved by CTTL.



Fig.44. Conducted spurious emission: π/4 DQPSK, Channel 78, 2480MHz



Fig.45. Conducted spurious emission: π/4 DQPSK, Channel 78, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL.



Fig.46. Conducted spurious emission: π/4 DQPSK, Channel 78, 1GHz - 3GHz



Fig.47. Conducted spurious emission: π/4 DQPSK, Channel 78, 3GHz - 10GHz

©Copyright. All rights reserved by CTTL.



Fig.48. Conducted spurious emission: π/4 DQPSK, Channel 78, 10GHz - 26GHz



Fig.49. Conducted spurious emission: 8DPSK, Channel 0,2402MHz

©Copyright. All rights reserved by CTTL.



Fig.50. Conducted spurious emission: 8DPSK, Channel 0, 30MHz - 1GHz



Fig.51. Conducted spurious emission: 8DPSK, Channel 0, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.52. Conducted spurious emission: 8DPSK, Channel 0, 3GHz - 10GHz



Fig.53. Conducted spurious emission: 8DPSK, Channel 0,10GHz - 26GHz

©Copyright. All rights reserved by CTTL.



Fig.54. Conducted spurious emission: 8DPSK, Channel 39, 2441MHz



Fig.55. Conducted spurious emission: 8DPSK, Channel 39, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL.



Fig.56. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz



Fig.57. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz

©Copyright. All rights reserved by CTTL.



Fig.58. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz



Fig.59. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz

©Copyright. All rights reserved by CTTL.



Fig.60. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz



Fig.61. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.62. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz



Fig.63. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz

©Copyright. All rights reserved by CTTL.

B.6. Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 &6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency (MHz)	Field strength(μV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Set up:

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m

The EUT and transmitting antenna shall be centered on the turntable.

©Copyright. All rights reserved by CTTL.





Test Condition

The EUT shall be tested 1 near top, 1 near middle, and 1 near bottom. Set the unlicensed wireless device to operate in continuous transmit mode. For unlicensed wireless devices unable to be configured for 100% duty cycle even in test mode, configure the system for the maximum duty cycle supported.

When required for unlicensed wireless devices, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the

©Copyright. All rights reserved by CTTL.

nominal rated supply voltage.

Exploratory radiated emissions measurements

Exploratory radiated measurements shall be performed at the measurement distance or at a closer distance than that specified for compliance to determine the emission characteristics of the EUT and, if applicable, the EUT configuration that produces the maximum level of emissions. The frequencies of maximum emission may be determined by manually positioning the antenna close to the EUT, and then moving the antenna over all sides of the EUT while observing a spectral display. It is advantageous to have prior knowledge of the frequencies of emissions, although this may be determined from such a near-field scan. The near-field scan shall only be used to determine the frequency but not the amplitude of the emissions. Where exploratory measurements are not adequate to determine the worst-case operating modes and are used only to identify the frequencies of the highest emissions, additional preliminary tests can be required.

For emissions from the EUT, the maximum level shall be determined by rotating the EUT and its antenna through 0° to 360°. For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored.

Broadband antennas and a spectrum analyzer or a radio-noise meter with a panoramic display are often useful in this type of test. If either antenna height or EUT azimuth are not fully measured during exploratory testing, then complete testing can be required at the OATS or semi-anechoic chamber when the final full spectrum testing is performed.

Final radiated emissions measurements

The final measurements are using the orientation and equipment arrangement of the EUT based on the measurement results found during the preliminary (exploratory) measurements, the EUT arrangement, appropriate modulation, and modes of operation that produce the emissions that have the highest amplitude relative to the limit shall be selected for the final measurement.

For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.

For each mode selected, record the frequency and amplitude of the highest fundamental emission (if applicable), as well as the frequency and amplitude of the six highest spurious emissions relative to the limit. Emissions more than 20 dB below the limit do not need to be reported.

This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

The receiver references:

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100kHz/300kHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

©Copyright. All rights reserved by CTTL.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= P_{Mea} + Cable Loss + Antenna Factor

Where:

P_{Mea}	field strength recorded from the instrument

©Copyright. All rights reserved by CTTL.

Peak Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17908.500	54.50	-25.50	46.70	33.30	74.00	19.50	H
13764.000	51.54	-29.10	40.90	39.74	74.00	22.46	V
12823.000	49.60	-30.70	39.10	41.10	74.00	24.40	H
9102.000	46.89	-33.80	38.10	42.49	74.00	27.11	V
7859.500	45.62	-34.90	37.10	43.42	74.00	28.38	H
2367.500	56.79	-20.10	28.00	48.79	74.00	17.21	V

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17972.000	54.33	-25.50	46.70	33.13	74.00	19.67	V
13724.000	50.99	-29.10	40.90	39.19	74.00	23.01	H
12884.500	49.39	-30.70	39.10	40.89	74.00	24.61	V
9431.000	47.14	-32.90	37.90	42.14	74.00	26.86	H
7609.000	45.94	-35.00	36.90	44.14	74.00	28.06	H
4989.000	41.22	-36.60	33.40	44.42	74.00	32.78	H

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17924.500	54.85	-25.50	46.70	33.65	74.00	19.15	V
14218.500	51.07	-29.00	42.00	38.07	74.00	22.93	H
12896.000	49.37	-30.70	39.10	40.87	74.00	24.63	H
8995.500	47.66	-33.30	38.20	42.76	74.00	26.34	V
7955.000	45.56	-34.80	37.10	43.26	74.00	28.44	V
2490.400	56.74	-20.00	28.30	48.44	74.00	17.26	H

©Copyright. All rights reserved by CTTL.

π/4 DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17995.500	53.81	-25.50	46.70	32.61	74.00	20.19	V
14205.000	50.48	-29.00	42.00	37.48	74.00	23.52	H
11811.500	49.02	-31.80	39.00	41.82	74.00	24.98	V
9097.000	47.62	-33.80	38.10	43.22	74.00	26.38	V
7877.500	45.22	-34.90	37.10	43.02	74.00	28.78	V
2344.100	56.64	-20.10	28.00	48.74	74.00	17.36	H

π/4 DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17956.500	53.73	-25.50	46.70	32.53	74.00	20.27	V
14200.000	50.60	-29.00	42.00	37.60	74.00	23.40	V
12335.500	48.96	-31.10	38.90	41.16	74.00	25.04	H
9211.000	47.20	-33.70	38.00	42.90	74.00	26.80	H
7781.000	45.37	-35.10	37.00	43.47	74.00	28.63	H
4602.500	42.03	-37.30	32.70	46.73	74.00	31.97	H

π/4 DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17797.000	54.05	-25.50	46.70	32.85	74.00	19.95	V
14196.000	51.00	-29.00	42.00	38.00	74.00	23.00	H
12999.000	49.59	-30.50	39.20	40.89	74.00	24.41	V
8872.500	47.18	-33.50	38.10	42.58	74.00	26.82	H
7391.000	45.59	-35.20	36.70	43.99	74.00	28.41	H
2499.700	56.79	-20.00	28.40	48.39	74.00	17.21	H

©Copyright. All rights reserved by CTTL.

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17987.000	53.89	-25.50	46.70	32.69	74.00	20.11	H
13725.000	50.73	-29.10	40.90	38.93	74.00	23.27	V
12355.500	49.18	-31.10	38.90	41.38	74.00	24.82	H
8987.500	47.77	-33.30	38.20	42.87	74.00	26.23	V
7815.000	46.02	-35.10	37.00	44.12	74.00	27.98	H
2383.300	56.02	-20.00	28.10	48.02	74.00	17.98	H

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17955.000	53.71	-25.50	46.70	32.51	74.00	20.29	V
14193.500	50.95	-29.00	42.00	37.95	74.00	23.05	V
12829.500	49.84	-30.70	39.10	41.34	74.00	24.16	H
9211.500	47.12	-33.70	38.00	42.82	74.00	26.88	H
7129.500	46.02	-35.40	36.30	45.12	74.00	27.98	V
4757.500	40.85	-37.30	33.00	45.15	74.00	33.15	V

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17603.000	54.33	-25.70	46.00	34.13	74.00	19.67	V
13642.000	51.11	-29.50	40.40	40.21	74.00	22.89	H
12950.000	49.56	-30.50	39.20	40.86	74.00	24.44	V
9784.000	47.64	-33.50	38.00	43.14	74.00	26.36	H
7538.500	45.81	-35.00	36.90	44.01	74.00	28.19	V
2489.900	56.37	-20.00	28.30	48.07	74.00	17.63	H

©Copyright. All rights reserved by CTTL.

Average Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17982.500	42.79	-25.50	46.70	21.59	54.00	11.21	H
13626.000	39.47	-29.50	40.40	28.57	54.00	14.53	V
12991.000	37.73	-30.50	39.20	29.03	54.00	16.27	H
9527.000	35.50	-33.20	37.90	30.80	54.00	18.50	V
7988.500	34.09	-34.80	37.10	31.79	54.00	19.91	H
2349.500	42.95	-20.10	28.00	35.05	54.00	11.05	H

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17603.000	42.74	-25.70	46.00	22.54	54.00	11.26	V
14186.500	39.60	-29.00	42.00	26.60	54.00	14.40	H
12844.000	37.92	-30.70	39.10	29.42	54.00	16.08	H
9197.500	35.60	-33.70	38.00	31.30	54.00	18.40	V
7876.000	34.00	-34.90	37.10	31.80	54.00	20.00	H
4829.500	29.60	-37.50	33.10	33.90	54.00	24.40	V

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17997.000	42.77	-25.50	46.70	21.57	54.00	11.23	V
13648.500	39.27	-29.50	40.40	28.37	54.00	14.73	V
12820.000	37.60	-30.70	39.10	29.10	54.00	16.40	H
9184.500	35.36	-33.80	38.10	31.16	54.00	18.64	V
7869.500	34.15	-34.90	37.10	31.95	54.00	19.85	V
2485.100	43.42	-20.00	28.30	35.12	54.00	10.58	H

©Copyright. All rights reserved by CTTL.

π/4 DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17996.500	42.67	-25.50	46.70	21.47	54.00	11.33	V
13710.000	39.39	-29.10	40.90	27.59	54.00	14.61	V
12919.000	37.61	-30.50	39.20	28.91	54.00	16.39	H
9425.500	35.38	-32.90	37.90	30.38	54.00	18.62	H
7999.000	34.24	-34.80	37.10	31.94	54.00	19.76	V
2347.900	42.96	-20.10	28.00	35.06	54.00	11.04	H

π/4 DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17992.000	42.92	-25.50	46.70	21.72	54.00	11.08	H
14178.500	39.30	-29.00	42.00	26.30	54.00	14.70	V
12832.500	37.52	-30.70	39.10	29.02	54.00	16.48	H
9103.000	35.71	-33.80	38.10	31.31	54.00	18.29	V
7810.500	34.01	-35.10	37.00	32.11	54.00	19.99	H
4853.500	29.44	-37.50	33.10	33.74	54.00	24.56	V

π/4 DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17966.500	43.17	-25.50	46.70	21.97	54.00	10.83	H
14184.500	39.46	-29.00	42.00	26.46	54.00	14.54	H
12352.000	37.74	-31.10	38.90	29.94	54.00	16.26	V
9208.000	35.34	-33.70	38.00	31.04	54.00	18.66	H
7984.500	34.08	-34.80	37.10	31.78	54.00	19.92	V
2485.100	43.62	-20.00	28.30	35.32	54.00	10.38	H

©Copyright. All rights reserved by CTTL.

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17941.000	42.62	-25.50	46.70	21.42	54.00	11.38	H
13693.500	39.38	-29.50	40.40	28.48	54.00	14.62	H
12860.500	37.95	-30.70	39.10	29.45	54.00	16.05	V
9108.500	35.64	-33.80	38.10	31.44	54.00	18.36	H
7973.000	34.06	-34.80	37.10	31.76	54.00	19.94	H
2355.000	42.95	-20.10	28.00	34.95	54.00	11.05	H

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17952.000	42.78	-25.50	46.70	21.58	54.00	11.22	V
14179.000	39.23	-29.00	42.00	26.23	54.00	14.77	H
12892.000	37.74	-30.70	39.10	29.24	54.00	16.26	V
8991.500	35.30	-33.30	38.20	30.40	54.00	18.70	H
7205.000	33.86	-35.50	36.40	32.96	54.00	20.14	V
4823.500	29.48	-37.50	33.10	33.78	54.00	24.52	V

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17982.500	42.84	-25.50	46.70	21.64	54.00	11.16	V
14188.500	39.38	-29.00	42.00	26.38	54.00	14.62	V
12852.000	37.77	-30.70	39.10	29.27	54.00	16.23	V
9210.500	35.41	-33.70	38.00	31.11	54.00	18.59	V
7988.000	33.94	-34.80	37.10	31.64	54.00	20.06	H
2486.000	43.63	-20.00	28.30	35.33	54.00	10.37	H

Conclusion: Pass

©Copyright. All rights reserved by CTTL.

B.7. Time of Occupancy (Dwell Time)

Method of Measurement: See ANSI C63.10-clause 7.8.4

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW ≥ RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

Measurement Result:

For GFSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	DH1	Fig.64	0.38	Fig.65	319	121.22	P
	DH3	Fig.66	1.64	Fig.67	94	154.16	P
	DH5	Fig.68	2.89	Fig.69	60	173.4	P

For π/4 DQPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	2DH1	Fig.70	0.39	Fig.71	321	125.19	P
	2DH3	Fig.72	1.64	Fig.73	111	182.04	P
	2DH5	Fig.74	2.89	Fig.75	57	164.73	P

For 8DPSK

©Copyright. All rights reserved by CTTL.

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	3DH1	Fig.76	0.39	Fig.77	321	125.19	P
	3DH3	Fig.78	1.64	Fig.79	114	186.96	P
	3DH5	Fig.80	2.89	Fig.81	73	210.97	P

Conclusion: PASS

Test graphs as below:



Fig.64. Time of occupancy (Dwell Time): Channel 39, Packet DH1

©Copyright. All rights reserved by CTTL.



Fig.65. Number of Transmissions Measurement: Channel 39,Packet DH1



Fig.66. Time of occupancy (Dwell Time): Channel 39, Packet DH3

©Copyright. All rights reserved by CTTL.



Fig.67. Number of Transmissions Measurement: Channel 39,Packet DH3



Fig.68. Time of occupancy (Dwell Time): Channel 39, Packet DH5

©Copyright. All rights reserved by CTTL.



Fig.69. Number of Transmissions Measurement: Channel 39,Packet DH5



Fig.70. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1

©Copyright. All rights reserved by CTTL.



Fig.71. Number of Transmissions Measurement: Channel 39,Packet 2-DH1



Fig.72. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3

©Copyright. All rights reserved by CTTL.



Fig.73. Number of Transmissions Measurement: Channel 39,Packet 2-DH3



Fig.74. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5

©Copyright. All rights reserved by CTTL.



Fig.75. Number of Transmissions Measurement: Channel 39,Packet 2-DH5



Fig.76. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1

©Copyright. All rights reserved by CTTL.



Fig.77. Number of Transmissions Measurement: Channel 39,Packet 3-DH1



Fig.78. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3

©Copyright. All rights reserved by CTTL.



Fig.79. Number of Transmissions Measurement: Channel 39,Packet 3-DH3



Fig.80. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5

©Copyright. All rights reserved by CTTL.



Fig.81. Number of Transmissions Measurement: Channel 39,Packet 3-DH5

©Copyright. All rights reserved by CTTL.

B.8. 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 6.9.2

Measurement Procedure - Unwanted Emissions

1. Set RBW = 30kHz.

2. Set VBW = 100 kHz.

3. Set span to 3MHz

4. Detector = peak.

5. Trace Mode = max hold.

6. Sweep = auto couple.

7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

Use NdB Down function of the SA to measure the 20dB Bandwidth

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for "carrier frequency separation" test case, in Annex A.8.

Measurement Results:

For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.82	922.50	NA
39	Fig.83	921.75	NA
78	Fig.84	926.25	NA

For π/4 DQPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.85	1314.00	NA
39	Fig.86	1295.25	NA
78	Fig.87	1311.75	NA

For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.88	1302.75	NA
39	Fig.89	1298.25	NA
78	Fig.90	1301.25	NA

Conclusion: NA

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.82. 20dB Bandwidth: GFSK, Channel 0



Fig.83. 20dB Bandwidth: GFSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.84. 20dB Bandwidth: GFSK, Channel 78



Fig.85. 20dB Bandwidth: π/4 DQPSK, Channel 0

©Copyright. All rights reserved by CTTL.



Fig.86. 20dB Bandwidth: π/4 DQPSK, Channel 39



Fig.87. 20dB Bandwidth: π/4 DQPSK, Channel 78

©Copyright. All rights reserved by CTTL.



Fig.88. 20dB Bandwidth: 8DPSK, Channel 0



Fig.89. 20dB Bandwidth: 8DPSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.90. 20dB Bandwidth: 8DPSK, Channel 78

©Copyright. All rights reserved by CTTL.

B.9. Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

* Comment: This limit should be over 25 kHz or (2/3) * 20dB bandwidth, whichever is greater.

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or (2/3) * 20dB bandwidth

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.91	976.50	P

For π/4 DQPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.92	1007.25	P

For 8DPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.93	1137.00	P

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.91. Carrier frequency separation measurement: GFSK, Channel 39



Fig.92. Carrier frequency separation measurement: π/4 DQPSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.93. Carrier frequency separation measurement: 8DPSK, Channel 39

©Copyright. All rights reserved by CTTL.

B.10. Number of Hopping Channels

Method of Measurement: See ANSI C63.10-clause 7.8.3

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = the frequency band of operation
- RBW = 500kHz
- VBW = 500kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii)	At least 15 non-overlapping channels

Measurement Result:

For GFSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.94	79	P
40~78	Fig.95		

Forπ/4 DQPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.96	79	P
40~78	Fig.97		

For 8DPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.98	79	P
40~78	Fig.99		

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.94. Number of hopping frequencies: GFSK, Channel 0 - 39



Fig.95. Number of hopping frequencies: GFSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.



Fig.96. Number of hopping frequencies: π/4 DQPSK, Channel 0 - 39



Fig.97. Number of hopping frequencies: π/4 DQPSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.



Fig.98. Number of hopping frequencies: 8DPSK, Channel 0 - 39



Fig.99. Number of hopping frequencies: 8DPSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.

B.11. AC Powerline Conducted Emission

Method of Measurement: See ANSI C63.10-clause 6.2

Setup:

A stand-alone EUT shall be placed in the center along the back edge of the tabletop. For multiunit tabletop systems, the EUT shall be centered laterally (left to right facing the tabletop) on the tabletop and its rear shall be flush with the rear of the table.

Accessories that are part of an EUT system tested on a tabletop shall be placed in a test arrangement on one or both sides of the host with a 10 cm separation between the nearest points of the cabinets. The rear of the host and accessories shall be flush with the back of the supporting tabletop unless that would not be typical of normal use. If more than two accessories are present, then an equipment test arrangement shall be chosen that maintains 10 cm spacing between cabinets unless the equipment is normally located closer together.



Exploratory ac power-line conducted emission measurements

Exploratory measurements shall be used to identify the frequency of the emission that has the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable positions, and with a typical system equipment configuration and arrangement. For each mode of operation and for each ac power current-carrying conductor, cable manipulation shall be performed within the range of likely configurations. For this measurement or series of measurements, the frequency spectrum of interest shall be monitored looking for the emission that has the highest amplitude relative to the limit. Once that emission is found for each current-carrying conductor of each power cord associated with the EUT (but not the cords associated with non-EUT equipment in the overall system), the one configuration and

©Copyright. All rights reserved by CTTL.

arrangement and mode of operation that produces the emission closest to the limit over all of the measured conductors shall be recorded.

Final ac power-line conducted emission measurements

Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT. If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation. If the EUT is composed of equipment units that have their own separate ac power connections (e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network), then each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be measured separately. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.

Test Condition:

Voltage（V）	Frequency（Hz）
120	60

Measurement Result and limit:

EUT ID: EUT1

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV) With charger		Conclusion
		bluetooth	Idle	
0.15 to 0.5	66 to 56	Fig.B.11.1	Fig.B.11.2	P
0.5 to 5	56			
5 to 30	60			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV) With charger		Conclusion
		bluetooth	Idle	
0.15 to 0.5	56 to 46	Fig.B.11.1	Fig.B.11.2	P
0.5 to 5	46			
5 to 30	50			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

©Copyright. All rights reserved by CTTL.

Conclusion: Pass

Test graphs as below:



Fig.B.11.1 AC Powerline Conducted Emission- bluetooth

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Line	Margin (dB)	Limit (dBµV)
0.166000	46.8	N	18.4	65.2
0.430000	41.6	N	15.7	57.3
0.530000	39.2	N	16.8	56.0
1.178000	38.1	N	17.9	56.0
1.510000	37.2	N	18.8	56.0
2.538000	33.1	N	22.9	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Line	Margin (dB)	Limit (dBµV)
0.162000	40.6	L1	14.8	55.4
0.430000	31.2	N	16.1	47.3
0.530000	26.7	N	19.3	46.0
1.226000	27.4	N	18.6	46.0
1.478000	25.5	N	20.5	46.0
4.122000	27.8	L1	18.2	46.0

©Copyright. All rights reserved by CTTL.



Fig.B.11.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Line	Margin (dB)	Limit (dBµV)
0.158000	46.8	L1	18.8	65.6
0.434000	40.4	N	16.7	57.2
1.178000	38.4	N	17.6	56.0
1.494000	34.8	N	21.2	56.0
3.150000	33.8	N	22.2	56.0
4.894000	35.7	L1	20.3	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Line	Margin (dB)	Limit (dBµV)
0.158000	37.5	L1	18.1	55.6
0.378000	37.3	L1	11.0	48.3
0.434000	30.0	N	17.1	47.2
1.178000	28.8	N	17.2	46.0
1.494000	27.8	N	18.2	46.0
4.846000	29.6	L1	16.4	46.0

©Copyright. All rights reserved by CTTL.

ANNEX C: Accreditation Certificate

United States Department of Commerce
National Institute of Standards and Technology

NVLAP®

ilac-MRA

Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 600118-0

Telecommunication Technology Labs, CAICT
Beijing
China

is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:

Electromagnetic Compatibility & Telecommunications

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).

2021-09-29 through 2022-09-30
Effective Dates

DEPARTMENT OF COMMERCE · UNITED STATES OF AMERICA

For the National Voluntary Laboratory Accreditation Program

*****END OF REPORT*****

©Copyright. All rights reserved by CTTL.