TESTING
NVLAP LAB CODE 600118-0

HAC T-Coil TESTREPORT

No. I20Z60089-SEM03

For

OnePlus Technology (Shenzhen) Co., Ltd.

Smart Phone

Model name: HD1925

With

Hardware Version: 46

Software Version: 10.0.25.HD61CB

FCC ID: 2ABZ2-EE143

Results Summary: T Category = T3

Issued Date: 2020-3-17

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

©Copyright. All rights reserved by CTTL.

REPORT HISTORY

Report Number	Revision	Issue Date	Description
I20Z60089-SEM03	Rev.0	2020-3-17	Initial creation of test report

©Copyright. All rights reserved by CTTL.

TABLE OF CONTENT

1 TEST LABORATORY 5

1.1 TESTING LOCATION 5
1.2 TESTING ENVIRONMENT 5
1.3 PROJECT DATA 5
1.4 SIGNATURE 5

2 CLIENT INFORMATION 6

2.1 APPLICANT INFORMATION 6
2.2 MANUFACTURER INFORMATION 6

3 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 7

3.1 ABOUT EUT 7
3.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST 7
3.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST 7
3.4 AIR INTERFACES / BANDS INDICATING OPERATING MODES 8

4 REFERENCE DOCUMENTS 8

5 OPERATIONAL CONDITIONS DURING TEST 9

5.1 HAC MEASUREMENT SET-UP 9
5.2 AM1D PROBE 10
5.3 AMCC 11
5.4 AMMI 11
5.5 TEST ARCH PHANTOM &PHONE POSITIONER 11
5.6 ROBOTIC SYSTEM SPECIFICATIONS 12
5.7 T-COIL MEASUREMENT POINTS AND REFERENCE PLANE 12

6 T-COIL TEST PROCEDUERES 14

7 T-COIL PERFORMANCE REQUIREMENTS 15

7.1 T-COIL COUPLING FIELD INTENSITY 15
7.2 FREQUENCY RESPONSE 15

8 CMRS VOICE DUT CONFIGURATION 17

8.1 GSM CODEC INVESTIGATION 17
8.2 CDMA CODEC INVESTIGATION 17
8.3 UMTS CODEC INVESTIGATION 17

9 VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION 18

9.1 TEST SYSTEM SETUP FOR VOLTE OVER IMS T-COIL TESTING 18
9.2 CODEC CONFIGURATION 19
9.3 RADIO CONFIGURATION 19
9.4 LTE TDD UPLINK-DOWNLINK CONFIGURATION INVESTIGATION 20

10 VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION 22

10.1 TEST SYSTEM SETUP FOR VOWIFI OVER IMS T-COIL TESTING 22
10.2 CODEC CONFIGURATION 23
10.3 RADIO CONFIGURATION 23

11 OTT VOIP TEST SYSTEM AND DUT CONFIGURATION 25

11.1 TEST SYSTEM SETUP FOR OTT VOIP T-COIL TESTING 25
11.2 AIR INTERFACE INVESTIGATION FOR 5G NR 29
11.3 CODEC CONFIGURATION 30
11.4 RADIO CONFIGURATION FOR OTT VOIP (LTE) 31
11.5 RADIO CONFIGURATION FOR OTT VOIP (WIFI) 33

12 HAC T-COIL TEST DATA SUMMARY 35

12.1 TEST RESULTS FOR 2/3G 35
12.2 TEST RESULTS FOR LTE 36

©Copyright. All rights reserved by CTTL.

12.3 TEST RESULTS FOR WIFI 37
12.4 TEST RESULTS FOR OTT VOIP 38
12.5 TOTAL MEASUREMENT CONCLUSION 41

13 MEASUREMENT UNCERTAINTY 42

14 MAIN TEST INSTRUMENTS 44

ANNEX A TEST LAYOUT 45

ANNEX B TEST PLOTS 46

ANNEX C FREQUENCY REPONSE CURVES 146

ANNEX D PROBE CALIBRATION CERTIFICATE 155

ANNEX E DAE CALIBRATION CERTIFICATE 158

©Copyright. All rights reserved by CTTL.

1 Test Laboratory

1.1 Testing Location

Company Name:	CTTL(Shouxiang)
Address:	No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191

1.2 Testing Environment

Temperature:	18°C~25°C,
Relative humidity:	30%~ 70%
Ground system resistance:	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

1.3 Project Data

Project Leader:	Qi Dianyuan
Test Engineer:	Lin Hao
Testing Start Date:	October 7, 2019
Testing End Date:	March 17, 2020

1.4 Signature

Lin Xiaojun

(Prepared this test report)



Qi Dianyuan

(Reviewed this test report)



Lu Bingsong

Deputy Director of the laboratory

(Approved this test report)

©Copyright. All rights reserved by CTTL.

2 Client Information

2.1 Applicant Information

Company Name:	OnePlus Technology (Shenzhen) Co., Ltd
Address /Post:	18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen
Contact:	Ariel Cheng
Email:	ariel.cheng@oneplus.com
Telephone:	13823398081
Fax:	\

2.2 Manufacturer Information

Company Name:	OnePlus Technology (Shenzhen) Co., Ltd.
Address /Post:	18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen
Contact:	Ariel Cheng
Email:	ariel.cheng@oneplus.com
Telephone:	13823398081
Fax:	\

©Copyright. All rights reserved by CTTL.

3 Equipment Under Test (EUT) and Ancillary Equipment (AE)

This EUT is a variant product and the report of original sample is No.I19Z61344-SEM02.
We share the test results of original sample delete LTE Band13/14 and add the 5G NR n41.

3.1 About EUT

Description:	Smart Phone
Model name:	HD1925
Operating mode(s):	GSM850/900/1800/1900, WCDMAB1/B2/B4/B5/B8/B9/B19, CDMA BC0/BC1/BC10, 5G NR n71/n41/n2/n66, BT, Wi-Fi, NFC LTE Band 1/2/3/4/5/7/8/12/17/18/19/20/25/26/28/29/34/38/39/41/46/48/66/71

3.2 Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version
EUT1	990013820111370	46	10.0.25.HD61CB

*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test T-coil with the EUT1

3.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	BLP745	/	Sunwoda Electronic Co.,Ltd.

*AE ID: is used to identify the test sample in the lab internally.

©Copyright. All rights reserved by CTTL.

3.4 Air Interfaces / Bands Indicating Operating Modes

Air-interface	Band(MHz)	Type	C63.19/tested	Simultaneous Transmissions	OTT
GSM	850	VO	Yes	BT, WLAN	NA
	1900				
GPRS/EDGE	850	DT	Yes		Google duo
	1900				
WCDMA (UMTS)	850	VO	Yes	BT, WLAN	NA
	1700				
	1900				
	HSPA	DT	Yes		Google duo
CDMA	BC 0/1/10	VO	Yes	BT, WLAN	NA
	EVDO	DT	Yes	BT, WLAN	Google duo
LTE TDD	Band41/48	V/D	Yes	BT, WLAN	Google duo
LTE FDD	Band7/12/25/26/66/71	V/D	Yes	BT, WLAN	Google duo
BT	2450	DT	NA	GSM,WCDMA ,CDMA,LTE	NA
WLAN	2450	V/D	Yes	GSM,WCDMA ,CDMA,LTE	Google duo
WLAN	5G	V/D	Yes	GSM,WCDMA ,CDMA,LTE	Google duo

NA: Not Applicable VO: Voice Only V/D: CMRS and IP Voice Service over Digital Transport
DT: Digital Transport
* HAC Rating was not based on concurrent voice and data modes, Non current mode was found to represent worst case rating for both M and T rating
Note1 = No Associated T-Coil measurement has been made in accordance with 285076 D02 T-Coil testing for CMRS IP

4 Reference Documents

The following document listed in this section is referred for testing.

Reference	Title	Version
ANSI C63.19-2011	American National Standard for Methods of Measurement of Compatibility between Wireless Communication Devices and Hearing Aids	2011 Edition
KDB285076 D01v05	Equipment Authorization Guidance for Hearing Aid Compatibility	2017 Edition
KDB285076 D02v03	Guidance for performing T-Coil tests for air interfaces supporting voice over IP (e.g., LTE and WiFi) to support CMRS based telephone services	2017 Edition

©Copyright. All rights reserved by CTTL.

5 OPERATIONAL CONDITIONS DURING TEST

5.1 HAC MEASUREMENT SET-UP

These measurements are performed using the DASY5 NEO automated dosimetric assessment system. It is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland. It consists of high precision robotics system (Stäubli), robot controller, Intel Core2 computer, near-field probe, probe alignment sensor. The robot is a six-axis industrial robot performing precise movements. A cell controller system contains the power supply, robot controller, teach pendant (Joystick),and remote control, is used to drive the robot motors. The PC consists of the HP Intel Core21.86 GHz computer with Windows XP system and HAC Measurement Software DASY5 NEO, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE)circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.



Figure 5.1 HAC Test Measurement Set-up

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

©Copyright. All rights reserved by CTTL.



Figure 5.2 T-Coil setup with HAC Test Arch and AMCC

5.2 AM1D probe

The AM1D probe is an active probe with a single sensor. It is fully RF-shielded and has a rounded tip 6mm in diameter incorporating a pickup coil with its center offset 3mm from the tip and the sides. The symmetric signal preamplifier in the probe is fed via the shielded symmetric output cable from the AMMI with a 48V ”phantom” voltage supply. The 7-pin connector on the back in the axis of the probe does not carry any signals. It is mounted to the DAE for the correct orientation of the sensor. If the probe axis is tilted 54.7 degree from the vertical, the sensor is approximately vertical when

©Copyright. All rights reserved by CTTL.

the signal connector is at the underside of the probe (cable hanging downwards).

Specification:

Frequency range	0.1~20kHz (RF sensitivity < -100dB, fully RF shielded)
Sensitivity	< -50dB A/m @ 1kHz
Pre-amplifier	40dB, symmetric
Dimensions	Tip diameter/length: 6/290mm, sensor according to ANSI-C63.19

5.3 AMCC

The Audio Magnetic Calibration coil is a Helmholtz Coil designed for calibration of the AM1D probe. The two horizontal coils generate a homogeneous magnetic field in the z direction. The DC input resistance is adjusted by a series resistor to approximately 50Ohm, and a shunt resistor of 10Ohm permits monitoring the current with a scale of 1:10

Port description:

Signal	**Connector**	**Resistance**
Coil In	BNC	Typically 50Ohm
Coil Monitor	BNO	10Ohm±1% (100mV corresponding to 1 A/m)

Specification:

Dimensions	370 x 370 x 196 mm, according to ANSI-C63.19

5.4 AMMI

Figure 5.3 AMMI front panel

The Audio Magnetic Measuring Instrument (AMMI) is a desktop 19-inch unit containing a sampling unit, a waveform generator for test and calibration signals, and a USB interface.

Specification:

Sampling rate	48 kHz / 24 bit
Dynamic range	85 dB
Test signal generation	User selectable and predefined (vis PC)
Calibration	Auto-calibration / full system calibration using AMCC with monitor output
Dimensions	482 x 65 x 270 mm

5.5 Test Arch Phantom &Phone Positioner

The Test Arch phantom should be positioned horizontally on a stable surface. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. It enables easy and well defined positioning of the phone and validation dipoles as well as simple teaching of the robot (Dimensions: 370 x 370 x 370 mm).

The Phone Positioner supports accurate and reliable positioning of any phone with effect on near

©Copyright. All rights reserved by CTTL.

field <±0.5 dB.



Figure 5.4 HAC Phantom & Device Holder

5.6 Robotic System Specifications

Specifications

Positioner: Stäubli Unimation Corp. Robot Model: RX160L
Repeatability: ±0.02 mm
No. of Axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller
Processor: Intel Core2
Clock Speed: 1.86GHz
Operating System: Windows XP
Data Converter
Features: Signal Amplifier, multiplexer, A/D converter, and control logic
Software: DASY5 software
Connecting Lines: Optical downlink for data and status info.
Optical uplink for commands and clock

5.7 T-Coil measurement points and reference plane

Figure 6.5 illustrates the standard probe orientations. Position 1 is the perpendicular orientation of the probe coil; orientation 2 is the transverse orientations. The space between the measurement positions is not fixed. It is recommended that a scan of the WD be done for each probe coil orientation and that the maximum level recorded be used as the reading for that orientation of the probe coil.

1) The reference plane is the planar area that contains the highest point in the area of the phone that normally rests against the user's ear. It is parallel to the centerline of the receiver area of the

©Copyright. All rights reserved by CTTL.

phone and is defined by the points of the receiver-end of the WD handset, which, in normal handset use, rest against the ear.

2) The measurement plane is parallel to, and 10 mm in front of, the reference plane.

3) The reference axis is normal to the reference plane and passes through the center of the receiver speaker section (or the center of the hole array); or may be centered on a secondary inductive source. The actual location of the measurement point shall be noted in the test report as the measurement reference point.

4) The measurement points may be located where the axial and radial field intensity measurements are optimum with regard to the requirements. However, the measurement points should be near the acoustic output of the WD and shall be located in the same half of the phone as the WD receiver. In a WD handset with a centered receiver and a circularly symmetrical magnetic field, the measurement axis and the reference axis would coincide.

5) The relative spacing of each measurement orientation is not fixed. The axial and two radial orientations should be chosen to select the optimal position.

6) The measurement point for the axial position is located 10 mm from the reference plane on the measurement axis. The actual location of the measurement point shall be noted in test reports and designated as the measurement reference point.



Figure 5.5 Axis and planes for WD audio frequency magnetic field measurements

©Copyright. All rights reserved by CTTL.

6 T-Coil TEST PROCEDUERES

The following illustrate a typical test scan over a wireless communications device:

1) Geometry and signal check: system probe alignment, proper operation of the field probe, probe measurement system, other instrumentation, and the positioning system was confirmed. A surface calibration was performed before each setup change to ensure repeatable spacing and proper maintenance of the measurement plane using the test Arch.

2) Set the reference drive level of signal voice defined in C63.19 per 7.4.2.1.

3) The ambient and test system background noise (dB A/m) was measured as well as ABM2 over the full measurement. The maximum noise level must be at least 10dB below the limit.

4) The DUT was positioned in its intended test position, acoustic output point of the device perpendicular to the field probe.

5) The DUT operation for maximum rated RF output power was configured and connected by using of coaxial cable connection to the base station simulator at the test channel and other normal operating parameters as intended for the test. The battery was ensured to be fully charged before each test. The center sub-grid was centered over the center of the acoustic output (also audio band magnetic output, if applicable). The DUT audio output was positioned tangent (as physically possible) to the measurement plane.

6) The DUT's RF emission field was eliminated from T-coil results by using a well RF-shielding of the probe, AM1D, and by using of coaxial cable connection to a Base Station Simulator. One test channel was pre-measurement to avoid this possibility.

7) Determined the optimal measurement locations for the DUT by following the three steps, coarse resolution scan, fine resolution scans, and point measurement, as described in C63.19 per 7.4.4.2. At each measurement locations, samples in the measurement window duration were evaluated to get ABM1 and the signal spectrum. The noise measurement was performed after the scan with the signal, the same happened, just with the voice signal switched off. The ABM2 was calculated from this second scan.

8) All results resulting from a measurement point in a T-Coil job were calculated from the signal samples during this window interval. ABM values were averaged over the sequence of there samples.

9) At an optimal point measurement, the SNR (ABM1/ABM2) was calculated for perpendicular and transverse orientation, and the frequency response was measured for perpendicular.

10) Corrected for the frequency response after the DUT measurement since the DASY5 system had known the spectrum of the input signal by using a reference job.

11) In SEMCAD postprocessing, the spectral points are in addition scaled with the high-pass (half-band) and the A-weighting, bandwidth compensated factor (BWC) and those results are final as shown in this report.

©Copyright. All rights reserved by CTTL.

7 T-Coil PERFORMANCE REQUIREMENTS

In order to be rated for T-Coil use, a WD shall meet the requirements for signal level and signal quality contained in this part.

7.1 T-Coil coupling field intensity

When measured as specified in ANSI C63.19, the T-Coil signal shall be ≥ –18 dB (A/m) at 1 kHz, ina1/3 octave band filter for all orientations.

7.2 Frequency response

The frequency response of the axial component of the magnetic field, measured in 1/3 octave bands, shall follow the response curve specified in this sub-clause, over the frequency range 300 Hz to 3000 Hz. Figure 7.1 and Figure 7.2 provide the boundaries for the specified frequency. These response curves are for true field strength measurements of the T-Coil signal. Thus the 6 dB/octave probe response has been corrected from the raw readings.



NOTE—Frequency response is between 300 Hz and 3000 Hz.

Figure 7.1—Magnetic field frequency response for WDs with a field ≤ –15 dB (A/m) at 1 kHz



NOTE—Frequency response is between 300 Hz and 3000 Hz.

Figure 7.2—Magnetic field frequency response for WDs with a fieldthat exceeds –15 dB(A/m) at 1 kHz

©Copyright. All rights reserved by CTTL.

7.3 Signal quality

This part provides the signal quality requirement for the intended T-Coil signal from a WD. Only the RF immunity of the hearing aid is measured in T-Coil mode. It is assumed that a hearing aid can have noimmunity to an interference signal in the audio band, which is the intended reception band for this mode. So, the only criteria that can be measured is the RF immunity in T-Coil mode. This is measured using the same procedure as for the audio coupling mode and at the same levels.

The worst signal quality of the three T-Coil signal measurements shall be used to determine the T-Coil mode category per Table 1

Table 1:T-Coil signal quality categories

Category	Telephone parameters WD signal quality [(signal + noise) – to – noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

©Copyright. All rights reserved by CTTL.

8 CMRS Voice DUT CONFIGURATION

8.1 GSM Codec Investigation

The middle channel of each frequency band is used for T-coil testing according ANSI C63.19-2011. Choose worst case from radio configuration investigation. After investigation was performed to determine the audio codec configuration to be used for testing, the following tests results which the worst case codec would be remarked to be used for the testing for the DUT. According to C63 and KDB 285076 D02v03, GSM input level is -16dBm0.

Table 8-1 GSM CMRS Codec Investigation

Codec Setting	FR VR	HR V1	EFR	Orientation	Band	Channel
ABM1 (dBA/m)	2.00	2.28	2.70	Z(axial)	GSM1900	661
Frequency Response	PASS	PASS	PASS			
SNR (dB)	32.36	33.23	32.53			

8.2 CDMA Codec Investigation

The middle channel of each frequency band is used for T-coil testing according ANSI C63.19-2011. Choose worst case from radio configuration investigation. After investigation was performed to determine the audio codec configuration to be used for testing, the following tests results which the worst case codec would be remarked to be used for the testing for the DUT. According to C63 and KDB 285076 D02v03, CDMA input level is -18dBm0.

Table 8-2 CDMA CMRS Codec Investigation

Codec Setting	RC1/SO1	RC3/SO1	RC4/SO1	RC1/SO3	RC3/SO3	RC4/SO3	RC1/SO68	RC3/SO68	RC4/SO68	Orientation	Band	Channel
ABM1 (dBA/m)	0.52	0.15	-0.26	0.67	-0.49	-1.25	0.85	0.27	-0.58	Z(axial)	BC1	600
F.Response	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS			
SNR (dB)	48.26	47.85	48.18	46.89	46.57	47.63	48.24	46.79	48.27			

8.3 UMTS Codec Investigation

The middle channel of each frequency band is used for T-coil testing according ANSI C63.19-2011. Choose worst case from radio configuration investigation. After investigation was performed to determine the audio codec configuration to be used for testing, the following tests results which the worst case codec would be remarked to be used for the testing for the DUT. According to C63 and KDB 285076 D02v03, UMTS input level is -16dBm0.

Table 8-3 WCDMA/UMTS CMRS Codec Investigation

Codec Setting	AMR 12.2kbps	AMR 7.95kbps	AMR 4.75kbps	Orientation	Band	Channel
ABM1 (dBA/m)	3.33	3.22	3.22	Z(axial)	WCDMA 1900	9400
Frequency Response	PASS	PASS	PASS			
SNR (dB)	49.51	49.65	49.70			

©Copyright. All rights reserved by CTTL.

9 VoLTE TEST SYSTEM SETUP AND DUT CONFIGURATION

9.1 Test System Setup for VoLTE over IMS T-coil Testing

The general test setup used for VoLTE over IMS is shown below. The callbox used when performing VoLTE over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server. According to C63 and KDB 285076 D02v03, VoLTE input level is -20dBm0.



Figure 9.1 Test Setup for VoLTE over IMS T-coil Measurements

No correction gain factors were measured for VoLTE due to the Rohde & Schwarz CMW500, hosting a calibrated audio board. The gains used to measure VoLTE are set to 100.
The following software/firmware was used to simulate the VoLTE server for testing:

Firmware	License Keys	Software Name
V3.7.50 for LTE	KS500	LTE FDD R8 SIG BASIC
	KS550	LTE TDD R8 SIG BASIC
	KA100	IP APPL ENABLING IPv4
	KA150	IP APPL ENABLING IPv6
V3.7.20 for Audio	KAA20	IP APPL IMS BASIC
	KM050	DATA APPL MEAS
	KS104	EVS SPEECH CODEC

©Copyright. All rights reserved by CTTL.

9.2 Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. NB AMR 4.75kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

Table 9-1 AMR Codec Investigation – VoLTE over IMS

Codec Setting	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band/BW	Channel
ABM1 (dBA/m)	6.77	8.39	8.77	5.24	Z(axial)	B25/20M	26365
Frequency Response	PASS	PASS	PASS	PASS			
SNR (dB)	51.82	52.84	51.99	49.23			

Table 9-2 EVS Codec Investigation – VoLTE over IMS

Codec Setting	EVS Primary SWB 13.2kbps	EVS Primary SWB 9.6kbps	EVS Primary WB 13.2kbps	EVS Primary WB 5.9kbps	EVS Primary NB 13.2kbps	EVS Primary NB 5.9kbps	Orientation	Band /BW	Channel
ABM1 (dBA/m)	9.68	11.68	8.72	6.77	8.45	8.26	Z(axial)	B25/20M	26365
Frequency Response	PASS	PASS	PASS	PASS	PASS	PASS			
SNR (dB)	53.32	56.22	53.45	51.56	53.32	53.63			

9.3 Radio Configuration

An investigation was performed to determine the modulation, the bandwidth configuration and RB configuration to be used for testing. 20MHz BW，QPSK, 1RB, 50RB offset was used for the testing as the worst-case configuration for the handset. See below table for comparisons between different radio configurations:

Table 9-3 VoLTE over IMS SNR by Radio Configuration

Band	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	SNR [dB]
LTE B25	26365	20	QPSK	1	0	10.00	56.19
LTE B25	26365	20	QPSK	1	50	5.24	49.23
LTE B25	26365	20	QPSK	1	99	11.82	56.86
LTE B25	26365	20	QPSK	50	0	10.01	55.77
LTE B25	26365	20	QPSK	50	25	10.89	56.62
LTE B25	26365	20	QPSK	50	50	11.22	56.59
LTE B25	26365	20	QPSK	100	0	9.80	55.30
LTE B25	26365	20	16QAM	1	50	9.98	54.27
LTE B25	26365	20	64QAM	1	50	9.92	53.63
LTE B25	26365	15	QPSK	1	50	7.95	52.65
LTE B25	26365	10	QPSK	1	50	8.22	52.59
LTE B25	26365	5	QPSK	1	50	8.34	53.09
LTE B25	26365	3	QPSK	1	50	8.33	52.49
LTE B25	26365	1.4	QPSK	1	50	8.26	53.32

©Copyright. All rights reserved by CTTL.

9.4 LTE TDD Uplink-Downlink Configuration Investigation

An investigation was performed to determine the worst-case Uplink-Downlink configuration for LTE TDD T-coil testing.

Per 3GPP TS 36.211, the total frame length for each TDD radio frame of length T_f=307200.T_s=10 ms, where T_s is a number of time units equal to 1/(150002048) seconds. Additionally, each radio frame consists of 10 subframes, each of length 30720*T_s= 1ms, and subframes can be designated as uplink (U), downlink (D), or special subframe (S), depending on the Uplink-Downlink configuration as indicated in Table 4.2-2 of 3GPP TS 36.211. In the transmission duty factor calculation, the special subframe configuration with the shortest UpPTS duration within the special subframe is used and will be applied for measurement. From 3GPP TS 36.211 Table 4.2-1, the shortest UpPTS is 2192*T_s which occurs in the normal cyclic prefix and special subframe configuration 4.

See table below outlining the calculated transmission duty cycles for each Uplink-Downlink configuration:

Table 9-4 Uplink-Downlink Configurations for Type 2 Frame Structures

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number										Calculated Transmission Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	61.4%
1	5 ms	D	S	U	U	D	D	S	U	U	D	41.4%
2	5 ms	D	S	U	D	D	D	S	U	D	D	21.4%
3	10 ms	D	S	U	U	U	D	D	D	D	D	30.7%
4	10 ms	D	S	U	U	D	D	D	D	D	D	20.7%
5	10 ms	D	S	U	D	D	D	D	D	D	D	10.7%
6	5 ms	D	S	U	U	U	D	S	U	U	D	51.4%

a. Power Class 2 Uplink-Downlink Configuration Investigation

Power Class 2 was evaluated with the following radio configurations: channel 40620, 20MHz BW, QPSK, 1RB, 50RB Offset. For Power Class 2, configurations 1-5 are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 1 was used as the worst-case configuration for LTE TDD T-coil testing. See table below for the SNR comparison between each Uplink-Downlink configuration:

Table 9-5 LTE TDD Power Class 2 SNR by UL-DL Configuration

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	SNR [dB]
2593.0	40620	20	QPSK	1	50	1	8.66	42.07
2593.0	40620	20	QPSK	1	50	2	9.84	42.37
2593.0	40620	20	QPSK	1	50	3	5.39	38.28
2593.0	40620	20	QPSK	1	50	4	4.35	40.47
2593.0	40620	20	QPSK	1	50	5	3.93	39.95

©Copyright. All rights reserved by CTTL.

b. Power Class 3 Uplink-Downlink Configuration Investigation

Power Class 3 was evaluated with the following radio configurations: channel 40620, 20MHz BW, QPSK, 1RB, 50RB Offset. For Power Class 3, all configurations (0-6) are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 1 was used as the worst-case configuration for LTE TDD T-coil testing. See table below for the SNR comparison between each Uplink-Downlink configuration:

Table 9-6 LTE TDD Power Class 3 SNR by UL-DL Configuration

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	SNR [dB]
2593.0	40620	20	QPSK	1	50	0	8.07	42.24
2593.0	40620	20	QPSK	1	50	1	8.83	40.68
2593.0	40620	20	QPSK	1	50	2	5.34	38.39
2593.0	40620	20	QPSK	1	50	3	5.01	40.60
2593.0	40620	20	QPSK	1	50	4	4.76	40.66
2593.0	40620	20	QPSK	1	50	5	4.11	39.86
2593.0	40620	20	QPSK	1	50	6	4.48	37.16

c. Conclusion

Per the investigations above, UL-DL Configuration 3 was used to evaluate LTE TDD Power Class 2 and UL-DL Configuration 6 was used to evaluate LTE TDD Power Class 3.

©Copyright. All rights reserved by CTTL.

10 VoWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION

10.1 Test System Setup for VoWiFI over IMS T-coil Testing

Note1: the yellow highlight section has been approved for reuse.
General Note2:
Regards the protocols, the highlighting section of the test set up, reference levels used, will be re-used in future.

The general test setup used for VoWiFi over IMS, or CMRS WiFi Calling, is shown below. The callbox used when performing VoWiFi over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server. According to C63 and KDB 285076 D02v03, VoWiFi input level is -20dBm0.



Figure 10.1 Test Setup for VoWiFi over IMS T-coil Measurements

No correction gain factors were measured for VoWiFi due to the Rohde & Schwarz CMW500, hosting a calibrated audio board. The gains used to measure VoWiFi are set to 100.

Firmware	License Keys	Software Name
V3.7.40 for WLAN	KS650	WLAN A/B/G SIG BASIC
	KS651	WLAN N SIG BASIC
	KA100	IP APPL ENABLING IPv4
	KA150	IP APPL ENABLING IPv6
V3.7.20 for Audio	KAA20	IP APPL IMS BASIC
	KM050	DATA APPL MEAS
	KS104	EVS SPEECH CODEC

©Copyright. All rights reserved by CTTL.

10.2 Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The NB AMR 4.75kbps setting was used for the audio codec on the CMW500 for VoWiFi over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

Table 10-1 AMR Codec Investigation – VoWiFi over IMS

Codec Setting	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band/BW	Channel
ABM1 (dBA/m)	6.14	7.52	6.84	6.46	Z(axial)	2.4GHz 802.11b	6
Frequency Response	PASS	PASS	PASS	PASS			
SNR (dB)	48.37	49.26	48.67	47.54			

Table 10-2 EVS Codec Investigation – VoWiFi over IMS

Codec Setting	EVS Primary SWB 13.2kbps	EVS Primary SWB 9.6kbps	EVS Primary WB 13.2kbps	EVS Primary WB 5.9kbps	EVS Primary NB 13.2kbps	EVS Primary NB 5.9kbps	Orientation	Band /BW	Channel
ABM1 (dBA/m)	7.05	8.12	6.85	5.74	8.95	9.02	Z(axial)	2.4GHz 802.11b	6
Frequency Response	PASS	PASS	PASS	PASS	PASS	PASS			
SNR (dB)	50.26	49.83	48.76	49.37	50.04	49.52			

10.3 Radio Configuration

An investigation was performed on all applicable data rates and modulations to determine the radio configuration to be used for testing. See below table for comparisons between different radio configurations in each 802.11 standard:

Table10-3 802.11b SNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	SNR [dB]
802.11b	6	DSSS	1	6.46	47.54
802.11b	6	DSSS	2	6.55	47.06
802.11b	6	CCK	5.5	5.49	48.09
802.11b	6	CCK	11	4.61	47.64

Table 10-4 802.11g/a SNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	SNR [dB]
802.11g	6	BPSK	6	6.79	46.73
802.11g	6	BPSK	9	7.56	48.02
802.11g	6	QPSK	12	5.23	47.18
802.11g	6	QPSK	18	8.94	46.92
802.11g	6	16-QAM	24	8.21	49.16
802.11g	6	16-QAM	36	7.35	47.23

©Copyright. All rights reserved by CTTL.

802.11g	6	64-QAM	48	7.22	47.01
802.11g	6	64-QAM	54	6.58	47.25

Table 10-5 802.11n/ac 20MHz BW SNR by Radio Configuration

Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	SNR [dB]
802.11ac	20	44	BPSK	6.5	9.67	50.88
802.11ac	20	44	QPSK	13	8.25	51.02
802.11ac	20	44	QPSK	19.5	8.63	51.23
802.11ac	20	44	16-QAM	26	7.51	50.68
802.11ac	20	44	16-QAM	39	4.52	49.86
802.11ac	20	44	64-QAM	52	4.82	50.19
802.11ac	20	44	64-QAM	58.5	5.76	51.42
802.11ac	20	44	64-QAM	65	4.52	50.82
802.11ac	20	44	256-QAM	78	5.27	50.23

Table 10-6 802.11n/ac 40MHz BW SNR by Radio Configuration

Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	SNR [dB]
802.11ac	40	46	BPSK	13.5	9.21	50.60
802.11ac	40	46	QPSK	27	7.52	50.79
802.11ac	40	46	QPSK	40.5	8.98	50.92
802.11ac	40	46	16-QAM	54	9.63	51.29
802.11ac	40	46	16-QAM	81	10.05	51.08
802.11ac	40	46	64-QAM	108	8.74	50.86
802.11ac	40	46	64-QAM	121.5	8.65	51.27
802.11ac	40	46	64-QAM	135	8.52	51.25
802.11ac	40	46	256-QAM	162	7.26	52.14
802.11ac	40	46	256-QAM	180	8.92	52.36

Table 10-7 802.11ac 80MHz BW SNR by Radio Configuration

Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	SNR [dB]
802.11ac	80	42	BPSK	29.3	8.15	51.85
802.11ac	80	42	QPSK	58.5	7.26	50.07
802.11ac	80	42	QPSK	87.8	8.36	51.26
802.11ac	80	42	16-QAM	117	4.52	49.75
802.11ac	80	42	16-QAM	175.5	5.38	49.83
802.11ac	80	42	64-QAM	234	5.27	50.26
802.11ac	80	42	64-QAM	263.3	7.34	49.68
802.11ac	80	42	64-QAM	292.5	5.02	49.56
802.11ac	80	42	256-QAM	351	6.22	50.27
802.11ac	80	42	256-QAM	390	5.92	50.69

©Copyright. All rights reserved by CTTL.

11 OTT VoIP TEST SYSTEM AND DUT CONFIGURATION

11.1 Test System Setup for OTT VoIP T-coil Testing

Note1: the yellow highlight section has been approved for reuse.

General Note2:

Regards the protocols, Google Duo, the highlighting section of the test set up, reference levels used, codec(s) and the fact that an investigation was done to determine the worst-case codec/rate documented in the test results below, will be re-used in future.

OTT VoIP Application

Google Duo is a pre-installed application on the DUT which allows for VoIP calls in a head-to-ear scenario. Duo uses the OPUS audio codec and supports a bitrate range of 6kbps to 75kbps. All air interfaces capable of a data connection were evaluated with Google Duo. When HAC testing we are using the Google Duo version is 26.0.179825522.alpha.DEV and the bitrate configuration can find at settings → Voice call parameters settings → Audio codec bitrate(6-75kbps).

Test Procedure and Equipment Setup

The test procedure for OTT testing is identical to the section above, except for how the signal is sent to the DUT, as outlined in the diagram below.

The AMMI is connected to the support device's Mic via Audio Data Line. The support device is connected to the Internet via Wi-Fi and the DUT is connected to the mobile base station via the technology under test. Using the DUT's OTT application, a VoIP call is established with the support device. The test signal is sent from the DASY PC to the AMMI, from the AMMI to the support device, and finally to the DUT. To exercise the license antenna, the DUT was simultaneously connected to an external AP and to a mobile base station.

©Copyright. All rights reserved by CTTL.



Device1：



©Copyright. All rights reserved by CTTL.

Device2：



Device3：

©Copyright. All rights reserved by CTTL.

Device4：

Device5：The auxiliary device is pre-installed with a test version of Google duo app, The test version app can control the configurations of audio codec bitrate

Device6：The photo of DUT are presented in the additional document: Appendix to test report No.I20Z60089-SEM02/03 The photos of HAC test

Audio Level Settings

According to KDB 285076 D02, the average speech level of -20dBm0 shall be used for protocols not specifically listed in Table 7.1 of ANSI C63.19-2001.

Determine Input Audio level is based on the Added additional dBFS level readout by Google Duo customize application and three steps need to do.

1. Input a gain value to readout the -23dBFS level as reference. (0dBFS = 3.14 dBm0)
2. Adjust gain level to readout the dBFS level until it changes to -24dBFS.
3. Based on the step 1 and 2, and then calculate the gain value(dB) by interpolation to get the -20dBm0 corresponding gain value.

Codec Bit-rate Investigation

An investigation between the various bit-rate configurations (Low/Mid/High bit rates for Narrowband, Wideband, and EVS) are documented (ABM, SNNR, frequency response) to determine the worst case bit-rate for each voice service type. The tables below compare the varying bit-rate configurations

Air Interface Investigation

Using the worst-case bit-rate and Radio Configuration found in §11.2/11.3/11.4, a limited set of bands/channel/ bandwidths were then tested to confirm that there is no effect to the T-rating when changing the band/channel/bandwidth, it is necessary to report only a set band/channel/bandwidth for each orientation for a voice service/air interface.

©Copyright. All rights reserved by CTTL.

11.2 Air Interface Investigation for 5G NR

An investigation was performed to determine the modulation and RB configuration to be used for NR band n71/n41 testing. Due to equipment limitation, the worst-case ABM1 from LTE B25 was used with the ABM2 measured for each NR band n71/n41/n2/n66 modulation and RB configuration.

Air Interface	Channel	SCS (kHz)	Band width [MHz]	Modulation	RB allocation	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNR [dB]
5G NR n71	137600	15	5	DFT-s-OFDM QPSK	Inner_Full	5.24	-48.41	53.65
5G NR n71	137600	15	5	DFT-s-OFDM 16QAM	Inner_Full	5.24	-53.77	59.01
5G NR n71	137600	15	5	DFT-s-OFDM 64QAM	Inner_Full	5.24	-54.26	59.5
5G NR n71	137600	15	5	DFT-s-OFDM 256QAM	Inner_Full	5.24	-53.87	59.11
5G NR n71	137600	15	5	DFT-s-OFDM PI/2 BPSK	Inner_Full	5.24	-53.98	59.22
5G NR n71	137600	15	5	CP-OFDM QPSK	Inner_Full	5.24	-55.02	60.26
5G NR n71	137600	15	5	CP-OFDM 16QAM	Inner_Full	5.24	-54.26	59.5
5G NR n71	137600	15	5	CP-OFDM 64QAM	Inner_Full	5.24	-54.75	59.99
5G NR n71	137600	15	5	CP-OFDM 256QAM	Inner_Full	5.24	-54.39	59.63
5G NR n71	137600	15	5	DFT-s-OFDM QPSK	Edge_Full_Right	5.24	-50.38	55.62
5G NR n71	137600	15	5	DFT-s-OFDM QPSK	Edge_Full_Left	5.24	-49.04	54.28
5G NR n71	137600	15	5	DFT-s-OFDM QPSK	Inner_1RB_Right	5.24	-49.65	54.89
5G NR n71	137600	15	5	DFT-s-OFDM QPSK	Inner_1RB_Left	5.24	-49.99	55.23
5G NR n71	137600	15	5	DFT-s-OFDM QPSK	Outer_Full	5.24	-50.13	55.37
5G NR n71	137600	15	10	DFT-s-OFDM QPSK	Inner_Full	5.24	-49.57	54.81
5G NR n71	137600	15	15	DFT-s-OFDM QPSK	Inner_Full	5.24	-50.11	55.35
5G NR n71	137600	30	5	DFT-s-OFDM QPSK	Inner_Full	5.24	-48.63	53.87

©Copyright. All rights reserved by CTTL.

Air Interface	Channel	SCS (kHz)	Band width [MHz]	Modulation	RB allocation	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNR [dB]
5G NR n41	518598	30	20	DFT-s-OFDM QPSK	Inner_Full	5.24	-45.63	50.87
5G NR n41	518598	30	40	DFT-s-OFDM QPSK	Inner_Full	5.24	-45.27	50.51
5G NR n41	518598	30	50	DFT-s-OFDM QPSK	Inner_Full	5.24	-48.26	53.50
5G NR n41	518598	30	60	DFT-s-OFDM QPSK	Inner_Full	5.24	-45.38	50.62
5G NR n41	518598	30	80	DFT-s-OFDM QPSK	Inner_Full	5.24	-44.96	50.20
5G NR n41	518598	30	90	DFT-s-OFDM QPSK	Inner_Full	5.24	-46.11	51.35
5G NR n41	518598	30	100	DFT-s-OFDM QPSK	Inner_Full	5.24	-44.15	49.39

11.3 Codec Configuration

An investigation was performed for each applicable data mode to determine the audio codec configuration to be used for testing. The 6kbps codec setting was used for the audio codec on the auxiliary VoIP unit for OTT VoIP T-coil testing. See below tables for comparisons between codec data rates on all applicable data modes:

Table 11-2 Codec Investigation – OTT over EDGE

Codec Setting	64kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	6.23	5.19	Z(axial)	661
Frequency Response	Pass	Pass		
SNR (dB)	51.47	49.52		

Table 11-3 Codec Investigation – OTT over HSPA

Codec Setting	64kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	7.89	8.50	Z(axial)	9400
Frequency Response	Pass	Pass		
SNR (dB)	52.33	51.66		

Table 11-4 Codec Investigation – OTT over LTE

Codec Setting	64kbps	6kbps	Orientation	Band/BW	Channel
ABM1 (dBA/m)	13.60	3.65	Z(axial)	B25/20M	26365
Frequency Response	Pass	Pass			
SNR (dB)	56.08	48.60			

Table 11-5 Codec Investigation – OTT over WiFi

Codec Setting	64kbps	6kbps	Orientation	Band/BW	Channel

©Copyright. All rights reserved by CTTL.

ABM1 (dBA/m)	11.24	10.89	Z(axial)	2.4GHz 802.11b	6
Frequency Response	Pass	Pass			
SNR (dB)	51.38	50.19			

11.4 Radio Configuration for OTT VoIP (LTE)

An investigation was performed to determine the modulation and RB configuration to be used for testing. 20MHz BW， QPSK, 1RB, 50RB offset was used for the testing as the worst-case configuration for the handset. See below table for comparisons between different radio configurations:

Table 11-6 OTT VoIP (LTE) SNR by Radio Configuration

Band	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	SNR [dB]
LTE B25	26365	20	QPSK	1	0	2.48	48.89
LTE B25	26365	20	QPSK	1	50	3.65	48.60
LTE B25	26365	20	QPSK	1	99	3.96	50.23
LTE B25	26365	20	QPSK	50	0	4.03	50.27
LTE B25	26365	20	QPSK	50	25	4.25	49.86
LTE B25	26365	20	QPSK	50	50	4.28	49.25
LTE B25	26365	20	QPSK	100	0	3.56	49.63
LTE B25	26365	20	16QAM	1	50	3.78	50.24
LTE B25	26365	20	64QAM	1	50	2.96	50.14
LTE B25	26365	15	QPSK	1	50	3.41	50.06
LTE B25	26365	10	QPSK	1	50	4.22	48.77
LTE B25	26365	5	QPSK	1	50	4.08	51.27
LTE B25	26365	3	QPSK	1	50	5.03	50.63
LTE B25	26365	1.4	QPSK	1	50	5.27	49.85

Table 11-7 LTE TDD Power Class 2 SNR by UL-DL Configuration

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	SNR [dB]
2593.0	40620	20	QPSK	1	50	1	5.13	43.56
2593.0	40620	20	QPSK	1	50	2	3.56	44.27
2593.0	40620	20	QPSK	1	50	3	4.89	42.79
2593.0	40620	20	QPSK	1	50	4	4.82	42.95
2593.0	40620	20	QPSK	1	50	5	4.67	43.58

©Copyright. All rights reserved by CTTL.

Table 11-8 LTE TDD Power Class 3 SNR by UL-DL Configuration

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	SNR [dB]
2593.0	40620	20	QPSK	1	50	0	6.31	43.65
2593.0	40620	20	QPSK	1	50	1	5.87	44.27
2593.0	40620	20	QPSK	1	50	2	4.96	45.16
2593.0	40620	20	QPSK	1	50	3	5.26	45.72
2593.0	40620	20	QPSK	1	50	4	7.13	45.23
2593.0	40620	20	QPSK	1	50	5	5.81	44.72
2593.0	40620	20	QPSK	1	50	6	5.62	43.87

An investigation was performed to determine the worst-case LTE band to be used for OTT VoIP testing. LTE Band 25 of FDD and LTE Band 41 (Power Class 2) of TDD were used for the testing as the worst-case configuration for the handset. See below table for comparisons between different LTE bands:

Table 11-9 OTT VoIP (LTE) SNR by LTE bands

Band	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	SNR [dB]
LTE B7	21100	20	QPSK	1	50	4.82	50.03
LTE B12	23095	10	QPSK	1	50	3.78	50.24
LTE B25	26365	20	QPSK	1	50	3.65	48.60
LTE B26	26865	10	QPSK	1	50	4.56	51.21
LTE B66	132322	20	QPSK	1	50	4.23	48.97
LTE B71	133297	20	QPSK	1	50	4.21	48.85

©Copyright. All rights reserved by CTTL.

11.5 Radio Configuration for OTT VoIP (WiFi)

An investigation was performed on all applicable data rates and modulations to determine the radio configuration to be used for testing. See below tables for comparisons between different radio configurations in each 802.11 standard:

Table 11-10 802.11b SNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	SNR [dB]
802.11b	6	DSSS	1	10.89	50.19
802.11b	6	DSSS	2	12.58	51.12
802.11b	6	CCK	5.5	12.71	48.89
802.11b	6	CCK	11	11.56	50.34

Table 11-11 802.11g/a SNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	SNR [dB]
802.11g	6	BPSK	6	13.92	47.89
802.11g	6	BPSK	9	11.24	48.76
802.11g	6	QPSK	12	12.35	49.83
802.11g	6	QPSK	18	11.87	50.74
802.11g	6	16-QAM	24	14.60	50.72
802.11g	6	16-QAM	36	15.24	50.32
802.11g	6	64-QAM	48	12.88	49.25
802.11g	6	64-QAM	54	13.26	48.95

Table 11-12 802.11n/ac 20MHz BW SNR by Radio Configuration

Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	SNR [dB]
802.11ac	20	44	BPSK	6.5	9.56	56.81
802.11ac	20	44	QPSK	13	9.42	57.09
802.11ac	20	44	QPSK	19.5	9.17	57.42
802.11ac	20	44	16-QAM	26	10.07	56.21
802.11ac	20	44	16-QAM	39	10.15	56.74
802.11ac	20	44	64-QAM	52	10.23	56.39
802.11ac	20	44	64-QAM	58.5	10.96	57.15
802.11ac	20	44	64-QAM	65	10.45	56.04
802.11ac	20	44	256-QAM	78	10.24	56.38

Table 11-13 802.11n/ac 40MHz BW SNR by Radio Configuration

Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	SNR [dB]

©Copyright. All rights reserved by CTTL.

802.11ac	40	46	BPSK	13.5	10.34	55.98
802.11ac	40	46	QPSK	27	11.02	55.72
802.11ac	40	46	QPSK	40.5	9.68	56.68
802.11ac	40	46	16-QAM	54	7.83	56.84
802.11ac	40	46	16-QAM	81	10.35	56.23
802.11ac	40	46	64-QAM	108	10.54	56.18
802.11ac	40	46	64-QAM	121.5	9.27	55.96
802.11ac	40	46	64-QAM	135	9.68	55.78
802.11ac	40	46	256-QAM	162	9.44	56.34
802.11ac	40	46	256-QAM	180	10.26	56.21

Table 11-14 802.11ac 80MHz BW SNR by Radio Configuration

Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	SNR [dB]
802.11ac	80	42	BPSK	29.3	10.23	56.23
802.11ac	80	42	QPSK	58.5	11.05	55.89
802.11ac	80	42	QPSK	87.8	9.56	55.36
802.11ac	80	42	16-QAM	117	9.85	56.04
802.11ac	80	42	16-QAM	175.5	10.23	56.27
802.11ac	80	42	64-QAM	234	10.47	56.23
802.11ac	80	42	64-QAM	263.3	9.68	55.92
802.11ac	80	42	64-QAM	292.5	9.35	55.74
802.11ac	80	42	256-QAM	351	9.27	55.65
802.11ac	80	42	256-QAM	390	9.41	55.81

©Copyright. All rights reserved by CTTL.

12 HAC T-Coil TEST DATA SUMMARY

12.1 Test Results for 2/3G

Table 12-1 Test results for 2/3G

Probe Position	Band	Ch.	Measurement Position (x mm, y mm)	ABM1 (dB A/m)	SNR (dB)	T category
transverse	GSM 850	190	0.8,12.9	-9.98	32.96	T4
	GSM 1900	661	0.4,12.9	-9.71	36.79	T4
	WCDMA850	4182	4.2,-4.2	-5.27	47.42	T4
	WCDMA1900	9400	6.3,-1.7	-4.42	49.77	T4
	WCDMA1700	1412	5.8,-2.9	-4.54	48.05	T4
	CDMA BC0	384	4.6,-2.9	-7.83	44.67	T4
	CDMA BC1	600	5.4,-3.8	-8.47	46.43	T4
	CDMA BC10	580	7.1,-4.6	-9.62	46.00	T4
perpendicular	GSM 850	190	4.2,8.3	1.93	27.20	T3
	GSM 1900	661	4.2,7.9	2.00	32.36	T4
	WCDMA850	4182	5.4,5.4	3.32	49.24	T4
	WCDMA1900	9400	5.4,5	3.33	49.51	T4
	WCDMA1700	1412	5.4,5.4	3.32	49.37	T4
	CDMA BC0	384	6.7,7.5	0.88	45.76	T4
	CDMA BC1	600	5.8,5.0	-0.49	46.57	T4
	CDMA BC10	580	6.7,7.9	-0.66	46.63	T4

Note:

1. Bluetooth and WiFi function is turn off and microphone is muted.
2. Signal strength measurement scan plots are presented in Annex B.
3. The volume is adjusted to maximum level during T-Coil testing.

©Copyright. All rights reserved by CTTL.

12.2 Test Results for LTE

Table 12-2 Test results for LTE

Probe Position	Band	Ch.	Bandwidth	Measurement Position (x mm, y mm)	ABM1 (dBA/m)	SNR (dB)	Category T ?
Transverse y	LTE B7	21100	20	5,-2.1	-2.25	51.28	T4
	LTE B12	23095	3	5.4,-2.1	-2.01	52.63	T4
	LTE B25	26365	20	2.5,-1.3	-3.39	51.39	T4
	LTE B26	26865	3	4.6,-2.5	-2.39	52.74	T4
	LTE B66	132322	20	4.2,-1.7	-2.02	52.02	T4
	LTE B71	133322	20	7.5,-4.6	-1.36	50.74	T4
	LTE B41（Power Class 2）	40620	20	4.2.12.9	-3.98	43.55	T4
	LTE B41（Power Class 3）	40620	20	4.2,13.3	-3.36	44.98	T4
	LTE B48	55990	20	7.5,3.7	-1.96	45.39	T4
Perpendicular z	LTE B7	21100	20	5,6.7	5.32	52	T4
	LTE B12	23095	3	5.4,7.5	4.70	51.49	T4
	LTE B25	26365	20	5,7.1	5.24	49.23	T4
	LTE B26	26865	3	5,7.5	5.69	52.88	T4
	LTE B66	132322	20	5,7.5	4.65	51.55	T4
	LTE B71	133322	20	5.4,4.2	5.93	51.46	T4
	LTE B41（Power Class 2）	40620	20	4.2,6.2	5.39	38.28	T4
	LTE B41（Power Class 3）	40620	20	4.6,7.9	4.48	37.16	T4
	LTE B48	55990	20	4.6,8.3	5.96	45.34	T4

Note:

1. Bluetooth and WiFi function is turn off and microphone is muted.
2. The worse case of each band for signal strength measurement scan plots are presented in Annex B.
3. The volume is adjusted to maximum level during T-Coil testing.
4. For LTE Band 41, UL-DL Configuration 3 was used to evaluate Power Class 2 and UL-DL Configuration 6 was used to evaluate Power Class 3.

©Copyright. All rights reserved by CTTL.

12.3 Test Results for WiFi

Table 12-3 Test results for WiFi

Probe Position	Mode	Ch.	Bandwidth	Measurement Position (x mm, y mm)	ABM1 (dB A/m)	SNR (dB)	Category T ?
Transverse y	802.11b	6	20M	4.2,16.7	-2.43	47.11	T4
	802.11g	6	20M	0.8,16.7	-5.07	46.20	T4
	802.11n	6	20M	0,0	-6.94	46.07	T4
	802.11n	6	40M	5.4,-1.3	-2.83	48.34	T4
	802.11a UNII-1	44	20M	4.6,-2.1	0.62	52.15	T4
	802.11n UNII-1	44	20M	4.2,-5	-3.30	44.87	T4
		46	40M	5,-4.2	0.34	55.60	T4
	802.11ac UNII-1	44	20M	5.4,-2.1	0.59	50.98	T4
		46	40M	7.5,-3.8	0.04	52.10	T4
		42	80M	0.4,-3.3	-3.00	49.99	T4
	802.11n	60	20M	4.2,-1.7	0.23	52	T4
	802.11n	124	20M	4.2,-1.3	-2.01	49.89	T4
	802.11n	157	20M	3.8,-4.2	-3.73	47.58	T4
Perpendicular z	802.11b	6	20M	5.4,7.9	6.55	47.06	T4
	802.11g	6	20M	7.1,8.7	6.79	46.73	T4
	802.11n	6	20M	8.3,8.3	3.00	46.13	T4
	802.11n	6	40M	4.6,8.3	4.49	48.55	T4
	802.11a UNII-1	44	20M	7.1,7.1	8.71	53.34	T4
	802.11n UNII-1	44	20M	6.7,6.7	8.68	51.09	T4
		46	40M	4.2,4.6	8.09	52.54	T4
	802.11ac UNII-1	44	20M	4.2,7.5	4.52	49.86	T4
		46	40M	5,4.2	5.02	49.56	T4
		42	80M	8.3,8.3	9.21	50.60	T4
	802.11ac	62	40M	5,8.3	3.20	47.53	T4
	802.11ac	126	40M	3.3,4.6	5.88	50.03	T4
	802.11ac	159	40M	7.5,4.6	6.37	49.18	T4

Note:

1. Bluetooth and WiFi function is turn off and microphone is muted.
2. The worse case of each mode for signal strength measurement scan plots are presented in Annex B.
3. The volume is adjusted to maximum level during T-Coil testing.

©Copyright. All rights reserved by CTTL.

12.4 Test Results for OTT VoIP

Table 12-4 Test results for 2/3G

Probe Position	Band	Ch.	Measurement Position (x mm, y mm)	ABM1 (dB A/m)	SNR (dB)	Category T ?
Transverse y	EDGE850(3TX)	190	5.8,16.7	6.55	53.53	T4
	EDGE1900(3TX)	661	8.3,16.7	5.19	49.52	T4
	W850	4407	4.2,2.9	10.08	53.36	T4
	W1900	9800	7.1,0.8	9.29	50.27	T4
	W1700	1637	1.3,-4.2	6.96	52.05	T4
Perpendicular z	EDGE850(3TX)	190	2.5,8.3	6.28	48.47	T4
	EDGE1900(3TX)	661	0.9.6	6.51	47.56	T4
	W850	4407	4.2,4.2	5.06	50.36	T4
	W1900	9800	3.8,9.2	8.50	51.66	T4
	W1700	1637	7.9,9.2	7.48	51.41	T4

Note:

1. Bluetooth and WiFi function is turn off and microphone is muted.
2. Signal strength measurement scan plots are presented in Annex B.
3. The volume is adjusted to maximum level during T-Coil testing.

Table 12-5 Test results for LTE

Probe Position	Band	Ch.	Bandwidth	Measurement Position (x mm, y mm)	ABM1 (dB A/m)	SNR (dB)	Category T ?
Transverse y	LTE B25	26365	20	3.3,-0.4	5.80	55.02	T4
	LTE B41（High power）	40620	20	3.8,12.9	5.43	49.05	T4
Perpendicular z	LTE B25	26365	20	4.6,7.1	3.65	48.60	T4
	LTE B41（High power）	40620	20	4.2,5	4.89	42.79	T4

Note:

1. Bluetooth and WiFi function is turn off and microphone is muted.
2. The worse case of each band for signal strength measurement scan plots are presented in Annex B.
3. The volume is adjusted to maximum level during T-Coil testing.
4. For LTE Band 41, UL-DL Configuration 3 was used to evaluate Power Class 2.

©Copyright. All rights reserved by CTTL.

Table 12-6 Test results for 5G NR n71/n41

Probe Position	Band	Ch.	Modulation/Mode	Measurement Position (x mm, y mm)	ABM1 (dB A/m)	ABM2 (dB A/m)	SNR (dB)	Category T ?
Transverse y	5G NR n71	137600	5M- DFT-s-OFDM QPSK- Inner_Full	3.3,-0.4	5.80	-50.43	56.23	T4
	5G NR n41	509400	100M- DFT-s-OFDM QPSK- Inner_Full	3.3,-0.4	5.80	-45.23	51.03	T4
	5G NR n2	376000	20M- DFT-s-OFDM QPSK- Inner_Full	3.3,-0.4	5.80	-50.28	56.08	T4
	5G NR n66	349000	20M- DFT-s-OFDM QPSK- Inner_Full	3.3,-0.4	5.80	-51.69	57.49	T4
Perpendicular z	5G NR n71	137600	5M- DFT-s-OFDM QPSK- Inner_Full	4.6,7.1	3.65	-45.62	49.27	T4
	5G NR n41	509400	100M- DFT-s-OFDM QPSK- Inner_Full	4.6,7.1	3.65	-44.36	48.01	T4
	5G NR n2	376000	20M- DFT-s-OFDM QPSK- Inner_Full	4.6,7.1	3.65	-46.73	50.38	T4
	5G NR n66	349000	20M- DFT-s-OFDM QPSK- Inner_Full	4.6,7.1	3.65	-47.25	50.90	T4

Note:

1. Bluetooth and WiFi function is turn off and microphone is muted.
2. The volume is adjusted to maximum level during T-Coil testing.
3. Due to equipment limitation, ABM1 and frequency response measurement were not possible. Therefore, the worst-case ABM1 measurement from LTE FDD OTT VoIP testing for Axial and Radial were combined with 5G NR n71/n41/n2/n66 ABM2 measurement to obtain SNNR values.

Table 12-7 Test results for WiFi

Probe Position	Mode	Ch.	Bandwidth	Measurement Position (x mm, y mm)	ABM1 (dB A/m)	SNR (dB)	Category T ?
Transverse y	802.11b	6	20M	3.8,14.2	6.60	51.15	T4
	802.11g	6	20M	0,0.4	4.60	53.16	T4
	802.11n	6	20M	-0.4,15	1.38	48.01	T4
	802.11n	6	40M	7.1,5.8	13.82	56.50	T4
	802.11a UNII-1	44	20M	8.3,-2.1	7.21	53.73	T4
	802.11n UNII-1	44	20M	5.6,8.3	6.35	54.13	T4
		46	40M	3.9,13.6	7.12	54.06	T4
	802.11ac UNII-1	44	20M	4.6,17.5	5.87	53.22	T4
		46	40M	3.8,10.5	6.11	53.78	T4

©Copyright. All rights reserved by CTTL.

		42	80M	4.4,8.9	5.89	53.89	**T4**
	802.11ac	60	20M	5.6,10.2	5.14	54.26	**T4**
	802.11ac	124	20M	6.3,10.7	5.26	54.17	**T4**
	802.11ac	157	20M	3.6,10.2	5.38	54.12	**T4**
Perpendicular z	**802.11b**	6	20M	11.7,10.8	12.71	48.89	**T4**
	802.11g	6	20M	9.6,11.2	13.92	47.89	**T4**
	802.11n	6	20M	12.1,11.7	12.06	48.86	**T4**
	802.11n	6	40M	7.1,5.8	13.82	56.50	**T4**
	802.11a UNII-1	44	20M	4.6,8.3	11.05	54.01	**T4**
	802.11n UNII-1	44	20M	4.4,8.1	10.26	55.21	**T4**
		46	40M	6.8,9.6	9.38	54.76	**T4**
	802.11ac UNII-1	44	20M	5.2,7.6	10.45	56.04	**T4**
		46	40M	3.2,8.2	11.02	55.72	**T4**
		42	80M	4.5，8.1	9.56	55.36	**T4**
	802.11a	60	20M	2.5,10.2	8.52	55.02	**T4**
	802.11a	124	20M	3.5,7.8	10.71	54.28	**T4**
	802.11a	157	20M	4.3,10.4	9.28	54.39	**T4**

Note:

4. Bluetooth and WiFi function is turn off and microphone is muted.
5. The worse case of each mode for signal strength measurement scan plots are presented in Annex B.
6. The volume is adjusted to maximum level during T-Coil testing.

©Copyright. All rights reserved by CTTL.

12.5 Total Measurement Conclusion

Probe Position	Frequency Band(MHz)	ABM1	Frequency Response	T Category
Transverse	GSM 850	Pass	/	T4
	GSM 1900	Pass		T4
	WCDMA850	Pass		T4
	WCDMA1900	Pass		T4
	WCDMA1700	Pass		T4
	CDMA BC0	Pass		T4
	CDMA BC1	Pass		T4
	CDMA BC10	Pass		T4
	LTE B7	Pass		T4
	LTE B12	Pass		T4
	LTE B25	Pass		T4
	LTE B26	Pass		T4
	LTE B41 Power Class 2	Pass		T4
	LTE B41 Power Class 3	Pass		T4
	LTE B66	Pass		T4
	LTE B71	Pass		T4
	5G NR n71	NA		T4
	5G NR n41	NA		T4
	5G NR n2	NA		T4
	5G NR n66	NA		T4
	WiFi 2.4G	Pass		T4
	WiFi 5G	Pass		T4
Perpendicular	GSM 850	Pass	Pass	T3
	GSM 1900	Pass	Pass	T4
	WCDMA850	Pass	Pass	T4
	WCDMA1900	Pass	Pass	T4
	WCDMA1700	Pass	Pass	T4
	CDMA BC0	Pass	Pass	T4
	CDMA BC1	Pass	Pass	T4
	CDMA BC10	Pass	Pass	T4
	LTE B7	Pass	Pass	T4
	LTE B12	Pass	Pass	T4
	LTE B25	Pass	Pass	T4
	LTE B26	Pass	Pass	T4
	LTE B41 Power Class 2	Pass	Pass	T4
	LTE B41 Power Class 3	Pass	Pass	T4
	LTE B66	Pass	Pass	T4
	LTE B71	Pass	Pass	T4
	5G NR n71	NA	NA	T4
	5G NR n41	NA	NA	T4
	5G NR n2	NA	NA	T4
	5G NR n66	NA	NA	T4
	WiFi 2.4G	Pass	Pass	T4
	WiFi 5G	Pass	Pass	T4

©Copyright. All rights reserved by CTTL.

13 MEASUREMENT UNCERTAINTY

No.	Error source	Type	Uncertainty Value a_i (%)	Prob. Dist.	Div.	ABM1 ci	ABM2 ci	Std. Unc. ABM1 u_i' (%)	Std. Unc. ABM2 u_i' (%)
1	System Repeatability	A	0.016	N	1	1	1	0.016	0.016
Probe Sensitivity									
2	Reference Level	B	3.0	R	$\sqrt{3}$	1	1	3.0	3.0
3	AMCC Geometry	B	0.4	R	$\sqrt{3}$	1	1	0.2	0.2
4	AMCC Current	B	0.6	R	$\sqrt{3}$	1	1	0.4	0.4
5	Probe Positioning during Calibration	B	0.1	R	$\sqrt{3}$	1	1	0.1	0.1
6	Noise Contribution	B	0.7	R	$\sqrt{3}$	0.0143	1	0.0	0.4
7	Frequency Slope	B	5.9	R	$\sqrt{3}$	0.1	1	0.3	3.5
Probe System									
8	Repeatability / Drift	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
9	Linearity / DynamicRange	B	0.6	N	1	1	1	0.4	0.4
10	Acoustic Noise	B	1.0	R	$\sqrt{3}$	0.1	1	0.1	0.6
11	Probe Angle	B	2.3	R	$\sqrt{3}$	1	1	1.4	1.4
12	Spectral Processing	B	0.9	R	$\sqrt{3}$	1	1	0.5	0.5
13	Integration Time	B	0.6	N	1	1	5	0.6	3.0
14	Field Distribution	B	0.2	R	$\sqrt{3}$	1	1	0.1	0.1
Test Signal									
15	Ref.Signal Spectral Response	B	0.6	R	$\sqrt{3}$	0	1	0.0	0.4
Positioning									
16	Probe Positioning	B	1.9	R	$\sqrt{3}$	1	1	1.1	1.1
17	Phantom Thickness	B	0.9	R	$\sqrt{3}$	1	1	0.5	0.5

©Copyright. All rights reserved by CTTL.

18	DUT Positioning	B	1.9	R	$\sqrt{3}$	1	1	1.1	1.1
External Contributions									
19	RF Interference	B	0.0	R	$\sqrt{3}$	1	0.3	0.0	0.0
20	Test Signal Variation	B	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
Combined Std. Uncertainty (ABM Field)		$u_c^{'} = \sqrt{\sum_{i=1}^{20} c_i^2 u_i^2}$						4.1	6.1
Expanded Std. Uncertainty		$u_e = 2u_c$		N	$k = 2$			**8.2**	**12.2**

©Copyright. All rights reserved by CTTL.

14 MAIN TEST INSTRUMENTS

List of Main Instruments

No.	Name	Type	Serial Number	Calibration Date	Valid Period
01	Audio Magnetic 1D Field Probe	AM1DV2	1064	July 23, 2019	One year
02	Audio Magnetic Calibration Coil	AMCC	1064	NCR	NCR
03	Audio Measuring Instrument	AMMI	1044	NCR	NCR
04	HAC Test Arch	N/A	1014	NCR	NCR
05	DAE	SPEAG DAE4	771	January 11, 2019	One year
06	DAE	SPEAG DAE4	777	January 8, 2020	One year
07	Software	DASY5 V5.0 Build 119.9	N/A	NCR	NCR
08	Software	SEMCAD V13.2 Build 87	N/A	NCR	NCR
09	Universal Radio Communication Tester	CMW 500	166370	June 26, 2019	One year

END OF REPORT BODY

©Copyright. All rights reserved by CTTL.

ANNEX A TEST LAYOUT



Picture A1: HAC T-Coil System Layout

©Copyright. All rights reserved by CTTL.

ANNEX B TEST PLOTS

T-Coil GSM 850 Transverse
Date: 2019-10-7
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -4.64 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, -2.1, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm,

dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 32.96 dB
ABM1 comp = -9.98 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5, 8.7, 3.7 mm



0 dB = 0.5860 A/m = -4.64 dBA/m

Fig B.1 T-Coil GSM 850

©Copyright. All rights reserved by CTTL.

T-Coil GSM 850 Perpendicular
Date: 2019-10-7
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 3.72 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, 4.6, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 27.20 dB
ABM1 comp = 1.93 dBA/m
BWC Factor = 0.16 dB
Location: 4.6, 5.4, 3.7 mm

©Copyright. All rights reserved by CTTL.



0 dB = 1.534 A/m = 3.72 dBA/m

Fig B.2 T-Coil GSM 850

©Copyright. All rights reserved by CTTL.

T-Coil GSM 1900 Transverse
Date: 2019-10-7
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -4.19 dBA/m
BWC Factor = 0.16 dB
Location: 7.9, -0.8, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 36.79 dB
ABM1 comp = -9.71 dBA/m
BWC Factor = 0.16 dB
Location: 0.4, 12.9, 3.7 mm

©Copyright. All rights reserved by CTTL.



0 dB = 0.6170 A/m = -4.19 dBA/m

Fig B.3 T-Coil GSM 1900

©Copyright. All rights reserved by CTTL.

T-Coil GSM 1900 Perpendicular
Date: 2019-10-7
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 FRV1/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 3.34 dBA/m
BWC Factor = 0.16 dB
Location: 7.9, 6.2, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 FRV1/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 32.36 dB
ABM1 comp = 2.00 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 4.2, 7.9, 3.7 mm



0 dB = 1.468 A/m = 3.34 dBA/m

Fig B.4 T-Coil GSM 1900

©Copyright. All rights reserved by CTTL.

T-Coil WCDMA 850 Transverse
Date: 2019-10-7
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WCDMA 850; Frequency: 836.4 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 2/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -4.19 dBA/m
BWC Factor = 0.16 dB
Location: 7.5, -2.1, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 2/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 47.42 dB
ABM1 comp = -5.27 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 4.2, -4.2, 3.7 mm



0 dB = 0.6172 A/m = -4.19 dBA/m

Fig B.5 T-Coil WCDMA 850

©Copyright. All rights reserved by CTTL.

T-Coil WCDMA 850 Perpendicular
Date: 2019-10-7
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WCDMA 850; Frequency: 836.4 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 3.90 dBA/m
BWC Factor = 0.16 dB
Location: 7.5, 5, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 49.24 dB
ABM1 comp = 3.32 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5.4, 5.4, 3.7 mm



0 dB = 1.567 A/m = 3.90 dBA/m

Fig B.6 T-Coil WCDMA 850

©Copyright. All rights reserved by CTTL.

T-Coil WCDMA 1900 Transverse
Date: 2019-10-7
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -4.00 dBA/m
BWC Factor = 0.16 dB
Location: 7.9, -0.4, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 49.77 dB
ABM1 comp = -4.42 dBA/m
BWC Factor = 0.16 dB
Location: 6.3, -1.7, 3.7 mm

©Copyright. All rights reserved by CTTL.



0 dB = 0.6310 A/m = -4.00 dBA/m

Fig B.7 T-Coil WCDMA 1900

©Copyright. All rights reserved by CTTL.

T-Coil WCDMA 1900 Perpendicular
Date: 2019-10-7
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 12.2kbps/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 3.86 dBA/m
BWC Factor = 0.16 dB
Location: 7.5, 5, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 12.2kbps/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 49.51 dB
ABM1 comp = 3.33 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5.4, 5, 3.7 mm



0 dB = 1.560 A/m = 3.86 dBA/m

Fig B.8 T-Coil WCDMA 1900

©Copyright. All rights reserved by CTTL.

T-Coil WCDMA 1700 Transverse
Date: 2019-10-7
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WCDMA 1700; Frequency: 1732.4 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -4.26 dBA/m
BWC Factor = 0.16 dB
Location: 7.5, -1.7, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 48.05 dB
ABM1 comp = -4.54 dBA/m
BWC Factor = 0.16 dB
Location: 5.8, -2.9, 3.7 mm

©Copyright. All rights reserved by CTTL.



0 dB = 0.6126 A/m = -4.26 dBA/m

Fig B.9 T-Coil WCDMA 1700

©Copyright. All rights reserved by CTTL.

T-Coil WCDMA 1700 Perpendicular
Date: 2019-10-7
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WCDMA 1700; Frequency: 1732.4 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 3.86 dBA/m
BWC Factor = 0.16 dB
Location: 7.5, 5, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 49.37 dB
ABM1 comp = 3.32 dBA/m
BWC Factor = 0.16 dB
Location: 5.4, 5.4, 3.7 mm

©Copyright. All rights reserved by CTTL.



0 dB = 1.559 A/m = 3.86 dBA/m

Fig B.10 T-Coil WCDMA 1700

©Copyright. All rights reserved by CTTL.

T-Coil CDMA BC0 Transverse
Date: 2019-10-8
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: CDMA BC0; Frequency: 836.52 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 2/y (transversal) 4.2mm 50 x 50/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -7.75 dBA/m
BWC Factor = 0.16 dB
Location: 4.6, -2.1, 3.7 mm

T-Coil/General Scans 2/y (transversal) 4.2mm 50 x 50/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 44.67 dB
ABM1 comp = -7.83 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 4.6, -2.9, 3.7 mm



0 dB = 0.4096 A/m = -7.75 dBA/m

Fig B.11 T-Coil CDMA BC0

©Copyright. All rights reserved by CTTL.

T-Coil CDMA BC0 Perpendicular
Date: 2019-10-8
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: CDMA BC0; Frequency:836.52 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 2/z (axial) 4.2mm 50 x 50RC3 S033/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 1.21 dBA/m
BWC Factor = 0.16 dB
Location: 7.9, 7.5, 3.7 mm

T-Coil/General Scans 2/z (axial) 4.2mm 50 x 50RC3 S033/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 45.76 dB
ABM1 comp = 0.88 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 6.7, 7.5, 3.7 mm



0 dB = 1.150 A/m = 1.21 dBA/m

Fig B.12 T-Coil CDMA BC0

©Copyright. All rights reserved by CTTL.

T-Coil CDMA BC1 Transverse
Date: 2019-10-8
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: CDMA BC1; Frequency: 1880 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 2/y (transversal) 4.2mm 50 x 50/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -7.92 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, -2.9, 3.7 mm

T-Coil/General Scans 2/y (transversal) 4.2mm 50 x 50/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 46.43 dB

©Copyright. All rights reserved by CTTL.

ABM1 comp = -8.47 dBA/m
BWC Factor = 0.16 dB
Location: 5.4, -3.8, 3.7 mm



0 dB = 0.4017 A/m = -7.92 dBA/m

Fig B.13 T-Coil CDMA BC1

©Copyright. All rights reserved by CTTL.

T-Coil CDMA BC1 Perpendicular
Date: 2019-10-8
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: CDMA BC1; Frequency:1880 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 2/z (axial) 4.2mm 50 x 50 RC3 S01/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 0.47 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, 6.2, 3.7 mm

T-Coil/General Scans 2/z (axial) 4.2mm 50 x 50 RC3 S01/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 46.57 dB
ABM1 comp = -0.49 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5.8, 5, 3.7 mm



0 dB = 1.055 A/m = 0.47 dBA/m

Fig B.14 T-Coil CDMA BC1

©Copyright. All rights reserved by CTTL.

T-Coil CDMA BC10 Transverse
Date: 2019-10-8
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: CDMA BC10; Frequency: 820.5 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 2/y (transversal) 4.2mm 50 x 50/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -8.24 dBA/m
BWC Factor = 0.16 dB
Location: 8.8, 14.2, 3.7 mm

T-Coil/General Scans 2/y (transversal) 4.2mm 50 x 50/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 46.00 dB

©Copyright. All rights reserved by CTTL.

ABM1 comp = -9.62 dBA/m
BWC Factor = 0.16 dB
Location: 7.1, -4.6, 3.7 mm



0 dB = 0.3874 A/m = -8.24 dBA/m

Fig B.15 T-Coil CDMA BC10

©Copyright. All rights reserved by CTTL.

T-Coil CDMA BC10 Perpendicular
Date: 2019-10-8
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: CDMA BC10; Frequency:820.5 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 2/z (axial) 4.2mm 50 x 50/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -0.10 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, 7.1, 3.7 mm

T-Coil/General Scans 2/z (axial) 4.2mm 50 x 50/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 46.63 dB
ABM1 comp = -0.66 dBA/m
BWC Factor = 0.16 dB
Location: 6.7, 7.9, 3.7 mm

©Copyright. All rights reserved by CTTL.



0 dB = 0.9890 A/m = -0.10 dBA/m

Fig B.16 T-Coil CDMA BC10

©Copyright. All rights reserved by CTTL.

T-Coil LTE B7 20M Transverse
Date: 2019-10-9
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B7; Frequency: 2535 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -1.44 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, -0.8, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 51.28 dB
ABM1 comp = -2.25 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5, -2.1, 3.7 mm



0 dB = 0.8475 A/m = -1.44 dBA/m

Fig B.17 T-Coil LTE B7

©Copyright. All rights reserved by CTTL.

T-Coil LTE B7 20M Perpendicular
Date: 2019-10-9
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B7; Frequency: 2535 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 6.39 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, 5.4, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 52.00 dB
ABM1 comp = 5.32 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5, 6.7, 3.7 mm



0 dB = 2.088 A/m = 6.39 dBA/m

Fig B.18 T-Coil LTE B7

©Copyright. All rights reserved by CTTL.

T-Coil LTE B12 3M Transverse
Date: 2019-10-9
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: LTE B12; Frequency: 707.5 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 3M/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -1.29 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, -0.8, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 3M/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 52.63 dB
ABM1 comp = -2.01 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5.4, -2.1, 3.7 mm



0 dB = 0.8618 A/m = -1.29 dBA/m

Fig B.19 T-Coil LTE B12

©Copyright. All rights reserved by CTTL.

T-Coil LTE B12 3M Perpendicular
Date: 2019-10-9
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: LTE B12; Frequency: 707.5 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 3M/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 5.88 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, 6.2, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 3M/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 51.49 dB
ABM1 comp = 4.70 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5.4, 7.5, 3.7 mm



0 dB = 1.968 A/m = 5.88 dBA/m

Fig B.20 T-Coil LTE B12

©Copyright. All rights reserved by CTTL.

T-Coil LTE B25 20M Transverse
Date: 2019-10-10
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: LTE B25; Frequency: 1882.5 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -1.34 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, -1.7, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 51.39 dB
ABM1 comp = -3.39 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 2.5, -1.3, 3.7 mm



0 dB = 0.8570 A/m = -1.34 dBA/m

Fig B.21 T-Coil LTE B25

©Copyright. All rights reserved by CTTL.

T-Coil LTE B25 20M Perpendicular
Date: 2019-10-10
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B25; Frequency: 1882.5 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 5.71 dBA/m
BWC Factor = 0.16 dB
Location: 7.5, 5.8, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 49.23dB
ABM1 comp = 5.24dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5, 7.1, 3.7 mm



0 dB = 1.929 A/m = 5.71 dBA/m

Fig B.22 T-Coil LTE B25

©Copyright. All rights reserved by CTTL.

T-Coil LTE B26 3M Transverse
Date: 2019-10-10
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B26; Frequency: 831.5 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 3M/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -1.58 dBA/m
BWC Factor = 0.16 dB
Location: 7.9, -1.3, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 3M/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 52.74 dB
ABM1 comp = -2.39 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 4.6, -2.5, 3.7 mm



0 dB = 0.8340 A/m = -1.58 dBA/m

Fig B.23 T-Coil LTE B26

©Copyright. All rights reserved by CTTL.

T-Coil LTE B26 3M Perpendicular
Date: 2019-10-10
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B26; Frequency: 831.5 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 3M/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 6.04 dBA/m
BWC Factor = 0.16 dB
Location: 7.1, 7.1, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 3M/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 52.88 dB
ABM1 comp = 5.69 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5, 7.5, 3.7 mm



0 dB = 2.005 A/m = 6.04 dBA/m

Fig B.24 T-Coil LTE B26

©Copyright. All rights reserved by CTTL.

T-Coil LTE B66 20M Transverse
Date: 2019-10-11
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: LTE B66; Frequency: 1745 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -1.54 dBA/m
BWC Factor = 0.16 dB
Location: 6.7, -1.7, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 52.02 dB
ABM1 comp = -2.02 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 4.2, -1.7, 3.7 mm



0 dB = 0.8376 A/m = -1.54 dBA/m

Fig B.25 T-Coil LTE B66

©Copyright. All rights reserved by CTTL.

T-Coil LTE B66 20M Perpendicular
Date: 2019-10-11
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B66; Frequency: 1745 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 6.08 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, 5, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 51.55 dB
ABM1 comp = 4.65 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5, 7.5, 3.7 mm



0 dB = 2.013 A/m = 6.08 dBA/m

Fig B.26 T-Coil LTE B66

©Copyright. All rights reserved by CTTL.

T-Coil LTE B71 20M Transverse
Date: 2019-10-11
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: LTE B71; Frequency: 683 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -1.26 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, -4.2, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 50.74 dB
ABM1 comp = -1.36 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 7.5, -4.6, 3.7 mm



0 dB = 0.8651 A/m = -1.26 dBA/m

Fig B.27 T-Coil LTE B71

©Copyright. All rights reserved by CTTL.

T-Coil LTE B71 20M Perpendicular
Date: 2019-10-11
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B71; Frequency: 683 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 6.62 dBA/m
BWC Factor = 0.16 dB
Location: 7.9, 4.2, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 51.46 dB
ABM1 comp = 5.93 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5.4, 4.2, 3.7 mm



0 dB = 2.142 A/m = 6.62 dBA/m

Fig B.28 T-Coil LTE B71

©Copyright. All rights reserved by CTTL.

T-Coil LTE B41 20M Transverse Power Class 2
Date: 2019-10-12
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B41; Frequency: 2593 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 1RB_MIddle(QPSK)/y (transversal) 4.2mm 50 x 50 h-3/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -1.59 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, -0.8, 3.7 mm

T-Coil/General Scans 1RB_MIddle(QPSK)/y (transversal) 4.2mm 50 x 50 h-3/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 43.55 dB
ABM1 comp = -3.98 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 4.2, 12.9, 3.7 mm



0 dB = 0.8330 A/m = -1.59 dBA/m

Fig B.29 T-Coil LTE B41

©Copyright. All rights reserved by CTTL.

T-Coil LTE B41 20M Perpendicular Power Class 2
Date: 2019-10-12
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B41; Frequency: 2593 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 1RB_MIddle(QPSK)/z (axial) 4.2mm 50 x 50 h-3/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 6.31 dBA/m
BWC Factor = 0.16 dB
Location: 7.5, 6.7, 3.7 mm

T-Coil/General Scans 1RB_MIddle(QPSK)/z (axial) 4.2mm 50 x 50 h-3/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 38.28 dB

©Copyright. All rights reserved by CTTL.

ABM1 comp = 5.39 dBA/m
BWC Factor = 0.16 dB
Location: 4.2, 6.2, 3.7 mm



0 dB = 2.068 A/m = 6.31 dBA/m

Fig B.30 T-Coil LTE B41

©Copyright. All rights reserved by CTTL.

T-Coil LTE B41 20M Transverse Power Class 3
Date: 2019-10-12
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B41; Frequency: 2593 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 1RB_MIddle(QPSK)/y (transversal) 4.2mm 50 x 50 n-5/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -1.78 dBA/m
BWC Factor = 0.16 dB
Location: 6.3, -1.3, 3.7 mm

T-Coil/General Scans 1RB_MIddle(QPSK)/y (transversal) 4.2mm 50 x 50 n-5/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 44.98 dB
ABM1 comp = -3.36 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 4.2, 13.3, 3.7 mm



0 dB = 0.8149 A/m = -1.78 dBA/m

Fig B.31 T-Coil LTE B41

©Copyright. All rights reserved by CTTL.

T-Coil LTE B41 20M Perpendicular Power Class 3
Date: 2019-10-12
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B41; Frequency: 2593 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 1RB_MIddle(QPSK)/z (axial) 4.2mm 50 x 50 N-6/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 6.29 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, 7.1, 3.7 mm

T-Coil/General Scans 1RB_MIddle(QPSK)/z (axial) 4.2mm 50 x 50 N-6/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 37.16 dB

©Copyright. All rights reserved by CTTL.

ABM1 comp = 4.48 dBA/m
BWC Factor = 0.16 dB
Location: 4.6, 7.9, 3.7 mm



0 dB = 2.062 A/m = 6.29 dBA/m

Fig B.32 T-Coil LTE B41

©Copyright. All rights reserved by CTTL.

T-Coil LTE B48 20M Transverse
Date: 2019-10-12
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: LTE B48; Frequency: 3625 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -0.65 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, 16.7, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 45.39 dB
ABM1 comp = -1.96 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 7.5, 3.7, 3.7 mm



0 dB = 0.9278 A/m = -0.65 dBA/m

Fig B.33 T-Coil LTE B48

©Copyright. All rights reserved by CTTL.

T-Coil LTE B48 20M Perpendicular
Date: 2019-10-12
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B48; Frequency: 3625 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 7.48 dBA/m
BWC Factor = 0.16 dB
Location: 7.9, 7.5, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 45.34 dB
ABM1 comp = 5.96 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 4.6, 8.3, 3.7 mm



0 dB = 2.366 A/m = 7.48 dBA/m

Fig B.34 T-Coil LTE B48

©Copyright. All rights reserved by CTTL.

T-Coil WiFi-2.4G 11n Transverse
Date: 2019-10-13
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WiFi-2.4G; Frequency: 2437 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 11n MCS4/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = -2.57 dBA/m
BWC Factor = 0.16 dB
Location: 8.8, 0, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 11n MCS4/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 46.07 dB
ABM1 comp = -6.94 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 0, 0, 3.7 mm



0 dB = 0.7436 A/m = -2.57 dBA/m

Fig B.35 T-Coil WiFi-2.4G

©Copyright. All rights reserved by CTTL.

T-Coil WiFi-2.4G 11n Perpendicular
Date: 2019-10-13
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WiFi-2.4G; Frequency: 2437 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 MCS4/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 3.64 dBA/m
BWC Factor = 0.16 dB
Location: 12.1, 4.2, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 MCS4/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 46.13 dB
ABM1 comp = 3.00 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 8.3, 8.3, 3.7 mm



0 dB = 1.520 A/m = 3.64 dBA/m

Fig B.36 T-Coil WiFi-2.4G

©Copyright. All rights reserved by CTTL.

T-Coil WiFi-5G 11n Transverse
Date: 2019-10-14
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WiFi-5G; Frequency: 5220 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 11n MCS4/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 1.16 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, -0.4, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 11n MCS4/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 44.87 dB
ABM1 comp = -3.30 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 4.2, -5, 3.7 mm



0 dB = 1.143 A/m = 1.16 dBA/m

Fig B.37 T-Coil WiFi-5G

©Copyright. All rights reserved by CTTL.

T-Coil WiFi-5G 11ac Perpendicular
Date: 2019-10-14
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WiFi-5G; Frequency: 5310 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 MCS0/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 5.49 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, 5, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 MCS0/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 47.53 dB
ABM1 comp = 3.20 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 5, 8.3, 3.7 mm



0 dB = 1.881 A/m = 5.49 dBA/m

Fig B.38 T-Coil WiFi-5G

©Copyright. All rights reserved by CTTL.

T-Coil EDGE 1900 Transverse – OTT VoIP
Date: 2019-10-15
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.67
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 2/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 5.32 dBA/m
BWC Factor = 0.13 dB
Location: 8.8, 17.9, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 2/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 49.52 dB
ABM1 comp = 5.19 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.13 dB
Location: 8.3, 16.7, 3.7 mm



0 dB = 1.85 A/m = 5.32 dBA/m

Fig B.39 T-Coil EDGE 1900

©Copyright. All rights reserved by CTTL.

T-Coil EDGE 1900 Perpendicular – OTT VoIP
Date: 2019-10-15
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.67
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 64k/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 6.58 dBA/m
BWC Factor = 0.13 dB
Location: 4.2, 12.1, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 64k/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 47.56 dB
ABM1 comp = 6.51 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.13 dB
Location: 0, 9.6, 3.7 mm



0 dB = 2.13 A/m = 6.58 dBA/m

Fig B.40 T-Coil EDGE 1900

©Copyright. All rights reserved by CTTL.

T-Coil WCDMA 1900 Transverse - OTT VoIP
Date: 2019-10-15
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 11.04 dBA/m
BWC Factor = 0.13 dB
Location: 8.8, 17.1, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 50.27 dB
ABM1 comp = 9.29 dBA/m
BWC Factor = 0.13 dB
Location: 7.1, 0.8, 3.7 mm

©Copyright. All rights reserved by CTTL.



0 dB = 3.56 A/m = 11.04 dBA/m

Fig B.41 T-Coil WCDMA 1900

©Copyright. All rights reserved by CTTL.

T-Coil WCDMA 850 Perpendicular – OTT VoIP
Date: 2019-10-15
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WCDMA 850; Frequency: 836.4 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50/ABM Interpolated

Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 5.59 dBA/m
BWC Factor = 0.13 dB
Location: 8.3, 8.7, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50/ABM Interpolated

SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 50.36 dB
ABM1 comp = 5.06 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.13 dB
Location: 4.2, 4.2, 3.7 mm



0 dB = 1.90 A/m = 5.59 dBA/m

Fig B.42 T-Coil WCDMA 850

©Copyright. All rights reserved by CTTL.

T-Coil LTE B25 20M Transverse – OTT VoIP
Date: 2019-10-16
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: LTE B25; Frequency: 1882.5 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 6.80 dBA/m
BWC Factor = 0.16 dB
Location: 7.1, -0.4, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 20M/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 55.02 dB
ABM1 comp = 5.80 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: 3.3, -0.4, 3.7 mm



0 dB = 2.189 A/m = 6.80 dBA/m

Fig B.43 T-Coil LTE B25

©Copyright. All rights reserved by CTTL.

T-Coil LTE B25 20M Perpendicular － OTT VoIP
Date: 2019-10-16
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B25; Frequency: 1882.5 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M 6Kpbs/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 5.44 dBA/m
BWC Factor = 0.16 dB
Location: 7.9, 7.9, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M 6Kpbs/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 48.60 dB

©Copyright. All rights reserved by CTTL.

ABM1 comp = 3.65 dBA/m
BWC Factor = 0.16 dB
Location: 4.6, 7.1, 3.7 mm



0 dB = 1.870 A/m = 5.44 dBA/m

Fig B.44 T-Coil LTE B25

©Copyright. All rights reserved by CTTL.

T-Coil LTE B41 20M Transverse Power Class 2 – OTT VoIP
Date: 2019-10-17
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: LTE B41; Frequency: 2593 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 h3/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 5.97 dBA/m
BWC Factor = 0.13 dB
Location: 6.7, 14.6, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50 h3/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 49.05 dB
ABM1 comp = 5.43 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.13 dB
Location: 3.8, 12.9, 3.7 mm



0 dB = 1.99 A/m = 5.97 dBA/m

Fig B.45 T-Coil LTE B41

©Copyright. All rights reserved by CTTL.

T-Coil LTE B41 20M Perpendicular Power Class 2 – OTT VoIP
Date: 2019-10-17
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: LTE B41; Frequency: 2593 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M h3/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 5.12 dBA/m
BWC Factor = 0.13 dB
Location: 5, 4.6, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 20M h3/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 37.15
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.13 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 42.79 dB

©Copyright. All rights reserved by CTTL.

ABM1 comp = 4.89 dBA/m
BWC Factor = 0.13 dB
Location: 4.2, 5, 3.7 mm



0 dB = 1.80 A/m = 5.12dBA/m

Fig B.46 T-Coil LTE B41

©Copyright. All rights reserved by CTTL.

T-Coil WiFi-2.4G 11n Transverse - OTT VoIP
Date: 2019-10-18
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: WiFi-2.4G; Frequency: 2437 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 11b ch6/y (transversal) 4.2mm 50 x 50 11n 20M 2/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 8.09 dBA/m
BWC Factor = 0.16 dB
Location: 9.2, -1.3, 3.7 mm

T-Coil/General Scans 11b ch6/y (transversal) 4.2mm 50 x 50 11n 20M 2/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 48.01 dB
ABM1 comp = 1.38 dBA/m

©Copyright. All rights reserved by CTTL.

BWC Factor = 0.16 dB
Location: -0.4, 15, 3.7 mm



0 dB = 2.538 A/m = 8.09 dBA/m

Fig B.47 T-Coil WiFi-2.4G

©Copyright. All rights reserved by CTTL.

T-Coil WiFi-2.4G 11g Perpendicular - OTT VoIP
Date: 2019-10-18
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5°C
Communication System: WiFi-2.4G; Frequency: 2437 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans 11b ch6/z (axial) 4.2mm 50 x 50 11g 6Mbps/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 15.82 dBA/m
BWC Factor = 0.16 dB
Location: 9.2, 7.1, 3.7 mm

T-Coil/General Scans 11b ch6/z (axial) 4.2mm 50 x 50 11g 6Mbps/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 47.89 dB

©Copyright. All rights reserved by CTTL.

ABM1 comp = 13.92 dBA/m
BWC Factor = 0.16 dB
Location: 9.6, 11.2, 3.7 mm



0 dB = 6.180 A/m = 15.82 dBA/m

Fig B.48 T-Coil WiFi-2.4G

©Copyright. All rights reserved by CTTL.

T-Coil WiFi-5G 11ac Transverse
Date: 2019-10-19
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WiFi-5G; Frequency: 5220 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 7.28 dBA/m
BWC Factor = 0.16 dB
Location: 8.3, 1.7, 3.7 mm

T-Coil/General Scans/y (transversal) 4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 53.22 dB
ABM1 comp = 5.87 dBA/m
BWC Factor = 0.16 dB
Location: 4.6, 17.5, 3.7 mm

©Copyright. All rights reserved by CTTL.



0 dB = 2.311 A/m = 7.28 dBA/m

Fig B.49 T-Coil WiFi-5G

©Copyright. All rights reserved by CTTL.

T-Coil WiFi-5G 11a Perpendicular
Date: 2019-10-19
Electronics: DAE4 Sn771
Medium: Air
Medium parameters used: $\sigma = 0$ mho/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature:22.5ºC
Communication System: WiFi-5G; Frequency: 5220 MHz; Duty Cycle: 1:1
Probe: AM1DV2 - 1064;

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 11a20m/ABM

Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1 = 11.58 dBA/m
BWC Factor = 0.16 dB
Location: 7.9, 7.1, 3.7 mm

T-Coil/General Scans/z (axial) 4.2mm 50 x 50 11a20m/ABM

Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 100
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 54.01 dB

©Copyright. All rights reserved by CTTL.

ABM1 comp = 11.05 dBA/m
BWC Factor = 0.16 dB
Location: 4.6, 8.3, 3.7 mm



0 dB = 3.793 A/m = 11.58 dBA/m

Fig B.50 T-Coil WiFi-5G

©Copyright. All rights reserved by CTTL.

ANNEX C FREQUENCY REPONSE CURVES



Figure C.1 Frequency Response of GSM 850



Figure C.2 Frequency Response of GSM 1900



Figure C.3 Frequency Response of WCDMA 850

©Copyright. All rights reserved by CTTL.



Figure C.4 Frequency Response of WCDMA 1900



Figure C.5 Frequency Response of WCDMA 1700



Figure C.6 Frequency Response of CDMA BC0

©Copyright. All rights reserved by CTTL.



Figure C.7 Frequency Response of CDMA BC1



Figure C.8 Frequency Response of CDMA BC10



Figure C.9 Frequency Response of LTE B7

©Copyright. All rights reserved by CTTL.



Figure C.10 Frequency Response of LTE B12



Figure C.11 Frequency Response of LTE B25



Figure C.12 Frequency Response of LTE B26

©Copyright. All rights reserved by CTTL.



Figure C.13 Frequency Response of LTE B66



Figure C.14 Frequency Response of LTE B71

Figure C.15 Frequency Response of LTE B41 Power Class 2

©Copyright. All rights reserved by CTTL.



Figure C.16 Frequency Response of LTE B41 Power Class 3



Figure C.17 Frequency Response of LTE B48



Figure C.18 Frequency Response of WiFi-2.4G

©Copyright. All rights reserved by CTTL.



Figure C.19 Frequency Response of WiFi-5G



Figure C.20 Frequency Response of EDGE 1900 - OTT VoIP



Figure C.21 Frequency Response of W850 - OTT VoIP

©Copyright. All rights reserved by CTTL.



Figure C.22 Frequency Response of LTE B25 - OTT VoIP



Figure C.23 Frequency Response of LTE B41 **Power Class 2** - OTT VoIP



Figure C.24 Frequency Response of WiFi-2.4G - OTT VoIP

©Copyright. All rights reserved by CTTL.



Figure C.25 Frequency Response of WiFi-5G - OTT VoIP

©Copyright. All rights reserved by CTTL.