



FCC RF Test Report

APPLICANT : OnePlus Technology (Shenzhen) Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : ONEPLUS, 1+
MODEL NAME : CPH2749
FCC ID : 2ABZ2-OP24865
STANDARD : 47 CFR Part 22, 24
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Jul. 15, 2025 ~ Aug. 27, 2025

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP and Emission Designator	7
1.7 Testing Location	8
1.8 Test Software	8
1.9 Applicable Standards	9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1 Test Mode	10
2.2 Connection Diagram of Test System	12
2.3 Support Unit used in test configuration and system	12
2.4 Measurement Results Explanation Example	13
2.5 Frequency List of Low/Middle/High Channels	13
3 CONDUCTED TEST ITEMS	16
3.1 Measuring Instruments	16
3.2 Test Setup	16
3.3 Test Result of Conducted Test	16
3.4 Conducted Output Power and ERP/EIRP	17
3.5 Peak-to-Average Ratio	18
3.6 Occupied Bandwidth	19
3.7 Conducted Band Edge	20
3.8 Conducted Spurious Emission	21
3.9 Frequency Stability	22
4 RADIATED TEST ITEMS	23
4.1 Measuring Instruments	23
4.2 Test Setup	23
4.3 Test Result of Radiated Test	24
4.4 Radiated Spurious Emission	25
5 LIST OF MEASURING EQUIPMENT	26
6 MEASUREMENT UNCERTAINTY	27
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG561202I	Rev. 01	Initial issue of report	Sep. 01, 2025



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power (5G NR n5, n26)	ERP < 7 Watt		
	§24.232(c)	Equivalent Isotropic Radiated Power (5G NR n2, n25)	EIRP < 2Watt		
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	Conducted Band Edge Measurement (5G NR n5, n26) (5G NR n2, n25)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission (5G NR n5, n26) (5G NR n2, n25)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§24.235		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a)	Radiated Spurious Emission (5G NR n5, n26) (5G NR n2, n25)	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 8.83 dB at 14482.00 MHz

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

OnePlus Technology (Shenzhen) Co., Ltd.

18C02, 18C03, 18C04, and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen, Guangdong, P.R. China.

1.2 Manufacturer

OnePlus Technology (Shenzhen) Co., Ltd.

18C02, 18C03, 18C04, and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen, Guangdong, P.R. China.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	ONEPLUS, 
Model Name	CPH2749
FCC ID	2ABZ2-OP24865
IMEI Code	Conducted : 867621080022994/867621080022986 Radiation : 867621080023190/867621080023182
HW Version	11
SW Version	OxygenOS 16.0
EUT Stage	Production Unit

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	5G NR n2 : 1850 MHz ~ 1910 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n25 : 1850 MHz ~ 1915 MHz 5G NR n26 : 824 MHz ~ 849 MHz
Rx Frequency	5G NR n2 : 1930 MHz ~ 1990 MHz 5G NR n5 : 869 MHz ~ 894 MHz 5G NR n25 : 1930 MHz ~ 1995 MHz 5G NR n26 : 869 MHz ~ 894 MHz
Bandwidth	n2, n25 : 5MHz / 10MHz / 15MHz / 20MHz / 25MHz / 30MHz / 35MHz / 40MHz n5, n26 : 5MHz / 10MHz / 15MHz / 20MHz
SCS	15kHz
Antenna Gain	<Ant. 0>: n2: 2.0 dBi n5: -2.0 dBi n25: 2.0 dBi n26: -2.0 dBi <Ant. 1>: n5: -4.4 dBi n26: -4.4 dBi <Ant. 5>: n2: -0.5 dBi n25: -0.5 dBi <Ant. 6>: n2: -2.0 dBi n25: -2.0 dBi <Ant. 7>: n2: 0.5 dBi n25: 0.5 dBi
Type of Modulation	CP-OFDM: QPSK / 16QAM / 64QAM / 256QAM DFT-s-OFDM: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM

Remark:

1. The maximum ERP/EIRP is calculated from max output power and max antenna gain, only the maximum ERP/EIRP are shown in the report, 5G NR n2/n5/n25/n26 for Ant.0.
2. 5G NR support SA (n2/n5/n25/n26) mode and NSA(n2/n5/n25) mode. According to the maximum power between SA and NSA mode, SA covers NSA mode for (n2/n5/n25).
3. The device supports two PAs for 5G NR n2/n25 (main PA for Ant.6/7 and other PA for Ant.0/5) , both the PAs are full tested, only the worst EIRP are shown in the report.
4. For conducted test items, only the test data of Ant.5 for n25(other PA), Ant.6 for n2/n25 and Ant.1 for n26(covers n5) are shown in the report according to the maximum conducted power.
5. The EN-DC mode combination could be referred to the product spec.
6. All the supported ENDC combinations are verified conducted power, only the ENDC combination with highest power are shown in the report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP and Emission Designator

5G NR n2		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	1852.5 ~ 1907.5	0.4159	4M48G7D	0.3556	4M50W7D
10	1855.0 ~ 1905.0	0.4276	9M30G7D	0.3508	9M30W7D
15	1857.5 ~ 1902.5	0.4256	14M1G7D	0.3475	14M1W7D
20	1860.0 ~ 1900.0	0.4121	18M9G7D	0.3540	19M0W7D
25	1862.5 ~ 1897.5	0.4276	23M8G7D	0.3548	23M8W7D
30	1865.0 ~ 1895.0	0.4315	28M6G7D	0.3622	28M6W7D
35	1867.5 ~ 1892.5	0.4295	33M6G7D	0.3499	33M6W7D
40	1870.0 ~ 1890.0	0.4325	38M7G7D	0.3459	38M7W7D

5G NR n25		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	1852.5 ~ 1912.5	0.4295	4M48G7D	0.3573	4M48W7D
10	1855.0 ~ 1910.0	0.4285	9M30G7D	0.3556	9M30W7D
15	1857.5 ~ 1907.5	0.4335	14M1G7D	0.3548	14M1W7D
20	1860.0 ~ 1905.0	0.4285	18M9G7D	0.3556	19M0W7D
25	1862.5 ~ 1902.5	0.4335	23M8G7D	0.3639	23M8W7D
30	1865.0 ~ 1900.0	0.4345	28M6G7D	0.3606	28M6W7D
35	1867.5 ~ 1897.5	0.4285	33M6G7D	0.3639	33M6W7D
40	1870.0 ~ 1895.0	0.4355	38M7G7D	0.3540	38M7W7D

5G NR n5		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
5	826.5 ~ 846.5	0.1042	4M46G7D	0.0845	4M49W7D
10	829.0 ~ 844.0	0.1038	9M27G7D	0.0818	9M29W7D
15	831.5 ~ 841.5	0.1038	14M1G7D	0.0826	14M1W7D
20	834.0 ~ 839.0	0.1052	18M9G7D	0.0836	18M9W7D



5G NR n26		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
5	826.5 ~ 846.5	0.1054	4M46G7D	0.0830	4M49W7D
10	829.0 ~ 844.0	0.1047	9M27G7D	0.0820	9M29W7D
15	831.5 ~ 841.5	0.1045	14M1G7D	0.0836	14M1W7D
20	834.0 ~ 839.0	0.1072	18M9G7D	0.0841	18M9W7D

Note:

1. 5G NR n26 overlaps the entire frequency range of 5G NR n5. Therefore, the test results provided in this report covers 5G NR n5 and the portion of 5G NR n26 subject to Part 22.
2. 5G NR n25 overlaps the entire frequency range of 5G NR n2. Therefore, the test results provided in this report covers 5G NR n25 as well as 5G NR n2 for other PA, and n2 main PA was full tested..
3. All modulations have been tested, only the worst test results of PSK & QAM are shown in the report.

1.7 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ 03CH02-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a



1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 22, 24
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

All test items were verified and recorded according to the standards and without any deviation during the test.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.


Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			

Test Items	5G NR	Bandwidth (MHz)														Modulation					RB #		Test Channel		
		5	10	15	20	25	30	35	40	60	70	80	90	100	PI/2 BPSK	QPSK	16 QAM	64 QAM	256 QAM	1	Full	L	M	H	
Max. Output Power	n2	v	v	v	v	v	v	v	v	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v	
	n5	v	v	v	v	-	-	-	-	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v	
	n25	v	v	v	v	v	v	v	v	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v	
	n26	v	v	v	v	-	-	-	-	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v	
Peak-to-Average Ratio	n2				v					-	-	-	-	-	v	v					v		v		
	n25				v					-	-	-	-	-	v	v					v		v		
	n26				v	-	-	-	-	-	-	-	-	-	v	v					v		v		
26dB and 99% Bandwidth	n2	v	v	v	v	v	v	v	v	-	-	-	-	-		v	v	v	v		v		v		
	n25	v	v	v	v	v	v	v	v	-	-	-	-	-		v	v	v	v		v		v		
	n26	v	v	v	v	-	-	-	-	-	-	-	-	-		v	v	v	v		v		v		
Conducted Band Edge	n2	v			v				v	-	-	-	-	-	v	v				v	v	v		v	
	n25	v			v				v	-	-	-	-	-	v	v				v	v	v		v	
	n26	v	v		v	-	-	-	-	-	-	-	-	-	v	v				v	v	v		v	
Conducted Spurious Emission	n2	v			v				v	-	-	-	-	-	v	v				v		v	v	v	
	n25	v			v				v	-	-	-	-	-	v	v				v		v	v	v	
	n26	v	v		v	-	-	-	-	-	-	-	-	-	v	v				v		v	v	v	
Frequency	n2				v					-	-	-	-	-		v					v		v		



Test Items	5G NR	Bandwidth (MHz)													Modulation					RB #		Test Channel		
		5	10	15	20	25	30	35	40	60	70	80	90	100	PI/2 BPSK	QPSK	16 QAM	64 QAM	256 QAM	1	Full	L	M	H
Stability	n25				v					-	-	-	-	-		v					v		v	
	n26				v	-	-	-	-	-	-	-	-	-		v					v		v	
E.R.P / E.I.R.P	n2	v	v	v	v	v	v	v	v	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v
	n5	v	v	v	v	-	-	-	-	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v
	n25	v	v	v	v	v	v	v	v	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v
	n26	v	v	v	v	-	-	-	-	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v
Radiated Spurious Emission	n2	Worst Case																				v	v	v
	n5	Worst Case																				v	v	v
	n25	Worst Case																				v	v	v
	n26	Worst Case																				v	v	v
Note	1. The mark “v ” means that this configuration is chosen for testing 2. The mark “- ” means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. Frequency Stability : Normal Voltage = 8.0V ; Low Voltage =7.2V. ; High Voltage =9.0V																							

2.2 Connection Diagram of Test System



The EUT has been configuration operated in a manner tended to maximize its emission characteristics in a typical application.

2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
3.	NR Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 7.5 dB.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 7.5 \text{ (dB)} \end{aligned}$$

2.5 Frequency List of Low/Middle/High Channels

5G NR n2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
40	Channel	374000	376000	378000
	Frequency	1870	1880	1890
35	Channel	373500	376000	378500
	Frequency	1867.5	1880	1892.5
30	Channel	373000	376000	379000
	Frequency	1865	1880	1895
25	Channel	372500	376000	379500
	Frequency	1862.5	1880	1897.5
20	Channel	372000	376000	380000
	Frequency	1860	1880	1900
15	Channel	371500	376000	380500
	Frequency	1857.5	1880	1902.5
10	Channel	371000	376000	381000
	Frequency	1855	1880	1905
5	Channel	370500	376000	381500
	Frequency	1852.5	1880	1907.5



5G NR n5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	166800	167300	167800
	Frequency	834	836.5	839
15	Channel	166300	167300	168300
	Frequency	831.5	836.5	841.5
10	Channel	165800	167300	168800
	Frequency	829	836.5	844
5	Channel	165300	167300	169300
	Frequency	826.5	836.5	846.5

5G NR n25 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
40	Channel	390000	392500	395000
	Frequency	1870	1882.5	1895
35	Channel	373500	376500	379500
	Frequency	1867.5	1882.5	1897.5
30	Channel	389000	392500	396000
	Frequency	1865	1882.5	1900
25	Channel	388500	392500	396500
	Frequency	1862.5	1882.5	1902.5
20	Channel	372000	376500	381000
	Frequency	1860	1882.5	1905
15	Channel	371500	376500	381500
	Frequency	1857.5	1882.5	1907.5
10	Channel	371000	376500	382000
	Frequency	1855	1882.5	1910
5	Channel	370500	376500	382500
	Frequency	1852.5	1882.5	1912.5



5G NR n26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	166800	167300	167800
	Frequency	834	836.5	839
15	Channel	166300	167300	168300
	Frequency	831.5	836.5	841.5
10	Channel	165800	167300	168800
	Frequency	829	836.5	844
5	Channel	165300	167300	169300
	Frequency	826.5	836.5	846.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for 5G NR n5, n26.

The EIRP of mobile transmitters must not exceed 2 Watts for 5G NR n2, n25.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used (generally limited to no less than 1% of the OBW) and the measured power was integrated over the full required measurement bandwidth.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)\text{dB}$ below the transmitter power $P(\text{Watts})$

$$= P(\text{W}) - [43 + 10\log(P)] (\text{dB})$$

$$= [30 + 10\log(P)] (\text{dBm}) - [43 + 10\log(P)] (\text{dB}) = -13\text{dBm}.$$

9. When using the integration method, the starting frequency of the integration shall be centered at one-half of the RBW away from the band edge.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and power divider.
The path loss was compensated to the results for each measurement.
Path Loss Factor = Cable + Power Divider, Where the cable and power divider are the total path loss for the system calibration.
4. The low/middle/high channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13$ dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$= P(W) - [43 + 10\log(P)] \text{ (dB)}$

$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$

$= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 02, 2025	Jul. 15, 2025~ Aug. 27, 2025	Apr. 01, 2026	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V, 3A	Oct.14,2024	Jul. 15, 2025~ Aug. 27, 2025	Oct. 13, 2025	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 24, 2024	Jul. 15, 2025~ Aug. 27, 2025	Dec. 23, 2025	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 02, 2025	Jul. 15, 2025~ Aug. 27, 2025	Jul. 01, 2026	Conducted (TH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2025	Aug. 15, 2025	Jul. 02, 2026	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Aug. 15, 2025	Dec. 27, 2025	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Oct. 24, 2023	Aug. 15, 2025	Oct. 23, 2025	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2025	Aug. 15, 2025	Jul. 04, 2026	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 03, 2025	Aug. 15, 2025	Jul. 03, 2026	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Apr. 03, 2025	Aug. 15, 2025	Apr. 02, 2027	Radiation (03CH02-SZ)
LF Amplifier	EM Electronics	EM330	060788	20MHz~3GHz	Dec. 25, 2024	Aug. 15, 2025	Dec. 24, 2025	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 14, 2024	Aug. 15, 2025	Oct. 13, 2025	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010003043	N/A	Oct. 18, 2024	Aug. 15, 2025	Oct. 17, 2025	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Aug. 15, 2025	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Aug. 15, 2025	NCR	Radiation (03CH02-SZ)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	± 1.34 dB
Occupied Channel Bandwidth	± 0.012 MHz
Conducted Power	± 1.34 dB
Peak to Average Ratio	± 1.34 dB
Frequency Stability	± 1.3 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.47 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.31 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.72 dB
---	---------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Khan Zhen	Temperature :	22~23°C
		Relative Humidity :	40~42%



FR1 N2 ANT0 - other PA

Transmitter Conducted Output Power And EIRP, ($G_T - L_C$)=2dB

NR Band	SCS	Band Width	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP(W)
2	15	5	370500	1852.5	DFT-s-OFDM QPSK	12@6	24.11	26.11	0.4083
2	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@1	24	26	0.3981
2	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@23	24.09	26.09	0.4064
2	15	5	370500	1852.5	DFT-s-OFDM 16 QAM	12@6	22.88	24.88	0.3076
2	15	5	370500	1852.5	DFT-s-OFDM 16 QAM	1@1	23.43	25.43	0.3491
2	15	5	370500	1852.5	DFT-s-OFDM 16 QAM	1@23	23.16	25.16	0.3281
2	15	5	376000	1880	DFT-s-OFDM QPSK	12@6	24.16	26.16	0.4130
2	15	5	376000	1880	DFT-s-OFDM QPSK	1@1	24.09	26.09	0.4064
2	15	5	376000	1880	DFT-s-OFDM QPSK	1@23	23.96	25.96	0.3945
2	15	5	376000	1880	DFT-s-OFDM 16 QAM	12@6	23.06	25.06	0.3206
2	15	5	376000	1880	DFT-s-OFDM 16 QAM	1@1	23.37	25.37	0.3443
2	15	5	376000	1880	DFT-s-OFDM 16 QAM	1@23	23.25	25.25	0.3350
2	15	5	381500	1907.5	DFT-s-OFDM QPSK	12@6	24.19	26.19	0.4159
2	15	5	381500	1907.5	DFT-s-OFDM QPSK	1@1	24.13	26.13	0.4102
2	15	5	381500	1907.5	DFT-s-OFDM QPSK	1@23	24	26	0.3981
2	15	5	381500	1907.5	DFT-s-OFDM 16 QAM	12@6	23.04	25.04	0.3192
2	15	5	381500	1907.5	DFT-s-OFDM 16 QAM	1@1	23.51	25.51	0.3556
2	15	5	381500	1907.5	DFT-s-OFDM 16 QAM	1@23	23.29	25.29	0.3381
2	15	10	371000	1855	DFT-s-OFDM QPSK	25@12	24.16	26.16	0.4130
2	15	10	371000	1855	DFT-s-OFDM QPSK	1@1	24.08	26.08	0.4055
2	15	10	371000	1855	DFT-s-OFDM QPSK	1@50	24.08	26.08	0.4055
2	15	10	371000	1855	DFT-s-OFDM 16 QAM	25@12	23.23	25.23	0.3334
2	15	10	371000	1855	DFT-s-OFDM 16 QAM	1@1	23.18	25.18	0.3296
2	15	10	371000	1855	DFT-s-OFDM 16 QAM	1@50	23.26	25.26	0.3357
2	15	10	376000	1880	DFT-s-OFDM QPSK	25@12	24.12	26.12	0.4093
2	15	10	376000	1880	DFT-s-OFDM QPSK	1@1	24.1	26.1	0.4074
2	15	10	376000	1880	DFT-s-OFDM QPSK	1@50	23.95	25.95	0.3936
2	15	10	376000	1880	DFT-s-OFDM 16 QAM	25@12	23.28	25.28	0.3373
2	15	10	376000	1880	DFT-s-OFDM 16 QAM	1@1	23.29	25.29	0.3381
2	15	10	376000	1880	DFT-s-OFDM 16 QAM	1@50	23.33	25.33	0.3412
2	15	10	381000	1905	DFT-s-OFDM QPSK	25@12	24.31	26.31	0.4276
2	15	10	381000	1905	DFT-s-OFDM QPSK	1@1	24.07	26.07	0.4046



2	15	10	381000	1905	DFT-s-OFDM QPSK	1@50	24.24	26.24	0.4207
2	15	10	381000	1905	DFT-s-OFDM 16 QAM	25@12	23.31	25.31	0.3396
2	15	10	381000	1905	DFT-s-OFDM 16 QAM	1@1	23.45	25.45	0.3508
2	15	10	381000	1905	DFT-s-OFDM 16 QAM	1@50	23.11	25.11	0.3243
2	15	15	371500	1857.5	DFT-s-OFDM QPSK	36@18	24.24	26.24	0.4207
2	15	15	371500	1857.5	DFT-s-OFDM QPSK	1@1	24.25	26.25	0.4217
2	15	15	371500	1857.5	DFT-s-OFDM QPSK	1@77	23.93	25.93	0.3917
2	15	15	371500	1857.5	DFT-s-OFDM 16 QAM	36@18	23.15	25.15	0.3273
2	15	15	371500	1857.5	DFT-s-OFDM 16 QAM	1@1	23.35	25.35	0.3428
2	15	15	371500	1857.5	DFT-s-OFDM 16 QAM	1@77	23.39	25.39	0.3459
2	15	15	376000	1880	DFT-s-OFDM QPSK	36@18	24.29	26.29	0.4256
2	15	15	376000	1880	DFT-s-OFDM QPSK	1@1	24.21	26.21	0.4178
2	15	15	376000	1880	DFT-s-OFDM QPSK	1@77	24.1	26.1	0.4074
2	15	15	376000	1880	DFT-s-OFDM 16 QAM	36@18	23.2	25.2	0.3311
2	15	15	376000	1880	DFT-s-OFDM 16 QAM	1@1	23.41	25.41	0.3475
2	15	15	376000	1880	DFT-s-OFDM 16 QAM	1@77	23.37	25.37	0.3443
2	15	15	380500	1902.5	DFT-s-OFDM QPSK	36@18	24.08	26.08	0.4055
2	15	15	380500	1902.5	DFT-s-OFDM QPSK	1@1	24.02	26.02	0.3999
2	15	15	380500	1902.5	DFT-s-OFDM QPSK	1@77	24.03	26.03	0.4009
2	15	15	380500	1902.5	DFT-s-OFDM 16 QAM	36@18	23.14	25.14	0.3266
2	15	15	380500	1902.5	DFT-s-OFDM 16 QAM	1@1	23.37	25.37	0.3443
2	15	15	380500	1902.5	DFT-s-OFDM 16 QAM	1@77	23.12	25.12	0.3251
2	15	20	372000	1860	DFT-s-OFDM QPSK	50@25	24.12	26.12	0.4093
2	15	20	372000	1860	DFT-s-OFDM QPSK	1@1	24.04	26.04	0.4018
2	15	20	372000	1860	DFT-s-OFDM QPSK	1@104	23.83	25.83	0.3828
2	15	20	372000	1860	DFT-s-OFDM 16 QAM	50@25	23.14	25.14	0.3266
2	15	20	372000	1860	DFT-s-OFDM 16 QAM	1@1	23.4	25.4	0.3467
2	15	20	372000	1860	DFT-s-OFDM 16 QAM	1@104	23.27	25.27	0.3365
2	15	20	376000	1880	DFT-s-OFDM QPSK	50@25	23.98	25.98	0.3963
2	15	20	376000	1880	DFT-s-OFDM QPSK	1@1	24.06	26.06	0.4036
2	15	20	376000	1880	DFT-s-OFDM QPSK	1@104	23.89	25.89	0.3882
2	15	20	376000	1880	DFT-s-OFDM 16 QAM	50@25	23.22	25.22	0.3327
2	15	20	376000	1880	DFT-s-OFDM 16 QAM	1@1	23.37	25.37	0.3443
2	15	20	376000	1880	DFT-s-OFDM 16 QAM	1@104	23.44	25.44	0.3499
2	15	20	380000	1900	DFT-s-OFDM QPSK	50@25	24.15	26.15	0.4121
2	15	20	380000	1900	DFT-s-OFDM QPSK	1@1	24.02	26.02	0.3999
2	15	20	380000	1900	DFT-s-OFDM QPSK	1@104	24.05	26.05	0.4027
2	15	20	380000	1900	DFT-s-OFDM 16 QAM	50@25	23.24	25.24	0.3342



2	15	20	380000	1900	DFT-s-OFDM 16 QAM	1@1	23.36	25.36	0.3436
2	15	20	380000	1900	DFT-s-OFDM 16 QAM	1@104	23.49	25.49	0.3540
2	15	25	372500	1862.5	DFT-s-OFDM QPSK	64@32	24.26	26.26	0.4227
2	15	25	372500	1862.5	DFT-s-OFDM QPSK	1@1	24.08	26.08	0.4055
2	15	25	372500	1862.5	DFT-s-OFDM QPSK	1@131	24.14	26.14	0.4111
2	15	25	372500	1862.5	DFT-s-OFDM 16 QAM	64@32	23.3	25.3	0.3388
2	15	25	372500	1862.5	DFT-s-OFDM 16 QAM	1@1	23.35	25.35	0.3428
2	15	25	372500	1862.5	DFT-s-OFDM 16 QAM	1@131	23.4	25.4	0.3467
2	15	25	376000	1880	DFT-s-OFDM QPSK	64@32	24.28	26.28	0.4246
2	15	25	376000	1880	DFT-s-OFDM QPSK	1@1	24.3	26.3	0.4266
2	15	25	376000	1880	DFT-s-OFDM QPSK	1@131	24.1	26.1	0.4074
2	15	25	376000	1880	DFT-s-OFDM 16 QAM	64@32	23.21	25.21	0.3319
2	15	25	376000	1880	DFT-s-OFDM 16 QAM	1@1	23.45	25.45	0.3508
2	15	25	376000	1880	DFT-s-OFDM 16 QAM	1@131	23.36	25.36	0.3436
2	15	25	379500	1897.5	DFT-s-OFDM QPSK	64@32	24.26	26.26	0.4227
2	15	25	379500	1897.5	DFT-s-OFDM QPSK	1@1	24.31	26.31	0.4276
2	15	25	379500	1897.5	DFT-s-OFDM QPSK	1@131	24.16	26.16	0.4130
2	15	25	379500	1897.5	DFT-s-OFDM 16 QAM	64@32	23.24	25.24	0.3342
2	15	25	379500	1897.5	DFT-s-OFDM 16 QAM	1@1	23.5	25.5	0.3548
2	15	25	379500	1897.5	DFT-s-OFDM 16 QAM	1@131	23.33	25.33	0.3412
2	15	30	373000	1865	DFT-s-OFDM QPSK	80@40	24.23	26.23	0.4198
2	15	30	373000	1865	DFT-s-OFDM QPSK	1@1	24.1	26.1	0.4074
2	15	30	373000	1865	DFT-s-OFDM QPSK	1@158	24.25	26.25	0.4217
2	15	30	373000	1865	DFT-s-OFDM 16 QAM	80@40	23.36	25.36	0.3436
2	15	30	373000	1865	DFT-s-OFDM 16 QAM	1@1	23.37	25.37	0.3443
2	15	30	373000	1865	DFT-s-OFDM 16 QAM	1@158	23.48	25.48	0.3532
2	15	30	376000	1880	DFT-s-OFDM QPSK	80@40	24.19	26.19	0.4159
2	15	30	376000	1880	DFT-s-OFDM QPSK	1@1	24.25	26.25	0.4217
2	15	30	376000	1880	DFT-s-OFDM QPSK	1@158	24.26	26.26	0.4227
2	15	30	376000	1880	DFT-s-OFDM 16 QAM	80@40	23.16	25.16	0.3281
2	15	30	376000	1880	DFT-s-OFDM 16 QAM	1@1	23.28	25.28	0.3373
2	15	30	376000	1880	DFT-s-OFDM 16 QAM	1@158	23.58	25.58	0.3614
2	15	30	379000	1895	DFT-s-OFDM QPSK	80@40	24.35	26.35	0.4315
2	15	30	379000	1895	DFT-s-OFDM QPSK	1@1	24.27	26.27	0.4236
2	15	30	379000	1895	DFT-s-OFDM QPSK	1@158	24.23	26.23	0.4198
2	15	30	379000	1895	DFT-s-OFDM 16 QAM	80@40	23.28	25.28	0.3373
2	15	30	379000	1895	DFT-s-OFDM 16 QAM	1@1	23.58	25.58	0.3614
2	15	30	379000	1895	DFT-s-OFDM 16 QAM	1@158	23.59	25.59	0.3622



2	15	35	373500	1867.5	DFT-s-OFDM QPSK	90@45	24.33	26.33	0.4295
2	15	35	373500	1867.5	DFT-s-OFDM QPSK	1@1	24.07	26.07	0.4046
2	15	35	373500	1867.5	DFT-s-OFDM QPSK	1@186	24.18	26.18	0.4150
2	15	35	373500	1867.5	DFT-s-OFDM 16 QAM	90@45	23.22	25.22	0.3327
2	15	35	373500	1867.5	DFT-s-OFDM 16 QAM	1@1	23.23	25.23	0.3334
2	15	35	373500	1867.5	DFT-s-OFDM 16 QAM	1@186	23.35	25.35	0.3428
2	15	35	376000	1880	DFT-s-OFDM QPSK	90@45	24.22	26.22	0.4188
2	15	35	376000	1880	DFT-s-OFDM QPSK	1@1	24.07	26.07	0.4046
2	15	35	376000	1880	DFT-s-OFDM QPSK	1@186	24.15	26.15	0.4121
2	15	35	376000	1880	DFT-s-OFDM 16 QAM	90@45	23.29	25.29	0.3381
2	15	35	376000	1880	DFT-s-OFDM 16 QAM	1@1	23.3	25.3	0.3388
2	15	35	376000	1880	DFT-s-OFDM 16 QAM	1@186	23.34	25.34	0.3420
2	15	35	378500	1892.5	DFT-s-OFDM QPSK	90@45	24.29	26.29	0.4256
2	15	35	378500	1892.5	DFT-s-OFDM QPSK	1@1	24.18	26.18	0.4150
2	15	35	378500	1892.5	DFT-s-OFDM QPSK	1@186	23.88	25.88	0.3873
2	15	35	378500	1892.5	DFT-s-OFDM 16 QAM	90@45	23.12	25.12	0.3251
2	15	35	378500	1892.5	DFT-s-OFDM 16 QAM	1@1	23.44	25.44	0.3499
2	15	35	378500	1892.5	DFT-s-OFDM 16 QAM	1@186	23.34	25.34	0.3420
2	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	108@54	22.8	24.8	0.3020
2	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	1@1	22.65	24.65	0.2917
2	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	1@214	22.68	24.68	0.2938
2	15	40	374000	1870	DFT-s-OFDM QPSK	108@54	24.36	26.36	0.4325
2	15	40	374000	1870	DFT-s-OFDM QPSK	1@1	24.02	26.02	0.3999
2	15	40	374000	1870	DFT-s-OFDM QPSK	1@214	24.05	26.05	0.4027
2	15	40	374000	1870	DFT-s-OFDM 16 QAM	108@54	23.19	25.19	0.3304
2	15	40	374000	1870	DFT-s-OFDM 16 QAM	1@1	23.3	25.3	0.3388
2	15	40	374000	1870	DFT-s-OFDM 16 QAM	1@214	23.39	25.39	0.3459
2	15	40	374000	1870	DFT-s-OFDM 64 QAM	108@54	21.72	23.72	0.2355
2	15	40	374000	1870	DFT-s-OFDM 64 QAM	1@1	21.74	23.74	0.2366
2	15	40	374000	1870	DFT-s-OFDM 64 QAM	1@214	21.81	23.81	0.2404
2	15	40	374000	1870	DFT-s-OFDM 256 QAM	108@54	19.81	21.81	0.1517
2	15	40	374000	1870	DFT-s-OFDM 256 QAM	1@1	19.37	21.37	0.1371
2	15	40	374000	1870	DFT-s-OFDM 256 QAM	1@214	19.37	21.37	0.1371
2	15	40	374000	1870	CP-OFDM QPSK	108@54	22.72	24.72	0.2965
2	15	40	374000	1870	CP-OFDM QPSK	1@1	22.79	24.79	0.3013
2	15	40	374000	1870	CP-OFDM QPSK	1@214	22.93	24.93	0.3112
2	15	40	376000	1880	DFT-s-OFDM PI/2 BPSK	108@54	22.9	24.9	0.3090
2	15	40	376000	1880	DFT-s-OFDM PI/2 BPSK	1@1	22.89	24.89	0.3083



2	15	40	376000	1880	DFT-s-OFDM PI/2 BPSK	1@214	22.86	24.86	0.3062
2	15	40	376000	1880	DFT-s-OFDM QPSK	108@54	24.25	26.25	0.4217
2	15	40	376000	1880	DFT-s-OFDM QPSK	1@1	24.02	26.02	0.3999
2	15	40	376000	1880	DFT-s-OFDM QPSK	1@214	24.23	26.23	0.4198
2	15	40	376000	1880	DFT-s-OFDM 16 QAM	108@54	23.25	25.25	0.3350
2	15	40	376000	1880	DFT-s-OFDM 16 QAM	1@1	23.32	25.32	0.3404
2	15	40	376000	1880	DFT-s-OFDM 16 QAM	1@214	23.26	25.26	0.3357
2	15	40	376000	1880	DFT-s-OFDM 64 QAM	108@54	21.7	23.7	0.2344
2	15	40	376000	1880	DFT-s-OFDM 64 QAM	1@1	21.72	23.72	0.2355
2	15	40	376000	1880	DFT-s-OFDM 64 QAM	1@214	21.66	23.66	0.2323
2	15	40	376000	1880	DFT-s-OFDM 256 QAM	108@54	19.6	21.6	0.1445
2	15	40	376000	1880	DFT-s-OFDM 256 QAM	1@1	19.41	21.41	0.1384
2	15	40	376000	1880	DFT-s-OFDM 256 QAM	1@214	19.41	21.41	0.1384
2	15	40	376000	1880	CP-OFDM QPSK	108@54	22.74	24.74	0.2979
2	15	40	376000	1880	CP-OFDM QPSK	1@1	22.92	24.92	0.3105
2	15	40	376000	1880	CP-OFDM QPSK	1@214	22.89	24.89	0.3083
2	15	40	378000	1890	DFT-s-OFDM PI/2 BPSK	108@54	22.89	24.89	0.3083
2	15	40	378000	1890	DFT-s-OFDM PI/2 BPSK	1@1	22.83	24.83	0.3041
2	15	40	378000	1890	DFT-s-OFDM PI/2 BPSK	1@214	22.71	24.71	0.2958
2	15	40	378000	1890	DFT-s-OFDM QPSK	108@54	24.07	26.07	0.4046
2	15	40	378000	1890	DFT-s-OFDM QPSK	1@1	24.25	26.25	0.4217
2	15	40	378000	1890	DFT-s-OFDM QPSK	1@214	24.09	26.09	0.4064
2	15	40	378000	1890	DFT-s-OFDM 16 QAM	108@54	23.23	25.23	0.3334
2	15	40	378000	1890	DFT-s-OFDM 16 QAM	1@1	23.38	25.38	0.3451
2	15	40	378000	1890	DFT-s-OFDM 16 QAM	1@214	23.25	25.25	0.3350
2	15	40	378000	1890	DFT-s-OFDM 64 QAM	108@54	21.68	23.68	0.2333
2	15	40	378000	1890	DFT-s-OFDM 64 QAM	1@1	21.81	23.81	0.2404
2	15	40	378000	1890	DFT-s-OFDM 64 QAM	1@214	21.88	23.88	0.2443
2	15	40	378000	1890	DFT-s-OFDM 256 QAM	108@54	19.67	21.67	0.1469
2	15	40	378000	1890	DFT-s-OFDM 256 QAM	1@1	19.17	21.17	0.1309
2	15	40	378000	1890	DFT-s-OFDM 256 QAM	1@214	19.39	21.39	0.1377
2	15	40	378000	1890	CP-OFDM QPSK	108@54	22.76	24.76	0.2992
2	15	40	378000	1890	CP-OFDM QPSK	1@1	22.88	24.88	0.3076
2	15	40	378000	1890	CP-OFDM QPSK	1@214	22.85	24.85	0.3055



FR1 N2 ANT6 - Main PA

Software Version: 23.06.16

Frequency Stability

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (Hz)	Verdict	Environment
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	18.7	PASS	NV
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	17.7	PASS	LV
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	16.4	PASS	HV
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	19.3	PASS	-30°C
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	15.5	PASS	-20°C
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	19.2	PASS	-10°C
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	10.7	PASS	0°C
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	18.6	PASS	10°C
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	15.3	PASS	20°C
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	8.2	PASS	30°C
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	14.9	PASS	40°C
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	11.2	PASS	50°C



|MAX(Δf)| = 19.3 Hz

Frequency Stability	Frequency (MHz)	Limit Line	Result
$f_L - \text{MAX}(\Delta f) $	1850.773482	$\geq 1850 \text{ MHz}$	PASS
$f_H + \text{MAX}(\Delta f) $	1908.638619	$\leq 1910 \text{ MHz}$	



Peak to Average Ratio

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result (dB)	Limit (dB)	Verdict
2	15	20	376000	1880.0	DFT-s-OFDM PI/2 BPSK	100@0	3.91	13	PASS
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	100@0	4.47	13	PASS

N2(20M)_DFT-s-OFDM_PI_2-
BPSK_Outer_Full_Mid_CHN2(20M)_DFT-s-
OFDM_QPSK_Outer_Full_Mid_CH



Occupied Bandwidth


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	OBW (MHz)	26dB BW (MHz)
2	15	5	376000	1880.0	CP-OFDM QPSK	25@0	4.4782	5.09
2	15	5	376000	1880.0	CP-OFDM 16 QAM	25@0	4.4984	5.119
2	15	5	376000	1880.0	CP-OFDM 64 QAM	25@0	4.4631	4.97
2	15	5	376000	1880.0	CP-OFDM 256 QAM	25@0	4.4827	5.044
2	15	10	376000	1880.0	CP-OFDM QPSK	52@0	9.2862	10.06
2	15	10	376000	1880.0	CP-OFDM 16 QAM	52@0	9.2827	9.939
2	15	10	376000	1880.0	CP-OFDM 64 QAM	52@0	9.2781	9.812
2	15	10	376000	1880.0	CP-OFDM 256 QAM	52@0	9.2885	9.943
2	15	15	376000	1880.0	CP-OFDM QPSK	79@0	14.105	14.91
2	15	15	376000	1880.0	CP-OFDM 16 QAM	79@0	14.081	14.83
2	15	15	376000	1880.0	CP-OFDM 64 QAM	79@0	14.119	14.85
2	15	15	376000	1880.0	CP-OFDM 256 QAM	79@0	14.102	15.05
2	15	20	376000	1880.0	CP-OFDM QPSK	106@0	18.915	19.77
2	15	20	376000	1880.0	CP-OFDM 16 QAM	106@0	18.942	19.77
2	15	20	376000	1880.0	CP-OFDM 64 QAM	106@0	18.91	19.75
2	15	20	376000	1880.0	CP-OFDM 256 QAM	106@0	18.974	19.96
2	15	25	376000	1880.0	CP-OFDM QPSK	133@0	23.734	24.85
2	15	25	376000	1880.0	CP-OFDM 16 QAM	133@0	23.797	24.77
2	15	25	376000	1880.0	CP-OFDM 64 QAM	133@0	23.78	24.69
2	15	25	376000	1880.0	CP-OFDM 256 QAM	133@0	23.74	24.72
2	15	30	376000	1880.0	CP-OFDM QPSK	160@0	28.529	29.63
2	15	30	376000	1880.0	CP-OFDM 16 QAM	160@0	28.592	29.68
2	15	30	376000	1880.0	CP-OFDM 64 QAM	160@0	28.554	29.58




2	15	30	376000	1880.0	CP-OFDM 256 QAM	160@0	28.574	29.51
2	15	35	376000	1880.0	CP-OFDM QPSK	188@0	33.51	34.83
2	15	35	376000	1880.0	CP-OFDM 16 QAM	188@0	33.51	34.75
2	15	35	376000	1880.0	CP-OFDM 64 QAM	188@0	33.565	34.82
2	15	35	376000	1880.0	CP-OFDM 256 QAM	188@0	33.527	34.8
2	15	40	376000	1880.0	CP-OFDM QPSK	216@0	38.522	40.06
2	15	40	376000	1880.0	CP-OFDM 16 QAM	216@0	38.54	40.09
2	15	40	376000	1880.0	CP-OFDM 64 QAM	216@0	38.577	39.97
2	15	40	376000	1880.0	CP-OFDM 256 QAM	216@0	38.497	39.92




N2(5M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N2(5M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N2(5M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N2(5M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N2(10M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N2(10M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N2(10M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N2(10M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N2(15M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N2(15M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N2(15M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N2(15M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N2(20M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N2(20M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N2(20M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N2(20M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N2(25M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N2(25M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N2(25M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N2(25M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N2(30M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N2(30M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N2(30M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N2(30M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N2(35M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N2(35M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N2(35M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N2(35M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N2(40M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N2(40M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N2(40M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH



N2(40M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH





Conducted Spurious Emissions


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
2	15	5	370500	1852.5	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	5	370500	1852.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	5	376000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	5	376000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	5	376000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	5	376000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	5	381500	1907.5	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	5	381500	1907.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	5	381500	1907.5	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	5	381500	1907.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	20	372000	1860.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	20	372000	1860.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	20	372000	1860.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	20	372000	1860.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	20	376000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	20	376000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	20	376000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	20	380000	1900.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	20	380000	1900.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	20	380000	1900.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	20	380000	1900.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	40	374000	1870.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	40	374000	1870.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	40	374000	1870.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	40	374000	1870.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	40	376000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	40	376000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	40	376000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	---




2	15	40	376000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	40	378000	1890.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	40	378000	1890.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	40	378000	1890.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	40	378000	1890.0	DFT-s-OFDM QPSK	1@0	see graph	PASS




N2(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N2(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N2(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH




N2(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH







N2(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH




N2(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH



N2(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N2(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH







N2(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH




N2(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH



N2(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH




N2(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH







N2(40M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N2(40M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N2(40M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH




N2(40M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH






N2(40M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH



N2(40M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH






Conducted Band Edge


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
2	15	5	370500	1852.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	5	370500	1852.5	DFT-s-OFDM BPSK	25@0	see graph	PASS
2	15	5	370500	1852.5	DFT-s-OFDM QPSK	25@0	see graph	PASS
2	15	5	381500	1907.5	DFT-s-OFDM BPSK	1@24	see graph	PASS
2	15	5	381500	1907.5	DFT-s-OFDM QPSK	1@24	see graph	PASS
2	15	5	381500	1907.5	DFT-s-OFDM BPSK	25@0	see graph	PASS
2	15	5	381500	1907.5	DFT-s-OFDM QPSK	25@0	see graph	PASS
2	15	20	372000	1860.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	20	372000	1860.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	20	372000	1860.0	DFT-s-OFDM BPSK	100@0	see graph	PASS
2	15	20	372000	1860.0	DFT-s-OFDM QPSK	100@0	see graph	PASS
2	15	20	380000	1900.0	DFT-s-OFDM BPSK	1@105	see graph	PASS
2	15	20	380000	1900.0	DFT-s-OFDM QPSK	1@105	see graph	PASS
2	15	20	380000	1900.0	DFT-s-OFDM BPSK	100@0	see graph	PASS
2	15	20	380000	1900.0	DFT-s-OFDM QPSK	100@0	see graph	PASS
2	15	40	374000	1870.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	40	374000	1870.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	40	374000	1870.0	DFT-s-OFDM BPSK	216@0	see graph	PASS
2	15	40	374000	1870.0	DFT-s-OFDM QPSK	216@0	see graph	PASS
2	15	40	378000	1890.0	DFT-s-OFDM BPSK	1@215	see graph	PASS
2	15	40	378000	1890.0	DFT-s-OFDM QPSK	1@215	see graph	PASS
2	15	40	378000	1890.0	DFT-s-OFDM BPSK	216@0	see graph	PASS
2	15	40	378000	1890.0	DFT-s-OFDM QPSK	216@0	see graph	PASS




N2(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N2(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N2(5M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N2(5M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH







N2(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH




N2(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH



N2(5M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH




N2(5M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH







N2(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N2(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N2(20M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N2(20M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH







N2(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH




N2(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH



N2(20M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH




N2(20M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH







N2(40M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N2(40M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N2(40M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N2(40M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH







N2(40M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH




N2(40M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH



N2(40M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH



N2(40M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH





FR1 N5 ANT0

Transmitter Conducted Output Power And ERP, (G_T - L_C)=-2dB

NR Band	SCS	Band Width	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	ERP(dBm)	ERP(W)
5	15	5	165300	826.5	DFT-s-OFDM QPSK	12@6	24.21	20.06	0.1014
5	15	5	165300	826.5	DFT-s-OFDM QPSK	1@1	24.32	20.17	0.1040
5	15	5	165300	826.5	DFT-s-OFDM QPSK	1@23	24.24	20.09	0.1021
5	15	5	165300	826.5	DFT-s-OFDM 16 QAM	12@6	23.14	18.99	0.0793
5	15	5	165300	826.5	DFT-s-OFDM 16 QAM	1@1	23.26	19.11	0.0815
5	15	5	165300	826.5	DFT-s-OFDM 16 QAM	1@23	23.42	19.27	0.0845
5	15	5	167300	836.5	DFT-s-OFDM QPSK	12@6	24.24	20.09	0.1021
5	15	5	167300	836.5	DFT-s-OFDM QPSK	1@1	24.33	20.18	0.1042
5	15	5	167300	836.5	DFT-s-OFDM QPSK	1@23	24.27	20.12	0.1028
5	15	5	167300	836.5	DFT-s-OFDM 16 QAM	12@6	23	18.85	0.0767
5	15	5	167300	836.5	DFT-s-OFDM 16 QAM	1@1	23.37	19.22	0.0836
5	15	5	167300	836.5	DFT-s-OFDM 16 QAM	1@23	23.26	19.11	0.0815
5	15	5	169300	846.5	DFT-s-OFDM QPSK	12@6	23.99	19.84	0.0964
5	15	5	169300	846.5	DFT-s-OFDM QPSK	1@1	24.22	20.07	0.1016
5	15	5	169300	846.5	DFT-s-OFDM QPSK	1@23	24.02	19.87	0.0971
5	15	5	169300	846.5	DFT-s-OFDM 16 QAM	12@6	22.87	18.72	0.0745
5	15	5	169300	846.5	DFT-s-OFDM 16 QAM	1@1	23.11	18.96	0.0787
5	15	5	169300	846.5	DFT-s-OFDM 16 QAM	1@23	23.03	18.88	0.0773
5	15	10	165800	829	DFT-s-OFDM QPSK	25@12	24.17	20.02	0.1005
5	15	10	165800	829	DFT-s-OFDM QPSK	1@1	24.18	20.03	0.1007
5	15	10	165800	829	DFT-s-OFDM QPSK	1@50	24.24	20.09	0.1021
5	15	10	165800	829	DFT-s-OFDM 16 QAM	25@12	23.17	19.02	0.0798
5	15	10	165800	829	DFT-s-OFDM 16 QAM	1@1	23.18	19.03	0.0800
5	15	10	165800	829	DFT-s-OFDM 16 QAM	1@50	23.28	19.13	0.0818
5	15	10	167300	836.5	DFT-s-OFDM QPSK	25@12	24.25	20.1	0.1023
5	15	10	167300	836.5	DFT-s-OFDM QPSK	1@1	24.31	20.16	0.1038
5	15	10	167300	836.5	DFT-s-OFDM QPSK	1@50	24.15	20	0.1000
5	15	10	167300	836.5	DFT-s-OFDM 16 QAM	25@12	23.19	19.04	0.0802
5	15	10	167300	836.5	DFT-s-OFDM 16 QAM	1@1	23.2	19.05	0.0804
5	15	10	167300	836.5	DFT-s-OFDM 16 QAM	1@50	23.21	19.06	0.0805
5	15	10	168800	844	DFT-s-OFDM QPSK	25@12	24.1	19.95	0.0989
5	15	10	168800	844	DFT-s-OFDM QPSK	1@1	24.03	19.88	0.0973



NR Band	SCS	Band Width	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	ERP(dBm)	ERP(W)
5	15	10	168800	844	DFT-s-OFDM QPSK	1@50	24	19.85	0.0966
5	15	10	168800	844	DFT-s-OFDM 16 QAM	25@12	23.04	18.89	0.0774
5	15	10	168800	844	DFT-s-OFDM 16 QAM	1@1	23.04	18.89	0.0774
5	15	10	168800	844	DFT-s-OFDM 16 QAM	1@50	23.01	18.86	0.0769
5	15	15	166300	831.5	DFT-s-OFDM QPSK	36@18	24.23	20.08	0.1019
5	15	15	166300	831.5	DFT-s-OFDM QPSK	1@1	24.15	20	0.1000
5	15	15	166300	831.5	DFT-s-OFDM QPSK	1@77	24.13	19.98	0.0995
5	15	15	166300	831.5	DFT-s-OFDM 16 QAM	36@18	23.12	18.97	0.0789
5	15	15	166300	831.5	DFT-s-OFDM 16 QAM	1@1	23.24	19.09	0.0811
5	15	15	166300	831.5	DFT-s-OFDM 16 QAM	1@77	23.32	19.17	0.0826
5	15	15	167300	836.5	DFT-s-OFDM QPSK	36@18	24.26	20.11	0.1026
5	15	15	167300	836.5	DFT-s-OFDM QPSK	1@1	24.31	20.16	0.1038
5	15	15	167300	836.5	DFT-s-OFDM QPSK	1@77	24.28	20.13	0.1030
5	15	15	167300	836.5	DFT-s-OFDM 16 QAM	36@18	23.21	19.06	0.0805
5	15	15	167300	836.5	DFT-s-OFDM 16 QAM	1@1	23.24	19.09	0.0811
5	15	15	167300	836.5	DFT-s-OFDM 16 QAM	1@77	23.17	19.02	0.0798
5	15	15	168300	841.5	DFT-s-OFDM QPSK	36@18	24.19	20.04	0.1009
5	15	15	168300	841.5	DFT-s-OFDM QPSK	1@1	24.07	19.92	0.0982
5	15	15	168300	841.5	DFT-s-OFDM QPSK	1@77	23.79	19.64	0.0920
5	15	15	168300	841.5	DFT-s-OFDM 16 QAM	36@18	23.09	18.94	0.0783
5	15	15	168300	841.5	DFT-s-OFDM 16 QAM	1@1	23.2	19.05	0.0804
5	15	15	168300	841.5	DFT-s-OFDM 16 QAM	1@77	23.03	18.88	0.0773
5	15	20	166800	834	DFT-s-OFDM PI/2 BPSK	50@25	23.87	19.72	0.0938
5	15	20	166800	834	DFT-s-OFDM PI/2 BPSK	1@1	23.76	19.61	0.0914
5	15	20	166800	834	DFT-s-OFDM PI/2 BPSK	1@104	23.62	19.47	0.0885
5	15	20	166800	834	DFT-s-OFDM QPSK	50@25	24.24	20.09	0.1021
5	15	20	166800	834	DFT-s-OFDM QPSK	1@1	24.21	20.06	0.1014
5	15	20	166800	834	DFT-s-OFDM QPSK	1@104	24.09	19.94	0.0986
5	15	20	166800	834	DFT-s-OFDM 16 QAM	50@25	23.19	19.04	0.0802
5	15	20	166800	834	DFT-s-OFDM 16 QAM	1@1	23.07	18.92	0.0780
5	15	20	166800	834	DFT-s-OFDM 16 QAM	1@104	23.15	19	0.0794
5	15	20	166800	834	DFT-s-OFDM 64 QAM	50@25	21.86	17.71	0.0590
5	15	20	166800	834	DFT-s-OFDM 64 QAM	1@1	21.81	17.66	0.0583
5	15	20	166800	834	DFT-s-OFDM 64 QAM	1@104	21.7	17.55	0.0569
5	15	20	166800	834	DFT-s-OFDM 256 QAM	50@25	19.58	15.43	0.0349
5	15	20	166800	834	DFT-s-OFDM 256 QAM	1@1	19.44	15.29	0.0338



NR Band	SCS	Band Width	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	ERP(dBm)	ERP(W)
5	15	20	166800	834	DFT-s-OFDM 256 QAM	1@104	19.22	15.07	0.0321
5	15	20	166800	834	CP-OFDM QPSK	53@26	22.59	18.44	0.0698
5	15	20	166800	834	CP-OFDM QPSK	1@1	22.89	18.74	0.0748
5	15	20	166800	834	CP-OFDM QPSK	1@104	22.63	18.48	0.0705
5	15	20	167300	836.5	DFT-s-OFDM PI/2 BPSK	50@25	23.82	19.67	0.0927
5	15	20	167300	836.5	DFT-s-OFDM PI/2 BPSK	1@1	23.84	19.69	0.0931
5	15	20	167300	836.5	DFT-s-OFDM PI/2 BPSK	1@104	23.57	19.42	0.0875
5	15	20	167300	836.5	DFT-s-OFDM QPSK	50@25	24.37	20.22	0.1052
5	15	20	167300	836.5	DFT-s-OFDM QPSK	1@1	24.35	20.2	0.1047
5	15	20	167300	836.5	DFT-s-OFDM QPSK	1@104	24.06	19.91	0.0979
5	15	20	167300	836.5	DFT-s-OFDM 16 QAM	50@25	23.12	18.97	0.0789
5	15	20	167300	836.5	DFT-s-OFDM 16 QAM	1@1	23.31	19.16	0.0824
5	15	20	167300	836.5	DFT-s-OFDM 16 QAM	1@104	22.92	18.77	0.0753
5	15	20	167300	836.5	DFT-s-OFDM 64 QAM	50@25	21.87	17.72	0.0592
5	15	20	167300	836.5	DFT-s-OFDM 64 QAM	1@1	21.83	17.68	0.0586
5	15	20	167300	836.5	DFT-s-OFDM 64 QAM	1@104	21.64	17.49	0.0561
5	15	20	167300	836.5	DFT-s-OFDM 256 QAM	50@25	19.73	15.58	0.0361
5	15	20	167300	836.5	DFT-s-OFDM 256 QAM	1@1	19.42	15.27	0.0337
5	15	20	167300	836.5	DFT-s-OFDM 256 QAM	1@104	19.11	14.96	0.0313
5	15	20	167300	836.5	CP-OFDM QPSK	53@26	22.65	18.5	0.0708
5	15	20	167300	836.5	CP-OFDM QPSK	1@1	22.91	18.76	0.0752
5	15	20	167300	836.5	CP-OFDM QPSK	1@104	22.63	18.48	0.0705
5	15	20	167800	839	DFT-s-OFDM PI/2 BPSK	50@25	23.75	19.6	0.0912
5	15	20	167800	839	DFT-s-OFDM PI/2 BPSK	1@1	23.71	19.56	0.0904
5	15	20	167800	839	DFT-s-OFDM PI/2 BPSK	1@104	23.58	19.43	0.0877
5	15	20	167800	839	DFT-s-OFDM QPSK	50@25	24.32	20.17	0.1040
5	15	20	167800	839	DFT-s-OFDM QPSK	1@1	24.3	20.15	0.1035
5	15	20	167800	839	DFT-s-OFDM QPSK	1@104	24.06	19.91	0.0979
5	15	20	167800	839	DFT-s-OFDM 16 QAM	50@25	23.03	18.88	0.0773
5	15	20	167800	839	DFT-s-OFDM 16 QAM	1@1	23.37	19.22	0.0836
5	15	20	167800	839	DFT-s-OFDM 16 QAM	1@104	22.9	18.75	0.0750
5	15	20	167800	839	DFT-s-OFDM 64 QAM	50@25	21.76	17.61	0.0577
5	15	20	167800	839	DFT-s-OFDM 64 QAM	1@1	21.94	17.79	0.0601
5	15	20	167800	839	DFT-s-OFDM 64 QAM	1@104	21.52	17.37	0.0546
5	15	20	167800	839	DFT-s-OFDM 256 QAM	50@25	19.68	15.53	0.0357
5	15	20	167800	839	DFT-s-OFDM 256 QAM	1@1	19.45	15.3	0.0339



NR Band	SCS	Band Width	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	ERP(dBm)	ERP(W)
5	15	20	167800	839	DFT-s-OFDM 256 QAM	1@104	19.14	14.99	0.0316
5	15	20	167800	839	CP-OFDM QPSK	53@26	22.58	18.43	0.0697
5	15	20	167800	839	CP-OFDM QPSK	1@1	23	18.85	0.0767
5	15	20	167800	839	CP-OFDM QPSK	1@104	22.57	18.42	0.0695



Software Version: 23.06.1602

FR1 N25 ANT0 - Other PA**Transmitter Conducted Output Power And EIRP, ($G_T - L_c$)=2dB**

NR Band	SCS	Band Width	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP(dBm)	EIRP(W)
25	15	5	370500	1852.5	DFT-s-OFDM QPSK	12@6	24.23	26.23	0.4198
25	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@1	24.17	26.17	0.4140
25	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@23	24.08	26.08	0.4055
25	15	5	370500	1852.5	DFT-s-OFDM 16 QAM	12@6	23.13	25.13	0.3258
25	15	5	370500	1852.5	DFT-s-OFDM 16 QAM	1@1	23.51	25.51	0.3556
25	15	5	370500	1852.5	DFT-s-OFDM 16 QAM	1@23	23.44	25.44	0.3499
25	15	5	376500	1882.5	DFT-s-OFDM QPSK	12@6	24.2	26.2	0.4169
25	15	5	376500	1882.5	DFT-s-OFDM QPSK	1@1	24.23	26.23	0.4198
25	15	5	376500	1882.5	DFT-s-OFDM QPSK	1@23	24.23	26.23	0.4198
25	15	5	376500	1882.5	DFT-s-OFDM 16 QAM	12@6	23.29	25.29	0.3381
25	15	5	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	23.53	25.53	0.3573
25	15	5	376500	1882.5	DFT-s-OFDM 16 QAM	1@23	23.37	25.37	0.3443
25	15	5	382500	1912.5	DFT-s-OFDM QPSK	12@6	24.33	26.33	0.4295
25	15	5	382500	1912.5	DFT-s-OFDM QPSK	1@1	24	26	0.3981
25	15	5	382500	1912.5	DFT-s-OFDM QPSK	1@23	23.97	25.97	0.3954
25	15	5	382500	1912.5	DFT-s-OFDM 16 QAM	12@6	23.22	25.22	0.3327
25	15	5	382500	1912.5	DFT-s-OFDM 16 QAM	1@1	23.37	25.37	0.3443
25	15	5	382500	1912.5	DFT-s-OFDM 16 QAM	1@23	23.29	25.29	0.3381
25	15	10	371000	1855	DFT-s-OFDM QPSK	25@12	24.32	26.32	0.4285
25	15	10	371000	1855	DFT-s-OFDM QPSK	1@1	24.15	26.15	0.4121
25	15	10	371000	1855	DFT-s-OFDM QPSK	1@50	24.27	26.27	0.4236
25	15	10	371000	1855	DFT-s-OFDM 16 QAM	25@12	23.36	25.36	0.3436
25	15	10	371000	1855	DFT-s-OFDM 16 QAM	1@1	23.51	25.51	0.3556
25	15	10	371000	1855	DFT-s-OFDM 16 QAM	1@50	23.39	25.39	0.3459
25	15	10	376500	1882.5	DFT-s-OFDM QPSK	25@12	24.13	26.13	0.4102
25	15	10	376500	1882.5	DFT-s-OFDM QPSK	1@1	24.15	26.15	0.4121
25	15	10	376500	1882.5	DFT-s-OFDM QPSK	1@50	24.26	26.26	0.4227
25	15	10	376500	1882.5	DFT-s-OFDM 16 QAM	25@12	23.33	25.33	0.3412
25	15	10	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	23.36	25.36	0.3436
25	15	10	376500	1882.5	DFT-s-OFDM 16 QAM	1@50	23.28	25.28	0.3373
25	15	10	382000	1910	DFT-s-OFDM QPSK	25@12	24.29	26.29	0.4256
25	15	10	382000	1910	DFT-s-OFDM QPSK	1@1	24.11	26.11	0.4083
25	15	10	382000	1910	DFT-s-OFDM QPSK	1@50	24.15	26.15	0.4121
25	15	10	382000	1910	DFT-s-OFDM 16 QAM	25@12	23.28	25.28	0.3373
25	15	10	382000	1910	DFT-s-OFDM 16 QAM	1@1	23.44	25.44	0.3499



25	15	10	382000	1910	DFT-s-OFDM 16 QAM	1@50	23.3	25.3	0.3388
25	15	15	371500	1857.5	DFT-s-OFDM QPSK	36@18	24.31	26.31	0.4276
25	15	15	371500	1857.5	DFT-s-OFDM QPSK	1@1	24.37	26.37	0.4335
25	15	15	371500	1857.5	DFT-s-OFDM QPSK	1@77	24.2	26.2	0.4169
25	15	15	371500	1857.5	DFT-s-OFDM 16 QAM	36@18	23.32	25.32	0.3404
25	15	15	371500	1857.5	DFT-s-OFDM 16 QAM	1@1	23.46	25.46	0.3516
25	15	15	371500	1857.5	DFT-s-OFDM 16 QAM	1@77	23.41	25.41	0.3475
25	15	15	376500	1882.5	DFT-s-OFDM QPSK	36@18	24.25	26.25	0.4217
25	15	15	376500	1882.5	DFT-s-OFDM QPSK	1@1	24.28	26.28	0.4246
25	15	15	376500	1882.5	DFT-s-OFDM QPSK	1@77	24.14	26.14	0.4111
25	15	15	376500	1882.5	DFT-s-OFDM 16 QAM	36@18	23.31	25.31	0.3396
25	15	15	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	23.46	25.46	0.3516
25	15	15	376500	1882.5	DFT-s-OFDM 16 QAM	1@77	23.36	25.36	0.3436
25	15	15	381500	1907.5	DFT-s-OFDM QPSK	36@18	24.24	26.24	0.4207
25	15	15	381500	1907.5	DFT-s-OFDM QPSK	1@1	24.18	26.18	0.4150
25	15	15	381500	1907.5	DFT-s-OFDM QPSK	1@77	24.17	26.17	0.4140
25	15	15	381500	1907.5	DFT-s-OFDM 16 QAM	36@18	23.46	25.46	0.3516
25	15	15	381500	1907.5	DFT-s-OFDM 16 QAM	1@1	23.5	25.5	0.3548
25	15	15	381500	1907.5	DFT-s-OFDM 16 QAM	1@77	23.5	25.5	0.3548
25	15	20	372000	1860	DFT-s-OFDM QPSK	50@25	24.26	26.26	0.4227
25	15	20	372000	1860	DFT-s-OFDM QPSK	1@1	24.18	26.18	0.4150
25	15	20	372000	1860	DFT-s-OFDM QPSK	1@104	23.93	25.93	0.3917
25	15	20	372000	1860	DFT-s-OFDM 16 QAM	50@25	23.32	25.32	0.3404
25	15	20	372000	1860	DFT-s-OFDM 16 QAM	1@1	23.47	25.47	0.3524
25	15	20	372000	1860	DFT-s-OFDM 16 QAM	1@104	23.34	25.34	0.3420
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	50@25	24.2	26.2	0.4169
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	1@1	24.14	26.14	0.4111
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	1@104	24.09	26.09	0.4064
25	15	20	376500	1882.5	DFT-s-OFDM 16 QAM	50@25	23.26	25.26	0.3357
25	15	20	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	23.43	25.43	0.3491
25	15	20	376500	1882.5	DFT-s-OFDM 16 QAM	1@104	23.4	25.4	0.3467
25	15	20	381000	1905	DFT-s-OFDM QPSK	50@25	24.32	26.32	0.4285
25	15	20	381000	1905	DFT-s-OFDM QPSK	1@1	24.29	26.29	0.4256
25	15	20	381000	1905	DFT-s-OFDM QPSK	1@104	24.12	26.12	0.4093
25	15	20	381000	1905	DFT-s-OFDM 16 QAM	50@25	23.44	25.44	0.3499
25	15	20	381000	1905	DFT-s-OFDM 16 QAM	1@1	23.51	25.51	0.3556
25	15	20	381000	1905	DFT-s-OFDM 16 QAM	1@104	23.36	25.36	0.3436
25	15	25	372500	1862.5	DFT-s-OFDM QPSK	64@32	24.23	26.23	0.4198
25	15	25	372500	1862.5	DFT-s-OFDM QPSK	1@1	24.09	26.09	0.4064
25	15	25	372500	1862.5	DFT-s-OFDM QPSK	1@131	24.33	26.33	0.4295
25	15	25	372500	1862.5	DFT-s-OFDM 16 QAM	64@32	23.2	25.2	0.3311
25	15	25	372500	1862.5	DFT-s-OFDM 16 QAM	1@1	23.44	25.44	0.3499



25	15	25	372500	1862.5	DFT-s-OFDM 16 QAM	1@131	23.5	25.5	0.3548
25	15	25	376500	1882.5	DFT-s-OFDM QPSK	64@32	24.36	26.36	0.4325
25	15	25	376500	1882.5	DFT-s-OFDM QPSK	1@1	24.32	26.32	0.4285
25	15	25	376500	1882.5	DFT-s-OFDM QPSK	1@131	24.37	26.37	0.4335
25	15	25	376500	1882.5	DFT-s-OFDM 16 QAM	64@32	23.32	25.32	0.3404
25	15	25	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	23.47	25.47	0.3524
25	15	25	376500	1882.5	DFT-s-OFDM 16 QAM	1@131	23.48	25.48	0.3532
25	15	25	380500	1902.5	DFT-s-OFDM QPSK	64@32	24.2	26.2	0.4169
25	15	25	380500	1902.5	DFT-s-OFDM QPSK	1@1	24.3	26.3	0.4266
25	15	25	380500	1902.5	DFT-s-OFDM QPSK	1@131	24.27	26.27	0.4236
25	15	25	380500	1902.5	DFT-s-OFDM 16 QAM	64@32	23.49	25.49	0.3540
25	15	25	380500	1902.5	DFT-s-OFDM 16 QAM	1@1	23.61	25.61	0.3639
25	15	25	380500	1902.5	DFT-s-OFDM 16 QAM	1@131	23.45	25.45	0.3508
25	15	30	373000	1865	DFT-s-OFDM QPSK	80@40	24.37	26.37	0.4335
25	15	30	373000	1865	DFT-s-OFDM QPSK	1@1	24.3	26.3	0.4266
25	15	30	373000	1865	DFT-s-OFDM QPSK	1@158	24.3	26.3	0.4266
25	15	30	373000	1865	DFT-s-OFDM 16 QAM	80@40	23.27	25.27	0.3365
25	15	30	373000	1865	DFT-s-OFDM 16 QAM	1@1	23.55	25.55	0.3589
25	15	30	373000	1865	DFT-s-OFDM 16 QAM	1@158	23.48	25.48	0.3532
25	15	30	376500	1882.5	DFT-s-OFDM QPSK	80@40	24.31	26.31	0.4276
25	15	30	376500	1882.5	DFT-s-OFDM QPSK	1@1	24.22	26.22	0.4188
25	15	30	376500	1882.5	DFT-s-OFDM QPSK	1@158	24.33	26.33	0.4295
25	15	30	376500	1882.5	DFT-s-OFDM 16 QAM	80@40	23.32	25.32	0.3404
25	15	30	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	23.57	25.57	0.3606
25	15	30	376500	1882.5	DFT-s-OFDM 16 QAM	1@158	23.55	25.55	0.3589
25	15	30	380000	1900	DFT-s-OFDM QPSK	80@40	24.32	26.32	0.4285
25	15	30	380000	1900	DFT-s-OFDM QPSK	1@1	24.38	26.38	0.4345
25	15	30	380000	1900	DFT-s-OFDM QPSK	1@158	24.33	26.33	0.4295
25	15	30	380000	1900	DFT-s-OFDM 16 QAM	80@40	23.37	25.37	0.3443
25	15	30	380000	1900	DFT-s-OFDM 16 QAM	1@1	23.57	25.57	0.3606
25	15	30	380000	1900	DFT-s-OFDM 16 QAM	1@158	23.39	25.39	0.3459
25	15	35	373500	1867.5	DFT-s-OFDM QPSK	90@45	24.32	26.32	0.4285
25	15	35	373500	1867.5	DFT-s-OFDM QPSK	1@1	24.11	26.11	0.4083
25	15	35	373500	1867.5	DFT-s-OFDM QPSK	1@186	24.23	26.23	0.4198
25	15	35	373500	1867.5	DFT-s-OFDM 16 QAM	90@45	23.35	25.35	0.3428
25	15	35	373500	1867.5	DFT-s-OFDM 16 QAM	1@1	23.36	25.36	0.3436
25	15	35	373500	1867.5	DFT-s-OFDM 16 QAM	1@186	23.54	25.54	0.3581
25	15	35	376500	1882.5	DFT-s-OFDM QPSK	90@45	24.31	26.31	0.4276
25	15	35	376500	1882.5	DFT-s-OFDM QPSK	1@1	24.12	26.12	0.4093
25	15	35	376500	1882.5	DFT-s-OFDM QPSK	1@186	24.18	26.18	0.4150
25	15	35	376500	1882.5	DFT-s-OFDM 16 QAM	90@45	23.36	25.36	0.3436
25	15	35	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	23.48	25.48	0.3532



25	15	35	376500	1882.5	DFT-s-OFDM 16 QAM	1@186	23.38	25.38	0.3451
25	15	35	379500	1897.5	DFT-s-OFDM QPSK	90@45	24.31	26.31	0.4276
25	15	35	379500	1897.5	DFT-s-OFDM QPSK	1@1	24.23	26.23	0.4198
25	15	35	379500	1897.5	DFT-s-OFDM QPSK	1@186	24.07	26.07	0.4046
25	15	35	379500	1897.5	DFT-s-OFDM 16 QAM	90@45	23.31	25.31	0.3396
25	15	35	379500	1897.5	DFT-s-OFDM 16 QAM	1@1	23.61	25.61	0.3639
25	15	35	379500	1897.5	DFT-s-OFDM 16 QAM	1@186	23.37	25.37	0.3443
25	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	108@54	22.97	24.97	0.3141
25	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	1@1	22.75	24.75	0.2985
25	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	1@214	22.87	24.87	0.3069
25	15	40	374000	1870	DFT-s-OFDM QPSK	108@54	24.39	26.39	0.4355
25	15	40	374000	1870	DFT-s-OFDM QPSK	1@1	23.94	25.94	0.3926
25	15	40	374000	1870	DFT-s-OFDM QPSK	1@214	24.24	26.24	0.4207
25	15	40	374000	1870	DFT-s-OFDM 16 QAM	108@54	23.35	25.35	0.3428
25	15	40	374000	1870	DFT-s-OFDM 16 QAM	1@1	23.34	25.34	0.3420
25	15	40	374000	1870	DFT-s-OFDM 16 QAM	1@214	23.48	25.48	0.3532
25	15	40	374000	1870	DFT-s-OFDM 64 QAM	108@54	21.94	23.94	0.2477
25	15	40	374000	1870	DFT-s-OFDM 64 QAM	1@1	21.79	23.79	0.2393
25	15	40	374000	1870	DFT-s-OFDM 64 QAM	1@214	22.03	24.03	0.2529
25	15	40	374000	1870	DFT-s-OFDM 256 QAM	108@54	19.84	21.84	0.1528
25	15	40	374000	1870	DFT-s-OFDM 256 QAM	1@1	19.36	21.36	0.1368
25	15	40	374000	1870	DFT-s-OFDM 256 QAM	1@214	19.59	21.59	0.1442
25	15	40	374000	1870	CP-OFDM QPSK	108@54	22.91	24.91	0.3097
25	15	40	374000	1870	CP-OFDM QPSK	1@1	22.69	24.69	0.2944
25	15	40	374000	1870	CP-OFDM QPSK	1@214	22.95	24.95	0.3126
25	15	40	376500	1882.5	DFT-s-OFDM PI/2 BPSK	108@54	22.93	24.93	0.3112
25	15	40	376500	1882.5	DFT-s-OFDM PI/2 BPSK	1@1	22.75	24.75	0.2985
25	15	40	376500	1882.5	DFT-s-OFDM PI/2 BPSK	1@214	22.86	24.86	0.3062
25	15	40	376500	1882.5	DFT-s-OFDM QPSK	108@54	24.31	26.31	0.4276
25	15	40	376500	1882.5	DFT-s-OFDM QPSK	1@1	24.05	26.05	0.4027
25	15	40	376500	1882.5	DFT-s-OFDM QPSK	1@214	24.26	26.26	0.4227
25	15	40	376500	1882.5	DFT-s-OFDM 16 QAM	108@54	23.39	25.39	0.3459
25	15	40	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	23.36	25.36	0.3436
25	15	40	376500	1882.5	DFT-s-OFDM 16 QAM	1@214	23.43	25.43	0.3491
25	15	40	376500	1882.5	DFT-s-OFDM 64 QAM	108@54	21.8	23.8	0.2399
25	15	40	376500	1882.5	DFT-s-OFDM 64 QAM	1@1	21.91	23.91	0.2460
25	15	40	376500	1882.5	DFT-s-OFDM 64 QAM	1@214	21.89	23.89	0.2449
25	15	40	376500	1882.5	DFT-s-OFDM 256 QAM	108@54	19.85	21.85	0.1531
25	15	40	376500	1882.5	DFT-s-OFDM 256 QAM	1@1	19.37	21.37	0.1371
25	15	40	376500	1882.5	DFT-s-OFDM 256 QAM	1@214	19.5	21.5	0.1413
25	15	40	376500	1882.5	CP-OFDM QPSK	108@54	22.91	24.91	0.3097
25	15	40	376500	1882.5	CP-OFDM QPSK	1@1	22.8	24.8	0.3020



25	15	40	376500	1882.5	CP-OFDM QPSK	1@214	23.1	25.1	0.3236
25	15	40	379000	1895	DFT-s-OFDM PI/2 BPSK	108@54	22.95	24.95	0.3126
25	15	40	379000	1895	DFT-s-OFDM PI/2 BPSK	1@1	22.92	24.92	0.3105
25	15	40	379000	1895	DFT-s-OFDM PI/2 BPSK	1@214	22.92	24.92	0.3105
25	15	40	379000	1895	DFT-s-OFDM QPSK	108@54	24.29	26.29	0.4256
25	15	40	379000	1895	DFT-s-OFDM QPSK	1@1	24.25	26.25	0.4217
25	15	40	379000	1895	DFT-s-OFDM QPSK	1@214	24.17	26.17	0.4140
25	15	40	379000	1895	DFT-s-OFDM 16 QAM	108@54	23.49	25.49	0.3540
25	15	40	379000	1895	DFT-s-OFDM 16 QAM	1@1	23.44	25.44	0.3499
25	15	40	379000	1895	DFT-s-OFDM 16 QAM	1@214	23.43	25.43	0.3491
25	15	40	379000	1895	DFT-s-OFDM 64 QAM	108@54	22.03	24.03	0.2529
25	15	40	379000	1895	DFT-s-OFDM 64 QAM	1@1	22.01	24.01	0.2518
25	15	40	379000	1895	DFT-s-OFDM 64 QAM	1@214	21.86	23.86	0.2432
25	15	40	379000	1895	DFT-s-OFDM 256 QAM	108@54	19.85	21.85	0.1531
25	15	40	379000	1895	DFT-s-OFDM 256 QAM	1@1	19.48	21.48	0.1406
25	15	40	379000	1895	DFT-s-OFDM 256 QAM	1@214	19.41	21.41	0.1384
25	15	40	379000	1895	CP-OFDM QPSK	108@54	22.92	24.92	0.3105
25	15	40	379000	1895	CP-OFDM QPSK	1@1	23.09	25.09	0.3228
25	15	40	379000	1895	CP-OFDM QPSK	1@214	22.79	24.79	0.3013



FR1 N25 ANT5 - Other PA

Frequency Stability

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (Hz)	Verdict	Environment
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	12.4	PASS	NV
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	10.5	PASS	LV
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	11.8	PASS	HV
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	11.8	PASS	-30°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	10.4	PASS	-20°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	15.4	PASS	-10°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	11.2	PASS	0°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	16.9	PASS	10°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	12.4	PASS	20°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	11.2	PASS	30°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	17.2	PASS	40°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	11.8	PASS	50°C

 $|\text{MAX}(\Delta f)| = 17.2 \text{ Hz}$

Frequency Stability	Frequency (MHz)	Limit Line	Result
$f_L - \text{MAX}(\Delta f) $	1850.529483	$\geq 1850 \text{ MHz}$	PASS
$f_H + \text{MAX}(\Delta f) $	1913.391617	$\leq 1915 \text{ MHz}$	

**Peak to Average Ratio**

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result (dB)	Limit (dB)	Verdict
25	15	20	376500	1882.5	DFT-s-OFDM PI/2 BPSK	100@0	4.32	13	PASS
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	5.8	13	PASS