




11BE320MIMO_Ant0_6905_3*996+484_Non-OFDMA_2




11BE320MIMO_Ant0_6905_3*996+484_Non-OFDMA_3




11BE320MIMO_Ant0_6905_3*996+484_Non-OFDMA_4




11BE320MIMO_Ant0_6905_3*996+484_Non-OFDMA_5



11BE320MIMO_Ant0_6905_3*996+484_Non-OFDMA_6




11BE320MIMO_Ant0_6905_3*996+484_Non-OFDMA_7




01:56:11 24.05.2024

11BE320MIMO_Ant0_6905_3*996+484_Non-OFDMA_8




01:58:21 24.05.2024


11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_1




11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_2



11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_3




11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_4




00:36:46 25.05.2024

11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_5




02:10:00 24.05.2024


11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_6




11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_7




11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_8




11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_9




11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_10




11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_11




11BE320MIMO_Ant1_6905_2*996+484_Non-OFDMA_12




11BE320MIMO_Ant1_6905_3*996_Non-OFDMA_1




11BE320MIMO_Ant1_6905_3*996_Non-OFDMA_2




11BE320MIMO_Ant1_6905_3*996_Non-OFDMA_3




11BE320MIMO_Ant1_6905_3*996_Non-OFDMA_4




11BE320MIMO_Ant1_6905_3*996+484_Non-OFDMA_1



11BE320MIMO_Ant1_6905_3*996+484_Non-OFDMA_2




11BE320MIMO_Ant1_6905_3*996+484_Non-OFDMA_3




02:47:13 24.05.2024

11BE320MIMO_Ant1_6905_3*996+484_Non-OFDMA_4




02:49:28 24.05.2024


11BE320MIMO_Ant1_6905_3*996+484_Non-OFDMA_5




11BE320MIMO_Ant1_6905_3*996+484_Non-OFDMA_6



11BE320MIMO_Ant1_6905_3*996+484_Non-OFDMA_7



11BE320MIMO_Ant1_6905_3*996+484_Non-OFDMA_8



22:51:05 24.05.2024

A.8. Transmitter Spurious Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407	-27 dBm/MHz

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).


Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)	Measurement distance(m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3


Frequency of emission (MHz)	Field strength (uV/m)	Field strength (dBuV/m)	Measurement distance (m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Note: When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor.


Test setup



Test Site Diagram (9kHz-30MHz)



Test Site Diagram (30MHz-1GHz)



Test Site Diagram (1GHz-40GHz)

Test Procedures

Radiated unwanted emissions from the EUT were measured according to ANSI C63.10.

Test setting

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100kHz/300kHz	5
1000-3000	1MHz/3MHz	15
3000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Sample Calculation

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= $P_{\text{Mea}}+A_{\text{Rpl}}= P_{\text{Mea}}+\text{Cable Loss}+\text{Antenna Factor}$

Test note

1. The EUT is operating at its maximum duty cycle and its maximum power control level.
2. Investigation has been done on all modes and modulations/data rates. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.
3. Spurious emissions for all channels were investigated and almost the same below 1GHz. According to FCC 47 CFR §15.31, emission levels are not report much lower than the limit by over 20dB
4. Measurement frequencies were performed from 9 kHz to the 10th harmonic of highest fundamental frequency or 40GHz, whichever is lower.
5. Both full RU and partial RU spurious emission was tested. And the results are basically noises with no suspicious emission. In this case, the measurement results of full RU were reported and represented worst cases.
6. The EUT support both SISO and MIMO, only the worst cases (MIMO)were reported.

Measurement Results:
AVERAGE Results:
802.11a
Channel 1

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17997.300	39.74	-29.55	45.95	23.34	54.00	14.26	V
17957.250	39.68	-29.55	45.95	23.28	54.00	14.32	V
14487.300	35.21	-30.35	41.90	23.66	54.00	18.79	V
14495.400	35.04	-30.35	41.90	23.49	54.00	18.96	V
5907.018	40.57	-27.15	34.30	33.42	68.20	27.63	H
5903.672	40.55	-27.15	34.30	33.40	68.20	27.65	H

Channel 45

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17977.500	39.91	-29.55	45.95	23.51	54.00	14.09	V
17993.250	39.82	-29.55	45.95	23.42	54.00	14.18	V
14491.800	34.94	-30.35	41.90	23.39	54.00	19.06	V
13345.650	34.84	-31.26	40.65	25.45	54.00	19.16	V
12698.550	33.98	-31.50	39.50	25.98	54.00	20.02	V
12681.000	33.77	-31.50	39.50	25.77	54.00	20.23	V

Channel 93

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17959.500	39.81	-29.55	45.95	23.41	54.00	14.19	V
17958.150	39.78	-29.55	45.95	23.38	54.00	14.22	H
14499.450	34.92	-30.35	41.90	23.37	54.00	19.08	V
13329.450	34.85	-31.26	40.65	25.46	54.00	19.15	V
12598.650	33.80	-31.43	39.30	25.93	54.00	20.20	V
12637.800	33.71	-31.89	39.40	26.20	54.00	20.29	V

Channel 97

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17956.350	40.30	-29.55	45.95	23.90	54.00	13.70	V
17962.650	40.06	-29.55	45.95	23.66	54.00	13.94	V
13280.850	35.71	-31.62	40.60	26.73	54.00	18.29	V
13356.450	35.57	-31.26	40.65	26.18	54.00	18.43	V
11902.500	34.93	-32.63	39.10	28.46	54.00	19.07	V
12699.000	34.78	-31.50	39.50	26.78	54.00	19.22	V

Channel 105

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17964.000	40.45	-29.55	45.95	24.05	54.00	13.55	H
17989.650	40.12	-29.55	45.95	23.72	54.00	13.88	V
13302.900	35.60	-31.62	40.60	26.62	54.00	18.40	V
13278.600	35.29	-31.62	40.60	26.31	54.00	18.71	V
11870.100	34.92	-32.13	39.15	27.90	54.00	19.08	V
12607.650	34.51	-31.43	39.30	26.64	54.00	19.49	V

Channel 113

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17986.950	40.36	-29.55	45.95	23.96	54.00	13.64	V
17964.450	39.91	-29.55	45.95	23.51	54.00	14.09	H
13306.950	35.72	-31.62	40.60	26.74	54.00	18.28	V
13297.950	35.51	-31.62	40.60	26.53	54.00	18.49	V
12697.200	34.60	-31.50	39.50	26.60	54.00	19.40	V
12691.800	34.45	-31.50	39.50	26.45	54.00	19.55	V

Channel 117

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17992.350	40.02	-29.55	45.95	23.62	54.00	13.98	V
17959.950	39.72	-29.55	45.95	23.32	54.00	14.28	V
13305.150	34.89	-31.62	40.60	25.91	54.00	19.11	H
14472.450	34.65	-30.35	41.90	23.10	54.00	19.35	V
12699.450	34.22	-31.50	39.50	26.22	54.00	19.78	H
12595.500	33.92	-31.43	39.30	26.05	54.00	20.08	V

Channel 149

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17991.000	40.09	-29.55	45.95	23.69	54.00	13.91	V
17980.200	40.04	-29.55	45.95	23.64	54.00	13.96	V
13304.250	35.13	-31.62	40.60	26.15	54.00	18.87	V
13330.350	35.06	-31.26	40.65	25.67	54.00	18.94	H
11884.050	34.33	-32.63	39.10	27.86	54.00	19.67	H
11858.850	34.29	-32.13	39.15	27.27	54.00	19.71	V

Channel 181

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17955.000	40.55	-29.55	45.95	24.15	54.00	13.45	H
17968.050	40.45	-29.55	45.95	24.05	54.00	13.55	H
13302.450	35.45	-31.62	40.60	26.47	54.00	18.55	V
13266.450	35.38	-31.65	40.50	26.53	54.00	18.62	H
11868.750	35.00	-32.13	39.15	27.98	54.00	19.00	H
11864.700	34.57	-32.13	39.15	27.55	54.00	19.43	V

Channel 185

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17971.650	40.29	-29.55	45.95	23.89	54.00	13.71	V
17987.400	40.28	-29.55	45.95	23.88	54.00	13.72	H
13292.550	35.98	-31.62	40.60	27.00	54.00	18.02	V
13260.600	35.95	-31.65	40.50	27.10	54.00	18.05	H
12680.550	35.49	-31.50	39.50	27.49	54.00	18.51	H
12684.150	35.13	-31.50	39.50	27.13	54.00	18.87	H

Channel 209

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17957.700	40.57	-29.55	45.95	24.17	54.00	13.43	H
17957.250	40.45	-29.55	45.95	24.05	54.00	13.55	H
13308.750	36.41	-31.62	40.60	27.43	54.00	17.59	V
13332.150	36.26	-31.26	40.65	26.87	54.00	17.74	H
12609.000	35.14	-31.43	39.30	27.27	54.00	18.86	H
12697.200	35.10	-31.50	39.50	27.10	54.00	18.90	V

Channel 233

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17964.000	40.54	-29.55	45.95	24.14	54.00	13.46	V
17973.000	40.42	-29.55	45.95	24.02	54.00	13.58	V
13273.200	35.88	-31.62	40.60	26.90	54.00	18.12	V
13310.550	35.88	-31.62	40.60	26.90	54.00	18.12	V
7125.060	56.96	-25.93	35.70	47.19	68.20	11.24	V
7125.192	56.93	-25.93	35.70	47.16	68.20	11.27	V

802.11ax-20M

Channel 1

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17995.050	39.82	-29.55	45.95	23.42	54.00	14.18	V
17945.550	39.65	-29.55	45.95	23.25	54.00	14.35	V
13299.750	35.06	-31.62	40.60	26.08	54.00	18.94	V
13322.250	34.91	-31.26	40.65	25.52	54.00	19.09	V
5901.432	40.33	-27.15	34.30	33.18	68.20	27.87	V
5923.230	40.03	-27.15	34.30	32.88	68.20	28.17	V

Channel 45

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17977.950	40.00	-29.55	45.95	23.60	54.00	14.00	V
17956.800	39.80	-29.55	45.95	23.40	54.00	14.20	H
13352.850	34.88	-31.26	40.65	25.49	54.00	19.12	V
14473.350	34.88	-30.35	41.90	23.33	54.00	19.12	V
12599.550	33.74	-31.43	39.30	25.87	54.00	20.26	V
12681.000	33.64	-31.50	39.50	25.64	54.00	20.36	V

Channel 93

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17965.800	39.97	-29.55	45.95	23.57	54.00	14.03	V
17971.200	39.97	-29.55	45.95	23.57	54.00	14.03	V
13288.050	35.32	-31.62	40.60	26.34	54.00	18.68	V
14497.200	35.11	-30.35	41.90	23.56	54.00	18.89	V
12678.300	34.02	-31.50	39.50	26.02	54.00	19.98	V
11869.200	33.77	-32.13	39.15	26.75	54.00	20.23	V

Channel 97

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17970.750	40.11	-29.55	45.95	23.71	54.00	13.89	V
17977.950	40.04	-29.55	45.95	23.64	54.00	13.96	V
13300.650	35.45	-31.62	40.60	26.47	54.00	18.55	V
13279.950	35.44	-31.62	40.60	26.46	54.00	18.56	V
12656.700	34.57	-31.89	39.40	27.06	54.00	19.43	V
11867.400	34.43	-32.13	39.15	27.41	54.00	19.57	V

Channel 105

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17961.750	40.12	-29.55	45.95	23.72	54.00	13.88	V
17977.950	40.02	-29.55	45.95	23.62	54.00	13.98	V
14498.100	35.43	-30.35	41.90	23.88	54.00	18.57	V
13291.200	35.34	-31.62	40.60	26.36	54.00	18.66	V
12687.750	34.65	-31.50	39.50	26.65	54.00	19.35	V
12692.700	34.62	-31.50	39.50	26.62	54.00	19.38	V

Channel 113

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17970.300	40.10	-29.55	45.95	23.70	54.00	13.90	V
17977.050	40.09	-29.55	45.95	23.69	54.00	13.91	V
13310.100	35.66	-31.62	40.60	26.68	54.00	18.34	V
13273.200	35.37	-31.62	40.60	26.39	54.00	18.63	V
12697.200	34.60	-31.50	39.50	26.60	54.00	19.40	V
12699.000	34.55	-31.50	39.50	26.55	54.00	19.45	V

Channel 117

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17990.550	39.97	-29.55	45.95	23.57	54.00	14.03	H
17957.250	39.81	-29.55	45.95	23.41	54.00	14.19	V
13300.650	35.04	-31.62	40.60	26.06	54.00	18.96	H
13324.950	35.02	-31.26	40.65	25.63	54.00	18.98	V
12683.250	34.25	-31.50	39.50	26.25	54.00	19.75	H
11860.650	34.19	-32.13	39.15	27.17	54.00	19.81	H

Channel 149

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17948.250	40.21	-29.55	45.95	23.81	54.00	13.79	V
17964.000	40.09	-29.55	45.95	23.69	54.00	13.91	V
13294.800	35.45	-31.62	40.60	26.47	54.00	18.55	H
13293.450	35.36	-31.62	40.60	26.38	54.00	18.64	H
11875.950	34.41	-32.13	39.15	27.39	54.00	19.59	V
11860.650	34.38	-32.13	39.15	27.36	54.00	19.62	V

Channel 181

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17980.200	40.25	-29.55	45.95	23.85	54.00	13.75	H
17963.100	40.18	-29.55	45.95	23.78	54.00	13.82	H
13340.700	35.61	-31.26	40.65	26.22	54.00	18.39	V
13324.050	35.39	-31.26	40.65	26.00	54.00	18.61	H
12689.550	34.88	-31.50	39.50	26.88	54.00	19.12	V
12299.400	34.81	-31.98	39.00	27.79	54.00	19.19	V

Channel 185

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17986.500	40.50	-29.55	45.95	24.10	54.00	13.50	V
17981.100	40.45	-29.55	45.95	24.05	54.00	13.55	V
13280.400	36.03	-31.62	40.60	27.05	54.00	17.97	H
13301.100	36.00	-31.62	40.60	27.02	54.00	18.00	V
11857.500	35.13	-32.13	39.15	28.11	54.00	18.87	V
11880.450	35.09	-32.13	39.15	28.07	54.00	18.91	H

Channel 209

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17960.850	40.60	-29.55	45.95	24.20	54.00	13.40	V
17972.100	40.52	-29.55	45.95	24.12	54.00	13.48	V
13320.000	36.32	-31.26	40.65	26.93	54.00	17.68	H
13338.900	36.02	-31.26	40.65	26.63	54.00	17.98	V
12194.100	35.30	-31.97	38.90	28.37	54.00	18.70	V
12601.800	35.27	-31.43	39.30	27.40	54.00	18.73	H

Channel 233

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17974.800	40.73	-29.55	45.95	24.33	54.00	13.27	V
17949.600	40.55	-29.55	45.95	24.15	54.00	13.45	H
13324.050	36.19	-31.26	40.65	26.80	54.00	17.81	H
13310.550	36.13	-31.62	40.60	27.15	54.00	17.87	V
7125.027	61.84	-25.93	35.70	52.07	68.20	6.36	V
7125.060	61.68	-25.93	35.70	51.91	68.20	6.52	V

802.11ax-40M

Channel 3

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17969.850	39.71	-29.55	45.95	23.31	54.00	14.29	V
17972.550	39.37	-29.55	45.95	22.97	54.00	14.63	H
14487.750	34.31	-30.35	41.90	22.76	54.00	19.69	H
13290.300	34.27	-31.62	40.60	25.29	54.00	19.73	V
5923.944	40.41	-27.15	34.30	33.26	68.20	27.79	V
5910.658	40.24	-27.15	34.30	33.09	68.20	27.96	V

Channel 43

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17994.600	39.42	-29.55	45.95	23.02	54.00	14.58	H
17989.650	39.33	-29.55	45.95	22.93	54.00	14.67	V
13299.750	34.56	-31.62	40.60	25.58	54.00	19.44	V
13349.250	34.22	-31.26	40.65	24.83	54.00	19.78	V
12697.200	33.25	-31.50	39.50	25.25	54.00	20.75	V
11915.100	33.21	-32.63	39.10	26.74	54.00	20.79	V

Channel 91

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17965.800	39.67	-29.55	45.95	23.27	54.00	14.33	V
17950.050	39.35	-29.55	45.95	22.95	54.00	14.65	H
13293.900	34.64	-31.62	40.60	25.66	54.00	19.36	V
13308.300	34.61	-31.62	40.60	25.63	54.00	19.39	V
12698.550	33.45	-31.50	39.50	25.45	54.00	20.55	V
12276.450	33.44	-32.39	38.95	26.88	54.00	20.56	V

Channel 99

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17997.300	40.44	-29.55	45.95	24.04	54.00	13.56	V
17964.900	40.07	-29.55	45.95	23.67	54.00	13.93	V
13337.100	35.60	-31.26	40.65	26.21	54.00	18.40	H
13290.300	35.44	-31.62	40.60	26.46	54.00	18.56	V
12691.350	34.60	-31.50	39.50	26.60	54.00	19.40	V
12687.750	34.55	-31.50	39.50	26.55	54.00	19.45	V

Channel 107

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17986.050	40.20	-29.55	45.95	23.80	54.00	13.80	H
17991.450	40.15	-29.55	45.95	23.75	54.00	13.85	V
13347.450	35.78	-31.26	40.65	26.39	54.00	18.22	V
13292.100	35.64	-31.62	40.60	26.66	54.00	18.36	H
11863.350	35.13	-32.13	39.15	28.11	54.00	18.87	V
12293.100	34.91	-31.98	39.00	27.89	54.00	19.09	V

Channel 115

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17977.950	40.08	-29.55	45.95	23.68	54.00	13.92	V
17965.350	40.07	-29.55	45.95	23.67	54.00	13.93	H
13293.000	35.90	-31.62	40.60	26.92	54.00	18.10	V
13303.350	35.62	-31.62	40.60	26.64	54.00	18.38	V
11876.400	34.91	-32.13	39.15	27.89	54.00	19.09	V
12692.700	34.87	-31.50	39.50	26.87	54.00	19.13	V

Channel 123

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17970.300	40.25	-29.55	45.95	23.85	54.00	13.75	V
17997.750	40.08	-29.55	45.95	23.68	54.00	13.92	V
13311.000	35.46	-31.62	40.60	26.48	54.00	18.54	H
13335.300	35.39	-31.26	40.65	26.00	54.00	18.61	V
11869.650	34.65	-32.13	39.15	27.63	54.00	19.35	H
11880.900	34.56	-32.13	39.15	27.54	54.00	19.44	H

Channel 155

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17960.400	40.20	-29.55	45.95	23.80	54.00	13.80	V
17978.850	40.06	-29.55	45.95	23.66	54.00	13.94	H
13256.100	35.64	-31.65	40.50	26.79	54.00	18.36	H
14479.650	35.46	-30.35	41.90	23.91	54.00	18.54	V
11876.850	34.79	-32.13	39.15	27.77	54.00	19.21	V
10904.850	34.75	-32.71	38.50	28.96	54.00	19.25	V

Channel 179

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17990.550	40.37	-29.55	45.95	23.97	54.00	13.63	V
17980.200	40.04	-29.55	45.95	23.64	54.00	13.96	V
13313.250	35.85	-31.62	40.60	26.87	54.00	18.15	V
13335.750	35.80	-31.26	40.65	26.41	54.00	18.20	V
11870.100	34.80	-32.13	39.15	27.78	54.00	19.20	V
12677.850	34.63	-31.50	39.50	26.63	54.00	19.37	H

Channel 187

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17932.950	40.66	-29.55	45.95	24.26	54.00	13.34	H
17969.850	40.54	-29.55	45.95	24.14	54.00	13.46	V
13262.850	36.16	-31.65	40.50	27.31	54.00	17.84	H
13347.450	36.11	-31.26	40.65	26.72	54.00	17.89	V
11872.350	35.56	-32.13	39.15	28.54	54.00	18.44	H
11867.850	35.39	-32.13	39.15	28.37	54.00	18.61	V

Channel 211

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17962.200	41.09	-29.55	45.95	24.69	54.00	12.91	V
17963.100	40.73	-29.55	45.95	24.33	54.00	13.27	V
13292.550	36.64	-31.62	40.60	27.66	54.00	17.36	H
13338.450	36.44	-31.26	40.65	27.05	54.00	17.56	H
11869.200	35.78	-32.13	39.15	28.76	54.00	18.22	H
11910.150	35.54	-32.63	39.10	29.07	54.00	18.46	H

Channel 227

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17991.900	41.29	-29.55	45.95	24.89	54.00	12.71	H
17970.750	40.94	-29.55	45.95	24.54	54.00	13.06	H
13330.800	36.87	-31.26	40.65	27.48	54.00	17.13	V
13329.900	36.79	-31.26	40.65	27.40	54.00	17.21	H
7213.962	43.39	-25.94	36.20	33.13	68.20	24.81	V
7222.575	43.38	-25.94	36.20	33.12	68.20	24.82	V

802.11ax-80M

Channel 7

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17982.900	39.64	-29.55	45.95	23.24	54.00	14.36	H
17982.450	39.58	-29.55	45.95	23.18	54.00	14.42	H
13278.600	34.59	-31.62	40.60	25.61	54.00	19.41	V
13290.750	34.51	-31.62	40.60	25.53	54.00	19.49	V
5911.232	40.17	-27.15	34.30	33.02	68.20	28.03	V
5918.428	40.13	-27.15	34.30	32.98	68.20	28.07	V

Channel 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17968.500	39.62	-29.55	45.95	23.22	54.00	14.38	V
17976.600	39.62	-29.55	45.95	23.22	54.00	14.38	H
13288.500	34.66	-31.62	40.60	25.68	54.00	19.34	V
13284.450	34.55	-31.62	40.60	25.57	54.00	19.45	V
11844.000	33.71	-32.13	39.15	26.69	54.00	20.29	V
11870.550	33.71	-32.13	39.15	26.69	54.00	20.29	V

Channel 87

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17986.050	39.87	-29.55	45.95	23.47	54.00	14.13	H
17981.100	39.73	-29.55	45.95	23.33	54.00	14.27	V
13303.800	34.60	-31.62	40.60	25.62	54.00	19.40	H
13295.250	34.58	-31.62	40.60	25.60	54.00	19.42	V
11864.250	34.02	-32.13	39.15	27.00	54.00	19.98	V
12592.800	33.65	-31.43	39.30	25.78	54.00	20.35	V

Channel 103

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17964.450	35.40	-29.55	45.95	19.00	54.00	18.60	V
17968.950	35.36	-29.55	45.95	18.96	54.00	18.64	H
13254.300	33.20	-31.65	40.50	24.35	54.00	20.80	V
13262.850	33.02	-31.65	40.50	24.17	54.00	20.98	V
9192.150	32.85	-33.96	37.70	29.11	54.00	21.15	V
9127.350	32.60	-33.82	37.70	28.72	54.00	21.40	V

Channel 119

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17977.500	40.46	-29.55	45.95	24.06	54.00	13.54	H
17962.650	40.17	-29.55	45.95	23.77	54.00	13.83	H
13281.300	35.66	-31.62	40.60	26.68	54.00	18.34	V
13292.100	35.62	-31.62	40.60	26.64	54.00	18.38	V
10907.550	35.10	-32.71	38.50	29.31	54.00	18.90	H
12699.000	34.87	-31.50	39.50	26.87	54.00	19.13	V

Channel 151

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17977.050	40.30	-29.55	45.95	23.90	54.00	13.70	V
17988.750	40.21	-29.55	45.95	23.81	54.00	13.79	V
13314.150	35.70	-31.62	40.60	26.72	54.00	18.30	H
13324.500	35.63	-31.26	40.65	26.24	54.00	18.37	V
11861.550	34.97	-32.13	39.15	27.95	54.00	19.03	V
11855.700	34.86	-32.13	39.15	27.84	54.00	19.14	H

Channel 183

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17997.750	40.47	-29.55	45.95	24.07	54.00	13.53	V
17957.250	40.44	-29.55	45.95	24.04	54.00	13.56	H
13326.750	36.02	-31.26	40.65	26.63	54.00	17.98	V
13306.050	36.01	-31.62	40.60	27.03	54.00	17.99	H
10901.250	34.73	-32.71	38.50	28.94	54.00	19.27	V
11869.650	34.73	-32.13	39.15	27.71	54.00	19.27	V

Channel 199

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17966.700	40.76	-29.55	45.95	24.36	54.00	13.24	V
17970.300	40.76	-29.55	45.95	24.36	54.00	13.24	H
13307.400	36.75	-31.62	40.60	27.77	54.00	17.25	V
13272.750	36.71	-31.62	40.60	27.73	54.00	17.29	V
11879.100	35.87	-32.13	39.15	28.85	54.00	18.13	H
11884.950	35.83	-32.63	39.10	29.36	54.00	18.17	H

Channel 215

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17990.550	40.92	-29.55	45.95	24.52	54.00	13.08	H
17970.750	40.86	-29.55	45.95	24.46	54.00	13.14	V
13312.800	36.66	-31.62	40.60	27.68	54.00	17.34	V
13275.000	36.52	-31.62	40.60	27.54	54.00	17.48	H
7229.307	43.58	-25.90	36.40	33.08	68.20	24.62	H
7212.444	43.48	-25.94	36.20	33.22	68.20	24.72	H

802.11ax-160M

Channel 15

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17952.750	39.70	-29.55	45.95	23.30	54.00	14.30	V
17972.100	39.59	-29.55	45.95	23.19	54.00	14.41	V
13351.500	34.88	-31.26	40.65	25.49	54.00	19.12	V
13299.300	34.80	-31.62	40.60	25.82	54.00	19.20	V
5923.860	40.19	-27.15	34.30	33.04	68.20	28.01	H
5907.382	40.06	-27.15	34.30	32.91	68.20	28.14	V

Channel 47

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17960.400	39.73	-29.55	45.95	23.33	54.00	14.27	H
17991.450	39.69	-29.55	45.95	23.29	54.00	14.31	V
14477.850	35.16	-30.35	41.90	23.61	54.00	18.84	V
13303.800	35.13	-31.62	40.60	26.15	54.00	18.87	V
12699.000	33.99	-31.50	39.50	25.99	54.00	20.01	H
12698.100	33.86	-31.50	39.50	25.86	54.00	20.14	V

Channel 79

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17965.800	40.00	-29.55	45.95	23.60	54.00	14.00	H
17953.200	39.81	-29.55	45.95	23.41	54.00	14.19	V
13300.650	34.95	-31.62	40.60	25.97	54.00	19.05	V
13310.100	34.74	-31.62	40.60	25.76	54.00	19.26	V
12682.350	33.92	-31.50	39.50	25.92	54.00	20.08	V
12294.000	33.87	-31.98	39.00	26.85	54.00	20.13	V

Channel 143

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17993.250	40.75	-29.55	45.95	24.35	54.00	13.25	V
17931.150	40.28	-29.55	45.95	23.88	54.00	13.72	H
13315.050	35.77	-31.62	40.60	26.79	54.00	18.23	H
13322.700	35.74	-31.26	40.65	26.35	54.00	18.26	H
12284.550	35.08	-31.98	39.00	28.06	54.00	18.92	V
12673.350	34.96	-31.50	39.50	26.96	54.00	19.04	V

Channel 207

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17958.150	41.18	-29.55	45.95	24.78	54.00	12.82	V
17963.100	41.07	-29.55	45.95	24.67	54.00	12.93	H
13330.800	36.65	-31.26	40.65	27.26	54.00	17.35	H
13288.500	36.57	-31.62	40.60	27.59	54.00	17.43	H
7225.875	43.74	-25.94	36.20	33.48	68.20	24.46	H
7227.129	43.55	-25.94	36.20	33.29	68.20	24.65	V

802.11be-20M

Channel 1

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17973.900	39.85	-29.55	45.95	23.45	54.00	14.15	H
17958.600	39.84	-29.55	45.95	23.44	54.00	14.16	H
14492.250	34.93	-30.35	41.90	23.38	54.00	19.07	H
13308.750	34.91	-31.62	40.60	25.93	54.00	19.09	V
5917.966	40.17	-27.15	34.30	33.02	68.20	28.03	V
5907.508	39.86	-27.15	34.30	32.71	68.20	28.34	V

Channel 45

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17959.500	39.93	-29.55	45.95	23.53	54.00	14.07	V
17991.900	39.92	-29.55	45.95	23.52	54.00	14.08	V
13339.350	35.07	-31.26	40.65	25.68	54.00	18.93	V
13340.250	34.96	-31.26	40.65	25.57	54.00	19.04	V
11884.500	33.83	-32.63	39.10	27.36	54.00	20.17	V
12613.050	33.83	-31.43	39.30	25.96	54.00	20.17	V

Channel 93

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17996.400	40.17	-29.55	45.95	23.77	54.00	13.83	V
17970.300	40.14	-29.55	45.95	23.74	54.00	13.86	H
14471.550	35.06	-30.35	41.90	23.51	54.00	18.94	V
13334.850	35.02	-31.26	40.65	25.63	54.00	18.98	V
12699.450	33.98	-31.50	39.50	25.98	54.00	20.02	V
12698.100	33.92	-31.50	39.50	25.92	54.00	20.08	V

Channel 97

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17950.950	40.14	-29.55	45.95	23.74	54.00	13.86	V
17950.500	40.11	-29.55	45.95	23.71	54.00	13.89	V
13292.550	35.63	-31.62	40.60	26.65	54.00	18.37	V
14476.950	35.46	-30.35	41.90	23.91	54.00	18.54	V
12678.750	34.88	-31.50	39.50	26.88	54.00	19.12	V
11884.050	34.64	-32.63	39.10	28.17	54.00	19.36	V

Channel 105

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17958.600	40.14	-29.55	45.95	23.74	54.00	13.86	V
17954.550	40.05	-29.55	45.95	23.65	54.00	13.95	V
13298.850	35.46	-31.62	40.60	26.48	54.00	18.54	V
14483.700	35.45	-30.35	41.90	23.90	54.00	18.55	V
12699.450	34.54	-31.50	39.50	26.54	54.00	19.46	V
11868.750	34.42	-32.13	39.15	27.40	54.00	19.58	V

Channel 113

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17964.900	40.27	-29.55	45.95	23.87	54.00	13.73	V
17995.050	40.00	-29.55	45.95	23.60	54.00	14.00	H
13276.350	35.57	-31.62	40.60	26.59	54.00	18.43	V
13300.650	35.50	-31.62	40.60	26.52	54.00	18.50	V
12660.300	34.61	-31.89	39.40	27.10	54.00	19.39	V
11889.000	34.60	-32.63	39.10	28.13	54.00	19.40	H

Channel 117

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17963.100	40.01	-29.55	45.95	23.61	54.00	13.99	H
17998.200	39.92	-29.55	45.95	23.52	54.00	14.08	H
13288.500	35.07	-31.62	40.60	26.09	54.00	18.93	V
13294.800	34.96	-31.62	40.60	25.98	54.00	19.04	H
12696.750	34.25	-31.50	39.50	26.25	54.00	19.75	V
12597.750	34.14	-31.43	39.30	26.27	54.00	19.86	V

Channel 149

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17966.700	39.95	-29.55	45.95	23.55	54.00	14.05	H
17990.100	39.93	-29.55	45.95	23.53	54.00	14.07	H
14477.400	35.21	-30.35	41.90	23.66	54.00	18.79	V
14499.450	35.21	-30.35	41.90	23.66	54.00	18.79	H
12694.950	34.51	-31.50	39.50	26.51	54.00	19.49	V
11855.700	34.50	-32.13	39.15	27.48	54.00	19.50	V

Channel 181

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17949.600	40.08	-29.55	45.95	23.68	54.00	13.92	V
17952.750	40.06	-29.55	45.95	23.66	54.00	13.94	H
14498.100	35.43	-30.35	41.90	23.88	54.00	18.57	V
13330.350	35.35	-31.26	40.65	25.96	54.00	18.65	V
11868.300	34.63	-32.13	39.15	27.61	54.00	19.37	V
11872.800	34.56	-32.13	39.15	27.54	54.00	19.44	V

Channel 185

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17994.150	40.47	-29.55	45.95	24.07	54.00	13.53	H
17993.700	40.38	-29.55	45.95	23.98	54.00	13.62	V
14499.900	36.09	-30.35	41.90	24.54	54.00	17.91	H
13291.200	35.99	-31.62	40.60	27.01	54.00	18.01	V
11869.650	35.39	-32.13	39.15	28.37	54.00	18.61	V
11864.700	35.05	-32.13	39.15	28.03	54.00	18.95	H

Channel 209

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17962.650	40.67	-29.55	45.95	24.27	54.00	13.33	H
17920.800	40.34	-29.55	45.95	23.94	54.00	13.66	V
13299.750	36.17	-31.62	40.60	27.19	54.00	17.83	H
13300.650	36.09	-31.62	40.60	27.11	54.00	17.91	V
12693.150	35.36	-31.50	39.50	27.36	54.00	18.64	H
11868.750	35.31	-32.13	39.15	28.29	54.00	18.69	V

Channel 233

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17968.500	40.74	-29.55	45.95	24.34	54.00	13.26	H
17981.550	40.67	-29.55	45.95	24.27	54.00	13.33	H
13308.750	36.10	-31.62	40.60	27.12	54.00	17.90	V
13305.150	36.07	-31.62	40.60	27.09	54.00	17.93	V
7125.027	61.74	-25.93	35.70	51.97	68.20	6.46	V
7125.060	61.55	-25.93	35.70	51.78	68.20	6.65	V

802.11be-40M

Channel 3

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17970.300	39.48	-29.55	45.95	23.08	54.00	14.52	V
17937.450	39.45	-29.55	45.95	23.05	54.00	14.55	H
13301.100	34.53	-31.62	40.60	25.55	54.00	19.47	V
13336.650	34.52	-31.26	40.65	25.13	54.00	19.48	V
5918.568	40.21	-27.15	34.30	33.06	68.20	27.99	V
5917.826	40.14	-27.15	34.30	32.99	68.20	28.06	V

Channel 43

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17957.250	39.55	-29.55	45.95	23.15	54.00	14.45	H
17966.250	39.38	-29.55	45.95	22.98	54.00	14.62	V
13342.500	34.40	-31.26	40.65	25.01	54.00	19.60	V
13305.150	34.32	-31.62	40.60	25.34	54.00	19.68	V
12686.850	33.51	-31.50	39.50	25.51	54.00	20.49	V
12698.550	33.46	-31.50	39.50	25.46	54.00	20.54	V

Channel 91

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17985.600	39.59	-29.55	45.95	23.19	54.00	14.41	V
17979.300	39.57	-29.55	45.95	23.17	54.00	14.43	V
14498.550	34.54	-30.35	41.90	22.99	54.00	19.46	V
13312.350	34.33	-31.62	40.60	25.35	54.00	19.67	V
11869.200	33.46	-32.13	39.15	26.44	54.00	20.54	V
12686.850	33.35	-31.50	39.50	25.35	54.00	20.65	H

Channel 99

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17980.650	40.13	-29.55	45.95	23.73	54.00	13.87	V
17976.600	40.08	-29.55	45.95	23.68	54.00	13.92	V
13351.950	35.83	-31.26	40.65	26.44	54.00	18.17	V
13293.900	35.74	-31.62	40.60	26.76	54.00	18.26	V
11884.950	34.75	-32.63	39.10	28.28	54.00	19.25	V
11872.800	34.66	-32.13	39.15	27.64	54.00	19.34	V

Channel 107

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17950.950	36.41	-29.55	45.95	20.01	54.00	17.59	H
17971.200	36.37	-29.55	45.95	19.97	54.00	17.63	V
13306.050	33.63	-31.62	40.60	24.65	54.00	20.37	V
13296.600	33.62	-31.62	40.60	24.64	54.00	20.38	V
11882.250	32.82	-32.63	39.10	26.35	54.00	21.18	H
11887.650	32.77	-32.63	39.10	26.30	54.00	21.23	V

Channel 115

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17959.950	36.41	-29.55	45.95	20.01	54.00	17.59	V
17987.850	36.32	-29.55	45.95	19.92	54.00	17.68	H
13278.600	33.46	-31.62	40.60	24.48	54.00	20.54	V
13275.000	33.40	-31.62	40.60	24.42	54.00	20.60	V
12698.550	33.08	-31.50	39.50	25.08	54.00	20.92	V
9001.350	33.03	-33.59	37.70	28.92	54.00	20.97	V

Channel 123

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17964.900	40.34	-29.55	45.95	23.94	54.00	13.66	H
17973.000	40.10	-29.55	45.95	23.70	54.00	13.90	H
13296.600	35.57	-31.62	40.60	26.59	54.00	18.43	H
13329.000	35.56	-31.26	40.65	26.17	54.00	18.44	V
10980.900	34.90	-33.43	38.55	29.78	54.00	19.10	V
11872.800	34.84	-32.13	39.15	27.82	54.00	19.16	V

Channel 155

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17957.700	40.38	-29.55	45.95	23.98	54.00	13.62	V
17933.850	40.23	-29.55	45.95	23.83	54.00	13.77	V
13342.050	35.66	-31.26	40.65	26.27	54.00	18.34	V
13308.750	35.54	-31.62	40.60	26.56	54.00	18.46	H
12290.400	34.71	-31.98	39.00	27.69	54.00	19.29	H
11862.000	34.67	-32.13	39.15	27.65	54.00	19.33	H

Channel 179

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17962.650	40.42	-29.55	45.95	24.02	54.00	13.58	H
17968.500	40.24	-29.55	45.95	23.84	54.00	13.76	H
13280.850	35.75	-31.62	40.60	26.77	54.00	18.25	V
13300.650	35.56	-31.62	40.60	26.58	54.00	18.44	V
11866.500	34.72	-32.13	39.15	27.70	54.00	19.28	V
11865.150	34.68	-32.13	39.15	27.66	54.00	19.32	H

Channel 211

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17971.650	41.11	-29.55	45.95	24.71	54.00	12.89	H
17979.300	40.85	-29.55	45.95	24.45	54.00	13.15	H
13320.900	36.60	-31.26	40.65	27.21	54.00	17.40	V
13323.600	36.57	-31.26	40.65	27.18	54.00	17.43	H
11873.700	35.84	-32.13	39.15	28.82	54.00	18.16	H
11860.650	35.80	-32.13	39.15	28.78	54.00	18.20	V

Channel 227

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17948.700	41.14	-29.55	45.95	24.74	54.00	12.86	H
17941.950	40.86	-29.55	45.95	24.46	54.00	13.14	H
13303.800	36.66	-31.62	40.60	27.68	54.00	17.34	H
13314.600	36.57	-31.62	40.60	27.59	54.00	17.43	V
7223.400	43.66	-25.94	36.20	33.40	68.20	24.54	V
7224.258	43.56	-25.94	36.20	33.30	68.20	24.64	H

802.11be-80M

Channel 7

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17976.150	39.62	-29.55	45.95	23.22	54.00	14.38	H
17966.250	39.54	-29.55	45.95	23.14	54.00	14.46	V
13335.750	34.73	-31.26	40.65	25.34	54.00	19.27	V
13350.150	34.67	-31.26	40.65	25.28	54.00	19.33	V
5908.110	40.04	-27.15	34.30	32.89	68.20	28.16	V
5887.964	40.03	-27.12	34.20	32.95	68.20	28.17	V

Channel 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17950.950	39.59	-29.55	45.95	23.19	54.00	14.41	H
17969.850	39.56	-29.55	45.95	23.16	54.00	14.44	V
14498.550	34.62	-30.35	41.90	23.07	54.00	19.38	V
14495.850	34.59	-30.35	41.90	23.04	54.00	19.41	H
11867.400	34.13	-32.13	39.15	27.11	54.00	19.87	V
12684.150	33.71	-31.50	39.50	25.71	54.00	20.29	V

Channel 87

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17976.150	39.64	-29.55	45.95	23.24	54.00	14.36	V
17976.600	39.63	-29.55	45.95	23.23	54.00	14.37	V
14499.000	34.90	-30.35	41.90	23.35	54.00	19.10	H
14497.650	34.71	-30.35	41.90	23.16	54.00	19.29	V
12692.250	33.80	-31.50	39.50	25.80	54.00	20.20	V
11849.850	33.65	-32.13	39.15	26.63	54.00	20.35	V

Channel 103

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17958.150	35.99	-29.55	45.95	19.59	54.00	18.01	V
17962.650	35.57	-29.55	45.95	19.17	54.00	18.43	V
13318.200	33.24	-31.26	40.65	23.85	54.00	20.76	V
13265.550	33.16	-31.65	40.50	24.31	54.00	20.84	V
11860.200	33.05	-32.13	39.15	26.03	54.00	20.95	V
11858.400	32.99	-32.13	39.15	25.97	54.00	21.01	V

Channel 119

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17939.700	40.42	-29.55	45.95	24.02	54.00	13.58	V
17963.550	40.33	-29.55	45.95	23.93	54.00	13.67	H
13320.000	35.67	-31.26	40.65	26.28	54.00	18.33	H
13296.150	35.64	-31.62	40.60	26.66	54.00	18.36	H
11887.650	34.88	-32.63	39.10	28.41	54.00	19.12	H
12590.100	34.79	-31.43	39.30	26.92	54.00	19.21	V

Channel 151

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17964.900	40.35	-29.55	45.95	23.95	54.00	13.65	H
17959.500	40.30	-29.55	45.95	23.90	54.00	13.70	H
13275.000	35.70	-31.62	40.60	26.72	54.00	18.30	V
13317.750	35.62	-31.26	40.65	26.23	54.00	18.38	H
12186.000	34.82	-31.97	38.90	27.89	54.00	19.18	H
11857.050	34.78	-32.13	39.15	27.76	54.00	19.22	V

Channel 183

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17976.150	40.46	-29.55	45.95	24.06	54.00	13.54	H
17959.500	40.24	-29.55	45.95	23.84	54.00	13.76	V
13299.300	35.84	-31.62	40.60	26.86	54.00	18.16	V
13333.500	35.77	-31.26	40.65	26.38	54.00	18.23	V
12601.800	35.34	-31.43	39.30	27.47	54.00	18.66	H
12605.850	35.00	-31.43	39.30	27.13	54.00	19.00	V

Channel 199

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17974.350	40.98	-29.55	45.95	24.58	54.00	13.02	H
17998.200	40.87	-29.55	45.95	24.47	54.00	13.13	V
13300.650	36.77	-31.62	40.60	27.79	54.00	17.23	V
13336.650	36.66	-31.26	40.65	27.27	54.00	17.34	H
11862.900	35.92	-32.13	39.15	28.90	54.00	18.08	V
11871.450	35.83	-32.13	39.15	28.81	54.00	18.17	V