

FCC PART 15E TEST REPORT FOR CERTIFICATION On Behalf of

Hui Zhou Gaoshengda Technology Co.,LTD

WIFI+BT Module

Model Number: DT3HR1601

FCC ID: 2AC23-DT2H

Applicant:	Hui Zhou GaoshengdaTechnology Co.,LTD
Address:	No.6 Qiaoguang Road, Chenjiang Street, Zhongkai High-tech
	Zone, Huizhou City, Guangdong Province, China.
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan,
	Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2609327
Date of Test:	Sep. 30, 2026 to Oct. 08, 2026
Date of Report:	Oct. 08, 2026

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. The antenna information for EUT	6
1.3. Information of RF Cable	6
2. SUMMARY OF TEST	7
2.1. Summary of test result	7
2.2. Test Facilities.....	8
2.3. Measurement uncertainty	9
2.4. Assistant equipment used for test	9
2.5. Block Diagram	9
2.6. Test Mode	10
2.7. Channel List.....	11
2.8. Power Setting of Test Software	12
2.9. Duty Cycle of Test Signal	13
2.10. Test Equipment List.....	14
3. 6dB BANDWIDTH & 26dB BANDWIDTH & 99% OCCUPIED BANDWIDTH	15
3.1. Limit.....	15
3.2. Test Setup.....	15
3.3. Spectrum Analyzer Setting.....	15
3.4. Test Procedure.....	16
3.5. Test Result.....	16
4. MAXIMUM CONDUCTED OUTPUT POWER	17
4.1. Limit.....	17
4.2. Test Setup.....	17
4.3. Spectrum Analyzer Setting.....	17
4.4. Test Procedure.....	18
4.5. Test Result.....	18
5. PEAK POWER SPECTRAL DENSITY	19
5.1. Limit.....	19
5.2. Test Setup.....	19
5.3. Spectrum Analyzer Setting.....	19
5.4. Test Procedure.....	19
5.5. Test Result.....	19
6. UNWANTED EMISSIONS AND BAND EDGE	20
6.1. Limit.....	20
6.2. Test Setup.....	21
6.3. Spectrum Analyzer Setting.....	22
6.4. Test Procedure.....	23
6.5. Test Result.....	24
7. FREQUENCY STABILITY	57
7.1. Limit.....	57
7.2. Test Setup.....	57

7.3. Spectrum Analyzer Setting.....	57
7.4. Test Procedure.....	58
7.5. Test Result.....	58
8. AC POWER LINE CONDUCTED EMISSIONS	59
8.1. Limit.....	59
8.2. Test Setup.....	59
8.3. Spectrum Analyzer Setting.....	59
8.4. Test Procedure.....	59
8.5. Test Result.....	60
9. ANTENNA REQUIREMENTS.....	62
9.1. Limit.....	62
9.2. Test Result.....	62
10. TEST SETUP PHOTO.....	63
11. EUT PHOTO	65

Applicant: Hui Zhou Gaoshengda Technology Co.,LTD
Address: No.2, Jin-da Road, Huinan High-tech Industrial Park,
Huizhou City, Guangdong, China

Manufacturer: Hui Zhou Gaoshengda Technology Co.,LTD
Address: No.2, Jin-da Road, Huinan High-tech Industrial Park,
Huizhou City, Guangdong, China

E.U.T: WIFI+BT Module

Model Number: DT3HR1601

Power Supply: DC 3.3V From PC

Trade Name: GSD **Sample No.:** EST-260930008-001

Date of Receipt: Sep. 30, 2026 **Date of Test:** Sep. 30, 2026 to
Oct. 08, 2026

Test Specification: FCC Part 15 Subpart E 15.407
ANSI C63.10:2020
FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01
FCC KDB 662911 D01 Multiple Transmitter Output v02r01

Test Result: The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart E requirements.


This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.

Date: Oct. 09, 2026

Prepared by:

Reviewed by:

Approved by:


Ring Yang / Assistant


Seven Wang / Engineer


Iceman Hu / Manager

Other Aspects:

None.

Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested

This test report is based on a single evaluation of one sample of above mentioned products, It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd. The statement of compliance in this report is based on the limit in the test standard, the measurement uncertainty is not considered.

1.GENERAL INFORMATION

1.1.Description of Device (EUT)

FCC ID	:	2AC23-DT2H
Product Name	:	WIFI+BT Module
Model Number	:	DT3HR1601
Software Version	:	N/A
Hardware Version	:	N/A
Operation frequency	:	U-NII-1: 5150 MHz~5250 MHz U-NII-2A: 5250 MHz~5350 MHz U-NII-2C: 5470 MHz~5725 MHz U-NII-3: 5725 MHz~5850 MHz
Number of channel	:	U-NII-1: IEEE 802.11a / n HT20: 4 Channels; IEEE 802.11n HT40: 2 Channels; U-NII-2A: IEEE 802.11a / n HT20: 4 Channels; IEEE 802.11n HT40: 2 Channels; U-NII-2C: IEEE 802.11a / n HT20: 11 Channels; IEEE 802.11n HT40: 5 Channels; U-NII-3: IEEE 802.11a / n HT20: 5 Channels; IEEE 802.11n HT40: 2 Channels;
Modulation	:	OFDM
Transmit Data Rate	:	IEEE 802.11a: 54, 48, 36, 24, 18, 12, 9, 6Mbps; IEEE 802.11n: up 150Mbps
Channels Spacing	:	IEEE 802.11a: 20MHz; IEEE 802.11n HT20: 20MHz; IEEE 802.11n HT40: 40MHz
Transmit Power	:	5150MHz~5250MHz U-NII-1 IEEE 802.11a: 18.05dBm IEEE 802.11n HT20: 18.19dBm IEEE 802.11n HT40: 17.73dBm
	:	5250MHz~5350MHz U-NII-2A IEEE 802.11a: 15.37dBm IEEE 802.11n HT20: 15.44dBm IEEE 802.11n HT40: 15.50dBm
	:	5470MHz~5725MHz U-NII-2C IEEE 802.11a: 15.50dBm IEEE 802.11n HT20: 15.55dBm IEEE 802.11n HT40: 15.14dBm
	:	5725MHz~5850MHz U-NII-3 IEEE 802.11a: 11.38dBm IEEE 802.11n HT20: 11.24dBm IEEE 802.11n HT40: 11.60dBm
Sample Type	:	Prototype production
Note: The product information is provided by the manufacturer. The laboratory is not responsible for this data.		

1.2.The antenna information for EUT

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	Metal	-	2.57

Note:

- 1.The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.
- 2.The test results of this report only apply to the sample as received.

1.3.Information of RF Cable

Cable Loss(dB)	Provided by
1.0	Hui Zhou Gaoshengda Technology Co.,LTD

Note:

- 1.The customer declared the loss value of the RF Cable. and the test results of this report only apply to the sample as received.
- 2.The laboratory is not responsible for the accuracy of the cable loss.

2.SUMMARY OF TEST

2.1.Summary of test result

No.	Description of Test Item	FCC Standard Section	Results
1	6dB Bandwidth & 26dB Bandwidth & 99% Occupied Bandwidth	15.407(a) 15.407(e)	PASS
2	Maximum Conducted Output Power	15.407(a)	PASS
3	Peak Power Spectral Density	15.407(a)	PASS
4	Unwanted Emissions and Band Edge	15.205 15.209 15.407(b)	PASS
5	Frequency Stability	15.407(g)	PASS
6	AC Power Line Conducted Emissions	15.207 15.407(b)(9)	PASS
7	Antenna Requirement	15.203	PASS

Note:"N/A" denotes test is not applicable in this test report.

2.2.Test Facilities

EMC Lab : Accredited by CNAS, CHINA
Registration No.: L5288
This Accreditation is valid until: November 12, 2029

Recognized by FCC, USA
Designation Number: CN1215
This Recognition is valid until: January 31, 2028

Accredited by A2LA, USA
Registration No.: 4366.01
This Accreditation is valid until: January 31, 2028

Recognized by Industry Canada
CAB identifier No.: CN0035
This Recognition is valid until: January 31, 2028

Recognized by VCCI, Japan
Registration No.:C-14103; T-20073; R-13663;
R-20103; G-20097
Date of registration: Apr. 20, 2026
This Recognition is valid until: Apr. 19, 2029

Recognized by TUV Rheinland, Germany
Registration No.: UA 50413872 0001
Date of registration: July 31, 2018

Recognized by Intertek
Registration No.: 2011-RTL-L2-64
Date of registration: November 08, 2018

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan,
Guangdong, China

2.3.Measurement uncertainty

Test Item	Uncertainty
Uncertainty for conducted RF Power	0.53dB
Uncertainty for Conduction emission test	0.46dB
Uncertainty for Power density test	0.46dB
Uncertainty for radio frequency	2×10^{-5}
Uncertainty for spurious emissions test (9kHz-30MHz)	± 2.88

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


2.4.Assistant equipment used for test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
A	Laptop computer	-	Think pad E485	-	PF-1E3QZY

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	0.5m	AC Cable

2.5.Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground.



DC 3.3V From PC

(EUT: WIFI+BT Module)

2.6.Test Mode

Pre-scan has been combined all possible modulations and data rates to determine the worst case test mode,the worst case test mode was selected for the final test as listed below.

Test Item	Test Mode	Channel	Modulation	Data rate
6dB Bandwidth	IEEE 802.11a	149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	151/159	OFDM	MCS0
26dB Bandwidth	IEEE 802.11a	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/118/134	OFDM	MCS0
99% Occupied Bandwidth	IEEE 802.11a	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/118/134/151/159/134/151/159	OFDM	MCS0
Maximum Conducted Output Power	IEEE 802.11a	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/118/134/151/159	OFDM	MCS0
Peak Power Spectral Density	IEEE 802.11a	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/118/134/151/159	OFDM	MCS0
Unwanted Emissions and Band Edge(Above 1GHz)	IEEE 802.11a	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/118/134/151/159	OFDM	MCS0
Unwanted Emissions Below 1GHz	IEEE 802.11a	100	OFDM	6Mbps
Frequency Stability	Unmodulation	36/64/100/149	N/A	N/A
AC Power Line Conducted Emissions	IEEE 802.11a	100	OFDM	6Mbps

Note: In radiated measurement,the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane**.

2.7.Channel List

Band	Mode	Channel	Frequency (MHz)
5150MHz~5250MHz U-NII-1	IEEE 802.11a & n HT20	36	5180
		40	5200
		44	5220
		48	5240
	IEEE 802.11n HT40	38	5190
		46	5230
5250MHz~5350MHz U-NII-2A	IEEE 802.11a & n HT20	52	5260
		56	5280
		60	5300
		64	5320
	IEEE 802.11n HT40	54	5270
		62	5310
5470MHz~5725MHz U-NII-2C	IEEE 802.11a & n HT20	100	5500
		104	5520
		108	5540
		112	5560
		116	5580
		120	5600
		124	5620
		128	5640
		132	5660
		136	5680
	IEEE 802.11n HT40	140	5700
		102	5510
		110	5550
		118	5590
		126	5630
		134	5670
5725MHz~5850MHz U-NII-3	IEEE 802.11a & n HT20	149	5745
		153	5765
		157	5785
		161	5805
		165	5825
	IEEE 802.11n HT40	151	5755
		159	5795

2.8.Power Setting of Test Software

Software Name	MTool		
U-NII-1			
Frequency(MHz)	5180	5200	5240
IEEE 802.11a Setting	16	16	16
IEEE 802.11n HT20 Setting	16	16	16
Frequency(MHz)	5190	5230	
IEEE 802.11n HT40 Setting	16	16	
U-NII-2A			
Frequency(MHz)	5260	5300	5320
IEEE 802.11a Setting	14	14	14
IEEE 802.11n HT20 Setting	14	14	14
Frequency(MHz)	5270	5310	
IEEE 802.11n HT40 Setting	14	14	
U-NII-2C			
Frequency(MHz)	5500	5580	5700
IEEE 802.11a Setting	13	13	14
IEEE 802.11n HT20 Setting	13	13	14
Frequency(MHz)	5510	5590	5670
IEEE 802.11n HT40 Setting	14	14	14
U-NII-3			
Frequency(MHz)	5745	5785	5825
IEEE 802.11a Setting	10	10	10
IEEE 802.11n HT20 Setting	10	10	10
Frequency(MHz)	5755	5795	
IEEE 802.11n HT40 Setting	10	10	

Note: This information is provided by the applicant.

2.9.Duty Cycle of Test Signal

Refer to Appendix B of Appendix FCC ID 5G Wi-Fi (the test data).

Note:

1. Duty Cycle=On Time/Total Time×100%.
2. Duty Factor=10×LOG(1/Duty Cycle).
3. If duty cycle <98 %, the conducted average output power and average power spectral density should be add duty factor.
4. If duty cycle ≥98 %,the EUT is consider to be transmitting continuously,the conducted average output power and average power spectral density no need to add duty factor.
5. The on-time time is transmission duration(T).
6. The VBW Setting is use for RMS measurement in Unwanted Emissions and Band Edge(Above 1GHz) Test.

2.10.Test Equipment List

For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESCI3	EST-E071	Jun. 11, 2026	Jun. 10, 2027
Artificial Mains Network	Rohde & Schwarz	ENV216	EST-E048	Jun. 11, 2026	Jun. 10, 2027
Artificial Mains Network	Rohde & Schwarz	ENV216	EST-E072	Jun. 11, 2026	Jun. 10, 2027
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	EST-E078	Jun. 11, 2026	Jun. 10, 2027
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A

NOTE: Test uncertainty: $\pm 3.42\text{dB}$ at a level of confidence of 95%.(2#CE)

For radiated emission test(9kHz-30MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR3	EST-E049	Jun. 11, 2026	Jun. 10, 2027
Active Loop Antenna	SCHWAREBECK	FMZB 1519B	EST-E054	Jun. 11, 2026	Jun. 10, 2027
Cable	/	/	EST-E314	Jun. 11, 2026	Jun. 10, 2027
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A

For radiated emissions test (30MHz-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR3	EST-E049	Jun. 11, 2026	Jun. 10, 2027
Bilog Antenna	Teseq	CBL 6111D	EST-E053	Jun. 11, 2026	Jun. 10, 2027
Cable	/	/	EST-E314	Jun. 11, 2026	Jun. 10, 2027
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A

Note: Test uncertainty: $\pm 4.26\text{ dB (H)}$; $\pm 4.74\text{ dB (V)}$ at a level of confidence of 95%.(2#966)

For radiated emission test(Above 1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	SCHWARZBECK	BBHA9120D	EST-E144	Jun. 11, 2026	Jun. 10, 2027
Horn Antenna	Com-Power	AHA-840	EST-E133	Jun. 11, 2026	Jun. 10, 2027
Low Noise Amplifier	RF	TRLA-010180G45N	EST-E142	Jun. 11, 2026	Jun. 10, 2027
Spectrum Analyzer	Rohde &Schwarz	FSV40	EST-E069	Jun. 11, 2026	Jun. 10, 2027
1#966Cable	/	/	EST-E330	Jun. 11, 2026	Jun. 10, 2027
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A

Note: Test uncertainty: $\pm 5.08\text{ dB (1GHz-18GHz)}$; $\pm 5.10\text{ dB (18GHz-40GHz)}$ at a level of confidence of 95%.

For connect EUT antenna terminal test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
TS 1120	Tonscend	/	/	/	/
Test Software	Tonscend	TS1120-3	3.5.39	/	/
RF Control Unit	Tonscend	JS0806-2	EST-E134	Jun. 11, 2026	Jun. 10, 2027
Signal and Spectrum Analyzer	Keysight	N9010B	EST-E143	Jun. 11, 2026	Jun. 10, 2027


Note: All calibration reports of the equipment were provided by LiSai calibration and Testing

3.6dB BANDWIDTH &26dB BANDWIDTH & 99% OCCUPIED BANDWIDTH

3.1.Limit

Band	Frequency (MHz)	Test Item	Limit
U-NII-1	5150-5250	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-2A	5250-5350	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-2C	5470-5725	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-3	5725-5850	6dB Bandwidth&99% Occupied Bandwidth	6dB Bandwidth≥500KHz

3.2.Test Setup



3.3.Spectrum Analyzer Setting

6dB Bandwidth	
Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	40MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

26dB Bandwidth	
Spectrum Parameters	Setting
RBW	approximately 1% of the emission bandwidth
VBW	>RBW
Span	40MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

99% Occupied Bandwidth	
Spectrum Parameters	Setting
RBW	1% to 5% of the OBW
VBW	approximately three times the RBW
Span	between 1.5 times and 5.0 times the OBW
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

3.4.Test Procedure

For 26dB Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, measure the maximum width of the emission that is 26 dB down from the peak of the emission.Compare this with the RBW setting of the instrument.
Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

For 6dB Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

For 99% Occupied Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the 99% power bandwidth function to measure bandwidth.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

3.5.Test Result

Refer to Appendix A1/A2/A3 of Appendix FCC ID 5G Wi-Fi (the test data).


4.MAXIMUM CONDUCTED OUTPUT POWER

4.1.Limit

Band	EUT Type	Limit
U-NII-1	Outdoor Access Point	1W(30dBm) (Max. e.i.r.p $\leq$ 125mW at any elevation angle above 30 degrees as measured from the horizon)
	Indoor Access Point	1W(30dBm)
	Fixed point-to-point Access Point	1W(30dBm)
	Mobile and Portable Client Device	250mW(23.98dBm)
U-NII-2A	All Device	250mW(23.98dBm) or 11dBm+10 log B,Which is lesser. (B is 26dB Bandwidth in MHz)
U-NII-2C	All Device	250mW(23.98dBm) or 11dBm+10 log B,Which is lesser. (B is 26dB Bandwidth in MHz)
U-NII-3	All Device	1W(30dBm)

Note: For the Band U-NII-2A and U-NII-2C,the maximum conducted output power limit calculate result refer to section 3.5.

4.2.Test Setup



4.3.Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	1MHz
VBW	3MHz
Span	40MHz(20MHz Bandwidth mode) 80MHz(40MHz Bandwidth mode) 160MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	RMS
Trace Mode	Max Hold

4.4.Test Procedure

- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 4.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Use the channel power function to measure maximum peak output power, allow trace to stabilize, save test pictures.
- e. Repeat above procedures until all modes and channels were measured.
- f. Record the results in the test report.

4.5.Test Result

Refer to Appendix C of Appendix FCC ID 5G Wi-Fi (the test data).

5. PEAK POWER SPECTRAL DENSITY

5.1. Limit

Band	EUT Type	Limit
U-NII-1	Outdoor Access Point	17dBm/MHz
	Indoor Access Point	17dBm/MHz
	Fixed point-to-point Access Point	17dBm/MHz
	Mobile and Portable Client Device	11dBm/MHz
U-NII-2A	All Device	11dBm/MHz
U-NII-2C	All Device	11dBm/MHz
U-NII-3	All Device	30dBm/500KHz

5.2. Test Setup



5.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	1MHz(For U-NII-1&U-NII-2A&U-NII-2C) 500KHz(For U-NII-3)
VBW	3MHz(For U-NII-1&U-NII-2A&U-NII-2C) 2MHz(For U-NII-3)
Span	encompass the entire 26 dB EBW or 99% OBW of the signal
Sweep Time	Auto
Number of Sweep Point	$\geq 2 \times \text{SPAN} / \text{RBW}$
Detector	RMS(power averaging)
Trace Average	≥ 100 traces

5.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 5.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker-to-peak function to set the marker to the average of the emission.
- If the duty cycle of test signal $< 98\%$, the result = max measured value + $10 \times \log(1/\text{duty cycle})$;
If the duty cycle of test signal $\geq 98\%$, the result = max measured value.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

5.5. Test Result

Refer to Appendix D of Appendix FCC ID 5G Wi-Fi (the test data).

6.UNWANTED EMISSIONS AND BAND EDGE

6.1.Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The unwanted emissions which fall in Restricted bands shall not exceed the field strength levels specified in the following table:

15.209 Radiated emission limits

Frequency (MHz)	Field Strength(μ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Note:

1. $\text{dB}\mu\text{V/m} = 20\text{Log}(\mu\text{V/m})$
2. Above 1GHz the formula is used to convert the EIRP to field strength


$$E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{m}]) + 104.77$$

where E is field strength and d is distance at which the field strength limit is specified in the applicable requirements.


for example, 3m field strength($\text{dB}\mu\text{V/m}$)= $\text{EIRP} - 20\log(3) + 104.77 = \text{EIRP} + 95.2$

6.2.Test Setup


9kHz~30MHz



30~1000MHz



Above 1GHz



6.3.Spectrum Analyzer Setting

For 9KHz-150KHz

Spectrum Parameters	Setting
RBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
VBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
Start frequency	9KHz
Stop frequency	150KHz
Sweep Time	Auto
Detector	PEAK/QP/AVG
Trace Mode	Max Hold

Note : For 9KHz-90KHz&110KHz-150KHz,the detector is average,other frequency is CISPR QP detector.

For 150KHz-30MHz

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

Note : For 150KHz-490KHz,the detector is average,other frequency is CISPR QP detector.

For 30MHz-1GHz

Spectrum Parameters	Setting
RBW	120KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	1GHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For Above 1GHz

Spectrum Parameters	Setting	
RBW	1MHz	
VBW	PEAK Measurement	AVG Measurement
	3MHz	Duty cycle $\geq$ 98%,VBW=10Hz Duty cycle<98%,VBW $\geq$ 1/T Video bandwidth mode=RMS (power averaging)
Start frequency	1GHz	
Stop frequency	40GHz	

Sweep Time	Auto
Detector	PEAK
Trace Mode	Max Hold

Note: T is the on-time of the duty cycle, when EUT is continuously emitted Maximum output power, in seconds. Refer to Section 2.8 on time.

6.4.Test Procedure

- a. EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test, and which is 1.5 meter high above ground for above 1GHz test.
- b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- c. Set the EUT transmit continuously with maximum output power.
- d. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- e. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- f. Spectrum analyzer setting parameters in accordance with section 6.3.
- g. Repeat above procedures until all channels were measured.
- h. Record the results in the test report.
- i. IEEE 802.11a, IEEE 802.11n HT20, IEEE 802.11n HT40 all have been tested, only worst case IEEE 802.11n HT40 is recorded.

6.5. Test Result

Radiated Emissions Below 1GHz


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 73

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (118)

Date: 2026-10-08




Site no. : 1# 966 Chamber Data no. : 73
Dis. / Ant. : 3m 1#966 ANT 37062 Ant. pol. : VERTICAL
Limit : FCC PART 15 C(3M)
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : TX Mode

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	94.02	9.70	7.12	42.05	54.95	29.72	43.50	13.78	QP
2	101.78	11.30	7.11	42.00	53.93	30.34	43.50	13.16	QP
3	115.36	11.20	6.65	41.96	51.98	27.87	43.50	15.63	QP
4	239.52	11.18	8.05	41.66	56.42	33.99	46.00	12.01	QP
5	398.60	16.00	8.82	41.70	52.41	35.53	46.00	10.47	QP
6	797.27	22.36	10.34	41.50	39.29	30.49	46.00	15.51	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878



Site no. : 1# 966 Chamber Data no. : 74
Dis. / Ant. : 3m 1#966 ANT 37062 Ant. pol. : HORIZONTAL
Limit : FCC PART 15 C(3M)
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : TX Mode

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	94.02	9.70	7.12	42.05	56.79	31.56	43.50	11.94	QP
2	107.60	11.10	6.91	41.98	56.46	32.49	43.50	11.01	QP
3	115.36	11.20	6.65	41.96	58.10	33.99	43.50	9.51	QP
4	238.55	11.07	8.05	41.66	61.14	38.60	46.00	7.40	QP
5	274.44	12.40	8.23	41.62	53.25	32.26	46.00	13.74	QP
6	399.57	16.00	8.83	41.70	54.63	37.76	46.00	8.24	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All channels had been pre-test,only the worst case was reported.

Radiated Emissions Above 1G


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 83

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\T\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 83
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5795MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7732.00	36.40	10.39	40.49	41.18	47.48	74.00	26.52	Peak
2	9364.00	39.23	11.41	39.88	39.15	49.91	74.00	24.09	Peak
3	11421.00	40.40	12.71	38.49	36.87	51.49	74.00	22.51	Peak
4	13223.00	40.28	13.95	36.90	35.35	52.68	68.20	15.52	Peak
5	13580.00	40.98	14.16	37.22	35.35	53.27	68.20	14.93	Peak
6	14124.00	41.56	14.39	37.79	36.05	54.21	68.20	13.99	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 84

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 84
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5795MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	9806.00	39.40	11.71	39.61	38.25	49.75	68.20	18.45	Peak
2	10605.00	39.80	12.17	39.01	38.41	51.37	74.00	22.63	Peak
3	11625.00	40.16	12.83	38.39	37.26	51.86	74.00	22.14	Peak
4	13223.00	40.28	13.95	36.90	35.14	52.47	68.20	15.73	Peak
5	13903.00	41.50	14.30	37.51	35.81	54.10	68.20	14.10	Peak
6	14549.00	41.75	14.58	38.47	37.48	55.34	68.20	12.86	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 85

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 85
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5755MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7222.00	36.47	9.97	40.85	40.69	46.28	68.20	21.92	Peak
2	7749.00	36.50	10.40	40.48	40.23	46.65	74.00	27.35	Peak
3	8718.00	38.07	11.07	40.16	39.27	48.25	68.20	19.95	Peak
4	10180.00	39.62	11.93	39.35	38.44	50.64	68.20	17.56	Peak
5	11608.00	40.30	12.82	38.39	35.96	50.69	74.00	23.31	Peak
6	13546.00	40.95	14.14	37.19	36.16	54.06	68.20	14.14	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 86

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 86
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5755MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7970.00	37.37	10.63	40.32	40.20	47.88	68.20	20.32	Peak
2	9534.00	39.10	11.51	39.78	38.58	49.41	68.20	18.79	Peak
3	11455.00	40.40	12.73	38.47	36.47	51.13	74.00	22.87	Peak
4	11795.00	39.60	12.94	38.30	36.58	50.82	74.00	23.18	Peak
5	13580.00	40.98	14.16	37.22	35.94	53.86	68.20	14.34	Peak
6	14532.00	41.83	14.57	38.44	35.88	53.84	68.20	14.36	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 87

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 87
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5670MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	10078.00	39.20	11.89	39.43	38.40	50.06	68.20	18.14	Peak
2	10860.00	39.50	12.41	38.81	39.05	52.15	74.00	21.85	Peak
3	11200.00	39.60	12.62	38.60	37.83	51.45	74.00	22.55	Peak
4	13478.00	40.82	14.11	37.13	35.17	52.97	68.20	15.23	Peak
5	13954.00	41.45	14.32	37.55	35.74	53.96	68.20	14.24	Peak
6	14532.00	41.83	14.57	38.44	35.40	53.36	68.20	14.84	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 88

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 88
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5670MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7970.00	37.37	10.63	40.32	39.55	47.23	68.20	20.97	Peak
2	9228.00	38.60	11.32	39.97	39.12	49.07	68.20	19.13	Peak
3	9568.00	39.13	11.54	39.76	38.74	49.65	68.20	18.55	Peak
4	10537.00	39.73	12.11	39.07	38.08	50.85	68.20	17.35	Peak
5	11795.00	39.60	12.94	38.30	37.52	51.76	74.00	22.24	Peak
6	13614.00	40.97	14.17	37.25	35.68	53.57	68.20	14.63	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 89

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 89
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5550MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	9976.00	39.13	11.84	39.51	38.88	50.34	68.20	17.86	Peak
2	11030.00	39.73	12.54	38.68	38.17	51.76	74.00	22.24	Peak
3	11795.00	39.60	12.94	38.30	37.31	51.55	74.00	22.45	Peak
4	13563.00	40.97	14.15	37.20	35.30	53.22	68.20	14.98	Peak
5	13988.00	41.42	14.33	37.58	35.39	53.56	68.20	14.64	Peak
6	14668.00	41.37	14.68	38.66	36.65	54.04	68.20	14.16	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 90

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 90
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5550MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	9007.00	38.00	11.19	40.10	38.80	47.89	74.00	26.11	Peak
2	9517.00	39.00	11.50	39.79	38.44	49.15	68.20	19.05	Peak
3	10520.00	39.72	12.10	39.08	37.86	50.60	68.20	17.60	Peak
4	12339.00	39.03	13.39	37.69	36.42	51.15	74.00	22.85	Peak
5	13529.00	40.93	14.13	37.17	35.93	53.82	68.20	14.38	Peak
6	14022.00	41.43	14.35	37.63	35.46	53.61	68.20	14.59	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 91

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 91
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5510MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	10231.00	39.63	11.96	39.31	38.19	50.47	68.20	17.73	Peak
2	11387.00	40.27	12.70	38.51	36.68	51.14	74.00	22.86	Peak
3	12475.00	39.02	13.52	37.49	36.36	51.41	74.00	22.59	Peak
4	13546.00	40.95	14.14	37.19	35.94	53.84	68.20	14.36	Peak
5	14515.00	41.92	14.55	38.41	35.29	53.35	68.20	14.85	Peak
6	15603.00	39.40	15.42	39.62	38.23	53.43	74.00	20.57	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 92

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 92
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5510MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	9551.00	39.20	11.53	39.77	39.78	50.74	68.20	17.46	Peak
2	10180.00	39.62	11.93	39.35	38.15	50.35	68.20	17.85	Peak
3	10860.00	39.50	12.41	38.81	38.28	51.38	74.00	22.62	Peak
4	11489.00	40.40	12.74	38.45	37.29	51.98	74.00	22.02	Peak
5	13631.00	40.93	14.18	37.26	35.51	53.36	68.20	14.84	Peak
6	14141.00	41.52	14.40	37.82	35.36	53.46	68.20	14.74	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 93

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 93
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5310MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	10537.00	39.73	12.11	39.07	38.07	50.84	68.20	17.36	Peak
2	11421.00	40.40	12.71	38.49	36.30	50.92	74.00	23.08	Peak
3	12475.00	39.02	13.52	37.49	36.87	51.92	74.00	22.08	Peak
4	13597.00	41.00	14.16	37.23	35.23	53.16	68.20	15.04	Peak
5	14056.00	41.50	14.36	37.68	36.25	54.43	68.20	13.77	Peak
6	14617.00	41.47	14.64	38.58	36.28	53.81	68.20	14.39	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 94

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 94
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5310MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	9687.00	39.50	11.63	39.69	38.58	50.02	68.20	18.18	Peak
2	11540.00	40.37	12.77	38.43	37.81	52.52	74.00	21.48	Peak
3	13002.00	39.90	13.81	36.70	35.43	52.44	68.20	15.76	Peak
4	13512.00	40.92	14.13	37.16	35.34	53.23	68.20	14.97	Peak
5	14090.00	41.57	14.37	37.74	36.02	54.22	68.20	13.98	Peak
6	15212.00	40.32	15.14	39.34	36.99	53.11	68.20	15.09	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 95

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 95
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5270MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7477.00	36.77	10.14	40.67	40.40	46.64	74.00	27.36	Peak
2	10231.00	39.63	11.96	39.31	38.58	50.86	68.20	17.34	Peak
3	11404.00	40.40	12.71	38.50	36.81	51.42	74.00	22.58	Peak
4	12152.00	39.40	13.22	37.97	36.88	51.53	74.00	22.47	Peak
5	13512.00	40.92	14.13	37.16	36.90	54.79	68.20	13.41	Peak
6	14209.00	41.52	14.42	37.93	35.61	53.62	68.20	14.58	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 96

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 96
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5270MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	8310.00	37.00	10.85	40.24	40.07	47.68	74.00	26.32	Peak
2	9551.00	39.20	11.53	39.77	38.96	49.92	68.20	18.28	Peak
3	10282.00	39.53	11.98	39.27	37.89	50.13	68.20	18.07	Peak
4	11506.00	40.40	12.75	38.45	36.73	51.43	74.00	22.57	Peak
5	12900.00	39.70	13.76	36.85	35.18	51.79	68.20	16.41	Peak
6	14005.00	41.40	14.34	37.60	35.37	53.51	68.20	14.69	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 97

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 97
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5230MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7766.00	36.50	10.42	40.47	42.26	48.71	68.20	19.49	Peak
2	9551.00	39.20	11.53	39.77	39.42	50.38	68.20	17.82	Peak
3	10265.00	39.57	11.97	39.28	38.86	51.12	68.20	17.08	Peak
4	11030.00	39.73	12.54	38.68	37.37	50.96	74.00	23.04	Peak
5	13308.00	40.20	14.00	36.97	36.37	53.60	74.00	20.40	Peak
6	14277.00	41.98	14.45	38.03	36.01	54.41	68.20	13.79	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 98

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 98
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5230MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	9228.00	38.60	11.32	39.97	38.65	48.60	68.20	19.60	Peak
2	10911.00	39.62	12.45	38.77	37.75	51.05	74.00	22.95	Peak
3	12543.00	39.00	13.57	37.39	36.37	51.55	74.00	22.45	Peak
4	13512.00	40.92	14.13	37.16	35.18	53.07	68.20	15.13	Peak
5	14413.00	42.00	14.51	38.25	35.04	53.30	68.20	14.90	Peak
6	15841.00	38.42	15.46	39.79	38.73	52.82	74.00	21.18	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 99

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 99
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5190MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	7307.00	36.10	10.03	40.79	41.14	46.48	74.00	27.52	Peak
2	9517.00	39.00	11.50	39.79	38.68	49.39	68.20	18.81	Peak
3	10996.00	39.70	12.53	38.70	37.86	51.39	74.00	22.61	Peak
4	11965.00	39.50	13.05	38.22	37.64	51.97	74.00	22.03	Peak
5	13631.00	40.93	14.18	37.26	35.09	52.94	68.20	15.26	Peak
6	14039.00	41.47	14.35	37.65	34.98	53.15	68.20	15.05	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 100

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 100
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5190MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7443.00	36.90	10.12	40.69	42.08	48.41	74.00	25.59	Peak
2	9551.00	39.20	11.53	39.77	39.31	50.27	68.20	17.93	Peak
3	10860.00	39.50	12.41	38.81	38.41	51.51	74.00	22.49	Peak
4	13546.00	40.95	14.14	37.19	36.37	54.27	68.20	13.93	Peak
5	13988.00	41.42	14.33	37.58	36.04	54.21	68.20	13.99	Peak
6	15569.00	39.23	15.41	39.60	38.29	53.33	74.00	20.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 18GHz to 40GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All test mode had been pre-test, only Low/Middle/High Channel of the worst case modulation mode was reported

Band Edge


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 17

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 17
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5190MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5150.00	32.70	8.36	41.18	48.86	48.74	54.00	5.26	Average
2	5150.00	32.70	8.36	41.18	61.90	61.78	68.20	6.42	Peak
3	5192.64	32.30	8.40	41.18	102.56	102.08	68.20	-33.88	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 18

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 18
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5190MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5150.00	32.70	8.36	41.18	44.12	44.00	68.20	24.20	Peak
2	5194.08	32.30	8.40	41.18	92.28	91.80	68.20	-23.60	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 19

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 19
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5310MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5315.99	32.47	8.50	41.17	90.90	90.70	68.20	-22.50	Peak
2	5350.00	32.60	8.52	41.16	43.69	43.65	68.20	24.55	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 20

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 20
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5310MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5314.10	32.47	8.50	41.17	102.18	101.98	68.20	-33.78	Peak
2	5350.00	32.60	8.52	41.16	50.58	50.54	54.00	3.46	Average
3	5350.00	32.60	8.52	41.16	62.79	62.75	68.20	5.45	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 21

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 21
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5510MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5470.00	32.63	8.62	41.15	63.85	63.95	68.20	4.25	Peak
2	5515.58	32.87	8.67	41.15	103.62	104.01	68.20	-35.81	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 22

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)



Site no. : 1# 966 Chamber Data no. : 22
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5510MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5470.00	32.63	8.62	41.15	43.45	43.55	68.20	24.65	Peak
2	5511.88	32.90	8.65	41.15	91.81	92.21	68.20	-24.01	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 23

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 23
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5670MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5668.16	32.65	8.81	41.13	89.25	89.58	68.20	-21.38	Peak
2	5725.00	32.80	8.86	41.13	41.29	41.82	68.20	26.38	Peak
3	7250.00	36.40	10.00	40.82	41.95	47.53	68.20	20.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 24

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 24
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5670MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5663.92	32.70	8.79	41.13	102.55	102.91	68.20	-34.71	Peak
2	5725.00	32.80	8.86	41.13	48.62	49.15	68.20	19.05	Peak
3	7250.00	36.40	10.00	40.82	40.71	46.29	68.20	21.91	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 25

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)



Site no. : 1# 966 Chamber Data no. : 25
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit :
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HRI601
Test Mode : IEEE 802.11n HT40 TX 5755MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5646.08	32.70	8.78	41.14	44.85	45.19	-----	-----	Peak
2	5689.15	32.60	8.82	41.13	47.46	47.75	-----	-----	Peak
3	5719.79	32.80	8.86	41.13	60.43	60.96	-----	-----	Peak
4	5723.84	32.80	8.86	41.13	64.80	65.33	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 26

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 26
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit :
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5755MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5646.08	32.70	8.78	41.14	42.39	42.73	-----	-----	Peak
2	5660.93	32.70	8.79	41.13	43.06	43.42	-----	-----	Peak
3	5715.20	32.70	8.84	41.13	42.63	43.04	-----	-----	Peak
4	5724.65	32.80	8.86	41.13	42.38	42.91	-----	-----	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 27

File: \\EMC-966-1\\test data\\2026\\REPORT\\RF\\TCL Duomeiti\\TCL.EM6 (122)



Site no. : 1# 966 Chamber Data no. : 27
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : HORIZONTAL
Limit :
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5795MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5850.36	32.90	8.97	41.12	42.24	42.99	-----	-----	Peak
2	5863.06	32.93	8.98	41.11	43.35	44.15	-----	-----	Peak
3	5898.87	33.00	9.01	41.11	44.17	45.07	-----	-----	Peak
4	5929.23	33.13	9.05	41.11	42.56	43.63	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 28

File: \\EMC-966-1\test data\2026\REPORT\RF\TCL Duomeiti\TCL.EM6 (122)

Date: 2026-10-08



Site no. : 1# 966 Chamber Data no. : 28
Dis. / Ant. : 3m 5#966 ANT 1002 1-18G Ant. pol. : VERTICAL
Limit :
Env. / Ins. : Temp:20.3℃;Humi:49%;Press:101.55kPa
Engineer : Aiden Yan
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : IEEE 802.11n HT40 TX 5795MHz
Sample No. :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5850.19	32.90	8.97	41.12	45.83	46.58	-----	-----	Peak
2	5858.94	32.93	8.98	41.11	46.64	47.44	-----	-----	Peak
3	5920.65	33.07	9.03	41.11	45.27	46.26	-----	-----	Peak
4	5927.25	33.13	9.05	41.11	44.37	45.44	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Band edge								
UNII BAND	Test Mode	Test Frequency (MHz)	Freq Range (MHz)	Fundamental Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Result	Antenna Pole (H/V)
U-NII-3	IEEE 802.11n HT40	5755	5645~5650	5646.08	45.19	68.2	Pass	V
			5650~5700	5689.145	47.75	97.2	Pass	
			5700~5720	5719.79	60.96	110.7	Pass	
			5720~5725	5723.84	65.33	119.6	Pass	
			5645~5650	5646.08	42.73	68.2	Pass	H
			5650~5700	5660.93	43.42	76.3	Pass	
			5700~5720	5715.2	43.04	109.5	Pass	
			5720~5725	5724.65	42.91	121.4	Pass	
		5795	5850~5855	5850.19	46.58	121.8	Pass	V
			5855~5875	5858.935	47.44	109.7	Pass	
			5875~5925	5920.645	46.26	71.4	Pass	
			5925~5935	5927.245	45.44	68.2	Pass	
			5850~5855	5850.355	42.99	121.4	Pass	H
			5855~5875	5863.06	44.15	108.5	Pass	
			5875~5925	5898.865	45.07	87.5	Pass	
			5925~5935	5929.255	43.63	68.2	Pass	

Note: All channels had been pre-test, only the worst case was reported.

18000MHz-40000MHz

Pass


Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

7.FREQUENCY STABILITY

7.1.Limit

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the operational description.

7.2.Test Setup



7.3.Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	10KHz
VBW	10KHz
Span	200KHz
Sweep Time	Auto
Detector	PEAK
Trace Mode	Max Hold

7.4.Test Procedure

For measurement frequency stability under temperature variation :

- a. Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT.
- b. Turn the EUT OFF and place it inside the environmental temperature chamber.
- c. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- d. Spectrum analyzer setting parameters in accordance with section 7.3.
- e. Set the temperature control on the chamber to the Specified temperature and allow the oscillator heater and the chamber temperature to stabilize.
- f. Turn the EUT ON with the rated voltage, and the EUT transmit continuously with maximum output power.
- g. Record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.
- h. Repeat step d through step f to measured the temperature form -20°C to +50°C in 10°C steps.

For frequency stability under voltage variation:

- a. Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT.
- b. Turn the EUT OFF and place it inside the environmental temperature chamber.
- c. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- d. Spectrum analyzer setting parameters in accordance with section 7.3.
- e. Unless otherwise specified, set the temperature control on the chamber to the ambient room temperature (+15°C to +25°C) and allow the oscillator heater and the chamber temperature to stabilize.
- f. Turn the EUT ON with the rated voltage, and the EUT transmit continuously with maximum output power.
- g. Record the operating frequency.
- h. Repeat step d through step f to measured the varied from 85% to 115% of the rated voltage.

7.5.Test Result

Refer to Appendix E of Appendix FCC ID 5G Wi-Fi (the test data).

8.AC POWER LINE CONDUCTED EMISSIONS


8.1.Limit

Frequency			Maximum RF Line Voltage	
			Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz	~	500kHz	66 ~ 56*	56 ~ 46*
500kHz	~	5MHz	56	46
5MHz	~	30MHz	60	50

Notes:

1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

8.2.Test Setup



8.3.Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP/AVG
Trace Mode	Max Hold

8.4.Test Procedure

- a. The EUT was placed on a non-metallic table, 80cm above the ground plane.
- b. The EUT Power connected to the power mains through a line impedance stabilization network.
- c. Provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs).
- d. Set the EUT transmit continuously with maximum output power.
- e. Spectrum analyzer setting parameters in accordance with section 8.3.
- f. The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2020 on Conducted Emission Test.
- g. Record the results in the test report.

8.5. Test Result


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 14

File: \\CE-2\Test Data\2026\Report\RF\TCL-高盛达\TCL-DT3HR1601.EM6 (16)

Date: 2026-10-08



Site no : 2#CE Shield Room Data no. : 14
Env. / Ins. : Temp:24.5℃;Humi:60%;Press:101.20kPa LINE Phase : NEUTRAL
Limit : FCC PART 15C QP
Engineer : Dylan Cai
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (db)	Cable Loss (db)	Reading dBuV	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.17	9.98	9.88	20.22	40.08	54.94	14.86	Average
2	0.17	9.98	9.88	31.31	51.17	64.94	13.77	QP
3	0.20	9.97	9.88	13.55	33.40	53.80	20.40	Average
4	0.20	9.97	9.88	27.96	47.81	63.80	15.99	QP
5	0.40	9.93	9.89	13.60	33.42	47.77	14.35	Average
6	0.40	9.93	9.89	18.16	37.98	57.77	19.79	QP
7	0.46	9.93	9.89	20.29	40.11	46.71	6.60	Average
8	0.46	9.93	9.89	22.19	42.01	56.71	14.70	QP
9	0.52	9.93	9.89	7.65	27.47	46.00	18.53	Average
10	0.52	9.93	9.89	12.64	32.46	56.00	23.54	QP
11	0.59	9.94	9.89	8.42	28.25	46.00	17.75	Average
12	0.59	9.94	9.89	13.63	33.46	56.00	22.54	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 16

File: \\CE-2\Test Data\2026\Report\RF\TCL-高盛达\TCL-DT3HR1601.EM6 (16)

Date: 2026-10-08



Site no : 2#CE Shield Room Data no. : 16
Env. / Ins. : Temp:24.5℃;Humi:60%;Press:101.20kPa LINE Phase : LINE
Limit : FCC PART 15C QP
Engineer : Dylan Cai
EUT : WIFI+BT Module
Power : DC 3.3V
M/N : DT3HR1601
Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (db)	Cable Loss (db)	Reading dBuV	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.19	9.98	9.88	17.34	37.20	54.24	17.04	Average
2	0.19	9.98	9.88	30.15	50.01	64.24	14.23	QP
3	0.40	9.97	9.89	14.24	34.10	47.77	13.67	Average
4	0.40	9.97	9.89	18.83	38.69	57.77	19.08	QP
5	0.46	9.96	9.89	12.78	32.63	46.71	14.08	Average
6	0.46	9.96	9.89	15.73	35.58	56.71	21.13	QP
7	0.52	9.96	9.89	10.02	29.87	46.00	16.13	Average
8	0.52	9.96	9.89	15.95	35.80	56.00	20.20	QP
9	0.92	9.96	9.91	5.79	25.66	46.00	20.34	Average
10	0.92	9.96	9.91	11.42	31.29	56.00	24.71	QP
11	1.85	10.03	9.94	5.93	25.90	46.00	20.10	Average
12	1.85	10.03	9.94	12.17	32.14	56.00	23.86	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.

9.ANTENNA REQUIREMENTS

9.1.Limit

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

9.2.Test Result

The antennas used for this product is Metal antenna, so compliance with antenna requirements. (Please refer to the EUT photo for details)

10.TEST SETUP PHOTO

Conducted Test



Radiated Test (Below 1GHz)



Radiated Test (Above 1GHz)



11.EUT PHOTO

Refer to report no. ESTE-R2609324

End of Test Report