

FCC Radio Test Report

FCC ID: 2AC2S-X8

Original Grant

Report No. : TB-FCC140907
Applicant : Wm Wireless& Mobile Ltda.
Equipment Under Test (EUT)
EUT Name : Rugged smart phone
Model No. : Rock X8
Series Model No. : N/A
Brand Name : Extrem
Receipt Date : 2014-08-11
Test Date : 2014-08-11 to 2014-08-29
Issue Date : 2014-09-03
Standards : FCC Part 15, Subpart C(15.247)
Test Method : ANSI C63.4:2003
Conclusions : **PASS**

In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC requirements

Test/Witness Engineer :

IWAN SU

Approved& Authorized :

Ray Lai



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
1.3 Block Diagram Showing the Configuration of System Tested.....	6
1.4 Description of Support Units	6
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting	7
1.7 Test Facility.....	8
2. TEST SUMMARY.....	9
3. CONDUCTED EMISSION TEST	10
3.1 Test Standard and Limit.....	10
3.2 Test Setup.....	10
3.3 Test Procedure.....	10
3.4 Test Equipment Used.....	11
3.5 EUT Operating Mode	11
3.6 Test Data.....	11
4. RADIATED EMISSION TEST	14
4.1 Test Standard and Limit.....	14
4.2 Test Setup.....	15
4.3 Test Procedure.....	16
4.4 EUT Operating Condition	16
4.5 Test Equipment	17
5. RESTRICTED BANDS REQUIREMENT	22
5.1 Test Standard and Limit.....	22
5.2 Test Setup.....	22
5.3 Test Procedure.....	22
5.4 EUT Operating Condition	23
5.5 Test Equipment	23
6. NUMBER OF HOPPING CHANNEL	36
6.1 Test Standard and Limit.....	36
6.2 Test Setup.....	36
6.3 Test Procedure.....	36
6.4 EUT Operating Condition	36
6.5 Test Equipment	36
6.6 Test Data.....	36
7. AVERAGE TIME OF OCCUPANCY.....	38
7.1 Test Standard and Limit.....	38
7.2 Test Setup.....	38
7.3 Test Procedure.....	38

7.4 EUT Operating Condition	38
7.5 Test Equipment	38
7.6 Test Data.....	39
8. CHANNEL SEPARATION AND BANDWIDTH TEST	43
8.1 Test Standard and Limit.....	43
8.2 Test Setup.....	43
8.3 Test Procedure.....	43
8.4 EUT Operating Condition	43
8.5 Test Equipment	44
8.6 Test Data.....	44
9. PEAK OUTPUT POWER TEST.....	52
9.1 Test Standard and Limit.....	52
9.2 Test Setup.....	52
9.3 Test Procedure.....	52
9.4 EUT Operating Condition	52
9.5 Test Equipment	52
9.6 Test Data.....	52
10. ANTENNA REQUIREMENT.....	59
10.1 Standard Requirement.....	59
10.2 Antenna Connected Construction	59
10.2 Result.....	59

1. General Information about EUT

1.1 Client Information

Applicant : Wm Wireless& Mobile Ltda.
Address : Calle 84#28-12 Bogota-Colombia
Manufacturer : Shenzhen Ematic Technology Co.,Ltd
Address : Hua lun Industrial Zone Phoenix Street Fu yong Town
Bao an district Shen zhen City.

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Rugged smart phone	
Models No.	:	Rock X8	
Model Difference	:	N/A	
Product Description	:	Operation Frequency: Bluetooth:2402~2480MHz	
		Number of Channel:	Bluetooth:79 Channels see note (2)
		Max Peak Output Power:	GFSK: 2.67 dBm (Conducted Power)
		Antenna Gain:	-1.0 dBi PIFA Antenna
		Modulation Type:	GFSK 1Mbps(1 Mbps) π /4-DQPSK(2 Mbps) 8-DPSK(3 Mbps)
Power Supply	:	DC power supplied by AC/DC Adapter DC Voltage supplied from Li-Polymer battery.	
Power Rating	:	AC/DC Adapter Input: AC 100~240V 50-60 Hz 0.15A Max Output: DC 5V 500mA DC 3.7V 2800mAh Li-ion battery	
Connecting I/O Port(S)	:	Please refer to the User's Manual	
Note:			

Note:


- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (2) This Test Report is FCC Part 15.247 for Bluetooth, and test procedure in accordance with Public Notice: DA 00-705.
- (3) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

(4) The Antenna information about the equipment is provided by the applicant.

1.3 Block Diagram Showing the Configuration of System Tested

TX Mode



1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/DOC	Manufacturer	Used “√”
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	YES	NO	0.8M	USB line
Cable 2	YES	NO	1.0M	Headphone line

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	TX GFSK Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	USB Charging with TX GFSK Mode
Mode 2	TX Mode(GFSK) Channel 00/39/78
Mode 3	TX Mode($\pi/4$ -DQPSK) Channel 00/39/78
Mode 4	TX Mode(8-DPSK) Channel 00/39/78
Mode 5	Hopping Mode(GFSK)
Mode 6	Hopping Mode($\pi/4$ -DQPSK)
Mode 7	Hopping Mode(8-DPSK)

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test mode above.

According to ANSI C63.4 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

TX Mode: GFSK (1 Mbps)

TX Mode: 8-DPSK (3 Mbps)

- (2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

Test Software Version	Test Program: ***3646633***		
Frequency	2402 MHz	2441MHz	2480 MHz
GFSK	DEF	DEF	DEF
$\pi/4$ -DQPSK	DEF	DEF	DEF
8-DPSK	DEF	DEF	DEF

1.7 Test Facility

The testing was performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at:

1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China.

At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

FCC List No.: (811562)

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)			
Standard Section	Test Item	Judgment	Remark
15.203	Antenna Requirement	PASS	N/A
15.207	Conducted Emission	PASS	N/A
15.205	Restricted Bands	PASS	N/A
15.247(a)(1)	Hopping Channel Separation	PASS	N/A
15.247(a)(1)	Dwell Time	PASS	N/A
15.247(b)(1)	Peak Output Power	PASS	N/A
15.247(b)(1)	Number of Hopping Frequency	PASS	N/A
15.247(c)	Radiated Spurious Emission	PASS	N/A
15.247(a)	20dB Bandwidth	PASS	N/A
Note: N/A is an abbreviation for Not Applicable.			

3. Conducted Emission Test

3.1 Test Standard and Limit

3.1.1 Test Standard

FCC Part 15.207

3.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) *Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.2 Test Setup



3.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

3.4 Test Equipment Used

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	ROHDE& SCHWARZ	ESCI	100321	Aug. 08, 2014	Aug.07, 2015
50ΩCoaxial Switch	Anritsu	MP59B	X10321	Aug. 08, 2014	Aug.07, 2015
L.I.S.N	Rohde & Schwarz	ENV216	101131	Aug. 08, 2014	Aug.07, 2015
L.I.S.N	SCHWARZBECK	NNBL 8226-2	8226-2/164	Aug. 08, 2014	Aug.07, 2015


3.5 EUT Operating Mode

Please refer to the description of test mode.

3.6 Test Data

Please see the next page.

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz for adapter		
Terminal:	Line		
Test Mode:	TX GFSK Mode 2402 MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector Comment
1		0.4586	37.43	10.29	47.72	56.72	-9.00	QP
2		0.4586	28.77	10.29	39.06	46.72	-7.66	AVG
3		2.3023	36.50	10.59	47.09	56.00	-8.91	QP
4		2.3023	32.50	10.59	43.09	46.00	-2.91	AVG
5		3.2227	39.62	10.48	50.10	56.00	-5.90	QP
6	*	3.2227	33.20	10.48	43.68	46.00	-2.32	AVG
7		4.1406	32.44	10.93	43.37	56.00	-12.63	QP
8		4.1406	25.90	10.93	36.83	46.00	-9.17	AVG
9		5.0663	32.43	10.95	43.38	60.00	-16.62	QP
10		5.0663	31.51	10.95	42.46	50.00	-7.54	AVG
11		15.9698	23.28	11.00	34.28	60.00	-25.72	QP
12		15.9698	17.42	11.00	28.42	50.00	-21.58	AVG

Emission Level= Read Level+ Correct Factor

Note: * remark the worst frequency in the range of 0.15MHz to 30MHz

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz for adapter		
Terminal:	Neutral		
Test Mode:	TX GFSK Mode 2402 MHz		
Remark:	Only worse case is reported		



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.4586	34.47	10.29	44.76	56.72	-11.96	QP	
2	0.4586	27.33	10.29	37.62	46.72	-9.10	AVG	
3	2.3023	33.54	10.59	44.13	56.00	-11.87	QP	
4 *	2.3023	31.87	10.59	42.46	46.00	-3.54	AVG	
5	3.2188	34.12	10.48	44.60	56.00	-11.40	QP	
6	3.2188	31.70	10.48	42.18	46.00	-3.82	AVG	
7	4.1406	33.98	10.93	44.91	56.00	-11.09	QP	
8	4.1406	26.88	10.93	37.81	46.00	-8.19	AVG	
9	5.0625	29.61	10.95	40.56	60.00	-19.44	QP	
10	5.0625	25.80	10.95	36.75	50.00	-13.25	AVG	
11	16.1953	26.67	11.01	37.68	60.00	-22.32	QP	
12	16.1953	20.54	11.01	31.55	50.00	-18.45	AVG	

Emission Level= Read Level+ Correct Factor

Note: * remark the worst frequency in the range of 0.15MHz to 30MHz

4. Radiated Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard
FCC Part 15.209

4.1.2 Test Limit

Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
Above 1000	74	54


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m)


4.2 Test Setup



Bellow 30MHz Test Setup



Bellow 1000MHz Test Setup



Above 1GHz Test Setup

4.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above the ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (7) For the actual test configuration, please see the test setup photo.

4.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power in TX mode.

4.5 Test Equipment


Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015
Spectrum Analyzer	Rohde & Schwarz	FSP30	DE25181	Aug. 08, 2014	Aug.07, 2015
EMI Test Receiver	Rohde & Schwarz	ESCI	101165	Aug. 08, 2014	Aug.07, 2015
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 07, 2014	Mar.06, 2015
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	11909A	185903	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	8447B	3008A00849	Mar. 07, 2014	Mar.06, 2015
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 07, 2014	Mar.06, 2015
Signal Generator	Rohde & Schwarz	SML03	IKW682-054	Feb. 11, 2014	Feb.10, 2015
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A

4.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Test data please refer the following pages.

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz for adapter		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	!	250.4858	50.40	-9.03	41.37	46.00	-4.63	QP		0
2	*	300.6988	51.30	-7.52	43.78	46.00	-2.22	QP		0
3		350.9721	44.40	-5.76	38.64	46.00	-7.36	QP		0
4		424.2998	41.10	-3.81	37.29	46.00	-8.71	QP		0
5		502.2472	40.20	-2.17	38.03	46.00	-7.97	QP		0
6		804.2522	38.20	-1.90	36.30	46.00	-9.70	QP		0

Emission Level= Read Level+ Correct Factor

Note: * remark the worst frequency in the range of 30MHz to 1000MHz

! remark the value of test frequency below 6 db margin line to limit

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz for adapter		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		300.6988	45.50	-7.52	37.98	46.00	-8.02	QP		0
2		350.9721	40.20	-5.76	34.44	46.00	-11.56	QP		0
3		401.1050	38.20	-4.45	33.75	46.00	-12.25	QP		0
4	*	509.3560	41.00	-2.14	38.86	46.00	-7.14	QP		0
5		669.9523	42.80	-3.97	38.83	46.00	-7.17	QP		0
6		754.9628	40.20	-2.32	37.88	46.00	-8.12	QP		0

Emission Level= Read Level+ Correct Factor

Note: * remark the worst frequency in the range of 30MHz to 1000MHz

! remark the value of test frequency below 6 db margin line to limit

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 DQPSK and 8DPSK mode, which indicates that the worst case is GFSK mode, so it is reported GFSK mode only.

Low channel: 2402 MHz

Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2390.00	H	50.71	---	-4.20	46.51	---	74	54	-7.49
4804.00	H	49.41	---	-3.94	45.47	---	74	54	-8.53
7206.00	H	45.20	---	0.52	45.72	---	74	54	-8.28
---	H	---	---	---	---	---	---	---	---
---	H	---	---	---	---	---	---	---	---
2390.0	V	50.71	---	-4.25	46.46	---	74	54	-7.54
4804.00	V	49.36	---	-3.94	45.42	---	74	54	-8.58
7206.00	V	44.32	---	0.59	44.91	---	74	54	-9.09
---	V	---	---	---	---	---	---	---	---
---	V	---	---	---	---	---	---	---	---

Middle channel: 2441 MHz

Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
1301.67	H	49.71	---	-4.20	45.51	---	74	54	-8.49
4882.00	H	49.09	---	-3.98	45.11	---	74	54	-8.89
7323.00	H	44.28	---	0.56	44.84	---	74	54	-9.16
---	H	---	---	---	---	---	---	---	---
---	H	---	---	---	---	---	---	---	---
1306.45	V	50.81	---	-4.25	46.56	---	74	54	-7.44
4882.00	V	50.47	---	-3.98	46.49	---	74	54	-7.51
7323.00	V	44.68	---	0.57	45.25	---	74	54	-8.75
---	V	---	---	---	---	---	---	---	---
---	V	---	---	---	---	---	---	---	---

High channel: 2480 MHz									
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2483.50	H	49.34	---	-4.20	45.14	---	74	54	-8.86
4960.00	H	48.46	---	-3.98	44.48	---	74	54	-9.52
7440.00	H	45.24	---	0.52	45.76	---	74	54	-8.24
---	H	---	---	---	---	---	---	---	---
---	H	---	---	---	---	---	---	---	---
2483.50	V	50.51	---	-4.25	46.26	---	74	54	-7.74
4960.00	V	50.92	---	-3.98	46.94	---	74	54	-7.06
7440.00	V	46.90	---	0.57	47.47	---	74	54	-6.53
---	V	---	---	---	---	---	---	---	---
---	V	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made (Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector).

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)


5. Restricted Bands Requirement

5.1 Test Standard and Limit

- 5.1.1 Test Standard
 - FCC Part 15.209
 - FCC Part 15.205
- 5.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54
Note: All restriction bands have been tested, only the worst case is reported.		

5.2 Test Setup



5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked

and then Quasi Peak detector mode re-measured.

- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (7) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Equipment


Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015
Spectrum Analyzer	Rohde & Schwarz	FSP30	DE25181	Aug. 08, 2014	Aug.07, 2015
EMI Test Receiver	Rohde & Schwarz	ESCI	101165	Aug. 08, 2014	Aug.07, 2015
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 07, 2014	Mar.06, 2015
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	11909A	185903	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	8447B	3008A00849	Mar. 07, 2014	Mar.06, 2015
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 07, 2014	Mar.06, 2015
Signal Generator	Rohde & Schwarz	SML03	IKW682-054	Feb. 11, 2014	Feb.10, 2015
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A

5.6 Test Data

All restriction bands have been tested, only the worst case is reported.

(1) Radiation Test

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz for adapter		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:			




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2367.900	49.87	0.68	50.55	74.00	-23.45	peak
2		2367.900	40.80	0.68	41.48	54.00	-12.52	AVG
3		2390.000	44.71	0.77	45.48	74.00	-28.52	peak
4		2390.000	35.64	0.77	36.41	54.00	-17.59	AVG
5	X	2402.100	97.42	0.82	98.24	74.00	24.24	peak
6	*	2402.100	88.35	0.82	89.17	54.00	35.17	AVG

Emission Level= Read Level+ Correct Factor

Note: x remark the frequency above the peak limit

* remark the worst average value have been tested

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz for adapter		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	N/A		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV		dB/m	dBuV/m	dB	Detector
1		2367.400	51.98	0.68	52.66	74.00	-21.34	peak
2		2367.400	42.91	0.68	43.59	54.00	-10.41	AVG
3		2390.000	44.47	0.77	45.24	74.00	-28.76	peak
4		2390.000	35.40	0.77	36.17	54.00	-17.83	AVG
5	X	2402.000	100.39	0.82	101.21	74.00	27.21	peak
6	*	2402.000	91.32	0.82	92.14	54.00	38.14	AVG

Emission Level= Read Level+ Correct Factor

Note: x remark the frequency above the peak limit

* remark the worst average value have been tested

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz for adapter		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2480 MHz		
Remark:	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2480.100	92.59	1.15	93.74	74.00	19.74	peak
2	*	2480.100	85.52	1.15	86.67	54.00	32.67	AVG
3		2483.500	60.88	1.17	62.05	74.00	-11.95	peak
4		2483.500	51.81	1.17	52.98	54.00	-1.02	AVG

Emission Level= Read Level+ Correct Factor

Note: x remark the frequency above the peak limit

*** remark the worst average value have been tested**

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz for adapter		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2480 MHz		
Remark:	N/A		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2480.000	90.17	1.15	91.32	74.00	17.32	peak
2	*	2480.000	81.10	1.15	82.25	54.00	28.25	AVG
3		2483.500	58.47	1.17	59.64	74.00	-14.36	peak
4		2483.500	49.40	1.17	50.57	54.00	-3.43	AVG

Emission Level= Read Level+ Correct Factor

Note: x remark the frequency above the peak limit

* remark the worst average value have been tested

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz for adapter		
Ant. Pol.	Horizontal		
Test Mode:	TX 8-DPSK Mode 2402MHz		
Remark:	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	45.25	0.77	46.02	74.00	-27.98	peak
2		2390.000	36.18	0.77	36.95	54.00	-17.05	AVG
3	X	2401.900	98.26	0.82	99.08	74.00	25.08	peak
4	*	2401.900	89.19	0.82	90.01	54.00	36.01	AVG

Emission Level= Read Level+ Correct Factor

Note: x remark the frequency above the peak limit

* remark the worst average value have been tested

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz for adapter		
Ant. Pol.	Vertical		
Test Mode:	TX 8-DPSK Mode 2402MHz		
Remark:	N/A		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	44.57	0.77	45.34	74.00	-28.66	peak
2		2390.000	35.50	0.77	36.27	54.00	-17.73	AVG
3	X	2402.100	96.92	0.82	97.74	74.00	23.74	peak
4	*	2402.100	87.85	0.82	88.67	54.00	34.67	AVG

Emission Level= Read Level+ Correct Factor

Note: x remark the frequency above the peak limit

* remark the worst average value have been tested

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz for adapter		
Ant. Pol.	Horizontal		
Test Mode:	TX 8-DPSK Mode 2480MHz		
Remark:	N/A		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.700	95.96	1.15	97.11	74.00	23.11	peak
2	*	2479.700	86.89	1.15	88.04	54.00	34.04	AVG
3		2483.500	60.45	1.17	61.62	74.00	-12.38	peak
4		2483.500	51.38	1.17	52.55	54.00	-1.45	AVG

Emission Level= Read Level+ Correct Factor

Note: x remark the frequency above the peak limit

* remark the worst average value have been tested

EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz for adapter		
Ant. Pol.	Vertical		
Test Mode:	TX 8-DPSK Mode 2480MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.700	101.28	1.15	102.43	74.00	28.43	peak
2	*	2479.700	92.21	1.15	93.36	54.00	39.36	AVG
3		2483.500	60.47	1.17	61.64	74.00	-12.36	peak
4		2483.500	51.40	1.17	52.57	54.00	-1.43	AVG



Emission Level= Read Level+ Correct Factor

Note: x remark the frequency above the peak limit



*** remark the worst average value have been tested**

(2) Conducted Test



EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX GFSK Mode 2402MHz / 2480 MHz		
Remark:	N/A		





EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	GFSK Hopping Mode		
Remark:	N/A		



EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX 8-DPSK Mode 2402MHz / 2480 MHz		
Remark:	N/A		



EUT:	Rugged smart phone	Model Name :	Rock X8
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	8-DPSK Hopping Mode		
Remark:	N/A		



6. Number of Hopping Channel

6.1 Test Standard and Limit


6.1.1 Test Standard

FCC Part 15.247 (a)(1)

6.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

6.2 Test Setup



6.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100 KHz, VBW=300 KHz, Sweep time= Auto.


6.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.

6.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Rohde & Schwarz	FSP30	DE25181	Aug. 08, 2014	Aug.07, 2015

6.6 Test Data




7. Average Time of Occupancy

7.1 Test Standard and Limit

- 5.1.1 Test Standard
FCC Part 15.247 (a)(1)
- 5.1.2 Test Limit

Section	Test Item	Limit
15.247(a)(1)/ RSS-210 Annex 8(A8.1d)	Average Time of Occupancy	0.4 sec

7.2 Test Setup



7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=1MHz.
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.

7.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.

7.5 Test Equipment


Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Rohde & Schwarz	FSP30	DE25181	Aug. 08, 2014	Aug.07, 2015

7.6 Test Data


EUT:	Rugged smart phone		Model Name :	Rock X8	
Temperature:	25 °C		Relative Humidity:	55%	
Test Voltage:	DC 3.7V				
Test Mode:	Hopping Mode (GFSK DH1)				
Packet type	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
DH1	0.401	128.3	31.60	400	PASS
DH3	1.667	266.7			
DH5	2.957	315.4			
GFSK Hopping Mode DH1					


</

GFSK Hopping Mode DH3




GFSK Hopping Mode DH5




EUT:	Rugged smart phone	Model Name :	Rock X8					
Temperature:	25 °C	Relative Humidity:	55%					
Test Voltage:	DC 3.7V							
Test Mode:	Hopping Mode							
Packet type	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result			
3DH1	0.425	136.0	31.60	400	PASS			
3DH3	1.659	265.4						
3DH5	2.993	319.3						
8-DPSK Hopping Mode 3DH1								
 Ref 15 dBm Att 20 dB RBW 1 MHz Delta 3 [T1] -0.84 dB VBW 1 MHz SWT 2.5 ms 1.245994 ms Marker 1 [T1] -67.29 dBm 637.019231 μs Delta 2 [T1] 0.30 dB 424.679487 μs 1 PK MAXH 3dB Center 2.402 GHz 250 μs/								

8-DPSK Hopping Mode 3DH3



8-DPSK Hopping Mode 3DH5




8. Channel Separation and Bandwidth Test

8.1 Test Standard and Limit

- 8.1.1 Test Standard
FCC Part 15.247
- 8.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	≤ 1 MHz (20dB bandwidth)	2400~2483.5
Channel Separation	>25 kHz or $>$ two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

8.2 Test Setup



8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
Channel Separation: RBW=100 kHz, VBW=300 kHz.
Bandwidth: RBW=30 kHz, VBW=100 kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz. Sweep Time set auto.


8.4 EUT Operating Condition

The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.

8.5 Test Equipment


Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Rohde & Schwarz	FSP30	DE25181	Aug. 08, 2014	Aug.07, 2015

8.6 Test Data




GFSK TX Mode


2441 MHz



GFSK TX Mode


2480 MHz






8-DPSK TX Mode


2441 MHz



8-DPSK TX Mode


2480 MHz






GFSK Hopping Mode


2441 MHz



GFSK Hopping Mode


2480 MHz






8-DPSK Hopping Mode

2441 MHz



8-DPSK Hopping Mode

2480 MHz



9. Peak Output Power Test

9.1 Test Standard and Limit


9.1.1 Test Standard

FCC Part 15.247 (b) (1)

9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	125 mW(21dBm)	2400~2483.5

9.2 Test Setup



9.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
 Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.
 RBW=3 MHz, VBW=3 MHz for bandwidth more than 1MHz.


9.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

9.5 Test Equipment


Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Rohde & Schwarz	FSP30	DE25181	Aug. 08, 2014	Aug.07, 2015

9.6 Test Data




GFSK TX Mode


2441 MHz




GFSK TX Mode

2480 MHz







10. Antenna Requirement

10.1 Standard Requirement

10.1.1 Standard

FCC Part 15.203

10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is -1.0 dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

10.2 Result

The EUT antenna is a PIFA Antenna. It complies with the standard requirement.