

Product Name	Lofree Bluetooth Mechanical Keyboard
Model No.	OE901
Test Mode	TX
FCC ID	2AC59-OE901

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Operational Mode: EDR (GFSK worst case)						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power(dBm)	Maximum tune-up Power(mW)	Calculated value	Exclusion threshold
2402MHz	-2.69	±1	-1.69	0.68	0.21	3
2441MHz	-3.10	±1	-2.1	0.62	0.19	3
2480MHz	-3.90	±1	-2.9	0.51	0.16	3
Conclusion: the calculated value ≤3.0, SAR is exempted.						