



Shenzhen unity wireless technology co., ltd

Address: Room 1002/1012, Building 7E, Hengda Fashion Valley, Dalang, Longhua District, Shenzhen  
telephone: 0755-23285621      portraiture: 0755-23285621

# Acknowledgement

Customer name: Shenzhen Yijing Technology Co., LTD



Customer part number: \_\_\_\_\_

Client projects: YJ-WIFI-PCB

Zhongcheng material number 众城料号: 01.01.0025

product description: PCB WIFI antenna 1.13black, IPEX1 L=200MM

date: 2025.5.24

|                     |                                                                                               |            |
|---------------------|-----------------------------------------------------------------------------------------------|------------|
| R&D<br>confirmation | SE:        | signature: |
|                     | RF:        |            |
| approval            | approval:  |            |

## Customer feedback


|            |                         |            |
|------------|-------------------------|------------|
| department | Engineering Department: | signature: |
|            | purchase department:    |            |

# 目录

|                                     |       |
|-------------------------------------|-------|
| 一、封面 (Cover)                        | 1     |
| 二、目录(Index)                         | 2     |
| 三、文件制定 (Document formulation)       | 3     |
| 四、工程图纸(Product Drawing)             | 4     |
| 五、产品参数(ProductParameter)            | 5~7   |
| 六、测试设备(Test Equipment & Conditions) | 9     |
| 七、环境与可靠性测试(reliabilitytesting)      | 10~11 |
| 八、包装规范(Package specification)       | 12    |

[illegible]

### 工程图纸：




**Product Parameter:**


| 品名            | FPC 天线    | Model                      | FPCantenna          |
|---------------|-----------|----------------------------|---------------------|
| 频率范围<br>(MHz) | 2400-2500 | Frequency                  | 2400-2500           |
| 极化方式          | 线极化       | Polarization Type          | Linear polarization |
| 天线增益<br>(dBi) | /         | Gain (dBi)                 | /                   |
| 电压驻波比         | 以实物样机为准   | VSWR                       | 以实物样机为准             |
| 输入阻抗<br>(Ω)   | 50        | Input Impedance (Ω)        | 50                  |
| 同轴线长度<br>(mm) | 200MM     | Cable length (mm)          | 200MM               |
| 电缆线颜色         | 黑色        | Cable Colour               | 黑色                  |
| 接口形式          | 一代端子      | Connector Type             | 一代端子                |
| 工作温度<br>(°C)  | -40~+85   | Operation temperature (°C) | -40~+85             |
| 存储温度<br>(°C)  | -40~+85   | Store temperat (°C)        | -40~+85             |

## 1. Antenna matching (formerly antenr

|  | E1  | E2   | E3  |
|--|-----|------|-----|
|  | N/A | 0 欧姆 | N/A |




## 2. 天线位置




## 3. Antenna isopropyl efficiency

| Freq<br>(MHz) | Effi<br>(%) | Gain<br>(dBi) |
|---------------|-------------|---------------|
| 2400          | 51.65       | 2.6           |
| 2410          | 62.07       | 2.57          |
| 2420          | 50.57       | 2.48          |
| 2430          | 51.47       | 2.44          |
| 2440          | 50.45       | 2.6           |
| 2450          | 50.88       | 2.64          |
| 2460          | 50.12       | 2.56          |
| 2470          | 52.53       | 2.44          |
| 2480          | 51.32       | 2.41          |
| 2490          | 51.36       | 2.66          |
| 2500          | 50.4        | 2.28          |

#### 4. Apple's antenna diagram:



#### 5. S11 ZEPP0



## ROHS Restricted Substance Composition Survey

## Product information provided

|               |                     |              |                                                  |
|---------------|---------------------|--------------|--------------------------------------------------|
| customer name | Material name/model | project name | manufacturer                                     |
| The ultimate  | 01.01.0025          | YJ-WIFI-PCB  | Shenzhen Zhongcheng Wireless Technology Co., LTD |

## Product composition information

| serial number | name                                    | component  | Third party inspection report |                    | Content of restricted substance in PPM |        |        |     |      |       | 备注  |
|---------------|-----------------------------------------|------------|-------------------------------|--------------------|----------------------------------------|--------|--------|-----|------|-------|-----|
|               |                                         |            | date                          | number             | 铅 (Pb)                                 | 镉 (Cd) | 汞 (Hg) | 六价铬 | 多溴联苯 | 多溴二苯醚 |     |
| 1             | PCB                                     | 基材 FR4(铜箔) | 2024.10.11                    | CANEC23010851106   | ○                                      | ○      | ○      | ○   | ○    | ○     | SGS |
| 2             |                                         | 油墨(字符)     | 2024/9/23                     | ETR24902229M01     | ○                                      | ○      | ○      | ○   | ○    | ○     | SGS |
| 3             |                                         | 焊盘 (OSP)   | 2024/3/14                     | CANEC24004013302   | ○                                      | ○      | ○      | ○   | ○    | ○     | CTI |
| 4             |                                         | 焊盘 (电金)    | 2024/3/30                     | A2240158803101001E | ○                                      | ○      | ○      | ○   | ○    | ○     | CTI |
| 5             |                                         | 线材         | 2024/1/12                     | XMP24-000173       | ○                                      | ○      | ○      | ○   | ○    | ○     |     |
| 6             |                                         | 端子         | 2024/4/25                     | 27322E20188R1M     | ○                                      | ○      | ○      | ○   | ○    | ○     |     |
| Note:         | 1. 请以○、×表示六项限用物质含量合规与否；合规者以○表示；不合规以×表示。 |            |                               |                    |                                        |        |        |     |      |       |     |

## testing facility

- Measuring instrument: microwave anechoic chamber, network analyzer, standard antenna.
- Micro-wave anechoic chamber description:

This is the microwave anechoic chamber set up in Shenzhen by our company. This microwave anechoic chamber belongs to a far-field measurement system. The size of the anechoic chamber is 7.0m x4.0m x3.0m, and the quiet zone size is 15cm x15cm x15cm.




图. 1. 微波暗室内部仪器设置 r.

图. 1. Configuration diagram for instruments in the microwave anechoic chamber and network analyzer connection: The transmitting antenna (TRC LPA0860 800MHz-6GHz model used in this chamber) is positioned 1.35 meters from the test antenna (AUT), which is mounted on a rotating platform. By adjusting the rotation angle of the platform, both preliminary and precise measurements can be performed on the test antenna.

The antenna under test is mounted on a rotating platform to collect 360-degree field strength data across its two planes (ZY and ZX). The antenna is then reconfigured as a standard dipole antenna (specifically the TRC AD series dipole antenna operating in the 800MHz-2500MHz frequency range used in this anechoic chamber) to measure its 360-degree field strength data. These measurements serve as the reference for calculating conversion gain values. Through Equation 1, the antenna's gain value and radiation pattern can be determined

$$G_{AUT} = G_{stand} + P_{AUT} - P_{stand}$$

$G_{AUT}$ : Gain of AUT

$G_{stand}$ : Gain of Standard Gain Antenna

$P_{AUT}$ : Measured Power of AUT

$P_{stand}$ : Measured Power of Standard Gain Antenna

## Environmental and Reliability Testing

| project     | Reference standards, and experimental conditions                                                                                                                                                                                                                                      | Judgment basis                                                                                                                                                                                               | Sample quantity / bad quantity (PCS) | Test / test the equipment    |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|------------------------------|
| collide     | GB/T 2423.6-1995<br>Acceleration: 200m / s <sup>2</sup><br>Collision pulse duration: 6ms<br>Number of collisions per minute: 40~80 times<br>Total collisions: 400<br>vertical direction, front and back<br>Left and right horizontal direction each 300 times, a total of 1000 times. | It should meet the requirements of electrical characteristics, and the mechanical properties are normal, but the appearance of touch marks, whitening and bending in the allowable range.                    | 5/0                                  | Collision experiment machine |
| vibrate     | GB/T2423.10-1995 Test the<br>FcFrequency: 10~30;<br>30~50Hz;<br>Resonance point<br>amplitude: 0.35mm<br>Amplitude: 0.75mm<br>Duration: X, Y & Z, 0.5 hours per direction.<br>Cycle: 1min;<br>Test for 1 hour after completing the experiment.                                         | And firmware without loose, parts without rupture or fatigue;<br>No original fall off, no solder point fracture;<br>The electrical performance index meets the requirements of the technical specifications; | 5/0                                  | Vibration test machine       |
| retentivity | Verification conditions:<br>both ends of the joint and wire are fixed on the drawing machine fixture, and the pulling force returns to zero<br>Verification method:<br>manually pull to the product IPEX connector and wire fall off                                                  | >10N                                                                                                                                                                                                         | 5/0                                  | Pull force test machine      |

|                          |                                                                                                                                        |                                                                                                                                                                                                                                                                                                      |      |                                         |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-----------------------------------------|
| decline                  | GB/T2423.8-95<br>From 100cm height to the floor 10 times. GB/T2423.8-95                                                                | 1. No significant abnormality in appearance<br>2. After the test, the electrical performance shall meet the requirements of the electrical characteristics, and the mechanical performance shall be normal, but the external collision marks, whitening and bending shall be in the allowable range. | 5/0  | Drop test machine                       |
| high-temperature storage | GB/T 2423.2-2001<br>trial B<br>Ambient conditions: + 85 ± 3°C for 96H<br>The experiment was completed 24 hours after room temperature. | The surface coating shall have no peeling, crack, wrinkle and separation; the non-metallic structures have no permanent deformation, cracking, bonding; the mobile components are not stuck or detached; the electrical performance indexes meet the requirements of technical specifications        | 10/0 | Temperature and humidity cycle test box |
| Low temperature storage  | The gb / t 2423.1-2001 test a ambient conditions: -40 ± 3°C for 96h was tested 24 hours after the experiment was at room temperature.  | The surface coating shall have no peeling, crack, wrinkle and separation; the non-metallic structures have no permanent deformation, cracking, bonding; the mobile components are not stuck or detached; the electrical performance indexes meet the requirements of technical specifications        | 10/0 | Temperature and humidity cycle test box |

|                                |                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                               |      |                                         |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-----------------------------------------|
| High and low temperature cycle | gb/t2423.22-2002 Test n: Place the antenna in t1=-40°C incubator for 30 minutes, then raise the temperature for 60 minutes to t2=80°C, then keep the temperature for 30 minutes, relative humidity at 50% rh, and the cycle is repeated 20 times. | The surface coating shall have no peeling, crack, wrinkle and separation; the non-metallic structures have no permanent deformation, cracking, bonding; the mobile components are not stuck or detached; the electrical performance indexes meet the requirements of technical specifications | 10/0 | Temperature and humidity cycle test box |
| humid heat test;               | Test gb / t 2423.3-1993 ca: ambient conditions: 40 ± 2°C, relative humidity 80 ~90% for 96 hours. The experiment was completed 24 hours after room temperature.                                                                                   | 2. After the test, the electrical performance meets the specification requirements, and the electrical performance meets the specification range.                                                                                                                                             | 10/0 | Temperature and humidity cycle test box |
| salt spray test                | The gb / t 2423.18-2000 test kb places the test in a salt spray chamber with saline injection concentration (5 ± 1)%, 35°C± 1°C, sedimentation rate (1-2) ml / 50mm2 * h, 48 hours, check the appearance.                                         | No rust phenomenon, mechanical performance and electrical performance to meet the range of specification.                                                                                                                                                                                     | 5/0  | Saline spray machine                    |

## Packaging specifications

Product material number: 01.01.0025

size of product, specifications of the products:PCB WIFI 天线 1.13 黑, 一代端子 L=200MM

1. Labeling requirements (according to the customer name reference corresponding finished product label production requirements, no requirements, according to the ordinary label requirements)

2. The inner label is about 8cm long and 5.5cm wide

|                                                                                                                                                        |  |                   |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|--|-------------------|--|
|  <b>众城无线</b><br>SHENZHEN UNITY WIRELESS TECHNOLOGY., LTD 深圳众城无线技术有限公司 |  |                   |  |
| SHENZHEN UNITY WIRELESS TECHNOLOGY., LTD                                                                                                               |  |                   |  |
| 客户                                                                                                                                                     |  | 规格型号              |  |
| 订单号                                                                                                                                                    |  | 送货数量              |  |
| 客户料号                                                                                                                                                   |  | 众城无线料号            |  |
| 日期                                                                                                                                                     |  | 生产批次              |  |
| TEL:0755-23285621                                                                                                                                      |  | FAX:0755-23285621 |  |

The outer label is about 8cm long and 5.5cm wide


|                                                                                                                                                        |  |                   |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|--|-------------------|--|
|  <b>众城无线</b><br>SHENZHEN UNITY WIRELESS TECHNOLOGY., LTD 深圳众城无线技术有限公司 |  |                   |  |
| SHENZHEN UNITY WIRELESS TECHNOLOGY., LTD                                                                                                               |  |                   |  |
| 客户                                                                                                                                                     |  | 规格型号              |  |
| 订单号                                                                                                                                                    |  | 送货数量              |  |
| 客户料号                                                                                                                                                   |  | 众城无线料号            |  |
| 日期                                                                                                                                                     |  | 生产批次              |  |
| TEL:0755-23285621                                                                                                                                      |  | FAX:0755-23285621 |  |

### 二、The packing requirements

job description:


1. inner packing:

Product according to actual packaging quantity pcs / pouch,  
Quantity of pcs / large bag according to the actual package



2. Packaging:

Quantity / box according to the actual packing



纸箱

matters need attention:

- Whether to add a partition board, pearl cotton;
- Label, such as rohs, etc.;

