55mm 55mm 55mm 55mm

55mm

User Manual for Smart Siren

HS2WD-E



*Please read the user manual carefully before operation.
The guide picture is for reference only, please in kind prevail.

Product Description

This Smart Siren adopts Zigbee Network mode. When an alarm is triggered inside the house, this Smart Siren will issue a high decibel sound and flash alarm, and also send alarm information to the user timely and effectively to avail the user to handle the emergency timely.

1



2

Technology Parameters

Product Description

1.Working Voltage: AC110-240V
2.Backup Battery: 3.8V/700mA
3.Alarm Sound Level: 95db(1m away)
4.Wireless Network Scope: ≤80m
（open indoors）
5.Working Temperature: -10℃-50℃
6.Working Humidity: ≤95% RH
（Indicating no condensation）
7..Network Mode: ZigBee ZHA1.2
8.Dimension: Φ80mm*32mm(plug not included)

3

55mm

Step 1



- You only need to insert the plug into socket, the Smart Siren will start to work.

4

Step 2



- The gateway network distributing mode will be shown after Clicking " + " in the APP interface. (⊕)

5

Step 3



- Insert the pin into the Network DistributingJack and press for 2 seconds until the Smart Siren light flashes (twice/second), which indicates that the Smart Siren has entered into the network distributing mode.
- The light will go off two seconds later, which indicates the network distributing is successful Then you can refresh the App interface, and you'll see the Smart Siren has already been added into the list.

6

- When the network needs to be changed, you can insert the pin into the Network Distributing Jack for 5 second to quit the current network. The light will flash for 3(once/second) seconds, indicating the quitting is successful.

Backup Battery

- After power off, the backup battery will start to work for 4 hours continuously and issue alarm signals for 5 minutes.

Statements

- The illustration is for reference only
- As the technology is constantly updated, if the instructions and the actual operation is inconsistent, the final interpretation is owned by the company herein.

7

55mm 55mm 55mm 55mm

FCC STATEMENT :

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) This device must accept any interference received, including interference that may cause undesired operation.

Warning: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class Bdigital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in aparticular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna.
Increase the separation between the equipment and receiver.
Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
Consult the dealer or an experienced radio/TV technician for help.

FCC Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

制作要求：

1、制作尺寸：220*55mm

2、四折扇形折页折法，折叠后尺寸为55*55mm

3、120g铜版纸彩色印刷

HEIMAN 海曼 深圳市海曼科技有限公司 Shenzhen Heiman Technology Co. Ltd

视角：	名　称：HS2WD-E 智能声光警号中性英文说明书		文件编号：
未注尺寸公差参照下表 线性公差： <=2 ±0.03 ＞2~25 ±0.05 ＞25~75 ±0.08 ＞75~100 ±0.10 ＞100 ±0.15 角度公差 ±0.5°	型　号：HS2WD-E		日　期：2017-03-24
	物料编号：601011087		制　图：吴劲洋
	版　本：M420-2Ever1.0		审　核：
	材　质：		核　准：
	单　位：mm	图　幅：1/1	比　例：1:1