TEST REPORT

APPLICANT	:	SEUIC Technologies Co., Ltd.
PRODUCT NAME	:	Handheld RFID Reader
MODEL NAME	:	AUTOID UTouch
BRAND NAME	:	Seuic
FCC ID	:	2AC68-AUTOIDUTOUCH
STANDARD(S)	:	47 CFR Part 15 Subpart E
RECEIPT DATE	:	2021-10-27
TEST DATE	:	2021-11-01 to 2021-11-24
ISSUE DATE	:	2021-12-20

Edited by: Peng Mi (Rapporteur)

Approved by: Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525
Http://www.morlab.cn E-mail: service@morlab.cn

DIRECTORY

1. Technical Information ····· 3
1.1. Applicant and Manufacturer Information ····· 3
1.2. Equipment Under Test (EUT) Description ····· 3
1.3. Modulation Type and Data Rate of EUT ····· 5
1.4. The Channel Number and Frequency ····· 6
1.5. Test Standards and Results ····· 7
1.6. Environmental Conditions ····· 8
2. 47 CFR Part 15E Requirements ····· 9
2.1. Antenna Requirement ····· 9
2.2. Duty Cycle of the Test Signal ····· 10
2.3. Maximum Conducted Output Power ····· 15
2.4. Emission Bandwidth ····· 20
2.5. Peak Power Spectral Density ····· 59
2.6. Frequency Stability ····· 100
2.7. Conducted Emission ····· 103
2.8. Restricted Frequency Bands ····· 107
2.9. Radiated Emission ····· 126
Annex A Test Uncertainty ····· 157
Annex B Testing Laboratory Information ····· 158

Change History		
Version	Date	Reason for change
1.0	2021-12-20	First edition

1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	SEUIC Technologies Co., Ltd..
Applicant Address:	NO.15 Xinghuo Road, Nanjing New & High Technology Industry Development Zone, 210061, Nanjing City, Jiangsu Province, China
Manufacturer:	SEUIC Technologies Co., Ltd.
Manufacturer Address:	NO.15 Xinghuo Road, Nanjing New & High Technology Industry Development Zone, 210061, Nanjing City, Jiangsu Province, China

1.2. Equipment Under Test (EUT) Description

Product Name:	Handheld RFID Reader
Sample No.:	5#
Hardware Version:	SLB761XC-64B_MB_PCBA_V1.00
Software Version:	V0.2.6.1
Modulation Technology:	OFDM
Modulation Mode:	802.11a, 802.11n (HT20), 802.11n (HT40) 802.11ac (VHT20), 802.11ac (VHT40), 802.11ac (VHT80)
Operating Frequency Range:	5180MHz-5240MHz; 5260MHz-5320MHz; 5500MHz-5720MHz; 5745MHz-5825MHz
Channel Number:	Refer to 1.3
Antenna Type:	Dipole Antenna
Antenna Gain:	2.50dBi

Accessory Information:	Battery 1	
	Brand Name:	N/A
	Model No.:	D500HB-V1(1S2P)
	Serial No.:	N/A
	Capacity:	6200mAh
	Rated Voltage:	3.6V
	Charge Limit:	4.2V
	Manufacturer:	Suzhou Xinfeibo Electrionic Technology Co.,ltd.
	Battery 2	
	Brand Name:	N/A
	Model No.:	BOB320724
	Serial No.:	N/A
	Capacity:	57mAh
	Rated Voltage:	3.8V
	Charge Limit:	4.35V
	Manufacturer:	DONGGUAN BOB ELECTRONICS CO.,LTD
	AC Adapter	
	Brand Name:	Tianyin
	Model No.:	TPA-23A050200UU01
	Serial No.:	N/A
	Rated Output:	5V⎓2A
	Rated Input:	100-240V~50/60Hz, 0.3A
	Manufacturer:	Shenzhen Tianyin Electronics Co.,Ltd
	USB Cable	
	Model No.:	2305018-2

Note 1: WiFi hotspot only support U-NII-1 and U-NII-3 band.

Note 2: We use the dedicated software to control the EUT continuous transmission.

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Modulation Type and Data Rate of EUT

Modulation Technology	Modulation Type	Data Rate (Mbps)Note1
OFDM (802.11a)	BPSK	**6**/9
	QPSK	12/18
	16QAM	24/36
	64QAM	48/54
OFDM (802.11n)	BPSK	**6.5**
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65
OFDM (802.11ac)	BPSK	**6.5**
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65
	256QAM	78

Note1: The worst-case mode(black bold) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.

1.4. The Channel Number and Frequency

(U-NII-1) 5180MHz-5240MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	**36**	**5180**	40	5200
	44	**5220**	**48**	**5240**
40MHz	**38**	**5190**	**46**	**5230**
80MHz	**42**	**5210**		
(U-NII-2A) 5260MHz-5320MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	**52**	**5260**	56	5280
	60	**5300**	**64**	**5320**
40MHz	**54**	**5270**	**62**	**5310**
80MHz	**58**	**5290**		
(U-NII-2C) 5500MHz-5720MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	**100**	**5500**	105	5520
	108	5540	112	5560
	116	5580	**120**	**5600**
	124	5620	128	5640
	132	5660	136	5680
	140	5700	**144**	**5720**
40MHz	**102**	**5510**	110	5550
	118	5590	**126**	**5630**
	134	5670	**142**	**5710**
80MHz	**106**	**5530**	**122**	**5610**
	138	**5690**		
(U-NII-3) 5745MHz-5825MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	**149**	**5745**	153	5765
	157	**5785**	161	5805
	165	**5825**		
40MHz	**151**	**5775**	**159**	**5795**
80MHz	**155**	**5775**		

Note 1: The black bold channels were selected for test.

1.5. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart E (U-NII band) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15(5-1-14 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	ANSI C63.10	Duty Cycle of the Test Signal	Nov 02, 2021	Meng Shurui	PASS	No deviation
3	15.407(a)	Maximum Conducted Output Power	Nov 02, 2021	Meng Shurui	PASS	No deviation
4	15.407(a)(e)	Emission Bandwidth	Nov 08, 2021	Meng Shurui	PASS	No deviation
5	15.407(a)	Peak Power Spectral Density	Nov 08, 2021	Meng Shurui	PASS	No deviation
6	15.407(g)	Frequency Stability	Nov 08, 2021	Meng Shurui	PASS	No deviation
7	15.207	Conducted Emission	Nov 11, 2021	Yang Lian	PASS	No deviation
8	15.407(b)	Restricted Frequency Bands	Nov 19&24, 2021	Su Zhan	PASS	No deviation
9	15.407(b)	Radiated Emission	Nov 23, 2021	Su Zhan	PASS	No deviation

Note 1: The DFS test report was documented in a separate report (Report No.: SZ21100063W05).

Note 2: The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.102013.

Note 3: These RF tests were performed according to the method of measurements prescribed in KDB789033 D02 v02r01.

Note 4: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 12dB contains two parts that cable loss 2dB and Attenuator 10dB.
Note 5: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.
Note 6: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.6. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR Part 15E Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Test Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Duty Cycle of the Test Signal

2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).
When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than ±2%; otherwise, the duty cycle is considered to be nonconstant.

2.2.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.2.3. Test Procedure

KDB 789033 Section B was used in order to prove compliance.

2.2.4. Test Result

A. Test Verdict:

Test Mode	Duty Cycle (%) (D)	Duty Factor (10*log[1/D])
802.11a	87.82	0.56
802.11n (HT20)	86.49	0.63
802.11n (HT40)	77.11	1.13
802.11ac (VHT20)	83.05	0.81
802.11ac (VHT40)	71.01	1.49
802.11ac (VHT80)	55.56	2.55

B. Test Plot:



(Channel 36, 5180MHz, 802.11a)



(Channel 36, 5180MHz, 802.11n (HT20))



(Channel 38, 5190MHz, 802.11n (HT40))



(Channel 36, 5180MHz, 802.11ac (VHT20))



(Channel 38, 5190MHz, 802.11ac (VHT40))



(Channel 42, 5210MHz, 802.11ac (VHT80))

2.3. Maximum Conducted Output Power

2.3.1. Requirement

(1) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi.
(2)For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or 11dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.
(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.
If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.
(4) According to KDB662911D01Measure-and-sum technique, the conducted emission level (e.g., transmit power or power in specified bandwidth) is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically to determine the total emission level from the device. Summing is performed in units that are directly proportional to power.
(5) According to KDB 662911 D01, the directional gain = G_{ANT} +10log(N_{ANT})dBi, where G_{ANT} is the antenna gain in dBi, N_{ANT} is the number of outputs.

2.3.2. Test Description

Section E) 3) of KDB 789033 defines a methodology using a USB Wideband Power Sensor.
Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in USB Wideband Power Sensor.

For ac (VHT80) mode power



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

2.3.3. Limits

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.

Mode	Band	Channel (MHz)	26dB BW (MHz)	11+10log(26dB BW)	Limits (dBm)
a	UNII-2a	5260	21.99	24.42	24.00
		5300	21.88	24.40	24.00
		5320	21.94	24.41	24.00
	UNII-2c	5500	21.53	24.33	24.00
		5600	21.53	24.33	24.00
		5720	21.79	24.38	24.00
n20	UNII-2a	5260	21.88	24.40	24.00
		5300	22.02	24.43	24.00
		5320	22.18	24.46	24.00
	UNII-2c	5500	22.76	24.57	24.00
		5600	21.97	24.42	24.00
		5720	22.93	24.60	24.00
ac20	UNII-2a	5260	21.94	24.41	24.00
		5300	21.95	24.41	24.00
		5320	21.72	24.37	24.00
	UNII-2c	5500	21.83	24.39	24.00
		5600	21.96	24.42	24.00
		5720	22.05	24.43	24.00

2.3.4. Test Result

Maximum Average Conducted Output Power

802.11a Mode

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated				
	dBm		dBm	W	dBm	W	
5180	10.17	0.56	10.73	0.012	24	0.25	PASS
5220	10.57		11.13	0.013			
5240	10.60		11.16	0.013			
5260	10.70		11.26	0.013			
5300	11.66		12.22	0.017			
5320	12.26		12.82	0.019			
5500	13.16		**13.72**	**0.024**			
5600	11.37		11.93	0.016			
5720	9.60		10.16	0.010			
5745	9.30		9.86	0.010	30	1	
5785	8.70		9.26	0.008			
5825	8.52		9.08	0.008			

802.11n (HT20) Mode

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated				
	dBm		dBm	W	dBm	W	
5180	10.29	0.63	10.92	0.012	24	0.25	PASS
5220	10.59		11.22	0.013			
5240	10.61		11.24	0.013			
5260	10.73		11.36	0.014			
5300	11.60		12.23	0.017			
5320	12.21		12.84	0.019			
5500	13.06		13.69	0.023			
5600	11.32		11.95	0.016			
5720	9.57		10.20	0.010			
5745	9.31		9.94	0.010	30	1	
5785	8.73		9.36	0.009			
5825	8.54		9.17	0.008			

802.11n (HT40) Mode

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated				
	dBm		dBm	W	dBm	W	
5190	9.13	1.13	10.26	0.011	24	0.25	PASS
5230	9.39		10.52	0.011			
5270	9.61		10.74	0.012			
5310	10.60		11.73	0.015			
5510	11.63		12.76	0.019			
5630	9.48		10.61	0.012			
5710	8.28		9.41	0.009			
5755	7.74		8.87	0.008	30	1	
5795	7.30		8.43	0.007			

802.11ac (VHT20) Mode

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated				
	dBm		dBm	W	dBm	W	
5180	9.15	0.81	9.96	0.010	24	0.25	PASS
5220	9.53		10.34	0.011			
5240	9.51		10.32	0.011			
5260	9.56		10.37	0.011			
5300	10.52		11.33	0.014			
5320	11.02		11.83	0.015			
5500	12.19		13.00	0.020			
5600	10.22		11.03	0.013			
5720	8.68		9.49	0.009			
5745	8.26		9.07	0.008	30	1	
5785	7.74		8.55	0.007			
5825	7.61		8.42	0.007			

802.11ac (VHT40) Mode

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated				
	dBm		dBm	W	dBm	W	
5190	9.15	1.49	10.64	0.012	24	0.25	PASS
5230	9.39		10.88	0.012			
5270	9.60		11.09	0.013			
5310	10.57		12.06	0.016			
5510	11.53		13.02	0.020			
5630	9.40		10.89	0.012			
5710	8.22		9.71	0.009			
5755	7.79		9.28	0.008	30	1	
5795	7.27		8.76	0.008			

802.11ac (VHT80) Mode

Frequency (MHz)	Average Power				Limit		Verdict
	Measured	Duty Factor	Duty factor Calculated				
	dBm		dBm	W	dBm	W	
5210	6.93	2.55	9.48	0.009	24	0.25	PASS
5290	7.74		10.29	0.011			
5530	9.01		**11.56**	**0.014**			
5610	7.51		10.06	0.010			
5690	6.15		8.70	0.007			
5775	5.17		7.72	0.006	30	1	

2.4. Emission Bandwidth

2.4.1. Requirement

For purposes of this subpart the emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Determination of the emissions bandwidth is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement. Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

2.4.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.4.3. Test Procedure

1. KDB 789033 Section C) 1) Emission Bandwidth was used in order to prove compliance
a) Set RBW = approximately 1% of the emission bandwidth.
b) Set VBW > RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
2. KDB 789033 Section C) 2) minimum emission bandwidth for the band 5.725-5.85GHz was used in order to prove compliance.
Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for theband5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

a) Set RBW = 100 kHz.
b) Set video bandwidth (VBW) ≥ 3 × RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

2.4.4. Test Result

802.11a Mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	22.28
44	5220	21.48
48	5240	21.71
52	5260	21.99
60	5300	21.88
64	5320	21.94
100	5500	21.53
120	5600	21.53
144	5720	21.79
Channel	**Frequency (MHz)**	**6 dB Bandwidth (MHz)**
144	5720	16.40
149	5745	16.45
157	5785	16.39
165	5825	16.45

B. Test Plot:

(Channel 36, 5180MHz, 802.11a)

(Channel 44, 5220 MHz, 802.11a)

(Channel 48, 5240MHz, 802.11a)

(Channel 52,5260MHz, 802.11a)

(Channel 60, 5300 MHz, 802.11a)

(Channel 64, 5320MHz, 802.11a)

(Channel 100,5500MHz, 802.11a)

(Channel 120, 5600 MHz, 802.11a)

(Channel 144, 5720MHz, 802.11a)

(Channel 144, 5720MHz, 802.11a)



(Channel 149, 5745MHz, 802.11a)



(Channel 157, 5785MHz, 802.11a)

(Channel 165, 5825MHz, 802.11a)

802.11n (HT20) Mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	22.15
44	5220	22.28
48	5240	22.27
52	5260	21.88
60	5300	22.02
64	5320	22.18
100	5500	22.76
120	5600	21.97
144	5720	22.93
Channel	**Frequency (MHz)**	**6 dB Bandwidth (MHz)**
144	5720	17.60
149	5745	17.67
157	5785	17.63
165	5825	17.65

B. Test Plot:

(Channel 36, 5180MHz, 802.11n (HT20))

(Channel 44, 5220MHz, 802.11n (HT20))

(Channel 48, 5240MHz, 802.11n (HT20))

(Channel 52, 5260MHz, 802.11n (HT20))

(Channel 60, 5300MHz, 802.11n (HT20))

(Channel 64, 5320MHz, 802.11n (HT20))

(Channel 100, 5500MHz, 802.11n (HT20))

(Channel 120, 5600MHz, 802.11n (HT20))

(Channel 144, 5720MHz, 802.11n (HT20))

(Channel 144, 5720MHz, 802.11 n (HT20))

(Channel 149, 5745MHz, 802.11 n (HT20))

(Channel 157, 5785MHz, 802.11 n (HT20))



(Channel 165, 5825MHz, 802.11 n (HT20))

802.11n (HT40) Test mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
38	5190	42.78
46	5230	43.43
54	5270	42.68
62	5310	42.89
102	5510	41.75
126	5630	42.78
142	5710	42.12
Channel	**Frequency (MHz)**	**6 dB Bandwidth (MHz)**
142	5710	35.16
151	5755	35.21
159	5795	35.65

B. Test Plot:

(Channel 38, 5190MHz, 802.11n (HT40))

(Channel 46, 5230MHz, 802.11n (HT40))

(Channel 54, 5270MHz, 802.11n (HT40))

(Channel 62, 5310MHz, 802.11n (HT40))



(Channel 102, 5510MHz, 802.11n (HT40))

(Channel 126, 5630MHz, 802.11n (HT40))

(Channel 142, 5710MHz, 802.11n (HT40))



(Channel 142, 5710MHz, 802.11n (HT40))

(Channel 151, 5755MHz, 802.11n (HT40))



(Channel 159, 5795MHz, 802.11n (HT40))

802.11ac (VHT20) Mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	22.63
44	5220	21.93
48	5240	22.63
52	5260	21.94
60	5300	21.95
64	5320	21.72
100	5500	21.83
120	5600	21.96
144	5720	22.05
Channel	**Frequency (MHz)**	**6 dB Bandwidth (MHz)**
144	5720	17.62
149	5745	17.61
157	5785	17.63
165	5825	17.63

B. Test Plot:

(Channel 36, 5180MHz, 802.11ac (VHT20))

(Channel 44, 5220MHz, 802.11ac (VHT20))

(Channel 48, 5240MHz, 802.11ac (VHT20))

(Channel 52, 5260MHz, 802.11ac (VHT20))

(Channel 60, 5300MHz, 802.11ac (VHT20))

(Channel 64, 5320MHz, 802.11ac (VHT20))

(Channel 100, 5500MHz, 802.11ac (VHT20))

(Channel 120, 5600MHz, 802.11ac (VHT20))

(Channel 144, 5720MHz, 802.11ac (VHT20))

(Channel 144, 5720MHz, 802.11ac (VHT20))

(Channel 149, 5745MHz, 802.11 ac (VHT20))

(Channel 157, 5785MHz, 802.11 ac (VHT20))



(Channel 165, 5825MHz, 802.11 ac (VHT20))

802.11ac (VHT40) Mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
38	5190	42.65
46	5230	42.37
54	5270	42.28
62	5310	41.94
102	5510	41.76
126	5630	42.22
142	5710	41.89
Channel	**Frequency (MHz)**	**6 dB Bandwidth (MHz)**
142	5710	35.51
151	5755	35.21
159	5795	35.50

B. Test Plot:

(Channel 38, 5190MHz, 802.11ac (VHT40))

(Channel 46, 5230MHz, 802.11ac (VHT40))

(Channel 54, 5270MHz, 802.11ac (VHT40))

(Channel 62, 5310MHz, 802.11ac (VHT40))



(Channel 102, 5510MHz, 802.11ac (VHT40))



(Channel 126, 5630MHz, 802.11ac (VHT40))

(Channel 142, 5710MHz, 802.11ac (VHT40))



(Channel 142, 5710MHz, 802.11ac (VHT40))



(Channel 151, 5755MHz, 802.11ac (VHT40))

(Channel 159, 5795MHz, 802.11ac (VHT40))

802.11ac (VHT80) Mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
42	5210	83.58
58	5290	83.96
106	5530	83.59
122	5610	82.51
138	5690	81.57
Channel	**Frequency (MHz)**	**6 dB Bandwidth (MHz)**
138	5690	73.84
155	5775	71.44

B. Test Plot:



(Channel 42, 5210MHz, 802.11ac (VHT80))

(Channel 58, 5290MHz, 802.11ac (VHT80))

(Channel 106, 5530MHz, 802.11ac (VHT80))

(Channel 122, 5610MHz, 802.11ac (VHT80))

(Channel 138, 5690MHz, 802.11ac (VHT80))



(Channel 138, 5690MHz, 802.11ac (VHT80))



(Channel 155, 5775MHz, 802.11ac (VHT80))

2.5. Peak Power Spectral Density

2.5.1. Requirement

(1)For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.
(2)For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.
(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30dBm in any 500kHz band.
If transmitting antennas of directional gain greater than 6dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.
(4) According to KDB662911D01Measure-and-sum technique, the conducted emission level (e.g., transmit power or power in specified bandwidth) is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically to determine the total emission level from the device. Summing is performed in units that are directly proportional to power.
(5) According to KDB 662911 D01, the directional gain = G_{ANT} +10log(N_{ANT}) dBi, where G_{ANT} is the antenna gain in dBi, N_{ANT} is the number of outputs.

2.5.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.5.3. Test Procedure

KDB 789033 Section F) Maximum Power Spectral Density (PSD) Method SA-3 was used in order to prove compliance

1) Set span to encompass the entire 26-dB emission bandwidth
2) Set RBW = 1MHz. Set VBW ≥ 3MHz
3) Number of points in sweep ≥ 2 Span / RBW. Sweep time = auto
4) Detector = Average
5) Trace mode=Max hold
6) Record the max value

2.5.4. Test Result

802.11a Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured PPSD (dBm/MHz)	Duty Factor	Corrected PPSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
36	5180	-0.18	0.56	0.38	11	PASS
44	5220	0.44		1.00		
48	5240	0.56		1.12		
52	5260	0.68		1.24		
60	5300	1.46		2.02		
64	5320	1.79		2.35		
100	5500	1.96		**2.52**		
120	5600	0.81		1.37		
144	5720	-1.53		-0.97		
Channel	Frequency (MHz)	Measured PPSD (dBm/500KHz)	Duty Factor	Corrected PPSD (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
144	5720	-4.34	0.56	-3.78	30	PASS
149	5745	-5.15		-4.59		
157	5785	-5.83		-5.27		
165	5825	-6.31		-5.75		

B. Test Plot:

(Channel 36, 5180MHz, 802.11a)

(Channel 44, 5220MHz, 802.11a)

(Channel 48, 5240MHz, 802.11a)

(Channel 52, 5260MHz, 802.11a)

(Channel 60, 5300MHz, 802.11a)

(Channel 64, 5320MHz, 802.11a)

(Channel 100, 5500MHz, 802.11a)

(Channel 120, 5600MHz, 802.11a)

(Channel 144, 5720MHz, 802.11a)

(Channel 144, 5720MHz, 802.11a)

(Channel 149, 5745MHz, 802.11a)

(Channel 157, 5785MHz, 802.11a)

(Channel 165, 5825MHz, 802.11a)

802.11n (HT20) Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured PPSD (dBm/MHz)	Duty Factor	Corrected PPSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
36	5180	-0.13	0.63	0.50	11	PASS
44	5220	0.36		0.99		
48	5240	0.42		1.05		
52	5260	0.66		1.29		
60	5300	1.31		1.94		
64	5320	1.61		2.24		
100	5500	1.75		2.38		
120	5600	0.61		1.24		
144	5720	-1.62		-0.99		
Channel	Frequency (MHz)	Measured PPSD (dBm/500KHz)	Duty Factor	Corrected (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
144	5720	-4.61	0.63	-3.98	30	PASS
149	5745	-5.32		-4.69		
157	5785	-5.90		-5.27		
165	5825	-6.77		-6.14		

B. Test Plot:

(Channel 36, 5180MHz, 802.11n (HT20))

(Channel 44, 5220MHz, 802.11n (HT20))

(Channel 48, 5240MHz, 802.11n (HT20))



(Channel 52, 5260MHz, 802.11n (HT20))

(Channel 60, 5300MHz, 802.11n (HT20))

(Channel 64, 5320MHz, 802.11n (HT20))

(Channel 100, 5500MHz, 802.11n (HT20))

(Channel 120, 5600MHz, 802.11n (HT20))

(Channel 144, 5720MHz, 802.11n (HT20))

(Channel 144, 5720MHz, 802.11n (HT20))

(Channel 149, 5745MHz, 802.11n (HT20))

(Channel 157, 5785MHz, 802.11n (HT20))

(Channel 165, 5825MHz, 802.11n (HT20))

802.11n (HT40) Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured PPSD (dBm/MHz)	Duty Factor	Corrected PPSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
38	5190	-4.24	1.13	-3.11	11	PASS
46	5230	-3.86		-2.73		
54	5270	-3.58		-2.45		
62	5310	-2.83		-1.70		
102	5510	-2.78		-1.65		
126	5630	-4.31		-3.18		
142	5710	-5.50		-4.37		
Channel	Frequency (MHz)	Measured PPSD (dBm/500KHz)	Duty Factor	Corrected (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
142	5710	-8.44	1.13	-7.31	30	PASS
151	5755	-9.68		-8.55		
159	5795	-10.59		-9.46		

B. Test Plot:

(Channel 38, 5190MHz, 802.11n (HT40))

(Channel 46, 5230MHz, 802.11n (HT40))

(Channel 54, 5270MHz, 802.11n (HT40))

(Channel 62, 5310MHz, 802.11n (HT40))

(Channel 102, 5510MHz, 802.11n (HT40))

(Channel 126, 5630 MHz, 802.11n (HT40))

(Channel 142, 5710MHz, 802.11n (HT40))