



REPORT No.: SZ21090283W09

TEST REPORT

APPLICANT : Shenzhen Chainway Information
Technology Co., Ltd.

PRODUCT NAME : Mobile Data Terminal

MODEL NAME : C72

BRAND NAME : CHAINWAY

FCC ID : 2AC6AC72P

STANDARD(S) : 47 CFR Part 22 Subpart H
47 CFR Part 24 Subpart E

RECEIPT DATE : 2021-10-26

TEST DATE : 2021-12-03 to 2022-04-02

ISSUE DATE : 2022-04-24



Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Fax: 86-755-36698525

Http://www.morlab.cn

E-mail: service@morlab.cn



DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
1.3. Maximum E.R.P./E.I.R.P. and Emission Designator	4
1.4. Test Standards and Results	5
1.5. Environmental Conditions	6
2. 47 CFR Part 2, Part 22H Requirements	7
2.1. Conducted RF Output Power	7
2.2. Peak to Average Ratio	9
2.3. Occupied Bandwidth	12
2.4. Frequency Stability	16
2.5. Conducted Out of Band Emissions	18
2.6. Band Edge	21
2.7. Determining E.R.P. and/or E.I.R.P. from conducted RF output power measurements	23
2.8. Radiated Out of Band Emissions	25
Annex A Test Uncertainty	34
Annex B Testing Laboratory Information	35

Change History		
Version	Date	Reason for change
1.0	2022-04-24	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Shenzhen Chainway Information Technology Co., Ltd.
Applicant Address:	9F Building 2, Daqian Industrial Park, District 67, XingDong Community, Xin'an Street, Bao'an District, Shenzhen, Guangdong, China
Manufacturer:	Shenzhen Chainway Information Technology Co., Ltd.
Manufacturer Address:	9F Building 2, Daqian Industrial Park, District 67, XingDong Community, Xin'an Street, Bao'an District, Shenzhen, Guangdong, China

1.2. Equipment Under Test (EUT) Description

Product Name:	Mobile Data Terminal	
Sample No.:	16#	
Hardware Version:	C72_Hardware_version_P	
Software Version:	C72_Software_version_P	
Modulation Type:	CDMA2000 1xRTT: BPSK,QPSK CDMA2000 1xEVDO Rev 0: BPSK CDMA2000 1xEVDO Rev A: BPSK,QPSK,8PSK	
Operating Frequency Range:	CDMA 2000 BC0	Tx: 824MHz-849MHz
		Rx: 869MHz-894MHz
Antenna Type:	Fixed Internal Antenna	
Antenna Gain:	CDMA 2000 BC0	-1.60dBi
Accessory Information:	Battery	
	Brand Name:	CHAINWAY
	Model No.:	J293
	Serial No.:	N/A
	Capacity:	8000mAh
	Rated Voltage:	3.8V
	Charge Limit:	4.35V
	Manufacturer:	Hixon (Shenzhen) Technology Limited



Accessory Information:	AC Adapter	
	Brand Name:	FULLPOWER
	Model No.:	NA010050020
	Serial No.:	N/A
	Rated Output:	5V $\Rightarrow$ 2A
	Rated Input:	100-240V~50/60Hz, 0.5A
	Manufacturer:	SHENZHEN SHI YING YUAN ELECTRONICS CO LTD
	Charging Base	
	Brand Name:	CHAINWAY
	Model No.:	CRD-C72-SCC
	Serial No.:	N/A
	Rated Output:	5V $\Rightarrow$ 2A
	Rated Input:	5V $\Rightarrow$ 2A
	Manufacturer:	Shenzhen Chainway Information Technology Co., Ltd.
	USB Cable	
	Model No.:	1.8.17.067
	Manufacturer:	SHENZHEN HUANJIAN ELECTRONIC CO., LTD.

Note 1: SIM 1 and SIM 2 is a chipset unit and tested as a single chipset. The SIM 1 is chosen for test.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Maximum E.R.P./E.I.R.P. and Emission Designator

Test Mode	Maximum E.R.P./E.I.R.P. (W)	Emission Designator
CDMA2000 BC0	0.092	1M27F9W



1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 2, Part 22 and Part24 for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 2 (10-1-12 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 (10-1-12 Edition)	Public Mobile Services
3	47 CFR Part 24 (10-1-12 Edition)	Personal Communications Services

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination/ Remark
1	2.1046	Conducted RF Output Power	Apr. 01, 2022	Yu Xiaoming	PASS	No deviation
2	24.232(d)	Peak -Average Ratio	Jan. 18, 2022	Li Huaijie	PASS	No deviation
3	2.1049	Occupied Bandwidth	Jan. 18, 2022	Li Huaijie	PASS	No deviation
4	2.1055, 22.355, 24.235	Frequency Stability	Mar. 23, 2022	Li Huaijie	PASS	No deviation
5	2.1051, 22.917(a), 24.238(a)	Conducted Out of Band Emissions	Jan. 18, 2022	Li Huaijie	PASS	No deviation
6	2.1051, 22.917(a), 24.238(a)	Band Edge	Jan. 18, 2022	Li Huaijie	PASS	No deviation
7	22.913(a) 24.232(c)	Transmitter Radiated Power (EIPR/E.R.P.)	Apr. 02, 2022	Li Huaijie	PASS	No deviation
8	2.1051, 22.917(a), 24.238(a)	Radiated Out of Band Emissions	Dec. 03, 2021	Lin Jiayong	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in KDB971168 D01 v03r01 and ANSI/TIA-603-E-2016.

Note 2: The path loss during the RF test is calibrated to correct the results by the offset setting in

the test equipments. The ref offset 24.5dB contains two parts that cable loss 14.5dB and Attenuator 10dB.

Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 4: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.47 CFR Part 2, Part 22H, Part24E Requirements


2.1. Conducted RF Output Power

2.1.1. Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

2.1.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

**2.1.3. Test Result**

CDMA2000 BC0	Average Power (dBm)		
TX Channel	1013	384	777
Frequency (MHz)	824.7	836.52	848.31
1xRTT RC1 SO55	23.01	23.22	23.26
1xRTT RC3 SO55	23.16	23.21	23.13
1xRTT RC3 SO32 (F+SCH)	23.11	23.08	23.17
1xRTT RC3 SO32 (+SCH)	23.01	22.97	23.11
1xEVDO RTAP 153.6Kbps	23.39	23.21	23.24
1xEVDO RETAP 4096Bits	23.16	23.19	23.28


2.2. Peak to Average Ratio

2.2.1. Requirement

According to FCC 24.232(d) the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

2.2.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

2.2.3. Test Procedure


1. For GSM/EDGE operating mode:
 - a. Set RBW=1MHz, VBW=3MHz, peak detector in spectrum analyzer.
 - b. Set EUT in maximum output power, and triggered the bust signal.
 - c. Measured respectively the peak level and mean level, and the deviation was recorded as Peak to Average ratio.
2. For UMTS operating mode:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1%.




2.2.4. Test Result

CDMA2000 BC0					
Mode	Channel	Frequency (MHz)	Peak to Average ratio (dB)	Limit (dB)	Verdict
1xRTT	1013	824.70	3.79	13	PASS
	384	836.52	3.85		PASS
	777	848.31	3.67		PASS
1xEVDO Rev 0	1013	824.70	4.76	13	PASS
	384	836.52	4.90		PASS
	777	848.31	4.60		PASS

CDMA BC0 (1xRTT), CH1013, 824.70MHz





CDMA BC0 (1xRTT), CH384, 836.52MHz



CDMA BC0 (1xRTT), CH777, 848.31MHz



**CDMA BC0 (1xEVDO Rev 0), CH1013, 824.70MHz****CDMA BC0 (1xEVDO Rev 0), CH384, 836.52MHz****CDMA BC0 (1xEVDO Rev 0), CH777, 848.31MHz**


2.3. Occupied Bandwidth

2.3.1. Requirement

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission. Occupied bandwidth is also known as the 99% emission bandwidth.

2.3.2. Test Description




Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

**2.3.3. Test Result**

CDMA2000 BC0				
Mode	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)
1xRTT	1013	824.70	1.27	1.43
	384	836.52	1.27	1.42
	777	848.31	1.27	1.43
1xEVDO Rev 0	1013	824.70	1.27	1.43
	384	836.52	1.27	1.43
	777	848.31	1.27	1.43

**CDMA BC0 (1xRTT), CH1013, 824.70MHz****CDMA BC0 (1xRTT), CH384, 836.52MHz****CDMA BC0 (1xRTT), CH777, 848.31MHz**

**CDMA BC0 (1xEVDO Rev 0), CH1013, 824.70MHz****CDMA BC0 (1xEVDO Rev 0), CH384, 836.52MHz****CDMA BC0 (1xEVDO Rev 0), CH777, 848.31MHz**

2.4. Frequency Stability

2.4.1. Requirement


According to FCC section 22.355 the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from -30°C to $+50^{\circ}\text{C}$ at intervals of not more than 10°C .
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

Note: The operating temperature of EUT is from -20°C to 50°C , which are specified by the applicant.

2.4.2. Test Description

Test Setup:



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS via a Common Antenna.



2.4.3. Test Result

The nominal, highest and lowest extreme voltages are separately 3.80V, 4.35V and 3.50V, which are specified by the applicant; the normal temperature here used is 20°C.

CDMA2000 BC0 (1xRTT), CH384, 836.52MHz					
Limit =±2.5ppm					
Voltage (%)	Power (VDC)	Temp (°C)	Fre. Dev. (Hz)	Deviation (ppm)	Result
Normal	3.80	+20(Ref)	-13	-0.016	PASS
Normal		-20	46	0.055	
Normal		-10	40	0.048	
Normal		0	38	0.045	
Normal		+10	54	0.065	
Normal		+20	18	0.022	
Normal		+30	-21	-0.025	
Normal		+40	-15	-0.018	
Normal		+50	35	0.042	
High	4.35	+20	49	0.059	
BATT.ENDPOINT	3.50	+20	28	0.033	

CDMA2000 BC0 (1xEVDO), CH384, 836.52MHz					
Limit =±2.5ppm					
Voltage (%)	Power (VDC)	Temp (°C)	Fre. Dev. (Hz)	Deviation (ppm)	Result
Normal	3.80	+20(Ref)	-51	-0.061	PASS
Normal		-20	45	0.054	
Normal		-10	20	0.024	
Normal		0	14	0.017	
Normal		+10	13	0.016	
Normal		+20	-59	-0.071	
Normal		+30	-23	-0.027	
Normal		+40	55	0.066	
Normal		+50	36	0.043	
High	4.35	+20	24	0.029	
BATT.ENDPOINT	3.50	+20	-45	-0.054	


2.5. Conducted Out of Band Emissions

2.5.1. Requirement

According to FCC section 22.917(a) and 24.238(a) the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \cdot \log(P)$ dB. This calculated to be -13dBm. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency.

2.5.2. Test Description

Test Setup:




The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.




2.5.3. Test Result


CDMA BC0 (1xRTT), CH1013, 824.70MHz



CDMA BC0 (1xRTT), CH384, 836.52MHz




CDMA BC0 (1xRTT), CH777, 848.31MHz







CDMA BC0 (1xEVDO Rev 0), CH1013, 824.70MHz



CDMA BC0 (1xEVDO Rev 0), CH384, 836.52MHz



CDMA BC0 (1xEVDO Rev 0), CH777, 848.31MHz




2.6. Band Edge

2.6.1. Requirement

According to FCC section 22.917(a) and 24.238(a) the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \cdot \log(P)$ dB. This calculated to be -13dBm. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency.

2.6.2. Test Description

Test Setup:




The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.




2.6.3. Test Result

The lowest and highest channels are tested to verify the band edge emissions.

CDMA BC0 (1xRTT), CH1013, 824.70MHz



CDMA BC0 (1xRTT), CH777, 848.31MHz



CDMA BC0 (1xEVDO Rev 0), CH1013, 824.70MHz



CDMA BC0 (1xEVDO Rev 0), CH777, 848.31MHz



2.7. Determining E.R.P. and/or E.I.R.P. from conducted RF output power measurements

2.7.1. Requirement

According to FCC section 22.913, the Effective Radiated Power (E.R.P.) of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to FCC section 24.232, the broadband PCS mobile station is limited to 2 Watts e.i.r.p. peak power.

2.7.2. Test Description

The test setups refer to section 2.1.3

A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power (i.e. GSM850MHz band Power Control Level (PCL) = 5/19 and Power Class = 4, GSM1900MHz band Power Control Level (PCL) = 0/15 and Power Class = 1), and only the test result of the maximum output power was recorded. Please refer to section 2.1.3 of this report.

The relevant equation for determining the maximum E.R.P. or E.I.R.P. from the measured RF output power is given in Equation (1) as follows:

$$\text{E.R.P. or E.I.R.P.} = P_{\text{Meas}} + G_T$$

Where:

E.R.P. or E.I.R.P. effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_T gain of the transmitting antenna, in dBd (E.R.P.) or dBi (E.I.R.P.)

For devices utilizing multiple antennas, see ANSI C63.25-2015 6.4 for guidance with respect to determining the effective array transmit antenna gain term to be used in the above equation.

The following equations demonstrate the mathematical relationship between E.R.P. and E.I.R.P.:

a) $\text{E.R.P.} = \text{E.I.R.P.} - 2.15$, where E.R.P. and E.I.R.P. are expressed in consistent units.

b) $\text{E.I.R.P.} = \text{E.R.P.} + 2.15$, where E.R.P. and E.I.R.P. are expressed in consistent units.

**2.7.3. Test Result**


CDMA2000 BC0								
Band	Channel	Frequency (MHz)	PCL	Measured E.R.P.		Limit		Verdict
				dBm	W	dBm	W	
1xRTT	1013	824.70	5	19.41	0.087	38.5	7	PASS
	384	836.52	5	19.47	0.089			PASS
	777	848.31	5	19.51	0.089			PASS
1xEVDO Rev 0	1013	824.70	5	19.64	0.092	38.5	7	PASS
	384	836.52	5	19.46	0.088			PASS
	777	848.31	5	19.49	0.089			PASS
1xEVDO Rev A	1013	824.70	5	19.41	0.087	38.5	7	PASS
	384	836.52	5	19.44	0.088			PASS
	777	848.31	5	19.53	0.090			PASS

2.8. Radiated Out of Band Emissions


2.8.1. Requirement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This calculated to be -13dBm. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency.

2.8.2. Test Description



(For the test frequency from 30MHz to 1GHz)



(For the test frequency above 1GHz)

The EUT is located in a 3m Full-Anechoic Chamber, the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading. A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power, and only the test result of the maximum output power was recorded.

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground and the Turn Table is actuated to turn from 0° to 360° to determine the maximum value of the radiated power. The emission levels at both horizontal and vertical polarizations should be tested. The Filters consists of Notch Filters and High Pass Filter.

Note: When doing measurements above 1GHz, the EUT has been within the 3dB cone width of the horn antenna during horizontal antenna.

2.8.3. Test Procedure

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements.



2.8.4. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

The substitution corrections are obtained as described below:

$$A_{\text{SUBST}} = P_{\text{SUBST_TX}} - P_{\text{SUBST_RX}} - L_{\text{SUBST_CABLES}} + G_{\text{SUBST_TX_ANT}}$$

$$A_{\text{TOT}} = L_{\text{CABLES}} + A_{\text{SUBST}}$$

Where A_{SUBST} is the final substitution correction including receive antenna gain.

$P_{\text{SUBST_TX}}$ is signal generator level,

$P_{\text{SUBST_RX}}$ is receiver level,

$L_{\text{SUBST_CABLES}}$ is cable losses including TX cable,

$G_{\text{SUBST_TX_ANT}}$ is substitution antenna gain.

A_{TOT} is total correction factor including cable loss and substitution correction

During the test, the data of A_{TOT} was added in the test spectrum analyze, so spectrum analyze reading is the final values which contain the data of A_{TOT} .

Note1: The power of the EUT transmitting frequency should be ignored.


Note2: All test mode and condition mentioned were considered and evaluated respectively by performing full test, only the worst data were recorded and reported.

Note3: All spurious emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note4: N/A means the frequency is the basic frequency or the base station frequency, they are no need to verdict.


Note5: The amplitude of emissions(18GHz to 10th harmonics) which are attenuated more than 20 dB below the limit are not be reported.

CDMA2000 BC0 (1xRTT), Low Channel



Final Test


No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	39.7100	-58.63	-13.00	Horizontal	PASS
2	57.1870	-63.07	-13.00	Horizontal	PASS
3	103.7940	-70.74	-13.00	Horizontal	PASS
4	228.0780	-71.86	-13.00	Horizontal	PASS
5	519.3690	-67.81	-13.00	Horizontal	PASS
6	881.5420	-28.73	-13.00	Horizontal	N/A



Final Test


No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1762.7630	-53.58	-13.00	Horizontal	PASS
2	2437.4370	-53.49	-13.00	Horizontal	PASS
3	3816.3160	-55.24	-13.00	Horizontal	PASS
4	6575.0750	-48.96	-13.00	Horizontal	PASS
5	8602.1020	-45.79	-13.00	Horizontal	PASS
6	11354.8550	-40.62	-13.00	Horizontal	PASS

CDMA2000 BC0 (1xRTT), Low Channel



Final Test


No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	35.8260	-61.59	-13.00	Vertical	PASS
2	90.2000	-66.6	-13.00	Vertical	PASS
3	179.5300	-74.7	-13.00	Vertical	PASS
4	326.1460	-71.61	-13.00	Vertical	PASS
5	470.8210	-64.82	-13.00	Vertical	PASS
6	880.5710	-32.88	-13.00	Vertical	N/A



Final Test


No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1762.7630	-56.95	-13.00	Vertical	PASS
2	2441.4410	-57.84	-13.00	Vertical	PASS
3	4131.6320	-56.52	-13.00	Vertical	PASS
4	7194.4440	-46.79	-13.00	Vertical	PASS
5	9984.7350	-42.62	-13.00	Vertical	PASS
6	11354.8550	-40.88	-13.00	Vertical	PASS

CDMA2000 BC0 (1xRTT), Mid Channel



Final Test


No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	37.7680	-57.46	-13.00	Horizontal	PASS
2	49.4190	-59.86	-13.00	Horizontal	PASS
3	96.9970	-71.46	-13.00	Horizontal	PASS
4	237.7880	-71.47	-13.00	Horizontal	PASS
5	548.4980	-66.97	-13.00	Horizontal	PASS
6	893.1930	-30.57	-13.00	Horizontal	N/A



Final Test


No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1786.7870	-53.42	-13.00	Horizontal	PASS
2	2439.4390	-56.69	-13.00	Horizontal	PASS
3	3805.8060	-54.45	-13.00	Horizontal	PASS
4	5399.9000	-53.59	-13.00	Horizontal	PASS
5	7488.4880	-45.21	-13.00	Horizontal	PASS
6	10697.9480	-42.49	-13.00	Horizontal	PASS

CDMA2000 BC0 (1xRTT), Mid Channel



Final Test


No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	35.8260	-60.7	-13.00	Vertical	PASS
2	90.2000	-66.78	-13.00	Vertical	PASS
3	179.5300	-75.49	-13.00	Vertical	PASS
4	301.8720	-74.01	-13.00	Vertical	PASS
5	483.4430	-65.56	-13.00	Vertical	PASS
6	893.1930	-34.13	-13.00	Vertical	N/A



Final Test


No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1396.3960	-60.81	-13.00	Vertical	PASS
2	2441.4410	-56.09	-13.00	Vertical	PASS
3	3802.3020	-55.67	-13.00	Vertical	PASS
4	7225.7260	-46.50	-13.00	Vertical	PASS
5	9984.7350	-42.60	-13.00	Vertical	PASS
6	12011.7620	-40.78	-13.00	Vertical	PASS

CDMA2000 BC0 (1xRTT), High Channel



Final Test


No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	36.7970	-59.78	-13.00	Horizontal	PASS
2	56.2160	-62.82	-13.00	Horizontal	PASS
3	104.7650	-72.43	-13.00	Horizontal	PASS
4	236.8170	-72.1	-13.00	Horizontal	PASS
5	528.1080	-67.88	-13.00	Horizontal	PASS
6	869.8900	-28.07	-13.00	Horizontal	N/A



Final Test


No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1738.7390	-54.62	-13.00	Horizontal	PASS
2	2439.4390	-57.2	-13.00	Horizontal	PASS
3	3700.7010	-56.38	-13.00	Horizontal	PASS
4	5624.1240	-53.65	-13.00	Horizontal	PASS
5	7988.9890	-45.17	-13.00	Horizontal	PASS
6	11999.2490	-39.6	-13.00	Horizontal	PASS

CDMA2000 BC0 (1xRTT), High Channel



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	35.8260	-62.04	-13.00	Vertical	PASS
2	54.2740	-70.75	-13.00	Vertical	PASS
3	100.8810	-68.75	-13.00	Vertical	PASS
4	180.5010	-75.85	-13.00	Vertical	PASS
5	483.4430	-63.47	-13.00	Vertical	PASS
6	869.8900	-31.9	-13.00	Vertical	N/A



Final Test

No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	1738.7390	-58.62	-13.00	Vertical	PASS
2	2443.4430	-55.53	-13.00	Vertical	PASS
3	3809.3090	-55.39	-13.00	Vertical	PASS
4	7613.6140	-46.32	-13.00	Vertical	PASS
5	9684.4340	-44.21	-13.00	Vertical	PASS
6	12268.2680	-41.36	-13.00	Vertical	PASS



Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Output Power	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{ dB}$
Radiated Emission	$\pm 2.95\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY51511149	N9020A	Agilent	2021.07.26	2022.07.25
System Simulator	6200995016	MT8820C	Anritsu	2021.10.21	2022.10.20
Temperature Chamber	20171112102	HZ-2019	Dongguan Lixian Instrument Technology Co., Ltd	2021.10.20	2022.10.19

4.2 List of Software Used

Description	Manufacturer	Software Version
Morlab FCC Test System	MORLAB	V3.0
TS+ -[JS36-RSE]	Tonscend	V2.0.1.3
MORLAB EMCR V1.2	MORLAB	V1.0

**4.2 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
System Simulator	152038	CMW500	R&S	2021.10.21	2022.10.20
Receiver	MY54130016	N9038A	Agilent	2021.07.16	2022.07.15
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2019.05.24	2022.05.23
Test Antenna - Horn	9170C-531	BBHA9170	Schwarzbeck	2019.07.26	2022.07.25
Test Antenna - Horn	01774	BBHA 9120D	Schwarzbeck	2019.07.26	2022.07.25
Coaxial cable (N male) (9kHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-40GHz)	CB05	EMC05	Morlab	N/A	N/A
1-18GHz pre-Amplifier	61171/61172	S020180L3203	Tonscend	2021.07.16	2022.07.15
18-26.5GHz pre-Amplifier	46732	S10M100L3802	Tonscend	2021.07.16	2022.07.15
26-40GHz pre-Amplifier	56774	S40M400L4002	Tonscend	2021.07.16	2022.07.15
Notch Filter	N/A	WRCG-CDM A2000 BC0	Wainwright	2021.07.16	2022.07.15
Notch Filter	N/A	WRCG-CDM A2000 BC1	Wainwright	2021.07.16	2022.07.15
Anechoic Chamber	N/A	9m*6m*6m	CRT	2019.07.13	2022.07.12

_____ END OF REPORT _____