



FCC RF Test Report

APPLICANT : Espressif Systems (Shanghai) Co.,Ltd.
EQUIPMENT : 2.4GHz Wi-Fi & BT IoT Module
BRAND NAME : ESPRESSIF
MODEL NAME : ESP32-C61-WROOM-1
FCC ID : 2AC7Z-ESPC61WRM1
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Aug. 19, 2025 ~ Sep. 05, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

***No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China***



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	14
3.5 Radiated Band Edges and Spurious Emission Measurement	15
3.6 AC Conducted Emission Measurement.....	19
3.7 Antenna Requirements.....	21
4 LIST OF MEASURING EQUIPMENT.....	22
5 MEASUREMENT UNCERTAINTY.....	23
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR570917A	Rev. 01	Initial issue of report	Dec. 26, 2025



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Conducted Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm/3kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 2.14 dB at 2483.50 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 7.80 dB at 0.188 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Espressif Systems (Shanghai) Co.,Ltd.

Suite 204, Block 2, 690 Bibo Road, Zhang Jiang Hi-Tech Park, Shanghai, China

1.2 Manufacturer

Espressif Systems (Shanghai) Co.,Ltd.

Suite 204, Block 2, 690 Bibo Road, Zhang Jiang Hi-Tech Park, Shanghai, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	2.4GHz Wi-Fi & BT IoT Module
Brand Name	ESPRESSIF
Model Name	ESP32-C61-WROOM-1
FCC ID	2AC7Z-ESPC61WRM1
SN Code	Conducted: N/A Conduction: #12 Radiation: #1, #2
HW Version	V1.2
SW Version	v1.1.3.4
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	BLE 1Mbps: 20.78 dBm (0.1197 W) BLE 2Mbps: 21.26 dBm (0.1337 W) BLE 125kbps: 15.23 dBm (0.0333 W) BLE 500kbps: 15.21 dBm (0.0332 W)
99% Occupied Bandwidth	BLE 1Mbps:1.043MHz BLE 2Mbps:2.058MHz BLE 125kbps: 1.067MHz BLE 500kbps: 1.043MHz
Antenna Type / Gain	PCB Antenna type with gain 3.26 dBi
Type of Modulation	Bluetooth LE : GFSK

Note: For BLE 1Mbps & 125Kbps & 500Kbps mode, the whole testing has assessed BLE 1Mbps mode by referring to the higher conducted power.



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH06-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH06-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2020

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-



2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
	Mode 7: Bluetooth Tx CH00_2402 MHz_BLE 125Kbps
	Mode 8: Bluetooth Tx CH19_2440 MHz_BLE 125Kbps
	Mode 9: Bluetooth Tx CH39_2480 MHz_BLE 125Kbps
	Mode 10: Bluetooth Tx CH00_2402 MHz_BLE 500Kbps
	Mode 11: Bluetooth Tx CH19_2440 MHz_BLE 500Kbps
	Mode 12: Bluetooth Tx CH39_2480 MHz_BLE 500Kbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
AC Conducted Emission	Mode 1: BLE TX + WLAN Link (2.4G) + Charging from Notebook

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
2.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	Shielded cable DC O/P 1.8m, Unshielded AC I/P cable 1.8m
3.	Hard disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
4.	Test Jig	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.11 dB and 20dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 2.11 + 20 = 22.11 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 11.8.1 for 6dB BW and 6.9.3 for 99% occupied bandwidth measurements
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth (VBW) $\geq 3 \times \text{RBW}$. Detector = Peak. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) approximately three times the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth & 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 clause 11.9.1.2 PKPM1 Peak power meter or ANSI C63.10-2020 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2020 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2020 clause 11.11.3
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2020 clause 6.3, 6.5, 6.6, 11.11 and 11.12.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW = RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f > 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY57290157	3Hz~8.5GHz;Max 30dBm	Feb. 22, 2025	Aug. 19, 2025	Feb. 21, 2026	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471084	10Hz~44GHz	Jul. 03, 2025	Aug. 19, 2025	Jul. 02, 2026	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Aug. 19, 2025	Sep. 07, 2025	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz~1GHz	Sep. 03, 2024	Aug. 19, 2025	Sep. 02, 2025	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00251694	1GHz~18GHz	May 15, 2025	Aug. 19, 2025	May 14, 2026	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101116	18GHz~40GHz	Oct. 22, 2024	Aug. 19, 2025	Oct. 21, 2025	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	380827	9KHz ~1GHZ	Jul. 03, 2025	Aug. 19, 2025	Jul. 02, 2026	Radiation (03CH06-KS)
Amplifier	EM	EM18G40GA	060728	18~40GHz	Jan. 03, 2025	Aug. 19, 2025	Jan. 02, 2026	Radiation (03CH06-KS)
high gain Amplifier	EM	EM01G18GA	060845	1Ghz~18Ghz	Jan. 03, 2025	Aug. 19, 2025	Jan. 02, 2026	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY57280119	500MHz~26.5GHz	Oct. 09, 2024	Aug. 19, 2025	Oct. 08, 2025	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 19, 2025	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 19, 2025	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 19, 2025	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 16, 2025	Sep. 02, 2025	Apr. 15, 2026	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Jul. 03, 2025	Sep. 02, 2025	Jul. 02, 2026	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Dec. 24, 2024	Sep. 02, 2025	Dec. 23, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 09, 2024	Sep. 02, 2025	Oct. 08, 2025	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024	Sep. 04, 2025~Sep. 05, 2025	Oct. 09, 2025	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2025	Sep. 04, 2025~Sep. 05, 2025	Jan. 01, 2026	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2025	Sep. 04, 2025~Sep. 05, 2025	Jan. 01, 2026	Conducted (TH01-KS)

NCR: No Calibration Required



5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.00 dB
Occupied Channel Bandwidth	±0.384%
Conducted Power	±0.90 dB
Conducted Power Spectral Density	±0.90 dB
Frequency	±0.38ppm

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.84 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.82 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.82 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.83 dB
---	---------

----- THE END -----



Appendix A. Conducted Test Results

**Ambient Condition:** 25 °C, 45 %RH**Test Date:** 2025.9.4~2025.9.5**Test Engineer:** Zhu Chong


DTS Bandwidth


Test Result


TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.67	2401.65	2402.32	0.5	PASS
		2440	0.67	2439.65	2440.32	0.5	PASS
		2480	0.68	2479.64	2480.32	0.5	PASS
BLE_2M	Ant1	2402	1.14	2401.40	2402.54	0.5	PASS
		2440	1.14	2439.40	2440.54	0.5	PASS
		2480	1.14	2479.40	2480.54	0.5	PASS



Test Graphs










Occupied Channel Bandwidth


Test Result


TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.043	2401.4645	2402.5075	---	---
		2440	1.043	2439.4645	2440.5075	---	---
		2480	1.043	2479.4645	2480.5075	---	---
BLE_2M	Ant1	2402	2.058	2400.9610	2403.0190	---	---
		2440	2.054	2438.9610	2441.0150	---	---
		2480	2.058	2478.9610	2481.0190	---	---
BLE_125K	Ant1	2402	1.059	2401.4525	2402.5115	---	---
		2440	1.055	2439.4565	2440.5115	---	---
		2480	1.067	2479.4486	2480.5155	---	---
BLE_500K	Ant1	2402	1.039	2401.4645	2402.5035	---	---
		2440	1.043	2439.4645	2440.5075	---	---
		2480	1.043	2479.4645	2480.5075	---	---



Test Graphs











BLE_125K_Ant1_2402




BLE_125K_Ant1_2440






BLE_125K_Ant1_2480



Date: 4.SEP.2025 23:50:53


BLE_500K_Ant1_2402



Date: 4.SEP.2025 23:51:34




BLE_500K_Ant1_2440



Date: 4.SEP.2025 23:52:10

BLE_500K_Ant1_2480



Date: 4.SEP.2025 23:52:46



Maximum conducted output power

Test Result Peak

TestMode	Antenna	CH.	Peak Conducted Power (dBm)	Conducted Power Limit	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit	Pass/Fail	Power Setting
BLE1M	Ant 1	0	20.53	30.00	3.26	23.79	36.00	Pass	15
		19	20.68	30.00	3.26	23.94	36.00	Pass	15
		39	20.78	30.00	3.26	24.04	36.00	Pass	15
BLE2M	Ant 1	0	20.58	30.00	3.26	23.84	36.00	Pass	15
		19	21.01	30.00	3.26	24.27	36.00	Pass	15
		39	21.26	30.00	3.26	24.52	36.00	Pass	15
BLE125K	Ant 1	0	15.11	30.00	3.26	18.37	36.00	Pass	13
		19	15.23	30.00	3.26	18.49	36.00	Pass	13
		39	15.08	30.00	3.26	18.34	36.00	Pass	13
BLE500K	Ant 1	0	15.05	30.00	3.26	18.31	36.00	Pass	13
		19	15.21	30.00	3.26	18.47	36.00	Pass	13
		39	15.20	30.00	3.26	18.46	36.00	Pass	13

Test Result Average

TestMode	Antenna	CH.	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting
BLE1M	Ant 1	0	0.00	19.93	15.00
		19	0.00	20.00	15.00
		39	0.00	20.13	15.00
BLE2M	Ant 1	0	0.00	19.63	15.00
		19	0.00	20.03	15.00
		39	0.00	20.16	15.00
BLE125K	Ant 1	0	0.00	14.36	13.00
		19	0.00	14.65	13.00
		39	0.00	14.44	13.00
BLE500K	Ant 1	0	0.00	14.33	13.00
		19	0.00	14.53	13.00
		39	0.00	14.46	13.00




Maximum power spectral density


Test Result


TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	6.58	≤8.00	PASS
		2440	6.72	≤8.00	PASS
		2480	6.59	≤8.00	PASS
BLE_2M	Ant1	2402	3.88	≤8.00	PASS
		2440	4.01	≤8.00	PASS
		2480	3.95	≤8.00	PASS
BLE_125K	Ant1	2402	7.99	≤8.00	PASS
		2440	7.91	≤8.00	PASS
		2480	7.56	≤8.00	PASS
BLE_500K	Ant1	2402	7.95	≤8.00	PASS
		2440	7.80	≤8.00	PASS
		2480	7.52	≤8.00	PASS



Test Graphs











BLE_125K_Ant1_2402



Date: 5.SEP.2025 00:01:29


BLE_125K_Ant1_2440




Date: 5.SEP.2025 00:01:55



BLE_125K_Ant1_2480




BLE_500K_Ant1_2402






BLE_500K_Ant1_2440



Date: 5.SEP.2025 00:03:06

BLE_500K_Ant1_2480



Date: 5.SEP.2025 00:03:29




Reference level measurement

Test Result

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm/100KHz]
BLE_1M	Ant1	2402	2401.99	19.09
		2440	2439.98	19.16
		2480	2479.99	19.08
BLE_2M	Ant1	2402	2401.98	18.84
		2440	2439.98	18.91
		2480	2479.98	18.77




Test Graphs






BLE_1M_Ant1_2480



Date: 4.SEP.2025 23:43:14

BLE_2M_Ant1_2402



Date: 4.SEP.2025 23:45:10






Band edge measurements

Test Result

TestMode	Antenna	ChName	Freq(MHz)	RefLevel[dBm /100KHz]	Result[dBm /100KHz]	Limit[dBm /100KHz]	Verdict
BLE_1M	Ant1	Low	2402	19.09	-27.16	≤-0.91	PASS
		High	2480	19.08	-44.7	≤-0.92	PASS
BLE_2M	Ant1	Low	2402	18.84	-19.65	≤-1.16	PASS
		High	2480	18.77	-41.73	≤-1.23	PASS




Test Graphs






BLE_2M_Ant1_Low_2402



BLE_2M_Ant1_High_2480







Conducted Spurious Emission


Test Result


TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm/100KHz]	Result [dBm/100KHz]	Limit [dBm/100KHz]	Verdict
BLE_1M	Ant1	2402	30~1000	19.09	-45.04	≤ -0.91	PASS
			1000~26500	19.09	-35.51	≤ -0.91	PASS
		2440	30~1000	19.16	-44.98	≤ -0.84	PASS
			1000~26500	19.16	-36.16	≤ -0.84	PASS
		2480	30~1000	19.08	-44.04	≤ -0.92	PASS
			1000~26500	19.08	-36.15	≤ -0.92	PASS
BLE_2M	Ant1	2402	30~1000	18.84	-44.39	≤ -1.16	PASS
			1000~26500	18.84	-35.57	≤ -1.16	PASS
		2440	30~1000	18.91	-44.7	≤ -1.09	PASS
			1000~26500	18.91	-35.27	≤ -1.09	PASS
		2480	30~1000	18.77	-44.65	≤ -1.23	PASS
			1000~26500	18.77	-35.89	≤ -1.23	PASS


Test Graphs

















Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos	Temperature :	25.3 ~ 26.2℃
		Relative Humidity :	38 ~ 40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-L 24+80 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.152	53.18	-12.73	65.91	42.50	0.23	10.45	QP
2	0.152	36.28	-19.63	55.91	25.60	0.23	10.45	Average
3 *	0.188	56.31	-7.80	64.11	45.60	0.25	10.46	QP
4	0.188	41.31	-12.80	54.11	30.60	0.25	10.46	Average
5	0.213	50.92	-12.18	63.10	40.20	0.26	10.46	QP
6	0.213	31.92	-21.18	53.10	21.20	0.26	10.46	Average
7	0.570	40.95	-15.05	56.00	30.20	0.37	10.38	QP
8	0.570	27.55	-18.45	46.00	16.80	0.37	10.38	Average
9	2.900	42.14	-13.86	56.00	31.51	0.41	10.22	QP
10	2.900	24.24	-21.76	46.00	13.61	0.41	10.22	Average
11	3.293	39.13	-16.87	56.00	28.50	0.41	10.22	QP
12	3.293	22.23	-23.77	46.00	11.60	0.41	10.22	Average



Test Engineer :	Amos	Temperature :	25.3 ~ 26.2℃
		Relative Humidity :	38 ~ 40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-N 24+80 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.162	49.59	-15.79	65.38	38.90	0.24	10.45	QP
2	0.162	32.19	-23.19	55.38	21.50	0.24	10.45	Average
3 *	0.201	54.00	-9.58	63.58	43.30	0.24	10.46	QP
4	0.201	36.60	-16.98	53.58	25.90	0.24	10.46	Average
5	0.244	45.34	-16.61	61.95	34.60	0.27	10.47	QP
6	0.244	31.94	-20.01	51.95	21.20	0.27	10.47	Average
7	0.313	41.98	-17.90	59.88	31.20	0.30	10.48	QP
8	0.313	27.98	-21.90	49.88	17.20	0.30	10.48	Average
9	0.510	38.25	-17.75	56.00	27.50	0.34	10.41	QP
10	0.510	23.35	-22.65	46.00	12.60	0.34	10.41	Average
11	2.809	39.42	-16.58	56.00	28.80	0.39	10.23	QP
12	2.809	22.82	-23.18	46.00	12.20	0.39	10.23	Average
13	3.364	37.21	-18.79	56.00	26.59	0.40	10.22	QP
14	3.364	22.91	-23.09	46.00	12.29	0.40	10.22	Average

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission

Test Engineer :	Jerry Xu	Relative Humidity :	41 ~ 42 %
		Temperature :	22 ~ 23 °C





Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	Bluetooth-LE_GSKF	0	2402	1Mbps	-	-
Mode 2	2400-2483.5	1	Bluetooth-LE_GSKF	19	2440	1Mbps	-	-
Mode 3	2400-2483.5	1	Bluetooth-LE_GSKF	39	2480	1Mbps	-	-
Mode 4	2400-2483.5	1	Bluetooth-LE_GSKF	0	2402	2Mbps	-	-
Mode 5	2400-2483.5	1	Bluetooth-LE_GSKF	19	2440	2Mbps	-	-
Mode 6	2400-2483.5	1	Bluetooth-LE_GSKF	39	2480	2Mbps	-	-





Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth-LE_GSKF	0	2379.81	48.31	54.00	-5.69	H	AVERAGE	Pass	Band Edge
1	Bluetooth-LE_GSKF	0	4804.00	48.72	54.00	-5.28	H	AVERAGE	Pass	Harmonic
2	Bluetooth-LE_GSKF	19	-	-	-	-	-	-	-	Band Edge
2	Bluetooth-LE_GSKF	19	4880.00	46.42	54.00	-7.58	H	AVERAGE	Pass	Harmonic
3	Bluetooth-LE_GSKF	39	2483.50	51.58	54.00	-2.42	H	AVERAGE	Pass	Band Edge
3	Bluetooth-LE_GSKF	39	4960.00	47.90	54.00	-6.10	H	AVERAGE	Pass	Harmonic
4	Bluetooth-LE_GSKF	0	2381.89	48.17	54.00	-5.83	H	AVERAGE	Pass	Band Edge
4	Bluetooth-LE_GSKF	0	4804.00	45.95	54.00	-8.05	H	AVERAGE	Pass	Harmonic
5	Bluetooth-LE_GSKF	19	-	-	-	-	-	-	-	Band Edge
5	Bluetooth-LE_GSKF	19	7320.00	49.41	54.00	-4.59	V	AVERAGE	Pass	Harmonic
6	Bluetooth-LE_GSKF	39	2483.50	51.86	54.00	-2.14	H	AVERAGE	Pass	Band Edge
6	Bluetooth-LE_GSKF	39	4960.00	46.76	74.00	-27.24	H	PEAK	Pass	Harmonic




Mode	1																																																							
	Band Edge																																																							
	2400-2483.5_Bluetooth-LE_GSKF_CH0_2402MHz																																																							
ANT	1																																																							
Pol.	Horizontal						Fundamental																																																	
Peak																																																								
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2384.36</td><td>60.23</td><td>74.00</td><td>-13.77</td><td>47.72</td><td>32.24</td><td>6.70</td><td>32.43</td><td>6.00</td><td>100</td><td>348 PEAK</td></tr></table>													Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2384.36	60.23	74.00	-13.77	47.72	32.24	6.70	32.43	6.00	100
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2384.36	60.23	74.00	-13.77	47.72	32.24	6.70	32.43	6.00	100	348 PEAK																																													
Fundamental																																																								
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>120.93</td><td>-----</td><td>-----</td><td>108.32</td><td>32.31</td><td>6.72</td><td>32.42</td><td>6.00</td><td>100</td><td>348 PEAK</td></tr></table>													Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	120.93	-----	-----	108.32	32.31	6.72	32.42	6.00	100
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2402.00	120.93	-----	-----	108.32	32.31	6.72	32.42	6.00	100	348 PEAK																																													
Avg																																																								
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2379.81</td><td>48.31</td><td>54.00</td><td>-5.69</td><td>35.83</td><td>32.22</td><td>6.69</td><td>32.43</td><td>6.00</td><td>100</td><td>348 AVERAGE</td></tr></table>													Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2379.81	48.31	54.00	-5.69	35.83	32.22	6.69	32.43	6.00	100
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2379.81	48.31	54.00	-5.69	35.83	32.22	6.69	32.43	6.00	100	348 AVERAGE																																													
Fundamental																																																								
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>119.63</td><td>-----</td><td>-----</td><td>107.02</td><td>32.31</td><td>6.72</td><td>32.42</td><td>6.00</td><td>100</td><td>348 AVERAGE</td></tr></table>													Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	119.63	-----	-----	107.02	32.31	6.72	32.42	6.00	100
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2402.00	119.63	-----	-----	107.02	32.31	6.72	32.42	6.00	100	348 AVERAGE																																													



Mode	1																																																																																									
	Band Edge																																																																																									
	2400-2483.5_Bluetooth-LE_GSKF_CH0_2402MHz																																																																																									
ANT	1																																																																																									
Pol.	Vertical	Fundamental																																																																																								
Peak	 <table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.04</td><td>58.39</td><td>74.00</td><td>-15.61</td><td>45.85</td><td>32.26</td><td>6.70</td><td>32.42</td><td>6.00</td><td>100 280 PEAK</td></tr></table>		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.04	58.39	74.00	-15.61	45.85	32.26	6.70	32.42	6.00	100 280 PEAK	 <table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>119.18</td><td>-----</td><td>-----</td><td>106.57</td><td>32.31</td><td>6.72</td><td>32.42</td><td>6.00</td><td>100 280 PEAK</td></tr></table>		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	119.18	-----	-----	106.57	32.31	6.72	32.42	6.00	100 280 PEAK
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2389.04	58.39	74.00	-15.61	45.85	32.26	6.70	32.42	6.00	100 280 PEAK																																																																																
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2402.00	119.18	-----	-----	106.57	32.31	6.72	32.42	6.00	100 280 PEAK																																																																																
Avg	 <table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2381.89</td><td>46.01</td><td>54.00</td><td>-7.99</td><td>33.52</td><td>32.23</td><td>6.69</td><td>32.43</td><td>6.00</td><td>100 280 AVERAGE</td></tr></table>		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2381.89	46.01	54.00	-7.99	33.52	32.23	6.69	32.43	6.00	100 280 AVERAGE	 <table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>117.97</td><td>-----</td><td>-----</td><td>105.36</td><td>32.31</td><td>6.72</td><td>32.42</td><td>6.00</td><td>100 280 AVERAGE</td></tr></table>		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	117.97	-----	-----	105.36	32.31	6.72	32.42	6.00	100 280 AVERAGE
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2381.89	46.01	54.00	-7.99	33.52	32.23	6.69	32.43	6.00	100 280 AVERAGE																																																																																
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2402.00	117.97	-----	-----	105.36	32.31	6.72	32.42	6.00	100 280 AVERAGE																																																																																







Mode	1																																																																																																				
	Harmonic																																																																																																				
	2400-2483.5_Bluetooth-LE_GSKF_CH0_2402MHz																																																																																																				
ANT	1																																																																																																				
Pol.	Horizontal																																																																																																				
Peak Avg																																																																																																					
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3202.50</td><td>48.48</td><td>99.25</td><td>-50.77</td><td>73.56</td><td>32.90</td><td>7.75</td><td>65.73</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>51.83</td><td>74.00</td><td>-22.17</td><td>74.36</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>117</td><td>194</td><td>PEAK</td></tr><tr><td>3</td><td>4804.00</td><td>48.72</td><td>54.00</td><td>-5.28</td><td>71.25</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>117</td><td>194</td><td>AVERAGE</td></tr><tr><td>4</td><td>7206.00</td><td>56.50</td><td>99.25</td><td>-42.75</td><td>75.71</td><td>35.69</td><td>11.79</td><td>66.69</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>																	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3202.50	48.48	99.25	-50.77	73.56	32.90	7.75	65.73	0.00	---	---	Peak	2	4804.00	51.83	74.00	-22.17	74.36	34.10	9.53	66.16	0.00	117	194	PEAK	3	4804.00	48.72	54.00	-5.28	71.25	34.10	9.53	66.16	0.00	117	194	AVERAGE	4	7206.00	56.50	99.25	-42.75	75.71	35.69	11.79	66.69	0.00	---	---	Peak
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
	Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																										
1	3202.50	48.48	99.25	-50.77	73.56	32.90	7.75	65.73	0.00	---	---	Peak																																																																																									
2	4804.00	51.83	74.00	-22.17	74.36	34.10	9.53	66.16	0.00	117	194	PEAK																																																																																									
3	4804.00	48.72	54.00	-5.28	71.25	34.10	9.53	66.16	0.00	117	194	AVERAGE																																																																																									
4	7206.00	56.50	99.25	-42.75	75.71	35.69	11.79	66.69	0.00	---	---	Peak																																																																																									
<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3202.50</td><td>48.48</td><td>99.25</td><td>-50.77</td><td>73.56</td><td>32.90</td><td>7.75</td><td>65.73</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>51.83</td><td>74.00</td><td>-22.17</td><td>74.36</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>117</td><td>194</td><td>PEAK</td></tr><tr><td>3</td><td>4804.00</td><td>48.72</td><td>54.00</td><td>-5.28</td><td>71.25</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>117</td><td>194</td><td>AVERAGE</td></tr><tr><td>4</td><td>7206.00</td><td>56.50</td><td>99.25</td><td>-42.75</td><td>75.71</td><td>35.69</td><td>11.79</td><td>66.69</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>																	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3202.50	48.48	99.25	-50.77	73.56	32.90	7.75	65.73	0.00	---	---	Peak	2	4804.00	51.83	74.00	-22.17	74.36	34.10	9.53	66.16	0.00	117	194	PEAK	3	4804.00	48.72	54.00	-5.28	71.25	34.10	9.53	66.16	0.00	117	194	AVERAGE	4	7206.00	56.50	99.25	-42.75	75.71	35.69	11.79	66.69	0.00	---	---	Peak	
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																											
1	3202.50	48.48	99.25	-50.77	73.56	32.90	7.75	65.73	0.00	---	---	Peak																																																																																									
2	4804.00	51.83	74.00	-22.17	74.36	34.10	9.53	66.16	0.00	117	194	PEAK																																																																																									
3	4804.00	48.72	54.00	-5.28	71.25	34.10	9.53	66.16	0.00	117	194	AVERAGE																																																																																									
4	7206.00	56.50	99.25	-42.75	75.71	35.69	11.79	66.69	0.00	---	---	Peak																																																																																									
<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3202.50</td><td>47.21</td><td>97.60</td><td>-50.39</td><td>72.29</td><td>32.90</td><td>7.75</td><td>65.73</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>50.32</td><td>74.00</td><td>-23.68</td><td>72.85</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>354</td><td>328</td><td>PEAK</td></tr><tr><td>3</td><td>4804.00</td><td>47.22</td><td>54.00</td><td>-6.78</td><td>69.75</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>354</td><td>328</td><td>AVERAGE</td></tr><tr><td>4</td><td>7206.00</td><td>54.90</td><td>97.60</td><td>-42.70</td><td>74.11</td><td>35.69</td><td>11.79</td><td>66.69</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>																	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3202.50	47.21	97.60	-50.39	72.29	32.90	7.75	65.73	0.00	---	---	Peak	2	4804.00	50.32	74.00	-23.68	72.85	34.10	9.53	66.16	0.00	354	328	PEAK	3	4804.00	47.22	54.00	-6.78	69.75	34.10	9.53	66.16	0.00	354	328	AVERAGE	4	7206.00	54.90	97.60	-42.70	74.11	35.69	11.79	66.69	0.00	---	---	Peak	
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																											
1	3202.50	47.21	97.60	-50.39	72.29	32.90	7.75	65.73	0.00	---	---	Peak																																																																																									
2	4804.00	50.32	74.00	-23.68	72.85	34.10	9.53	66.16	0.00	354	328	PEAK																																																																																									
3	4804.00	47.22	54.00	-6.78	69.75	34.10	9.53	66.16	0.00	354	328	AVERAGE																																																																																									
4	7206.00	54.90	97.60	-42.70	74.11	35.69	11.79	66.69	0.00	---	---	Peak																																																																																									
<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3202.50</td><td>47.21</td><td>97.60</td><td>-50.39</td><td>72.29</td><td>32.90</td><td>7.75</td><td>65.73</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>50.32</td><td>74.00</td><td>-23.68</td><td>72.85</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>354</td><td>328</td><td>PEAK</td></tr><tr><td>3</td><td>4804.00</td><td>47.22</td><td>54.00</td><td>-6.78</td><td>69.75</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>354</td><td>328</td><td>AVERAGE</td></tr><tr><td>4</td><td>7206.00</td><td>54.90</td><td>97.60</td><td>-42.70</td><td>74.11</td><td>35.69</td><td>11.79</td><td>66.69</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>																	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3202.50	47.21	97.60	-50.39	72.29	32.90	7.75	65.73	0.00	---	---	Peak	2	4804.00	50.32	74.00	-23.68	72.85	34.10	9.53	66.16	0.00	354	328	PEAK	3	4804.00	47.22	54.00	-6.78	69.75	34.10	9.53	66.16	0.00	354	328	AVERAGE	4	7206.00	54.90	97.60	-42.70	74.11	35.69	11.79	66.69	0.00	---	---	Peak	
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																											
1	3202.50	47.21	97.60	-50.39	72.29	32.90	7.75	65.73	0.00	---	---	Peak																																																																																									
2	4804.00	50.32	74.00	-23.68	72.85	34.10	9.53	66.16	0.00	354	328	PEAK																																																																																									
3	4804.00	47.22	54.00	-6.78	69.75	34.10	9.53	66.16	0.00	354	328	AVERAGE																																																																																									
4	7206.00	54.90	97.60	-42.70	74.11	35.69	11.79	66.69	0.00	---	---	Peak																																																																																									






Mode	2																																																																																																	
	Harmonic																																																																																																	
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																																																																	
ANT	1																																																																																																	
Pol.	Horizontal																																																																																																	
Peak Avg																																																																																																		
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><td>1</td><td>3253.50</td><td>47.24</td><td>96.38</td><td>-49.14</td><td>72.24</td><td>32.89</td><td>7.81</td><td>65.70</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4880.00</td><td>49.67</td><td>74.00</td><td>-24.33</td><td>72.14</td><td>34.10</td><td>9.61</td><td>66.18</td><td>0.00</td><td>100</td><td>137</td><td>PEAK</td></tr><tr><td>3</td><td>4880.00</td><td>46.42</td><td>54.00</td><td>-7.58</td><td>68.89</td><td>34.10</td><td>9.61</td><td>66.18</td><td>0.00</td><td>100</td><td>137</td><td>AVERAGE</td></tr><tr><td>4</td><td>7320.00</td><td>50.39</td><td>74.00</td><td>-23.61</td><td>69.56</td><td>35.64</td><td>11.88</td><td>66.69</td><td>0.00</td><td>124</td><td>23</td><td>PEAK</td></tr><tr><td>5</td><td>7320.00</td><td>44.86</td><td>54.00</td><td>-9.14</td><td>64.03</td><td>35.64</td><td>11.88</td><td>66.69</td><td>0.00</td><td>124</td><td>23</td><td>AVERAGE</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	1	3253.50	47.24	96.38	-49.14	72.24	32.89	7.81	65.70	0.00	---	---	Peak	2	4880.00	49.67	74.00	-24.33	72.14	34.10	9.61	66.18	0.00	100	137	PEAK	3	4880.00	46.42	54.00	-7.58	68.89	34.10	9.61	66.18	0.00	100	137	AVERAGE	4	7320.00	50.39	74.00	-23.61	69.56	35.64	11.88	66.69	0.00	124	23	PEAK	5	7320.00	44.86	54.00	-9.14	64.03	35.64	11.88	66.69	0.00	124	23	AVERAGE
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																								
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																								
1	3253.50	47.24	96.38	-49.14	72.24	32.89	7.81	65.70	0.00	---	---	Peak																																																																																						
2	4880.00	49.67	74.00	-24.33	72.14	34.10	9.61	66.18	0.00	100	137	PEAK																																																																																						
3	4880.00	46.42	54.00	-7.58	68.89	34.10	9.61	66.18	0.00	100	137	AVERAGE																																																																																						
4	7320.00	50.39	74.00	-23.61	69.56	35.64	11.88	66.69	0.00	124	23	PEAK																																																																																						
5	7320.00	44.86	54.00	-9.14	64.03	35.64	11.88	66.69	0.00	124	23	AVERAGE																																																																																						
Vertical																																																																																																		
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><td>1</td><td>3253.50</td><td>46.56</td><td>94.95</td><td>-48.39</td><td>71.56</td><td>32.89</td><td>7.81</td><td>65.70</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4880.00</td><td>47.69</td><td>74.00</td><td>-26.31</td><td>70.16</td><td>34.10</td><td>9.61</td><td>66.18</td><td>0.00</td><td>100</td><td>131</td><td>PEAK</td></tr><tr><td>3</td><td>4880.00</td><td>44.22</td><td>54.00</td><td>-9.78</td><td>66.69</td><td>34.10</td><td>9.61</td><td>66.18</td><td>0.00</td><td>100</td><td>131</td><td>AVERAGE</td></tr><tr><td>4</td><td>7320.00</td><td>50.66</td><td>74.00</td><td>-23.34</td><td>69.83</td><td>35.64</td><td>11.88</td><td>66.69</td><td>0.00</td><td>192</td><td>6</td><td>PEAK</td></tr><tr><td>5</td><td>7320.00</td><td>45.48</td><td>54.00</td><td>-8.52</td><td>64.65</td><td>35.64</td><td>11.88</td><td>66.69</td><td>0.00</td><td>192</td><td>6</td><td>AVERAGE</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	1	3253.50	46.56	94.95	-48.39	71.56	32.89	7.81	65.70	0.00	---	---	Peak	2	4880.00	47.69	74.00	-26.31	70.16	34.10	9.61	66.18	0.00	100	131	PEAK	3	4880.00	44.22	54.00	-9.78	66.69	34.10	9.61	66.18	0.00	100	131	AVERAGE	4	7320.00	50.66	74.00	-23.34	69.83	35.64	11.88	66.69	0.00	192	6	PEAK	5	7320.00	45.48	54.00	-8.52	64.65	35.64	11.88	66.69	0.00	192	6	AVERAGE
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																								
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																								
1	3253.50	46.56	94.95	-48.39	71.56	32.89	7.81	65.70	0.00	---	---	Peak																																																																																						
2	4880.00	47.69	74.00	-26.31	70.16	34.10	9.61	66.18	0.00	100	131	PEAK																																																																																						
3	4880.00	44.22	54.00	-9.78	66.69	34.10	9.61	66.18	0.00	100	131	AVERAGE																																																																																						
4	7320.00	50.66	74.00	-23.34	69.83	35.64	11.88	66.69	0.00	192	6	PEAK																																																																																						
5	7320.00	45.48	54.00	-8.52	64.65	35.64	11.88	66.69	0.00	192	6	AVERAGE																																																																																						



Mode	3																																																																																									
	Band Edge																																																																																									
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																									
ANT	1																																																																																									
Pol.	Horizontal	Fundamental																																																																																								
Peak	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>63.08</td><td>74.00</td><td>-10.92</td><td>50.16</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>105 350 PEAK</td></tr></table>		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	63.08	74.00	-10.92	50.16	32.50	6.83	32.41	6.00	105 350 PEAK	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>119.12</td><td>-----</td><td>-----</td><td>106.20</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>105 350 PEAK</td></tr></table>		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	119.12	-----	-----	106.20	32.50	6.83	32.41	6.00	105 350 PEAK
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2483.50	63.08	74.00	-10.92	50.16	32.50	6.83	32.41	6.00	105 350 PEAK																																																																																
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2480.00	119.12	-----	-----	106.20	32.50	6.83	32.41	6.00	105 350 PEAK																																																																																
Avg	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>51.58</td><td>54.00</td><td>-2.42</td><td>38.66</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>105 350 AVERAGE</td></tr></table>		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	51.58	54.00	-2.42	38.66	32.50	6.83	32.41	6.00	105 350 AVERAGE	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>117.84</td><td>-----</td><td>-----</td><td>104.92</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>105 350 AVERAGE</td></tr></table>		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	117.84	-----	-----	104.92	32.50	6.83	32.41	6.00	105 350 AVERAGE
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2483.50	51.58	54.00	-2.42	38.66	32.50	6.83	32.41	6.00	105 350 AVERAGE																																																																																
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2480.00	117.84	-----	-----	104.92	32.50	6.83	32.41	6.00	105 350 AVERAGE																																																																																







Mode	3																																																					
	Band Edge																																																					
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																					
ANT	1																																																					
Pol.	Vertical																																																					
Peak	Fundamental																																																					
																																																						
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.62</td><td>61.67</td><td>74.00</td><td>-12.33</td><td>48.75</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>201 241 PEAK</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.62	61.67	74.00	-12.33	48.75	32.50	6.83	32.41	6.00
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																													
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2483.62	61.67	74.00	-12.33	48.75	32.50	6.83	32.41	6.00	201 241 PEAK																																												
Avg																																																						
																																																						
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>117.72</td><td>-----</td><td>-----</td><td>104.80</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>201 241 PEAK</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	117.72	-----	-----	104.80	32.50	6.83	32.41	6.00
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																													
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2480.00	117.72	-----	-----	104.80	32.50	6.83	32.41	6.00	201 241 PEAK																																												







Mode	3																																																																																											
	Harmonic																																																																																											
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																											
ANT	1																																																																																											
Pol.	Horizontal																																																																																											
Peak Avg																																																																																												
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3306.00	45.69	97.75	-52.06	70.81	32.70	7.87	65.69	0.00	---	Peak	2	4960.00	51.03	74.00	-22.97	73.48	34.04	9.70	66.19	0.00	325	4 PEAK	3	4960.00	47.90	54.00	-6.10	70.35	34.04	9.70	66.19	0.00	325	4 AVERAGE	4	7440.00	50.02	74.00	-23.98	68.98	35.78	11.96	66.70	0.00	300	296 PEAK	5	7440.00	44.62	54.00	-9.38	63.58	35.78	11.96	66.70	0.00	300
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																			
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																		
1	3306.00	45.69	97.75	-52.06	70.81	32.70	7.87	65.69	0.00	---	Peak																																																																																	
2	4960.00	51.03	74.00	-22.97	73.48	34.04	9.70	66.19	0.00	325	4 PEAK																																																																																	
3	4960.00	47.90	54.00	-6.10	70.35	34.04	9.70	66.19	0.00	325	4 AVERAGE																																																																																	
4	7440.00	50.02	74.00	-23.98	68.98	35.78	11.96	66.70	0.00	300	296 PEAK																																																																																	
5	7440.00	44.62	54.00	-9.38	63.58	35.78	11.96	66.70	0.00	300	296 AVERAGE																																																																																	
Peak Avg																																																																																												
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3307.50	45.86	95.75	-49.89	70.98	32.70	7.87	65.69	0.00	---	Peak	2	4960.00	50.18	74.00	-23.82	72.63	34.04	9.70	66.19	0.00	263	126 PEAK	3	4960.00	46.67	54.00	-7.33	69.12	34.04	9.70	66.19	0.00	263	126 AVERAGE	4	7440.00	50.88	74.00	-23.12	69.84	35.78	11.96	66.70	0.00	100	326 PEAK	5	7440.00	45.58	54.00	-8.42	64.54	35.78	11.96	66.70	0.00	100
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																			
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																		
1	3307.50	45.86	95.75	-49.89	70.98	32.70	7.87	65.69	0.00	---	Peak																																																																																	
2	4960.00	50.18	74.00	-23.82	72.63	34.04	9.70	66.19	0.00	263	126 PEAK																																																																																	
3	4960.00	46.67	54.00	-7.33	69.12	34.04	9.70	66.19	0.00	263	126 AVERAGE																																																																																	
4	7440.00	50.88	74.00	-23.12	69.84	35.78	11.96	66.70	0.00	100	326 PEAK																																																																																	
5	7440.00	45.58	54.00	-8.42	64.54	35.78	11.96	66.70	0.00	100	326 AVERAGE																																																																																	





Mode	4																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5_Bluetooth-LE_GSKF_CH0_2402MHz																																																																																																		
ANT	1																																																																																																		
Pol.	Horizontal						Fundamental																																																																																												
Peak																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2383.19</td><td>59.97</td><td>74.00</td><td>-14.03</td><td>47.47</td><td>32.23</td><td>6.70</td><td>32.43</td><td>6.00</td><td>100 353 PEAK</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2383.19	59.97	74.00	-14.03	47.47	32.23	6.70	32.43	6.00	100 353 PEAK	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>120.78</td><td>-----</td><td>-----</td><td>108.17</td><td>32.31</td><td>6.72</td><td>32.42</td><td>6.00</td><td>100 353 PEAK</td></tr></table>						Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	120.78	-----	-----	108.17	32.31	6.72	32.42	6.00	100 353 PEAK
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																									
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2383.19	59.97	74.00	-14.03	47.47	32.23	6.70	32.43	6.00	100 353 PEAK																																																																																									
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																										
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	120.78	-----	-----	108.17	32.31	6.72	32.42	6.00	100 353 PEAK																																																																																									
Avg																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2381.89</td><td>48.17</td><td>54.00</td><td>-5.83</td><td>35.68</td><td>32.23</td><td>6.69</td><td>32.43</td><td>6.00</td><td>100 353 AVERAGE</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2381.89	48.17	54.00	-5.83	35.68	32.23	6.69	32.43	6.00	100 353 AVERAGE	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>118.27</td><td>-----</td><td>-----</td><td>105.66</td><td>32.31</td><td>6.72</td><td>32.42</td><td>6.00</td><td>100 353 AVERAGE</td></tr></table>						Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	118.27	-----	-----	105.66	32.31	6.72	32.42	6.00	100 353 AVERAGE
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																									
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2381.89	48.17	54.00	-5.83	35.68	32.23	6.69	32.43	6.00	100 353 AVERAGE																																																																																									
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																										
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	118.27	-----	-----	105.66	32.31	6.72	32.42	6.00	100 353 AVERAGE																																																																																									





Mode	4																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth-LE_GSKF_CH0_2402MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Vertical						Fundamental																																																																																													
Peak																																																																																																				
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2378.38</td><td>58.17</td><td>74.00</td><td>-15.83</td><td>45.70</td><td>32.21</td><td>6.69</td><td>32.43</td><td>6.00</td><td>100</td><td>282 PEAK</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2378.38	58.17	74.00	-15.83	45.70	32.21	6.69	32.43	6.00	100	282 PEAK	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>119.24</td><td>-----</td><td>-----</td><td>106.63</td><td>32.31</td><td>6.72</td><td>32.42</td><td>6.00</td><td>100</td><td>282 PEAK</td></tr></table>						Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	119.24	-----	-----	106.63	32.31	6.72	32.42	6.00	100
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2378.38	58.17	74.00	-15.83	45.70	32.21	6.69	32.43	6.00	100	282 PEAK																																																																																									
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	119.24	-----	-----	106.63	32.31	6.72	32.42	6.00	100	282 PEAK																																																																																									
Avg																																																																																																				
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>46.24</td><td>54.00</td><td>-7.76</td><td>33.69</td><td>32.26</td><td>6.71</td><td>32.42</td><td>6.00</td><td>100</td><td>282 AVERAGE</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.95	46.24	54.00	-7.76	33.69	32.26	6.71	32.42	6.00	100	282 AVERAGE	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>116.63</td><td>-----</td><td>-----</td><td>104.02</td><td>32.31</td><td>6.72</td><td>32.42</td><td>6.00</td><td>100</td><td>282 AVERAGE</td></tr></table>						Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	116.63	-----	-----	104.02	32.31	6.72	32.42	6.00	100
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2389.95	46.24	54.00	-7.76	33.69	32.26	6.71	32.42	6.00	100	282 AVERAGE																																																																																									
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	116.63	-----	-----	104.02	32.31	6.72	32.42	6.00	100	282 AVERAGE																																																																																									







Mode	4																																																																																			
	Harmonic																																																																																			
	2400-2483.5_Bluetooth-LE_GSKF_CH0_2402MHz																																																																																			
ANT	1																																																																																			
Pol.	Horizontal																																																																																			
Peak Avg																																																																																				
	<table><tr><th>Freq</th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><td>1</td><td>3282.50</td><td>47.49</td><td>98.35</td><td>-50.86</td><td>72.57</td><td>32.90</td><td>7.75</td><td>65.73</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>51.12</td><td>74.00</td><td>-22.88</td><td>73.65</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>168</td><td>190</td><td>PEAK</td></tr><tr><td>3</td><td>4804.00</td><td>45.95</td><td>54.00</td><td>-8.05</td><td>68.48</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>168</td><td>190</td><td>AVERAGE</td></tr><tr><td>4</td><td>7207.50</td><td>54.15</td><td>98.35</td><td>-44.20</td><td>73.36</td><td>35.69</td><td>11.79</td><td>66.69</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>											Freq	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	Level	Line	Limit	Level	Factor	Loss	Factor	Factor			1	3282.50	47.49	98.35	-50.86	72.57	32.90	7.75	65.73	0.00	---	---	Peak	2	4804.00	51.12	74.00	-22.88	73.65	34.10	9.53	66.16	0.00	168	190	PEAK	3	4804.00	45.95	54.00	-8.05	68.48	34.10	9.53	66.16	0.00	168	190	AVERAGE	4	7207.50	54.15	98.35	-44.20	73.36	35.69	11.79	66.69	0.00	---	---
Freq	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																										
MHz	Level	Line	Limit	Level	Factor	Loss	Factor	Factor																																																																												
1	3282.50	47.49	98.35	-50.86	72.57	32.90	7.75	65.73	0.00	---	---	Peak																																																																								
2	4804.00	51.12	74.00	-22.88	73.65	34.10	9.53	66.16	0.00	168	190	PEAK																																																																								
3	4804.00	45.95	54.00	-8.05	68.48	34.10	9.53	66.16	0.00	168	190	AVERAGE																																																																								
4	7207.50	54.15	98.35	-44.20	73.36	35.69	11.79	66.69	0.00	---	---	Peak																																																																								
Peak Avg																																																																																				
	<table><tr><th>Freq</th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><td>1</td><td>3282.50</td><td>47.26</td><td>96.82</td><td>-49.56</td><td>72.34</td><td>32.90</td><td>7.75</td><td>65.73</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>49.42</td><td>74.00</td><td>-24.58</td><td>71.95</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>376</td><td>318</td><td>PEAK</td></tr><tr><td>3</td><td>4804.00</td><td>44.15</td><td>54.00</td><td>-9.85</td><td>66.68</td><td>34.10</td><td>9.53</td><td>66.16</td><td>0.00</td><td>376</td><td>318</td><td>AVERAGE</td></tr><tr><td>4</td><td>7207.50</td><td>54.44</td><td>96.82</td><td>-42.38</td><td>73.65</td><td>35.69</td><td>11.79</td><td>66.69</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>											Freq	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	Level	Line	Limit	Level	Factor	Loss	Factor	Factor			1	3282.50	47.26	96.82	-49.56	72.34	32.90	7.75	65.73	0.00	---	---	Peak	2	4804.00	49.42	74.00	-24.58	71.95	34.10	9.53	66.16	0.00	376	318	PEAK	3	4804.00	44.15	54.00	-9.85	66.68	34.10	9.53	66.16	0.00	376	318	AVERAGE	4	7207.50	54.44	96.82	-42.38	73.65	35.69	11.79	66.69	0.00	---	---
Freq	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																										
MHz	Level	Line	Limit	Level	Factor	Loss	Factor	Factor																																																																												
1	3282.50	47.26	96.82	-49.56	72.34	32.90	7.75	65.73	0.00	---	---	Peak																																																																								
2	4804.00	49.42	74.00	-24.58	71.95	34.10	9.53	66.16	0.00	376	318	PEAK																																																																								
3	4804.00	44.15	54.00	-9.85	66.68	34.10	9.53	66.16	0.00	376	318	AVERAGE																																																																								
4	7207.50	54.44	96.82	-42.38	73.65	35.69	11.79	66.69	0.00	---	---	Peak																																																																								







Mode	5																																																																																												
	Harmonic																																																																																												
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																																																												
ANT	1																																																																																												
Pol.	Horizontal																																																																																												
Peak Avg																																																																																													
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><td>1</td><td>3253.50</td><td>48.33</td><td>97.47</td><td>-49.14</td><td>73.33</td><td>32.89</td><td>7.81</td><td>65.70</td><td>0.00</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4880.00</td><td>50.60</td><td>74.00</td><td>-23.40</td><td>73.07</td><td>34.10</td><td>9.61</td><td>66.18</td><td>0.00</td><td>134</td><td>135 PEAK</td></tr><tr><td>3</td><td>4880.00</td><td>45.49</td><td>54.00</td><td>-8.51</td><td>67.96</td><td>34.10</td><td>9.61</td><td>66.18</td><td>0.00</td><td>134</td><td>135 AVERAGE</td></tr><tr><td>4</td><td>7320.00</td><td>52.38</td><td>74.00</td><td>-21.62</td><td>71.55</td><td>35.64</td><td>11.88</td><td>66.69</td><td>0.00</td><td>100</td><td>25 PEAK</td></tr><tr><td>5</td><td>7320.00</td><td>47.14</td><td>54.00</td><td>-6.86</td><td>66.31</td><td>35.64</td><td>11.88</td><td>66.69</td><td>0.00</td><td>100</td><td>25 AVERAGE</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	1	3253.50	48.33	97.47	-49.14	73.33	32.89	7.81	65.70	0.00	---	Peak	2	4880.00	50.60	74.00	-23.40	73.07	34.10	9.61	66.18	0.00	134	135 PEAK	3	4880.00	45.49	54.00	-8.51	67.96	34.10	9.61	66.18	0.00	134	135 AVERAGE	4	7320.00	52.38	74.00	-21.62	71.55	35.64	11.88	66.69	0.00	100	25 PEAK	5	7320.00	47.14	54.00	-6.86	66.31	35.64	11.88	66.69	0.00	100	25 AVERAGE
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																			
	Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																		
	1	3253.50	48.33	97.47	-49.14	73.33	32.89	7.81	65.70	0.00	---	Peak																																																																																	
	2	4880.00	50.60	74.00	-23.40	73.07	34.10	9.61	66.18	0.00	134	135 PEAK																																																																																	
	3	4880.00	45.49	54.00	-8.51	67.96	34.10	9.61	66.18	0.00	134	135 AVERAGE																																																																																	
4	7320.00	52.38	74.00	-21.62	71.55	35.64	11.88	66.69	0.00	100	25 PEAK																																																																																		
5	7320.00	47.14	54.00	-6.86	66.31	35.64	11.88	66.69	0.00	100	25 AVERAGE																																																																																		
Vertical																																																																																													
																																																																																													
<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><td>1</td><td>3253.50</td><td>47.67</td><td>96.43</td><td>-48.76</td><td>72.67</td><td>32.89</td><td>7.81</td><td>65.70</td><td>0.00</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4880.00</td><td>48.99</td><td>74.00</td><td>-25.01</td><td>71.46</td><td>34.10</td><td>9.61</td><td>66.18</td><td>0.00</td><td>305</td><td>359 PEAK</td></tr><tr><td>3</td><td>4880.00</td><td>43.28</td><td>54.00</td><td>-10.72</td><td>65.75</td><td>34.10</td><td>9.61</td><td>66.18</td><td>0.00</td><td>305</td><td>359 AVERAGE</td></tr><tr><td>4</td><td>7320.00</td><td>54.60</td><td>74.00</td><td>-19.40</td><td>73.77</td><td>35.64</td><td>11.88</td><td>66.69</td><td>0.00</td><td>182</td><td>282 PEAK</td></tr><tr><td>5</td><td>7320.00</td><td>49.41</td><td>54.00</td><td>-4.59</td><td>68.58</td><td>35.64</td><td>11.88</td><td>66.69</td><td>0.00</td><td>182</td><td>282 AVERAGE</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	1	3253.50	47.67	96.43	-48.76	72.67	32.89	7.81	65.70	0.00	---	Peak	2	4880.00	48.99	74.00	-25.01	71.46	34.10	9.61	66.18	0.00	305	359 PEAK	3	4880.00	43.28	54.00	-10.72	65.75	34.10	9.61	66.18	0.00	305	359 AVERAGE	4	7320.00	54.60	74.00	-19.40	73.77	35.64	11.88	66.69	0.00	182	282 PEAK	5	7320.00	49.41	54.00	-4.59	68.58	35.64	11.88	66.69	0.00	182	282 AVERAGE	
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																				
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																			
1	3253.50	47.67	96.43	-48.76	72.67	32.89	7.81	65.70	0.00	---	Peak																																																																																		
2	4880.00	48.99	74.00	-25.01	71.46	34.10	9.61	66.18	0.00	305	359 PEAK																																																																																		
3	4880.00	43.28	54.00	-10.72	65.75	34.10	9.61	66.18	0.00	305	359 AVERAGE																																																																																		
4	7320.00	54.60	74.00	-19.40	73.77	35.64	11.88	66.69	0.00	182	282 PEAK																																																																																		
5	7320.00	49.41	54.00	-4.59	68.58	35.64	11.88	66.69	0.00	182	282 AVERAGE																																																																																		





Mode	6																																																																																																				
	Band Edge																																																																																																				
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																				
ANT	1																																																																																																				
Pol.	Horizontal						Fundamental																																																																																														
Peak																																																																																																					
	<table><thead><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.50</td><td>63.74</td><td>74.00</td><td>-10.26</td><td>50.82</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>100</td><td>351 PEAK</td></tr></tbody></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	63.74	74.00	-10.26	50.82	32.50	6.83	32.41	6.00	100	351 PEAK	<table><thead><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>116.59</td><td>-----</td><td>-----</td><td>103.67</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>100</td><td>351 PEAK</td></tr></tbody></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	116.59	-----	-----	103.67	32.50	6.83	32.41	6.00	100
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																											
1	2483.50	63.74	74.00	-10.26	50.82	32.50	6.83	32.41	6.00	100	351 PEAK																																																																																										
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																											
1	2480.00	116.59	-----	-----	103.67	32.50	6.83	32.41	6.00	100	351 PEAK																																																																																										
Avg																																																																																																					
	<table><thead><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.50</td><td>51.86</td><td>54.00</td><td>-2.14</td><td>38.94</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>100</td><td>351 AVERAGE</td></tr></tbody></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	51.86	54.00	-2.14	38.94	32.50	6.83	32.41	6.00	100	351 AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>114.03</td><td>-----</td><td>-----</td><td>101.11</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>100</td><td>351 AVERAGE</td></tr></tbody></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	114.03	-----	-----	101.11	32.50	6.83	32.41	6.00	100
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																											
1	2483.50	51.86	54.00	-2.14	38.94	32.50	6.83	32.41	6.00	100	351 AVERAGE																																																																																										
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																											
1	2480.00	114.03	-----	-----	101.11	32.50	6.83	32.41	6.00	100	351 AVERAGE																																																																																										





Mode	6																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																		
ANT	1																																																																																																		
Pol.	Vertical						Fundamental																																																																																												
Peak																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>62.11</td><td>74.00</td><td>-11.89</td><td>49.19</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>201 241 PEAK</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	62.11	74.00	-11.89	49.19	32.50	6.83	32.41	6.00	201 241 PEAK	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>115.41</td><td>-----</td><td>-----</td><td>102.49</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>201 241 PEAK</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	115.41	-----	-----	102.49	32.50	6.83	32.41	6.00
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																										
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2483.50	62.11	74.00	-11.89	49.19	32.50	6.83	32.41	6.00	201 241 PEAK																																																																																									
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																										
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	115.41	-----	-----	102.49	32.50	6.83	32.41	6.00	201 241 PEAK																																																																																									
Avg																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>51.06</td><td>54.00</td><td>-2.94</td><td>38.14</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>201 241 AVERAGE</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	51.06	54.00	-2.94	38.14	32.50	6.83	32.41	6.00	201 241 AVERAGE	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>112.80</td><td>-----</td><td>-----</td><td>99.88</td><td>32.50</td><td>6.83</td><td>32.41</td><td>6.00</td><td>201 241 AVERAGE</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	112.80	-----	-----	99.88	32.50	6.83	32.41	6.00
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																										
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2483.50	51.06	54.00	-2.94	38.14	32.50	6.83	32.41	6.00	201 241 AVERAGE																																																																																									
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																										
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	112.80	-----	-----	99.88	32.50	6.83	32.41	6.00	201 241 AVERAGE																																																																																									




Mode	6																																																																																
	Harmonic																																																																																
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																
ANT	1																																																																																
Pol.	Horizontal																																																																																
Peak Avg																																																																																	
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3307.50</td><td>44.95</td><td>97.07</td><td>-52.12</td><td>70.07</td><td>32.70</td><td>7.87</td><td>65.69</td><td>0.00</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4960.00</td><td>46.76</td><td>74.00</td><td>-27.24</td><td>69.21</td><td>34.04</td><td>9.70</td><td>66.19</td><td>0.00</td><td>---</td><td>PEAK</td></tr><tr><td>3</td><td>7440.00</td><td>43.78</td><td>74.00</td><td>-30.22</td><td>62.74</td><td>35.78</td><td>11.96</td><td>66.70</td><td>0.00</td><td>---</td><td>PEAK</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3307.50	44.95	97.07	-52.12	70.07	32.70	7.87	65.69	0.00	---	Peak	2	4960.00	46.76	74.00	-27.24	69.21	34.04	9.70	66.19	0.00	---	PEAK	3	7440.00	43.78	74.00	-30.22	62.74	35.78	11.96	66.70	0.00	---	PEAK
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																							
	Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																						
1	3307.50	44.95	97.07	-52.12	70.07	32.70	7.87	65.69	0.00	---	Peak																																																																						
2	4960.00	46.76	74.00	-27.24	69.21	34.04	9.70	66.19	0.00	---	PEAK																																																																						
3	7440.00	43.78	74.00	-30.22	62.74	35.78	11.96	66.70	0.00	---	PEAK																																																																						
Vertical																																																																																	
																																																																																	
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3307.50</td><td>46.00</td><td>93.84</td><td>-47.84</td><td>71.12</td><td>32.70</td><td>7.87</td><td>65.69</td><td>0.00</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>4960.50</td><td>46.42</td><td>74.00</td><td>-27.58</td><td>68.87</td><td>34.04</td><td>9.70</td><td>66.19</td><td>0.00</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>7440.00</td><td>43.51</td><td>74.00</td><td>-30.49</td><td>62.47</td><td>35.78</td><td>11.96</td><td>66.70</td><td>0.00</td><td>---</td><td>PEAK</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3307.50	46.00	93.84	-47.84	71.12	32.70	7.87	65.69	0.00	---	Peak	2	4960.50	46.42	74.00	-27.58	68.87	34.04	9.70	66.19	0.00	---	Peak	3	7440.00	43.51	74.00	-30.49	62.47	35.78	11.96	66.70	0.00	---	PEAK
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																								
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																						
1	3307.50	46.00	93.84	-47.84	71.12	32.70	7.87	65.69	0.00	---	Peak																																																																						
2	4960.50	46.42	74.00	-27.58	68.87	34.04	9.70	66.19	0.00	---	Peak																																																																						
3	7440.00	43.51	74.00	-30.49	62.47	35.78	11.96	66.70	0.00	---	PEAK																																																																						



Mode	6	
	18G-25G	
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz	
ANT	1	
Pol.	Horizontal	Vertical
Peak Avg		




Mode	6																																																																																																										
	30-1G																																																																																																										
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																										
ANT	1																																																																																																										
Pol.	Horizontal																																																																																																										
Peak																																																																																																											
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>95.96</td><td>35.94</td><td>43.50</td><td>-7.56</td><td>52.10</td><td>15.51</td><td>1.00</td><td>32.67</td><td>0.00</td><td>---</td><td>---</td></tr><tr><td>2</td><td>263.77</td><td>29.09</td><td>46.00</td><td>-16.91</td><td>40.03</td><td>20.23</td><td>1.71</td><td>32.88</td><td>0.00</td><td>---</td><td>---</td></tr><tr><td>3</td><td>351.07</td><td>29.93</td><td>46.00</td><td>-16.07</td><td>40.44</td><td>20.37</td><td>1.97</td><td>32.85</td><td>0.00</td><td>---</td><td>---</td></tr><tr><td>4</td><td>556.47</td><td>31.44</td><td>46.00</td><td>-14.56</td><td>35.91</td><td>26.31</td><td>2.45</td><td>33.23</td><td>0.00</td><td>---</td><td>---</td></tr><tr><td>5</td><td>785.87</td><td>29.51</td><td>46.00</td><td>-16.49</td><td>30.98</td><td>28.67</td><td>2.93</td><td>33.07</td><td>0.00</td><td>---</td><td>---</td></tr><tr><td>6</td><td>975.99</td><td>32.04</td><td>54.00</td><td>-21.96</td><td>29.09</td><td>31.06</td><td>3.28</td><td>31.39</td><td>0.00</td><td>---</td><td>---</td></tr></table>												Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	95.96	35.94	43.50	-7.56	52.10	15.51	1.00	32.67	0.00	---	---	2	263.77	29.09	46.00	-16.91	40.03	20.23	1.71	32.88	0.00	---	---	3	351.07	29.93	46.00	-16.07	40.44	20.37	1.97	32.85	0.00	---	---	4	556.47	31.44	46.00	-14.56	35.91	26.31	2.45	33.23	0.00	---	---	5	785.87	29.51	46.00	-16.49	30.98	28.67	2.93	33.07	0.00	---	---	6	975.99	32.04	54.00	-21.96	29.09	31.06	3.28	31.39	0.00	---	---
		Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																
1	95.96	35.94	43.50	-7.56	52.10	15.51	1.00	32.67	0.00	---	---																																																																																																
2	263.77	29.09	46.00	-16.91	40.03	20.23	1.71	32.88	0.00	---	---																																																																																																
3	351.07	29.93	46.00	-16.07	40.44	20.37	1.97	32.85	0.00	---	---																																																																																																
4	556.47	31.44	46.00	-14.56	35.91	26.31	2.45	33.23	0.00	---	---																																																																																																
5	785.87	29.51	46.00	-16.49	30.98	28.67	2.93	33.07	0.00	---	---																																																																																																
6	975.99	32.04	54.00	-21.96	29.09	31.06	3.28	31.39	0.00	---	---																																																																																																
<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>34.12</td><td>35.58</td><td>40.00</td><td>-4.42</td><td>44.74</td><td>23.02</td><td>0.60</td><td>32.78</td><td>0.00</td><td>---</td><td>---</td></tr><tr><td>2</td><td>95.96</td><td>30.33</td><td>43.50</td><td>-13.17</td><td>46.49</td><td>15.51</td><td>1.00</td><td>32.67</td><td>0.00</td><td>---</td><td>---</td></tr><tr><td>3</td><td>349.37</td><td>28.54</td><td>46.00</td><td>-17.46</td><td>39.10</td><td>20.32</td><td>1.97</td><td>32.85</td><td>0.00</td><td>---</td><td>---</td></tr><tr><td>4</td><td>555.74</td><td>33.26</td><td>46.00</td><td>-12.74</td><td>37.82</td><td>26.22</td><td>2.45</td><td>33.23</td><td>0.00</td><td>---</td><td>---</td></tr><tr><td>5</td><td>786.36</td><td>32.13</td><td>46.00</td><td>-13.87</td><td>33.58</td><td>28.67</td><td>2.94</td><td>33.06</td><td>0.00</td><td>---</td><td>---</td></tr><tr><td>6</td><td>957.81</td><td>31.71</td><td>46.00</td><td>-14.29</td><td>28.09</td><td>31.15</td><td>3.25</td><td>31.58</td><td>0.00</td><td>---</td><td>---</td></tr></table>												Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	34.12	35.58	40.00	-4.42	44.74	23.02	0.60	32.78	0.00	---	---	2	95.96	30.33	43.50	-13.17	46.49	15.51	1.00	32.67	0.00	---	---	3	349.37	28.54	46.00	-17.46	39.10	20.32	1.97	32.85	0.00	---	---	4	555.74	33.26	46.00	-12.74	37.82	26.22	2.45	33.23	0.00	---	---	5	786.36	32.13	46.00	-13.87	33.58	28.67	2.94	33.06	0.00	---	---	6	957.81	31.71	46.00	-14.29	28.09	31.15	3.25	31.58	0.00	---	---	
	Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																
1	34.12	35.58	40.00	-4.42	44.74	23.02	0.60	32.78	0.00	---	---																																																																																																
2	95.96	30.33	43.50	-13.17	46.49	15.51	1.00	32.67	0.00	---	---																																																																																																
3	349.37	28.54	46.00	-17.46	39.10	20.32	1.97	32.85	0.00	---	---																																																																																																
4	555.74	33.26	46.00	-12.74	37.82	26.22	2.45	33.23	0.00	---	---																																																																																																
5	786.36	32.13	46.00	-13.87	33.58	28.67	2.94	33.06	0.00	---	---																																																																																																
6	957.81	31.71	46.00	-14.29	28.09	31.15	3.25	31.58	0.00	---	---																																																																																																

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth –LE (1Mbps)	100	-	-	10Hz
Bluetooth –LE (2Mbps)	100	-	-	10Hz

Bluetooth – LE (1Mbps)



Bluetooth – LE (2Mbps)

